

Record: 1

Title: Novel complex network model and its application in identifying critical components of power grid.

Authors: Chen, Chong¹
Zhou, Xuan¹
Li, Zhuo¹
He, Zhiheng¹
Li, Zhengtian¹ *lizhengtian@hust.edu.cn*
Lin, Xiangning¹

Source: Physica A. Dec2018, Vol. 512, p316-329. 14p.

Document Type: Article

Subject Terms: *ELECTRIC power distribution grids
*POWER transmission
*ELECTRIC lines
*MECHANICAL engineering
*SIMULATION methods & models

Author-Supplied Keywords: Betweenness
Capability degree
Complex network model
Critical component identification
Power flow transmission network
Transmission capability

NAICS/Industry Codes: 237130 Power and Communication Line and Related Structures
Construction
238910 Site Preparation Contractors
541330 Engineering Services

Abstract: Abstract A novel power grid complex network model in order to in-depth characterize the power grid with its complexity is proposed in this paper, based on the power flow transmission network (PFTN). With novel definitions, considering the path, distance and capacity of power transmission comprehensively, the complex network model can comply with the basic electrical law and the physical constraints of power grid. On this basis, an index set for identifying critical buses and branches within the power grid is designed. The index set includes distance and capability degree, hub, distance and capability betweenness, which can fully evaluate the role of nodes or branches in composing the structure and maintaining the system operation of the power grid. Simulations on both IEEE benchmark systems and a provincial power grid in China are conducted using the proposed model, with critical components identification yielding good results. By comparison with existing methods, the effectiveness and superiority of

the proposed model are verified. Highlights • The power flow transmission network of the power grid is defined. • The proposed model captures both the structure and operating status of the grid. • A more systematic grid critical components identification model is proposed. • Extensive simulations show the effectiveness and superiority of the proposed model. [ABSTRACT FROM AUTHOR]

Copyright of Physica A is the property of Elsevier B.V. and its content may not be copied or emailed to multiple sites or posted to a listserv without the copyright holder's express written permission. However, users may print, download, or email articles for individual use. This abstract may be abridged. No warranty is given about the accuracy of the copy. Users should refer to the original published version of the material for the full abstract. (Copyright applies to all Abstracts.)

Author Affiliations: ¹State Key Laboratory of Advanced Electromagnetic Engineering and Technology, School of Electrical and Electronic Engineering, Huazhong University of Science and Technology (HUST), Wuhan 430074, China

ISSN: 0378-4371

DOI: 10.1016/j.physa.2018.08.095

Accession Number: 131732760

Database: Academic Search Complete