# Multi-phase classification of liquid crystal textures using convolutional neural networks

Joshua Heaton 10133722

Department of Physics and Astronomy, The University of Manchester

MPhys project report

Project performed in collaboration with James Harbon Supervisor: Dr Ingo Dierking

April 10, 2021

Abstract

### Contents

T	Introduction	T
2		2 2 2 2
3	Summary of previous work	2
4	CNN Models         4.1 Sequential          4.2 Inception          4.3 ResNet	
5	Methodology5.1 Data preparation	2 2 2
6	Classification tasks and results  6.1 Cholesteric and smectic	2 2 2 2 2 2
7	Conclusions	2

#### 1 Introduction

Machine learning (ML) is the term assigned to a wide range of computer algorithms that use data to automatically improve their performance on a specific task. These tasks can take various forms, including decision making, pattern recognition, and prediction [1]. A sub-field of ML known as deep learning (DL) generally consists of applying large-scale multi-layer neural networks, a type of algorithm inspired by the structure of the brain, to tasks involving highly complex abstractions of data. Such intensive algorithms typically require vast quantities of data and powerful computational resources to be trained effectively, with the advantage that they do not require any manual feature extraction [2]. With the recent explosion in availability of such data and sophisticated computing technology, DL has seen a surge in interest and application among several fields [3]. Computer vision is one such field that has been impacted greatly. Convolutional neural networks (CNNs), a type of neural network suited particularly well to grid-based data, have proven extremely successful in the tasks of image classification, segmentation, and object detection [4].

There are many thousands of individual documented liquid crystal (LC) compounds, with each displaying a certain sequence of identifiable phases between that of a liquid and solid [5]. Commonly, polarised microscopy is used to capture images of the textures produced by LC phases for identification by eye [5]. Literature on machine learning for LC phase classification is sparse, with most studies focusing on the extraction of physical properties of LCs using simulated texture data [6, 7, 8, 9], or other means [10, 11, 12, 13]. Of most relevance is the work by Sigaki et al., in which they utilise CNNs to classify simulated isotropic and nematic phases to high accuracy [6].

In this project, we prepare a novel dataset of LC texture images captured by polarised microscopy, spanning multiple phases of all orders. Subsequently, we apply CNN classifier models to various phase groupings, probing the limits of attainable model accuracy. The work expands on and consolidates that of the first semester report [14], in which we demonstrated the viability of CNNs in some simple LC phase classification tasks. This report will provide a brief overview of LC phases, supervised ML, and CNNs, with further detail found in the first report [14]. Details of the models used will then be provided, followed by a presentation of the results when they are applied to each of the prepared datasets. Summary conclusions and the limitations of the study will then be discussed.

#### 2 Background principles

- 2.1 Liquid crystals
- 2.2 A brief overview of supervised machine learning
- 2.3 A brief overview of convolutional neural networks
- 3 Summary of previous work
- 4 CNN Models
- 4.1 Sequential
- 4.2 Inception
- 4.3 ResNet
- 5 Methodology
- 5.1 Data preparation
- 5.2 Model training configurations
- 6 Classification tasks and results
- 6.1 Cholesteric and smectic
- 6.2 Smectic A and C
- 6.3 Smectic I and F
- 6.4 Cholesteric, fluid smectic and hexatic smectic
- 6.5 Cholesteric, smectic A, C, and hexatic smectic
- 7 Conclusions

#### References

- [1] K. Murphy, Machine Learning: A Probabilistic Perspective. MIT Press, 2012.
- [2] I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. MIT Press, 2016.
- [3] A. Shrestha and A. Mahmood, "Review of deep learning algorithms and architectures," *IEEE Access*, vol. 7, pp. 53040–53065, 2019.
- [4] A. Voulodimos, N. Doulamis, A. Doulamis, E. Protopapadakis, and D. Andina, "Deep learning for computer vision: A brief review," *Intell. Neuroscience*, vol. 2018, 2018.

- [5] I. Dierking, Textures of Liquid Crystals. WILEY-VCH, 2003.
- [6] H. Y. D. Sigaki *et al.*, "Learning physical properties of liquid crystals with deep convolutional neural networks," *Scientific Reports*, vol. 10, p. 7664, 2020.
- [7] H. Y. D. Sigaki, R. F. de Souza, R. T. de Souza, R. S. Zola, and H. V. Ribeiro, "Estimating physical properties from liquid crystal textures via machine learning and complexity-entropy methods," *Phys. Rev. E*, vol. 99, p. 013311, 2019.
- [8] E. N. Minor *et al.*, "End-to-end machine learning for experimental physics: using simulated data to train a neural network for object detection in video microscopy," *Soft Matter*, vol. 16, p. 1751, 2020.
- [9] M. Walters, Q. Wei, and J. Z. Y. Chen, "Machine learning topological defects of confined liquid crystals in two dimensions," *Phys. Rev. E*, vol. 99, p. 062701, 2019.
- [10] F. Leon, S. Curteanu, C. Ta, L. Lin, and N. Hurduc, "Machine learning methods used to predict the liquid-crystalline behavior of some copolyethers," *Molecular Crystals and Liquid Crystals*, vol. 469, 2007.
- [11] C. Butnariu, C. Lisa, F. Leon, and S. Curteanu, "Prediction of liquid-crystalline property using support vector machine classification," *Journal of Chemometrics*, vol. 27, no. 7-8, pp. 179–188, 2013.
- [12] H. Doi, K. Takahashi, K. Tagashira, J. Fukuda, and T. Aoyagi, "Machine learning-aided analysis for complex local structure of liquid crystal polymers," *Scientific Reports*, vol. 9, 2019.
- [13] T. Inokuchi, R. Okamoto, and N. Arai, "Predicting molecular ordering in a binary liquid crystal using machine learning," *Liquid Crystals*, vol. 47, no. 3, pp. 438–448, 2020.
- [14] J. Heaton, "Classification of liquid crystal textures using machine learning," 2020.

## Appendices