

An optimization-inspired approach to parallel sorting

Team Metropolis:
James Farzi, JJ Lay, Graham West

February 13, 2019

1 The Algorithm

- Distributing/Importing Files
- Sorting
- Binning
- Exchanging data

2 Testing

- Methodology
- Results

3 Conclusions

The Algorithm

The Algorithm

XXX

- XXX
- XXX

XXX

- XXX
- XXX

Distributing/Importing Files

XXX

- XXX
- XXX

XXX

- XXX
- XXX

We implemented Merge and Bubble Sort

XXX

- XXX
- XXX

XXX

- XXX
- XXX

Binary search

- Since the data is sorted, we can use a binary search to find where the bin edges lie in index space
- We can then subtract successive edges' indices to find the number of elements in that bin

XXX

- XXX
- XXX

Adapting the bins

for interior bin edges (endpoint bins stay constant):

$$\begin{aligned}\Delta C &= 2.0(c_i^n - c_{i-1}^n)/(c_i^n + c_{i-1}^n) \\ \Delta B &= b_{i+1}^n - b_i^n \\ b_i^{n+1} &= b_i^n + \alpha \Delta C \Delta B\end{aligned}\tag{1}$$

where $0 < \alpha < 0.5$ and $b_i^n < b_{i+1}^n$ for all n

Uniformity metric

$$U^n = \max\left(\frac{c_{\max} - c_{\text{avg}}}{c_{\text{avg}}}, \frac{c_{\text{avg}} - c_{\min}}{c_{\text{avg}}}\right)\tag{2}$$

Binning




Figure 1: 5 nodes, 1000 data points, $\alpha = 0.475$

Binning




Figure 2: 10 nodes, 1000 data points, $\alpha = 0.475$

Binning




Figure 3: 10 nodes, 1000 data points, $\alpha = 0.25$

Exchanging data

XXX

- XXX
- XXX

XXX

- XXX
- XXX

Testing

Conclusions