密级状态:	绝密()	秘密()	内部资	[料()	公开(()	
Security Clas	ss: Top-Sec	ret ()	Secret (()	Inte	ernal ()	Public (√)

$OTA_from_Android 9.0_to_Android 10.0_Introduction$

(第二系统产品部)

(Technical Department, R & D Dept. II)

	文件标识:	RK-SM-YF-207		
	File No.:	KK-SW-1F-207		
文件状态:	当前版本:	V1.0		
Status:	Current Version:			
[] 草稿	作 者:	纪大峣		
[] Draft	Author:	Ji Dayao		
[]正在修改	完成日期:	2019-11-18		
[] Modifying	Finish Date:	2017-11-10		
[√] 正式发布	审核:			
[√] Released	Auditor:			
	审核日期:			
	Finish Date:			



免责声明

本文档按"现状"提供,福州瑞芯微电子股份有限公司("本公司",下同)不对本文档的任何陈述、信息和内容的准确性、可靠性、完整性、适销性、特定目的性和非侵权性提供任何明示或暗示的声明或保证。本文档仅作为使用指导的参考。

由于产品版本升级或其他原因,本文档将可能在未经任何通知的情况下,不定期进行更新或修改。

Disclaimer

This document is provided "as is" and Fuzhou Rockchip Electronics Co. Ltd ("the company") makes no express or implied statement or warranty as to the accuracy, reliability, completeness, merchantability, specific purpose and non-infringement of any statement, information and contents of the document. This document is for reference only.

This document may be updated without any notification due to product version upgrades or other reasons.

商标声明

"Rockchip"、"瑞芯微"、"瑞芯"均为本公司的注册商标,归本公司所有。 本文档可能提及的其他所有注册商标或商标,由其各自拥有者所有。

Brand Statement

Rockchip, RockchipTM icon, Rockchip and other Rockchip trademarks are trademarks of Fuzhou Rockchip Electronics Co., Ltd., and are owned by Fuzhou Rockchip Electronics Co., Ltd.

All other trademarks or registered trademarks mentioned in this document are owned by their respective owners.

版权所有 © 2019 福州瑞芯微电子股份有限公司

超越合理使用范畴,非经本公司书面许可,任何单位和个人不得擅自摘抄、复制本文档内容的部分或全部,并不得以任何形式传播。

Copyright © 2019 Fuzhou Rockchip Electronics Co., Ltd.

Beyond reasonable use, without the written permission, any unit or individual shall not extract or copy part or all of the content of this document, and shall not spread in any form.

福州瑞芯微电子股份有限公司

Fuzhou Rockchip Electronics Co., Ltd.

地址: 福建省福州市铜盘路软件园 A 区 18 号

网址:www.rock-chips.com客户服务电话:+86-4007-700-590客户服务传真:+86-591-83951833客户服务邮箱:fae@rock-chips.com

Fuzhou Rockchip Electronics Co., Ltd.

Address: No. 18 Building, A District, No.89,software Boulevard Fuzhou,Fujian,PRC

Website: www.rock-chips.com
Customer service tel.: +86-4007-700-590
Customer service fax: +86-591-83951833
Customer service e-mail: fae@rock-chips.com

版本历史 Revision History

版本号	作者	修改日期	修改说明	备注
Version no.	Author	Revision Date	Revision description	Remark
V1.0	纪大峣	2019/11/18	初始版本	
			Initial version release	

目 录 Contents

1	概述 OVERVIEW	. 1
2	ANDROID 9.0 所需补丁说明 PATCH REQUIRED FOR ANDROID9.0	. 1
3	使用说明 USAGE	. 3

1 概述 Overview

本文档描述了如何从 Rockchip Android 9.0 非 A/B 系统通过 OTA 的方式升级到 Android 10.0 非 A/B 系统。

This document describes how to upgrade from Rockchip Android9.0 non-A/B system to Android10.0 non-A/B system through OTA.

在 Rockchip Android 10.0 平台上,通过对应 lunch 项来实现对应 9.0 系统升级到 10.0 系统。如 rk3326 10.0 平台上 lunch 项 rk3326_pie 就实现了 Android 9.0 的 rk3326_pie 通过 OTA 升级到 rk3326 10.0 系统。

On Rockchip Android10.0 platform, the corresponding lunch option can implement upgrading from the system Android9.0 to Android10.0. For example, on rk3326 10.0 platform, lunch option rk3326_pie can implement rk3326 upgrading from Android9.0 to 10.0 system through OTA.

通过OTA方式实现的Android 9.0到Android 10.0系统,不具备Android 10.0的动态分区功能。

The upgrade from Android9.0 to Android10.0 system implemented through OTA doesn't support Android10.0 dynamic partition function.

2 Android 9.0 所需补丁说明 Patch required for Android 9.0

在 Andriod 9.0 上需增加如下补丁,并确保升级 10.0 之前,设备中的 9.0 固件所包含该补丁。

The following patch needs to be added on Android9.0. Please confirm Android9.0 image in the device includes this patch before upgrading to Android10.0.

1.device/rockchip/rk3326 中的 recovery fstab 增加 dtbo 节点。

Add dtbo node in the recovery fstab of device/rockchip/rk3326.

diff --git a/rk3326_pie/recovery.fstab b/rk3326_pie/recovery.fstab

index 51fc8b5..e6b96cc 100755

--- a/rk3326_pie/recovery.fstab

+++ b/rk3326_pie/recovery.fstab

@@ -23,3 +23,4 @@

/dev/block/by-name/trust /trust emmc

defaults defaults

/dev/block/by-name/baseparamer /baseparamer emmc

defaults defaults

/dev/block/by-name/vbmeta /vbmeta emmc

defaults defaults

+/dev/block/by-name/dtbo /dtbo emmc

defaults defaults

2.关闭 libvintf 升级包兼容性检查

```
Disable the compatibility check for libvintf upgrading package
    system/libvintf:
    diff --git a/VintfObject.cpp b/VintfObject.cpp
    index 604f7cb..afea999 100644
    --- a/VintfObject.cpp
    +++ b/VintfObject.cpp
    @@ -528,7 +528,7 @@ int32_t checkCompatibility(const std::vector<std::string>& xmls, bool
mount,
          }
          return INCOMPATIBLE;
      }
    +#if 0
     if ((disabledChecks & DISABLE_RUNTIME_INFO) == 0) {
          if (!updated.runtimeInfo->checkCompatibility(*updated.fwk.matrix, error, disabledChecks)) {
               if (error) {
      @@ -538,6 +538,7 @@ int32_t checkCompatibility(const std::vector<std::string>& xmls, bool
mount,
               return INCOMPATIBLE;
          }
      }
    +#endif
     return COMPATIBLE;
  }
    3.recovery 中关闭 compability 兼容性检查。
    Disable the compatibility check in recovery.
    bootable/recovery:
    diff --git a/install.cpp b/install.cpp
    index 9e43ce3..28ea1d6 100644
    --- a/install.cpp
    +++ b/install.cpp
     @@ -508,7 +508,7 @@ bool verify_package_compatibility(ZipArchiveHandle package_zip) {
        ZipEntry compatibility_entry;
        std::string real_product = android::base::GetProperty("ro.target.product", "unkonw");
        if (FindEntry(package_zip, compatibility_entry_name, &compatibility_entry) != 0
           || real_product.compare("box")==0 ) {
           || real_product.compare("box")==0 || true) {
          LOG(INFO) << "Package doesn't contain " << COMPATIBILITY_ZIP_ENTRY << " entry";
          return true;
```

}

3 使用说明 Usage

在 Rockchip Android 10.0 平台上,按如下方式操作产生对应的 OTA 升级包,然后将该升级包放置在 Rockchip Android 9.0 设备上,进行正常的 OTA 升级即可。

On Rockchip Android10.0 platform, generate the corresponding OTA upgrading package according to the following steps, and then put the package on Rockchip Android9.0 device to do the normal OTA upgrade.

- 1. 选择 9.0 系统升级到 10.0 系统的对应 lunch 项,如 rk3326_pie Select the corresponding lunch option for upgrading from 9.0 to 10.0, such as rk3326_pie
- 2. 正常编译系统(编译 uboot、kernel 并且 lunch 后执行如下命令编译):

Compile the system normally (compile uboot, kernel and execute the following command after lunch to compile):

make clean && make -j32 && make otapackage -j32 && ./mkimage.sh ota

3. 取出第2步编译出来的升级包,命名为 update.zip

Fetch out the upgrading package compiled by step 2, and name it update.zip.

4. 将对应的 update.zip 放置在 Android 9.0 设备上升级即可。

Put the corresponding update.zip on Android9.0 device to do upgrading.