

PreLab Part 1

1. I think it will take at least 10 swaps
2. The worse case scenario of bubble swap would be if everything is in backwards order, so it will depend on how many elements in the array. $O(n^2)$.

PreLab Part 2:

1. The worst time complexity for Shell sort depends on how big the gap is between first element and last element but it would be $O(n^2)$.
2. I would use a while loop and update it every time so I won't have to continuous iterate again.

PreLab Part 3:

1. Quicksort worst case complexity occurs if an array is already sorted which creates a large complexity time. The good news is that it is already sorted, so it isn't completely doomed.

<https://www.geeksforgeeks.org/when-does-the-worst-case-of-quicksort-occur/>

PreLab Part 4:

1. The time complexity would be the same of $O(n^2)$ at worst case complexity but the binary search itself would be $O(\log 2n)$ with insertion..

PreLab Part 5:

1. I will keep track of comparison and moves by making a global variable that can reside through all files. I will use extern and then increment when needed. After each sort, I will reset it back to zero.

DESIGN

"Include all headers"

Main:

Extern moves and compares;

// Must input one of the case flags at command line

while(getopt(arguments) != -1):

Case A:

Store letter A in array

Case b:

Store letter b in array

Case s:

Store letter s in array

Case i:

Store letter i in array

Case p:

Get number in optarg which will be amount to print

Case r:

Get number for srand in optarg

Case n :

Get number for elements number

Allocate pointer to array;

Set srand()

For elements in the Letter array:

If letter = 'b' or 'A':

For i in range(0,array size)

rand() (less than 30 bits)

array[i]=random number

Bubble_sort(array,array size)

Print sorted array;

If letter = 's' or 'A':

For i in range(0,array size)

rand() (less than 30 bits)

array[i]=random number

Shell_sort(array,array size)

Print sorted array;

If letter = 'q' or 'A':

For i in range(0,array size)

rand() (less than 30 bits)

array[i]=random number

quick_sort(array,array size)

Print sorted array;

If letter = 'i' or 'A':

For i in range(0,array size)

rand() (less than 30 bits)

array[i]=random number

binary_sort(array,array size)

Print sorted array;

Print everything including headers

free();

END

// This sort goes through the whole array and checks adjacent values. It swaps and compares accordingly to determine which is smaller number

```
Bubble_sort(array,length):
    For range(i,length):
        If current element is less than element -1:
            Count comparisons
            Swap
            Count swap
    return
```

// This sorting method finds the gaps between elements and switches from that position. It then halves every time

Shell_sort(array,length)

```
While gap(length) !=1:
    For range(gap,length):
        For range(i,gap-1,-gap):
            If array[element]<array[element-gap])
                Swap
                Count swaps and comparisons
    length/=2;
```

```
Gap(length):
    If length <=2 : return 1
    Else:
        Return 5*n/11
```

//Quick sort separates the array into two, and then sorts each one and then combines.

```
Quick_sort(array,length,index 0, index last):
    If index 0<index last:
        index=Partition(array,index 0, index last)
        Quick sort(" ",index-1)
        Quick sort(" ", index+1, " ")
```

```
Partition(index 0, index last):
    Create a pivot point which is first element
    lo=index0
    hi=index last
```

```

while(true):
    While lo <= hi & array[hi] >= pivot point:
        hi-=1
    While lo <= hi & array[lo] <= pivot point:
        lo+=1
    If lo < hi:
        Swap
        Count swaps and comparisons

    Break;

```

//Binary sort is an insertion that finds the middle element and compares it with other and then places at the right location.

```

Binary Sort(array):
    For i in range(1,length):
        l=0
        r=i
        while(l<r):
            Get mid point
            If array[i] >mid point value:
                l=mid+1
            Else:
                r=mid

        For j in range(i,length,-1):
            Swap
            Count swap and comparisons

```