2.3.3.3 Data Dictionary

The following tables are the system's data dictionary.

Table 15. user

Field Name	Data Type	Description
id	VARCHAR	Primary Key. Unique identifier for the user.
name	VARCHAR	Full name of the user.
email	VARCHAR	Unique email address used for sign in.
email_verified	BOOLEAN	Indicates whether the email address was verified.
image	VARCHAR	URL of the profile picture. Nullable.
role	ENUM[]	List of roles held by the user ('buyer', 'seller').
is_active	BOOLEAN	Indicates whether the account may sign in.
last_active_at	TIMESTAMP	Date and time the user was last active.
two_factor_enabled	BOOLEAN	Indicates whether two-step sign in is turned on.
terms_accepted_at	TIMESTAMP	Date and time the terms were accepted. Nullable.
terms_version	VARCHAR	Version of the terms that was accepted. Nullable.
created_at	TIMESTAMP	Date and time the account was created.
updated_at	TIMESTAMP	Date and time the account was last changed.

Table 15 stores every account holder together with their roles, active status, and terms acceptance, so one record serves both buyers and sellers.

Table 16. session

Field Name	Data Type	Description
id	VARCHAR	Primary Key. Unique identifier for the session.
user_id	VARCHAR	Foreign Key linking to the USER table.
token	VARCHAR	Unique secret token that identifies the session.
expires_at	TIMESTAMP	Date and time the session ends.
ip_address	VARCHAR	IP address the session started from. Nullable.
user_agent	VARCHAR	Browser or device description. Nullable.
created_at	TIMESTAMP	Date and time the session was created.
updated_at	TIMESTAMP	Date and time the session was last changed.

Table 16 keeps each signed-in device session so users stay signed in securely.

Table 17. account

Field Name	Data Type	Description
id	VARCHAR	Primary Key. Unique identifier for the authentication account.
user_id	VARCHAR	Foreign Key linking to the USER table.
account_id	VARCHAR	Identifier of the account at the sign-in provider.
provider_id	VARCHAR	Name of the sign-in provider, such as credential or google.
password	VARCHAR	Hashed password. Never stored as plain text. Nullable.
access_token	VARCHAR	Provider access token. Nullable.
refresh_token	VARCHAR	Provider refresh token. Nullable.
id_token	VARCHAR	Provider identity token. Nullable.
access_token_expires_at	TIMESTAMP	Date and time the access token ends. Nullable.
refresh_token_expires_at	TIMESTAMP	Date and time the refresh token ends. Nullable.
scope	VARCHAR	Permissions granted by the provider. Nullable.
created_at	TIMESTAMP	Date and time the record was created.
updated_at	TIMESTAMP	Date and time the record was last changed.

Table 17 separates sign-in credentials and linked sign-in providers (email and password, Google) from the profile in the USER table.

Table 18. verification

Field Name	Data Type	Description
id	VARCHAR	Primary Key. Unique identifier for the verification record.
identifier	VARCHAR	What is being verified, such as an email address.
value	VARCHAR	The code or token value.
expires_at	TIMESTAMP	Date and time the code stops working.
created_at	TIMESTAMP	Date and time the record was created.
updated_at	TIMESTAMP	Date and time the record was last changed.

Table 18 holds short-lived codes used for email verification and one-time sign-in codes.

Table 19. two_factor

Field Name	Data Type	Description
id	VARCHAR	Primary Key. Unique identifier for the record.
user_id	VARCHAR	Foreign Key linking to the USER table.
secret	VARCHAR	Secret used to make one-time codes.
backup_codes	VARCHAR	Stored backup codes for emergency sign in.
verified	BOOLEAN	Indicates whether the setup was confirmed.
failed_verification_count	INT	Number of wrong codes entered in a row.
locked_until	TIMESTAMP	Date and time the lock ends after too many wrong codes. Nullable.

Table 19 stores the second sign-in step for users who turned on two-step verification.

Table 20. sellers_profile

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the stall profile.
user_id	VARCHAR	Foreign Key linking to the seller in the USER table.
shop_name	VARCHAR	Name of the seller's stall.
detail_address	VARCHAR	Written address of the stall.
latitude	DOUBLE	Geographic coordinate used for map positioning. Nullable.
longitude	DOUBLE	Geographic coordinate used for map positioning. Nullable.
phone_number	VARCHAR	Contact number of the seller. Nullable.
pickup_instructions	TEXT	Directions for finding the pickup point. Nullable.
pickup_capacity	INT	How many pickups may happen at the same time.
pickup_within_minutes	INT	Longest pickup range a buyer may choose, in minutes.
closed_date	VARCHAR	Date (YYYY-MM-DD) the stall is closed. Nullable.
away_started_at	TIMESTAMP	Date and time the seller went away. Nullable.
away_until	TIMESTAMP	Date and time the seller returns. Nullable.
away_reason	TEXT	Reason the seller is away. Nullable.
is_current	BOOLEAN	Indicates whether this is the seller's current profile.
created_at	TIMESTAMP	Date and time the profile was created.
updated_at	TIMESTAMP	Date and time the profile was last changed.

Table 20 stores each seller's stall details, map position, pickup rules, and away status so buyers can find and schedule a pickup.

Table 21. vegetable_catalog

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the vegetable.
filipino_name	VARCHAR	Unique Filipino name of the vegetable.
english_name	VARCHAR	English name of the vegetable.
search_aliases	JSONB	List of other names used when searching.
search_text	VARCHAR	Combined text used for fast search.
category	ENUM	Vegetable group, such as Leafy Greens or Root Vegetables.
scientific_name	VARCHAR	Scientific name. Nullable.
source_url	VARCHAR	Link to the reference for this entry.
review_status	ENUM	Review state: draft, approved, or inactive.
is_active	BOOLEAN	Indicates whether the vegetable can be listed.
created_at	TIMESTAMP	Date and time the entry was created.
updated_at	TIMESTAMP	Date and time the entry was last changed.

Table 21 lists the approved vegetables sellers can choose from, with Filipino and English names for search.

Table 22. sellers_product

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the listing.
user_id	VARCHAR	Foreign Key linking to the seller in the USER table.
vegetable_catalog_id	UUID	Foreign Key linking to the VEGETABLE_CATALOG table. Nullable.
product_name	VARCHAR	Name of the product being sold.
image_url	VARCHAR	URL of the product photo. Nullable.
product_type	ENUM	General group of the product.
scaling_type	ENUM	Selling unit: sack, kilo, or pile.
product_price	DECIMAL	Current listing price.
base_price	DECIMAL	Original price before any drops.
price_reduction_amount	DECIMAL	Pesos taken off at each automatic price drop.
minimum_price	DECIMAL	Lowest price the listing may drop to. Nullable.
price_reduction_enabled	BOOLEAN	Indicates whether automatic price drops are on.
price_schedule_started_at	TIMESTAMP	Date and time the drop schedule began. Nullable.
price_reduction_periods_applied	INT	Number of price drops already applied.
auto_post_enabled	BOOLEAN	Indicates whether the seller allowed automatic follow-up posts.
auto_post_accepted_at	TIMESTAMP	Date and time the seller allowed them. Nullable.
product_qty	DECIMAL	Quantity currently available.
original_qty	DECIMAL	Quantity when the listing was made.
low_stock_threshold	DECIMAL	Quantity that triggers a low-stock alert. Nullable.
condition	ENUM	Seller-declared condition: good, fair, or needs_inspection.
published_at	TIMESTAMP	Date and time the listing went live. Nullable.
is_marketable	BOOLEAN	Indicates whether the listing is shown in the marketplace.
is_active	BOOLEAN	Indicates whether the listing is active.
created_at	TIMESTAMP	Date and time the listing was created.
updated_at	TIMESTAMP	Date and time the listing was last changed.

Table 22 is the main listing record where sellers manage surplus vegetables, prices, stock, and automatic price drops.

Table 23. listing_cycles

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the cycle.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
vegetable_catalog_id	UUID	Foreign Key linking to the VEGETABLE_CATALOG table. Nullable.
scaling_type	ENUM	Selling unit used in this cycle.
vegetable_key	VARCHAR	Key that groups the same vegetable across listings.
started_at	TIMESTAMP	Date and time the cycle began.
original_qty	DECIMAL	Quantity at the start of the cycle.

Table 23 records each time a listing starts a new selling round, used for ranking and price history.

Table 24. product_stock_adjustments

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the adjustment.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
delta	DECIMAL	Amount added (positive) or taken away (negative).
before_qty	DECIMAL	Quantity before the change.
after_qty	DECIMAL	Quantity after the change.
reason	TEXT	Reason for the change.
created_at	TIMESTAMP	Date and time the change was made.

Table 24 keeps a change history of every stock increase or decrease made by a seller.

Table 25. seller_visibility_boosts

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the boost.
listing_cycle_id	UUID	Foreign Key linking to the LISTING_CYCLES table.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
reason	ENUM	Why the boost happened: initial or price_reduction.
reduction_period	INT	Which price drop this boost belongs to.
boost_key	VARCHAR	Unique key that prevents duplicate boosts.
status	ENUM	Boost state: prompt, queued, sent, failed, or dismissed.
retry_count	INT	Number of send retries.
lease_until	TIMESTAMP	Date and time the worker lock ends. Nullable.
next_attempt_at	TIMESTAMP	Date and time of the next send attempt.
read_at	TIMESTAMP	Date and time the seller read it. Nullable.
follow_up_due_at	TIMESTAMP	Date and time the follow-up is due. Nullable.
follow_up_attempts	INT	Number of follow-up attempts.
price_before	DECIMAL	Price before the boost. Nullable.
price_after	DECIMAL	Price after the boost. Nullable.
sent_at	TIMESTAMP	Date and time the boost was sent. Nullable.
last_error	TEXT	Latest error message. Nullable.
price_drop_setup_at	TIMESTAMP	Date and time the price-drop setup was asked. Nullable.
price_drop_setup_notified_at	TIMESTAMP	Date and time the seller was told about it. Nullable.
created_at	TIMESTAMP	Date and time the record was created.
updated_at	TIMESTAMP	Date and time the record was last changed.

Table 25 tracks each Priority Boost prompt and post, including retries, follow-ups, and the price before and after.

Table 26. fb_post_logs

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the post record.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
post_type	VARCHAR	Type of post, such as first or follow-up.
facebook_post_id	VARCHAR	Post identifier returned by Facebook. Nullable.
caption	TEXT	Text that was posted. Nullable.
price	DECIMAL	Price shown in the post.
posted_at	TIMESTAMP	Date and time the post was made.
status	VARCHAR	Result of the post, such as success or failed.

Table 26 records each Facebook post made for a listing and whether it worked.

Table 27. instagram_post_logs

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the post record.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
post_type	VARCHAR	Type of post, such as first or follow-up.
instagram_post_id	VARCHAR	Post identifier returned by Instagram. Nullable.
post_url	VARCHAR	Link to the post. Nullable.
price	DECIMAL	Price shown in the post.
posted_at	TIMESTAMP	Date and time the post was made.
status	VARCHAR	Result of the post, such as success or failed.

Table 27 records each Instagram post made for a listing and whether it worked.

Table 28. buyer_saved_products

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the saved item.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
created_at	TIMESTAMP	Date and time the listing was saved.

Table 28 lets buyers save listings to see again later.

Table 29. seller_follows

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the follow.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
created_at	TIMESTAMP	Date and time the buyer followed.

Table 29 records which buyers follow which sellers.

Table 30. seller_listing_events

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the event.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
shop_name	VARCHAR	Stall name at the time of the event.
product_name	VARCHAR	Product name at the time of the event.
event_type	VARCHAR	Kind of event, such as new_listing.
metadata	JSONB	Extra details such as old price, new price, and stock.
created_at	TIMESTAMP	Date and time the event happened.
processed_at	TIMESTAMP	Date and time followers were told. Nullable.

Table 30 records listing updates, such as new listings and price drops, that followers are told about.

Table 31. buyer_listing_notices

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the notice.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
event_id	UUID	Foreign Key linking to the SELLER_LISTING_EVENTS table.
read_at	TIMESTAMP	Date and time the buyer read it. Nullable.
email_sent_at	TIMESTAMP	Date and time the email was sent. Nullable.
email_attempts	INT	Number of email send attempts.
created_at	TIMESTAMP	Date and time the notice was created.

Table 31 delivers each listing event to a following buyer and tracks the email.

Table 32. notification_devices

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the device record.
user_id	VARCHAR	Foreign Key linking to the USER table.
platform	ENUM	Device type: android, ios, or web.
push_token	VARCHAR	Unique token used to send a push message.
device_id	VARCHAR	Identifier of the device. Nullable.
is_enabled	BOOLEAN	Indicates whether pushes are allowed.
last_seen_at	TIMESTAMP	Date and time the device was last seen.
invalidated_at	TIMESTAMP	Date and time the token stopped working. Nullable.
created_at	TIMESTAMP	Date and time the device was added.
updated_at	TIMESTAMP	Date and time the record was last changed.

Table 32 stores each device registered to receive push notifications.

Table 33. notification_outbox

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the queued message.
recipient_user_id	VARCHAR	Foreign Key linking to the receiving USER.
type	ENUM	Kind of notification, such as seller_message or seller_boost.
aggregation_key	VARCHAR	Key that groups similar messages into one.
dedupe_key	VARCHAR	Unique key that prevents duplicates.
reference_id	VARCHAR	Identifier of the related record. Nullable.
item_count	INT	Number of items grouped in the message.
payload	JSONB	Message content.
status	ENUM	Delivery state: pending, processing, sent, or failed.
attempt_count	INT	Number of send attempts.
available_at	TIMESTAMP	Date and time the message may be sent.
locked_at	TIMESTAMP	Date and time a worker took it. Nullable.
sent_at	TIMESTAMP	Date and time it was sent. Nullable.
failed_at	TIMESTAMP	Date and time it failed. Nullable.
last_error	TEXT	Latest error message. Nullable.
created_at	TIMESTAMP	Date and time the message was queued.
updated_at	TIMESTAMP	Date and time the record was last changed.

Table 33 is the queue of push notifications waiting to be sent, with retry and error tracking.

Table 34. seller_notifications

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the notification.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
kind	VARCHAR	Kind of notification.
order_id	UUID	Foreign Key linking to the ORDERS table. Nullable.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table. Nullable.
payload	JSONB	Notification content.
dedupe_key	VARCHAR	Unique key that prevents duplicates.
read_at	TIMESTAMP	Date and time the seller read it. Nullable.
created_at	TIMESTAMP	Date and time the notification was created.

Table 34 is the in-app notification feed shown to sellers.

Table 35. seller_notification_settings

Field Name	Data Type	Description
seller_id	VARCHAR	Primary Key and Foreign Key linking to the seller in the USER table.
stock_price	BOOLEAN	Indicates whether stock and price alerts are on.
boost	BOOLEAN	Indicates whether boost alerts are on.
account	BOOLEAN	Indicates whether account alerts are on.
night_mode	BOOLEAN	Indicates whether quiet hours are on.
updated_at	TIMESTAMP	Date and time the setting was last changed.

Table 35 stores which kinds of notifications each seller wants.

Table 36. seller_opening_hours

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the record.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
weekday	INT	Day of the week, 0 for Sunday to 6 for Saturday.
is_closed	BOOLEAN	Indicates whether the stall is closed that day.
opens_minute	INT	Opening time in minutes after midnight (Manila time).
closes_minute	INT	Closing time in minutes after midnight (Manila time).

Table 36 is the weekly opening hours of each seller's stall.

Table 37. seller_away_periods

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the away period.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
started_at	TIMESTAMP	Date and time the away period began.
ended_at	TIMESTAMP	Date and time it ended. Nullable.
reason	TEXT	Reason for being away. Nullable.

Table 37 is the history of times a seller was away from the stall.

Table 38. checkouts

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the checkout.
buyers_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
idempotency_key	VARCHAR	Unique key sent with the request to block repeats.
request_fingerprint	VARCHAR	Summary of the request used to detect changes.
created_at	TIMESTAMP	Date and time the checkout was made.

Table 38 protects against double reservations when a buyer taps reserve more than once.

Table 39. orders

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the reservation.
checkout_id	UUID	Foreign Key linking to the CHECKOUTS table. Nullable.
buyers_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
sellers_id	VARCHAR	Foreign Key linking to the seller in the USER table.
status	ENUM	Order state: pending, completed, cancelled, expired, or declined.
total_amount	DECIMAL	Total price of all items.
pickup_start	TIMESTAMP	Start of the reserved pickup range. Nullable.
pickup_end	TIMESTAMP	End of the reserved pickup range. Nullable.
confirmed_at	TIMESTAMP	Date and time the order was confirmed. Nullable.
confirmation_mode	VARCHAR	How it was confirmed: manual or auto.
packed_at	TIMESTAMP	Date and time it was packed. Nullable.
ready_at	TIMESTAMP	Date and time it was ready. Nullable.
declined_at	TIMESTAMP	Date and time the buyer declined it. Nullable.
no_show_at	TIMESTAMP	Date and time the buyer was marked a no-show. Nullable.
counts_for_ranking	BOOLEAN	Indicates whether the order counts for seller ranking.
expires_at	TIMESTAMP	Date and time the QR code stops working. Nullable.
completed_at	TIMESTAMP	Date and time pickup was completed. Nullable.
cancelled_at	TIMESTAMP	Date and time it was cancelled. Nullable.
expired_at	TIMESTAMP	Date and time it expired. Nullable.
cancelled_by	VARCHAR	Who cancelled the order. Nullable.
cancellation_reason	TEXT	Reason for cancelling. Nullable.
created_at	TIMESTAMP	Date and time the reservation was created.
updated_at	TIMESTAMP	Date and time the reservation was last changed.

Table 39 is the reservation record that tracks one buyer's pickup from one seller from reservation to completion.

Table 40. ordered_items

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the line item.
orders_id	UUID	Foreign Key linking to the parent ORDERS table.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
product_name	VARCHAR	Product name at the time of reservation. Nullable.
scaling_type	ENUM	Selling unit at the time of reservation. Nullable.
quantity	DECIMAL	Amount reserved by the buyer. Nullable.
unit_price	DECIMAL	Price per unit at the time of reservation.
subtotal	DECIMAL	Quantity multiplied by unit price.
created_at	TIMESTAMP	Date and time the item was added.
updated_at	TIMESTAMP	Date and time the item was last changed.

Table 40 is the line items of an order, keeping the price and amount at the time of reservation.

Table 41. order_status_history

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the history record.
order_id	UUID	Foreign Key linking to the ORDERS table.
status	VARCHAR	Status the order moved to.
actor_id	VARCHAR	User who caused the change. Nullable.
note	TEXT	Extra note. Nullable.
created_at	TIMESTAMP	Date and time of the change.

Table 41 is the change history of every status an order went through.

Table 42. order_qr_scans

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the scan.
order_id	UUID	Foreign Key linking to the ORDERS table. Nullable.
seller_id	VARCHAR	Foreign Key linking to the scanning seller in the USER table.
result	VARCHAR	Scan result, such as ok, invalid, expired, or wrong_seller.
created_at	TIMESTAMP	Date and time of the scan.

Table 42 is the log of every QR scan a seller made, including failed ones.

Table 43. seller_scan_grace

Field Name	Data Type	Description
order_id	UUID	Primary Key and Foreign Key linking to the ORDERS table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
grace_until	TIMESTAMP	Date and time the extra time ends.

Table 43 gives a seller extra time to scan an order's QR code.

Table 44. order_reschedules

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the request.
order_id	UUID	Foreign Key linking to the ORDERS table.
proposed_by	VARCHAR	User who asked for the change.
reason	TEXT	Reason for the change.
old_start	TIMESTAMP	Previous pickup start.
old_end	TIMESTAMP	Previous pickup end.
new_start	TIMESTAMP	Requested pickup start.
new_end	TIMESTAMP	Requested pickup end.
status	VARCHAR	Request state: pending, accepted, rejected, or withdrawn.
responded_at	TIMESTAMP	Date and time of the answer. Nullable.
created_at	TIMESTAMP	Date and time the request was made.

Table 44 is the pickup time change requests between buyer and seller.

Table 45. order_declines

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the decline.
order_id	UUID	Foreign Key linking to the ORDERS table.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
reason	VARCHAR	Reason chosen by the buyer.
reason_valid	BOOLEAN	Indicates whether the reason counts as valid.
details	TEXT	Extra details from the buyer. Nullable.
items	JSONB	Items and amounts declined.
is_full	BOOLEAN	Indicates whether the whole order was declined.
photo_key	VARCHAR	Storage key of the buyer's photo.
photo_hash	VARCHAR	Fingerprint of the photo used to catch reuse.
photo_reused	BOOLEAN	Indicates whether the same photo was used before.
declined_at	TIMESTAMP	Date and time of the decline.
seller_due_at	TIMESTAMP	Date and time the seller must answer.
seller_response	VARCHAR	The seller's answer. Nullable.
seller_photo_key	VARCHAR	Storage key of the seller's photo. Nullable.
seller_note	TEXT	Seller's note. Nullable.
seller_responded_at	TIMESTAMP	Date and time the seller answered. Nullable.
status	VARCHAR	Decision state, such as pending_seller or seller_fault.
decided_at	TIMESTAMP	Date and time of the decision. Nullable.

Table 45 is the buyer's refusal of goods at pickup, with photo proof and the seller's answer.

Table 46. buyer_no_shows

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the no-show.
order_id	UUID	Foreign Key linking to the ORDERS table.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
marked_by	VARCHAR	User or system that marked the no-show.
sequence	INT	Which missed pickup this is for the buyer.
weight	INT	Trust points added.
excused	BOOLEAN	Indicates whether the buyer was excused.
created_at	TIMESTAMP	Date and time it was recorded.

Table 46 records buyers who missed a pickup and the points it adds.

Table 47. order_excuses

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the excuse.
order_id	UUID	Foreign Key linking to the ORDERS table.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
reason	VARCHAR	Reason given.
details	TEXT	Extra details. Nullable.
status	VARCHAR	Review state: pending, confirmed, or rejected.
decided_by	VARCHAR	User who decided. Nullable.
decided_at	TIMESTAMP	Date and time of the decision. Nullable.
created_at	TIMESTAMP	Date and time it was filed.

Table 47 is the buyer's explanation for a missed pickup.

Table 48. order_inquiries

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the question.
order_id	UUID	Foreign Key linking to the ORDERS table.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
question	TEXT	The buyer's question.
reply	TEXT	The seller's reply. Nullable.
replied_at	TIMESTAMP	Date and time of the reply. Nullable.
deadline_stage	INT	Reply reminder stage already reached.
created_at	TIMESTAMP	Date and time the question was asked.

Table 48 is the questions a buyer asks the seller about a reservation.

Table 49. product_inquiries

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the question.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
question	TEXT	The buyer's question.
reply	TEXT	The seller's reply. Nullable.
replied_at	TIMESTAMP	Date and time of the reply. Nullable.
deadline_stage	INT	Reply reminder stage already reached.
created_at	TIMESTAMP	Date and time the question was asked.

Table 49 is the questions a buyer asks the seller about a listing before reserving.

Table 50. order_reviews

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the review.
order_id	UUID	Foreign Key linking to the ORDERS table. One review per order.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
rating	INT	Service stars. Used for the seller's rating.
product_rating	INT	Product stars. Not used for ranking. Nullable.
review	TEXT	Written comment. Nullable.
ignored_at	TIMESTAMP	Date and time a suspicious rating was set aside. Nullable.
photo_key	VARCHAR	Storage key of an optional photo. Nullable.
seller_response	TEXT	The seller's reply to the review. Nullable.
created_at	TIMESTAMP	Date and time the review was written.
updated_at	TIMESTAMP	Date and time the review was edited. Nullable.

Table 50 is the buyer's star ratings and comment after a completed pickup.

Table 51. order_reports

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the report.
order_id	UUID	Foreign Key linking to the ORDERS table.
reporter_id	VARCHAR	Foreign Key linking to the USER filing the report.
subject_id	VARCHAR	Foreign Key linking to the USER being reported.
reason	VARCHAR	Category of the complaint.
details	TEXT	Explanation from the reporter.
status	VARCHAR	Report state: submitted, pending_corroboration, confirmed, rejected, disputed, or overturned.
resolution	TEXT	Outcome of the report. Nullable.
resolved_at	TIMESTAMP	Date and time it was resolved. Nullable.
created_at	TIMESTAMP	Date and time the report was filed.

Table 51 is the complaints filed about the other side of a transaction.

Table 52. order_report_evidence

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the file record.
report_id	UUID	Foreign Key linking to the ORDER_REPORTS table.
object_key	VARCHAR	Unique storage key of the file.
content_type	VARCHAR	File type, such as image/jpeg.
size_bytes	INT	File size in bytes.
created_at	TIMESTAMP	Date and time the file was added.

Table 52 is the files attached to a report as proof.

Table 53. conversations

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the conversation.
context_type	ENUM	What the chat is about: product, order, or seller.
context_key	VARCHAR	Unique key that prevents duplicate chats.
buyer_id	VARCHAR	Foreign Key linking to the buyer in the USER table.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
product_id	UUID	Foreign Key linking to the SELLERS_PRODUCT table. Nullable.
order_id	UUID	Foreign Key linking to the ORDERS table. Nullable.
status	ENUM	Chat state: open or closed.
last_message_at	TIMESTAMP	Date and time of the latest message.
awaiting_reply_since	TIMESTAMP	Date and time a buyer message started waiting for a reply. Nullable.
deadline_stage	INT	Reply reminder stage already reached.
created_at	TIMESTAMP	Date and time the chat was created.
updated_at	TIMESTAMP	Date and time the chat was last changed.

Table 53 is the chat threads between a buyer and a seller about a product, an order, or the seller.

Table 54. conversation_participants

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the record.
conversation_id	UUID	Foreign Key linking to the CONVERSATIONS table.
user_id	VARCHAR	Foreign Key linking to the USER table.
last_read_at	TIMESTAMP	Date and time the person last read the chat. Nullable.
archived_at	TIMESTAMP	Date and time the person archived the chat. Nullable.
blocked_at	TIMESTAMP	Date and time the person blocked the chat. Nullable.
created_at	TIMESTAMP	Date and time the person joined the chat.

Table 54 is the per-person chat state, such as read, archived, and blocked.

Table 55. conversation_messages

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the message.
conversation_id	UUID	Foreign Key linking to the CONVERSATIONS table.
sender_id	VARCHAR	Foreign Key linking to the USER sending the message.
client_message_id	VARCHAR	Key from the sender's device that prevents duplicates.
body	TEXT	Written text of the message.
created_at	TIMESTAMP	Date and time the message was sent.

Table 55 is the individual chat messages.

Table 56. trust_events

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the event.
event_key	VARCHAR	Unique key that prevents duplicate events.
order_id	UUID	Foreign Key linking to the ORDERS table. Nullable.
subject_id	VARCHAR	Foreign Key linking to the USER the event is about.
kind	VARCHAR	Kind of event.
classification	VARCHAR	How the event is counted.
source_id	UUID	Identifier of the record that caused the event. Nullable.
weight	INT	Points added. Nullable.
reason	TEXT	Plain-words reason shown to the person. Nullable.
policy_version	VARCHAR	Version of the trust rules used.
invalidated_at	TIMESTAMP	Date and time the event was cancelled. Nullable.
created_at	TIMESTAMP	Date and time the event was recorded.

Table 56 is the rule events, such as late replies, cancellations, and low ratings, that add trust points.

Table 57. trust_notices

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the notice.
notice_key	VARCHAR	Unique key that prevents duplicate notices.
recipient_id	VARCHAR	Foreign Key linking to the receiving USER.
order_id	UUID	Foreign Key linking to the ORDERS table. Nullable.
kind	VARCHAR	Kind of notice.
detail	TEXT	Full message: what happened, the rule, points, and how to dispute. Nullable.
attempts	INT	Number of send attempts.
locked_until	TIMESTAMP	Date and time a worker lock ends. Nullable.
sent_at	TIMESTAMP	Date and time it was sent. Nullable.
read_at	TIMESTAMP	Date and time it was read. Nullable.
created_at	TIMESTAMP	Date and time the notice was created.

Table 57 is the messages that tell users about trust events and actions.

Table 58. trust_actions

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the action.
action_key	VARCHAR	Unique key that prevents duplicate actions.
subject_id	VARCHAR	Foreign Key linking to the USER the action is for.
action_type	VARCHAR	Kind of action.
level	VARCHAR	Level: notice, warning, pause_24h, pause_3d, or block. Nullable.
weighted_points	INT	Points that led to the action.
policy_version	VARCHAR	Version of the trust rules used.
reason	TEXT	Reason for the action.
source_event_id	UUID	Foreign Key linking to the TRUST_EVENTS table. Nullable.
source_order_id	UUID	Foreign Key linking to the ORDERS table. Nullable.
starts_at	TIMESTAMP	Date and time the action starts.
ends_at	TIMESTAMP	Date and time the action ends. Nullable.
revoked_at	TIMESTAMP	Date and time it was lifted. Nullable.
revoked_by	VARCHAR	Foreign Key linking to the USER who lifted it. Nullable.
revocation_reason	TEXT	Reason it was lifted. Nullable.
created_at	TIMESTAMP	Date and time the action was created.

Table 58 is the warnings, pauses, and blocks given to users based on their trust points.

Table 59. trust_corrections

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the correction.
event_id	UUID	Foreign Key linking to the TRUST_EVENTS table.
requester_id	VARCHAR	Foreign Key linking to the USER who asked.
reason	TEXT	Reason for the correction.
outcome	VARCHAR	Result of the correction.
created_at	TIMESTAMP	Date and time of the correction.

Table 59 is the corrections made to a trust event after a request.

Table 60. trust_disputes

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the dispute.
event_id	UUID	Foreign Key linking to the TRUST_EVENTS table.
user_id	VARCHAR	Foreign Key linking to the USER who disputed.
reason	TEXT	Reason for the dispute.
status	VARCHAR	Decision state: upheld, rejected, or unresolved.
decision	TEXT	Explanation of the decision. Nullable.
created_at	TIMESTAMP	Date and time the dispute was sent.
decided_at	TIMESTAMP	Date and time of the decision. Nullable.

Table 60 is the disputes a user sends against a trust event.

Table 61. seller_flags

Field Name	Data Type	Description
id	UUID	Primary Key. Unique identifier for the flag.
seller_id	VARCHAR	Foreign Key linking to the seller in the USER table.
kind	VARCHAR	Flag type: under_watch, needs_review, or repeat_returns.
detail	TEXT	Extra detail. Nullable.
opened_at	TIMESTAMP	Date and time the flag was opened.
closed_at	TIMESTAMP	Date and time the flag was closed. Nullable.

Table 61 is the watch flags opened on sellers who need attention.