Week 13

Agenda

1. Recsys / Personalization Discussion

Discussion Questions

- What is a recommender system?
- Is Google a recommender system?
- What are some recommender systems you use? Which ones do you feel are best?
- What other systems do you interact with that are 'personalized'?

Is this a recommender system?



What about this?



Personal Data Marketplaces





DMPs: Personal data marketplaces

- Bluekai.com/registry
- Discuss.
- How do you feel about them?
- Which datasets about yourself do you assume are public?

Taste Domains

Taste Domains

Taste Domains

- Early research focused on ‘taste’ domains, particularly movies, music, and books.
- In these domains, 'finding' often involved suggestions from friends or tastemakers
- Researchers created collaborative filtering and other approaches as means of emulating this process
- Usually cast as ratings prediction problem in part because its relatively easy to collect ratings data

1996 MovieLens (Minnesota)

- http://en.wikipedia.org/wiki/MovieLens
- Research project collected ratings on movies, etc
- Very early Amazon and Netflix strongly influenced by this
- User based CF: Find k-nearest users and use their ratings
- 2001 Item based CF: Find k nearest items to those items a user prefers. http://files.grouplens.org/papers/www10_sarwar.pdf
- Still popular recommendation algorithm

What about recommending open houses?

movielens (Late 90's)



movielens (Today)

MovieLens 10M Dataset

Stable benchmark dataset. 10 million ratings and 100,000 tag applications applied to 10,000 movies by 72,000 users. Released 1/2009.

- README.html
- ml-10m.zip (size: 63 MB, checksum)

Permalink: http://grouplens.org/datasets/movielens/10m/



Recommending Houses



Search vs. Discovery

- Real estate search used to involve looking at classifieds in newspaper, Sites like Trulia are the online equivalent.
- Real estate recommendation used to (and still does) involve agents passing along listings. These recommendations get better as the agent learns more about the homebuyers.
- There are no real estate sites that emulate agent recommendations particularly well

Listing Discovery

- Important decision in one's life
- Only partly a taste domain--utility also plays a role (e.g. space, commute distance)
- Decision making happens over a period of time
- Tastes sometimes evolve during search process
- Social component to both (family, agent, sometimes friends)

Recommending Houses



Recommending Houses



Netflix DVD Recommendations





Netflix DVD Recommendations



2002 Netflix DVDs

- Mailed 1-3 DVDs to users
- Brand based in part on ratings and recommendations
- Users could rate any movie, not just those recently watched
- Users were told recommendations get better with more ratings

Search and Discovery

- Amazon historically incorporated recommendations into search results, including to extend results
- Recommendations used at different stages of transaction (E.g. Product page, cart)

Amazon Recommendations (2003)

Figure 1. The "Your Recommendations" feature on the Amazon.com homepage. Using this feature, customers can sort recommendations and add their own product ratings.

Figure 2. Amazon.com shopping cart recommendations. The recommendations are based on the items in the customer's cart: The Pragmatic Programmer *and* Physics for Game Developers.

2003 Amazon

- Many people at time identified recommendations with Amazon
- Item-Item CF (http://www.cs.umd.edu/~samir/498/Amazon-Recommendations.pdf)
- Compares to User-Item based CF (as in GroupLens)
- Pointed to scalability: compute similarities between items offline, usually nightly. This is preferred as item similarities change less frequently than user similarities
- Use item similarities to recommend similar items to those a user has shown preference towards
- Item preference a weighted combination of views, ratings, cart adds, and purchases
- Added blended exponential decay to account for time
- Item similarities can also be used in non-personalized fashion ("users who considered this, also considered that…")
- Not fully real-time and suffers from cold-start problem
- Flawed problem setup: not directly optimizing sales

Amazon Recommendations

Item-based Collaborative Filtering Recommendation Algorithms

Badrul Sarwar, George Karypis, Joseph Konstan, and John Riedl

GroupLens Research Group/Army HPC Research Center
Department of Computer Science and Engineering
University of Minnesota, Minneapolis, MN 55455

{sarwar, karypis, konstan, riedl}@cs.umn.edu

Appears in WWW10, May 1-5, 2001, Hong Kong.



Figure 1: The Collaborative Filtering Process.

Amazon Recommendations

Item-based Collaborative Filtering Recommendation Algorithms

Badrul Sarwar, George Karypis, Joseph Konstan, and John Riedl

GroupLens Research Group/Army HPC Research Center
Department of Computer Science and Engineering
University of Minnesota, Minneapolis, MN 55455

{sarwar, karypis, konstan, riedl}@cs.umn.edu

pears in WWW10, May 1-5, 2001, Hong Kong.



$$sim(i, j) = \frac{\sum_{u \in U}(R_{u,i} - \bar{R}_i)(R_{u,j} - \bar{R}_j)}{\sqrt{\sum_{u \in U}(R_{u,i} - \bar{R}_i)^2}\sqrt{\sum_{u \in U}(R_{u,j} - \bar{R}_j)^2}}.$$

Figure 2: Isolation of the co-rated items and similarity computation

Amazon Recommendations

Item-based Collaborative Filtering Recommendation Algorithms

Badrul Sarwar, George Karypis, Joseph Konstan, and John Riedl

GroupLens Research Group/Army HPC Research Center
Department of Computer Science and Engineering
University of Minnesota, Minneapolis, MN 55455

{sarwar, karypis, konstan, riedl}@cs.umn.edu

Appears in WWW10, May 1-5, 2001, Hong Kong.



Figure 3: Item-based collaborative filtering algorithm. The prediction generation process is illustrated for 5 neighbors

the corresponding user average from each co-rated pair. Formally, the similarity between items i and j using this scheme is given by

$$sim(i, j) = \frac{\sum_{u \in U}(R_{u,i} - \bar{R_u})(R_{u,j} - \bar{R_u})}{\sqrt{\sum_{u \in U}(R_{u,i} - \bar{R_u})^2}\sqrt{\sum_{u \in U}(R_{u,j} - \bar{R_u})^2}}.$$

Here $\bar{R_u}$ is the average of the u-th user's ratings.

Cold Start Problem

How do we handle new items?

How do we handle new users?

Pandora Recommendations



The Netflix Prize

- Training data
  - 100,480,507 ratings
  - 480,189 users
  - 17,770 movies
  - <user, movie, date of grade, grade>
  - <integer, integer, date, 1–5>
- Test data
  - 2,817,131 ratings
  - <integer, integer, date>
- Objective: minimize RMSE:

$$\sqrt{\frac{1}{n}\sum_{i=1}^{n}\left(\hat{Y}_i - Y_i\right)^2}$$

Most Active Users

User ID	# Ratings	Mean Rating
305344	17,651	1.90
387418	17,432	1.81
2439493	16,560	1.22
1664010	15,811	4.26
2118461	14,829	4.08
1461435	9,820	1.37
1639792	9,764	1.33
1314869	9,739	2.95

Data about the Movies

Most Loved Movies	Avg rating	Count
The Shawshank Redemption	4.593	137812
Lord of the Rings :The Return of the King	4.545	133597
The Green Mile	4.306	180883
Lord of the Rings :The Two Towers	4.460	150676
Finding Nemo	4.415	139050
Raiders of the Lost Ark	4.504	117456

Most Rated Movies
Miss Congeniality
Independence Day
The Patriot
The Day After Tomorrow
Pretty Woman
Pirates of the Caribbean

Highest Variance
The Royal Tenenbaums
Lost In Translation
Pearl Harbor
Miss Congeniality
Napolean Dynamite
Fahrenheit 9/11

The Netflix Prize

The Netflix Prize

SVD for Rating Prediction

- User factor vectors $p_u \in \Re^f$ and item-factors vector $q_v \in \Re^f$
- Baseline $b_{uv} = \mu + b_u + b_v$ (user & item deviation from average)
- Predict rating as $r'_{uv} = b_{uv} + p_u^T q_v$
- SVD++ (Koren et. Al) asymmetric variation w. implicit feedback

$$r'_{uv} = b_{uv} + q_v^T \left(|R(u)|^{-\frac{1}{2}} \sum_{j \in R(u)} (r_{uj} - b_{uj}) x_j + |N(u)|^{-\frac{1}{2}} \sum_{j \in N(u)} y_j \right)$$

- Where
  - $q_v, x_v, y_v \in \Re^f$ are three item factor vectors
  - Users are not parametrized, but rather represented by:
    - R(u): items rated by user u
    - N(u): items for which the user has given implicit preference (e.g. rated vs. not rated)

The Netflix Prize

Clustering

- Item-item CF didn't work well
- http://gigapan.com/gigapans/65469

Matrix Factorization Approaches

- 'Simon Funk' released his matrix factorization solution, which supported data sparsity. Used in Netflix (for predicted rating) today
- Dim reduction on sparse data using SVD
- http://sifter.org/~simon/journal/20061211.html
- Later approaches added better formalization and incremental improvements

The Netflix Prize

What Happened

- October 2, 2006: contest launched—$1 million first prize
  - *Cinematch* RMSE = 0.9514
  - Naïve "average rating" RMSE = 1.0540
- October 8, 2006: "WXYZ" team beats *Cinematch*
- June 2007: 20,000 teams in competition (150 countries)
- September 2007: "BellKor" RMSE = 0.8728 ($50k)
- September 2008: "BellKor" RMSE = 0.8616 ($50k)
- July 2009: two teams hit 10% margin—no more entries
- September 2009: "BellKor's Pragmatic Chaos" wins $1 million with RMSE of 0.8567. Same RMSE matched by "The Ensemble," but submission made 20 minutes later. Tiebreaker went to BellKor's Pragmatic Chaos



The Netflix Prize

Netflix: The Winner (contd)

- Final product used ensemble methods, which combined results from several algorithms.
  - Neighborhood methods
  - Matrix decomposition methods
  - Regression
  - Boltzmann machines
  - *Et cetera*
- Combining results is topic of another lecture!
- Gradient-boosted decision trees combine 500+ models.

What Other Factors Matter?

- The number of other people who have rated the movie
- The (square root of the) number of days since first rating
- The number of days since the movie's first rating
- Plus a bunch of others!

The Netflix Prize



Netflix Today

Goodbye

& Cinematch

Hello

 & % Match

Why?

+200% ratings volume

Clear link to personalization

Netflix Today

Everything you see is a recommendation



Netflix Today

Netflix Today

Ranking

- Ranking = **Scoring** + **Sorting** + **Filtering** bags of movies for presentation to a user
- Goal: Find the best possible ordering of a set of *videos* for a *user* within a specific *context* in real-time
- Objective: maximize consumption
- Aspirations: Played & “enjoyed” titles have best score
- Akin to CTR forecast for ads/search results

- Factors
  - Accuracy
  - Novelty
  - Diversity
  - Freshness
  - Scalability
  - …

Netflix Today

Ranking

- Popularity is the obvious baseline
- Ratings prediction is a clear secondary data input that allows for personalization
- We have added many other features (and tried many more that have not proved useful)
- What about the weights?
  - Based on A/B testing
  - Machine-learned

Netflix Today

Learning to Rank Approaches

1. Pointwise
   - Ranking function minimizes loss function defined on individual relevance judgment
   - Ranking score based on regression or classification
   - Ordinal regression, Logistic regression, SVM, GBDT, …
2. Pairwise
   - Loss function is defined on pair-wise preferences
   - Goal: minimize number of inversions in ranking
   - Ranking problem is then transformed into the binary classification problem
   - RankSVM, RankBoost, RankNet, FRank…

Personalized Presentation

What Makes a Photo Click: Selecting Hero Images with Deep Learning



Trulia hero images, before (left) and after (right) implementing a hero image selection algorithm.

Personalized Presentation

Using Deep Learning to automatically rank millions of hotel images

At idealo.de we trained two Deep Neural Networks to assess the aesthetic and technical quality of images 🙂😐🙁

Aesthetic MobileNet predictions



Netflix Today

Here are some screenshots from the tool that we use to track relative artwork performance.

Dragons: Race to the Edge: the two marked images below significantly outperformed all others.



Unbreakable Kimmy Schmidt



Dating Recommendations - How would you do it?

EHarmony



EHarmony

- Straighforward supervised learning approach to building a recommender system.
- Focus is on feature engineering
- 320 attributes (e.g. romantic, height, photo zoom, food preferences)
- Predict likelihood of 'successful match' using logistic regression (Vowpal Wabbit, GBM)
- For more info https://ieondemand.com/divisions/big-data/presentations/data-science-of-love-1

Job Recommendation - How would you do it?

LinkedIn


The Recommender Ecosystem
Jobs You May Be Interested In
Talent Match
CAP
Similar Profiles
Related search
Profile browse maps
Connections
Companies
Recommendations, similar companies search, peer companies, and company browse maps, company products and services browse maps
Network updates
Jobs browse maps
Events You May Be Interested In
Ad matching engine
Groups
Recommendations, similar groups search
Similar jobs
Referral Engine
News
HBR
LinkedIn
11

News Recommendation - How would you do it?

News Recommendation



Prismatic (Acquired by MS in 2015)

- Apple news is almost identical
- Problem: Provide personal news feed
- Popular on mobile devices as way to kill time (e.g. on bus)
- Mobile usage impacts implicit data

ML Approach

- Doesn't use Netflix Prize style collaborative filtering
- Step 1: Featurization using Topic Modeling (25K+ topics)
- Step 2: Directly optimize likelihood to read using logistic regression

Frontier: Deep Latent Factors

Variational Autoencoders

Inference model:

$$q_\psi(\mathbf{z}_u \mid \mathbf{r}_u) = \mathcal{N}(\mu_\psi(\mathbf{r}_u), \mathrm{diag}\{\sigma^2_\psi(\mathbf{r}_u)\})$$

Generative model:

$$\mathbf{z}_u \sim \mathcal{N}(0, \mathbf{I}_K), \;\; \pi(\mathbf{z}_u) \propto \exp\{f_\theta(\mathbf{z}_u)\}$$
$$\mathbf{r}_u \sim \mathrm{Multi}(N_u, \pi(\mathbf{z}_u))$$



Liang et al. (2018), [Variational Autoencoders for Collaborative Filtering](), WWW.

Frontier: Whole Page Optimization

Beyond Ranking: Optimizing Whole-Page Presentation



Figure 1: Modern search engine result page.

The ACM Conference Series on
Recommender Systems

HOME | RECSYS 2018 | PAST CONFERENCES | HONORS | CONTACT | search...

LATEST NEWS

July 26, 2018: Tentative lists of accepted short and long papers for RecSys 2018 are online!

July 12, 2018: This year's RecSys conference will feature a record number of six tutorials, taking place on Oct 2, prior to the main conference.

July 10, 2018: Acceptance notifications have been sent out: It was very competitive this year, with 18% acceptance rate for long and 25% for short papers.

July 4, 2018: Registration for RecSys 2018 is open!

June 12, 2018: The call for late-breaking results (posters) is out now, and the call for demos has been updated!

June 05, 2018: RecSys 2018 will feature three exciting keynotes by Elizabeth F. Churchill (Google), Lise Getoor (UCSC), and Christopher Berry (Canadian Broadcasting Corporation)!

May 30, 2018: The tutorial submission deadline has been extended to next Monday, June 4, 2018!

SHORTCUTS TO CONFERENCES

- RecSys 2018 (Vancouver)
- RecSys 2017 (Como)
- RecSys 2016 (Boston)
- RecSys 2015 (Vienna)
- RecSys 2014 (Silicon Valley)
- RecSys 2013 (Hong Kong)
- RecSys 2012 (Dublin)
- RecSys 2011 (Chicago)
- RecSys 2010 (Barcelona)
- RecSys 2009 (New York)
- RecSys 2008 (Lausanne)
- RecSys 2007 (Minnesota)

Final Thoughts?