

Salesman Rollout!

Code

To implement the Rollout algorithm with a base heuristic of nearest neighbors, at each iteration, a set of paths to each possible city and then a nearest neighbors until the very end is simulated. From all of these paths calculated, the initial next city chosen with the shortest distance is added to the actual path. The code is seen in the appendix but here is the output of the total distance so far and the final path.

```
Current totDist = 2
Current totDist = 7
Current totDist = 8
Current totDist = 11
Current totDist = 17
Current totDist = 18
Current totDist = 27
Current totDist = 34
Current totDist = 40
Current totDist = 47
Current totDist = 59
Current totDist = 70
Current totDist = 83
Current totDist = 86
Current totDist = 90
Current totDist = 94
Current totDist = 96
Current totDist = 108
Current totDist = 122
Current totDist = 129
This is the distance traveled: 129
This is the salesman path: [0, 7, 20, 12, 8, 16, 17, 13, 11, 9, 19,
    10, 1, 15, 4, 3, 6, 14, 18, 5, 2]
```

This is interesting because if we used just the nearest neighbor method, we get a total distance of 139 which is not as good as the rollout method.

Appendix

Python

```
1 '''
2 Justine Serdoncillo
3 IE 5571 - Dynamic Programming
4 HW 4 Exercise 6.10
5 December 5, 2023
6 '''
7
8 """
9 Consider the distance matrix provided in the file HW6Data.
10 Your goal is to find a route of the Traveling Salesperson for this matrix assuming you start
    and finish your tour at node 1.
11 In a tour you can only visit each city once, and the tour is complete once you have visited
    all cities.
12 Your goal is to minimize your total distance traveled.
13 You will use rollout with a base policy of nearest neighbor to find your route.
14 """
15
16 import numpy as np
17 import pandas as pd
18 import matplotlib.pyplot as plt
19 import random
20 import math
21
22 # %% Inputs and Functions
23 filePath = 'HW6Data.csv'
24
25 def evalTravel(evalTravel):
26     evalTravel.append(0)
27     totDist = 0
28     for i in range(21):
29         totDist += dist_matrix[evalTravel[i], evalTravel[i+1]]
30     return totDist
31
32 def nearNeigh(numNodes, posNodes, currNode, currList, totDist):
33
34     for j in range(numNodes):
35         currMin = 1E5 # current minimum
36         currNodeMin = 0
37         for i in posNodes:
38             if dist_matrix[currNode, i] <= currMin:
39                 currMin = dist_matrix[currNode, i]
40                 currNodeMin = i
41         currList.append(currNodeMin)
42         totDist += currMin
43         posNodes = np.setdiff1d(np.copy(posNodes), [currNodeMin])
44         currNode = np.copy(currNodeMin)
45
46     return totDist
47
48 def cycle(numNodes):
49     global posNodes, currNode, currList, totDist
50
51     for j in range(numNodes):
52         currMin = 1E5 # current minimum
53         currNodeMin = 0
54         for i in posNodes:
55             dist = dist_matrix[currNode, i] + dist_matrix[i, 0]
56             if dist <= currMin:
57                 currMin = dist_matrix[currNode, i]
58                 currNodeMin = i
59         currList.append(currNodeMin)
60         totDist += currMin
61         posNodes = np.setdiff1d(np.copy(posNodes), [currNodeMin])
62         currNode = np.copy(currNodeMin)
63
64 def rollOut(numNodes, posNodes, currNode, currList, totDist):
65
```

```

66     for j in range(numNodes):
67         score = np.zeros(len(posNodes))
68         num = 0
69         for i in posNodes:
70             posCopy = np.setdiff1d(np.copy(posNodes),[i])
71             currCopy = currList + [i]
72             totCopy = totDist + dist_matrix[currNode, i]
73             score[num] = nearNeigh(numNodes-1, posCopy, i, currCopy, totCopy)
74             num += 1
75
76         currNodeMin = posNodes[np.argmin(score)]
77         currList.append(currNodeMin)
78         totDist += dist_matrix[currNode, currNodeMin]
79         posNodes = np.setdiff1d(np.copy(posNodes),[currNodeMin])
80         currNode = np.copy(currNodeMin)
81         print(f"Current totDist = {totDist}")
82
83     return totDist
84
85 # %%
86 df = pd.read_csv(filePath)
87 dist_matrix = df.values
88 baseScores = np.zeros(20)
89 posNodes = np.arange(21) #list of possible nodes initially available
90 posNodes = np.setdiff1d(posNodes,[0]) #remove 0
91 currNode = 0 # updating node location
92 currList = [0] # updating list
93 totDist = 0 # total distance
94 base = 0
95
96 #cycle(20) # totDist = 487
97 #nearNeigh(20) # totDist = 157
98 totDist += rollOut(20, posNodes, currNode, currList, totDist)
99
100 for i in range(21):
101     currList[i] += 1
102
103 totDist += dist_matrix[currNode, 0]
104
105 print(f"This is the distance traveled: {totDist}")
106 print(f"This is the salesman path: {currList}")

```