


Graphics Programming

5TH WEEK, 2022



Programmable Pipelines *★ Mtd*

- Two components
 - Vertex program (vertex shaders)
 - Fragment program (fragment shaders)
- In the pipeline architecture, the vertex processor and the fragment processor are programmable by application programs called shaders



Vertex Shader Applications

- Moving vertices
 - Morphing
 - Wave motion $\text{ex) } \frac{d}{dt}$
 - Fractals
- Lighting
 - More realistic models
 - Cartoon shaders

Fragment Shader Applications (1)

- Per fragment lighting calculations



Per vertex lighting

꼭지점




Per fragment lighting


픽셀

Fragment Shader Applications (2)

- Texture mapping



Smooth shading



Environment
mapping

환경 매핑

Bump mapping

Simple Vertex Shader


```
attribute vec4 vPosition;  
void main(void) delete  
{  
    gl_Position = vPosition;  
}
```

input from application

must link to variable in application

built in variable

Execution Model – Vertex Shader



Simple Fragment Shader

```
precision mediump float;
```

↳ 고정밀도 실수


```
void main(void)
```

```
{
```


```
    gl_FragColor = vec4( 1.0, 0.0, 0.0, 1.0 );
```

```
}
```


Execution Model – Fragment Shader



Data Type

- C types: **int**, **float**, **bool**
- Vectors:
 - float **vec2**, **vec3**, **vec4**
 - Also int (**ivec**) and boolean (**bvec**)
- Matrices: **mat2**, **mat3**, **mat4**
 -  Stored by columns
 - Standard referencing **m[row][column]**
- C++ style constructors
 - **vec3 a = vec3(1.0, 2.0, 3.0);**
 - **vec2 b = vec2(a);**

$$\begin{aligned} 2x + 3y &= 2 \\ 4x - y &= 3 \end{aligned}$$

$$\Downarrow$$
$$\begin{bmatrix} 2 & 3 \\ 4 & -1 \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} = \begin{bmatrix} 2 \\ 3 \end{bmatrix}$$

 \Leftrightarrow

$$\begin{bmatrix} x \\ y \end{bmatrix} = \begin{bmatrix} 2 & 3 \\ 4 & -1 \end{bmatrix}^{-1} \begin{bmatrix} 2 \\ 3 \end{bmatrix}$$

Pointers

- There are no pointers in GLSL
- We can use C structs which can be copied back from functions
- Because matrices and vectors are basic types they can be passed into and output from GLSL functions
 - Ex) `mat3 func(mat3 a);`
- Variables passed by copying

Qualifiers

NGA

- GLSL has many of the same qualifiers such as const as C/C++
- Need others due to the nature of the shader architecture
- Variables can change
 - Once per primitive
 - Once per vertex
 - Once per fragment
 - At any time in the application
- Vertex attributes are interpolated by the rasterizer into fragment attributes

Attribute Qualifiers

- Attribute-qualified variables can change at most once per vertex
- There are a few built in variables such as **gl_Position** but most have been deprecated
- User defined (in application program)
 - **attribute float temperature;**
 - **attribute vec3 velocity;**
 - Recent versions of GLSL use **in** and **out** qualifiers to get to and from shaders

Uniform Qualifiers

- Variables that are constant for an entire primitive
- Can be changed in application and sent to shaders
- ✧ • Cannot be changed in shader *нельзя менять*
- Used to pass information to shader such as the bounding box of a primitive

Varying Qualifiers

- Variables that are passed from vertex shader to fragment shader
- Automatically interpolated by the rasterizer
- With WebGL, GLSL uses the varying qualifier in both shaders
 - `varying vec4 color;`
- More recent versions of WebGL use out in vertex shader and in in the fragment shader
 - `out vec4 color; // vertex shader`
 - `in vec4 color; // fragment shader`

Example: Vertex Shader

```
attribute vec4 vPosition;  
attribute vec4 vColor;  
varying vec4 fColor;  
void main(void)  
{  
    gl_Position = vPosition;  
    fColor = vColor;  
}
```

73

7044, 12!

Corresponding Fragment Shader

```
precision mediump float;
```

```
varying vec4 fColor;
```

```
void main(void)
```

```
{
```

```
    gl_FragColor = fColor;
```

```
}
```

Sending Colors from Application

```
var cBuffer = gl.createBuffer();  
gl.bindBuffer(gl.ARRAY_BUFFER, cBuffer);  
gl.bufferData(gl.ARRAY_BUFFER, flatten(colors),  
gl.STATIC_DRAW);  
  
var vColor = gl.getAttribLocation(program, "vColor");  
gl.vertexAttribPointer(vColor, 4, gl.FLOAT, false, 0, 0);  
gl.enableVertexAttribArray(vColor);
```

Sending a Uniform Variable

```
// in application
```

```
vec4 color = vec4(1.0, 0.0, 0.0, 1.0);  
colorLoc = glGetUniformLocation(program, "uColor");  
glUniform4f(colorLoc, color);
```

```
// in fragment shader (similar in vertex shader)
```

```
uniform vec4 uColor;  
void main() {  
    gl_FragColor = uColor;  
}
```

Operators and Functions

- Standard C functions
 - Trigonometric
 - Arithmetic
 - Normalize, reflect, length
- Overloading of vector and matrix types

```
mat4 a;  
vec4 b, c, d;  
c = b*a; // a column vector stored as a 1d array  
d = a*b; // a row vector stored as a 1d array
```

Swizzling and Selection

- Can refer to array elements by element using [] or selection (.) operator with

- **x, y, z, w**

- **r, g, b, a**

- **s, t, p, q**

- Ex) **a[2], a.b, a.z, a.p** are the same


- Swizzling operator lets us manipulate components

```
vec4 a = vec4(1.0, 2.0, 3.0, 4.0);
```

```
a.yz = vec2(1.0, 2.0); // a = (1.0, 1.0, 2.0, 4.0)
```

Position Input

- Returning position from click event
 - Canvas specified in HTML file of size `canvas.width` x `canvas.height`
 - Returned window coordinates are `event.clientX` and `event.clientY`





$$(0, h) \rightarrow (-1, -1)$$

$$(w, 0) \rightarrow (1, 1)$$

$$x = -1 + \frac{2 * x_w}{w}$$

$$y = -1 + \frac{2 * (h - y_w)}{h}$$

opposite
side 3
height



```

1  <!DOCTYPE html>
2  <html>
3      <head>
4          <title>2022 Computer Graphics - Drawing Points</title>
5
6          <script id="vertex-shader" type="x-shader/x-vertex">
7              attribute vec4 vPosition;
8
9              void main() {
10                 gl_PointSize = 5.0;
11                 gl_Position = vPosition;
12             }
13          </script>
14
15          <script id="fragment-shader" type="x-shader/x-fragment">
16              precision mediump float;
17
18              void main() {
19                 gl_FragColor = vec4(1.0, 0.0, 0.0, 1.0);
20             }
21          </script>
22
23          <script type="text/javascript" src="../../Common/webgl-utils.js"></script>
24          <script type="text/javascript" src="../../Common/initShaders.js"></script>
25          <script type="text/javascript" src="../../Common/MV.js"></script>
26          <script type="text/javascript" src="drawPoints.js"></script>
27      </head>
28      <body>
29          <canvas id="gl-canvas" width="512" height="512">
30              Oops... your browser doesn't support the HTML5 canvas element!
31          </canvas>
32      </body>
33  </html>

```


File Edit Selection View Go Run Terminal HelpdrawPoints.js - Visual Studio Code

Restricted Mode is intended for safe code browsing. Trust this window to enable all features. Manage Learn More

drawPoints.html JS drawPoints.js

C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawPoints.js > ...

```
1 var gl;
2 var points;
3
4 window.onload = function init() {
5     var canvas = document.getElementById("gl-canvas");
6
7     gl = WebGLUtils.setupWebGL(canvas);
8     if( !gl ) {
9         alert("WebGL isn't available!");
10    }
11
12    points = [];
13    var bMouseDown = false;
14
15    canvas.addEventListener("mousedown", function(event) {
16        bMouseDown = true;
17    });
18    canvas.addEventListener("mouseup", function(event) {
19        bMouseDown = false;
20    });
21    canvas.addEventListener("mousemove", function(event) {
22        if( bMouseDown ) {
23            var point = vec2(2 * event.clientX/canvas.width - 1,
24                2 * (canvas.height - event.clientY) / canvas.height - 1);
25            points.push(point);
26            gl.bufferData(gl.ARRAY_BUFFER, flatten(points), gl.STATIC_DRAW);
27
28            render();
29        }
30    });
31
32    // Configure WebGL
33    gl.viewport(0, 0, canvas.width, canvas.height);
34    gl.clearColor(1.0, 1.0, 1.0, 1.0);
35
```

Ln 1, Col 1 Spaces: 4 UTF-8 CRLF JavaScript

File Edit Selection View Go Run Terminal Help

drawPoints.js - Visual Studio Code


Restricted Mode is intended for safe code browsing. Trust this window to enable all features. Manage Learn More

drawPoints.html JS drawPoints.js

C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawPoints.js > ...


```
35
36 // Load shaders and initialize attribute buffers
37 var program = initShaders(gl, "vertex-shader", "fragment-shader");
38 gl.useProgram(program);
39
40 // Load the data into the GPU
41 var bufferId = gl.createBuffer();
42 gl.bindBuffer(gl.ARRAY_BUFFER, bufferId);
43 gl.bufferData(gl.ARRAY_BUFFER, flatten(points), gl.STATIC_DRAW);
44
45 // Associate our shader variables with our data buffer
46 var vPosition = gl.getAttribLocation(program, "vPosition");
47 gl.vertexAttribPointer(vPosition, 2, gl.FLOAT, false, 0, 0);
48 gl.enableVertexAttribArray(vPosition);
49
50 render();
51 };
52
53 function render() {
54     gl.clear(gl.COLOR_BUFFER_BIT);
55     gl.drawArrays(gl.POINTS, 0, points.length);
56 }
57
```

Ln 1, Col 1 Spaces: 4 UTF-8 CRLF JavaScript



연습 문제 (1)

- 웹페이지에 슬라이더를 추가하여, 점의 크기를 입력받아 그리시오.



drawPoints.html - Visual Studio Code

File Edit Selection View Go Run Terminal Help

drawPoints.html x JS drawPoints.js

C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > <> drawPoints.html > html > body > div

```
3     <head>
4         <title>2022 Computer Graphics - Drawing Points</title>
5
6         <script id="vertex-shader" type="x-shader/x-vertex">
7             attribute vec4 vPosition;
8             uniform float pointSize;
9
10            void main() {
11                gl_PointSize = pointSize;
12                gl_Position = vPosition;
13            }
14        </script>
15
16        <script id="fragment-shader" type="x-shader/x-fragment">
17            precision mediump float;
18
19            void main() {
20                gl_FragColor = vec4(1.0, 0.0, 0.0, 1.0);
21            }
22        </script>
23
24        <script type="text/javascript" src="../../Common/webgl-utils.js"></script>
25        <script type="text/javascript" src="../../Common/initShaders.js"></script>
26        <script type="text/javascript" src="../../Common/MV.js"></script>
27        <script type="text/javascript" src="drawPoints.js"></script>
28    </head>
29    <body>
30        <canvas id="gl-canvas" width="512" height="512">
31            Oops... your browser doesn't support the HTML5 canvas element!
32        </canvas>
33        <div>
34            Point Size: 1<input type="range" id="pointSize" min="1" max="20" step="1" value="10">20
35        </div>
36    </body>
37</html>
```



drawPoints.html

JS drawPoints.js X



C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawPoints.js > init > onchange


```
35
36 // Load shaders and initialize attribute buffers
37 var program = initShaders(gl, "vertex-shader", "fragment-shader");
38 gl.useProgram(program);
39
40 // Load the data into the GPU
41 var bufferId = gl.createBuffer();
42 gl.bindBuffer(gl.ARRAY_BUFFER, bufferId);
43 gl.bufferData(gl.ARRAY_BUFFER, flatten(points), gl.STATIC_DRAW);
44
45 // Associate our shader variables with our data buffer
46 var vPosition = gl.getAttribLocation(program, "vPosition");
47 gl.vertexAttribPointer(vPosition, 2, gl.FLOAT, false, 0, 0);
48 gl.enableVertexAttribArray(vPosition);
49
50 var pointSize = gl.getUniformLocation(program, "pointSize");
51 gl.uniform1f(pointSize, 10.0);
52
53 document.getElementById("pointSize").onchange = function() {
54     var size = this.value;
55     gl.uniform1f(pointSize, size);
56
57     render();
58 }
59
60 render();
61 };
62
63 function render() {
64     gl.clear(gl.COLOR_BUFFER_BIT);
65     gl.drawArrays(gl.POINTS, 0, points.length);
66 }
67
```



```
35
36 // Load shaders and initialize attribute buffers
37 var program = initShaders(gl, "vertex-shader", "fragment-shader");
38 gl.useProgram(program);
39
40 // Load the data into the GPU
41 var bufferId = gl.createBuffer();
42 gl.bindBuffer(gl.ARRAY_BUFFER, bufferId);
43 gl.bufferData(gl.ARRAY_BUFFER, flatten(points), gl.STATIC_DRAW);
44
45 // Associate our shader variables with our data buffer
46 var vPosition = gl.getAttribLocation(program, "vPosition");
47 gl.vertexAttribPointer(vPosition, 2, gl.FLOAT, false, 0, 0);
48 gl.enableVertexAttribArray(vPosition);
49
50 var pointSize = gl.getUniformLocation(program, "pointSize");
51 gl.uniform1f(pointSize, 10.0);
52
53 document.getElementById("pointSize").onchange = function() {
54     var size = this.value;
55     gl.uniform1f(pointSize, size);
56
57     render();
58 }
59
60 render();
61 };
62
63 function render() {
64     gl.clear(gl.COLOR_BUFFER_BIT);
65     gl.drawArrays(gl.POINTS, 0, points.length);
66 }
67
```



연습 문제 (2)

- HTML의 Select/Option element를 이용하여 점의 색상을 변경하시오.





drawPoints.html x JS drawPoints.js

C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > <> drawPoints.html > html > body > div > select#pointColor > option


```
15
16     <script id="fragment-shader" type="x-shader/x-fragment">
17     precision mediump float;
18     uniform vec4 fColor;
19
20     void main() {
21         gl_FragColor = fColor;
22     }
23     </script>
24
25     <script type="text/javascript" src="../../Common/webgl-utils.js"></script>
26     <script type="text/javascript" src="../../Common/initShaders.js"></script>
27     <script type="text/javascript" src="../../Common/MV.js"></script>
28     <script type="text/javascript" src="drawPoints.js"></script>
29 </head>
30 <body>
31     <canvas id="gl-canvas" width="512" height="512">
32     |     Oops... your browser doesn't support the HTML5 canvas element!
33     </canvas>
34     <div>
35         Point Size: 1<input type="range" id="pointSize" min="1" max="20" step="1" value="10">20 &nbsp; &nbsp;
36         Point Color: <select id="pointColor">
37             <option value="red">Red</option>
38             <option value="green">Green</option>
39             <option value="blue">Blue</option>
40             <option value="yellow">Yellow</option>
41             <option value="cyan">Cyan</option>
42             <option value="magenta">Magenta</option>
43             <option value="gray">Gray</option>
44             <option value="black">Black</option>
45         </select>
46     </div>
47 </body>
48 </html>
```



[illegible]

연습 문제 (3)

- 점마다 색상을 다르게 채색하시오.



```
<> drawPoints.html x JS drawPoints.js
C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > <> drawPoints.html > html > head > script#fragment-shader
1 <!DOCTYPE html>
2 <html>
3 <head>
4 <title>2022 Computer Graphics - Drawing Points</title>
5
6 <script id="vertex-shader" type="x-shader/x-vertex">
7 attribute vec4 vPosition;
8 attribute vec4 vColor;
9 uniform float pointSize;
10 varying vec4 fColor;
11
12 void main() {
13     fColor = vColor;
14     gl_PointSize = pointSize;
15     gl_Position = vPosition;
16 }
17 </script>
18
19 <script id="fragment-shader" type="x-shader/x-fragment">
20 precision mediump float;
21 varying vec4 fColor;
22
23 void main() {
24     gl_FragColor = fColor;
25 }
26 </script>
27
28 <script type="text/javascript" src="../../Common/webgl-utils.js"></script>
29 <script type="text/javascript" src="../../Common/initShaders.js"></script>
30 <script type="text/javascript" src="../../Common/MV.js"></script>
31 <script type="text/javascript" src="drawPoints.js"></script>
32 </head>
33 <body>
34 <canvas id="gl-canvas" width="512" height="512">
35     Oops... your browser doesn't support the HTML5 canvas element!
```

```
File Edit Selection View Go Run Terminal Help drawPoints.js - Visual Studio Code
<> drawPoints.html JS drawPoints.js X
C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawPoints.js > init > onclick
1  var gl;
2  var points, colors;
3
4  window.onload = function init() {
5      var canvas = document.getElementById("gl-canvas");
6
7      gl = WebGLUtils.setupWebGL(canvas);
8      if( !gl ) {
9          alert("WebGL isn't available!");
10     }
11
12     points = [];
13     colors = [];
14     var bMouseDown = false;
15
16     canvas.addEventListener("mousedown", function(event) {
17         bMouseDown = true;
18     });
19     canvas.addEventListener("mouseup", function(event) {
20         bMouseDown = false;
21     });
22     canvas.addEventListener("mousemove", function(event) {
23         if( bMouseDown ) {
24             var point = vec2(2 * event.clientX/canvas.width - 1,
25                 2 * (canvas.height - event.clientY) / canvas.height - 1);
26             points.push(point);
27             gl.bindBuffer(gl.ARRAY_BUFFER, bufferId);
28             gl.bufferData(gl.ARRAY_BUFFER, flatten(points), gl.STATIC_DRAW);
29
30             colors.push(currentColor);
31             gl.bindBuffer(gl.ARRAY_BUFFER, cbufferId);
32             gl.bufferData(gl.ARRAY_BUFFER, flatten(colors), gl.STATIC_DRAW);
33
34             render();
35     }
```

[illegible]

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
84

File Edit Selection View Go Run Terminal Help

drawPoints.js - Visual Studio Code

drawPoints.html JS drawPoints.js

C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawPoints.js > init > onclick

```
75
76 //var fColor = gl.getUniformLocation(program, "fColor");
77 //gl.uniform4f(fColor, 1.0, 0.0, 0.0, 1.0);
78 var currentColor = vec4(1.0, 0.0, 0.0, 1.0);
79
80 document.getElementById("pointColor").onclick = function(event) {
81     switch(event.target.value) {
82         case "red":
83             //gl.uniform4f(fColor, 1.0, 0.0, 0.0, 1.0);
84             currentColor = vec4(1.0, 0.0, 0.0, 1.0);
85             break;
86         case "green":
87             //gl.uniform4f(fColor, 0.0, 1.0, 0.0, 1.0);
88             currentColor = vec4(0.0, 1.0, 0.0, 1.0);
89             break;
90         case "blue":
91             //gl.uniform4f(fColor, 0.0, 0.0, 1.0, 1.0);
92             currentColor = vec4(0.0, 0.0, 1.0, 1.0);
93             break;
94         case "yellow":
95             //gl.uniform4f(fColor, 1.0, 1.0, 0.0, 1.0);
96             currentColor = vec4(1.0, 1.0, 0.0, 1.0);
97             break;
98         case "cyan":
99             //gl.uniform4f(fColor, 0.0, 1.0, 1.0, 1.0);
100             currentColor = vec4(0.0, 1.0, 1.0, 1.0);
101             break;
102         case "magenta":
103             //gl.uniform4f(fColor, 1.0, 0.0, 1.0, 1.0);
104             currentColor = vec4(1.0, 0.0, 1.0, 1.0);
105             break;
106         case "gray":
107             //gl.uniform4f(fColor, 0.5, 0.5, 0.5, 1.0);
108             currentColor = vec4(0.5, 0.5, 0.5, 1.0);
109             break;
```

Ln 116, Col 11 Spaces: 4 UTF-8 CRLF JavaScript

```


<> drawPoints.html JS drawPoints.js X
C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawPoints.js > init > onclick
98     case "cyan":
99         //gl.uniform4f(fColor, 0.0, 1.0, 1.0, 1.0);
100        currentColor = vec4(0.0, 1.0, 1.0, 1.0);
101        break;
102    case "magenta":
103        //gl.uniform4f(fColor, 1.0, 0.0, 1.0, 1.0);
104        currentColor = vec4(1.0, 0.0, 1.0, 1.0);
105        break;
106    case "gray":
107        //gl.uniform4f(fColor, 0.5, 0.5, 0.5, 1.0);
108        currentColor = vec4(0.5, 0.5, 0.5, 1.0);
109        break;
110    case "black":
111        //gl.uniform4f(fColor, 0.0, 0.0, 0.0, 1.0);
112        currentColor = vec4(0.0, 0.0, 0.0, 1.0);
113        break;
114    }
115
116    //render();
117
118
119    render();
120 };
121
122 function render() {
123     gl.clear(gl.COLOR_BUFFER_BIT);
124     gl.drawArrays(gl.POINTS, 0, points.length);
125 }
126

```


연습 문제 (4)

- 점마다 크기를 다르게 설정하여 그리시오.

제기까지



Linking Shader with Application

- Read shaders
- Compile shaders
- Create a program object
- Link everything together
- Link variables in application with variables in shaders
 - Vertex attributes
 - Uniform variables

Program Object

- Container for shaders
 - Can contain multiple shaders
 - Other GLSL functions

```
var program = gl.createProgram();
```

```
/* define shader objects here */
```

```
gl.attachShader( program, vertShdr );  
gl.attachShader( program, fragShdr );  
gl.linkProgram( program );
```

Reading a Shader

- Shaders are added to the program object and compiled
- Usual method of passing a shader is as a null-terminated string using the function `glShaderSource(shdr, text);`
- If the shader is in HTML file, we can get it into application by `getElementById` method
- If the shader is in a file, we can write a reader to convert the file to a string

Adding a Vertex Shader

```
var vertShdr;  
var vertElem = document.getElementById(vertexShaderId);  
  
vertShdr = gl.createShader( gl.VERTEX_SHADER );  
  
gl.shaderSource( vertShdr, vertElem.text );  
gl.compileShader( vertShdr );  
  
// after program object created  
gl.attachShader( program, vertShdr );
```

Shader Reader

- Following code may be a security issue with some browsers if you try to run it locally
 - Cross origin request

```
function getShader( gl, shaderName, type ) {  
    var shader = gl.createShader( type );  
    shaderScript = loadFileAJAX( shaderName );  
    if( !shaderScript ) {  
        alert( "Could not find shader source:"  
            + shaderName );  
    }  
}
```

Precision Declaration

- In GLSL for WebGL we must specify desired precision in fragment shaders
 - Artifact inherited from OpenGL ES
 - ES must run on very simple embedded devices that may not support 32-bit floating point
 - All implementations must support mediump
 - No default for float in fragment shader
- Can use preprocessor directives (`#ifdef`) to check if highp supported and, if not, default to mediump


Pass Through Fragment Shader



```
#ifdef GL_FRAGMENT_SHADER_PRECISION_HIGH
precision highp float;
#else
precision mediump float;
#endif
```

```
varying vec4 fColor;
void main(void) {
    gl_FragColor = fColor;
}
```


연습 문제 (5)

- Drag하여 선분들을 그리시오.





```
File Edit Selection View Go Run Terminal Help drawLines.html - Visual Studio Code
drawPoints.html JS drawPoints.js drawLines.html X JS drawLines.js
C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > drawLines.html > html > body > div > select#lineColor
3 <head>
4 <title>2022 Computer Graphics - Drawing Lines</title>
5
6 <script id="vertex-shader" type="x-shader/x-vertex">
7   attribute vec4 vPosition;
8   attribute vec4 vColor;
9   varying vec4 fColor;
10
11   void main() {
12     fColor = vColor;
13     gl_Position = vPosition;
14   }
15 </script>
16
17 <script id="fragment-shader" type="x-shader/x-fragment">
18   precision mediump float;
19   varying vec4 fColor;
20
21   void main() {
22     gl_FragColor = fColor;
23   }
24 </script>
25
26 <script type="text/javascript" src="../../Common/webgl-utils.js"></script>
27 <script type="text/javascript" src="../../Common/initShaders.js"></script>
28 <script type="text/javascript" src="../../Common/MV.js"></script>
29 <script type="text/javascript" src="drawLines.js"></script>
30 </head>
31 <body>
32   <canvas id="gl-canvas" width="512" height="512">
33     Oops... your browser doesn't support the HTML5 canvas element!
34   </canvas>
35   <div>
36     Line Color: <select id="lineColor">
37       <option value="red">Red</option>
```

C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawLines.js > render

```

1  var gl;
2  var points, colors;
3
4  window.onload = function init() {
5      var canvas = document.getElementById("gl-canvas");
6
7      gl = WebGLUtils.setupWebGL(canvas);
8      if( !gl ) {
9          alert("WebGL isn't available!");
10     }
11
12     points = [];
13     colors = [];
14     var bMouseDown = false;
15
16     canvas.addEventListener("mousedown", function(event) {
17         if (!bMouseDown) {
18             var point = vec2(2 * event.clientX/canvas.width - 1,
19                 2 * (canvas.height - event.clientY) / canvas.height - 1);
20             points.push(point);
21             points.push(point);
22             gl.bindBuffer(gl.ARRAY_BUFFER, bufferId);
23             gl.bufferData(gl.ARRAY_BUFFER, flatten(points), gl.STATIC_DRAW);
24
25             colors.push(currentColor);
26             colors.push(currentColor);
27             gl.bindBuffer(gl.ARRAY_BUFFER, cbufferId);
28             gl.bufferData(gl.ARRAY_BUFFER, flatten(colors), gl.STATIC_DRAW);
29         }
30         bMouseDown = true;
31     });
32     canvas.addEventListener("mouseup", function(event) {
33         bMouseDown = false;
34     });
35     canvas.addEventListener("mousemove", function(event) {

```



drawLines.js - Visual Studio Code

drawPoints.html JS drawPoints.js drawLines.html JS drawLines.js

C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawLines.js > render

```
36     if( bMouseDown ) {
37         var point = vec2(2 * event.clientX/canvas.width - 1,
38             2 * (canvas.height - event.clientY) / canvas.height - 1);
39         points.pop();
40         points.push(point);
41         gl.bindBuffer(gl.ARRAY_BUFFER, bufferId);
42         gl.bufferData(gl.ARRAY_BUFFER, flatten(points), gl.STATIC_DRAW);
43     }
44     render();
45 }
46 });
47
48 // Configure WebGL
49 gl.viewport(0, 0, canvas.width, canvas.height);
50 gl.clearColor(1.0, 1.0, 1.0, 1.0);
51
52 // Load shaders and initialize attribute buffers
53 var program = initShaders(gl, "vertex-shader", "fragment-shader");
54 gl.useProgram(program);
55
56 // Load the data into the GPU
57 var bufferId = gl.createBuffer();
58 gl.bindBuffer(gl.ARRAY_BUFFER, bufferId);
59 gl.bufferData(gl.ARRAY_BUFFER, flatten(points), gl.STATIC_DRAW);
60
61 // Associate our shader variables with our data buffer
62 var vPosition = gl.getAttribLocation(program, "vPosition");
63 gl.vertexAttribPointer(vPosition, 2, gl.FLOAT, false, 0, 0);
64 gl.enableVertexAttribArray(vPosition);
65
66 // Create a buffer object, initialize it, and associate it with
67 // the associated attribute variable in our vertex shader
68 var cbufferId = gl.createBuffer();
69 gl.bindBuffer(gl.ARRAY_BUFFER, cbufferId);
70 gl.bufferData(gl.ARRAY_BUFFER, flatten(colors), gl.STATIC_DRAW);
```

Ln 124, Col 27 Spaces: 4 UTF-8 CRLF JavaScript

3

- render

[illegible][illegible]

```

1  # @param {String} str
2  # @return {String}
3  # Time complexity: O(n)
4  # Space complexity: O(1)
5  #
6  # Example 1:
7  # Input: str = "123456789101112131415"
8  # Output: "123456789101112131415"
9  #
10 # Example 2:
11 # Input: str = "1234567891011121314151617181920"
12 # Output: "1234567891011121314151617181920"
13 #
14 # Example 3:
15 # Input: str = "123456789101112131415161718192021222324252627282930"
16 # Output: "123456789101112131415161718192021222324252627282930"
17 #
18 # Example 4:
19 # Input: str = "123456789101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899100"
20 # Output: "123456789101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899100"
21 #
22 # Example 5:
23 # Input: str = "123456789101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899100101102103104105106107108109110111112113114115116117118119120121122123124125126127128129130131132133134135136137138139140141142143144145146147148149150151152153154155156157158159160161162163164165166167168169170171172173174175176177178179180181182183184185186187188189190191192193194195196197198199200"
24 # Output: "123456789101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899100101102103104105106107108109110111112113114115116117118119120121122123124125126127128129130131132133134135136137138139140141142143144145146147148149150151152153154155156157158159160161162163164165166167168169170171172173174175176177178179180181182183184185186187188189190191192193194195196197198199200"
25 #
26 # Example 6:
27 # Input: str = "123456789101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899100101102103104105106107108109110111112113114115116117118119120121122123124125126127128129130131132133134135136137138139140141142143144145146147148149150151152153154155156157158159160161162163164165166167168169170171172173174175176177178179180181182183184185186187188189190191192193194195196197198199200201202203204205206207208209210211212213214215216217218219220221222223224225226227228229230231232233234235236237238239240241242243244245246247248249250251252253254255256257258259260261262263264265266267268269270271272273274275276277278279280281282283284285286287288289290291292293294295296297298299300"
28 # Output: "123456789101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899100201202203204205206207208209210211212213214215216217218219220221222223224225226227228229230231232233234235236237238239240241242243244245246247248249250251252253254255256257258259260261262263264265266267268269270271272273274275276277278279280281282283284285286287288289290291292293294295296297298299300"
29 #
30 # Example 7:
31 # Input: str = "12345678910111213141516171819202122232425262728293031323334353637383940414243444546474849505152535455565758596061626364656667686970717273747576777879808182838485868788899091929394959697989910010110210310410510610710810911011111211311411511611711811912012112212312412512612712812913013113213313413513613713813914014114214314414514614714814915015115215315415515615715815916016116216316416516616716816917017117217317417517617717817918018118218318418518618718818919019119219319419519619719819920020120220320420520620720820921021121221321421521621721821922022122222322422522622722822923023123223323423523623723823924024124224324424524624724824925025125225325425525625725825926026126226326426526626726826927027127227327427527627727827928028128228328428528628728828929029129229329429529629729829930030130230330430530630730830931031131231331431531631731831932032132232332432532632732832933033133233333433533633733833934034134234334434534634734834935035135235335435535635735835936036136236336436536636736
```

C: > Users > Sun-Jeong Kim > Desktop > CG > Week04 > JS drawLines.js > render

```

98     case "cyan":
99         //gl.uniform4f(fColor, 0.0, 1.0, 1.0, 1.0);
100         currentColor = vec4(0.0, 1.0, 1.0, 1.0);
101         break;
102     case "magenta":
103         //gl.uniform4f(fColor, 1.0, 0.0, 1.0, 1.0);
104         currentColor = vec4(1.0, 0.0, 1.0, 1.0);
105         break;
106     case "gray":
107         //gl.uniform4f(fColor, 0.5, 0.5, 0.5, 1.0);
108         currentColor = vec4(0.5, 0.5, 0.5, 1.0);
109         break;
110     case "black":
111         //gl.uniform4f(fColor, 0.0, 0.0, 0.0, 1.0);
112         currentColor = vec4(0.0, 0.0, 0.0, 1.0);
113         break;
114     }
115
116     //render();
117 }
118
119 render();
120 };
121
122 function render() {
123     gl.clear(gl.COLOR_BUFFER_BIT);
124     gl.drawArrays(gl.LINES, 0, points.length);
125 }
126

```



연습 문제 (6)

- 세 점을 클릭하여 삼각형들을 그리시오.
- "drawTriangles.html"과 "drawTriangles.js"를 제출하시오.
- 결과 스크린샷 이미지도 함께 제출하시오.

