

Python 과학 프로그래밍 기초

7. NumPy (4)

한림대학교 소프트웨어융합대학

박섭형

2021년 1학기

NumPy 다차원 배열의 속성 변경

```
[1]: import numpy as np
      n = np.arange(5)
      print(n.dtype)
```

int32

```
[2]: n[0] = 5
      print(n, n.dtype)
```

[5 1 2 3 4] int32

```
[3]: n[2] = 10.8
      print(n, n.dtype)
```

[5 1 10 3 4] int32

```
[4]: m = n.astype(np.int64)
      print(m, m.dtype)
      print(n, n.dtype)
```

[5 1 10 3 4] int64

[5 1 10 3 4] int32

```
[5]: f = n.astype(np.float64)
      print(f, f.dtype)
```

[5. 1. 10. 3. 4.] float64

```
[6]: c = n.astype(np.complex128)
      print(c, c.dtype)
```

[5.+0.j 1.+0.j 10.+0.j 3.+0.j 4.+0.j] complex128

```
[7]: print(n.dtype)
```

int32

```
[8]: n.flags.writeable = False
      n[0] = 10
```

```
-----
ValueError                                Traceback (most recent call last)
<ipython-input-8-e12f5b469656> in <module>
      1 n.flags.writeable = False
----> 2 n[0] = 10

ValueError: assignment destination is read-only
```

NumPy 다차원 배열 변수와 할당 연산자

```
[9]: import numpy as np
      x = np.arange(5)
      print(x)
      print(id(x))
      x += 1
      print(x)
      print(id(x))
```

```
[0 1 2 3 4]
2352194966912
[1 2 3 4 5]
2352194966912
```

```
[10]: x = np.arange(5)
      print(x)
      print(id(x))
      x = x + 1
      print(x)
      print(id(x))
```

```
[0 1 2 3 4]
2352194911328
[1 2 3 4 5]
2352194911568
```

```
[11]: import numpy as np
      def add1(x):
          x += 1

      a = np.arange(5)
      print(a)
      add1(a)
      print(a)
```

```
[0 1 2 3 4]
[1 2 3 4 5]
```

```
[12]: import numpy as np
      def add2(x):
          x = x + 1

      a = np.arange(5)
      print(a)
      add2(a)
```

```
print(a)
```

```
[0 1 2 3 4]
```

```
[0 1 2 3 4]
```

```
[13]: import numpy as np
def mult1(x):
    x *= 2

a = np.arange(5)
print(a)
mult1(a)
print(a)
```

```
[0 1 2 3 4]
```

```
[0 2 4 6 8]
```

```
[14]: import numpy as np
def mult2(x):
    x = x * 2

a = np.arange(5)
print(a)
mult2(a)
print(a)
```

```
[0 1 2 3 4]
```

```
[0 1 2 3 4]
```

Broadcasting

- Shape이 다른 두 개의 ndarray들을 이용해서 산술 연산을 할 때 numpy가 ndarrays를 처리하는 방법

Shape이 같은 두 ndarray의 산술 연산

- 원소끼리 연산이 이루어짐

```
[15]: a = np.array([1, 2, 3])
      b = np.array([10, 20, 30])
      a + b
```

```
[15]: array([11, 22, 33])
```

```
[16]: a * b
```

```
[16]: array([10, 40, 90])
```

```
[17]: a = np.arange(12).reshape(3,4)
      a
```

```
[17]: array([[ 0,  1,  2,  3],
            [ 4,  5,  6,  7],
            [ 8,  9, 10, 11]])
```

```
[18]: b = np.arange(10, 22).reshape(3,4)
      b
```

```
[18]: array([[10, 11, 12, 13],
            [14, 15, 16, 17],
            [18, 19, 20, 21]])
```

```
[19]: a + b
```

```
[19]: array([[10, 12, 14, 16],
            [18, 20, 22, 24],
            [26, 28, 30, 32]])
```

```
[20]: a = np.array([1, 2, 3])
      b = np.array([1, 2])
      a + b
```

ValueError

Traceback (most recent call last)

<ipython-input-20-f5a67fd89fb2> in <module>

1 a = np.array([1, 2, 3])

2 b = np.array([1, 2])

----> 3 a + b

ValueError: operands could not be broadcast together with shapes (3,) (2,)

ndarray와 상수의 산술 연산

```
[21]: x = np.arange(1,5)
      print(x)
      print(x + 3)
```

[1 2 3 4]

[4 5 6 7]

1	2	3	4	3	3	3	3
---	---	---	---	---	---	---	---

```
[22]: print(x * 3)
```

[3 6 9 12]

```
[23]: print(x / 3)
```

[0.33333333 0.66666667 1. 1.33333333]

```
[24]: x = np.arange(1,7).reshape(2,3)
      print(x + 3)
```

[[4 5 6]

[7 8 9]]

```
[25]: print(3 * x)
```

1	2	3	3	3	3
4	5	6	3	3	3

[[3 6 9]

[12 15 18]]

Shape이 서로 다른 두 ndarray 사이의 산술 연산

axis의 원소의 갯수가 같은 두 ndarray 사이의 산술 연산

```
[26]: a = np.arange(1,7).reshape(2,3)
      b = np.array([[1, 2, 1]])
      print(a + b)
```

```
[[2 4 4]
 [5 7 7]]
```

1	2	3
4	5	6

1	2	1
1	2	1

```
[27]: a = np.arange(1,7).reshape(2,3)
      b = np.array([1, 2, 1])
      print(a + b)
```

```
[[2 4 4]
 [5 7 7]]
```

```
[28]: a = np.arange(1,7).reshape(2,3)
      b = np.array([1, 2])
      print(a + b)
```

```
-----
ValueError                                Traceback (most recent call last)
<ipython-input-28-5a11c48ce658> in <module>
      1 a = np.arange(1,7).reshape(2,3)
      2 b = np.array([1, 2])
----> 3 print(a + b)

ValueError: operands could not be broadcast together with shapes (2,3) (2,)
```

```
[29]: a = np.arange(1,7).reshape(2,3)
      b = np.array([[1], [2]])
      print(a + b)
```

```
[[2 3 4]
 [6 7 8]]
```

1	2	3
4	5	6

1	1	1
2	2	2

```
[30]: a = np.arange(1,7).reshape(2,3)
      b = np.array([[1, 1], [2, 2]])
      print(a + b)
```

```
-----
ValueError                                Traceback (most recent call last)
<ipython-input-30-a8b431da9202> in <module>
      1 a = np.arange(1,7).reshape(2,3)
      2 b = np.array([[1, 1], [2, 2]])
----> 3 print(a + b)

ValueError: operands could not be broadcast together with shapes (2,3) (2,2)
```

```
[31]: a = np.arange(1,9).reshape(2,4)
      b = np.array([[1, 1], [2, 2]])
      print(a + b)
```

```
-----
ValueError                                Traceback (most recent call last)
<ipython-input-31-7f68e1658272> in <module>
      1 a = np.arange(1,9).reshape(2,4)
      2 b = np.array([[1, 1], [2, 2]])
----> 3 print(a + b)
```


ValueError: operands could not be broadcast together with shapes (2,4) (2,2)

```
[32]: a = np.arange(1,25).reshape(2,3,4)
      b = np.array([1, 2, 1, 2])
      print(a + b)
```

```
[[[ 2  4  4  6]
   [ 6  8  8 10]
   [10 12 12 14]]
```

```
[[14 16 16 18]
 [18 20 20 22]
 [22 24 24 26]]]
```

1	2	3	4
5	6	7	8
9	10	11	12

1	2	1	2
1	2	1	2
1	2	1	2

13	14	15	16
17	18	19	20
21	22	23	24

1	2	1	2
1	2	1	2
1	2	1	2

```
[33]: a = np.arange(1, 25).reshape(2,3,4)
      b = np.arange(8).reshape(2,1,4)
      print(a)
      print(b)
      print(a + b)
```

```
[[[ 1  2  3  4]
   [ 5  6  7  8]
```

```
[ 9 10 11 12]]
```

```
[[13 14 15 16]
```

```
 [17 18 19 20]
```

```
 [21 22 23 24]]]
```

```
[[[0 1 2 3]]
```

```
 [[4 5 6 7]]]
```

```
[[[ 1  3  5  7]
```

```
 [ 5  7  9 11]
```

```
 [ 9 11 13 15]]]
```

```
[[17 19 21 23]
```

```
 [21 23 25 27]
```

```
 [25 27 29 31]]]
```

1	2	3	4
5	6	7	8
9	10	11	12

0	1	2	3
0	1	2	3
0	2	2	3

13	14	15	16
17	18	19	20
21	22	23	24

4	5	6	7
4	5	6	7
4	5	6	7

```
[34]: a = np.array([1,2,3]).reshape(3,1)
      b = np.array([1,2,1]).reshape(1,3)
      print(a)
      print(b)
      print(a + b)
```

```
[[1]
```

```
 [2]
```

[3]]

[[1 2 1]]

[[2 3 2]

[3 4 3]

[4 5 4]]

1	1	1
2	2	2
3	3	3

1	2	1
1	2	1
1	2	1