

Java Math class

Java Math class provides several methods to work on math calculations like min(), max(), avg(), sin(), cos(), tan(), round(), ceil(), floor(), abs() etc.

Unlike some of the StrictMath class numeric methods, all implementations of the equivalent function of Math class can't define to return the bit-for-bit same results. This relaxation permits implementation with better-performance where strict reproducibility is not required.

If the size is int or long and the results overflow the range of value, the methods addExact(), subtractExact(), multiplyExact(), and toIntExact() throw an ArithmeticException.

For other arithmetic operations like increment, decrement, divide, absolute value, and negation overflow occur only with a specific minimum or maximum value. It should be checked against the maximum and minimum value as appropriate.

Example 1

```
public class JavaMathExample1
{
    public static void main(String[] args)
    {
        double x = 28;
        double y = 4;

        // return the maximum of two numbers
        System.out.println("Maximum number of x and y is: " + Math.max(x, y));

        // return the square root of y
        System.out.println("Square root of y is: " + Math.sqrt(y));

        //returns 28 power of 4 i.e. 28*28*28*28
        System.out.println("Power of x and y is: " + Math.pow(x, y));

        // return the logarithm of given value
```

```

System.out.println("Logarithm of x is: " + Math.log(x));
System.out.println("Logarithm of y is: " + Math.log(y));

// return the logarithm of given value when base is 10
System.out.println("log10 of x is: " + Math.log10(x));
System.out.println("log10 of y is: " + Math.log10(y));

// return the log of x + 1
System.out.println("log1p of x is: " + Math.log1p(x));

// return a power of 2
System.out.println("exp of a is: " + Math.exp(x));

// return (a power of 2)-1
System.out.println("expm1 of a is: " + Math.expm1(x));
}
}

```

Test it Now

Output:

```

Maximum number of x and y is: 28.0
Square root of y is: 2.0
Power of x and y is: 614656.0
Logarithm of x is: 3.332204510175204
Logarithm of y is: 1.3862943611198906
log10 of x is: 1.4471580313422192
log10 of y is: 0.6020599913279624
log1p of x is: 3.367295829986474
exp of a is: 1.446257064291475E12
expm1 of a is: 1.446257064290475E12

```

Example 2

```
public class JavaMathExample2
{
    public static void main(String[] args)
    {
        double a = 30;

        // converting values to radian
        double b = Math.toRadians(a);

        // return the trigonometric sine of a
        System.out.println("Sine value of a is: " +Math.sin(a));

        // return the trigonometric cosine value of a
        System.out.println("Cosine value of a is: " +Math.cos(a));

        // return the trigonometric tangent value of a
        System.out.println("Tangent value of a is: " +Math.tan(a));

        // return the trigonometric arc sine of a
        System.out.println("Sine value of a is: " +Math.asin(a));

        // return the trigonometric arc cosine value of a
        System.out.println("Cosine value of a is: " +Math.acos(a));

        // return the trigonometric arc tangent value of a
        System.out.println("Tangent value of a is: " +Math.atan(a));

        // return the hyperbolic sine of a
        System.out.println("Sine value of a is: " +Math.sinh(a));

        // return the hyperbolic cosine value of a
```

```
System.out.println("Cosine value of a is: " +Math.cosh(a));

// return the hyperbolic tangent value of a
System.out.println("Tangent value of a is: " +Math.tanh(a));
}
}
```

Test it Now

Output:

```
Sine value of a is: -0.9880316240928618
Cosine value of a is: 0.15425144988758405
Tangent value of a is: -6.405331196646276
Sine value of a is: NaN
Cosine value of a is: NaN
Tangent value of a is: 1.5374753309166493
Sine value of a is: 5.343237290762231E12
Cosine value of a is: 5.343237290762231E12
Tangent value of a is: 1.0
```

Java Math Methods

The **java.lang.Math** class contains various methods for performing basic numeric operations such as the logarithm, cube root, and trigonometric functions etc. The various java math methods are as follows:

Basic Math methods

Method	Description
Math.abs()	It will return the Absolute value of the given value.
Math.max()	It returns the Largest of two values.

<code>Math.min()</code>	It is used to return the Smallest of two values.
<code>Math.round()</code>	It is used to round of the decimal numbers to the nearest value.
<code>Math.sqrt()</code>	It is used to return the square root of a number.
<code>Math.cbrt()</code>	It is used to return the cube root of a number.
<code>Math.pow()</code>	It returns the value of first argument raised to the power to second argument.
<code>Math.signum()</code>	It is used to find the sign of a given value.
<code>Math.ceil()</code>	It is used to find the smallest integer value that is greater than or equal to the argument or mathematical integer.
<code>Math.copySign()</code>	It is used to find the Absolute value of first argument along with sign specified in second argument.
<code>Math.nextAfter()</code>	It is used to return the floating-point number adjacent to the first argument in the direction of the second argument.
<code>Math.nextUp()</code>	It returns the floating-point value adjacent to d in the direction of positive infinity.
<code>Math.nextDown()</code>	It returns the floating-point value adjacent to d in the direction of negative infinity.
<code>Math.floor()</code>	It is used to find the largest integer value which is less than or equal to the argument and is equal to the mathematical integer of a double value.
<code>Math.floorDiv()</code>	It is used to find the largest integer value that is less than or equal to the algebraic quotient.
<code>Math.random()</code>	It returns a double value with a positive sign, greater than or equal to 0.0 and less than 1.0.
<code>Math rint()</code>	It returns the double value that is closest to the given argument and equal to mathematical integer.

<code>Math.hypot()</code>	It returns $\sqrt{x^2 + y^2}$ without intermediate overflow or underflow.
<code>Math.ulp()</code>	It returns the size of an ulp of the argument.
<code>Math.getExponent()</code>	It is used to return the unbiased exponent used in the representation of a value.
<code>Math.IEEEremainder()</code>	It is used to calculate the remainder operation on two arguments as prescribed by the IEEE 754 standard and returns value.
<code>Math.addExact()</code>	It is used to return the sum of its arguments, throwing an exception if the result overflows an int or long.
<code>Math.subtractExact()</code>	It returns the difference of the arguments, throwing an exception if the result overflows an int.
<code>Math.multiplyExact()</code>	It is used to return the product of the arguments, throwing an exception if the result overflows an int or long.
<code>Math.incrementExact()</code>	It returns the argument incremented by one, throwing an exception if the result overflows an int.
<code>Math.decrementExact()</code>	It is used to return the argument decremented by one, throwing an exception if the result overflows an int or long.
<code>Math.negateExact()</code>	It is used to return the negation of the argument, throwing an exception if the result overflows an int or long.
<code>Math.toIntExact()</code>	It returns the value of the long argument, throwing an exception if the value overflows an int.

Logarithmic Math Methods

Method	Description
<code>Math.log()</code>	It returns the natural logarithm of a double value.
<code>Math.log10()</code>	It is used to return the base 10 logarithm of a double value.

<code>Math.log1p()</code>	It returns the natural logarithm of the sum of the argument and 1.
<code>Math.exp()</code>	It returns E raised to the power of a double value, where E is Euler's number and it is approximately equal to 2.71828.
<code>Math.expm1()</code>	It is used to calculate the power of E and subtract one from it.

Trigonometric Math Methods

Method	Description
<code>Math.sin()</code>	It is used to return the trigonometric Sine value of a Given double value.
<code>Math.cos()</code>	It is used to return the trigonometric Cosine value of a Given double value.
<code>Math.tan()</code>	It is used to return the trigonometric Tangent value of a Given double value.
<code>Math.asin()</code>	It is used to return the trigonometric Arc Sine value of a Given double value
<code>Math.acos()</code>	It is used to return the trigonometric Arc Cosine value of a Given double value.
<code>Math.atan()</code>	It is used to return the trigonometric Arc Tangent value of a Given double value.

Hyperbolic Math Methods

Method	Description
<code>Math.sinh()</code>	It is used to return the trigonometric Hyperbolic Cosine value of a Given double value.
<code>Math.cosh()</code>	It is used to return the trigonometric Hyperbolic Sine value of a Given double value.
<code>Math.tanh()</code>	It is used to return the trigonometric Hyperbolic Tangent value of a Given double value.

Angular Math Methods

Method	Description
Math.toDegrees	It is used to convert the specified Radians angle to equivalent angle measured in Degrees.
Math.toRadians	It is used to convert the specified Degrees angle to equivalent angle measured in Radians.

[← Prev](#)

[Next →](#)

 [For Videos Join Our Youtube Channel: Join Now](#)


Feedback

- Send your Feedback to feedback@javatpoint.com

Help Others, Please Share




Learn Latest Tutorials

 [Splunk tutorial](#)
Splunk

 [SPSS tutorial](#)
SPSS

 [Swagger tutorial](#)
Swagger

 [T-SQL tutorial](#)
Transact-SQL

 [Tumblr tutorial](#)


 [React tutorial](#)


 [Regex tutorial](#)


Tumblr

ReactJS

Regex

 Reinforcement
learning tutorial
Reinforcement
Learning


 R Programming
tutorial
R Programming


 RxJS tutorial
RxJS

 React Native
tutorial
React Native

 Python Design
Patterns
Python Design
Patterns


 Python Pillow
tutorial
Python Pillow


 Python Turtle
tutorial
Python Turtle

 Keras tutorial
Keras

Preparation

 Aptitude
Aptitude

 Logical
Reasoning
Reasoning

 Verbal Ability
Verbal Ability


 Interview
Questions
Interview Questions


 Company
Interview
Questions
Company Questions


Trending Technologies

 Artificial
Intelligence
Artificial
Intelligence

 AWS Tutorial
AWS

 Selenium
tutorial
Selenium


 Cloud
Computing
Cloud Computing




Hadoop tutorial
Hadoop



ReactJS
Tutorial
ReactJS



Data Science
Tutorial
Data Science




Angular 7
Tutorial
Angular 7



Blockchain
Tutorial
Blockchain



Git Tutorial
Git



Machine
Learning Tutorial
Machine Learning




DevOps
Tutorial
DevOps


B.Tech / MCA




DBMS tutorial
DBMS




Data Structures
tutorial
Data Structures



DAA tutorial
DAA



Operating
System
Operating System




Computer
Network tutorial
Computer Network




Compiler
Design tutorial
Compiler Design



Computer
Organization and
Architecture
Computer
Organization




Discrete
Mathematics
Tutorial
Discrete
Mathematics




Ethical Hacking
Ethical Hacking



Computer
Graphics Tutorial
Computer Graphics



Software
Engineering
Software
Engineering




html tutorial
Web Technology




Cyber Security
tutorial
Cyber Security



Automata
Tutorial
Automata



C Language
tutorial
C Programming



C++ tutorial
C++



Java tutorial

Java



.Net
Framework
tutorial

.Net



Python tutorial
Python



List of
Programs
Programs



Control
Systems tutorial
Control System



Data Mining
Tutorial
Data Mining



Data
Warehouse
Tutorial
Data Warehouse