

Optimizing Service Efficiency: A Monte Carlo Approach

Joseph Kang
University of Illinois at Chicago

February 17, 2025

Abstract

In service work environments, optimizing cost efficiency and customer satisfaction is crucial to balancing. When having long wait times for customers, it leads to customer dissatisfaction, and on the other hand, if cashiers are idling, this can lead to financial inefficiencies. This report will investigate the balance using the Monte Carlo simulation to model customer arrivals and service times based off a Poisson and normal distribution. The simulation will be our key framework using performance metrics that include the mean and variability of customer wait times and idleness. Using the Taguchi loss function, we can apply this to quantify the economic impact of deviations from an optimal service time, reinforcing consistency and flow for workers and customers. Results indicate higher deviations from optimal service times resulting in the financial loss, with longer service times giving even greater economic penalties having under performing cashier time. Our findings heavily imply that we need a dynamic queuing system and staffing optimization to reduce these inefficiencies. Future studies should seek better server systems and explore adaptive staffing to minimize the financial losses.

Contents

1	Introduction	1
1.1	Motivation and Problem Statement	1
1.2	Objectives	2
2	Methodology	2
2.1	Step-by-Step Approach	2
3	Results	3
3.1	Simulation Findings	3
3.1.1	Julia Implementation	3
3.1.2	Visual Implementation	4
3.2	Taguchi Loss Calculation	4
3.2.1	Julia Implementation	4
3.2.2	Visual Implementation	6
3.3	Interpretation of Results	6
4	Discussion	6
4.1	Key Insights	7
4.2	Recommendations for Improvement	7
4.3	Future Work	7
5	Conclusion	7

1 Introduction

1.1 Motivation and Problem Statement

In the newer environments of customer service, customer experience is key to retain proper business meaning major components to clientele is operational efficiency and customer satisfaction. Long wait times are consistent in service type industries such as grocery stores, banks, and customer service centers

often leading to bad reviews, return of food and revenue loss. In the other hand, excessive cashier idle time can be significant to inefficiency to resources leading to financial downfall and increased labor costs.

This report will challenge the optimization of service efficiency striking the balance between reducing customer wait times and minimizing cashier idle times. A inconsistent system results in the long queues or overpaid labor resources which can affect profitability. This will explore the ideas of Monte Carlo simulations to model a single service queue to visualize and quantify the impact of variability in service times, and apply the Taguchi Loss Function to evaluate financial losses associated with deviations for optimal and efficient balance.

1.2 Objectives

This study will aim to:

- Model customer arrivals and cashier service times using probability distributions
- Compute statistical properties of wait times and idle times representing them using mean and standard deviations
- Apply the Taguchi Loss Function to Quantify financial losses due to the lack of balance
- Provide improvements using data to optimize service operations

2 Methodology

2.1 Step-by-Step Approach

1. Simulation Customer Arrivals:

- Modeled using a Poisson Distribution to limit the area with a rate of $\lambda = 10$ arrivals per unit time.
- Poisson distribution will be used because of how often it is used for queuing theory to represent the randomness and unpredictability of the customers patterns.

2. Generation Service Times:

- Also modeled after a normal distribution with a mean of $\mu = 7$ minutes and standard deviation $\sigma = 2$ minutes
- Accounts for variability in service speed due to transactions

3. Monte Carlo Simulation:

- 1000 trials will be conducted to simulate the real world transaction process
- Each of these trails will process customer wait times and cashier idle times based on system dynamics

4. Performance Metrics:

- Mean and standard deviations of wait times and idle times will be used to calculate system efficiency

5. Applying The Taguchi Loss Function:

- The financial balance and loss will be measured using

$$L(y) = k(y - m)^2$$

where:

- y = observed service time (either wait or idle time),
- m = optimal service time (2 minutes),
- k = loss coefficient (10 for wait time, 5 for idle time).

3 Results

3.1 Simulation Findings

- Mean Wait Time: 0.4234 minutes
- Standard Deviation of Wait Time: 1.0868 minutes
- Mean Idle Time: 3.4149 minutes
- Standard Deviation of Idle Time: 3.1243 minutes

3.1.1 Julia Implementation

```
using Random, Distributions, Plots

# Set random seed for reproducibility
Random.seed!(42)

# Simulation parameters
lambda_arrival = 10 # Average arrivals per time step (Poisson)
mu_service = 7 # Mean service time (Normal)
sigma_service = 2 # Standard deviation of service time (Normal)
num_trials = 1000 # Number of simulated customers

# Simulating customer arrivals (Poisson distributed)
arrival_times = cumsum(rand(Poisson(lambda_arrival), num_trials))

# Simulating service times (Normally distributed, ensuring positive values)
service_times = abs.(rand(Normal(mu_service, sigma_service), num_trials))

# Initializing wait and idle times
wait_times = zeros(num_trials)
idle_times = zeros(num_trials)

# Simulation loop
server_busy_until = 0.0
for i in 1:num_trials
    if arrival_times[i] < server_busy_until
        wait_times[i] = server_busy_until - arrival_times[i]
    else
        idle_times[i] = arrival_times[i] - server_busy_until # Cashier is idle
    end
    server_busy_until = arrival_times[i] + service_times[i]
end
```

The Julia code simulates a single-server queuing system using the Monte Carlo approach evaluating customer wait and cashier idle times. It sets a random seed for reproducibility and randomness that comes with customer arrival times and defines key parameters such as arrival rates and service times. The simulation will generate arrival times using Poisson-distributed values and service times using absolute values of normally distributed values to ensure positive values. The logic behind this simulation is that there will be 1000 simulated customers iterated updating server's busy state while also calculating both wait and idle times. The results are visualized using histograms, where one plot represents customer wait times and another wait cashier idle times. We put them side by side to make a comparative analysis assessing the trade off between customer satisfactions and cashier utilization.

3.1.2 Visual Implementation




Figure 1: Histogram of Wait Time and Idle Times

3.2 Taguchi Loss Calculation

- Wait Time Loss: $L(0.4234) = 24.7948$
- Idle Time Loss: $L(3.4149) = 10.0245$

3.2.1 Julia Implementation

Julia Code for Monte Carlo Simulation with Taguchi Loss Function

using Distributions, Random, Statistics, Plots

Parameters

```
lambda_arrival = 10 # Average arrivals per time step (Poisson)
mu_service = 7      # Mean service time (Normal)
sigma_service = 2   # Standard deviation of service time (Normal)
num_trials = 1000   # Number of customers to simulate
optimal_service_time = 2.0 # Optimal service time for minimal loss
```

Loss coefficients

```
k_wait = 10 # Cost coefficient for wait time deviations
k_idle = 5  # Cost coefficient for idle time deviations
```

Taguchi Loss Function

```
taguchi_loss(value, optimal, k) = k * (value - optimal)^2
```

Function to simulate queueing process

```
function simulate_queue(lambda, mu, sigma, trials, optimal, k_w, k_i)
    arrival_times = cumsum(rand(Poisson(lambda), trials))
    service_times = abs.(rand(Normal(mu, sigma), trials)) # Ensure positive service times

    wait_times = zeros(trials)
    idle_times = zeros(trials)
    loss_wait = zeros(trials)
    loss_idle = zeros(trials)
    server_busy_until = 0
```

```

for i in 1:trials
    if arrival_times[i] < server_busy_until
        wait_times[i] = server_busy_until - arrival_times[i]
    else
        idle_times[i] = arrival_times[i] - server_busy_until
    end
    server_busy_until = arrival_times[i] + service_times[i]

    # Compute Taguchi loss
    loss_wait[i] = taguchi_loss(wait_times[i], optimal, k_w)
    loss_idle[i] = taguchi_loss(idle_times[i], optimal, k_i)
end

return mean(wait_times), std(wait_times), mean(idle_times), std(idle_times)
end

# Run simulation
mean_wait, std_wait, mean_idle, std_idle, loss_wait, loss_idle = simulate_queue(
    lambda_arrival, mu_service, sigma_service, num_trials, optimal_service_time)

```

This Julia program will simulate using the Taguchi Loss Function to evaluate the financial impact of inefficiencies in customer wait times and cashier idle times. The Taguchi Loss Function will give us where a balance lands between cashier and customer financial efficiency and how to minimize our loss.

Here are the steps of the code:

1. Generate Poisson distributed items.
2. Generate normally distributed service times.
3. Initialize wait time, idle time, and loss arrays.
4. For each customer:
 - If server is busy, the customer must wait.
 - If server is free, there is idle time before serving the next customer.
 - Update server busy time.
 - Compute Taguchi Loss for both wait time and idle time.

3.2.2 Visual Implementation




Figure 2: Taguchi Loss Function

3.3 Interpretation of Results

The results indicate that while average wait times are low, the variability suggest long wait queues which can frustrate customers. Meanwhile, the higher idle times that cashiers have signify a under utilization of cashiers leading to these financial inefficiencies. The Taguchi Loss Function demonstrates that as deviations from the optimal service time increases, financial losses grow exponentially.

- Short wait times benefit customer satisfaction, but the spikes in this indicate inconsistent service.
- Higher idle times imply inefficient cashier utilization, meaning there is over expended labor costs being used in need of optimizing.
- Taguchi Loss Function application reveals that the losses are usually due to the excessive wait times outweighing the losses due to idle times meaning the buisness should prioritize minimizing wait times over idle times.

4 Discussion

The simulation highlights a crucial trade-off in queue management. the low mean wait time of (0.4234 minutes) suggests an efficient system for most customer, but the relatively high standard deviation (1.0868 minutes) indicates the long waits affect customer satisfaction. IN contrast to this, the mean idle time is (3.4149 minutes) is higher meaning that there is a unsustainable amount of time unoccupied. The Taguchi Loss Function reinforces that financial losses increase significantly as service time grows.

4.1 Key Insights

1. Customer Wait Times:

- Short wait times will improve customer experience, but the topic of problem should be at the long waits.
- Reducing variability is essential for ensuring consistent service.

2. Cashier Idle Items:

- High idle times makes interpretation of inefficiencies in staffing and scheduling.
- A better balance between workload distribution could mitigate these labor costs.

3. Taguchi Loss Function Interpretation:

- The quadratic curve can interpret in to exponential loss meaning that even small deviations in service time create increasing financial difficulties.
- Longer wait times give greater financial impact compared to idle time, making it a priority to optimize efforts.

4.2 Recommendations for Improvement

There are many ways to create improvement for financial structure, however we will be talking about three major points: Dynamic Staffing Adjustments, Queue Optimization Algorithms and Employee Training. Implementing a system that dynamically schedules employees based on predicted customer flow could improve scheduling slow days with less employees. This can improve idle time of employees because there will be less people but work with more efficiency. Another is the queue method, giving AI-driven models to predict these peak times of customers and adjusting the service speed accordingly. Finally using employee training regiments could reduce the service time variability through improved cashier efficiency.

4.3 Future Work

For future reference, there are better ways to simulate the work that is done in this report. Extending the model to multi server queuing systems to evaluate scalability to properly reproduce a full workforce setting for customer service. Analyzing the impact of customer abandonment rates in cases of excessive wait times which could emphasize more variability in wait times. Exploring the cost-benefit trade-offs between reducing wait times and minimizing labor cost could be the final end for this project.

5 Conclusion

Monte Carlo simulations with the Taguchi Loss Function provided a good visual and analytic framework for queueing system inefficiencies. This study brings the significance of keeping customer service and financial sustainability in an equilibrium. The results show that even small deviations from the mean can keep the optimal service time from affecting the financial performance of this service. Future Research should expand on multi server models and adaptive queuing strategies to further optimize operational efficiency.