Publish Checkstyle a	marysis results						
Checkstyle results	**/target/checkstyle-result.xml						
	Fileset includes setting that specifies the generated raw CheckStyle XML report files, such as **/checkstyle-result.xml. Basedir of the fileset is the workspace root. If no value is set, then the default **/checkstyle-result.xml is used. Be sure not to include any non-report files into this pattern.						
Run always							
	By default, this plug-in runs only for stable or unstable builds, but not for failed builds. If this plug-in should run even for failed builds then activate this check box.						
Health thresholds	100% 10		<i>\$</i> 0	% 200			
	Configure the thresholds for the build health. If the actual number of warnings is between the provided thresholds, then the build health is interpolated.						
Health priorities	Only priority high O Priorities high and normal O All priorities						
	Determines	which warning priorit	ies should be considered v	when evaluating the build health			
Status thresholds	A	All priorities	Priority high	Priority normal	Priority low		
	O Total	200					
	O New	50					
		500					
	O New	100					
			gs exceeds one of these ti	nresholds then a build is conside	ered as unstable or failed,		
Use delta for new warr	respectively.						
Default Foresting	reference bu then the nur build. This v	uild. This may lead to mber of new warning: vill find all new warnir	wrong results if you have is calculated by an asym igs even if the number of	both fixed and new warnings in metric set difference of the warn	ernings of the current build from the a build. If the checkbox is not set, nings in the current and reference wever, sometimes false positives will stc.)		
Default Encoding	Default enco	oding when parsing o	showing files. Leave this	field empty to use the default e	ncoding of the platform.		
Trend graph			You can define the default values for the trend graph in a separate view.				