Discrete Constrained Interaction Principle (DCIP)

Why complex systems optimize via modular, block-sparse interactions

(A reference-conditions paper: what the claim means, where it applies, and how to model it)

Kevin T. N.
jkdkr2439@gmail.com

February 2026

Abstract

Many domains report the same structural pattern: as systems scale, performance improves when the system is decomposed into modules with controlled interfaces. This paper formalizes that pattern as a reference-indexed principle for bounded information-processing systems. We model a system as interacting processes with a coupling matrix. We define three costs that typically dominate at scale: coordination cost, error-propagation cost, and abstraction-induced information loss. We then state and justify a theorem-level claim: under finite capacity constraints and nontrivial interaction costs, optimal (or evolutionarily stable) interaction structures are approximately block-sparse (modular), with a domain-dependent optimal granularity. We provide spectral and graph-theoretic interpretations, dynamic (time) formulations, and concrete examples across software, biology, neuroscience, economics, policy, and culture. We close with scope boundaries: DCIP is an intersubjective structural model (not an absolute metaphysical claim about reality).

Contents

1 Reference Conditions (SEF-style): what exactly is being claimed? 2
- 1.1 Reference frame and scope . . . 2
- 1.2 Core intuition (plain language) . . . 2

2 System Model 3
- 2.1 Processes and coupling . . . 3
- 2.2 Interaction complexity . . . 3

3 Costs: coordination, error propagation, and abstraction loss 3
- 3.1 Coordination cost . . . 3
- 3.2 Error propagation cost (spectral view) . . . 3
- 3.3 Abstraction / information loss (epistemic entropy proxy) . . . 3

4 Objective: performance under bounded resources 4
- 4.1 Utility and constraints . . . 4

5 The DCIP theorem-level claim 4
- 5.1 Block-sparse optimality (informal-to-formal) . . . 4
- 5.2 Corollaries . . . 5

6 Graph-theoretic and spectral formulations (the "all options" upgrade) 5
- 6.1 Graph cut view . . . 5
- 6.2 Modularity score (Newman–Girvan proxy) . . . 5
- 6.3 Spectral radius and stability . . . 5

7 Time dynamics: why modularity emerges (not just designed) **5**

8 Algorithmic recipe: estimating the optimal modularity level **6**

9 Domain examples: same structure, different semantics **6**
9.1 Software systems . . . 6
9.2 Systems biology . . . 6
9.3 Neuroscience . . . 6
9.4 Economics and organizations . . . 6
9.5 Public policy and governance . . . 7
9.6 Culture (preservation & development) . . . 7

10 Scope boundaries and an R3-facing conjecture (careful) **7**
10.1 What DCIP is (and is not) . . . 7
10.2 Conjecture (optional, explicitly marked) . . . 7

11 Practical checklist (turn the principle into an engineering tool) **7**

A Appendix A: A more explicit "symbolic core" statement **8**

B Appendix B: Interference as "uncontrolled shared variables" **8**

C Appendix C: Minimal bibliography (optional) **8**

1 Reference Conditions (SEF-style): what exactly is being claimed?

1.1 Reference frame and scope

Definition 1 (Reference Conditions)**.** We consider systems that satisfy:

1. **Bounded capacity:** finite compute/energy/attention budget.
2. **Distributed processing:** multiple processes/agents/components with local state.
3. **Structured interaction:** components influence one another through channels (edges) that can be strengthened, weakened, or constrained.

Call this class $\mathfrak{S}_{\text{bounded}}$.

Remark 1 (Stratum discipline)*.* DCIP is a *model about accessible structure* (shared, operational, intersubjective). It does *not* claim an ultimate ontological fact about reality-in-itself. Any extension beyond $\mathfrak{S}_{\text{bounded}}$ must be stated as conjecture with extra assumptions.

1.2 Core intuition (plain language)

When many processes are tightly entangled, each one must spend resources handling interference, debugging, and coordination. Modular boundaries and standardized interfaces reduce uncontrolled cross-talk, isolate faults, stabilize outputs, and improve scalability. But over-modularization increases interface overhead and can destroy global coherence. Therefore an optimal granularity typically exists.

2 System Model

2.1 Processes and coupling

Let S contain n processes $P_1, \ldots, P_n$. Each process has input-output behavior

$$P_i : X_i \to Y_i,$$

and can influence others through couplings.

Definition 2 (Coupling graph and matrix)**.** Represent the system by a directed weighted graph $G = (\mathcal{V}, \mathcal{E}, \boldsymbol{W})$ with $\mathcal{V} = \{1, \ldots, n\}$ and weights $w_{ij} \geq 0$. The coupling matrix is $\boldsymbol{C} = [c_{ij}]$ where $c_{ij} = w_{ij}$ measures the strength by which output of i influences input of j.

2.2 Interaction complexity

A simple proxy for total interaction load is the weighted edge mass:

$$I(\boldsymbol{C}) \coloneqq \sum_{i \neq j} c_{ij} = \|\boldsymbol{C} - \operatorname{diag}(\boldsymbol{C})\|_1 .$$

Dense coupling implies $I(\boldsymbol{C})$ grows as $\mathcal{O}(n^2)$ under naive scaling.

3 Costs: coordination, error propagation, and abstraction loss

3.1 Coordination cost

Definition 3 (Coordination cost)**.** Let

$$E_{\text{coord}}(\boldsymbol{C}) \coloneqq \alpha\, I(\boldsymbol{C})$$

for some $\alpha > 0$. This captures time/energy spent on communication, synchronization, negotiation, and cross-dependency management.

3.2 Error propagation cost (spectral view)

Coupling causes disturbances to spread. A standard control/graph proxy for amplification is the spectral radius $\rho(\boldsymbol{C})$ (largest magnitude eigenvalue).

Definition 4 (Error propagation cost)**.** Define

$$E_{\text{err}}(\boldsymbol{C}) \coloneqq \beta\, \phi(\rho(\boldsymbol{C})),$$

where $\beta > 0$ and ϕ is increasing, e.g. $\phi(u) = \frac{u}{1-u}$ for $u < 1$, or $\phi(u) = u$ as a linear proxy.

Remark 2 (Why $\rho(\boldsymbol{C})$?)*.* In linearized dynamics $z_{t+1} = \boldsymbol{C} z_t + \eta_t$, the growth rate of disturbances is governed by $\rho(\boldsymbol{C})$. Making $\boldsymbol{C}$ block-sparse typically reduces long-range amplification paths.

3.3 Abstraction / information loss (epistemic entropy proxy)

Modularization forces coarse-graining: modules summarize internal microstates for the outside world.

Definition 5 (Abstraction loss)**.** Let X denote the system microstate and Z the coarse-grained state exposed through module interfaces (APIs, protocols, role boundaries, etc.). Define abstraction loss

$$EE(\mathcal{P}) \coloneqq H(X \mid Z),$$

where $\mathcal{P}$ is the partition into modules inducing the mapping $X \mapsto Z$.

Remark 3*.* This term penalizes destroying global coherence by over-partitioning. It formalizes the intuition: "split too much and you lose the whole." In practice one may substitute measurable proxies (prediction error, mutual information loss, interface mismatch rates).

4 Objective: performance under bounded resources

4.1 Utility and constraints

Let $F(\boldsymbol{C})$ be task performance (throughput, accuracy, adaptability, utility). Consider:

$$\max_{\boldsymbol{C},\mathcal{P}} \quad \mathcal{U}(\boldsymbol{C},\mathcal{P}) \coloneqq F(\boldsymbol{C}) - \lambda E_{\text{coord}}(\boldsymbol{C}) - \mu E_{\text{err}}(\boldsymbol{C}) - \eta EE(\mathcal{P}) - \gamma E_{\text{iface}}(\mathcal{P}),$$

where $E_{\text{iface}}(\mathcal{P})$ is interface overhead (standards, translation layers, meetings, API maintenance), typically increasing with number of modules and interface complexity.

Alternatively, as a constraint:

$$E_{\text{coord}}(\boldsymbol{C}) + E_{\text{err}}(\boldsymbol{C}) + EE(\mathcal{P}) + E_{\text{iface}}(\mathcal{P}) \leq K,$$

where $K < \infty$ is the capacity bound.

Assumption 1 (Finite capacity)**.** The system has bounded resources $K < \infty$. Without this, "keep everything fully coupled" may not be penalized.

5 The DCIP theorem-level claim

5.1 Block-sparse optimality (informal-to-formal)

We now state a theorem capturing the principle.

Definition 6 (Block-sparse / modular coupling)**.** A coupling matrix $\boldsymbol{C}$ is *block-sparse* w.r.t. a partition $\mathcal{P} = \{M_1, \ldots, M_k\}$ if most weight concentrates within blocks:

$$\sum_{a \neq b} \sum_{i \in M_a,\ j \in M_b} c_{ij} \ll \sum_{a} \sum_{i \in M_a,\ j \in M_a} c_{ij}.$$

Theorem 1 (Discrete Constrained Interaction Theorem (DCIT))**.** *Consider any $S \in \mathfrak{S}_{bounded}$. Suppose:*

1. *$E_{coord}(\boldsymbol{C})$ increases with total cross-coupling mass $I(\boldsymbol{C})$.*
2. *$E_{err}(\boldsymbol{C})$ increases with long-range amplification (e.g. $\rho(\boldsymbol{C})$).*
3. *$EE(\mathcal{P}) + E_{iface}(\mathcal{P})$ increases when partitioning becomes too fine (over-modularization).*
4. *$F(\boldsymbol{C})$ is nontrivial (requires some coupling; the optimum is not the empty graph).*

Then, for any optimum (or stable local optimum) $(\boldsymbol{C}^\star, \mathcal{P}^\star)$ of the bounded optimization problem, $\boldsymbol{C}^\star$ is approximately block-sparse with respect to $\mathcal{P}^\star$, and $\mathcal{P}^\star$ has an interior optimum granularity $k^\star$ (neither $k = 1$ nor $k = n$) whenever interface overhead and abstraction loss are non-negligible.

Proof sketch (structural, not measure-theoretic). High cross-coupling simultaneously increases coordination load (more edges to manage) and increases error amplification paths (more feedback loops and long-range dependencies). Reducing inter-block coupling decreases both costs but sacrifices some performance. Over-partitioning reduces coupling costs further but increases abstraction/interface penalties because global dependencies must be reconstructed via more interfaces and weaker summaries. Under finite capacity K, the trade-off yields an interior optimum where inter-block coupling is suppressed (block sparsity) while intra-block coupling remains strong enough to support performance. Formalizations can be made via Lagrangian relaxation with sparsity-inducing penalties on inter-block edges and a convex (or quasi-convex) interface cost in k. □

5.2 Corollaries

Corollary 1 (Optimal granularity exists)**.** *If $E_{iface}(\mathcal{P})$ grows at least linearly in module count k and $EE(\mathcal{P})$ increases beyond some granularity threshold, then there exists $k^\star \in \{2, \dots, n-1\}$ that locally maximizes $\mathcal{U}$.*

Corollary 2 (Fault containment)**.** *If $\boldsymbol{C}$ is block-sparse and inter-block couplings are bounded by δ, then disturbance propagation from one module to another is bounded by a function of δ and the block spectral radii, implying improved robustness compared to dense coupling.*

6 Graph-theoretic and spectral formulations (the "all options" upgrade)

6.1 Graph cut view

Let $\mathcal{P}$ be a partition. Define the *inter-module cut weight*:

$$\mathrm{Cut}(\boldsymbol{C}, \mathcal{P}) \coloneqq \sum_{a \neq b} \sum_{i \in M_a,\ j \in M_b} c_{ij}.$$

Many modularity objectives minimize Cut subject to constraints on module sizes.

6.2 Modularity score (Newman–Girvan proxy)

Define undirected weights $w_{ij}^{(u)} = c_{ij} + c_{ji}$. Then modularity:

$$Q(\mathcal{P}) \coloneqq \frac{1}{2m} \sum_{i,j} \left(w_{ij}^{(u)} - \frac{d_i d_j}{2m} \right) \mathbf{1}\{i, j \text{ in same module}\},$$

with $d_i = \sum_j w_{ij}^{(u)}$, $2m = \sum_i d_i$. High Q indicates block structure. DCIP predicts high-Q structures emerge under bounded optimization.

6.3 Spectral radius and stability

For linearized dynamics $z_{t+1} = \boldsymbol{C} z_t$, stability requires $\rho(\boldsymbol{C}) < 1$. Dense cross-coupling tends to increase ρ unless carefully tuned; block-sparse structure reduces uncontrolled feedback.

7 Time dynamics: why modularity emerges (not just designed)

We can model structural adaptation as gradient flow on a cost landscape.

Proposition 1 (Modularity as attractor under constrained adaptation)**.** *Let coupling adapt via*

$$\frac{d\boldsymbol{C}}{dt} = -\nabla_{\boldsymbol{C}} \Big(E_{coord}(\boldsymbol{C}) + E_{err}(\boldsymbol{C}) \Big) - \nabla_{\boldsymbol{C}} R(\boldsymbol{C}, \mathcal{P}) + noise,$$

where R is a regularizer that penalizes inter-block coupling (e.g. group sparsity) and the dynamics are projected onto feasible sets (capacity constraints, nonnegativity). Then, for broad classes of R, stationary points are block-sparse with respect to an emergent partition $\mathcal{P}$.

Remark 4. This is the "designed vs evolved" bridge: if the environment penalizes interference and coordination overhead, systems that survive tend to discover modular boundaries.

8 Algorithmic recipe: estimating the optimal modularity level

Algorithm 1: Estimate optimal granularity $k^\star$ and a block-sparse coupling structure

Input: Observed interaction data, candidate partitions $\mathcal{P}_k$ for $k = 1, \ldots, k_{\max}$, capacity bound K

Output: Estimated $k^\star$, partition $\mathcal{P}^\star$, coupling $\boldsymbol{C}^\star$

```
for k = 1 to k_max do                                   // scan granularity
    Construct partition candidate P_k (e.g. spectral clustering / community detection)
    Fit coupling C_k constrained by interfaces implied by P_k
    Compute costs E_coord(C_k), E_err(C_k), EE(P_k), E_iface(P_k)
    if E_coord + E_err + EE + E_iface ≤ K then
        Score utility U_k
```

Return $k^\star = \arg\max_k \mathcal{U}_k$, with $\mathcal{P}^\star = \mathcal{P}_{k^\star}$ and $\boldsymbol{C}^\star = \boldsymbol{C}_{k^\star}$

9 Domain examples: same structure, different semantics

9.1 Software systems

Processes: services/components. **Coupling:** shared databases, internal calls, implicit dependencies.
Dense coupling failure mode: a small schema change breaks multiple subsystems; debugging cost explodes.
Block-sparse solution: microservices / modular monolith with clean interfaces (APIs), contract tests, versioning.
Granularity trade-off: too many services increase deployment/observability overhead (interface cost).

9.2 Systems biology

Processes: biochemical pathways, organ functions. **Coupling:** signaling molecules, feedback loops.
Dense coupling failure mode: systemic cascade from local perturbation.
Block-sparse solution: compartmentalization (membranes), organs with controlled interfaces (blood/nerve signals).
Granularity trade-off: too much compartmentalization slows global coordination.

9.3 Neuroscience

Processes: functional networks (vision, motor, language).
Coupling: synaptic connectivity, long-range tracts.
Block-sparse solution: modular brain networks with hubs; strong intra-network coherence + controlled inter-network routing.
Trade-off: excessive segregation reduces integration (abstraction/interface penalties).

9.4 Economics and organizations

Processes: production tasks, teams, institutions.
Coupling: approvals, shared resources, cross-team dependencies.
Dense coupling failure mode: coordination overhead; one team's delay blocks many others.
Block-sparse solution: specialization, clear ownership, standardized contracts, modular supply chains.
Trade-off: too many silos create misalignment and duplication.

9.5 Public policy and governance

Processes: state agencies, market actors, civil society.
Coupling: regulation, incentives, data-sharing, procurement.
Dense coupling failure mode: unclear roles, overlapping authority, "everyone touches everything" causing waste.
Block-sparse solution: partition responsibilities + shared protocols (standards, audits, KPIs) + escalation paths.
Trade-off: over-fragmentation increases bureaucracy and slows response.

9.6 Culture (preservation & development)

Processes: communities of practice, creators, distributors, educators.
Coupling: who influences what (market pressures, institutional rules, community norms).
Block-sparse solution: protect a stable core (techniques, meanings, standards) while allowing form innovation through explicit "interfaces" (translation, formats, storytelling, productization).
Trade-off: too much fragmentation = loss of shared coherence; too much coupling = innovation suffocates.

10 Scope boundaries and an R3-facing conjecture (careful)

10.1 What DCIP is (and is not)

- DCIP is a **structural principle** about $\mathfrak{S}_{\text{bounded}}$: bounded, distributed, interacting systems.
- DCIP is **not** a claim that "reality must be discrete" in an absolute metaphysical sense.
- DCIP can still *suggest* why discreteness appears broadly: bounded interaction + robustness pressures favor modular discretization.

10.2 Conjecture (optional, explicitly marked)

Proposition 2 (Conjecture: Discreteness bias under survivability constraints)**.** *If a broad class of physical and social systems are subject to survivability constraints that penalize uncontrolled amplification and coordination blow-up, then emergent modular discretization becomes a generic attractor across scales.*

Remark 5. This conjecture is intentionally weaker than "the universe is discrete." It claims a *selection bias*: systems that persist tend to be modular/discrete in their effective organization.

11 Practical checklist (turn the principle into an engineering tool)

Given a target system, ask:

1. What are the processes P_i? What are the true interfaces?
2. Where is coupling dense? Which couplings are *necessary* for performance?
3. Where do errors cascade? What are the biggest amplification loops?
4. What is the capacity bound K (compute/energy/attention/budget)?
5. What is the current granularity k? Is interface overhead dominating?
6. Can we redesign toward block-sparse coupling with explicit protocols?

A Appendix A: A more explicit "symbolic core" statement

Definition 7 (DCIP (compact symbolic form))**.** Let $S \in \mathfrak{S}_{\text{bounded}}$ with coupling matrix $\boldsymbol{C}$ and partition $\mathcal{P}$. Define

$$\mathcal{L}(\boldsymbol{C}, \mathcal{P}) = \lambda \left\| \boldsymbol{C} - \operatorname{diag}(\boldsymbol{C}) \right\|_1 + \mu \phi(\rho(\boldsymbol{C})) + \eta H(X \mid Z_{\mathcal{P}}) + \gamma E_{\text{iface}}(\mathcal{P}).$$

Under non-degenerate performance constraints $F(\boldsymbol{C}) \geq F_{\min}$ and finite budget K,

$$(\boldsymbol{C}^\star, \mathcal{P}^\star) = \arg\min_{\boldsymbol{C}, \mathcal{P}} \ \mathcal{L}(\boldsymbol{C}, \mathcal{P}) \quad \text{s.t.} \quad F(\boldsymbol{C}) \geq F_{\min}, \quad \mathcal{L}(\boldsymbol{C}, \mathcal{P}) \leq K,$$

yields $\boldsymbol{C}^\star$ approximately block-sparse and $\mathcal{P}^\star$ with an interior optimal $k^\star$.

B Appendix B: Interference as "uncontrolled shared variables"

An equivalent view: coupling is high when processes share mutable state. Replace $\boldsymbol{C}$ with a bipartite graph between processes and shared variables. Modularization corresponds to minimizing cross-module shared-variable incidence while preserving required dependencies.

C Appendix C: Minimal bibliography (optional)

References

[1] H. A. Simon, *Designing Organizations for an Information-Rich World*, 1971.

[2] K. J. S. Zollman, *The Communication Structure of Epistemic Communities*, 2007.

[3] M. E. J. Newman, *Modularity and community structure in networks*, 2006.