Fractal Semantic Coordinate System (FSCS)

A Symbol-First Architecture for Dynamic Semantic Fields,
Semantic Gravity, and Contextual Intelligence

Kevin T.N
Vietnam
keedavinci@gmail.com

March 18, 2026

Abstract

This paper introduces the Fractal Semantic Coordinate System (FSCS), a symbol-first semantic architecture in which meaning is not represented by a single fixed embedding vector but by a dynamic coordinate within a recursively organized semantic field. The system begins from atomic symbols rather than pre-tokenized lexical units. Through repeated exposure, local co-occurrence structure, contextual variation, and verification thresholds, stable nodes emerge from symbol clusters. Verified nodes are then anchored into a small set of primitive semantic fields, and their positions evolve through contextual resonance, field attraction, semantic compression, and memory dynamics.

The central proposal is that semantic representation should be re-founded on four coupled principles. First, lexical structure should emerge from symbol interaction rather than be assumed in advance. Second, a node is not merely a cluster but a local coordinate origin capable of generating multiple contextual profiles. Third, semantic meaning should be represented as displacement inside a field geometry rather than as a static vector. Fourth, semantic organization should be recursively extensible: every node may act both as an entity and as a local frame for finer semantic decomposition. This leads to a fractal semantics in which local and global meaning are coupled across scale.

The paper formalizes symbol co-occurrence learning, candidate node formation, contextual frequency, contextual diversity, surprise-based learning pressure, node verification, semantic field anchoring, field balancing, semantic metric construction, semantic energy, memory decay, semantic compression, and grammar emergence. In addition, three further contributions are developed in depth: a semantic gravity model, a fractal node hierarchy theorem, and a proof sketch for why symbol-first contextual learning may achieve faster semantic acquisition than conventional embedding-heavy language systems under certain conditions.

The purpose of this document is not to present a complete implementation but to provide a principled formal substrate specification. It is intended as the semantic-computational layer that complements prior foundational and ledger-based architectural work by defining how meaning itself may emerge, stabilize, move, compress, and scale within a dynamic semantic field.

Contents

1 Introduction **6**

2 Motivation and Design Position **6**
2.1 Why Embedding-First Architectures Are Not Enough . . . 6
2.2 Why a Symbol-First Approach Matters . . . 7
2.3 The Intended Role of This Paper . . . 7

3 System Overview **7**

4 Core Definitions **7**
4.1 Atomic Symbol . . . 7
4.2 Candidate Node . . . 8
4.3 Verified Node . . . 8
4.4 Semantic Profile . . . 8
4.5 Semantic Field . . . 8
4.6 Local Coordinate Origin . . . 8
4.7 Context . . . 8

5 Layer 0: Universal Symbol Intake **8**
5.1 Tokenizer Principle . . . 8
5.2 Design Rationale . . . 9

6 IPOD Data Ontology at the Symbol Layer **9**
6.1 Input Layer . . . 9
6.2 Process Layer . . . 10
6.3 Output Layer . . . 10
6.4 Data Layer . . . 10

7 Symbol Co-occurrence Learning **10**
7.1 Local Context Windows . . . 10
7.2 Co-occurrence Matrix . . . 10
7.3 Pointwise Mutual Information . . . 11
7.4 Symbol Graph . . . 11

8 Candidate Node Formation **11**
8.1 Clusters of Associated Symbols . . . 11
8.2 Node Coherence . . . 11
8.3 Cluster Stability . . . 11

9 Cross-Layer Weights **12**
9.1 Symbol-to-Symbol Attraction . . . 12
9.2 Symbol-to-Node Binding . . . 12
9.3 Node-to-Context Weight . . . 12
9.4 Cross-Layer Composition . . . 12

10 Node Identity **12**
10.1 Node Structure . . . 12

10.2 Identity Invariance . . . 13

11 Fractal Coordinate Semantics **13**
11.1 Local Origins . . . 13
11.2 Semantic Profiles as Displacements . . . 13
11.3 Contextual Position of a Node . . . 13
11.4 Why This Is Fractal . . . 13

12 Context Activation **14**
12.1 Profile Resonance . . . 14
12.2 Interpretation . . . 14

13 Context Expansion and Profile Creation **14**
13.1 Context Distance . . . 14
13.2 Profile Creation Rule . . . 14

14 Contextual Learning and Memory Strength **15**
14.1 Raw Frequency Is Not Enough . . . 15
14.2 Contextual Frequency . . . 15
14.3 Context Diversity . . . 15
14.4 Surprise . . . 15
14.5 Learning Strength . . . 15

15 Node Verification **15**

16 The Six Semantic Fields **16**
16.1 Why a Small Fixed Number of Fields . . . 16

17 Field Resonance and Node Anchoring **16**
17.1 Resonance with a Field . . . 16
17.2 Field Weight Vector . . . 17
17.3 Learning-Weighted Anchoring . . . 17

18 Field Balancing, Capacity, and Drift **17**
18.1 Total Field Load . . . 17
18.2 Global Balancing . . . 17
18.3 Field Capacity . . . 17
18.4 Field Drift . . . 17

19 Semantic Metric **18**
19.1 Composite Semantic Distance . . . 18
19.2 Coordinate Distance . . . 18
19.3 Field Distance . . . 18
19.4 Context Distance . . . 18
19.5 Lineage Distance . . . 18
19.6 Interpretation . . . 18

20 Semantic Energy **18**
20.1 Node Energy . . . 18

20.2 Interpretation . . . 19

21 Semantic Gravity Model **19**
21.1 Motivation . . . 19
21.2 Gravity Function . . . 19
21.3 Interpretation . . . 19
21.4 Field-Mediated Gravity . . . 19
21.5 Node Motion Under Gravity . . . 19
21.6 Semantic Interpretation . . . 20

22 Node Strength **20**
22.1 Components of Strength . . . 20
22.2 Why Degree Alone Is Not Enough . . . 20

23 Memory Dynamics and Forgetting **20**
23.1 Decay . . . 20
23.2 Protected Decay for Stable Nodes . . . 21
23.3 Why Decay Matters . . . 21

24 Semantic Compression **21**
24.1 Compression Criterion . . . 21
24.2 Compression Rule . . . 21
24.3 Interpretation . . . 21

25 Fractal Node Hierarchy **21**
25.1 Hierarchy Principle . . . 22
25.2 Recursive Structure . . . 22
25.3 Theorem . . . 22
25.4 Corollary . . . 22

26 Emergent Grammar **22**
26.1 Node Sequence Patterns . . . 23
26.2 Grammar Emergence Criterion . . . 23
26.3 Interpretation . . . 23

27 Semantic Metric Revisited as Comparison Logic **23**

28 Why Context Is Not a Problem but a Generator **23**

29 Computational Pipeline **24**

30 Proof Sketch: Why Symbol-First Contextual Learning Can Be Faster **24**
30.1 The Claim . . . 24
30.2 Informal Reason . . . 24
30.3 A Simple Learning Comparison . . . 25
30.4 Proposition . . . 25
30.5 What This Does Not Claim . . . 26

31 Relation to Dynamic Context Field Semantics **26**

32 Comparison with Conventional Embedding Models **26**

33 Limitations **26**

34 Experimental Directions **27**
34.1 Experiment 1: Early Vocabulary Formation 27
34.2 Experiment 2: Contextual Concept Growth 27
34.3 Experiment 3: Semantic Gravity Clustering 27
34.4 Experiment 4: Compression and Grammar Emergence 27
34.5 Experiment 5: Cross-Language Portability 27

35 Architectural Position in the Larger Project **27**

36 Conclusion **28**

1. Introduction

Most contemporary language models rely on a token-first abstraction. Raw text is segmented into pre-defined units, those units are embedded into high-dimensional spaces, and downstream learning optimizes predictions through gradient-based adjustment over enormous corpora. This approach has achieved remarkable fluency. However, the representation of meaning inside such systems remains difficult to interpret at a structural level. Tokens are given semantic lives inside large parameter spaces, but the model usually does not expose the intermediate semantic geometry by which these meanings become stable, diverge under context, or compress into larger conceptual units.

The Fractal Semantic Coordinate System (FSCS) is motivated by a different question: what would a semantic system look like if it learned language in a more developmental way? Instead of beginning from words, it would begin from symbols. Instead of assuming lexical stability, it would discover stable nodes through repeated structural exposure. Instead of assigning a single embedding to each unit, it would allow a node to behave as a local coordinate origin from which multiple semantic profiles may be activated. Instead of treating semantics as a fixed location in latent space, it would treat semantics as movement and positioning within a field that changes as the system learns.

Such a view has several consequences. First, meaning becomes dynamic rather than static. Second, semantic organization becomes hierarchical and recursive rather than flat. Third, context stops being a mere modifier and becomes a genuine geometric operator. Fourth, semantic memory is naturally developmental: repeated encounters across varied contexts strengthen concepts in a way more similar to child learning than to batch optimization over static vocabularies.

Core shift. In FSCS, meaning is not "the vector assigned to a token." Meaning is the dynamically realized position of a verified node inside a semantic field, relative to context, field resonance, and local hierarchy.

This paper is written as a formal specification for that shift.

2. Motivation and Design Position

2.1. Why Embedding-First Architectures Are Not Enough

Embedding-first systems are effective but limited in three ways. First, they presuppose lexical segmentation at the front of the pipeline. Second, they encode semantic relations implicitly within high-dimensional numerical structure rather than explicitly as semantic geometry. Third, they usually collapse universal understanding and personalized relevance into one shared representation stack.

The consequence is that the model often "knows" many semantic relationships but cannot easily expose why a meaning changed, where a new conceptual distinction came from, or what local frame was used when a concept shifted under context.

2.2. Why a Symbol-First Approach Matters

A symbol-first approach allows the system to postpone lexical commitments. This matters because words are not primitive facts of language. They are stabilized outcomes of recurring symbolic structure. By learning from symbols upward, the system can:

- operate across languages without requiring early vocabulary closure,
- absorb new symbol systems with less front-loaded engineering,
- construct word-like units from experience,
- expose the structural path by which meaning stabilizes.

2.3. The Intended Role of This Paper

This paper should be understood as the semantic-computational layer complementing two earlier kinds of architectural work: foundational ontological work and distributed memory or substrate work. If earlier work defines what kinds of entities and persistence rules exist, the present work defines how semantic entities are learned, positioned, compared, and transformed.

3. System Overview

At the highest level, FSCS proceeds through the following chain:

Raw Input → Symbol Layer → Symbol Graph → Candidate Node Formation → Contextual Learning → Node

In more concrete operational terms, the system performs:

1. universal symbol normalization and intake;
2. symbol-level co-occurrence learning;
3. cluster formation from stable symbolic association;
4. contextual accumulation for candidate node strengthening;
5. verification of node identity and stability;
6. anchoring of verified nodes into six primitive semantic fields;
7. contextual activation of node profiles;
8. metric-based comparison, attraction, and compression;
9. emergence of grammar-like and higher-order semantic patterns.

4. Core Definitions

4.1. Atomic Symbol

Definition 4.1 (Atomic Symbol)**.** *An* atomic symbol *is the smallest representational unit admitted by the system after normalization. It may be a character, punctuation mark, ideograph,*

emoji, mathematical sign, or any other atomic Unicode unit. The symbol alphabet is

$$\Sigma = \{s_1, s_2, \ldots, s_n\}.$$

4.2. Candidate Node

Definition 4.2 (Candidate Node)**.** *A* candidate node *is a structured cluster of symbols recurrently bound by strong local association and contextual recurrence. Candidate nodes become semantic units only after verification.*

4.3. Verified Node

Definition 4.3 (Verified Node)**.** *A* verified node *is a candidate node that has accumulated sufficient structural cohesion and contextual learning strength to be treated as a stable semantic entity.*

4.4. Semantic Profile

Definition 4.4 (Semantic Profile)**.** *A* semantic profile *of a node is a context-conditioned semantic displacement pattern relative to the node's local origin. A node may possess multiple profiles.*

4.5. Semantic Field

Definition 4.5 (Semantic Field)**.** *A* semantic field *is a primitive semantic axis in the global semantic substrate. FSCS assumes a set of six such fields:*

$$\mathcal{F} = \{F_1, F_2, F_3, F_4, F_5, F_6\}.$$

A field is not a final meaning category but a foundational direction of semantic attraction.

4.6. Local Coordinate Origin

Definition 4.6 (Local Coordinate Origin)**.** *For each verified node n, the system assigns a local origin o_n. The node acts as a semantic reference center from which profile displacements are measured.*

4.7. Context

Definition 4.7 (Context)**.** *A* context *is the structured environment in which a symbol or node appears. At low levels, context is local symbolic neighborhood. At higher levels, context includes neighboring nodes, discourse structure, field activation, and interaction history.*

5. Layer 0: Universal Symbol Intake

5.1. Tokenizer Principle

The system begins from a universal symbol tokenizer rather than a vocabulary tokenizer. Let

$$\tau : X \mapsto (s_1, \ldots, s_T)$$

be the tokenization of raw input X into normalized symbols.

Each symbol is produced by:

$$s_i = \text{Normalize}(c_i),$$

where c_i is a raw codepoint or raw symbol instance.

Normalization may include:

- Unicode canonicalization,
- normalization of compatibility variants,
- language-specific preservation when needed,
- optional collapsing of equivalent symbol families.

5.2. Design Rationale

This layer is intended to be:

- language-agnostic,
- script-agnostic,
- not dependent on early lexical segmentation,
- able to accept code, text, formulae, and hybrid symbol systems.

Universal Intake Principle

The semantic substrate must be able to process symbols before it knows what counts as a word. Lexical structure is a learned outcome, not a prerequisite.

6. IPOD Data Ontology at the Symbol Layer

For each symbol s, the system maintains a symbol-centered record structured by an IPOD-style ontology:

```
Symbol/
    s/
        I/
        P/
        O/
        D/
```

6.1. Input Layer

$$I(s) = \{p_1, p_2, \ldots, p_m\}$$

stores positions or indexed occurrences of symbol s.

6.2. Process Layer

For a local radius w, the local context window of occurrence i is

$$C_i(s) = \{s_{i-w}, \dots, s_{i-1}, s_{i+1}, \dots, s_{i+w}\}.$$

The collection of all such windows forms the process-context store:

$$P(s) = \{C_1(s), C_2(s), \dots\}.$$

6.3. Output Layer

The output layer stores likely continuations or structural consequences such as:

$$O(s) = \{s_{i+1}, s_{i+2}, \dots\}, \qquad P(s_b \mid s_a).$$

6.4. Data Layer

The data layer stores statistics:

- raw frequency,
- normalized frequency,
- entropy of neighborhood,
- candidate cluster participation,
- context distributions.

7. Symbol Co-occurrence Learning

7.1. Local Context Windows

For a sequence $X = (s_1, \dots, s_T)$, define the local context of s_i by:

$$C(s_i) = \{s_{i-w}, \dots, s_{i-1}, s_{i+1}, \dots, s_{i+w}\}.$$

7.2. Co-occurrence Matrix

The co-occurrence count between symbols s_a and s_b is:

$$M_{ab} = \#(s_a \text{ occurs near } s_b).$$

Conditional probability:

$$P(s_b \mid s_a) = \frac{M_{ab}}{\sum_k M_{ak}}.$$

7.3. Pointwise Mutual Information

To distinguish meaningful attraction from raw frequency:

$$\mathrm{PMI}(s_a, s_b) = \log \frac{P(s_a, s_b)}{P(s_a)P(s_b)}.$$

7.4. Symbol Graph

The symbol layer induces a weighted graph:

$$\mathcal{G}_\Sigma = (\Sigma, \mathcal{E}_\Sigma),$$

where edge weights are:

$$w_{ab}^{(\Sigma)} = \mathrm{PMI}(s_a, s_b).$$

This graph is the first structural substrate from which lexical and pre-lexical organization emerges.

8. Candidate Node Formation

8.1. Clusters of Associated Symbols

A candidate node is a cluster

$$n = \{s_{i_1}, s_{i_2}, \ldots, s_{i_r}\}$$

whose internal symbolic relations exceed a cohesion threshold.

8.2. Node Coherence

Define the coherence of candidate cluster n:

$$\mathrm{Coh}(n) = \frac{1}{|E(n)|} \sum_{(u,v)\in E(n)} \mathrm{PMI}(u, v),$$

where $E(n)$ is the set of internal symbol-pair edges.

8.3. Cluster Stability

To prevent combinatorial explosion, define:

$$\sigma(n) = \frac{\mathrm{freq}(n)^\alpha \ \mathrm{Coh}(n)^\beta}{\mathrm{H}(\mathrm{context}(n)) + \varepsilon}.$$

A candidate node is retained only if:

$$\sigma(n) > \theta_\sigma.$$

Remark 8.1. *This prevents arbitrary fragments from proliferating merely because they occur once or twice in local coincidence.*

9. Cross-Layer Weights

The architecture requires explicit weights linking symbols, nodes, and contexts.

9.1. Symbol-to-Symbol Attraction

This is given directly by:

$$w_{ab}^{(\Sigma)} = \mathrm{PMI}(s_a, s_b).$$

9.2. Symbol-to-Node Binding

Let $\beta_{a,j}$ measure how strongly symbol s_a belongs to node n_j:

$$\beta_{a,j} = \frac{\mathrm{PMI}(s_a, n_j)}{\sum_k \mathrm{PMI}(s_a, n_k)}.$$

9.3. Node-to-Context Weight

Let the context class set be

$$\mathcal{C} = \{c_1, \ldots, c_p\}.$$

Then:

$$\gamma_{j,k} = P(c_k \mid n_j).$$

9.4. Cross-Layer Composition

A symbol's induced participation in a context is:

$$\omega_{a,k} = \sum_j \beta_{a,j}\gamma_{j,k}.$$

Thus the semantic chain is:

$$s_a \to n_j \to c_k.$$

10. Node Identity

A node is not merely a cluster of symbols. It is an identity-bearing semantic object with structural invariants.

10.1. Node Structure

We define a node as:

$$n = (o_n, P_n, \Phi_n, \Lambda_n),$$

where:

- o_n: local semantic origin,
- P_n: set of semantic profiles,
- Φ_n: transformation rules,

- Λ_n: lineage and memory trace.

10.2. Identity Invariance

A node may shift semantically under context while preserving identity:

$$n \equiv (o_n, \text{variable profiles}, \text{stable lineage}).$$

This means that meaning changes are represented by displacement or activation, not by annihilating the node's identity.

11. Fractal Coordinate Semantics

11.1. Local Origins

Each verified node acts as a local semantic origin:

$$o_n = (0, 0, 0).$$

This does not mean the node has no meaning. It means that inside its own local reference frame it is the origin.

11.2. Semantic Profiles as Displacements

Let the profile set of node n be:

$$P_n = \{p_{n,1}, p_{n,2}, \ldots, p_{n,m_n}\},$$

with each profile represented by:

$$p_{n,k} = (x_{n,k}, y_{n,k}, z_{n,k}).$$

11.3. Contextual Position of a Node

Under active context C, the realized semantic position of node n is:

$$p_n(C) = \sum_{k=1}^{m_n} a_{n,k}(C)\, p_{n,k},$$

where $a_{n,k}(C)$ are context-dependent profile activation weights.

11.4. Why This Is Fractal

A node is simultaneously:

- a point in a larger system,
- a local coordinate frame for finer meanings,
- a possible parent of a deeper subtree of semantic subnodes.

Thus semantics is recursively structured across scale.

12. Context Activation

12.1. Profile Resonance

Let $R_{n,k}(C)$ be the resonance of profile $p_{n,k}$ under context C. Then:

$$a_{n,k}(C) = \frac{\exp(R_{n,k}(C)/T)}{\sum_j \exp(R_{n,j}(C)/T)}.$$

12.2. Interpretation

This means that the same node may occupy different semantic positions depending on which context is active.

Context Activation Principle

A node does not carry one fixed meaning. It carries a family of possible semantic displacements, and context selects or mixes them.

13. Context Expansion and Profile Creation

When a new context C_{new} arrives, the system must decide whether to:

1. update an existing profile, or
2. create a new semantic profile.

13.1. Context Distance

Let d_C be a distance between contexts. A simple form is:

$$d_C(C_i, C_j) = 1 - \frac{|N(C_i) \cap N(C_j)|}{|N(C_i) \cup N(C_j)|},$$

where $N(C)$ is the set of active neighboring nodes in context C.

13.2. Profile Creation Rule

If

$$d_C(C_{\text{new}}, C_i) > \theta_{\text{profile}}$$

for all existing profiles C_i, a new profile is created.

Otherwise the nearest existing profile is updated.

This prevents uncontrolled profile explosion while preserving semantic novelty.

14. Contextual Learning and Memory Strength

14.1. Raw Frequency Is Not Enough

Raw repetition alone:

$$\mathrm{freq}(n)$$

cannot explain conceptual strength. Common function fragments may repeat often without becoming conceptually rich.

14.2. Contextual Frequency

Define the contextual frequency of node n:

$$\mathrm{CF}(n) = |\mathcal{C}(n)|,$$

where $\mathcal{C}(n)$ is the set of distinct contexts in which n appears.

14.3. Context Diversity

Let $p(c)$ be the frequency of context c for node n. Then:

$$D(n) = -\sum_{c \in \mathcal{C}(n)} p(c) \log p(c).$$

14.4. Surprise

Unexpected appearance in a novel context produces additional learning pressure:

$$\mathrm{Surprise}(n, c) = -\log P(n \mid c).$$

14.5. Learning Strength

Define learning strength:

$$L(n) = \mathrm{freq}(n)^{\alpha} \cdot \mathrm{CF}(n)^{\beta} \cdot D(n)^{\gamma} \cdot (1 + \overline{\mathrm{Surprise}}(n))^{\delta},$$

where $\overline{\mathrm{Surprise}}(n)$ is average surprise across observed contexts.

Developmental learning claim. A node is remembered strongly not merely because it repeats often, but because it repeats across many distinct, informative, and sometimes surprising contexts.

15. Node Verification

A candidate node becomes a verified node only if structural and contextual criteria are both satisfied.

Definition 15.1 (Verification Rule)**.** *A candidate node n is verified if:*

$$\mathrm{Verify}(n) = 1 \quad \Longleftrightarrow \quad L(n) > \theta_L \quad \textit{and} \quad \mathrm{Coh}(n) > \theta_{coh}.$$

Only verified nodes are anchored into the semantic field layer.

This models the transition:

$$\text{fragment} \to \text{recurrent pattern} \to \text{stable concept}.$$

16. The Six Semantic Fields

FSCS assumes six primitive semantic fields:

$$\mathcal{F} = \{F_1, F_2, F_3, F_4, F_5, F_6\}.$$

At initialization:

$$\mathcal{N}_{F_k}(0) = \varnothing.$$

These six fields are best understood as seed axes of semantic organization. Their interpretive labels may be refined over time by the node distributions that gather around them.

16.1. Why a Small Fixed Number of Fields

A small field basis provides:

- global semantic structure,
- manageable interpretability,
- room for recursive internal differentiation inside nodes.

The fields do not need to encode every meaning directly. Their role is to provide large-scale semantic directions.

17. Field Resonance and Node Anchoring

17.1. Resonance with a Field

For a verified node n and field F_k, define:

$$\mathrm{Res}(n, F_k).$$

One admissible formulation is:

$$\mathrm{Res}(n, F_k) = \frac{1}{|\mathcal{C}(n)|} \sum_{c \in \mathcal{C}(n)} \mathrm{sim}(c, \mathrm{proto}(F_k)),$$

where $\mathrm{proto}(F_k)$ is the current field prototype.

17.2. Field Weight Vector

Normalize field resonance:

$$w_{n,k} = \frac{\mathrm{Res}(n, F_k)}{\sum_{j=1}^{6} \mathrm{Res}(n, F_j)}.$$

Thus:

$$\mathbf{W}_n = [w_{n,1}, \ldots, w_{n,6}], \qquad \sum_{k=1}^{6} w_{n,k} = 1.$$

17.3. Learning-Weighted Anchoring

A more mature node should exert stronger anchoring pressure:

$$\mathrm{Res}'(n, F_k) = L(n) \cdot \mathrm{Res}(n, F_k).$$

Then:

$$w_{n,k} = \frac{\mathrm{Res}'(n, F_k)}{\sum_{j=1}^{6} \mathrm{Res}'(n, F_j)}.$$

18. Field Balancing, Capacity, and Drift

18.1. Total Field Load

Define:

$$S_k = \sum_{n \in \mathcal{N}_{\mathrm{ver}}} w_{n,k}.$$

18.2. Global Balancing

A normalized contribution is:

$$\widetilde{w}_{n,k} = \frac{w_{n,k}}{S_k + \varepsilon}.$$

18.3. Field Capacity

Each field may have capacity K_k. If a field saturates, its attraction weakens:

$$\widehat{w}_{n,k} = w_{n,k} \exp\left(-\lambda \max\left(0, \frac{S_k - K_k}{K_k}\right)\right).$$

18.4. Field Drift

Field centers evolve with accumulated node mass:

$$F_k^{t+1} = F_k^t + \eta \sum_n w_{n,k} p_n.$$

Thus fields are not static containers; they are dynamic semantic attractors shaped by what they collect.

19. Semantic Metric

A full semantic system requires more than position. It requires a metric for comparing nodes.

19.1. Composite Semantic Distance

Define:

$$d(n_i, n_j) = \alpha d_{\text{coord}}(n_i, n_j) + \beta d_{\text{field}}(n_i, n_j) + \gamma d_{\text{context}}(n_i, n_j) + \delta d_{\text{lineage}}(n_i, n_j),$$

with $\alpha, \beta, \gamma, \delta \geq 0$.

19.2. Coordinate Distance

$$d_{\text{coord}}(n_i, n_j) = \|p_i - p_j\| .$$

19.3. Field Distance

$$d_{\text{field}}(n_i, n_j) = \|\mathbf{W}_i - \mathbf{W}_j\| .$$

19.4. Context Distance

$$d_{\text{context}}(n_i, n_j) = 1 - \frac{|\mathcal{C}(n_i) \cap \mathcal{C}(n_j)|}{|\mathcal{C}(n_i) \cup \mathcal{C}(n_j)|}.$$

19.5. Lineage Distance

Let $\text{depth}(n_i, n_j)$ denote the depth distance in the node hierarchy. Then:

$$d_{\text{lineage}}(n_i, n_j) = \text{depth}(n_i, n_j).$$

19.6. Interpretation

This metric allows the system to compare nodes not only by geometric position but by field affinity, contextual overlap, and hierarchical inheritance.

20. Semantic Energy

Nodes differ not only by position and distance but also by semantic intensity.

20.1. Node Energy

Define semantic energy:

$$E(n) = \sum_{k=1}^{6} w_{n,k}^2.$$

A more concentrated field profile yields higher energy.

20.2. Interpretation

High-energy nodes may act as semantic attractors. They pull nearby nodes, stabilize clusters, and influence compression decisions.

Remark 20.1. *Energy here is not physical energy in a literal sense. It is a semantic concentration measure.*

21. Semantic Gravity Model

We now introduce the first major extension beyond the earlier skeleton: semantic gravity.

21.1. Motivation

If meaning lives in a field, then semantic organization should not be purely static. Nodes should exert attraction on each other. Strong nodes, especially verified and high-energy nodes, should bias the motion and compression of nearby nodes.

21.2. Gravity Function

For nodes n_i and n_j, define semantic gravity:

$$G(n_i, n_j) = \lambda \frac{\mathrm{Strength}(n_i)\,\mathrm{Strength}(n_j)}{(d(n_i, n_j) + \varepsilon)^p},$$

where $\lambda > 0$, $p > 0$, and $\varepsilon > 0$.

21.3. Interpretation

This says:

- semantically strong nodes attract each other more strongly,
- attraction decreases with semantic distance,
- local semantic organization becomes self-reinforcing.

21.4. Field-Mediated Gravity

A field-weighted version is:

$$G_F(n_i, n_j) = G(n_i, n_j) \cdot \left(\sum_{k=1}^{6} \min(w_{i,k}, w_{j,k}) \right).$$

This means that shared field orientation increases attraction.

21.5. Node Motion Under Gravity

If nodes are treated dynamically, their positions may be updated by:

$$p_i^{t+1} = p_i^t + \eta \sum_{j \neq i} G(n_i, n_j) \frac{p_j^t - p_i^t}{\left\| p_j^t - p_i^t \right\| + \varepsilon}.$$

21.6. Semantic Interpretation

This model explains:

- why concept clusters form naturally,
- why strong semantic hubs stabilize neighborhoods,
- why related ideas condense even without fixed external labels.

Semantic Gravity Principle

Semantic space is not merely a coordinate map. It is a dynamic field in which stable and energetic nodes exert attraction, thereby shaping the geometry of later meaning formation.

22. Node Strength

To support gravity and field dynamics, node strength must combine multiple factors.

22.1. Components of Strength

Let:

- $W_i = \sum_j \mathrm{PMI}(i, j)$: total mutual-information connectivity,
- C_i: clustering coefficient,
- S_i: temporal-contextual stability,
- R_i: field resonance contribution.

Define:

$$\mathrm{Strength}(i) = \alpha W_i + \beta C_i + \gamma S_i + \delta R_i.$$

22.2. Why Degree Alone Is Not Enough

Raw degree:

$$\deg(i) = \sum_j A_{ij}$$

is insufficient because frequent but semantically thin nodes may have high degree. Strength must reward informative structure, not just raw connectivity.

23. Memory Dynamics and Forgetting

A viable semantic system must forget selectively.

23.1. Decay

If a weight is not reinforced, it decays:

$$w(t + 1) = w(t)e^{-\lambda \Delta t}.$$

23.2. Protected Decay for Stable Nodes

For highly verified nodes:

$$w_{\text{stable}}(t+1) = w_{\text{stable}}(t)e^{-\lambda_s \Delta t}, \qquad \lambda_s < \lambda.$$

Thus deeply consolidated concepts decay more slowly.

23.3. Why Decay Matters

Without decay:

- graphs grow without bound,
- noisy contexts persist too long,
- false structures accumulate,
- compression loses discriminative value.

24. Semantic Compression

24.1. Compression Criterion

If two nodes become sufficiently close:

$$d(n_i, n_j) < \epsilon,$$

the system may generate a higher-level abstraction node n_{ij}.

24.2. Compression Rule

Let:

$$n_{ij} = \text{Compress}(n_i, n_j).$$

A simple coordinate update:

$$p_{ij} = \frac{\text{Strength}(i)p_i + \text{Strength}(j)p_j}{\text{Strength}(i) + \text{Strength}(j)}.$$

Field vector:

$$\mathbf{W}_{ij} = \frac{\text{Strength}(i)\mathbf{W}_i + \text{Strength}(j)\mathbf{W}_j}{\text{Strength}(i) + \text{Strength}(j)}.$$

24.3. Interpretation

Compression turns local semantic regularity into abstraction. This is one mechanism by which phrases, concepts, and higher categories emerge.

25. Fractal Node Hierarchy

We now introduce the second major extension: a formal statement of node hierarchy.

25.1. Hierarchy Principle

Every verified node may itself become the root of a deeper semantic subtree. Thus the architecture is recursively extensible.

Let:

$$\mathcal{T}(n) = \{n; n_1, n_2, \dots; n_{11}, n_{12}, \dots\}$$

denote the hierarchy rooted at node n.

25.2. Recursive Structure

A node behaves simultaneously as:

- an object in its parent frame,
- a local origin for child distinctions,
- a candidate for compression into a higher abstraction.

25.3. Theorem

Theorem 25.1 (Fractal Node Hierarchy Theorem)**.** *Suppose a semantic architecture satisfies the following:*

1. *every verified node possesses a local origin o_n,*
2. *every node admits a finite set of context-activated profiles P_n,*
3. *new profiles may be created when context distance exceeds a threshold,*
4. *sufficiently close nodes may compress into parent abstraction nodes.*

Then the induced semantic structure is recursively self-similar in the following sense: any verified node may be treated as both a semantic point in a higher frame and a semantic frame for lower distinctions. Consequently, the semantic space admits a fractal hierarchical organization.

Proof sketch. The proof is structural. Because each verified node has a local origin, it can serve as a reference point. Because each node has multiple profiles, local distinctions may appear around that origin. Because sufficiently novel contexts generate new profiles, local semantic refinement continues within the node. Because nearby nodes may compress into abstractions, local refinement can be folded back upward into higher units. These two operations – downward profile differentiation and upward abstraction compression – can be repeated across scales. Therefore the same semantic logic recurs locally and globally, yielding recursive self-similarity. □

25.4. Corollary

Corollary 25.1. *Semantic meaning in FSCS is not flat. It is inherently multi-scale and recursively reframeable.*

26. Emergent Grammar

Grammar is not assumed as an explicit prior. It emerges from stable sequence patterns of nodes.

26.1. Node Sequence Patterns

Let a sequence of nodes be:

$$(n_1, n_2, \ldots, n_r).$$

Recurrent sequences form pattern candidates:

$$P = \text{Cluster}(\text{sequence}(n_1, \ldots, n_r)).$$

26.2. Grammar Emergence Criterion

A sequence pattern becomes grammatically salient when:

- it recurs with high contextual stability,
- its internal transitions have strong mutual predictability,
- it compresses efficiently into a reusable pattern unit.

26.3. Interpretation

Syntactic regularities can therefore emerge from repeated node-sequence stabilization without requiring explicit grammar rules from the outset.

27. Semantic Metric Revisited as Comparison Logic

The metric defined earlier is not a decorative add-on. It governs key decisions:

- whether a new context creates a new profile,
- whether two nodes are close enough to compress,
- whether two nodes should attract each other gravitationally,
- whether a node belongs near a field center.

Thus the metric is the comparison logic of the entire architecture.

Metric Principle

If the system cannot compare contexts, nodes, and field alignments in a consistent way, then it cannot decide whether to stabilize, split, merge, or move a semantic entity.

28. Why Context Is Not a Problem but a Generator

A context-heavy system may appear unstable because contexts proliferate. However, in this architecture context proliferation is not treated as a defect. It is a generative mechanism.

More contexts imply:

- richer profile differentiation,
- more opportunities for abstraction,

- more robust learning of concept boundaries,
- better discrimination between shallow repetition and genuine semantic growth.

Context is therefore not merely noise around meaning. It is what drives meaning outward from a node's origin into its semantic neighborhood.

29. Computational Pipeline

The full pipeline may be written compactly as:

$$X \to \tau(X) \to \mathcal{G}_\Sigma \to \mathcal{N}_{\text{cand}} \to L(n) \to \text{Verify}(n) \to \mathbf{W}_n \to p_n(C) \to G(n_i, n_j) \to \text{compression / grammar / hig}$$

Expanded:

$$\begin{aligned}
X &\mapsto (s_1, \ldots, s_T), \\
(s_1, \ldots, s_T) &\mapsto \mathcal{G}_\Sigma \text{ through co-occurrence}, \\
\mathcal{G}_\Sigma &\mapsto \mathcal{N}_{\text{cand}} \text{ through clustering}, \\
n &\mapsto L(n), \\
n &\mapsto \text{Verify}(n), \\
n &\mapsto \mathbf{W}_n \text{ through field anchoring}, \\
(n, C) &\mapsto p_n(C) \text{ through profile activation}, \\
(n_i, n_j) &\mapsto d(n_i, n_j), G(n_i, n_j), \\
\{n_i\} &\mapsto \text{compression and pattern emergence.}
\end{aligned}$$

30. Proof Sketch: Why Symbol-First Contextual Learning Can Be Faster

We now introduce the third major extension: a proof sketch for why the proposed architecture may learn language faster than conventional embedding-heavy systems under certain structural assumptions.

30.1. The Claim

The claim is not that FSCS universally dominates all language models. The claim is narrower: if semantic learning depends strongly on repeated contextual discrimination rather than on sheer exposure volume alone, then a symbol-first system with explicit contextual accumulation may achieve faster early concept formation than a purely embedding-driven system.

30.2. Informal Reason

A standard embedding-heavy model often needs many exposures before a stable semantic distinction becomes encoded across distributed parameters. In contrast, FSCS stores learning pressure explicitly in:

- contextual frequency,

- contextual diversity,
- surprise,
- structural coherence,
- field resonance.

Thus each informative context contributes directly to concept stabilization.

30.3. A Simple Learning Comparison

Suppose semantic maturation of a concept in a parameter-heavy model depends on N exposures, each contributing a small distributed gradient update δ. Then the total semantic signal scales approximately like:

$$S_{\mathrm{LLM}}(N) \approx \sum_{t=1}^{N} \delta_t.$$

In FSCS, semantic maturation scales more like:

$$S_{\mathrm{FSCS}}(N) \approx \sum_{t=1}^{N} \Big(\alpha\,\Delta\,\mathrm{freq} + \beta\,\Delta\,\mathrm{CF} + \gamma\,\Delta D + \delta\,\Delta\,\mathrm{Surprise}\Big)_t.$$

If many exposures are redundant, then in a gradient-heavy model the incremental signal may remain small and diffuse. In FSCS, the marginal gain from a novel context may be comparatively large because $\Delta\,\mathrm{CF}$, ΔD, and $\Delta\,\mathrm{Surprise}$ can spike sharply.

30.4. Proposition

Proposition 30.1. *Assume two systems receive the same exposure sequence for a candidate concept. Suppose further that:*

1. *many exposures are redundant repetitions of already-seen contexts,*
2. *a smaller subset of exposures introduces new contexts,*
3. *concept stabilization depends primarily on contextual discrimination rather than raw repetition alone.*

Then an architecture that explicitly rewards contextual novelty and diversity may reach a concept verification threshold with fewer total exposures than an architecture that absorbs all exposures mainly through diffuse parameter updates.

Proof sketch. If redundant exposures dominate the corpus, then raw frequency grows quickly but semantic differentiation grows slowly. In FSCS, only exposures that expand $\mathrm{CF}(n)$, $D(n)$, or $\mathrm{Surprise}(n, c)$ substantially increase learning strength. The verification threshold is tied to those quantities. Therefore the stabilization criterion depends more directly on informative exposures. In a distributed parameter model, the same novel exposure must propagate through many parameter couplings before becoming a stable semantic distinction. Hence, under the stated assumptions, the explicit contextual learner may cross its concept threshold sooner. □

30.5. What This Does Not Claim

This does not prove that FSCS is globally better than all LLMs. It only shows that the architecture has a plausible theoretical advantage in *context-efficient semantic acquisition*, especially during early learning and concept formation.

31. Relation to Dynamic Context Field Semantics

This architecture is deeply compatible with Dynamic Context Field thinking. In such a view, the meaning of an entity is not intrinsic in isolation but depends on the active context frame. The present system provides a concrete symbol-first substrate for that principle.

Nodes become the carriers of local identity. Profiles become the local meaning variants. Context activation selects profiles. Field anchoring provides global semantic orientation. Metric and gravity supply dynamic structure. Compression produces abstraction. This is precisely the sort of machinery needed if semantics is to be context-native rather than token-fixed.

32. Comparison with Conventional Embedding Models

Aspect	**Embedding-Heavy LLMs**	**FSCS**
Primitive unit	token / subword	atomic symbol
Vocabulary dependence	high early	low early
Meaning representation	vector embedding	coordinate in field
Context role	modulates prediction	activates profiles and movement
Interpretability	low	higher
Concept formation	implicit	explicit verification
Compression	distributed / opaque	structural and trackable
Personalization potential	usually external or later	native at the field level

33. Limitations

This framework is ambitious and incomplete in several ways.

First, symbol-first learning risks combinatorial explosion without strong pruning and compression. Second, the design of the six primitive fields is philosophically elegant but requires empirical validation. Third, the gravity and metric functions are formal proposals, not experimentally proven laws. Fourth, computational efficiency remains open: building and updating explicit symbolic, contextual, and field structures may be expensive at scale. Fifth, grammar emergence is plausible but still requires strong experimental demonstration.

These limitations do not invalidate the framework, but they do mark the gap between formal architecture and production system.

34. Experimental Directions

Several experimental programs suggest themselves.

34.1. Experiment 1: Early Vocabulary Formation

Train the system on symbol streams and compare how quickly stable word-like nodes emerge relative to BPE-based token learners.

34.2. Experiment 2: Contextual Concept Growth

Track concept strength $L(n)$ as a function of:

- raw frequency,
- contextual frequency,
- context diversity,
- surprise.

34.3. Experiment 3: Semantic Gravity Clustering

Test whether semantic gravity accelerates stable conceptual cluster formation.

34.4. Experiment 4: Compression and Grammar Emergence

Measure whether repeated node-sequence compression yields reusable grammar-like patterns.

34.5. Experiment 5: Cross-Language Portability

Because the substrate begins from symbols, evaluate how well the system transfers across writing systems.

35. Architectural Position in the Larger Project

If the larger project already contains a foundational ontology paper and a substrate or ledger paper, this paper fills the missing semantic-computational role.

The division is natural:

- foundational theory asks what kinds of entities and transformations are admitted,
- substrate theory asks how memory, lineage, persistence, and distributed structure operate,
- the present paper asks how semantic meaning itself is learned, positioned, compared, compressed, and expanded.

In that sense, this is the third necessary paper: the paper that gives the system a semantic body.

36. Conclusion

This paper introduced the Fractal Semantic Coordinate System (FSCS), a symbol-first semantic architecture in which language learning begins from atomic symbols and builds upward through structure, context, field anchoring, and recursive semantic hierarchy. The framework rejects the idea that a word must first be given as a stable token before meaning can be learned. Instead, it treats words and concepts as stabilized nodes emerging from symbol interaction and contextual recurrence.

The main contributions were threefold. First, the paper formalized a symbol-to-node-to-field learning chain, together with contextual learning strength, node verification, field anchoring, dynamic position, and semantic metric. Second, it introduced semantic gravity as a model of attraction between strong nodes within a semantic field. Third, it stated a fractal node hierarchy theorem and provided a proof sketch for why explicit contextual learning may achieve faster concept formation than embedding-heavy alternatives under certain assumptions.

The conceptual result is simple but far-reaching: meaning is not a static vector. Meaning is a dynamic coordinate realized by a node inside a field, under a context, within a hierarchy, and across time. If that claim is correct, then semantic intelligence should be built less like a bag of embeddings and more like a living geometry.

Appendix A: Compact Equation Set

$$\Sigma = \{s_1, \ldots, s_n\}$$

$$M_{ab} = \#(s_a \text{ near } s_b)$$

$$\mathrm{PMI}(s_a, s_b) = \log \frac{P(s_a, s_b)}{P(s_a)P(s_b)}$$

$$\mathrm{Coh}(n) = \frac{1}{|E(n)|} \sum_{(u,v)\in E(n)} \mathrm{PMI}(u, v)$$

$$\sigma(n) = \frac{\mathrm{freq}(n)^{\alpha}\ \mathrm{Coh}(n)^{\beta}}{\mathrm{H}(\mathrm{context}(n)) + \varepsilon}$$

$$\mathrm{CF}(n) = |\mathcal{C}(n)|$$

$$D(n) = -\sum_{c\in\mathcal{C}(n)} p(c) \log p(c)$$

$$\mathrm{Surprise}(n, c) = -\log P(n \mid c)$$

$$L(n) = \mathrm{freq}(n)^{\alpha} \cdot \mathrm{CF}(n)^{\beta} \cdot D(n)^{\gamma} \cdot (1 + \overline{\mathrm{Surprise}}(n))^{\delta}$$

$$\text{Verify}(n) = 1 \iff L(n) > \theta_L \text{ and } \text{Coh}(n) > \theta_{\text{coh}}$$

$$a_{n,k}(C) = \frac{\exp(R_{n,k}(C)/T)}{\sum_j \exp(R_{n,j}(C)/T)}$$

$$p_n(C) = \sum_k a_{n,k}(C) p_{n,k}$$

$$w_{n,k} = \frac{\text{Res}(n, F_k)}{\sum_{j=1}^{6} \text{Res}(n, F_j)}$$

$$d(n_i, n_j) = \alpha d_{\text{coord}} + \beta d_{\text{field}} + \gamma d_{\text{context}} + \delta d_{\text{lineage}}$$

$$G(n_i, n_j) = \lambda \frac{\text{Strength}(n_i)\,\text{Strength}(n_j)}{(d(n_i, n_j) + \varepsilon)^p}$$

Appendix B: Suggested Layer Naming

Layer	**Role**
Layer 0	Universal symbol intake and normalization
Layer 1	Symbol co-occurrence graph
Layer 2	Candidate node formation
Layer 3	Contextual learning and node strengthening
Layer 4	Node verification and identity stabilization
Layer 5	Six-field semantic anchoring
Layer 6	Dynamic coordinate realization under context
Layer 7	Semantic gravity, compression, and grammar emergence