

MX Chip type, Long Life Assurance Series

- Load life of 20000 hours at 105℃.
- SMD type: Lead free reflow soldering condition at 260℃ peak correspondence.
- RoHS Compliance (2011/65/EU)




SPECIFICATIONS

Items	Performance Characteristics		
Category Temperature Range	-55 ~ +105℃		
Rated Voltage Range	4 ~ 16V		
Rated Capacitance Range	22 ~ 560μF		
Capacitance Tolerance	± 20 % (at 120Hz , 20℃)		
Tangent of Loss Angle (tan δ)	Less than or equal to the specified value at 120Hz, 20℃		
ESR (※1)	Less than or equal to the specified value at 100KHz, 20℃		
Leakage Current (※2)	Less than or equal to the specified value. After 2 minutes' application of rated voltage at 20℃		
Temperature Characteristics (Max. Impedance Ratio)	Z+105℃ / Z+20℃ ≤1.25 (100kHz) Z- 55℃ / Z+20℃ ≤1.25		
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20℃ after the rated voltage is applied for 20,000 hours at 105℃.	Capacitance change	Within ±20% of the initial capacitance value (※3)
		tan δ	150% or less than the initial specified value
		ESR (※1)	150% or less than the initial specified value
		Leakage current (※2)	Less than or equal to the initial specified value
Damp Heat (Steady State)	The specifications listed at right shall be met when the capacitors are restored to 20℃ after the rated voltage is applied for 1,000 hours at 60℃, 90% RH.	Capacitance change	Within ±20% of the initial capacitance value (※3)
		tan δ	150% or less than the initial specified value
		ESR (※1)	150% or less than the initial specified value
		Leakage current (※2)	Less than or equal to the initial specified value
Resistance to Soldering Heat	After soldering the capacitor shall meet the specifications listed at right. Pre-heating shall be done at 150 to 200℃ and for 60 to 180 sec. The duration for over +230℃ at capacitor surface shall not exceed 60 seconds. In case peak temperature is 250℃ or less, reflow soldering shall be two times maximum. In case peak temperature is 260℃ or less, reflow soldering shall be once. Measurement for solder temperature profiles shall be made at the capacitor top and the terminal.	Capacitance change	Within ±10% of the initial capacitance value (※3)
		tan δ	130% or less than the initial specified value
		ESR (※1)	130% or less than the initial specified value
		Leakage current (※2)	Less than or equal to the initial specified value
Marking	Red print on the case top.		


- ※1. ESR should be measured at both of the terminal ends closest where the terminals protrude through the plastic platform.
- ※2. Conditioning: If any doubt arises, measure the leakage current after the voltage treatment of applying DC rated voltage continuously to the capacitor for 120 minutes at 105℃.
- ※3. Initial value: The value before test of examination of resistance to soldering.

Dimensions



Φ x L(mm)			
Size	5x6	6.3x6	8x7
ΦD	5.0	6.3	8.0
L	5.9	5.9	6.9
A	6.0	7.3	9.0
B	5.3	6.6	8.3
C	5.3	6.6	8.3
E	1.6	2.1	3.2
H	0.5-0.8	0.5-0.8	0.8-1.1

Type numbering system (Ex.: 6.3V 220μF)



Voltage				
V	4	6.3	10	16
Code	0G	0J	1A	1C

MX

Series

■STANDARD RATINGS

Rated Voltage (V)(CCode)	Surge Voltage (V)	Rated Capacitance (μF)	Case Size ΦD x L(mm)	tan δ	Leakage Current (μA)	ESR (mΩ) max. (100kHz, 20℃)	Rated Ripple Current (mA rms)	Part Number
4 (0G)	4.6	150	5 x 6	0.12	120	25	2200	EPMS0G151M0506TR
		330	6.3 x 6	0.12	264	20	2800	EPMS0G331M6306TR
		330	8 x 7	0.12	264	22	3200	EPMS0G331M0807TR
		560	8 x 7	0.12	448	18	3600	EPMS0G561M0807TR
6.3 (0J)	7.2	47	5 x 6	0.12	100	35	1600	EPMS0J470M0506TR
		100	5 x 6	0.12	126	25	2400	EPMS0J101M0506TR
		100	6.3 x 6	0.12	126	22	2800	EPMS0J101M6306TR
		120	6.3 x 6	0.12	151	22	2800	EPMS0J121M6306TR
		220	6.3 x 6	0.12	277	20	2800	EPMS0J221M6306TR
		220	8 x 7	0.12	277	22	3200	EPMS0J221M0807TR
		390	8 x 7	0.12	491	22	3200	EPMS0J391M0807TR
10 (1A)	11.5	33	5 x 6	0.12	100	40	1300	EPMS1A330M0506TR
		56	6.3 x 6	0.12	112	27	2300	EPMS1A560M6306TR
		68	5 x 6	0.12	136	30	2100	EPMS1A680M0506TR
		120	6.3 x 6	0.12	240	27	2300	EPMS1A121M6306TR
		150	8 x 7	0.12	300	30	2600	EPMS1A151M0807TR
		270	8 x 7	0.12	540	22	3200	EPMS1A271M0807TR
16 (1C)	18.4	22	5 x 6	0.12	100	45	1100	EPMS1C220M0506TR
		39	5 x 6	0.12	125	35	2000	EPMS1C390M0506TR
		39	6.3 x 6	0.12	125	30	2200	EPMS1C390M6306TR
		68	6.3 x 6	0.12	218	30	2200	EPMS1C680M6306TR
		82	8 x 7	0.12	262	28	2800	EPMS1C820M0807TR
		120	8 x 7	0.12	384	28	2800	EPMS1C121M0807TR