





# SHENZHEN KINGCCTV TECHNOLOGY CO.,LTD.













26E, Block 2, Nanguo Bldg., No. 2065, Hongling Middle Rd., Futian District  
Shenzhen, Guangdong, P.R.CHINA ZIP: 518028  
TEL:86-755-8616 5030 FAX: 86-755-8241 8186










www.kingcctv.com E-Mail: sales5@kingcctv.com Skype: sales5@kingcctv.com Wechat&whatsapp: 86 13549962364 Contact: Sandy Lee

## KingCCTV-Quotation

No.	Picture	Model	Specification	EX-W Unit Price (USD/PC)	Quantity (PCS)	Total
1		Intel Xeon E5-2620 v4(20M Cache, 2.10 GHz)	Intel Xeon E5-2620 v4(20M Cache, 2.10 GHz) <b>Second hand</b>	US\$1.60	5	US\$8.00
2		DS-AT1000S/450/25T	<b>DS-AT1000S/480 Stop production, replace with DS-AT1000S/450/25T</b> <b>24-slot Cost-efficient Super Capacity Storage</b> 18*25 TB IoT SMR enterprise HDD IoT fully sealed helium HDD technology Surveillance-specialized direct storage (Direct Streaming mode) Highly cost efficient, safe and reliable Energy saving and space saving Easy operation and maintenance SMR HDD providing 5-year warranty	US\$13,276.20	1	US\$13,276.20
3		DS-6916UDI (B)	<b>4K Decoder</b> Provides HDMI (adaptable to DVI-D) and BNC output interfaces. Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for odd interface). Up to 8-ch decoding at 24 MP resolution. H.265+/H.265, H.264+/H.264, Hik264, MPEG4 and MJPEG video compression. PS, RTP, TS, ES, HIK encapsulation formats. Three encoding levels: baseline, main, and high-profile. G.722, G711A, G726, G711U, MPEG2-L2, and AAC audio compression. Two decoding modes: active decoding and passive decoding. Supports two-way audio via client software. Remote video files' decoding output. Provides VGA and DVI input interfaces. Supports window opening, window roaming and window split. Supports multi-screen control with PC installed with RSC server. Gets stream and decodes via URL and RTSP from encoding devices. Displays the decoded video stream on the video wall by directly linking cameras or by stream media forwarding. Configurable LED width and height parameters when the LED is connected. Regular and irregular virtual screen configurable to display multiple signal sources and get rid of the restriction of physical screen. Accessible by thermal network camera and you can view the temperature measurement, dynamic fire source detection, ship detection and VCA information in live view and playback. You can enable or disable the smart information for the thermal network camera. Port aggregation technology (Ethernet Channel). Accessible by 2.4 MP DeepinView camera. Two-way audio. You can configure what the video wall shows when decoding ends and streaming fails via the Web browser and client software.	US\$1,598.90	3	US\$4,796.70
4		DC HC560 from Western Digital	20TB HDD	US\$368.80	24	US\$8,851.20

5		Защита шин питания 404994 Power protection			1	
6		КЛАВИАТУРА И МЫШЬ (S.927-2 OF 2) Keyboard and Mouse	Lenovo MK11 keyboard and wired mouse	US\$9.80	5	US\$49.00
7		DS-1100KI(B)	<b>Network Keyboard</b> Divide video wall into regions to manage video wall by region open/close window, move window, resize window, divide window, and enlarge/narrow sub-window. Group and macro Preview camera live image on network keyboard touchscreen Quickly switch to the previous/next camera Control speed dome movement via joystick Play the decoder videos on video wall Play the video recorder videos on network keyboard touchscreen. Supports clipping and capturing during playback Add devices via SDK or ONVIF protocol HikCentral and KPS platforms access Support up to 32 users (1 administrator and 31 operators) and 4,000 devices Add/modify/delete cameras in batch Import/export configuration file	US\$575.80	3	US\$1,727.40
8		DS-K4H250-LZ	<b>Pro Series Magnetic Lock Bracket</b> v The LZ-bracket adopts aldural material with the surface sandblast v It is suitable for in-swing doors v The door opens towards inside at the angle of 90° v The bracket is suitable for magnetic lock of 300kg series v The shell is hard anodizing electroplating operated v The weight of the bracket is 0.75kg (1.58lb) v The dimension(L×W×H) of L-bracket is 250×47×28.5mm (9.84×1.85×1.12") v The dimension (L×W×H) of Z-bracket is 180×50×50mm (7.09×1.97×1.97") (ABK-280ZL)	US\$16.50	1	US\$16.50
9		DS-DN4655W/U	<b>Wall-mounted Bracket</b> Solid steel structure, preventing screen bending or twisting Cold-rolled steel plate (SPCC) Quick and easy installation	US\$53.10	8	US\$424.80
10		Лоток перфорированный 100x300x3000MM LLK1- 100-300-3			1	
11		Модуль аналоговых линий PMOD 6 XAL 001/1	PMOD 6 XAL 001 ANALOG LINE MODULE		1	

12		27" Minitor	Screen size: 27 inches (615.5 x 361.1mm) Panel type: IPS Border type: Borderless Resolution: 1920 x 1080 (1K) Curvature: Planar Display color: 16.7M Color saturation: 99% sRGB Aspect ratio: 16:9 Brightness: 300cd/m2 Screen refresh rate (maximum): 75Hz Response time: 1ms Contrast: 1000:1 Visual angle: 178 °/178 ° Power consumption: 42W Standby power consumption: 0.5W	US\$72.10	8	US\$576.80
13		Монтажная рейка, перфорированная, размеры согласно EN 60715 - 35 x 7,5 мм, оцинк. дл.2 м, арт.801733			1	
14		Нарезаемая рейка с продольными отверстиями глубиной 7,5 мм - длина 2 м 0 477 22			1	
15		Оборуд.СДСО:Громкоговоритель потолочный 6 Вт /100 В (47944) Installation: ceiling speaker	Rated power: 6-10w Box material: ABS Input voltage: 70/100v Sensitivity: 90dB Frequency response: 100-18000Hz Speaker: High quality full frequency speaker Installation opening: 170mm External dimensions: 188 * 88mm	US\$9.00	24	US\$216.00
16		Перегородка разделительная 100x3000MM 36510HDZ			3	
17		Перегородка угла SEP 100MM в комплекте с крепежными элементами SSG01000KHDZ			1	
18		Подвес V-образный для профнастила VPSM8 с гайкой M8			25	
19		Полка телескопическая 425MM 646505			3	
20		Полка телескопическая 825MM 646510			4	
21		Рамка 1 пост HDMI 754002			6	

22		Сейсмоцоколь 800x600x100MM R5ZE861SY			1	
23		DS-VD22D-B/HW5	The Hikvision DS-VD22D-B/HW5 was designed to accelerate application performance leveraging accelerator cards and storage scalability. The 2-socket, 2U platform has the optimum balance of resources to power the most demanding environments.	US\$7,245.20	1	US\$7,245.20
24		Угол внешний вертикаль ный 90 80x40MM			2	
25		Угол внутренний неизмен яемый			4	
26		Устройство удаленного м ониторинга NetPing Input+Relay v1			8	
27		Цоколь 600x800x100MM 646401			2	
28		Цоколь для шкафа ширин ой 600 мм			1	
29		Шина питания вилочная LEGR_404913			1	
30		DS-D2046LU-Y	<b>46-inch 3.5mm LCD Display Unit</b> 4K signal input, auto loop up to 30 screens with HDMI interfaces Switching between three picture modes: Monitoring, Meeting, and Movie Factory calibration for color and brightness uniformity Direct-lit LED backlight with uniform brightness and no boundary shadows 1920 × 1080 resolution, 178° viewing angle Ultra-narrow 3.5 mm bezel design Anti-glare, high definition, high brightness, high color gamut, and vivid images with rich colors Stable and 24-hour continuous working Metal casing for preventing from radiation and magnetic & electric field interference Wall-mount and modular brackets available to meet various installation requirements	US\$802.40	8	US\$6,419.20
Total					157	US\$43,607.00