



Адрес: РУз г.Ташкент м/в Белтепа 5/8 ИНН: 307 574 998 ОКЭД:95110  
Банковские реквизиты р/с: 2020 8000 2052 5488 3001 в  
o'zsanoatqurilishbank Toshkent viloyat mintaqaviy filiali МФО:00440  
+998 91 1324884/ +998 99 7100105 <https://pp.gl.uz>

## ООО "PROCESS PROGRAM"

Исх. №04/0624-1 от 04.06.2024г [100 085]

ООО "PROCESS PROGRAM" предоставляет Вашему вниманию технико-коммерческое предложение нижеуказанных товаров:

### Note:

- [1]. Если перечисленные товары сняты с производства, могут быть предложены новые обновленные/или аналоговые модели.
- [2]. По истечении срока действия предложения, предлагаемые цены могут быть изменены и это коммерческое предложение, будет предлагаться с новыми последними обновленными ценами
- [3]. Если контракт будет заключен сегодня, а оплата будет произведена через несколько месяцев, следует учитывать, что цена товаров может измениться. В связи с этим может потребоваться дополнительный платеж для соблюдения обновленных условий. Дополнительное соглашение будет заключено официально до или после доставки заказанных товаров.
- [1]. If items listed are discontinued, new updated/or analog models may be offered.
- [2]. After the expiration of the offer, the prices offered are subject to change and this quotation will be offered with new latest updated prices
- [3]. If the contract is made today and payment is to be made after several months, it should be noted that the price of the items may change. Consequently, an additional payment may be necessary to comply with the updated terms. The additional agreement will be made officially before or after the delivery of the ordered items.

**Условия оплаты: 100% предоплата** [или 30% предоплата, 60% по факту готовности товара, 10% после поставки]

**Условия и срок поставки:** г. Ташкент, срок доставки каждого товара указан отдельно\*

**Срок действия предложения:** 30 дней

Директор  
ООО "PROCESS PROGRAM"



Орзикулова К.С.

N	Заявка	Номенклатура	ТЭГ номер	BRAND	OFFERED ПРЕДЛАГАЕМЫЙ Товар	Ед. изм.	QTY Кол-во по заявке	Цена за шт без НДС, сум	Цена за сумм без НДС,сум	LEAD TIME	NOTE
1	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Блок системный Intel Xeon 2xE5-2620v4 DDR4 32ГБ SSD 500ГБ Nvidia Quadro M4000			Блок системный Intel Xeon 2xE5-2620v4 DDR4 32ГБ SSD 500ГБ Nvidia Quadro M4000	комп	5	49 872 900	249 364 500	40-65 дней	
2	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Видеосервер DS-AT1000S/480		HIKVISION	DS-AT1000S/450/25T DS-AT1000S/480 Stop production , replace with DSAT1000S/450/25T 24-slot Cost-efficient Super Capacity Storage 18*25 TB IoT SMR enterprise HDD IoT fully sealed helium HDD technology Surveillance-specialized direct storage (Direct Streaming mode) Highly cost efficient, safe and reliable Energy saving and space saving Easy operation and maintenance	шт	1	293 559 230	293 559 230	40-65 дней	
3	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Декодер DS-6916UDI (B)		HIKVISION	DS-6916UDI(B) 4K Decoder Provides HDMI (adaptable to DVI-D) and BNC output interfaces. Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for odd interface). Up to 8-ch decoding at 24 MP resolution. H.265+/H.265, H.264+/H.264, Hik264, MPEG4 and MJPEG video compression. PS, RTP, TS, ES, HIK encapsulation formats. Three encoding levels: baseline, main, and high-profile. G.722, G711A, G726, G711U, MPEG2-L2, and AAC audio compression. Two decoding modes: active decoding and passive decoding. Supports two-way audio via client software. Remote video files' decoding output. Provides VGA and DVI input interfaces. Supports window opening, window roaming and window split. Supports multi-screen control with PC installed with RSC server. Gets stream and decodes via URL and RTSP from encoding devices. Displays the decoded video stream on the video wall by directly linking cameras or by stream media forwarding. Configurable LED width and height parameters when the LED is connected. Regular and irregular virtual screen configurable to display multiple signal sources and get rid of the restriction of physical screen. Accessible by thermal network camera and you can view the temperature measurement, dynamic fire source detection, ship detection and VCA information in live view and playback. You can enable or disable the smart information for the thermal network camera. Port aggregation technology (Ethernet Channel). Accessible by 2.4 MP DeepinView camera	шт	3	35 731 450	107 194 350	40-65 дней	
4	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Жесткий диск HDD 20TB HC560 0F38755		WD	DC HC560 from Western Digital 20TB HDD	шт	24	8 139 430	195 346 320	40-65 дней	
6	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	КЛАВИАТУРА И МЫШЬ (S.927-2 OF 2)			Lenovo MK11 keyboard and wired mouse	шт	5	388 620	1 943 100	40-65 дней	
7	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Клавиатура управления беспроводной DS-1100KI(B)	Комплект	HIKVISION	DS-1100KI(B) Network Keyboard Divide video wall into regions to manage video wall by region open/close window, move window, resize window, divide window, and enlarge/narrow sub-window. Group and macro Preview camera live image on network keyboard touchscreen Quickly switch to the previous/next camera Control speed dome movement via joystick Play the decoder videos on video wall Play the video recorder videos on network keyboard touchscreen. Supports clipping and capturing during playback Add devices via SDK or ONVIF protocol HikCentral and KPS platforms access Support up to 32 users (1 administrator and 31 operators) and 4,000 devices Add/modify/delete cameras in batch Import/export configuration file	шт	3	12 781 280	38 343 840	40-65 дней	
8	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Комплект монтажный DS-K4H250-LZ		HIKVISION	DS-K4H250-LZ Pro Series Magnetic Lock Bracket <input type="checkbox"/> The LZ-bracket adopts aldural material with the surface sandblast <input type="checkbox"/> It is suitable for in-swing doors <input type="checkbox"/> The door opens towards inside at the angle of 90° <input type="checkbox"/> The bracket is suitable for magnetic lock of 300kg series <input type="checkbox"/> The shell is hard anodizing electroplating operated <input type="checkbox"/> The weight of the bracket is 0.75kg (1.58lb) <input type="checkbox"/> The dimension(L×W×H) of L-bracket is 250×47×28.5mm (9.84×1.85×1.12") <input type="checkbox"/> The dimension (L×W×H) of Z-bracket is 180×50×50mm (7.09×1.97×1.97") (ABK-280ZL)	комп	1	539 750	539 750	40-65 дней	
9	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Кронштейн настенный 762x473x85MM [DS-DN4655W/U]		HIKVISION	DS-DN4655W/U Wall-mounted Bracket Solid steel structure, preventing screen bending or twisting Cold-rolled steel plate (SPCC) Quick and easy installation	шт	8	2 202 180	17 617 440	40-65 дней	
12	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Монитор 27"	2 K 2560 x 1440 (16:9)		27" Monitor Screen size: 27 inches (615.5 x 361.1mm) Panel type: IPS Border type: Borderless Resolution: 1920 x 1080 (1K) Curvature: Planar Display color: 16.7M Color saturation: 99% sRGB Aspect ratio: 16:9 Brightness: 300cd/m2 Screen refresh rate (maximum): 75Hz Response time: 1ms Contrast: 1000:1 Visual angle: 178 °/178 ° Power consumption: 42W Standby power consumption: 0.5W	шт	8	2 785 110	22 280 880	40-65 дней	
15	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Оборуд.СДКО-Громкоговоритель потолочный 6 Вт/100 В (47944)	IP54, 1.5Вт; 3Вт; 6Вт.		Rated power: 6-10w Box material: ABS Input voltage: 70/100v Sensitivity: 90dB Frequency response: 100-18000Hz Speaker: High quality full frequency speaker Installation opening: 170mm External dimensions: 188 * 88mm	шт	24	734 060	17 617 440	40-65 дней	
23	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Сервер DS-VD22D-B/HW5	CUSTOMIZING 2 slot SFP+	HIKVISION	DS-VD22D-B/HW5 The Hikvision DS-VD22D-B/HW5 was designed to accelerate application performance leveraging accelerator cards and storage scalability. The 2-socket, 2U platform has the optimum balance of resources to power the most demanding environments.	шт	1	162 659 060	162 659 060	40-65 дней	NO CUSTOMIZED, because the order quantity is not enough to be customized
30	Заявка MOF3-PR-IT-PROJECT-0016 от 06.11.2023 9:33:21	Экран LCD 46" DS-D2046LU-Y		HIKVISION	DS-D2046LU-Y 46-inch 3.5mm LCD Display Unit 4K signal input, auto loop up to 30 screens with HDMI interfaces Switching between three picture modes: Monitoring, Meeting, and Movie Factory calibration for color and brightness uniformity Direct-lit LED backlight with uniform brightness and no boundary shadows 1920 × 1080 resolution, 178° viewing angle Ultra-narrow 3.5 mm bezel design Anti-glare, high definition, high brightness, high color gamut, and vivid images with rich colors Stable and 24-hour continuous working Metal casing for preventing from radiation and magnetic & electric field interference Wall-mount and modular brackets available to meet various installation requirements	комп	8	20 445 730	163 565 840	40-65 дней	
	ИТОГО:								1 270 031 750		