OOO "PROCESS PROGRAM"

Исх. №22/1124-1 от 22.11.2024г [99 115]

OOO "PROCESS PROGRAM" предоставляет Вашему **вниманию технико-коммерческое предложение** нижеуказанных товаров:

Note:

[1].Если перечисленные товары сняты с производства, могут быть предложены новые обновленные/или аналоговые модели.

[2].По истечении срока действия предложения, предлагаемые цены могут быть изменены и это коммерческое предложение, будет предлагаться с новыми последними обновленными ценами

[3].Если контракт будет заключен сегодня, а оплата будет произведена через несколько месяцев, следует учитывать, что цена товаров может измениться. В связи с этим может потребоваться дополнительный платеж для соблюдения обновленных условий. Дополнительное соглашение будет заключено официально до или после доставки заказанных товаров.

[4].Цены условно указаны в USD, все расчеты в документации осуществляются в узбекских сумах

Условия оплаты: 90% предоплата, 5% после уведомления о готовности товара на заводе-изготовителе, 5% после проведения инспекции товара на складе поставщика.

Условия и срок поставки: г. Ташкент, срок доставки каждого товара указан отдельно*

Срок действия предложения: 20 дней

Директор
ООО PROCESS PROGRAM   Орзикулова К.С.

Юридический адрес: Республика Узбекистан, г.Ташкент, массив Белтепа 5/8
ИНН: 307 574 998

ОКЭД: 95110
Т: +998 91 1324884/ +998 99 7100105

Банковские реквизиты:

Oʻzsanoatqurilishbank Uchtepa BXM
Адрес Банка: Тошкент шахри Учтепа тумани 12-мавзе, 3А уй
МФО 00440

X/r:

UZS	2020 8000 2052 5488 3001
USD	2020 8840 5052 5488 3001
EUR	2020 8978 9052 5488 3001
CNY	2020 8156 3052 5488 3001

No.	Номенклатура **OFFERED** Предлагаемый товар						Цена за шт без НДС, USD	Цена за СУММ без НДС, USD*	LEAD TIME	NOTE
No.	**Original Inquiry**	Proposal stock Model	Picture	Specification	QTY	Unit				
1	DS-7764NI-K4	DS-7764NI-M4		**64-ch 1.5U 8K NVR** H.265+/H.265/H.264+/H.264 video formats Up to 64-ch IP camera inputs Up to 2-ch@32 MP/2-ch@24 MP/4-ch@12 MP/8-ch@8 MP/16-ch@4 MP/32-ch@1080p decoding capacity Up to 400 Mbps incoming bandwidth and 400 Mbps outgoing bandwidth 2 HDMI and 1 VGA interfaces, 8K or dual 4K video outputs Up to 8-ch IP speakers can be connected	1	PCS	995.20	995.20	45-65 дней	
2	Монитор 27"	27" Monitor		Size:27 inch Resolution:1920 x 1080 Refresh rate:75 HZ Panel type:VA/TN Active Area:597.888(W) ×336.312(H) mm Dot Pitch:0.300 mm Aspect ratio:16:9 Backlight:LED Typical Brightness:MAX:300cd/M2 Contrast Ratio:1000:1 Color Temp. default:default:7500K 6500/7500/9300 Number of colors：16.7M Language Menu：7 languages max	2	PCS	272.00	544.00	45-65 дней	
3	Connector RJ45 UTP, 5E CAT	Cat 5E 3U Gold Plated UTP Connector		Samzhe Cat 5E 3U Gold Plated UTP Connector	2	BOX	38.00	76.00	45-65 дней	
4	Патч-корд UTP Cat 5e 1M	UTP Cat 5e 1m Patch Cord		Samzhe Cat5e Engineering/Home Patch Cord 1m	43	PCS	6.80	292.40	45-65 дней	
5	Патч-корд UTP Cat 5e 5M	UTP Cat 5e 5m Patch Cord		Samzhe Cat5e Engineering/Home Patch Cord 5m	3	PCS	12.40	37.20	45-65 дней	
6	Коммутатор управляемый уровня 2 SNR- S2982G-24T-POE-E 24 порта	HK-POE33028PFM		OVERVIEW The POE33028PFM is a Gigabit managed PoE fiber switch. It has 24*10/100/1000Base -T adaptive RJ45 ports and 4*100/1000Base-X uplink SFP fiber ports. Port 1-24 can support IEEE 802.3 af/at PoE standard and single-port PoE power up to 30W. As a PoE power supply device, it can automatically detect and identify powered devices that meet standards and power them through network cables. It can power PoE terminal equipment such as wireless AP, IP camera, IP telephone, and building visual access control intercoms through network cables to meet network environments that require high-density PoE power supply. It is suitable for hotels, campuses, parks, supermarkets, scenic spots, factory dormitories, and small and medium-sized enterprises to establish cost-effective networks. The POE33028PFM has L2+ network management functions. It can support IPV4 management and static routing forwarding, complete security protection mechanisms, complete ACL/ QoS policies, and rich VLAN functions, making it easy to manage and maintain. Supports multiple network redundancy protocols RSTP (<50ms) to improve link backup and network reliability. When a one-way network fails, communication can be quickly restored to ensure uninterrupted communication of important transmissions. According to application needs, PoE power supply management, port flow control, VLAN division, QoS, and other application service configurations can be performed through network management methods such as	1	PCS	520.80	520.80	45-65 дней	
7	DS-2CD2143G2 -IU	DS-2CD2143G2-IU		**4 MP AcuSense Built-in Mic Fixed Dome Network Camera** High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning	8	PCS	180.00	1 440.00	45-65 дней	
8	Патч-панель 24 port. UTP. 5e cat	24 panel port		24 panel port	3	PCS	54.00	162.00	45-65 дней	
9	Крепеж-клипса для трубы 20мм	20mm pipe clamp		Lesso PVC flame retardant conduit 20mm	866	PCS	0.36	311.76	45-65 дней	
10	Жесткий диск WD80PURX-78	WD82PURX-78		WD82PURX-78	4	PCS	348.00	1 392.00	45-65 дней	
11	Коммутатор управля емый SNR-S2982G-24T-POE 24 портов	HK-POE33028PFM		OVERVIEW The POE33028PFM is a Gigabit managed PoE fiber switch. It has 24*10/100/1000Base -T adaptive RJ45 ports and 4*100/1000Base-X uplink SFP fiber ports. Port 1-24 can support IEEE 802.3 af/at PoE standard and single-port PoE power up to 30W. As a PoE power supply device, it can automatically detect and identify powered devices that meet standards and power them through network cables. It can power PoE terminal equipment such as wireless AP, IP camera, IP telephone, and building visual access control intercoms through network cables to meet network environments that require high-density PoE power supply. It is suitable for hotels, campuses, parks, supermarkets, scenic spots, factory dormitories, and small and medium-sized enterprises to establish cost-effective networks. The POE33028PFM has L2+ network management functions. It can support IPV4 management and static routing forwarding, complete security protection mechanisms, complete ACL/ QoS policies, and rich VLAN functions, making it easy to manage and maintain. Supports multiple network redundancy protocols RSTP (<50ms) to improve link backup and network reliability. When a one-way network fails, communication can be quickly restored to ensure uninterrupted communication of important transmissions. According to application needs, PoE power supply management, port flow control, VLAN division, QoS, and other application service configurations can be performed through network	2	PCS	520.80	1 041.60	45-65 дней	
12	Металлорукав Р3-Ц Пнг-LS 20MM	Plastic coated hose		Plastic coated hose Inner diameter 19mm Outer diameter 20.5mm Material: Outer layer PVC coated, inner layer galvanized steel strip 20m/roll	5	ROLL	176.60	883.00	45-65 дней	

13	DS-1475ZJ-SUS	DS-1475ZJ-SUS		**Vertical pole mount** Vertical Pole Mount Stainless Steel Hikvision White	10	PCS	52.80	528.00	45-65 дней
14	MikroTik RB5009UPr+S+IN	MikroTik RB5009UPr+S+IN		RB5009UPr+S+IN A new version of our popular heavy-duty RB5009 router with PoE-in and PoE-out on all ports. Perfect for small and medium ISPs. 2.5 Gigabit Ethernet & 10 Gigabit SFP+, numerous powering options	1	PCS	642.80	642.80	45-65 дней
15	DS-2CD2047G2-L	DS-2CD2047G2H-LIU/SL (2.8mm)		**4 MP Smart Hybrid Light with ColorVu Fixed Mini Bullet Network Camera** High quality imaging with 4 MP resolution Smart Hybrid Light: advanced technology with long range Clear imaging against strong backlight due to 130 dB WDR technology Efficient H.265+ compression technology Focus on human and vehicle classification based on deep learning Active strobe light and audio alarm to warn intruders off Provide real-time security via built-in two-way audio Support on-board storage up to 512 GB (SD card slot) Water and dust resistant (IP67)	34	PCS	262.40	8 921.60	45-65 дней
16	DS-2702ZJ				7	PCS	0.00	0.00	45-65 дней
17	iDS-2CD7A45G0/P-IZHS(Y)	iDS-2CD7A46G0/P-IZHS(Y) (2.8mm-12mm)		**4MP DeepinView ANPR Moto Varifocal Bullet Camera** High quality imaging with 4 MP resolution Excellent low-light performance via DarkFighter technology Clear imaging against strong back light due to 140 dB WDR technology License Plate Recognition Efficient H.265+ compression technology to save bandwidth and storage 5 streams to meet a wide variety of applications Water and dust resistant (IP67) and vandal proof (IK10)	3	PCS	1 078.00	3 234.00	45-65 дней
18	Компьютер стационарный Intel Core i7- 12700F ОЗУ 32ГБ SSD 500ГБ Видеокарта Geforce RTX 3060Ti 8ГБ GS-600	Intel Core i7-1270F RAM 32GB SSD 500GB GeForce RTX 3060Ti 8GB GS-600		MSI H610M-S WIFI DDR4 motherboard i7-12700F Four copper tubes for heat dissipation Aigo 32g3200 Aigo P7000E-512G NVMe PCIe 4.0 Solid State Drive 7100/6300MB/S Rainbow Axe GeForce RTX 4060ti DUO 8GB AOC Armored A650B0/93 Active PFC Power Supply (Rated 650W) AOC CG265B Black Wide Body Side Transmitting RGB Magic Edition U3 Chassis	2	PCS	2 576.50	5 153.00	45-65 дней
19	DS-1280ZJ-XS	DS-1280ZJ-XS		**Junction box** Junction Box Aluminum Alloy Hikvision White	43	PCS	18.00	774.00	45-65 дней
20	Модуль оптический SFP-S1LC13-G- 1310-1550	SK1000-1.25G-SFP-40km		SK1000-1.25G-SFP-40km **SFP BIDI 1.25G 1310/1550nm(1550/1310nm)40KM Transceiver** Up to 1.25Gb/s data links DFB laser transmitter PIN photo-detector Up to 40KM on 9/125um SME Hot-pluggable SFP footprint BIDI LC/UPC type pluggable optical interface Low power dissipation Metal enclosure, for lower EMI RoHS compliant and lead-free Single +3.3V power supply Compliant with SFF-8472 Case operating temperature Commercial: 0°C to +70°C Extended: -10°C to +80°C Industrial: -40°C to +85°C	1	PAIR	72.00	72.00	45-65 дней
21	Модуль оптический SFP-S1LC13-G- 1550-1310	SK1000-1.25G-SFP-40km		SK1000-1.25G-SFP-40km **SFP BIDI 1.25G 1310/1550nm(1550/1310nm)40KM Transceiver** Up to 1.25Gb/s data links DFB laser transmitter PIN photo-detector Up to 40KM on 9/125um SME Hot-pluggable SFP footprint BIDI LC/UPC type pluggable optical interface Low power dissipation Metal enclosure, for lower EMI RoHS compliant and lead-free Single +3.3V power supply Compliant with SFF-8472 Case operating temperature Commercial: 0°C to +70°C Extended: -10°C to +80°C Industrial: -40°C to +85°C	1	PAIR	72.00	72.00	45-65 дней
22	Патч-корд оптический LC/UPC-LC/UPC SM 9/125 (OS2)	LC/UPC-LC/UPC 1M		LC/UPC-LC/UPC 1M	2	PCS	3.60	7.20	45-65 дней
23	Сетевой фильтр (пи лот)	PDU		Cabinet PDU 6-pole lightning protection PDU	2	PCS	92.00	184.00	45-65 дней
24	Клавиатура и компьютерная мышь	Keyboard and Mouse		Logitech MK200 Keyboard and Mouse	2	PCS	66.00	132.00	45-65 дней

№					Кол-во	Ед.	Цена	Сумма	Срок	
25	Гофротруба ГФ3 ф 20мм	Flame Retardant Plastic Pipe		ADP42.5 inner diameter 36mm 25 meters Material: Polypropylene Working humidity: -30 degrees Celsius+100 degrees Celsius, can reach+110 degrees Celsius in a short time Product structure: Both the interior and exterior are wavy Inner diameter * outer diameter (mm): 36 * 42.5 Bending radius (mm): 70	13	ROLL	94.00	1 222.00	45-65 дней	
26	Cabeus 19"Кабельный органайзер 1U с крышкой (метал)	24 port cable rack		24 port cable rack	2	PCS	40.00	80.00	45-65 дней	
27	Кабель HDMI 2m	HDMI 2M cable		HDMI 2M cable	2	PCS	11.20	22.40	45-65 дней	
	ИТОГО:							28 740.96		