

Concurrent Queue


Concurrent Programming

Introduction


- Bounded Lock-free Queue
- Evaluation
 - Queue with coarse-grained locking
 - Unbounded Lock-free Queue (covered in lecture note)
 - Bounded Lock-free Queue

Bounded lock-free queue


front 0 rear 0




Enqueue



Enqueue




Enqueue




| | | | | | |
|------|------|------|------|------|------|
| data | | | | | |
| flag | 0 | 0 | 0 | 0 | 0 |
| | Q[0] | Q[1] | Q[2] | Q[3] | Q[4] |


Enqueue




Enqueue



Deque




Deque




| | | | | | |
|------|------|------|------|------|------|
| data | A | B | | | |
| | 1 | 1 | 0 | 0 | 0 |
| | Q[0] | Q[1] | Q[2] | Q[3] | Q[4] |

Deque




| | | | | | |
|------|------|------|------|------|------|
| data | A | B | | | |
| | 1 | 1 | 0 | 0 | 0 |
| | Q[0] | Q[1] | Q[2] | Q[3] | Q[4] |


Deque




Deque




Deque



Deque




Deque




| | | | | | |
|------|------|------|------|------|------|
| data | A | B | | | |
| | 2 | 2 | 0 | 0 | 0 |
| | Q[0] | Q[1] | Q[2] | Q[3] | Q[4] |


Deque




Deque




Deque




Deque




Deque




Deque




Deque



Deque



Deque




Deque

front 3 rear 3


| | | | | | |
|------|------|------|------|------|------|
| data | A | B | C | | |
| | 2 | 2 | 2 | 0 | 0 |
| | Q[0] | Q[1] | Q[2] | Q[3] | Q[4] |

Deque




| | | | | | |
|------|------|------|------|------|------|
| data | A | B | C | | |
| | 2 | 2 | 2 | 0 | 0 |
| | Q[0] | Q[1] | Q[2] | Q[3] | Q[4] |

Dequeue




| | | | | | |
|------|------|------|------|------|------|
| data | A | B | C | | |
| flag | 2 | 2 | 2 | 0 | 0 |
| | Q[0] | Q[1] | Q[2] | Q[3] | Q[4] |


Deque




Deque




Deque




Deque




Deque




Deque




Deque



Deque



Dequeue




Enqueue


front 0 rear 0

| | | | | | |
|------|------|------|------|------|------|
| data | | | | | |
| flag | 0 | 0 | 0 | 0 | 0 |
| | Q[0] | Q[1] | Q[2] | Q[3] | Q[4] |


Enqueue




Enqueue




Enqueue




Enqueue



Enqueue



Enqueue



For the fairness, which thread should write the data first?

How can you implement it?

Evaluation

CPU: 24 x 2 (Hyperthreading enabled)

Number of producer / consumer threads: 16

Number of enqueue / dequeue operations per thread: 1,000,000

```
jongbin@multicore-24:~/TA/Multicore/lab13$ time ./queue_giantlock
CORRECT!

real    0m5.593s
user    0m4.432s
sys     2m49.276s
```

```
jongbin@multicore-24:~/TA/Multicore/lab13$ time ./queue_unbounded
CORRECT!

real    0m14.373s
user    7m3.264s
sys     0m8.220s
```

```
jongbin@multicore-24:~/TA/Multicore/lab13$ time ./queue_bounded
CORRECT!

real    0m1.972s
user    0m56.572s
sys     0m0.848s
```

Thank You
