

Chapter 1

Introduction

1.1 Introduction

1.1.1 Definitions

Lets list some definitions of Tensor. A Tensor T can be regarded as an element of a tensor product space

$$T \in \bigotimes_{j \in J} V^j$$

and we say T is a $|J|$ -legged tensor.

Given finite dimensional Vector spaces V and W , we have the identity that $V \otimes W^* \equiv \text{Hom}(W, V)$. Now, if we have a Tensor $T \in V_1 \otimes \cdots \otimes V_n$, and since for any Vector space V , $(V^*)^* = V$, we can peel off any number of V_i s, take their duals and represent T as a map

$$T : V_n^* \otimes \cdots \otimes V_{k+1}^* \rightarrow V_1 \otimes \cdots \otimes V_k$$

Note that we present the domain here in a contravariant fashion due to the contravariance of the dual.

Lets look at an example, let $t : V_1 \otimes V_2 \otimes W_2^* \otimes W_1^*$. We can represent as an operator in dirac notation:

$$t = \sum_{i_1, i_2, j_1, j_2} T_{j_1 j_2 i_1 i_2} |v_{i_1}\rangle |v_{i_2}\rangle \langle w_{j_1}| \langle w_{j_2}|$$

Graphically, we represent a general tensor

$$T : (W_n^* \otimes \cdots \otimes W_1) \rightarrow (V_1 \otimes V_2 \otimes \cdots \otimes V_n)$$

as follows, where we choose incoming arrows for duals in the domain and outgoings for normal spaces, and on the bottom we choose incoming for duals and outgoing for normals.

1.1.2 Review of Symmetric Tensor networks.

Generally, we follow the notations of [SV12], [Sch+20], [Sch+20], [Sch20] which gave an overview for implementing $SU(2)$ invariant tensor networks. A general overview for (Non)abelian symmetries is [SPV10], and a detailed account for the abelian $U(1)$ in [SPV11]. There are a multitude of implementations given in major packages, such as ITensor, [FWS22], Cyten, TenPy, [Hau+24], QSpace, [Wei24] ChemTensor, UniTensor, YasTn (Abelian Only) [Ram+25] (MP-SKit?), (Cytex (Abelian only i think.)). A general account of symmetries is given in [Unf24] with its respective implementation in [Hau+24] (We have to build cytens citation manually.)

1.1.3 Quantum Gates as Tensor Network Operators

As a sanity check, view this in context of a quantum circuit. A quantum circuit is defined as (unitary) map $(\mathbb{C}^2)^n \rightarrow (\mathbb{C}^2)^m$.

$$CNOT : C^2 \otimes C^2 \rightarrow C^2 \otimes C^2 = \sum_{ij} |i, i \oplus j\rangle \langle i, j|$$

$$H = \frac{1}{\sqrt{2}} \sum_{ij} (-1)^{ij} |i\rangle \langle j|$$

1.2 Symmetries

What do we know now? First of all, we take a symmetry group G that is finite and compact (why?)[For compact groups, representations are completely reducible (Maschke) and the irreps are finite aswell. Finite groups are contained in compact groups.]. Then we look for its unitary representation $U(G)$ on a Hilbert space H . Furthermore, if this is a multiparty hilbert space, lets say n sites, we view the unitary representations U_n at site n . The unitary representation $U_n : G \rightarrow Hom(V_n, V_n)$ is a covariant linear unitary map. A map $V_i \rightarrow V_j$ is symmetric if it is an intertwiner of the representations, i.e. the following diagram commutes:

$$\begin{array}{ccc} V_i & \xrightarrow{U_{V_i}(g)} & V_i \\ f \downarrow & & \downarrow f \\ V_j & \xrightarrow{U_{V_j}(g)} & V_j \end{array}$$

Note that here V_i is called a *symmetry space*.

Some examples of these groups include $U(1)$, $SU(2)$, $\mathbb{Z}_n$

Now where the intuition is more shaky: Consider a symmetry space V_i on a single site (why single). Then we get that it decomposes into a direct sum of irreps V_i^a ,

$$V_i = \bigoplus_a \bigoplus_{i=1}^{d_a} V_i^a$$

and we can easily construct an isomorphism (but this depends on choosing a basis for D_a .)

$$V_i = \bigoplus_a \bigoplus_{i=1}^{d_a} V_i^a = \bigoplus_a (D_a \otimes V_i^a).$$

Well, the isom we can construct here would look like $\bigoplus_1^{d_a} V_i^a \rightarrow D_a \otimes V_i^a$.

Consider a single site of 3 spin 1/2 particles. Under $SU(2)$ this decomposes as

$$2 \otimes 2 \otimes 2 = 4 \oplus 2 \oplus 2$$

Now consider that C^2 is just the fundamental representation of $SU(2)$.

Note here, an invariant subspace $W \subseteq V$ is a subset of vectors s.t. for all $U \in SU(2)$, $Uw \in W$.

symmetry obviously implies pullthrough properties, do Intertwiners as well?

Yes, because $U(V \otimes W) : g \rightarrow U_V(g) \otimes U_W(g)$ and the following diagram commutes:

$$\begin{array}{ccc} V_i \otimes V_j & \xrightarrow{U_{V_i \otimes V_j}(g)} & V_i \otimes V_j \\ T \downarrow & & \downarrow T \\ V_k & \xrightarrow{U_{V_k}(g)} & V_k \end{array}$$

1.2.1 Some Symmetry Groups

$\mathbb{Z}_n$

This group is given by integers $0, \dots, n-1$ with addition mod n . Since this happens to be abelian, all the irreps are 1 dimensional, i.e. $U_a(g) : g \rightarrow \text{Hom}(\mathbb{C}, \mathbb{C})$ with representatives $U_a(g) = z \mapsto e^{2\pi i a g / N} z$. What is the fusion rule here?

$$a \otimes b \equiv (c := a + b \mod n)$$

This also does not have fusion multiplicities.

The group $SU(2)$

Summarize the results from the paper here.

The group $SU(2)_3$

Technically this is a fusion category, the thesis [Unf24] handles this distinction. But if we think of this in terms of the programming guide, this seems to be doable using a group.

Now, since we can argue that Products of symmetry groups again form a symmetry group (proof?), we would also need another type for sector.

We could use `classSector(NamedTuple)` holding an array charges.

1.2.2 Notes on structural tensors and fusion trees

What do the CG tensors look like? As they are three index and have no intermediates, these are simply $Q_{j_1, j_2, j_3} = (C^{fuse})_{(j_1, m_{j_1}), (j_2, m_{j_2})}^{(j_3, m_{j_3})}$.

1.2.3 Notes on the papers

Lets assume we only look at incoming legs, i.e. we look at T_{j_a, j_b, j_c} in a composite vectors space $V^a \otimes V^b \otimes V^c$. By the decomposition

$$V^a \otimes V^b \otimes V^c = \left(\bigoplus_{j_a} D_{j_a} \otimes V_{j_a} \right) \otimes \left(\bigoplus_{j_b} D_{j_b} \otimes V_{j_b} \right) \otimes \left(\bigoplus_{j_c} D_{j_c} \otimes V_{j_c} \right)$$

and we can represent a single index inside the block space

$$T_{j_a, j_b, j_c} \in (D_{j_a j_b j_c} \otimes V_{j_a j_b j_c})$$

Choosning a basis $t = (t_{j_a}, t_{j_b}, t_{j_c})$ and $m = (m_{j_a}, m_{j_b}, m_{j_c})$ we can write

$$T_{j_a, j_b, j_c} = \sum_{t, n} (T_{j_a, j_b, j_c})_{t, m} (|t\rangle \otimes |m\rangle)$$

Now we can use Wigner-Eckart to obtain

$$\begin{aligned} T_{j_a, j_b, j_c} &= \sum_{t, n} ((P_{j_a j_b j_c})_t \cdot (Q_{j_a j_b j_c})_m)_{t, m} (|t\rangle \otimes |m\rangle) \\ &= \left(\sum_t (P_{j_a j_b j_c})_t |t\rangle \right) \otimes \left(\sum_m (Q_{j_a j_b j_c})_m |m\rangle \right) = P_{j_a j_b j_c} \otimes Q_{j_a j_b j_c} \end{aligned}$$

If we generalize this with the decomposition for k indices $i = (i_1, i_2, \dots, i_k)$ and let $j_e = (j_{e_1}, j_{e_2}, \dots, j_{e_{k-3}})$ be the internals

$$T_i = \sum_{j_e} (P_j^{j_e})_t \cdot (Q_j^{j_e})_m$$

1.2.4 Q intertwiners

Lets look at 2 paths for the 4 index tensor, $(a, b, c \rightarrow d)$ and $(a, b \rightarrow c, d)$.

$$(Q_{j_a j_b j_c}^{j_e})_{m_1, m_2, m_3, m_4} = \sum_{m_e} \langle j_1 m_1; j_2 m_2 | j_e m_e \rangle \langle j_e m_e; j_3 m_3 | j_4 m_4 \rangle$$

while the other topology would look like

$$Q \dots = \sum_{m_e} \langle j_1 m_1; j_2 m_2 | j_e m_e \rangle \langle j_e m_e | j_3 m_3; j_4 m_4 \rangle$$

and as an operator this would have to live in $Hom(V_{j_1} \otimes V_{j_2}, V_{j_3} \otimes V_{j_4})$

The yoga tree $(-1, 1, -3), (-2, 1, -4)$ Gives us a good mixture of those. This Q would then have to look like

$$Q_{-1-2-3-4}^1 = \sum_1 \langle j_{-1} m_{-1}; j_1 m_1 | j_{-3} m_{-3} \rangle \langle j_{-2} m_{-2}; j_1 m_1; j_{-4} m_{-4} \rangle = \sum_{m_1} C_{-1,1 \rightarrow -3} \cdot C_{-2,1 \rightarrow -4}$$

How would we do this when we have a contraction of two simultaneous indices:

$$Q_{-1-2}^{1,2} = \sum_{1,2} \langle -1 | 1; 2 \rangle \langle 1; 2 | -2 \rangle$$

If we define τ to be the fusion trees topology, then we can define ${}_{\tau}Q_j^i$

What would this look like for general symmetry groups G ? Lets choose a basis of its invariant decomp $|\lambda_a \mu_a \mu_a\rangle$. Then the generalized CG coefficient would look like

$$(C_{\lambda_a \lambda_b \rightarrow \lambda_c}^{\alpha})_{\mu_a \mu_b}^{\mu_c} = \langle \lambda_a \mu_a; \lambda_b \mu_b | \lambda_c \mu_c \rangle_{\alpha}$$

where alpha denotes the singular fusion multiplicity at μ_c .

Now to fully specify Q here for k sectors (λ_i, μ_i) , we need to give it $k - 3$ internal edges $(\lambda_{e_1}, \dots, \lambda_{e_{k-3}})$ along with $k - 2$ mulitplicity symbols, $(\alpha_1, \dots, \alpha_{k-2})$

Can we write down a general formula for Q ?

This would then be

$$Q_{\lambda}$$

1.3 implementation

We want to be able to represent a traditional tensor op such as

```
1 np.einsum("ijklmn,nkol -> ijmo", a, b)
```

for symmetric tensors. As we want to reuse code from existing libraries that is written using numpy, it would be ideal to write our classes in a way that would only require substituting *np* for our own libraries *snp*. Towards this goal we define an abstractclass `Tensor`

```

1 class Tensor(abc.ABC):
2     ...
3     @abstractmethod
4     def transpose(cls, new_shape:list[int]): ...
5     ...

```

and we implement both an *np* wrapper *NPTensor* and our symmetric *Tensor* as *STensor*, i.e.

```

1 class STensor(Tensor):
2
3     def __init__(self, ...):
4         self.open_legs:list[int|str]
5         self.fusion_tree:FusionTree(self.open_legs, ...)
6         ...
7     @abstractmethod
8     def transpose(cls, new_shape:list[int]): ...
9     ...

```

Bibliography

- [FWS22] Matthew Fishman, Steven R. White, and E. Miles Stoudenmire. *The ITensor Software Library for Tensor Network Calculations*. In: *SciPost Phys. Codebases* (2022), p. 4. [[doi:10.21468/SciPostPhysCodeb.4](https://doi.org/10.21468/SciPostPhysCodeb.4)], [<https://arxiv.org/abs/2007.14822>].
- [Hau+24] Johannes Hauschild et al. *Tensor Network Python (TeNPy) Version 1*. In: *SciPost Phys. Codebases* (2024), p. 41. [[doi:10.21468/SciPostPhysCodeb.41](https://doi.org/10.21468/SciPostPhysCodeb.41)], [<https://scipost.org/10.21468/SciPostPhysCodeb.41>].
- [Ram+25] Marek M. Rams, Gabriela Wójtowicz, Aritra Sinha, and Juraj Hasik. *YASTN: Yet Another Symmetric Tensor Networks; A Python Library for Abelian Symmetric Tensor Network Calculations*. In: *SciPost Phys. Codebases* (2025), p. 52. [[doi:10.21468/SciPostPhysCodeb.52](https://doi.org/10.21468/SciPostPhysCodeb.52)], [<https://scipost.org/10.21468/SciPostPhysCodeb.52>].
- [Sch+20] Philipp Schmoll, Sukhbinder Singh, Matteo Rizzi, and Román Orús. *A Programming Guide for Tensor Networks with Global $SU(2)$ Symmetry*. In: *Annals of Physics* 419 (Aug. 1, 2020), p. 168232. [[doi:10.1016/j.aop.2020.168232](https://doi.org/10.1016/j.aop.2020.168232)], [<https://www.sciencedirect.com/science/article/pii/S0003491620301664>].
- [Sch20] Philipp Schmoll. *Tensor Network Simulations with Global $SU(2)$ Symmetry*. Mainz: Johannes Gutenberg University, July 2020. 150 pp., [<https://openscience.ub.uni-mainz.de/server/api/core/bitstreams/d9d9ca4e-46c8-4a8e-a831-7611475d2504/content>].
- [SPV10] Sukhwinder Singh, Robert N. C. Pfeifer, and Guifre Vidal. *Tensor Network Decompositions in the Presence of a Global Symmetry*. In: *Physical Review A* 82.5 (Nov. 8, 2010), p. 050301. [[doi:10.1103/PhysRevA.82.050301](https://doi.org/10.1103/PhysRevA.82.050301)], arXiv: 0907.2994 (cond-mat.str-el), [<http://arxiv.org/abs/0907.2994>].
- [SPV11] Sukhwinder Singh, Robert N. C. Pfeifer, and Guifre Vidal. *Tensor Network States and Algorithms in the Presence of a Global $U(1)$ Symmetry*. In: *Physical Review B* 83.11 (Mar. 15, 2011), p. 115125. [[doi:10.1103/PhysRevB.83.115125](https://doi.org/10.1103/PhysRevB.83.115125)], [<https://arxiv.org/abs/1008.4774>].

- [SV12] Sukhwinder Singh and Guifre Vidal. *Tensor Network States and Algorithms in the Presence of a Global $SU(2)$ Symmetry*. In: *Physical Review B* 86.19 (Nov. 9, 2012), p. 195114. [[doi:10.1103/PhysRevB.86.195114](https://doi.org/10.1103/PhysRevB.86.195114)], [<https://arxiv.org/abs/1208.3919v1>].
- [Unf24] Jakob Unfried. *Advancing Tensor Network Simulations* -. PhD thesis. Technische Universität München, 2024, p. 208, [<https://mediatum.ub.tum.de/1755273>].
- [Wei24] Andreas Weichselbaum. *QSpace - An Open-Source Tensor Library for Abelian and Non-Abelian Symmetries*. In: *SciPost Physics Codebases* (Nov. 14, 2024), p. 40. [[doi:10.21468/SciPostPhysCodeb.40](https://doi.org/10.21468/SciPostPhysCodeb.40)], [<https://scipost.org/10.21468/SciPostPhysCodeb.40>].