OnCore REST API Specification

Version 2025.4

CONFIDENTIAL

Table of Contents

URI scheme . . . 1
Operations . . . 1
ContactCredentials . . . 1
Search for contact credentials . . . 1
Contacts . . . 1
Create a contact . . . 1
Get a contact by its ID . . . 2
Search for contacts . . . 3
Update the contact . . . 4
ProtocolAttachments . . . 4
Create a protocol attachment . . . 4
Delete a protocol attachment . . . 5
Download a protocol attachment . . . 6
Search for protocol attachments . . . 7
Update a protocol attachment . . . 7
ProtocolConsents . . . 8
Search for protocol consents . . . 8
ProtocolEprmsSubmissions . . . 9
Create a protocol ePRMS submission . . . 9
Search for protocol ePRMS submissions . . . 9
ProtocolIde . . . 10
Add an investigational device record to a protocol . . . 10
Search for investigational devices on a protocol . . . 11
Update the investigational device record . . . 11
ProtocolInd . . . 12
Add an investigational drug record to a protocol . . . 12
Search for investigational drugs on a protocol . . . 13
Update the investigational drug record . . . 13
ProtocolInstitutionIrbReviewCommunications . . . 14
Add a communication record to the protocol institution IRB review . . . 14
Search for protocol institution IRB review communications . . . 14
Update the protocol institution IRB review communication record . . . 15
ProtocolInstitutionIrbReviewDetails . . . 16
Add a protocol institution IRB review attachment . . . 16
Add a detail record to the protocol institution IRB review . . . 17
Delete a protocol institution IRB review attachment . . . 17
Download a protocol institution IRB review detail attachment . . . 18
Retrieve the attachment information for a protocol institution IRB review detail record . . . 19
Search for protocol institution IRB review details . . . 19

Update the protocol institution IRB review detail record . . . 20
ProtocolInstitutionIrbReviewReviewers . . . 20
Add a reviewer to the protocol institution IRB review . . . 20
Search for protocol institution IRB review reviewers . . . 21
ProtocolInstitutionIrbReviews . . . 22
Add a protocol institution IRB review . . . 22
Get a protocol institution IRB review by its ID . . . 22
Search for protocol institution IRB reviews . . . 23
Update a protocol institution IRB review . . . 24
ProtocolInstitutions . . . 25
Add an institution to the protocol . . . 25
Retrieve all institutions participating on the given protocol . . . 25
Update the protocol institution record . . . 26
ProtocolIrbReviewCommunications . . . 27
Add a communication record to the IRB review . . . 27
Search for protocol IRB review communications . . . 27
Update the protocol IRB review communication record . . . 28
ProtocolIrbReviewDetails . . . 29
Add a protocol IRB review attachment . . . 29
Add a detail record to the IRB review . . . 30
Delete a protocol IRB review attachment . . . 30
Download a protocol IRB review detail attachment . . . 31
Retrieve the attachment information for a protocol IRB review detail record . . . 32
Search for protocol IRB review details . . . 32
Update the protocol IRB review detail record . . . 33
ProtocolIrbReviewReviewers . . . 34
Add a reviewer to the IRB review . . . 34
Search for protocol IRB review reviewers . . . 34
ProtocolIrbReviews . . . 35
Add a protocol IRB review . . . 35
Get a protocol IRB review by its ID . . . 36
Search for protocol IRB reviews . . . 37
Update a protocol IRB review . . . 37
ProtocolManagementDetails . . . 38
Search for protocol management details . . . 38
Get management details by protocol ID . . . 39
Update protocol management details . . . 39
ProtocolPrmcReviewCommunications . . . 40
Add a communication record to the PRMC review . . . 40
Search for protocol PRMC review communications . . . 41
Update the protocol PRMC review communication record . . . 41

ProtocolPrmcReviewDetails . . . 42
Add a detail record to the PRMC review . . . 42
Search for protocol PRMC review details . . . 43
Update the protocol PRMC review detail record . . . 43
ProtocolPrmcReviewReviewers . . . 44
Add a reviewer to the PRMC review . . . 44
Search for protocol PRMC review reviewers . . . 45
ProtocolPrmcReviews . . . 45
Add a protocol PRMC review . . . 45
Get a protocol PRMC review by its ID . . . 46
Search for protocol PRMC reviews . . . 47
Update a protocol PRMC review . . . 47
ProtocolSipConfiguration . . . 48
Get a protocol ARP/SIP configuration by protocol ID . . . 48
Update the protocol ARP/SIP configuration . . . 49
ProtocolSponsors . . . 49
Add a protocol sponsor to the protocol . . . 49
Search for protocol sponsors . . . 50
Update the protocol sponsor . . . 51
ProtocolStaff . . . 51
Add protocol staff . . . 51
Search for protocol staff . . . 52
Get a protocol staff by its ID . . . 53
Update protocol staff . . . 53
ProtocolStatus . . . 54
Set a protocol status . . . 54
Delete a specified protocol status . . . 55
Get the next available protocol statuses for the given protocol . . . 56
ProtocolSubjectAttachments . . . 57
Download a protocol subject attachment . . . 57
Get a protocol subject attachment . . . 57
Search for protocol subject attachments . . . 58
ProtocolSubjectConsents . . . 59
Add a protocol consent to a subject . . . 59
Search for subject consents . . . 59
ProtocolSubjectOnStudy . . . 60
Get protocol subject on study information by ID . . . 60
Update protocol subject on study information by ID . . . 61
ProtocolSubjectTreatments . . . 62
Get treatment details by protocol subject ID . . . 62
ProtocolSubjects . . . 62

Add a subject to a protocol . . . 62
Search for protocol subjects for the given protocol . . . 63
ProtocolSummaryAccruals . . . 64
Add a summary accrual to the protocol . . . 64
Delete a protocol summary accrual . . . 64
Search for protocol summary accruals . . . 65
ProtocolTaskLists . . . 66
Search for protocol task lists . . . 66
ProtocolTasks . . . 66
Search for protocol tasks . . . 66
Update a protocol task . . . 67
ProtocolTreatment . . . 68
Get treatment details by protocol ID . . . 68
Protocols . . . 68
Create a protocol . . . 68
Get a protocol by its ID . . . 69
Search for protocols . . . 70
Update a protocol . . . 70
SponsorAddresses . . . 71
Add an address to a sponsor . . . 71
Search for sponsor addresses . . . 72
Update a sponsor address . . . 72
SponsorGrants . . . 73
Create a sponsor grant . . . 73
Search for sponsor grants . . . 73
Update a sponsor grant . . . 74
Sponsors . . . 75
Create a sponsor . . . 75
Get a sponsor by its ID . . . 75
Search for sponsors . . . 76
Update the sponsor . . . 77
SubjectDemographics . . . 77
Search for subject demographics . . . 77
Get subject demographics by ID . . . 78
Definitions . . . 79
AdministrativeGroups . . . 79
ConstraintViolationError . . . 79
Contact . . . 79
ContactCredential . . . 80
ContactNumber . . . 81
FieldValidationError . . . 81

CONFIDENTIAL

Group . . . 81
Identifier . . . 82
InvalidField . . . 82
IrbReviewAttachment . . . 82
IrbReviewCommunication . . . 82
IrbReviewReviewer . . . 83
MessageError . . . 84
Protocol . . . 84
ProtocolAttachment . . . 87
ProtocolConsent . . . 88
ProtocolEprmsSubmission . . . 88
ProtocolIde . . . 89
ProtocolInd . . . 90
ProtocolInstitution . . . 92
ProtocolInstitutionIrbReview . . . 92
ProtocolInstitutionIrbReviewDetail . . . 93
ProtocolIrbReview . . . 94
ProtocolIrbReviewDetail . . . 95
ProtocolManagementDetails . . . 96
ProtocolPrmcReview . . . 97
ProtocolPrmcReviewCommunication . . . 98
ProtocolPrmcReviewDetail . . . 98
ProtocolPrmcReviewReviewer . . . 99
ProtocolSipConfiguration . . . 99
ProtocolSponsor . . . 100
ProtocolStaff . . . 101
ProtocolStatusChange . . . 102
ProtocolStatusInquiry . . . 102
ProtocolSubject . . . 103
ProtocolSubjectAttachment . . . 103
ProtocolSubjectConsent . . . 104
ProtocolSubjectIdentifier . . . 104
ProtocolSubjectOnStudy . . . 105
ProtocolSubjectTreatment . . . 105
ProtocolSummaryAccrual . . . 106
ProtocolTask . . . 107
ProtocolTaskList . . . 107
ProtocolTreatment . . . 108
ProtocolTreatmentArm . . . 108
ProtocolTreatmentLevel . . . 108
ProtocolTreatmentStep . . . 109

Sponsor 109
SponsorAddress 109
SponsorGrant 110
SubjectDemographics 111
SubjectIdentifier 113
UpdateError 113

CONFIDENTIAL

URI scheme

```
BasePath: /oncore-api/rest
```

Operations

ContactCredentials

Search for contact credentials

```
GET /contactCredentials
```

Description

Returns a list of contact credentials matching the given search criteria.

Required Permissions

Administration > Contacts - View
Administration > Contacts - Credentials - View

Request Parameters

Type	Name	Description	Default	Schema
Query	**contactId** *required*	The contact ID.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of contact credentials matching the given search criteria.	< ContactCredential > array
400	Message error.	MessageError

Contacts

Create a contact

```
POST /contacts
```


CONFIDENTIAL

Required Permissions

Administration > Contacts - Add

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**contacts** *required*			Contact

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Get a contact by its ID

```
GET /contacts/{contactId}
```

Description

Returns the contact with the given ID.

Required Permissions

Administration > Contacts - View
Administration > Contacts - User Account Details - View

Request Parameters

Type	Name	Description	Default	Schema
Path	**contactId** *required*		`null`	integer

Response Body `application/json`

CONFIDENTIAL

HTTP Code	Description	Schema
200	The contact matching the given ID.	Contact
400	Message error.	MessageError

Search for contacts

```
GET /contacts
```

Description

Returns a list of contacts matching the given search criteria. Requires email, or contactIdentifier and contactIdentifierType, or lastName and homeOrganization. Other parameters are used to further filter the returned list of contacts. All name parameters are treated as exact matches.

Required Permissions

Administration > Contacts - View
Administration > Contacts - User Account Details - View

Request Parameters

Type	Name	Description	Default	Schema
Query	**contactIdentifier** *optional*		`null`	string
Query	**contactIdentifierType** *optional*	The Contact Identifier Type reference list description.	`null`	string
Query	**email** *optional*		`null`	string
Query	**firstName** *optional*		`null`	string
Query	**middleName** *optional*		`null`	string
Query	**lastName** *optional*		`null`	string
Query	**homeOrganization** *optional*	The contact's home organization name.	`null`	string
Query	**activeContact** *optional*		`null`	boolean

CONFIDENTIAL

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of contacts matching the search criteria.	< Contact > array
400	Message error.	MessageError

Update the contact

```
PUT /contacts/{contactId}
```

Required Permissions

Administration > Contacts - Edit
Administration > Contacts - User Account Details - Edit

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**contactId** *required*		`null`	integer
Body	**contacts** *required*			Contact

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolAttachments

Create a protocol attachment

```
POST /protocolAttachments
```

Required Permissions

Consoles > PC Console

CONFIDENTIAL

Protocol > Attachments/Links
Protocol > Attachments/Links Update

Request Body `multipart/form-data`

Type	Name	Description	Default	Schema
FormData	**protocolAttachment** *required*	A JSON serialized protocol attachment.	`null`	string
FormData	**attachmentFile** *optional*	If provided, the attachment file must have a fileName and the URL must be null. The file size must be less than or equal to OnCore's maximum file size, set in the MAX_FILE_UPLOAD_SIZE setting in the environment.conf file on the server.	`null`	file

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Delete a protocol attachment

```
DELETE /protocolAttachments/{protocolAttachmentId}
```

Description

Deletes the given protocol attachment record.

Required Permissions

Consoles > PC Console
Protocol > Attachments/Links
Protocol > Attachments/Links Update

Request Parameters

CONFIDENTIAL

Type	Name	Description	Default	Schema
Path	**protocolAttachmentId** *required*	ID of the protocol attachment.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully deleted.	No Content
400	Message error.	MessageError

Download a protocol attachment

```
GET /protocolAttachments/{protocolAttachmentId}/download
```

Description

Downloads a protocol attachment file.

Required Permissions

Consoles > PC Console
Protocol > Attachments/Links

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolAttachmentId** *required*	ID of the protocol attachment.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The contents of the protocol attachment. **Headers:** `content-disposition` (string): The file name of the protocol attachment. Example: attachment; filename="example.pdf" `content-type` (string): The content type of the protocol attachment. Example: application/pdf `content-length` (long): The size of the protocol attachment in bytes. Example: 123456	file

HTTP Code	Description	Schema
400	Message error.	MessageError

Search for protocol attachments

```
GET /protocolAttachments
```

Description

Returns a list of protocol attachments matching the given search criteria.

Required Permissions

Consoles > PC Console
Protocol > Attachments/Links

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of protocol attachments matching the given search criteria.	< ProtocolAttachment > array
400	Message error.	MessageError

Update a protocol attachment

```
PUT /protocolAttachments/{protocolAttachmentId}
```

Required Permissions

Consoles > PC Console
Protocol > Attachments/Links
Protocol > Attachments/Links Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolAttachmentId** *required*	ID of the protocol attachment.	`null`	integer
Body	**protocolAttachment** *required*			ProtocolAttachment

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolConsents

Search for protocol consents

```
GET /protocolConsents
```

Description

Returns all protocol consents for a given protocol ID.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	ID of the protocol.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all consents on the protocol.	< ProtocolConsent > array

CONFIDENTIAL

HTTP Code	Description	Schema
400	Message error.	MessageError

ProtocolEprmsSubmissions

Create a protocol ePRMS submission

```
POST /protocolEprmsSubmissions
```

Required Permissions

Consoles > PC Console
Consoles > ePRMS Submission Console

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolEprmsSubmission** *required*			ProtocolEprmsSubmission

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol ePRMS submissions

```
GET /protocolEprmsSubmissions
```

Description

Returns a list of protocol ePRMS submissions for the given protocol ID.

CONFIDENTIAL

Required Permissions

Consoles > PC Console
Consoles > ePRMS Submission Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	ID of the protocol.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of ePRMS submissions on the protocol.	< ProtocolEprmsSubmission > array
400	Message error.	MessageError

ProtocolIde

Add an investigational device record to a protocol

```
POST /protocolIde
```

Required Permissions

Consoles > PC Console
Protocol > Investigative Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolIde** *required*			ProtocolIde

Response Body `application/json`

CONFIDENTIAL

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for investigational devices on a protocol

```
GET /protocolIde
```

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all investigational devices on the protocol.	< ProtocolIde > array
400	Message error.	MessageError

Update the investigational device record

```
PUT /protocolIde/{protocolIdeId}
```

Required Permissions

Consoles > PC Console
Protocol > Investigative Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolIdeId** *required*	ID of the protocol investigational device record.	`null`	integer
Body	**protocolIde** *required*			ProtocolIde

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolInd

Add an investigational drug record to a protocol

```
POST /protocolInd
```

Required Permissions

Consoles > PC Console
Protocol > Investigative Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolInd** *required*			ProtocolInd

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

CONFIDENTIAL

Search for investigational drugs on a protocol

```
GET /protocolInd
```

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all investigational drugs on the protocol.	< ProtocolInd > array
400	Message error.	MessageError

Update the investigational drug record

```
PUT /protocolInd/{protocolIndId}
```

Required Permissions

Consoles > PC Console
Protocol > Investigative Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolIndId** *required*	ID of the investigational drug record.	`null`	integer
Body	**protocolInd** *required*			ProtocolInd

Response Body `application/json`

CONFIDENTIAL

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolInstitutionIrbReviewCommunications

Add a communication record to the protocol institution IRB review

```
POST /protocolInstitutionIrbReviewCommunications
```

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**irbReviewCommunication** *required*			IrbReviewCommunication

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol institution IRB review communications

```
GET /protocolInstitutionIrbReviewCommunications
```

Required Permissions

Consoles > PC Console

CONFIDENTIAL

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolInstitutionIrbReviewId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all communications on the protocol institution IRB review.	< IrbReviewCommunication > array
400	Message error.	MessageError

Update the protocol institution IRB review communication record

```
PUT /protocolInstitutionIrbReviewCommunications/{irbReviewCommunicationId}
```

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**irbReviewCommunicationId** *required*	ID of the protocol institution IRB review communication record.	`null`	integer
Body	**irbReviewCommunication** *required*			IrbReviewCommunication

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

CONFIDENTIAL

ProtocolInstitutionIrbReviewDetails

Add a protocol institution IRB review attachment

```
POST /protocolInstitutionIrbReviewDetails/{irbReviewDetailId}/attachment
```

Description

An attachment can only be created if one does not already exist for the IRB review detail record.

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews

Request Body `multipart/form-data`

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol institution IRB review detail record.	`null`	integer
FormData	**irbReviewAttachment** *required*	A JSON serialized irbReviewAttachment.	`null`	string
FormData	**attachmentFile** *optional*	If provided, the irbReviewAttachment must have a fileName and the URL must be null. The file size must be less than or equal to OnCore's maximum file size, set in the MAX_FILE_UPLOAD_SIZE setting in the environment.conf file on the server.	`null`	file

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError
404	Returns Not Found if the IRB review detail does not exist.	No Content

CONFIDENTIAL

Add a detail record to the protocol institution IRB review

```
POST /protocolInstitutionIrbReviewDetails
```

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**irbReviewDetail** *required*			ProtocolInstitutionIrbReviewDetail

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Delete a protocol institution IRB review attachment

```
DELETE /protocolInstitutionIrbReviewDetails/{irbReviewDetailId}/attachment
```

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews

Request Parameters

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol institution IRB review detail record.	`null`	integer

CONFIDENTIAL

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully deleted.	No Content
400	Message error.	MessageError
404	Returns Not Found if no attachment is associated with the IRB review detail or the IRB review detail does not exist.	No Content

Download a protocol institution IRB review detail attachment

```
GET /protocolInstitutionIrbReviewDetails/{irbReviewDetailId}/attachment/download
```

Description

Downloads a protocol institution IRB review detail attachment.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol institution IRB review detail record.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The contents of the institution IRB review detail attachment. **Headers:** `content-disposition` (string): The file name of the institution IRB review detail attachment. Example: attachment; filename="example.pdf" `content-type` (string): The content type of the institution IRB review detail attachment. Example: application/pdf `content-length` (long): The size of the institution IRB review detail attachment in bytes. Example: 123456	file
400	Message error.	MessageError

Retrieve the attachment information for a protocol institution IRB review detail record

```
GET /protocolInstitutionIrbReviewDetails/{irbReviewDetailId}/attachment
```

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol institution IRB review detail record.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The attachment associated with the IRB review detail, if one exists.	IrbReviewAttachment
400	Message error.	MessageError
404	Returns Not Found if no attachment is associated with the IRB review detail or the IRB review detail does not exist.	No Content

Search for protocol institution IRB review details

```
GET /protocolInstitutionIrbReviewDetails
```

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolInstitutionIrbReviewId** *required*		`null`	integer

Response Body `application/json`

CONFIDENTIAL

HTTP Code	Description	Schema
200	A list of all details on the IRB review.	< ProtocolInstitutionIrbReviewDetail > array
400	Message error.	MessageError

Update the protocol institution IRB review detail record

```
PUT /protocolInstitutionIrbReviewDetails/{irbReviewDetailId}
```

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol institution IRB review detail record.	`null`	integer
Body	**irbReviewDetail** *required*			ProtocolInstitutionIrbReviewDetail

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolInstitutionIrbReviewReviewers

Add a reviewer to the protocol institution IRB review

```
POST /protocolInstitutionIrbReviewReviewers
```


CONFIDENTIAL

Description

Adds a reviewer to the protocol institution IRB review.

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews
Reviews > IRB Reviewer
Reviews > IRB Reviewer Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**irbReviewReviewer** *required*			IrbReviewReviewer

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol institution IRB review reviewers

```
GET /protocolInstitutionIrbReviewReviewers
```

Required Permissions

Consoles > PC Console
Reviews > IRB Reviewer

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolInstitutionIrbReviewId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all reviewers on the protocol institution IRB review.	< IrbReviewReviewer > array
400	Message error.	MessageError

ProtocolInstitutionIrbReviews

Add a protocol institution IRB review

```
POST /protocolInstitutionIrbReviews
```

Description

Adds an IRB review to the protocol affiliate institution.

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolInstitutionIrbReview** *required*			ProtocolInstitutionIrbReview

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Get a protocol institution IRB review by its ID

CONFIDENTIAL

```
GET /protocolInstitutionIrbReviews/{protocolInstitutionIrbReviewId}
```

Description

Returns the protocol affiliate institution IRB review record with the given ID.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolInstitutionIrbReviewId** *required*	ID of the protocol affiliate institution IRB review.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Details for the protocol IRB review matching the given ID.	ProtocolInstitutionIrbReview
400	Message error.	MessageError

Search for protocol institution IRB reviews

```
GET /protocolInstitutionIrbReviews
```

Description

Returns all protocol affiliate institution IRB reviews matching the search criteria.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*		`null`	integer

Type	Name	Description	Default	Schema
Query	**institution** *required*	The name of the affiliate institution on the protocol.	`null`	string

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all IRB reviews on the protocol affiliate institution.	< ProtocolInstitutionIrbReview > array
400	Message error.	MessageError

Update a protocol institution IRB review

```
PUT /protocolInstitutionIrbReviews/{protocolInstitutionIrbReviewId}
```

Description

Updates the protocol affiliate institution IRB review.

Required Permissions

Consoles > PC Console
Reviews > Update IRB Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolInstitutionIrbReviewId** *required*	ID of the protocol affiliate institution IRB review.	`null`	integer
Body	**protocolInstitutionIrbReview** *required*			ProtocolInstitutionIrbReview

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolInstitutions

Add an institution to the protocol

```
POST /protocolInstitutions
```

Description

Adds the institution to the protocol.

Required Permissions

Consoles > PC Console
Protocol > Affiliates Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolInstitution** *required*			ProtocolInstitution

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Retrieve all institutions participating on the given protocol

```
GET /protocolInstitutions
```

Required Permissions

Consoles > PC Console

Request Parameters

CONFIDENTIAL

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	ID of the protocol.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all institutions participating on the protocol.	< ProtocolInstitution > array
400	Message error.	MessageError

Update the protocol institution record

```
PUT /protocolInstitutions/{protocolInstitutionId}
```

Description

Updates the given protocol institution.

Required Permissions

Consoles > PC Console
Protocol > Affiliates Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolInstitutionId** *required*	ID of the protocol institution.	`null`	integer
Body	**protocolInstitution** *required*			ProtocolInstitution

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

CONFIDENTIAL

ProtocolIrbReviewCommunications

Add a communication record to the IRB review

```
POST /protocolIrbReviewCommunications
```

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Update
Protocol > Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**irbReviewCommunication** *required*			IrbReviewCommunication

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol IRB review communications

```
GET /protocolIrbReviewCommunications
```

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

CONFIDENTIAL

Type	Name	Description	Default	Schema
Query	**protocolIrbReviewId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all communications on the IRB review.	< IrbReviewCommunication > array
400	Message error.	MessageError

Update the protocol IRB review communication record

```
PUT /protocolIrbReviewCommunications/{irbReviewCommunicationId}
```

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Update
Protocol > Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**irbReviewCommunicationId** *required*	ID of the protocol IRB review communication record.	`null`	integer
Body	**irbReviewCommunication** *required*			IrbReviewCommunication

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolIrbReviewDetails

Add a protocol IRB review attachment

```
POST /protocolIrbReviewDetails/{irbReviewDetailId}/attachment
```

Description

An attachment can only be created if one does not already exist for the IRB review detail record.

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Update
Protocol > Reviews

Request Body `multipart/form-data`

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol IRB review detail record.	`null`	integer
FormData	**irbReviewAttachment** *required*	A JSON serialized irbReviewAttachment.	`null`	string
FormData	**attachmentFile** *optional*	If provided, the irbReviewAttachment must have a fileName and the URL must be null. The file size must be less than or equal to OnCore's maximum file size, set in the MAX_FILE_UPLOAD_SIZE setting in the environment.conf file on the server.	`null`	file

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError
404	Returns Not Found if the IRB review detail does not exist.	No Content

CONFIDENTIAL

Add a detail record to the IRB review

```
POST /protocolIrbReviewDetails
```

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Update
Protocol > Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**irbReviewDetail** *required*			ProtocolIrbReviewDetail

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Delete a protocol IRB review attachment

```
DELETE /protocolIrbReviewDetails/{irbReviewDetailId}/attachment
```

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Update
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol IRB review detail record.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully deleted.	No Content
400	Message error.	MessageError
404	Returns Not Found if no attachment is associated with the IRB review detail or the IRB review detail does not exist.	No Content

Download a protocol IRB review detail attachment

```
GET /protocolIrbReviewDetails/{irbReviewDetailId}/attachment/download
```

Description

Downloads an IRB review detail attachment.

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol IRB review detail record.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The contents of the IRB review detail attachment. **Headers:** `content-disposition` (string): The file name of the IRB review detail attachment. Example: attachment; filename="example.pdf" `content-type` (string): The content type of the IRB review detail attachment. Example: application/pdf `content-length` (long): The size of the IRB review detail attachment in bytes. Example: 123456	file
400	Message error.	MessageError

Retrieve the attachment information for a protocol IRB review detail record

```
GET /protocolIrbReviewDetails/{irbReviewDetailId}/attachment
```

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol IRB review detail record.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The attachment associated with the IRB review detail, if one exists.	IrbReviewAttachment
400	Message error.	MessageError
404	Returns Not Found if no attachment is associated with the IRB review detail or the IRB review detail does not exist.	No Content

Search for protocol IRB review details

```
GET /protocolIrbReviewDetails
```

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolIrbReviewId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all details on the IRB review.	< ProtocolIrbReviewDetail > array
400	Message error.	MessageError

Update the protocol IRB review detail record

```
PUT /protocolIrbReviewDetails/{irbReviewDetailId}
```

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Update
Protocol > Reviews

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**irbReviewDetailId** *required*	ID of the protocol IRB review detail record.	`null`	integer
Body	**irbReviewDetail** *required*			ProtocolIrbReviewDetail

CONFIDENTIAL

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolIrbReviewReviewers

Add a reviewer to the IRB review

```
POST /protocolIrbReviewReviewers
```

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Update
Protocol > Reviews
Reviews > IRB Reviewer
Reviews > IRB Reviewer Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**irbReviewReviewer** *required*			IrbReviewReviewer

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol IRB review reviewers

```
GET /protocolIrbReviewReviewers
```

Required Permissions

Consoles > PC Console
Protocol > Reviews
Reviews > IRB Reviewer

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolIrbReviewId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all reviewers on the IRB review.	< IrbReviewReviewer > array
400	Message error.	MessageError

ProtocolIrbReviews

Add a protocol IRB review

```
POST /protocolIrbReviews
```

Description

Adds an IRB review to the protocol.

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Add and Delete
Protocol > Reviews

CONFIDENTIAL

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolIrbReview** *required*			ProtocolIrbReview

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Get a protocol IRB review by its ID

```
GET /protocolIrbReviews/{protocolIrbReviewId}
```

Description

Returns the protocol IRB review record with the given ID.

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolIrbReviewId** *required*	ID of the protocol IRB review.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Details for the protocol IRB review matching the given ID.	ProtocolIrbReview
400	Message error.	MessageError

Search for protocol IRB reviews

```
GET /protocolIrbReviews
```

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all IRB reviews on the protocol.	< ProtocolIrbReview > array
400	Message error.	MessageError

Update a protocol IRB review

```
PUT /protocolIrbReviews/{protocolIrbReviewId}
```

Description

Updates the given protocol IRB review.

Required Permissions

Consoles > PC Console
Protocol > IRB Reviews Update
Protocol > Reviews

Request Body `application/json`

CONFIDENTIAL

Type	Name	Description	Default	Schema
Path	**protocolIrbReviewId** *required*	ID of the protocol IRB review.	`null`	integer
Body	**protocolIrbReview** *required*			ProtocolIrbReview

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolManagementDetails

Search for protocol management details

```
GET /protocolManagementDetails
```

Description

Returns management details for protocols with the given irbNo.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**irbNo** *required*	The IRB number.	`null`	string

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of protocolManagementDetails matching the search criteria.	< ProtocolManagementDetails > array
400	Message error.	MessageError

CONFIDENTIAL

Get management details by protocol ID

```
GET /protocolManagementDetails/{protocolId}
```

Description

Returns management details for the protocol with the given ID.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolId** *required*	ID of the protocol.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Management details for the protocol matching the given ID.	ProtocolManagementDetails
400	Message error.	MessageError

Update protocol management details

```
PUT /protocolManagementDetails/{protocolId}
```

Description

Updates the management details for the protocol with the given ID.

Required Permissions

Consoles > PC Console
Protocol > Management Update

Request Body `application/json`

CONFIDENTIAL

Type	Name	Description	Default	Schema
Path	**protocolId** *required*	ID of the protocol.	`null`	integer
Body	**managementDetails** *required*			ProtocolManagementDetails

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolPrmcReviewCommunications

Add a communication record to the PRMC review

```
POST /protocolPrmcReviewCommunications
```

Description

Adds a PRMC review communication to the protocol.

Required Permissions

Consoles > PC Console
Protocol > Reviews
Protocol > PRMC Reviews Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**prmcReviewCommunication** *required*			ProtocolPrmcReviewCommunication

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol PRMC review communications

```
GET /protocolPrmcReviewCommunications
```

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Query	**prmcReviewId** *optional*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all communications on the PRMC review.	< ProtocolPrmcReviewCommunication > array
400	Message error.	MessageError

Update the protocol PRMC review communication record

```
PUT /protocolPrmcReviewCommunications/{prmcReviewCommunicationId}
```

Required Permissions

Consoles > PC Console
Protocol > Reviews

Protocol > PRMC Reviews Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**prmcReviewCommunicationId** *required*	ID of the protocol PRMC review communication record.	`null`	integer
Body	**prmcReviewCommunication** *required*			ProtocolPrmcReviewCommunication

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolPrmcReviewDetails

Add a detail record to the PRMC review

```
POST /protocolPrmcReviewDetails
```

Required Permissions

Consoles > PC Console
Protocol > Reviews
Protocol > PRMC Reviews Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolPrmcReviewDetail** *required*			ProtocolPrmcReviewDetail

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol PRMC review details

```
GET /protocolPrmcReviewDetails
```

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Query	**prmcReviewId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of details on the PRMC review.	< ProtocolPrmcReviewDetail > array
400	Message error.	MessageError

Update the protocol PRMC review detail record

```
PUT /protocolPrmcReviewDetails/{prmcReviewDetailId}
```

Required Permissions

Consoles > PC Console
Protocol > Reviews
Protocol > PRMC Reviews Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**prmcReviewDetailId** *required*	ID of the protocol PRMC review detail.	`null`	integer
Body	**protocolPrmcReviewDetail** *required*			ProtocolPrmcReviewDetail

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolPrmcReviewReviewers

Add a reviewer to the PRMC review

```
POST /protocolPrmcReviewReviewers
```

Description

Adds a PRMC review reviewer to the protocol.

Required Permissions

Consoles > PC Console
Protocol > Reviews
Protocol > PRMC Reviews Update
Reviews > PRMC Reviewer
Reviews > PRMC Reviewer Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolPrmcReviewReviewer** *required*			ProtocolPrmcReviewReviewer

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol PRMC review reviewers

```
GET /protocolPrmcReviewReviewers
```

Required Permissions

Consoles > PC Console
Protocol > Reviews
Reviews > PRMC Reviewer

Request Parameters

Type	Name	Description	Default	Schema
Query	**prmcReviewId** *required*		`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all reviewers on the PRMC review.	< ProtocolPrmcReviewReviewer > array
400	Message error.	MessageError

ProtocolPrmcReviews

Add a protocol PRMC review

```
POST /protocolPrmcReviews
```


CONFIDENTIAL

Description

Adds a PRMC review to the protocol.

Required Permissions

Consoles > PC Console
Protocol > Reviews
Protocol > PRMC Reviews Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolPrmcReview** *required*			ProtocolPrmcReview

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Get a protocol PRMC review by its ID

```
GET /protocolPrmcReviews/{prmcReviewId}
```

Description

Returns the protocol PRMC review record with the given ID.

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

CONFIDENTIAL

Type	Name	Description	Default	Schema
Path	**prmcReviewId** *required*	ID of the protocol PRMC review.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Details for the protocol PRMC review matching the given ID.	ProtocolPrmcReview
400	Message error.	MessageError

Search for protocol PRMC reviews

```
GET /protocolPrmcReviews
```

Required Permissions

Consoles > PC Console
Protocol > Reviews

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	The protocol ID.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all PRMC reviews on the protocol.	< ProtocolPrmcReview > array
400	Message error.	MessageError

Update a protocol PRMC review

```
PUT /protocolPrmcReviews/{prmcReviewId}
```


CONFIDENTIAL

Description

Updates the given protocol PRMC review.

Required Permissions

Consoles > PC Console
Protocol > Reviews
Protocol > PRMC Reviews Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**prmcReviewId** *required*	ID of the protocol PRMC review.	`null`	integer
Body	**protocolPrmcReview** *required*			ProtocolPrmcReview

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolSipConfiguration

Get a protocol ARP/SIP configuration by protocol ID

```
GET /protocolSipConfiguration/{protocolId}
```

Description

Returns the protocol ARP/SIP configuration for the given protocol ID.

Required Permissions

Consoles > Advarra Research Portal Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolId** *required*	ID of the protocol.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Protocol ARP/SIP configuration for the protocol matching the given ID.	ProtocolSipConfiguration
400	Message error.	MessageError

Update the protocol ARP/SIP configuration

```
PUT /protocolSipConfiguration/{protocolId}
```

Required Permissions

Consoles > Advarra Research Portal Console

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolId** *required*	ID of the protocol.	`null`	integer
Body	**protocolSipConfiguration** *required*			ProtocolSipConfiguration

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolSponsors

Add a protocol sponsor to the protocol

```
POST /protocolSponsors
```

Required Permissions

Consoles > PC Console
Protocol > Sponsor Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolSponsor** *required*			ProtocolSponsor

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol sponsors

```
GET /protocolSponsors
```

Description

Returns all protocol sponsors for a given protocol ID or sponsor protocol number. Requires protocolId or sponsorProtocolNo.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *optional*	ID of the protocol.	`null`	integer
Query	**sponsorProtocolNo** *optional*	Sponsor protocol number.	`null`	string

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all sponsors on the protocol.	< ProtocolSponsor > array
400	Message error.	MessageError

Update the protocol sponsor

```
PUT /protocolSponsors/{protocolSponsorId}
```

Required Permissions

Consoles > PC Console
Protocol > Sponsor Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolSponsorId** *required*	ID of the protocol sponsor record.	`null`	integer
Body	**protocolSponsor** *required*			ProtocolSponsor

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolStaff

Add protocol staff

```
POST /protocolStaff
```


CONFIDENTIAL

Description

Adds a staff member to the protocol. Returns a validation error if the DISABLE_MULTIPLE_PIS config setting is True and the create results in PIs with overlapping dates.

Required Permissions

Consoles > PC Console
Protocol > Staff Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolStaff** *required*			ProtocolStaff

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol staff

```
GET /protocolStaff
```

Description

Returns all protocol staff on the protocol with the given ID.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	ID of the protocol.	`null`	integer

CONFIDENTIAL

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all staff members on the protocol.	< ProtocolStaff > array
400	Message error.	MessageError

Get a protocol staff by its ID

```
GET /protocolStaff/{protocolStaffId}
```

Description

Returns the protocol staff record with the given ID.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolStaffId** *required*	ID of the protocol staff.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The protocol staff matching the given ID.	ProtocolStaff
400	Message error.	MessageError

Update protocol staff

```
PUT /protocolStaff/{protocolStaffId}
```

Description

Updates the given protocol staff record. Returns a validation error if the DISABLE_MULTIPLE_PIS config setting is True and the update results in PIs with overlapping dates.

Required Permissions

Consoles > PC Console
Protocol > Staff Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolStaffId** *required*	ID of the protocol staff.	`null`	integer
Body	**protocolStaff** *required*			ProtocolStaff

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolStatus

Set a protocol status

```
POST /protocolStatus
```

Required Permissions

Consoles > PC Console

Conditional Permissions

Permission	Action
Protocol > For Affiliates Only	Set status to For Affiliates Only
Protocol > Abandon	Set status to Abandoned
Protocol > Close	Set status to Closed to Accrual
Protocol > IRB Study Closure	Set status to IRB Study Closure
Protocol > On Hold	Set status to On Hold
Protocol > Off Hold	Set status to Off Hold
Protocol > Open	Set status to Open to Accrual

Permission	Action
Protocol > Suspend	Set status to Suspended
Protocol > Terminate	Set status to Terminated
Protocol > Custom Protocol Signoff	Set status to custom protocol signoff

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolStatusChange** *required*			ProtocolStatusChange

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Delete a specified protocol status

```
DELETE /protocolStatus
```

Required Permissions

Consoles > PC Console

Conditional Permissions

Permission	Action
Protocol > For Affiliates Only	Undo status from For Affiliates Only
Protocol > Abandon	Undo status from Abandoned
Protocol > Close	Undo status from Closed to Accrual
Protocol > IRB Study Closure	Undo status from IRB Study Closure
Protocol > On Hold	Undo status from On Hold
Protocol > Off Hold	Return protocol to On Hold

Permission	Action
Protocol > Open	Undo status from Open to Accrual
Protocol > Suspend	Undo status from Suspended
Protocol > Terminate	Undo status from Terminated
Protocol > Custom Protocol Signoff	Undo status from custom protocol signoff

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	The ID of the protocol whose status is to be changed.	`null`	integer
Query	**status** *required*	The protocol status to delete.	`null`	string

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully deleted.	No Content
400	Message error.	MessageError

Get the next available protocol statuses for the given protocol

```
GET /protocolStatus/{protocolId}
```

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolId** *required*	The protocol ID.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Protocol status inquiry for the protocol matching the given ID.	ProtocolStatusInquiry

HTTP Code	Description	Schema
400	Message error.	MessageError

ProtocolSubjectAttachments

Download a protocol subject attachment

```
GET /protocolSubjectAttachments/{protocolSubjectAttachmentId}/download
```

Description

Downloads a protocol subject attachment file.

Required Permissions

Consoles > Subject Console
Subject > Attachments

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolSubjectAttachmentId** *required*	ID of the protocol subject attachment.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The contents of the protocol subject attachment. **Headers:** `content-disposition` (string): The file name of the protocol subject attachment. Example: attachment; filename="example.pdf" `content-type` (string): The content type of the protocol subject attachment. Example: application/pdf `content-length` (long): The size of the protocol subject attachment in bytes. Example: 123456	file
400	Message error.	MessageError

Get a protocol subject attachment

```
GET /protocolSubjectAttachments/{protocolSubjectAttachmentId}
```

Description

Returns a protocol subject attachment by its ID.

Required Permissions

Consoles > Subject Console
Subject > Attachments

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolSubjectAttachmentId** *required*	ID of the protocol subject attachment.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The protocol subject attachment.	ProtocolSubjectAttachment
400	Message error.	MessageError

Search for protocol subject attachments

```
GET /protocolSubjectAttachments
```

Description

Returns a list of protocol subject attachments matching the given search criteria.

Required Permissions

Consoles > Subject Console
Subject > Attachments

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolSubjectId** *required*	ID of the protocol subject.	`null`	integer

CONFIDENTIAL

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of protocol subject attachments matching the given search criteria.	< ProtocolSubjectAttachment > array
400	Message error.	MessageError

ProtocolSubjectConsents

Add a protocol consent to a subject

```
POST /protocolSubjectConsents
```

Required Permissions

Consoles > Subject Console
Consoles > PC Console
Subject > On Study Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolSubjectConsent** *required*			ProtocolSubjectConsent

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for subject consents

```
GET /protocolSubjectConsents
```

Required Permissions

Consoles > PC Console
Consoles > Subject Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolSubjectId** *required*	The protocol subject ID.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Returns all subject consent information for a given protocol subject ID.	< ProtocolSubjectConsent > array
400	Message error.	MessageError

ProtocolSubjectOnStudy

Get protocol subject on study information by ID

```
GET /protocolSubjectOnStudy/{protocolSubjectId}
```

Description

Returns on study information for the protocol subject with the given ID.

Required Permissions

Consoles > PC Console
Consoles > Subject Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolSubjectId** *required*	ID of the protocol subject.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	On study information for the given protocol subject ID.	ProtocolSubjectOnStudy
400	Message error.	MessageError

Update protocol subject on study information by ID

```
PUT /protocolSubjectOnStudy/{protocolSubjectId}
```

Description

Updates protocol subject on study information.

Required Permissions

Consoles > PC Console
Consoles > Subject Console
Subject > On Study Update
Subject > On Study Date Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolSubjectId** *required*	ID of the protocol subject.	`null`	integer
Body	**protocolSubjectOnStudy** *required*			ProtocolSubjectOnStudy

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolSubjectTreatments

Get treatment details by protocol subject ID

```
GET /protocolSubjectTreatments
```

Description

Returns a list of treatment details for the given protocol subject.

Required Permissions

Consoles > Subject Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolSubjectId** *required*	ID of the protocol subject.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The treatment details for the protocol subject.	< ProtocolSubjectTreatment > array
400	Message error.	MessageError

ProtocolSubjects

Add a subject to a protocol

```
POST /protocolSubjects
```

Required Permissions

Consoles > CRA Console
Subject > Find and Register Subject
Subject > Create Subject
Subject > Demographics Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolSubject** *required*			ProtocolSubject
Query	**generateMrn** *optional*	Only applicable when registering new subjects. If true, an MRN will be generated by OnCore and an MRN must not be provided in the request. Default value is false.	`null`	boolean

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for protocol subjects for the given protocol

```
GET /protocolSubjects
```

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	The protocol ID.	`null`	integer
Query	**pageSize** *optional*	The maximum number of records to retrieve. **Minimum value:** `1` **Maximum value:** `10000`	`1000`	integer
Query	**page** *optional*	The result page if the total number of records is greater than pageSize. **Minimum value:** `1`	`1`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all subjects on the protocol.	< ProtocolSubject > array
400	Message error.	MessageError

ProtocolSummaryAccruals

Add a summary accrual to the protocol

```
POST /protocolSummaryAccruals
```

Required Permissions

Consoles > PC Console
Protocol > Accrual Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocolSummaryAccrual** *required*			ProtocolSummaryAccrual

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Delete a protocol summary accrual

```
DELETE /protocolSummaryAccruals/{protocolSummaryAccrualId}
```


CONFIDENTIAL

Required Permissions

Consoles > PC Console
Protocol > Accrual Update

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolSummaryAccrualId** *required*	ID of the protocol summary accrual record.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully deleted.	No Content
400	Message error.	MessageError

Search for protocol summary accruals

```
GET /protocolSummaryAccruals
```

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	ID of the protocol.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all summary accruals on the protocol.	< ProtocolSummaryAccrual > array
400	Message error.	MessageError

CONFIDENTIAL

ProtocolTaskLists

Search for protocol task lists

```
GET /protocolTaskLists
```

Description

Returns a list of protocol task lists matching the given search criteria.

Required Permissions

Consoles > PC Console
Task Management > Task List View All
Task Management > Task Lists

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolId** *required*	The protocol ID.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of protocol task lists matching the given search criteria.	< ProtocolTaskList > array
400	Message error.	MessageError

ProtocolTasks

Search for protocol tasks

```
GET /protocolTasks
```

Description

Returns a list of protocol tasks matching the given search criteria.

CONFIDENTIAL

Required Permissions

Consoles > PC Console
Task Management > Task List View All
Task Management > Task Lists

Request Parameters

Type	Name	Description	Default	Schema
Query	**taskListId** *required*	The task list ID.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of all the protocol tasks on the specified task list.	< ProtocolTask > array
400	Message error.	MessageError

Update a protocol task

```
PUT /protocolTasks/{taskId}
```

Required Permissions

Consoles > PC Console
Task Management > Task List Edit All
Task Management > Task Lists

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**taskId** *required*	ID of the protocol task.	`null`	integer
Body	**ProtocolTask** *required*			ProtocolTask

Response Body `application/json`

CONFIDENTIAL

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

ProtocolTreatment

Get treatment details by protocol ID

```
GET /protocolTreatment/{protocolId}
```

Description

Returns protocol treatment details for a given protocol ID.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolId** *required*	ID of the protocol.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Protocol treatment details on the protocol.	ProtocolTreatment
400	Message error.	MessageError

Protocols

Create a protocol

```
POST /protocols
```

Required Permissions

Consoles > PC Console

CONFIDENTIAL

Protocol > New Protocol

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**protocol** *required*			Protocol

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Get a protocol by its ID

```
GET /protocols/{protocolId}
```

Description

Retrieves a protocol based on its ID.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Path	**protocolId** *required*	ID of the protocol.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The protocol matching the given ID.	Protocol
400	Message error.	MessageError

Search for protocols

```
GET /protocols
```

Description

Returns protocols matching the search criteria. Requires protocolNo or nctNo.

Required Permissions

Consoles > PC Console

Request Parameters

Type	Name	Description	Default	Schema
Query	**protocolNo** *optional*	The protocol number.	`null`	string
Query	**nctNo** *optional*	The NCT number.	`null`	string

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of protocols matching the search criteria.	< Protocol > array
400	Message error.	MessageError

Update a protocol

```
PUT /protocols/{protocolId}
```

Description

The library can only be updated if the protocol does not have subjects accrued. If the organizationalUnit is updated, all management groups are removed from the protocol.

Required Permissions

Consoles > PC Console
Protocol > Main Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**protocolId** *required*	ID of the protocol.	`null`	integer
Body	**protocol** *required*			Protocol

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

SponsorAddresses

Add an address to a sponsor

```
POST /sponsorAddresses
```

Required Permissions

Sponsor > Sponsor
Sponsor > Sponsor Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**sponsorAddress** *required*			SponsorAddress

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for sponsor addresses

```
GET /sponsorAddresses
```

Description

Returns sponsor addresses matching the search criteria.

Required Permissions

Sponsor > Sponsor

Request Parameters

Type	Name	Description	Default	Schema
Query	**sponsorId** *required*	The sponsor ID.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of addresses associated with the sponsor.	< SponsorAddress > array
400	Message error.	MessageError

Update a sponsor address

```
PUT /sponsorAddresses/{sponsorAddressId}
```

Required Permissions

Sponsor > Sponsor
Sponsor > Sponsor Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**sponsorAddressId** *required*	ID of the sponsor address record.	`null`	integer

CONFIDENTIAL

Type	Name	Description	Default	Schema
Body	**sponsorAddress** *required*			SponsorAddress

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

SponsorGrants

Create a sponsor grant

```
POST /sponsorGrants
```

Required Permissions

Sponsor > Sponsor
Sponsor > Sponsor Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**sponsorGrant** *required*			SponsorGrant

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Search for sponsor grants

```
GET /sponsorGrants
```


CONFIDENTIAL

Description

Returns sponsor grants matching the search criteria.

Required Permissions

Sponsor > Sponsor

Request Parameters

Type	Name	Description	Default	Schema
Query	**sponsorId** *required*	The sponsor ID.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of grants associated with the sponsor.	< SponsorGrant > array
400	Message error.	MessageError

Update a sponsor grant

```
PUT /sponsorGrants/{sponsorGrantId}
```

Required Permissions

Sponsor > Sponsor
Sponsor > Sponsor Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**sponsorGrantId** *required*	ID of the sponsor grant record.	`null`	integer
Body	**sponsorGrant** *required*			SponsorGrant

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

Sponsors

Create a sponsor

```
POST /sponsors
```

Required Permissions

Sponsor > Sponsor
Sponsor > New Sponsor

Request Body `application/json`

Type	Name	Description	Default	Schema
Body	**sponsor** *required*			Sponsor

Response Body `application/json`

HTTP Code	Description	Schema
201	The resource was successfully created. **Headers:** `location` (string): Location URL of the created resource. Example: location_example	No Content
400	Message error.	MessageError

Get a sponsor by its ID

```
GET /sponsors/{sponsorId}
```

Description

Retrieves a sponsor based on its ID.

CONFIDENTIAL

Required Permissions

Sponsor > Sponsor

Request Parameters

Type	Name	Description	Default	Schema
Path	**sponsorId** *required*	ID of the sponsor record.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	The sponsor matching the given ID.	Sponsor
400	Message error.	MessageError

Search for sponsors

```
GET /sponsors
```

Description

Returns a list of sponsors matching the given search criteria. Requires sponsorName or sponsorCode.

Required Permissions

Sponsor > Sponsor

Request Parameters

Type	Name	Description	Default	Schema
Query	**sponsorName** *optional*	The sponsor name.	`null`	string
Query	**sponsorCode** *optional*	The sponsor code.	`null`	string

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of sponsors matching the search criteria.	< Sponsor > array
400	Message error.	MessageError

Update the sponsor

```
PUT /sponsors/{sponsorId}
```

Required Permissions

Sponsor > Sponsor
Sponsor > Sponsor Update

Request Body `application/json`

Type	Name	Description	Default	Schema
Path	**sponsorId** *required*	ID of the sponsor record.	`null`	integer
Body	**sponsor** *required*			Sponsor

Response Body `application/json`

HTTP Code	Description	Schema
204	The resource was successfully updated.	No Content
400	Message error.	MessageError

SubjectDemographics

Search for subject demographics

```
GET /subjectDemographics
```

Description

Returns subject demographics matching the search criteria.

Required Permissions

Subject > Find and Register Subject
Subject > Identification

Request Parameters

CONFIDENTIAL

Type	Name	Description	Default	Schema
Query	**mrn** *required*	The subject's MRN.	`null`	string
Query	**subjectSource** *optional*	The location to search for demographics information (OnCore or Onstage).	`OnCore`	string

Response Body `application/json`

HTTP Code	Description	Schema
200	A list of subject demographics matching the search criteria.	< SubjectDemographics > array
400	Message error.	MessageError

Get subject demographics by ID

```
GET /subjectDemographics/{subjectDemographicsId}
```

Description

Returns demographic information for the subject with the given ID.

Required Permissions

Subject > Identification

Request Parameters

Type	Name	Description	Default	Schema
Path	**subjectDemographicsId** *required*	ID of the subject.	`null`	integer

Response Body `application/json`

HTTP Code	Description	Schema
200	Subject demographics for the given ID.	SubjectDemographics
400	Message error.	MessageError

CONFIDENTIAL

Definitions

AdministrativeGroups

Name	Description	Default	Schema
programAreas *optional*	Name parameter based on Program Area reference list description (case sensitive). For Oncology protocols only. A validation error will be returned if set on protocols in other libraries.	`null`	< Group > array
oncologyGroups *optional*	Name parameter based on Oncology Group reference list description (case sensitive). For Oncology protocols only. A validation error will be returned if set on protocols in other libraries.	`null`	< Group > array
managementGroups *optional*	Name parameter based on the Management Group list defined in Group Admin Console based on the protocol's organizational unit (case sensitive).	`null`	< Group > array

ConstraintViolationError

A validation constraint failed while processing this request.

Name	Description	Default	Schema
message *optional*	The error message accompanying this response. Example: Protocol 123 does not exist.	`null`	string
errorType *optional*	The type of the error. Can be used to distinguish the actual error type that occurred.	`null`	string
invalidFields *optional*		`null`	< InvalidField > array

Contact

Contains details about a contact.

Name	Description	Default	Schema
contactId *optional* *read-only*		`null`	integer
additionalIdentifiers *optional*	Uses the Contact Identifier Type reference list (case sensitive). A contact can only have one identifier of a given type.	`null`	< Identifier > array
firstName *required*	**Maximal length:** `255`	`null`	string
middleName *optional*	**Maximal length:** `255`	`null`	string

Name	Description	Default	Schema
lastName *required*	**Maximal length:** `255`	`null`	string
email *optional*	Must be formatted as a valid email address. Required when updating a contact that is also a user. **Maximal length:** `254`	`null`	string
activeContact *optional*		`true`	boolean
appUser *optional* *read-only*		`null`	boolean
homeOrganization *required*	The contact's home organization name.	`null`	string
canAccessAllOrganizations *optional* *read-only*		`null`	boolean
assignableTo *required*	A list of contexts where the contact can be assigned or All if the contact can be assigned in all contexts.	`null`	< enum (All, Audits, Committees, Protocols, Subjects, Tasks, Registries) > array
collegeDivision *optional*	**Maximal length:** `255`	`null`	string
mailDepartment *optional*	**Maximal length:** `255`	`null`	string
contactNumbers *optional*	A contact can only have one contact number of a given type.	`null`	< ContactNumber > array
title *optional*	**Maximal length:** `255`	`null`	string

ContactCredential

Contains details about a contact's credentials.

Name	Description	Default	Schema
contactId *required* *read-only*		`null`	integer

Name	Description	Default	Schema
contactCredentialId *optional* *read-only*		`null`	integer
credentialType *optional*	Credential Type reference list description (case sensitive).	`null`	string
number *optional*		`null`	string
effectiveDate *optional*		`null`	string (date)
expirationDate *optional*		`null`	string (date)

ContactNumber

Name	Description	Default	Schema
numberType *required*	Contact Number Type reference list description (case sensitive).	`null`	string
phoneNumber *required*	Must be formatted as a valid phone number.	`null`	string

FieldValidationError

A field-level validation error occurred while processing this request.

Name	Description	Default	Schema
message *optional*	The error message accompanying this response. Example: Protocol 123 does not exist.	`null`	string
errorType *optional*	The type of the error. Can be used to distinguish the actual error type that occurred.	`null`	string
field *optional*	Name of the field that was invalid. Example: age	`null`	string

Group

Name	Description	Default	Schema
name *optional*		`null`	string
primary *optional*	Only one group can be set as the primary. A validation error will be returned if multiple groups have this field set to true.	`null`	boolean

CONFIDENTIAL

Identifier

Contains an identifier and its type.

Name	Description	Default	Schema
id *optional*	**Maximal length:** `50`	`null`	string
idType *optional*	Entry name from the corresponding identifier type reference list.	`null`	string

InvalidField

Contains details on the field causing an error.

Name	Description	Default	Schema
field *optional*	The field that was invalid.	`null`	string
message *optional*	What was invalid about the field.	`null`	string
type *optional*	The constraint violation type.	`null`	string

IrbReviewAttachment

Contains data for an IRB review attachment. Requires either fileName or URL to be set.

Name	Description	Default	Schema
fileName *optional*	If fileName is provided, then url must be null. **Maximal length:** `255`	`null`	string
url *optional*	If url is provided, then fileName must be null. **Maximal length:** `2000`	`null`	string
released *optional*		`null`	boolean

IrbReviewCommunication

Contains information about a communication for an IRB review.

Name	Description	Default	Schema
irbReviewCommunicationId *optional* *read-only*		`null`	integer
irbReviewId *required*	Either a protocol IRB review ID or a protocol institution IRB review ID.	`null`	integer
communicationType *required*	IRB Communication Type reference list description (case sensitive).	`null`	string
sentTo *optional*	ID of the contact the communication was sent to.	`null`	integer
sentDate *optional*	The date the communication was sent. Cannot be a future date.	`null`	string (date)
response *optional*	Review Communication Response reference list description (case sensitive).	`null`	string
respondedBy *optional*	ID of the contact that responded to the communication.	`null`	integer
responseDate *optional*	The date the communication was responded to.	`null`	string (date)
comments *optional*	**Maximal length:** `100`	`null`	string

IrbReviewReviewer

Contains information about a reviewer for an IRB review.

Name	Description	Default	Schema
irbReviewReviewerId *optional* *read-only*		`null`	integer
irbReviewId *required*	Either a protocol IRB review ID or a protocol institution IRB review ID.	`null`	integer
contactId *required*	Contact must be a valid IRB committee appointee for the review.	`null`	integer
reviewerType *optional*	Reviewer Type reference list description (case sensitive).	`null`	string
attended *optional*		`null`	boolean

MessageError

An error occurred while processing the request.

Name	Description	Default	Schema
message *optional*	The error message accompanying this response. Example: Protocol 123 does not exist.	`null`	string
errorType *optional*	The type of the error. Can be used to distinguish the actual error type that occurred.	`null`	string

Protocol

Contains general details about an OnCore protocol.

Name	Description	Default	Schema
protocolId *optional* *read-only*		`null`	integer
protocolStatus *optional* *read-only*		`null`	string
protocolNo *required*	Can only contain alphanumerics, -, \, or / **Maximal length:** `30`	`null`	string
library *required*	If the ONCORE_INSTANCE_FOR configuration setting is "CC" this should be set to "Oncology".	`null`	string
department *required*	Department name (case sensitive). If the ONCORE_INSTANCE_FOR configuration setting is "CC" this should be set to "Oncology".	`null`	string
organizationalUnit *required*	Organizational Unit name (case sensitive). If the ONCORE_INSTANCE_FOR configuration setting is "CC" this should be set to "Cancer Center".	`null`	string
protocolType *required*	Protocol Type reference list description (case sensitive).	`null`	string
nctNo *optional*	Validated based on the NCT_NUMBER_REGEX config setting.	`null`	string
title *optional*	Required if the RC_EXPANDED_VALIDATION_OVERRIDE configuration setting is "N" or not set. **Maximal length:** `4000`	`null`	string
shortTitle *optional*	**Maximal length:** `100`	`null`	string

CONFIDENTIAL

Name	Description	Default	Schema
objectives *optional*	**Maximal length:** `4000`	`null`	string
phase *optional*	Phase reference list description (case sensitive).	`null`	string
scope *optional*	Scope reference list description (case sensitive).	`null`	string
age *optional*	Required if the RC_EXPANDED_VALIDATION_OVERRIDE configuration setting is "N" or not set.	`null`	enum (Adults, Children, Both)
investigatorInitiated *optional*	Required if the RC_EXPANDED_VALIDATION_OVERRIDE configuration setting is "N" or not set.	`null`	boolean
investigationalDrug *optional*		`null`	enum (Yes, No, N/A)
investigationalDevice *optional*		`null`	enum (Yes, No, N/A)
drugAccountability *optional*		`null`	enum (Yes, No, N/A)
dataMonitoring *optional*	Data Monitoring reference list description.	`null`	string
includesSpecimenBanking *optional*		`null`	boolean
dataTable4ReportType *optional*	Data Table 4 Report Type reference list description (case sensitive). For Oncology protocols only. A validation error will be returned if set on protocols in other libraries.	`null`	string
multiSiteTrial *optional*		`null`	boolean
excludeProtocolOnWeb *optional*		`null`	boolean
summaryAccrualInfoOnly *optional*	If a protocol has patient accruals, a validation error will be returned if set to true. If a protocol has summary accruals, a validation error will be returned if set to false or null.	`null`	boolean
involvesTherapy *optional*		`null`	enum (Yes, No, N/A)

CONFIDENTIAL

Name	Description	Default	Schema
precisionTrial *optional*		`null`	boolean
precisionTrialClassification *optional*	This should only be set if precisionTrial is set to true. A validation error will be returned if set when precisionTrial is false.	`null`	enum (Basket, Umbrella, Targeted, Other Adaptive Trials)
pilot *optional*		`null`	boolean
involvesCorrelates *optional*		`null`	boolean
cancerControl *optional*	For Oncology protocols only. A validation error will be returned if set on protocols in other libraries.	`null`	boolean
cancerPrevention *optional*	For Oncology protocols only. A validation error will be returned if set on protocols in other libraries.	`null`	boolean
adjuvant *optional*		`null`	enum (Yes, No, N/A)
registrationCenter *optional*	Patient Registration reference list description (case sensitive).	`null`	string
accrualInformationNotApplicable *optional*	This field is mutually exclusive to the Accrual Information fields. When set to true, the following fields will be set to null - protocolTargetAccrual, rcLowerAccrualGoal, rcUpperAccrualGoal, rcAnnualAccrualGoal, affiliateAccrualGoal, and accrualDuration.	`null`	boolean
protocolTargetAccrual *optional*	Required if the RC_EXPANDED_VALIDATION_OVERRIDE configuration setting is "N" or not set. **Minimum value:** `0` **Maximum value:** `99999999`	`null`	integer
rcLowerAccrualGoal *optional*	**Minimum value:** `0` **Maximum value:** `99999999`	`null`	integer
rcUpperAccrualGoal *optional*	Required if the RC_EXPANDED_VALIDATION_OVERRIDE configuration setting is "N" or not set. **Minimum value:** `0` **Maximum value:** `99999999`	`null`	integer

Name	Description	Default	Schema
rcAnnualAccrualGoal *optional*	**Minimum value:** `0` **Maximum value:** `99999999`	`null`	integer
affiliateAccrualGoal *optional*	**Minimum value:** `0` **Maximum value:** `99999999`	`null`	integer
accrualDuration *optional*	Required if the RC_EXPANDED_VALIDATION_OVERRIDE configuration setting is "N" or not set. **Minimum value:** `0` **Maximum value:** `99999999`	`null`	integer
primaryCompletionDate *optional*		`null`	string (date)
primaryCompletionDateType *optional*		`null`	enum (Actual, Anticipated)
studyCompletionDate *optional*		`null`	string (date)
studyCompletionDateType *optional*		`null`	enum (Actual, Anticipated)

ProtocolAttachment

Contains data for a protocol attachment. This resource covers only attachments created and managed under PC Console > Documents/Info.

Name	Description	Default	Schema
protocolAttachmentId *optional* *read-only*		`null`	integer
protocolId *required*	Cannot be updated.	`null`	integer
documentType *required*	Document Type must be selectable from PC Console > Documents/Info > Update > Add > Document Type drop-down list.	`null`	string

Name	Description	Default	Schema
versionDate *required*		`null`	string (date)
expirationDate *optional*		`null`	string (date)
attachmentDescription *optional*	**Maximal length:** `255`	`null`	string
fileName *optional*	If fileName is provided, then url must be null. **Maximal length:** `255`	`null`	string
url *optional*	If url is provided, then fileName must be null. **Maximal length:** `2000`	`null`	string

ProtocolConsent

Contains information about a consent on a protocol.

Name	Description	Default	Schema
protocolId *required*		`null`	integer
consentId *optional*		`null`	integer
institution *optional*	Institution name.	`null`	string
consentType *optional*	The Document Type reference list description (case sensitive).	`null`	string
consentDescription *optional*		`null`	string
versionDate *optional*		`null`	string (date)
approvedDate *optional*		`null`	string (date)
expirationDate *optional*		`null`	string (date)

ProtocolEprmsSubmission

Contains information about a protocol ePRMS submission.

Name	Description	Default	Schema
submissionNo *optional* *read-only*		`null`	integer
protocolId *required*	Cannot be updated.	`null`	integer
reviewType *required*	The PRMC Review Type reference list description (case sensitive).	`null`	string
reviewReason *required*	The PRMC Reason reference list description (case sensitive).	`null`	string
action *optional* *read-only*	The PRMC Action reference list description (case sensitive).	`null`	string

ProtocolIde

Contains details specific to an investigational device for a protocol.

Name	Description	Default	Schema
protocolId *required*	Cannot be updated.	`null`	integer
id *required*	**Maximal length:** `50`	`null`	string
holderName *required*	**Maximal length:** `200`	`null`	string
holderType *optional*	The Investigative Holder Types reference list description (case sensitive).	`null`	string
nciInstitution *optional*	Only used if holderType is NCI. Must be null otherwise. The valid values for this field are established and maintained by the NCI/NIH and can change across versions.	`null`	enum (CCR, CCT/CTB, CDP, CIP, CTEP, DCB, DCCPS, DCEG, DCP, DEA, DESP, DTP, N/A, OD, OSB/SPORE, RRP, TRP)
nihInstitution *optional*	Only used if holderType is NIH. Must be null otherwise. The valid values for this field are established and maintained by the NCI/NIH and can change across versions.	`null`	enum (CC, CIT, CSR, FIC, NCATS, NCCAM, NCCIH, NCRR, NEI, NHGRI, NHLBI, NIA, NIAAA, NIAID, NIAMS, NIBIB, NICHD, NIDA, NIDCD, NIDCR, NIDDK, NIEHS, NIGMS, NIMH, NIMHD, NINDS, NINR, NLM, OD)

CONFIDENTIAL

Name	Description	Default	Schema
submitDate *optional*		`null`	string (date)
fdaApprovalDate *optional*		`null`	string (date)
expirationDate *optional*		`null`	string (date)
expandedAccess *optional*		`null`	boolean
expandedAccessStatus *optional*	Required if expandedAccess is set to true. Must be null otherwise.	`null`	enum (Approved For Marketing, Available, No Longer Available, Temporarily Not Available)
serialNumber *optional*	**Maximal length:** `50`	`null`	string
exempt *optional*		`null`	boolean
comments *optional*	**Maximal length:** `2000`	`null`	string
protocolIdeId *optional* *read-only*		`null`	integer
grantor *optional*		`null`	enum (CDRH, CBER)
risk *optional*	The Device Risk reference list description (case sensitive).	`null`	string

ProtocolInd

Contains details specific to an investigational drug for a protocol.

Name	Description	Default	Schema
protocolId *required*	Cannot be updated.	`null`	integer
id *required*	**Maximal length:** `50`	`null`	string
holderName *required*	**Maximal length:** `200`	`null`	string
holderType *optional*	The Investigative Holder Types reference list description (case sensitive).	`null`	string

Name	Description	Default	Schema
nciInstitution *optional*	Only used if holderType is NCI. Must be null otherwise. The valid values for this field are established and maintained by the NCI/NIH and can change across versions.	`null`	enum (CCR, CCT/CTB, CDP, CIP, CTEP, DCB, DCCPS, DCEG, DCP, DEA, DESP, DTP, N/A, OD, OSB/SPORE, RRP, TRP)
nihInstitution *optional*	Only used if holderType is NIH. Must be null otherwise. The valid values for this field are established and maintained by the NCI/NIH and can change across versions.	`null`	enum (CC, CIT, CSR, FIC, NCATS, NCCAM, NCCIH, NCRR, NEI, NHGRI, NHLBI, NIA, NIAAA, NIAID, NIAMS, NIBIB, NICHD, NIDA, NIDCD, NIDCR, NIDDK, NIEHS, NIGMS, NIMH, NIMHD, NINDS, NINR, NLM, OD)
submitDate *optional*		`null`	string (date)
fdaApprovalDate *optional*		`null`	string (date)
expirationDate *optional*		`null`	string (date)
expandedAccess *optional*		`null`	boolean
expandedAccessStatus *optional*	Required if expandedAccess is set to true. Must be null otherwise.	`null`	enum (Approved For Marketing, Available, No Longer Available, Temporarily Not Available)
serialNumber *optional*	**Maximal length:** `50`	`null`	string
exempt *optional*		`null`	boolean
comments *optional*	**Maximal length:** `2000`	`null`	string
protocolIndId *optional* *read-only*		`null`	integer
grantor *optional*		`null`	enum (CBER, CDER)

CONFIDENTIAL

ProtocolInstitution

Contains information about institutions participating on a protocol.

Name	Description	Default	Schema
protocolInstitutionId *optional* *read-only*		`null`	integer
protocolId *required*		`null`	integer
institution *required*	Institution name.	`null`	string
usesResearchCenterIRB *optional*	Only used when the REGIONAL_PARTNER_TRACKING config setting is Y. Indicates whether the institution uses the research center's IRB. Ignored if the institution is the research center. Required if the institution is not the research center.	`null`	boolean

ProtocolInstitutionIrbReview

Contains details for an affiliate-only IRB review.

Name	Description	Default	Schema
irbReviewId *optional* *read-only*		`null`	integer
protocolId *required*	Cannot be updated.	`null`	integer
committee *optional*	The IRB Committee reference list description (case sensitive).	`null`	string
reviewReason *optional*	The IRB Review Reason reference list description (case sensitive).	`null`	string
reviewType *optional*	The IRB Review Type reference list description (case sensitive).	`null`	string
action *optional*	The IRB Action Description reference list description (case sensitive). If set, actionDate is required.	`null`	string
actionDate *optional*	Must be on or after the submit date. Cannot be a future date. If set, action is required.	`null`	string (date)
expirationDate *optional*	Must be on or after the action date if there is one.	`null`	string (date)
reviewNo *optional*	**Maximal length:** 15	`null`	string

CONFIDENTIAL

Name	Description	Default	Schema
summary *optional*	**Maximal length:** `4000`	`null`	string
yesVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer
noVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer
abstainVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer
institution *required*	The name of the affiliate institution. Cannot be updated.	`null`	string
submitDate *optional*	Required if actionDate is set.	`null`	string (date)

ProtocolInstitutionIrbReviewDetail

Contains details about the protocol institution IRB review.

Name	Description	Default	Schema
irbReviewDetailId *optional* *read-only*		`null`	integer
irbReviewId *required*	Cannot be updated.	`null`	integer
detailTypes *required*	The Review Change Type reference list descriptions (case sensitive).	`null`	< string > array
amendmentNo *optional*	**Maximal length:** `10`	`null`	string
receivedDate *optional*		`null`	string (date)
versionDate *optional*	Required for consent types.	`null`	string (date)
detailDescription *optional*	**Maximal length:** `500`	`null`	string

CONFIDENTIAL

Name	Description	Default	Schema
comments *optional*	**Maximal length:** `2000`	`null`	string
reconsentRequired *optional*	Sets all subject statuses to true/false at once.	`false`	boolean

ProtocolIrbReview

Contains details for a research center IRB review.

Name	Description	Default	Schema
irbReviewId *optional* *read-only*		`null`	integer
protocolId *required*	Cannot be updated.	`null`	integer
committee *optional*	The IRB Committee reference list description (case sensitive).	`null`	string
reviewReason *optional*	The IRB Review Reason reference list description (case sensitive).	`null`	string
reviewType *optional*	The IRB Review Type reference list description (case sensitive).	`null`	string
action *optional*	The IRB Action Description reference list description (case sensitive). If set, actionDate is required.	`null`	string
actionDate *optional*	Must be on or after the submit date. Cannot be a future date. If set, action is required.	`null`	string (date)
expirationDate *optional*	Must be on or after the action date if there is one.	`null`	string (date)
reviewNo *optional*	**Maximal length:** `15`	`null`	string
summary *optional*	**Maximal length:** `4000`	`null`	string
yesVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer
noVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer

Name	Description	Default	Schema
abstainVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer
reviewDate *optional*	The IRB review meeting date. A new meeting will be created if one doesn't exist for the given date. Must be on or after the submit date if there is one. Must be on or before the action date if there is one.	`null`	string (date)
institution *required*	Can only contain the research center name and names of affiliates that use the research center IRB. The research center will be added by default when creating a new ProtocolIrbReview.	`null`	< string > array
submitDate *optional*	Required if actionDate is set.	`null`	string (date)

ProtocolIrbReviewDetail

Contains details about the protocol IRB review.

Name	Description	Default	Schema
irbReviewDetailId *optional* *read-only*		`null`	integer
irbReviewId *required*	Cannot be updated.	`null`	integer
detailTypes *required*	The Review Change Type reference list descriptions (case sensitive).	`null`	< string > array
amendmentNo *optional*	**Maximal length:** `10`	`null`	string
receivedDate *optional*		`null`	string (date)
versionDate *optional*	Required for consent types.	`null`	string (date)
detailDescription *optional*	**Maximal length:** `500`	`null`	string
comments *optional*	**Maximal length:** `2000`	`null`	string
reconsentRequired *optional*	Sets all subject statuses to true/false at once.	`false`	boolean

Name	Description	Default	Schema
global *optional*		`false`	boolean

ProtocolManagementDetails

Contains details related to management of an OnCore protocol.

Name	Description	Default	Schema
protocolId *optional* *read-only*		`null`	integer
irbNo *optional*	**Maximal length:** `55`	`null`	string
gcrcParticipation *optional*	The corresponding field in OnCore is named based on the GCRC_NAME configuration setting. Required if the RC_EXPANDED_VALIDATION_OVERRIDE configuration setting is "N" or not set.	`null`	boolean
dsmcReviewFrequency *optional*	Measured in months. **Minimum value:** `0` **Maximum value:** `99`	`null`	integer
prmcReviewRequired *optional*		`null`	boolean
hospitalAccountNo *optional*	**Maximal length:** `40`	`null`	string
internalAccountNo *optional*	**Maximal length:** `50`	`null`	string
priorityScore *optional*	Limited to five characters of precision including the decimal point. **Minimum value:** `0`	`null`	float
nciTrialId *optional*	**Maximal length:** `35`	`null`	string
adminstrativeGroups *optional*		`null`	AdministrativeGroups
codingScheme *optional* *read-only*		`null`	string

ProtocolPrmcReview

Contains details for a PRMC review.

Name	Description	Default	Schema
prmcReviewId *optional* *read-only*		`null`	integer
protocolId *required*	Cannot be updated.	`null`	integer
committee *optional*	The PRMC Committee reference list description (case sensitive).	`null`	string
reviewReason *optional*	The PRMC Reason reference list description (case sensitive).	`null`	string
reviewType *optional*	The PRMC Review Type reference list description (case sensitive).	`null`	string
action *optional*	The PRMC Action Description reference list description (case sensitive). If set, actionDate is required.	`null`	string
actionDate *optional*	Must be on or after the submit date. Cannot be a future date. If set, action is required.	`null`	string (date)
expirationDate *optional*	Must be on or after the action date if there is one.	`null`	string (date)
reviewNo *optional*	**Maximal length:** `15`	`null`	string
summary *optional*	**Maximal length:** `4000`	`null`	string
yesVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer
noVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer
abstainVotes *optional*	**Minimum value:** `0` **Maximum value:** `999`	`null`	integer

CONFIDENTIAL

Name	Description	Default	Schema
reviewDate *optional*	The PRMC review meeting date. A new meeting will be created if one doesn't exist for the given date. Must be on or after the submit date if there is one. Must be on or before the action date if there is one. After it's set, a reviewDate can't be deleted, but can be changed to a new, valid date.	`null`	string (date)
institution *optional*	Can only contain the research center name and names of affiliates that use the research center IRB.	`null`	< string > array
submitDate *optional*	Required if actionDate is set.	`null`	string (date)

ProtocolPrmcReviewCommunication

Contains information about a communication for a PRMC review.

Name	Description	Default	Schema
prmcReviewCommunicationId *optional* *read-only*		`null`	integer
prmcReviewId *required*		`null`	integer
communicationType *required*	PRMC Communication Type reference list description (case sensitive).	`null`	string
sentTo *optional*	ID of the contact the communication was sent to.	`null`	integer
sentDate *optional*	The date the communication was sent. Cannot be a future date.	`null`	string (date)
response *optional*	Review Communication Response reference list description (case sensitive).	`null`	string
respondedBy *optional*	ID of the contact that responded to the communication.	`null`	integer
responseDate *optional*	The date the communication was responded to.	`null`	string (date)
comments *optional*	**Maximal length:** `100`	`null`	string

ProtocolPrmcReviewDetail

Contains details about the protocol PRMC review.

CONFIDENTIAL

Name	Description	Default	Schema
prmcReviewDetailId *optional* *read-only*		`null`	integer
prmcReviewId *required*	Cannot be updated.	`null`	integer
detailTypes *required*	The Review Change Type reference list descriptions (case sensitive).	`null`	< string > array
amendmentNo *optional*	**Maximal length:** `10`	`null`	string
receivedDate *optional*		`null`	string (date)
versionDate *optional*	Required for consent types.	`null`	string (date)
detailDescription *optional*	**Maximal length:** `500`	`null`	string
comments *optional*	**Maximal length:** `2000`	`null`	string

ProtocolPrmcReviewReviewer

Contains information about a reviewer for a PRMC review.

Name	Description	Default	Schema
prmcReviewReviewerId *optional* *read-only*		`null`	integer
prmcReviewId *required*		`null`	integer
contactId *required*	Contact must be a valid PRMC committee appointee for the review.	`null`	integer
reviewerType *optional*	Reviewer Type reference list description (case sensitive).	`null`	string
attended *optional*		`null`	boolean

ProtocolSipConfiguration

Contains details for a protocol's ARP/SIP configuration.

Name	Description	Default	Schema
protocolId *optional* *read-only*		`null`	integer
displayProtocol *required*		`null`	enum (Yes, No, Excluded, Unmarked)
phase *optional*	The Phase reference list description (case sensitive).	`null`	string
displayTitle *required*		`null`	enum (Title, Short Title)
objective *optional*	**Maximal length:** `4000`	`null`	string
treatment *optional*	**Maximal length:** `1024`	`null`	string
description *optional*	**Maximal length:** `4000`	`null`	string
keyEligibility *optional*	**Maximal length:** `4000`	`null`	string
detailedEligibility *optional*	**Maximal length:** `4000`	`null`	string
useDefaultObjective *optional*		`null`	boolean
overrideCancerControl *optional*		`null`	boolean
displayDrugs *optional*		`null`	boolean
displayTherapies *optional*		`null`	boolean
displayGeneticInformation *optional*		`null`	boolean
diseaseDiagnosisOverride *optional*	The Web Descriptions For Disease Codes reference list description (case sensitive).	`null`	< string > array

ProtocolSponsor

Contains information about a sponsor on a protocol.

Name	Description	Default	Schema
protocolSponsorId *optional* *read-only*		`null`	integer
protocolId *required*	Cannot be updated.	`null`	integer
sponsorId *required*	Cannot be updated.	`null`	integer
sponsorProtocolNo *optional*	**Maximal length:** `50`	`null`	string
principalSponsor *optional*		`null`	boolean
sponsorRoles *optional*	The Sponsor Role reference list descriptions (case sensitive).	`null`	< string > array
sponsorGrants *optional*	Grant IDs associated with this protocol sponsor.	`null`	< integer > array

ProtocolStaff

Contains information about staff on a protocol.

Name	Description	Default	Schema
protocolStaffId *optional* *read-only*		`null`	integer
protocolId *required*	Cannot be updated.	`null`	integer
contactId *required*	Cannot be updated. Contact must be active and assignable to protocols.	`null`	integer
role *required*	The Staff Role reference list description (case sensitive).	`null`	string
organization *optional*	Institution or study site name.	`null`	string
canAccessAllProtocolOrganizations *optional*	Can only be set if the contact is also an OnCore user.	`false`	boolean

CONFIDENTIAL

Name	Description	Default	Schema
additionalOrganizationAccess *optional*	Can only be set if the contact is also an OnCore user. Any organizations the user has access to on the contact level are ignored. All values are ignored if canAccessAllProtocolOrganizations is true.	`null`	< string > array
startDate *optional*		`null`	string (date)
stopDate *optional*	Must be on or after the startDate if startDate is not null.	`null`	string (date)
stopReason *optional*	**Maximal length:** `100`	`null`	string

ProtocolStatusChange

Contains details on the protocol's upcoming status change.

Name	Description	Default	Schema
protocolId *required*		`null`	integer
action *required*	Specifies the valid action the user wants to use to advance the protocol status.	`null`	string
actionDate *required*	The date that the protocol status changed. Cannot be a future date.	`null`	string (date)
initiator *optional*	The Protocol Status Change Initiator reference list description (case sensitive). Required for a given status change based on the statuses listed in the PCL_STATUS_DETAILS_REQ_FOR_STATUS OnCore configuration setting.	`null`	string
reason *optional*	The Protocol Status Change reason reference list description (case sensitive). Required for a given status change based on the statuses listed in the PCL_STATUS_DETAILS_REQ_FOR_STATUS OnCore configuration setting.	`null`	string

ProtocolStatusInquiry

Contains details for a protocol status inquiry.

Name	Description	Default	Schema
protocolId *optional*		`null`	integer
currentStatus *optional*		`null`	string

Name	Description	Default	Schema
currentStatusDate *optional*		`null`	string (date)
nextAvailableActions *optional*		`null`	< string > array

ProtocolSubject

Contains information about a subject on a protocol.

Name	Description	Default	Schema
protocolSubjectId *optional* *read-only*		`null`	integer
protocolId *required*		`null`	integer
studySite *required*	Participating study site name.	`null`	string
subjectDemographicsId *optional*	If provided, subjectDemographics must be null.	`null`	integer
subjectDemographics *optional*		`null`	SubjectDemographics
status *optional* *read-only*		`null`	enum (CONSENT WAIVED, CONSENT REFUSED, CONSENTED, WITHDRAWN, ELIGIBLE, ELIGIBLE(O), NOT ELIGIBLE, ON STUDY, ON TREATMENT, OFF TREATMENT, ON FOLLOW UP, OFF STUDY, EXPIRED)

ProtocolSubjectAttachment

Contains data for a protocol subject attachment. This resource covers only attachments created and managed under Subject Console > Documents/Info.

Name	Description	Default	Schema
protocolSubjectAttachmentId *optional* *read-only*		`null`	integer
protocolSubjectId *required*	Cannot be updated.	`null`	integer
description *optional*	Description of the attachment. **Maximal length:** `255`	`null`	string
documentType *required*	Document Type must be selectable from Subject Console > Documents/Info > Attachments > Add or Edit > Document Type drop-down list.	`null`	string
versionDate *required*		`null`	string (date)
fileName *optional*	If fileName is provided, then url must be null. **Maximal length:** `255`	`null`	string
url *optional*	If url is provided, then fileName must be null. **Maximal length:** `2000`	`null`	string

ProtocolSubjectConsent

Contains information about a protocol consent for a subject.

Name	Description	Default	Schema
protocolSubjectId *required*		`null`	integer
consentId *required*		`null`	integer
signedDate *required*	Must be on or after the consent's Approved Date and cannot be a future date.	`null`	string (date)
status *required*		`null`	enum (Accepted, Refused)

ProtocolSubjectIdentifier

Contains a protocol subject identifier.

Name	Description	Default	Schema
identifier *required*	**Maximal length:** `50`	`null`	string
identifierType *required*	Protocol Subject Identifier Type reference list description (case sensitive).	`null`	string

ProtocolSubjectOnStudy

Contains on study information for a protocol subject.

Name	Description	Default	Schema
protocolSubjectId *optional* *read-only*		`null`	integer
sequenceNo *optional*	Can only be updated when protocol's Automated Sequence No. is set to No. **Maximal length:** `25`	`null`	string
onStudyDate *optional*	Must be on or before the protocol subject's Off Treatment Date, On Follow-Up Date, and earliest On Arm Date. Must be a date when the protocol is Open to Accrual. Cannot be in the future.	`null`	string (date)
zipAtRegistration *optional*	**Maximal length:** `10`	`null`	string
additionalProtocolSubjectIds *optional*		`null`	< ProtocolSubjectIdentifier > array

ProtocolSubjectTreatment

Contains protocol subject treatment details.

Name	Description	Default	Schema
protocolSubjectId *required*		`null`	integer
treatmentId *optional* *read-only*		`null`	integer
stepCode *required*		`null`	string

Name	Description	Default	Schema
armCode *required*		`null`	string
armDescription *optional* *read-only*		`null`	string
levelCode *optional*		`null`	string
levelDescription *optional* *read-only*		`null`	string
onArmDate *optional*		`null`	string (date)
onTreatmentDate *optional*		`null`	string (date)
offArmDate *optional*		`null`	string (date)

ProtocolSummaryAccrual

Contains summary accrual information for a protocol.

Name	Description	Default	Schema
protocolSummaryAccrualId *optional* *read-only*		`null`	integer
protocolId *required*		`null`	integer
fromDate *required*	Must be on or before the thruDate and be in the same calendar year. Future dates are not allowed.	`null`	string (date)
thruDate *required*	Must be on or after the fromDate and be in the same calendar year. Future dates are not allowed.	`null`	string (date)
accrual *required*	**Minimum value:** `0` **Maximum value:** `99999999`	`null`	integer
institution *required*	The protocol institution credited with the accrual group.	`null`	string
gender *optional*	Biological Sex reference list description (case insensitive).	`null`	string

Name	Description	Default	Schema
ageGroup *optional*		`null`	enum (0-9, 10-19, 20-29, 30-39, 40-49, 50-59, 60-69, 70-79, 80-89, 90-99, 100+, Unknown)
ethnicity *optional*	Subject Ethnicity reference list description (case sensitive).	`null`	string
race *optional*	Race reference list description (case sensitive).	`null`	string
diseaseSite *optional*	Data Table 3 Sites reference list description (case sensitive). Must be null if the protocol library is not Oncology.	`null`	string
diagnosis *optional*	Diagnosis reference list description (case sensitive). Must be null if the protocol library is Oncology.	`null`	string
recruitedBy *optional*	The contact ID of the recruiter.	`null`	integer
zipCode *optional*	**Maximal length:** 15	`null`	string

ProtocolTask

Contains details about a protocol task.

Name	Description	Default	Schema
taskListId *optional* *read-only*		`null`	integer
taskId *optional* *read-only*		`null`	integer
name *optional* *read-only*		`null`	string
notApplicable *optional*		`null`	boolean
completedDate *optional*	Cannot be a future date.	`null`	string (date)

ProtocolTaskList

Contains details about a protocol task list.

Name	Description	Default	Schema
taskListId *optional* *read-only*		`null`	integer
protocolId *optional*		`null`	integer
name *optional*		`null`	string
status *optional*		`null`	enum (New, In Progress, Complete)

ProtocolTreatment

Contains protocol treatment details.

Name	Description	Default	Schema
protocolId *required*		`null`	integer
steps *optional*	Contains protocol treatment step information.	`null`	< ProtocolTreatmentStep > array

ProtocolTreatmentArm

Contains details specific to a treatment arm.

Name	Description	Default	Schema
armCode *required*	Indicates a specific treatment arm.	`null`	string
armDescription *optional*		`null`	string
suspended *optional*		`null`	boolean
levels *optional*		`null`	< ProtocolTreatmentLevel > array

ProtocolTreatmentLevel

Contains details specific to a treatment level.

Name	Description	Default	Schema
levelCode *required*	Indicates a specific treatment level.	`null`	string
levelDescription *optional*		`null`	string
suspended *optional*		`null`	boolean

ProtocolTreatmentStep

Contains details specific to a treatment step.

Name	Description	Default	Schema
stepCode *required*	Indicates a specific treatment step.	`null`	string
stepType *required*		`null`	enum (Registration, Randomization)
arms *optional*		`null`	< ProtocolTreatmentArm > array

Sponsor

Contains information about a sponsor.

Name	Description	Default	Schema
sponsorId *optional* *read-only*		`null`	integer
sponsorCode *optional*	**Maximal length:** `20`	`null`	string
sponsorName *required*	**Maximal length:** `75`	`null`	string
sponsorType *required*	Sponsor Type reference list description (case sensitive).	`null`	string
active *optional*		`true`	boolean

SponsorAddress

Contains information about a sponsor address.

Name	Description	Default	Schema
sponsorAddressId *optional* *read-only*		`null`	integer
sponsorId *required*	Cannot be updated.	`null`	integer
addressCode *optional*	If provided, must be unique for the sponsor. **Maximal length:** `20`	`null`	string
addressName *required*	Must be unique for the sponsor. **Maximal length:** `75`	`null`	string
organizationName *required*	**Maximal length:** `55`	`null`	string
addressLine1 *optional*	**Maximal length:** `100`	`null`	string
addressLine2 *optional*	**Maximal length:** `100`	`null`	string
city *optional*	**Maximal length:** `100`	`null`	string
stateProvince *optional*	State reference list description (case sensitive). If a country is specified, this must be a valid state or province in that country.	`null`	string
country *optional*	Country reference list description (case sensitive).	`null`	string
postalCode *optional*	**Maximal length:** `20`	`null`	string
email *optional*	Must be formatted as a valid email address. **Maximal length:** `254`	`null`	string

SponsorGrant

Contains information about a sponsor grant.

Name	Description	Default	Schema
sponsorGrantId *optional* *read-only*		`null`	integer

Name	Description	Default	Schema
sponsorId *required*	Cannot be updated.	`null`	integer
fundAccountNo *optional*	**Maximal length:** `18`	`null`	string
grantNo *optional*	**Maximal length:** `18`	`null`	string
piContactId *required*	Contact ID of principal investigator.	`null`	integer
grantContractTitle *required*	**Maximal length:** `250`	`null`	string

SubjectDemographics

Contains details about a subject's demographics.

Name	Description	Default	Schema
subjectDemographicsId *optional* *read-only*		`null`	integer
subjectSource *optional* *read-only*		`null`	enum (OnCore, Onstage)
mrn *optional*	Required when creating a protocol subject and generateMrn is false. **Maximal length:** `40`	`null`	string
lastName *required*	**Maximal length:** `80`	`null`	string
firstName *required*	**Maximal length:** `55`	`null`	string
middleName *optional*	**Maximal length:** `65`	`null`	string
suffix *optional*	**Maximal length:** `20`	`null`	string
birthDate *optional*	Required unless birthDateNotAvailable is true.	`null`	string (date)
approximateBirthDate *optional*	Must be false if birthDate is not populated.	`null`	boolean

Name	Description	Default	Schema
birthDateNotAvailable *optional*		`null`	boolean
expiredDate *optional*		`null`	string (date)
approximateExpiredDate *optional*	Must be false if expiredDate is not populated.	`null`	boolean
lastDateKnownAlive *optional*		`null`	string (date)
ssn *optional*	Must be formatted as a valid SSN. **Maximal length:** `11` **Minimal length:** `9`	`null`	string
gender *required*	Biological Sex reference list description (case insensitive).	`null`	string
ethnicity *required*	Subject Ethnicity reference list description (case sensitive).	`null`	string
race *required*		`null`	< string > array
subjectComments *optional*	**Maximal length:** `4000`	`null`	string
additionalSubjectIds *optional*		`null`	< SubjectIdentifier > array
streetAddress *optional*	**Maximal length:** `100`	`null`	string
addressLine2 *optional*	**Maximal length:** `100`	`null`	string
city *optional*	**Maximal length:** `20`	`null`	string
state *optional*	State reference list description (case sensitive).	`null`	string
zip *optional*	**Maximal length:** `10`	`null`	string
county *optional*	County reference list description (case sensitive).	`null`	string

Name	Description	Default	Schema
country *optional*	Country reference list description (case sensitive).	`null`	string
phoneNo *optional*	**Maximal length:** `20`	`null`	string
alternatePhoneNo *optional*	**Maximal length:** `20`	`null`	string
email *optional*	Must be formatted as a valid email address. **Maximal length:** `55`	`null`	string

SubjectIdentifier

Contains a subject identifier.

Name	Description	Default	Schema
identifier *required*	**Maximal length:** `50`	`null`	string
identifierType *required*	Subject Identifier Type reference list description (case sensitive).	`null`	string
identifierOwner *optional*	**Maximal length:** `200`	`null`	string

UpdateError

An error occurred while processing this request.

Name	Description	Default	Schema
message *optional*	The error message accompanying this response. Example: Protocol 123 does not exist.	`null`	string
errorType *optional*	The type of the error. Can be used to distinguish the actual error type that occurred.	`null`	string
field *optional*	Name of the field that was invalid for certain validation errors.	`null`	string
invalidFields *optional*	Collection of validation errors that occurred when processing the request input data.	`null`	< InvalidField > array