

Database & Data Model — FindLostPuppy

Relational Schema

1. `users`

* `id` (UUID / string, Primary Key) * `name` (string) * `email` (string, Unique) * `phone` (string, Optional) * `created_at` (ISO timestamp)

2. `owner_profiles`

* `id` (UUID / string, Primary Key) * `user_id` (Foreign Key → `users.id`) * `full_name` (string) * `phone` (string) * `email` (string) * `address` (string, **STRICTLY PRIVATE**) * `state` (string) * `district` (string) * `mandal_or_municipality` (string) * `street_or_locality` (string) * `pin_code` (string) * `preferred_contact` (`phone` | `email` | `whatsapp`) * `has_location_consent` (boolean) * `latitude` (float, approximate) * `longitude` (float, approximate) * `approximate_area` (string, **PUBLIC SAFE REPRESENTATION**) * `updated_at` (ISO timestamp)

3. `dogs`

* `id` (UUID / string, Primary Key) * `owner_id` (Foreign Key → `owner_profiles.id`) * `name` (string) * `breed` (string) * `gender` (`Male` | `Female` | `Unknown`) * `age` (string) * `size` (string enum) * `color` (string) * `coat_description` (text) * `distinguishing_marks` (text) * `collar_info` (string) * `microchip_id` (string) * `temperament` (string) * `medical_notes` (text) * `primary_photo` (URL / base64 string) * `photos` (array of URLs / strings) * `created_at` (ISO timestamp)

4. `lost_reports`

* `id` (string, formatted e.g. `LOST-BRUNO-881`, Primary Key) * `dog_id` (Foreign Key → `dogs.id`) * `owner_id` (Foreign Key → `owner_profiles.id`) * `owner_approximate_location` (string, safe) * `last_known_location` (string) * `last_known_latitude` (float, optional) * `last_known_longitude` (float, optional) * `date_lost` (date) * `time_lost` (string) * `additional_notes` (text) * `status` (`LOST` | `SIGHTED` | `REUNITED` | `CLOSED`) * `contact_mechanism` (JSON with visibility flags) * `sighting_count` (integer) * `created_at` (ISO timestamp) * `updated_at` (ISO timestamp)

5. `sightings`

* `id` (string, Primary Key) * `report_id` (Foreign Key → `lost_reports.id`) * `dog_name` (string) * `date` (date) * `time` (string) * `location` (string) * `photo` (URL / string, optional) * `description` (text) * `reporter_name` (string, optional) * `reporter_phone` (string, **PRIVATE**) * `reporter_email` (string, **PRIVATE**) * `created_at` (ISO timestamp)