

Firestore setup for FindLostPuppy

Use the Spark plan.

Collections

- `profiles/{uid}` : one owner profile per Firebase Auth user.
- `pets/{uid}` : one pet per owner, updated in place.
- `missing_reports/{uid}` : one owner safety/report row, updated in place.
- `sightings/{sightingId}` : private sighting records.
- `app_suggestions/{suggestionId}` : user feedback and screenshots for admin review.

This follows SCD Type 1 for owner, pet, and report records: updates overwrite the same document instead of creating duplicates. Deletes are hard deletes.

Console steps

1. Project overview → Add app → Web. 2. App nickname: `FindLostPuppy Web`. 3. Copy the Firebase config values into `.env`. 4. Authentication → Sign-in method → Enable `Email/Password`, then enable `Email link`. 5. Authentication → Settings → Authorized domains: - `localhost` - `jksurampudi5.github.io` - Add the exact production hostname users visit, preserving protocol and host spelling. Do not mix `www` and non-`www` hosts. 6. Authentication → Settings → Authorized domains / OAuth redirect setup: - Keep `VITE_FIREBASE_AUTH_DOMAIN` set to the Firebase project's auth domain (`findlostpuppy.firebaseio.com` unless the Firebase console shows another value). - The app must start and return on the same deployed origin, for example `https://jksurampudi5.github.io/findlostpuppy/`. A flow started on another protocol or hostname can lose redirect state even when the Firebase config is correct. 7. Firestore Database → Create database → Production mode. 8. Firestore Rules → paste `firebase.firestore.rules`. 9. Storage → Get started → Production mode. 10. Storage Rules → paste `firebase.storage.rules`.

Required env values

```
`` env VITE_FIREBASE_API_KEY= VITE_FIREBASE_AUTH_DOMAIN=findlostpuppy.firebaseio.com
VITE_FIREBASE_PROJECT_ID=findlostpuppy VITE_FIREBASE_STORAGE_BUCKET=findlostpuppy.appspot.com
VITE_FIREBASE_MESSAGING_SENDER_ID= VITE_FIREBASE_APP_ID= ``
```