= Logic Big

Tutorials Core Java Tutorials

Java 11 Features

Low Level Design made easy

Java 11 - String Changes

[Last Updated: Sep 29, 2018]

Java 11, added various new methods in java.lang.String. Let's see each one of them with examples.

Stripping white spaces

Following new methods have been added to remove white spaces:

```
public String stripLeading()

public String stripTrailing()
```

Example:

```
package com.logicbig.example;

public class StringStripExample {
    public static void main(String[] args) {
        String s = " test string ";
        System.out.printf("'%s'%n", s);
        String striped = s.strip();
        System.out.printf("strip():%n '%s'%n", striped);

        striped = s.stripLeading();
        System.out.printf("stripLeading():%n '%s'%n", striped);

        striped = s.stripTrailing();
        System.out.printf("stripTrailing():%n '%s'%n", striped);
    }
}
```

```
' test string '
strip():
  'test string'
stripLeading():
  'test string '
stripTrailing():
  ' test string'
```

strip() vs trim()

strip() is <u>Unicode whitespace</u> aware, whereas the existing method <u>trim()</u> removes any space which is less than or equal to (\u0020).

PROJECTS

Pr

```
public class StringStripVsTrimExample {
  public static void main(String[] args) {
    String s = "test string\u205F";
    String striped = s.strip();
    System.out.printf("'%s'%n", striped);

    String trimmed = s.trim();
    System.out.printf("'%s'%n", trimmed);
  }
}
```

```
'test string'
'test string'
```

See also JDK-8200378 .

Blank strings

```
public boolean isBlank()
```

This method returns true if the string is empty or contains only white space codepoints, otherwise false. The existing method isEmpty() returns true if length() is 0.

```
public class StringIsBlankExample {

public static void main(String[] args) {
    String s = " ";
    //old isEmpty() method
    boolean empty = s.isEmpty();
    System.out.println(empty);
    //new isBlank()
    boolean blank = s.isBlank();
    System.out.println(blank);
}
```

```
false
true
```

Streaming lines

```
public Stream<String> lines()
```

```
public class StringLinesExample {
  public static void main(String[] args) {
    String s = "jujube\nsatsuma\nguava";
    s.lines()
    .forEach(System.out::println);
  }
}
```

```
jujube
satsuma
```











Core Java Tuto

Java 16 Features
Java 15 Features
Java 14 Features
Java 13 Features
Java 12 Features

Java 11 Features

guava

Repeating

```
public String repeat(int count)
```

This method returns a string whose value is repeated 'count' times

```
public class StringRepeatExample {
  public static void main(String[] args) {
    String s = "-";
    String newString = s.repeat(10);
    System.out.println(newString);
  }
}
```

Example Project

Dependencies and Technologies Used:

• JDK 9.0.1

```
Recent Tutorial
 Spring - Built-in o
 Spring - DataBing
 Spring - Condition
 Spring - Generic
 Spring - Creating
 Spring - Converte
 Spring - Creating
 Spring - Using Co
 ApplicationContex
 Python - Tuples
 Python - Lists
 Python - Naming
 Python - Built In
 Python None Type
 Python Boolean
 Python Keywords
 Python String
 Python Numbers
 Python Variables
 Python Comment
 Python Basic Syn
 Python with Intel
 Python language
 Installing Python
 Spring - Mixed va
 Annotations and :
 Spring Annotation
 Spring Core Valid
 Java Bean Validat
 validators for the
 Spring - The Use
 Annotation
 Spring - The Use
 Configuration
 Spring - Use of Pi
 Spring - Using Be
 based method sig
 Spring - Copying
 Spring - Obtainin
```

Java 10 Features

Java 9 Module Sy

Java 9 Misc Featu

Java 9 JShell

```
Java 11 - New String methods

java-11-string-changes
src
com
logicbig

public class StringRepeatExample {
public static void main(String[] args) {
```

PropertyDescripto

```
example
StringslankExample.java
StringPapeatExample.java
StringStripExample.java
StringStripVsTrimExample.java

StringStripVsTrimExample.java

StringStripVsTrimExample.java

StringStripVsTrimExample.java
```

Project Structure

(UP)

```
java-11-string-changes
src
com
logicbig
example
StringlsBlankExample.java
StringLinesExample.java
StringRepeatExample.java
StringStripExample.java
StringStripExample.java
```

```
package com.logicbig.example;

public class StringIsBlankExample {
    public static void main(String[] args) {
        String s = " ";
        //old isEmpty() method
        boolean empty = s.isEmpty();
        System.out.println(empty);
        //new isBlank()
        boolean blank = s.isBlank();
        System.out.println(blank);
    }
}
```

```
package com.logicbig.example;

public class StringLinesExample {
    public static void main(String[] args) {
        String s = "jujube\nsatsuma\nguava";
        s.lines()
        .forEach(System.out::println);
```

}

(UP)

```
package com.logicbig.example;

public class StringRepeatExample {
    public static void main(String[] args) {
        String s = "-";
        String newString = s.repeat(10);
        System.out.println(newString);
    }
}
```

```
package com.logicbig.example;

public class StringStripExample {
    public static void main(String[] args) {
        String s = " test string ";
        System.out.printf("'%s'%n", s);
        String striped = s.strip();
        System.out.printf("strip():%n '%s'%n", striped);

        striped = s.stripLeading();
        System.out.printf("stripLeading():%n '%s'%n", striped);

        striped = s.stripTrailing();
        System.out.printf("stripTrailing():%n '%s'%n", striped);
    }
}
```

```
package com.logicbig.example;

public class StringStripVsTrimExample {
    public static void main(String[] args) {
        String s = "test string\u2005F";
        String striped = s.strip();
        System.out.printf("'%s'%n", striped);

        String trimmed = s.trim();
        System.out.printf("'%s'%n", trimmed);
    }
}
```



(UP)







