

*sample book*

*me*



---

## *Table of contents*

---

List of Figures	5
List of Tables	7
1 About this R	9
2 One	11
3 Two	13
4 Three	15
5 Four	17
6 Five	19
7 Six	21
8 Seven	23
9 Eight	25
10 Nine	27
11 Ten	29



---

## *List of Figures*

---

11.1 Sample 1 . . . . .	29
11.2 Sample 2 . . . . .	30
11.3 Sample 3 . . . . .	30
11.4 Sample 4 . . . . .	31
11.5 Sample 5 . . . . .	32
11.6 Sample 6 . . . . .	32
11.7 Sample 7 . . . . .	33
11.8 Sample 8 . . . . .	34
11.9 Sample 9 . . . . .	34
11.10Sample 10 . . . . .	35



---

## *List of Tables*

---





# 1

## *About this R*

```
library('tidyverse')
```

```
-- Attaching core tidyverse packages -----
tidyverse 2.0.0 --
v dplyr      1.1.2      v readr      2.1.4
v forcats    1.0.0      v stringr    1.5.0
v ggplot2    3.4.2      v tibble     3.2.1
v lubridate  1.9.2      v tidyr      1.3.0
v purrr      1.0.1
-- Conflicts -----
tidyverse_conflicts() --
x dplyr::filter() masks stats::filter()
x dplyr::lag()     masks stats::lag()
i Use the conflicted package (<http://conflicted.r-lib.org/>) to
force all conflicts to become errors
```

```
paste("RStudio version", "2023.03.0+386")
```

```
[1] "RStudio version 2023.03.0+386"
```

```
paste("quarto version", paste(quarto::quarto_version(),
  ↪ sep='. '))
```

```
[1] "quarto version 1.4.11"
```

```
tibble::enframe(Sys.info()) %>%
  filter(name %in%
    ↪ c('sysname', 'release', 'version', 'machine')) %>%
```

```
knitr::kable()
```

name	value
sysname	Windows
release	10 x64
version	build 22621
machine	x86-64

```
tibble::as_tibble(R.Version()) %>%
  tidyr::pivot_longer(everything()) %>%
  knitr::kable()
```

name	value
platform	x86_64-w64-mingw32
arch	x86_64
os	mingw32
crt	ucrt
system	x86_64, mingw32
status	
major	4
minor	3.0
year	2023
month	04
day	21
svn rev	84292
language	R
version.string	R version 4.3.0 (2023-04-21 ucrt)
nickname	Already Tomorrow

**2**

*One*



**3**

*Two*



4

*Three*





5

*Four*



**6**

*Five*



7

*Six*



8

*Seven*





9

*Eight*



**10**

*Nine*



# 11

## Ten

```
library(ggplot2)

ggplot(mtcars, aes(x = wt, y = mpg)) +
  geom_point()
```




Figure 11.1: Sample 1

```
ggplot(mtcars, aes(x = wt, y = mpg)) +
  geom_point()
```



Figure 11.2: Sample 2

```
ggplot(mtcars, aes(x = wt, y = mpg)) +  
  geom_point()
```



Figure 11.3: Sample 3

```
ggplot(mtcars, aes(x = wt, y = mpg)) +  
  geom_point()
```



Figure 11.4: Sample 4

```
ggplot(mtcars, aes(x = wt, y = mpg)) +  
  geom_point()
```



Figure 11.5: Sample 5

```
ggplot(mtcars, aes(x = wt, y = mpg)) +  
  geom_point()
```



Figure 11.6: Sample 6



```
ggplot(mtcars, aes(x = wt, y = mpg)) +  
  geom_point()
```



Figure 11.7: Sample 7

```
ggplot(mtcars, aes(x = wt, y = mpg)) +  
  geom_point()
```



Figure 11.8: Sample 8

```
ggplot(mtcars, aes(x = wt, y = mpg)) +  
  geom_point()
```



Figure 11.9: Sample 9

```
ggplot(mtcars, aes(x = wt, y = mpg)) +  
  geom_point()
```




Figure 11.10: Sample 10