- **B Grade Is 100% Tested for Noise**
  30 nV/√Hz Max at f = 10 Hz
  12 nV/√Hz Max at f = 1 kHz
- **Low Input Offset Voltage . . . 500 μV Max**
- **Excellent Offset Voltage Stability With Temperature . . . 0.5 μV/°C Typ**
- **Rail-to-Rail Output Swing**
- **Low Input Bias Current**
  1 pA Typ at T_A = 25°C
- **Common-Mode Input Voltage Range Includes the Negative Rail**
- **Fully Specified For Both Single-Supply and Split-Supply Operation**

description

The TLC220x, TLC220xA, TLC220xB, and TLC220xY are precision, low-noise operational amplifiers using Texas Instruments Advanced LinCMOS™ process. These devices combine the noise performance of the lowest-noise JFET amplifiers with the dc precision available previously only in bipolar amplifiers. The Advanced LinCMOS™ process uses silicon-gate technology to obtain input offset voltage stability with temperature and time that far exceeds that obtainable using metal-gate technology. In addition, this technology makes possible input impedance levels that meet or exceed levels offered by top-gate JFET and expensive dielectric-isolated devices.

The combination of excellent dc and noise performance with a common-mode input voltage range that includes the negative rail makes these devices an ideal choice for high-impedance, low-level signal-conditioning applications in either single-supply or split-supply configurations.

TYPICAL EQUIVALENT INPUT NOISE VOLTAGE vs FREQUENCY



The device inputs and outputs are designed to withstand –100-mA surge currents without sustaining latch-up. In addition, internal ESD-protection circuits prevent functional failures at voltages up to 2000 V as tested under MIL-PRF-38535, Method 3015.2; however, care should be exercised in handling these devices as exposure to ESD may result in degradation of the parametric performance.

The C-suffix devices are characterized for operation from 0°C to 70°C. The I-suffix devices are characterized for operation from –40°C to 85°C. The M-suffix devices are characterized for operation over the full military temperature range of –55°C to 125°C.

TLC2201 AVAILABLE OPTIONS

T_A	V_{IO}max AT 25°C	$V_n$max f = 10 Hz AT 25°C	$V_n$max f = 1 kHz AT 25°C	PACKAGED DEVICES				CHIP FORM‡ (Y)
				SMALL OUTLINE† (D)	CHIP CARRIER (FK)	CERAMIC DIP (JG)	PLASTIC DIP (P)	
0°C to 70°C	200 µV 200 µV 500 µV	35 nV/√Hz 30 nV/√Hz —	15 nV/√Hz 12 nV/√Hz —	TLC2201ACD TLC2201BCD TLC2201CD	—	—	TLC2201ACP TLC2201BCP TLC2201CP	TLC2201Y
–40°C to 85°C	200 µV 200 µV 500 µV	35 nV/√Hz 30 nV/√Hz —	15 nV/√Hz 12 nV/√Hz —	TLC2201AID TLC2201BID TLC2201ID	—	—	TLC2201AIP TLC2201BIP TLC2201IP	—
–55°C to 125°C	200 µV 200 µV 500 µV	35 nV/√Hz 30 nV/√Hz —	15 nV/√Hz 12 nV/√Hz —	TLC2201AMD TLC2201BMD TLC2201MD	TLC2201AMFK TLC2201BMFK TLC2201MFK	TLC2201AMJG TLC2201BMJG TLC2201MJG	TLC2201AMP TLC2201BMP TLC2201MP	—

† The D packages are available taped and reeled. Add R suffix to device type (e.g. TLC220xBCDR).
‡ Chip forms are tested at 25°C only.

TLC2202 AVAILABLE OPTIONS

T_A	V_{IO}max AT 25°C	$V_n$max f = 10 Hz AT 25°C	$V_n$max f = 1 kHz AT 25°C	PACKAGED DEVICES				CHIP FORM‡ (Y)
				SMALL OUTLINE† (D)	CHIP CARRIER (FK)	CERAMIC DIP (JG)	PLASTIC DIP (P)	
0°C to 70°C	500 µV 500 µV 1 mV	30 nV/√Hz 35 nV/√Hz —	12 nV/√Hz 15 nV/√Hz —	TLC2202BCD TLC2202ACD TLC2202CD	— — —	— — —	TLC2202BCP TLC2202ACP TLC2202CP	TLC2202Y
–40°C to 85°C	500 µV 500 µV 1 mV	30 nV/√Hz 35 nV/√Hz —	12 nV/√Hz 15 nV/√Hz —	TLC2202BID TLC2202AID TLC2202ID	— — —	— — —	TLC2202BIP TLC2202AIP TLC2202IP	—
–55°C to 125°C	500 µV 500 µV 1 mV	30 nV/√Hz 35 nV/√Hz —	12 nV/√Hz 15 nV/√Hz —	TLC2202BMD TLC2202AMD TLC2202MD	TLC2202BMFK TLC2202AMFK TLC2202MFK	TLC2202BMJG TLC2202AMJG TLC2202MJG	TLC2202BMP TLC2202AMP TLC2202MP	—

† The D packages are available taped and reeled. Add R suffix to device type (e.g. TLC220xBCDR).
‡ Chip forms are tested at 25°C only.

TLC2201
D, JG, OR P PACKAGE
(TOP VIEW)



TLC2202
JG OR P PACKAGE
(TOP VIEW)



TLC2202
D PACKAGE
(TOP VIEW)



TLC2201
FK PACKAGE
(TOP VIEW)



TLC2202
FK PACKAGE
(TOP VIEW)



NC – No internal connection

equivalent schematic (each amplifier)



ACTUAL DEVICE COMPONENT COUNT		
COMPONENT	**TLC2201**	**TLC2202**
Transistors	17	34
Resistors	2	2
Diodes	1	4
Capacitors	1	2

TLC2201Y chip information

This chip, when properly assembled, displays characteristics similar to the TLC2201C. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding path. Chips may be mounted with conductive epoxy or a gold-silicon preform.

BONDING PAD ASSIGNMENTS





CHIP THICKNESS: 15 MILS TYPICAL

BONDING PADS: 4 × 4 MILS MINIMUM

$T_J$max = 150°C

TOLERANCES ARE ±10%.

ALL DIMENSIONS ARE IN MILS.

PIN (4) IS INTERNALLY CONNECTED TO BACK SIDE OF CHIP.

TERMINAL NUMBERS ARE FOR THE D, JG, AND P PACKAGES.

TLC2202Y chip formation

This chip, when properly assembled, displays characteristics similar to the TLC2202C. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. Chips may be mounted with conductive epoxy or a gold-silicon preform.

BONDING PAD ASSIGNMENTS





CHIP THICKNESS: 15 MILS TYPICAL

BONDING PADS: 4 × 4 MILS MINIMUM

$T_J$max = 150°C

TOLERANCES ARE ±10%.

ALL DIMENSIONS ARE IN MILS.

PIN (4) IS INTERNALLY CONNECTED TO BACKSIDE OF CHIP.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage, V_{DD+} (see Note 1) . . . . . 8 V
Supply voltage, V_{DD-} . . . . . –8 V
Differential input voltage, V_{ID} (see Note 2) . . . . . ±16 V
Input voltage, V_I (any input) . . . . . ±8 V
Input current, I_I (each input) . . . . . ±5 mA
Output current, I_O (each output) . . . . . ±50 mA
Duration of short-circuit current at (or below) 25°C (see Note 3) . . . . . unlimited
Continuous total dissipation . . . . . See Dissipation Rating Table
Operating free-air temperature range, T_A: C suffix . . . . . 0°C to 70°C
I suffix . . . . . –40°C to 85°C
M suffix . . . . . –55°C to 125°C
Storage temperature range . . . . . –65°C to 150°C
Case temperature for 60 seconds: FK package . . . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D or P package . . . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: JG package . . . . . 300°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values except differential voltages are with respect to the midpoint between V_{DD+} and V_{DD-}.
2. Differential voltages are at IN+ with respect to IN–.
3. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating in not exceeded.

DISSIPATION RATING TABLE

PACKAGE	$T_A \le 25°C$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25°C$	$T_A = 70°C$ POWER RATING	$T_A = 85°C$ POWER RATING	$T_A = 125°C$ POWER RATING
D–8	725 mW	5.8 mW/°C	464 mW	377 mW	145 mW
D–14	950 mW	7.6 mW/°C	608 mW	494 mW	190 mW
FK	1375 mW	11.0 mW/°C	880 mW	715 mW	275 mW
JG	1050 mW	8.4 mW/°C	672 mW	546 mW	210 mW
P	1000 mW	8.0 mW/°C	640 mW	520 mW	200 mW

recommended operating conditions

	C SUFFIX		I SUFFIX		M SUFFIX		UNIT
	MIN	MAX	MIN	MAX	MIN	MAX	
Supply voltage, V_{DD}±	±2.3	±8	±2.3	±8	±2.3	±8	V
Common-mode input voltage, V_{IC}	V_{DD-}	$V_{DD+}-2.3$	V_{DD-}	$V_{DD+}-2.3$	V_{DD-}	$V_{DD+}-2.3$	V
Operating free-air temperature, T_A	0	70	–40	85	–55	125	°C

TLC2201C electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201C			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	500	μV
			Full range			600	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5		pA
			Full range			100	
I_{IB}	Input bias current		25°C		1		pA
			Full range			100	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		V
			Full range	4.7			
V_{OM-}	Maximum negative peak output voltage swing		25°C	−4.7	−4.9		V
			Full range	−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	400	560		V/mV
			Full range	300			
		V_O = ±4 V, R_L = 10 kΩ	25°C	90	100		
			Full range	70			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	Full range	85			dB
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	90	110		dB
			Full range	85			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.1	1.5	mA
			Full range			1.5	

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150 °C extrapolated to T_A = 25 °C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201C operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201C			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	2	2.7		V/μs
			Full range	1.5			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°		

† Full range is 0°C to 70°C.

TLC2201C electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AC			TLC2201BC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	200		80	200	µV
			Full range			300			300	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005		0.001	0.005	µV/mo
I_{IO}	Input offset current		25°C		0.5			0.5		pA
			Full range			100			100	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			100			100	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OM-}	Maximum negative peak output voltage swing		25°C	−4.7	−4.9		−4.7	−4.9		V
			Full range	−4.7			−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	400	560		400	560		V/mV
			Full range	300			300			
		V_O = ±4 V, R_L = 10 kΩ	25°C	90	100		90	100		
			Full range	70			70			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	115		90	115		dB
			Full range	85			85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	90	110		90	110		dB
			Full range	85			85			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.1	1.5		1.1	1.5	mA
			Full range			1.5			1.5	

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150 °C extrapolated to T_A = 25 °C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201C operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AC			TLC2210BC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	2	2.7		2	2.7		V/μs
			Full range	1.5			1.5			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°			48°		

† Full range is 0°C to 70°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2201A and on all devices for the TLC2201B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2201C electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201C			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	500	μV
			Full range			600	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5		pA
			Full range			100	
I_{IB}	Input bias current		25°C		1		pA
			Full range			100	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		V
			Full range	4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50	mV
			Full range			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		V/mV
			Full range	100			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		
			Full range	15			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	110		dB
			Full range	85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	90	110		dB
			Full range	85			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1	1.5	mA
			Full range			1.5	

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150 °C extrapolated to T_A = 25 °C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201C operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201C			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.8	2.5		V/μs
			Full range	1.3			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.8		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		45°		

† Full range is 0°C to 70°C.

TLC2201C electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AC			TLC2201BC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	200		80	200	μV
			Full range			300			300	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5			0.5		pA
			Full range			100			100	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			100			100	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50		0	50	mV
			Full range			50			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		150	315		V/mV
			Full range	100			100			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		25	55		
			Full range	15			15			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	110		90	110		dB
			Full range	85			85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	90	110		90	110		dB
			Full range	85			85			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1	1.5		1	1.5	mA
			Full range			1.5			1.5	

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150 °C extrapolated to T_A = 25 °C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201C operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AC			TLC2210BC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V,	25°C	1.8	2.5		1.8	2.5		V/μs
		R_L = 10 kΩ, C_L = 100 pF	Full range	1.3			1.3			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.8			1.8		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		45°			45°		

† Full range is 0°C to 70°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2201A and on all devices for the TLC2201B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2202C electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise specified)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202C			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	1000	μV
			Full range			1150	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω	Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω	25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	25°C		0.5		pA
			Full range			100	
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω	25°C		1		
			Full range			100	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		V
			Full range	4.7			
V_{OM-}	Maximum negative peak output voltage swing	R_L = 10 kΩ	25°C	−4.7	−4.9		
			Full range	−4.7			V
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	300	560		V/mV
			Full range	200			
		V_O = ±4 V, R_L = 10 kΩ	25°C	50	100		
			Full range	25			
CMRR	Common-mode rejection ratio	V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	80	115		dB
			Full range	80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	80	110		dB
			Full range	80			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.8	2.7	mA
			Full range			2.7	

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150 °C extrapolated to T_A = 25 °C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202C operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202C			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.8	2.7		V/μs
			Full range	1.3			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°		

† Full range is 0°C to 70°C.

TLC2202C electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AC			TLC2202BC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	500		80	500	µV
			Full range			650			650	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω	Full range		0.5			0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω	25°C		0.001	0.005		0.001	0.005	µV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	25°C		0.5			0.5		pA
			Full range			100			100	
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω	25°C		1			1		pA
			Full range			100			100	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OM-}	Maximum negative peak output voltage swing	R_L = 10 kΩ	25°C	−4.7	−4.9		−4.7	−4.9		V
			Full range	−4.7			−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	300	560		300	560		V/mV
			Full range	200			200			
		V_O = ±4 V, R_L = 10 kΩ	25°C	50	100		50	100		
			Full range	25			25			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	80	115		80	115		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	80	110		80	110		dB
			Full range	80			80			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.8	2.7		1.8	2.7	mA
			Full range			2.7			2.7	

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202C operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AC			TLC2202BC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.8	2.7		1.8	2.7		V/µs
			Full range	1.3			1.3			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		µV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°			48°		

† Full range is 0°C to 70°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2202A and on all devices for the TLC2202B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2202C electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202C			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	1000	μV
			Full range			1150	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω	Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω	25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	Full range			100	pA
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω	25°C		1		pA
		V_{IC} = 0, R_S = 50 Ω	Full range			100	pA
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		V
		R_L = 10 kΩ	Full range	4.7			V
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50	mV
		I_O = 0	Full range			50	mV
A_{VD}	Large-signal differential voltage amplification	V_O =1 V to 4 V, R_L = 500 kΩ	25°C	150	315		V/mV
		V_O =1 V to 4 V, R_L = 500 kΩ	Full range	100			V/mV
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		V/mV
		V_O = 1 V to 4 V, R_L = 10 kΩ	Full range	15			V/mV
CMRR	Common-mode rejection ratio	V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	75	110		dB
		V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	Full range	75			dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD}= 4.6 V to 16 V	25°C	80	110		dB
		V_{DD}= 4.6 V to 16 V	Full range	80			dB
I_{DD}	Supply current	V_O = 0, No load	25°C		1.7	2.6	mA
		V_O = 0, No load	Full range			2.6	mA

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202C operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202C			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.6	2.5		V/μs
		V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	Full range	1.1			V/μs
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		nV/√Hz
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		μV
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		47°		

† Full range is 0°C to 70°C.

TLC2202C electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AC			TLC2202BC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	500		80	500	μV
			Full range			650			650	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005		0.001	0.005	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	25°C		0.5			0.5		pA
			Full range			100			100	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			100			100	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50		0	50	mV
			Full range			50			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		150	315		V/mV
			Full range	100			100			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		25	55		
			Full range	15			15			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	75	110		75	110		dB
			Full range	75			75			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	80	110		80	110		dB
			Full range	80			80			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1.7	2.6		1.7	2.6	mA
			Full range			2.6			2.6	

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202C operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AC			TLC2202BC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.6	2.5		1.6	2.5		V/μs
			Full range	1.1			1.1			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		47°			47°		

† Full range is 0°C to 70°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2202A and on all devices for the TLC2202B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2201I electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201I			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	500	μV
			Full range			650	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5		pA
			Full range			150	
I_{IB}	Input bias current		25°C		1		pA
			Full range			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		V
			Full range	4.7			
V_{OM-}	Maximum negative peak output voltage swing		25°C	−4.7	−4.9		V
			Full range	−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	400	560		V/mV
			Full range	250			
		V_O = ±4 V, R_L = 10 kΩ	25°C	90	100		
			Full range	65			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	115		dB
			Full range	85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	90	110		dB
			Full range	85			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.1	1.5	mA
			Full range			1.5	

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150 °C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201I operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201I			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	2	2.7		V/μs
			Full range	1.4			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°		

† Full range is –40°C to 85°C.

TLC2201I electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AI			TLC2210BI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	200		80	200	μV
			Full range			350			350	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5			0.5		pA
			Full range			150			150	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			150			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OM-}	Maximum negative peak output voltage swing		25°C	−4.7	−4.9		−4.7	−4.9		V
			Full range	−4.7			−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	400	560		400	560		V/mV
			Full range	250			250			
		V_O = ±4 V, R_L = 10 kΩ	25°C	90	100		90	100		
			Full range	65			65			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	115		90	115		dB
			Full range	85			85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	90	110		90	110		dB
			Full range	85			85			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.1	1.5		1.1	1.5	mA
			Full range			1.5			1.5	

† Full range is −40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150 °C extrapolated to T_A = 25°C using the Arrhenius equation assuming an activation energy of 0.96 eV.

TLC2201I operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AI			TLC2210BI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V,	25°C	2	2.7		2	2.7		V/μs
		R_L = 10 kΩ, C_L = 100 pF	Full range	1.4			1.4			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°			48°		

† Full range is –40°C to 85°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2201A and on all devices for the TLC2201B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2201I electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201I			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	500	μV
			Full range			650	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5		pA
			Full range			150	
I_{IB}	Input bias current		25°C		1		pA
			Full range			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		V
			Full range	4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50	mV
			Full range			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		V/mV
			Full range	100			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		
			Full range	15			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	110		dB
			Full range	85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	90	110		dB
			Full range	85			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1	1.5	mA
			Full range			1.5	

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201I operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201I			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ,, C_L = 100 pF	25°C	1.8	2.5		V/μs
			Full range	1.2			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.8		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		45°		

† Full range is –40°C to 85°C.

TLC2201I electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AI			TLC2201BI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	200		80	200	μA
			Full range			350			350	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5			0.5		pA
			Full range			150			150	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			150			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50		0	50	mV
			Full range			50			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		150	315		V/mV
			Full range	100			100			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		25	55		
			Full range	15			15			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	110		90	110		dB
			Full range	85			85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	90	110		90	110		dB
			Full range	85			85			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1	1.5		1	1.5	mA
			Full range			1.5			1.5	

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201I operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AI			TLC2210BI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.8	2.5		1.8	2.5		V/μs
			Full range	1.2			1.2			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.8			1.8		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		45°			45°		

† Full range is –40°C to 85°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2201A and on all devices for the TLC2201B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2202I electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202I			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	1000	μV
			Full range			1200	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω	Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω	25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	Full range			150	pA
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω	25°C		1		pA
		V_{IC} = 0, R_S = 50 Ω	Full range			150	pA
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		V
		R_L = 10 kΩ	Full range	4.7			V
V_{OM-}	Maximum negative peak output voltage swing	R_L = 10 kΩ	25°C	−4.7	−4.9		V
		R_L = 10 kΩ	Full range	−4.7			V
A_{VD}	Large-signal differential voltage amplification	V_O = ± 4 V, R_L = 500 kΩ	25°C	300	560		V/mV
		V_O = ± 4 V, R_L = 500 kΩ	Full range	150			V/mV
		V_O = ± 4 V, R_L = 10 kΩ	25°C	50	100		V/mV
		V_O = ± 4 V, R_L = 10 kΩ	Full range	25			V/mV
CMRR	Common-mode rejection ratio	V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	80	115		dB
		V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	Full range	80			dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = ±2.3 V to ±8 V	25°C	80	110		dB
		V_{DD} = ±2.3 V to ±8 V	Full range	80			dB
I_{DD}	Supply current	V_O = 0, No load	25°C		1.8	2.7	mA
		V_O = 0, No load	Full range			2.7	mA

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202I operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202I			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, C_L = 100 pF, R_L = 10 kΩ	25°C	1.8	2.7		V/μs
		V_O = ±2.3 V, C_L = 100 pF, R_L = 10 kΩ	Full range	1.2			V/μs
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		nV/√Hz
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		μV
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, C_L = 100 pF, R_L = 10 kΩ,	25°C		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°		

† Full range is –40°C to 85°C.

TLC2202I electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AI			TLC2202BI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	500		80	500	μV
			Full range			700			700	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω	Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω	25°C		0.001	0.005		0.001	0.005	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	25°C		0.5			0.5		pA
			Full range			150			150	
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω	25°C		1			1		pA
			Full range			150			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OM-}	Maximum negative peak output voltage swing	R_L = 10 kΩ	25°C	−4.7	−4.9		−4.7	−4.9		V
			Full range	−4.7			−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	300	560		300	560		V/mV
			Full range	150			150			
		V_O = ±4 V, R_L = 10 kΩ	25°C	50	100		50	100		
			Full range	25			25			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	80	115		80	115		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ ±2.3 V to ±8 V	25°C	80	110		80	110		dB
			Full range	80			80			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.8	2.7		1.8	2.7	mA
			Full range			2.7			2.7	

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202I operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AI			TLC2202BI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.8	2.7		1.8	2.7		V/μs
			Full range	1.2			1.2			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°			48°		

† Full range is –40°C to 85°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2202A and on all devices for the TLC2202B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2202I electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202I			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	1000	μV
			Full range			1200	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω	Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω	25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	Full range			150	pA
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω	25°C		1		pA
		V_{IC} = 0, R_S = 50 Ω	Full range			150	pA
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		V
		R_L = 10 kΩ	Full range	4.7			V
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50	mV
		I_O = 0	Full range			50	mV
A_{VD}	Large-signal differential voltage amplification	V_O =1 V to 4 V, R_L = 500 kΩ	25°C	150	315		V/mV
		V_O =1 V to 4 V, R_L = 500 kΩ	Full range	100			V/mV
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		V/mV
		V_O = 1 V to 4 V, R_L = 10 kΩ	Full range	15			V/mV
CMRR	Common-mode rejection ratio	V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	75	110		dB
		V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	Full range	75			dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD}= 4.6 V to 16 V	25°C	80	110		dB
		V_{DD}= 4.6 V to 16 V	Full range	80			dB
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1.7	2.6	mA
		V_O = 2.5 V, No load	Full range			2.6	mA

† Full range is –40°C to 85°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202I operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202I			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.6	2.5		V/μs
		V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	Full range	1			V/μs
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		nV/√Hz
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		μV
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		47°		

† Full range is –40°C to 85°C.

TLC2202I electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AI			TLC2202BI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	500		80	500	μV
			Full range			700			700	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005		0.001	0.005	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	25°C		0.5			0.5		pA
			Full range			150			150	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			150			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50		0	50	mV
			Full range			50			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		150	315		V/mV
			Full range	100			100			
		V_O =1 V to 4 V, R_L = 10 kΩ	25°C	25	55		25	55		
			Full range	15			15			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	75	110		75	110		dB
			Full range	75			75			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	80	110		80	110		dB
			Full range	80			80			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1.7	2.6		1.7	2.6	mA
			Full range			2.6			2.6	

† Full range is –40°C to 85°C

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202I operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AI			TLC2202BI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.6	2.5		1.6	2.5		V/μs
			Full range	1			1			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		47°			47°		

† Full range is –40°C to 85°C

NOTE 5: This parameter is tested on a sample basis for the TLC2202A and on all devices for the TLC2202B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2201M electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201M			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	500	μV
			Full range			700	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5		pA
			Full range			500	
I_{IB}	Input bias current		25°C		1		pA
			Full range			500	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		V
			Full range	4.7			
V_{OM-}	Maximum negative peak output voltage swing		25°C	−4.7	−4.9		V
			Full range	−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	400	560		V/mV
			Full range	200			
		V_O = ±4 V, R_L = 10 kΩ	25°C	90	100		
			Full range	45			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	115		dB
			Full range	85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	90	110		dB
			Full range	85			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.1	1.5	mA
			Full range			1.5	

† Full range is –55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201M operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201M			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	2	2.7		V/μs
			Full range	1.3			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9		MHz
ϕ_m	Phase margin	R_L = 10 kΩ, C_L = 100 pF	25°C		48°		

† Full range is –55°C to 125°C.

TLC2201M electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AM			TLC2210BM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	200		80	200	μV
			Full range			400			400	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5			0.5		pA
			Full range			500			500	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			500			500	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OM-}	Maximum negative peak output voltage swing		25°C	−4.7	−4.9		−4.7	−4.9		V
			Full range	−4.7			−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ±4 V, R_L = 500 kΩ	25°C	400	560		400	560		V/mV
			Full range	200			200			
		V_O = ±4 V, R_L = 10 kΩ	25°C	90	100		90	100		
			Full range	45			45			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	115		90	115		dB
			Full range	85			85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	90	110		90	110		dB
			Full range	85			85			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.1	1.5		1.1	1.5	mA
			Full range			1.5			1.5	

† Full range is −55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observable through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201M operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AM			TLC2201BM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	2	2.7		2	2.7		V/μs
			Full range	1.3			1.3			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°			48°		

† Full range is –55°C to 125°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2201A and on all devices for the TLC2201B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2201M electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201M			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	500	μV
			Full range			700	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005*	μV/mo
I_{IO}	Input offset current		25°C		0.5		pA
			Full range			500	
I_{IB}	Input bias current		25°C		1		pA
			Full range			500	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		V
			Full range	4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50	mV
			Full range			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		V/mV
			Full range	75			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		
			Full range	10			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	110		dB
			Full range	85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	90	110		dB
			Full range	85			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1	1.5	mA
			Full range			1.5	

*On products compliant to MIL-PRF-38535, Class B, this parameter is not production tested.
† Full range is –55°C to 125°C.
NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201M operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201M			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.8	2.5		V/μs
			Full range	1.1			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.8		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		45°		

† Full range is –55°C to 125°C.

TLC2201M electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AM			TLC2210BM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	200		80	200	μV
			Full range			400			400	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005		0.001	0.005	μV/mo
I_{IO}	Input offset current		25°C		0.5			0.5		pA
			Full range			500			500	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			500			500	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50		0	50	V
			Full range			50			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		150	315		V/mV
			Full range	75			75			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		25	55		
			Full range	10			10			
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω	25°C	90	110		90	110		dB
			Full range	85			85			
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	90	110		90	110		dB
			Full range	85			85			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1.1	1.5		1.1	1.5	mA
			Full range			1.5			1.5	

† Full range is –55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observable through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201M operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2201AM			TLC2201BM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.8	2.5		1.8	2.5		V/μs
			Full range	1.1			1.1			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35		18	30	nV/√Hz
		f = 1 kHz	25°C		8	15		8	12	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.8			1.8		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		45°			45°		

† Full range is –55°C to 125°C.

NOTE 5: This parameter is tested on a sample basis for the TLC2201A and on all devices for the TLC2201B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2202M electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202M			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	1000	µV
			Full range			1250	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω	Full range		0.5		µV/°C
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω	25°C		0.001	0.005*	µV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	Full range			500	pA
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω	25°C		1		
		V_{IC} = 0, R_S = 50 Ω	Full range			500	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	–5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		V
		R_L = 10 kΩ	Full range	4.7			
V_{OM-}	Maximum negative peak output voltage swing	R_L = 10 kΩ	25°C	–4.7	–4.9		
		R_L = 10 kΩ	Full range	–4.7			V
A_{VD}	Large-signal differential voltage amplification	V_O =1 V to 4 V, R_L = 500 kΩ	25°C	300	560		V/mV
		V_O =1 V to 4 V, R_L = 500 kΩ	Full range	100			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	50	100		
		V_O = 1 V to 4 V, R_L = 10 kΩ	Full range	25			
CMRR	Common-mode rejection ratio	V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	80	115		dB
		V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	Full range	80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD}= ±2.3 V to ±8 V	25°C	80	110		dB
		V_{DD}= ±2.3 V to ±8 V	Full range	80			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.8	2.7	mA
		V_O = 0, No load	Full range			2.7	

*On products compliant to MIL-PRF-38535, Class B, this parameter is not production tested.
† Full range is –55°C to 125°C.
NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202M operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202M			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, C_L = 100 pF, R_L = 10 kΩ	25°C	1.8	2.7		V/µs
		V_O = ±2.3 V, C_L = 100 pF, R_L = 10 kΩ	Full range	1.1			
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		µV
		f = 0.1 to 10 Hz	25°C		0.7		
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, C_L = 100 pF, R_L = 10 kΩ,	25°C		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°		

† Full range is –55°C to 125°C.

TLC2202M electrical characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AM			TLC2202BM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	500		80	500	μV
			Full range			750			750	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005*		0.001	0.005*	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	25°C		0.5			0.5		pA
			Full range			500			500	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			500			500	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	−5 to 2.7			−5 to 2.7			V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OM-}	Maximum negative peak output voltage swing		25°C	−4.7	−4.9		−4.7	−4.9		V
			Full range	−4.7			−4.7			
A_{VD}	Large-signal differential voltage amplification	V_O = ± 4 V, R_L = 500 kΩ	25°C	300	560		300	560		V/mV
			Full range	100			100			
		V_O = ± 4 V, R_L = 10 kΩ	25°C	50	100		50	100		
			Full range	25			25			
CMRR	Common-mode rejection ratio	V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	80	115		80	115		dB
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	$V_{DD\pm}$ = ±2.3 V to ±8 V	25°C	80	110		80	110		dB
			Full range	80			80			
I_{DD}	Supply current	V_O = 0, No load	25°C		1.8	2.7		1.8	2.7	mA
			Full range			2.7			2.7	

*On products compliant to MIL-PRF-38535, Class B, this parameter is not production tested.
† Full range is −55°C to 125°C.
NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202M operating characteristics at specified free-air temperature, $V_{DD\pm}$ = ±5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AM			TLC2202BM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = ±2.3 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.8	2.7		1.8	2.7		V/μs
			Full range	1.1			1.1			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35*		18	30*	nV/√Hz
		f = 1 kHz	25°C		8	15*		8	12*	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		48°			48°		

*On products compliant to MIL-PRF-38535, Class B, this parameter is not production tested.
† Full range is –55°C to 125°C.
NOTE 5: This parameter is tested on a sample basis for the TLC2202A and on all devices for the TLC2202B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2202M electrical characteristics at specified free-air temperatures, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202M			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		100	1000	μV
			Full range			1250	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω	Full range		0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω	25°C		0.001	0.005*	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	Full range			500	pA
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω	25°C		1		pA
		V_{IC} = 0, R_S = 50 Ω	Full range			500	pA
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		V
		R_L = 10 kΩ	Full range	4.7			V
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50	mV
		I_O = 0	Full range			50	mV
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		V/mV
		V_O = 1 V to 4 V, R_L = 500 kΩ	Full range	75			V/mV
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		V/mV
		V_O = 1 V to 4 V, R_L = 10 kΩ	Full range	10			V/mV
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	75	110		dB
		V_{IC} = V_{ICR}min, R_S = 50 Ω	Full range	75			dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	80	110		dB
		V_{DD} = 4.6 V to 16 V	Full range	80			dB
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1.7	2.6	mA
		V_O = 2.5 V, No load	Full range			2.6	mA

*On products compliant to MIL-PRF-38535, Class B, this parameter is not production tested.
† Full range is –55°C to 125°C.
NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202M operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202M			UNIT
				MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.6	2.5		V/μs
		V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	Full range	0.9			V/μs
V_n	Equivalent input noise voltage	f = 10 Hz	25°C		18		nV/√Hz
		f = 1 kHz	25°C		8		nV/√Hz
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7		μV
I_n	Equivalent input noise current		25°C		0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		47°		

† Full range is –55°C to 125°C.

TLC2202M electrical characteristics at specified free-air temperature, V_{DD} = 5 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AM			TLC2202BM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		80	500		80	500	μV
			Full range			750			750	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.5			0.5		μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.001	0.005*		0.001	0.005*	μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω	25°C		0.5			0.5		pA
			Full range			500			500	
I_{IB}	Input bias current		25°C		1			1		pA
			Full range			500			500	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	Full range	0 to 2.7			0 to 2.7			V
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ	25°C	4.7	4.8		4.7	4.8		V
			Full range	4.7			4.7			
V_{OL}	Maximum low-level output voltage	I_O = 0	25°C		0	50		0	50	mV
			Full range			50			50	
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 kΩ	25°C	150	315		150	315		V/mV
			Full range	75			75			
		V_O = 1 V to 4 V, R_L = 10 kΩ	25°C	25	55		25	55		
			Full range	10			10			
CMRR	Common-mode rejection ratio	V_O = 0, V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	75	110		75	110		dB
			Full range	75			75			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 V to 16 V	25°C	80	110		80	110		dB
			Full range	80			80			
I_{DD}	Supply current	V_O = 2.5 V, No load	25°C		1.7	2.6		1.7	2.6	mA
			Full range			2.6			2.6	

*On products compliant to MIL-PRF-38535, Class B, this parameter is not production tested.
† Full range is –55°C to 125°C
NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202M operating characteristics at specified free-air temperature, V_{DD} = 5 V

PARAMETER		TEST CONDITIONS	T_A†	TLC2202AM			TLC2202BM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	V_O = 0.5 V to 2.5 V, R_L = 10 kΩ, C_L = 100 pF	25°C	1.6	2.5		1.6	2.5		V/μs
			Full range	0.9			1.1			
V_n	Equivalent input noise voltage (see Note 5)	f = 10 Hz	25°C		18	35*		18	30*	nV/√Hz
		f = 1 kHz	25°C		8	15*		8	12*	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C		0.5			0.5		μV
		f = 0.1 to 10 Hz	25°C		0.7			0.7		
I_n	Equivalent input noise current		25°C		0.6			0.6		fA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF	25°C		1.9			1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF	25°C		47°			47°		

*On products compliant to MIL-PRF-38535, Class B, this parameter is not production tested.
† Full range is –55°C to 125°C
NOTE 5: This parameter is tested on a sample basis for the TLC2202A and on all devices for the TLC2202B. For other test requirements, please contact the factory. This statement has no bearing on testing or nontesting of other parameters.

TLC2201Y electrical characteristics at $V_{DD\pm}$ = ±5 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS	TLC2201Y			UNIT
			MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω		100		μV
	Input offset voltage long-term drift (see Note 4)			0.001		μV/mo
I_{IO}	Input offset current			0.5		pA
I_{IB}	Input bias current			1		pA
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ		4.8		V
V_{OL}	Maximum low-level output voltage	I_O = 0		0		mV
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V, R_L = 500 Ω		55		V/mV
		V_O = 1 V to 4 V, R_L = 10 Ω		55		
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, V_O = 0, R_S = 50 Ω		110		dB
k_{SVR}	Supply voltage rejection ratio ($\Delta V_{DD\pm}/\Delta V_{IO}$)	V_{DD} = 4.6 to 16 V		110		dB
I_{DD}	Supply current per amplifier	V_O = 2.5 V, No load		1		mA

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2201Y operating characteristics at $V_{DD\pm}$ = ± 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS	TLC2201Y			UNIT
			MIN	TYP	MAX	
SR	Positive slew rate at unity gain	V_O = ±0.5 to 2.5 V, R_L = 10 kΩ, C_L = 100 pF		2.5		V/μs
V_n	Equivalent input noise voltage	f = 10 Hz		18		nV/√Hz
		f = 1 kHz		8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz		0.5		μV
		f = 0.1 to 10 Hz		0.7		
I_n	Equivalent input noise current			0.6		pA/√Hz
	Gain-bandwidth product	f = 10 kHz, R_L = 10 kΩ, C_L = 100 pF		1.8		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ, C_L = 100 pF		48°		

TLC2202Y electrical characteristics, V_{DD} = 5 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLC2202Y			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0,	R_S = 50 Ω		100		μV
	Input offset voltage long-term drift (see Note 4)				0.001		μV/mo
I_{IO}	Input offset current				0.5		pA
I_{IB}	Input bias current				1		pA
V_{OH}	Maximum high-level output voltage	R_L = 10 kΩ			4.8		V
V_{OL}	Maximum low-level output voltage	I_O = 0			0		mV
A_{VD}	Large-signal differential voltage amplification	V_O = 1 V to 4 V,	R_L = 500 Ω		315		V/mV
		V_O = 1 V to 4 V,	R_L = 10 Ω		55		
CMRR	Common-mode rejection ratio	V_O = 0, V_{ICR}min,	R_S = 50 Ω		110		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{DCC}/\Delta V_{IO}$)	V_{DD} = 4.6 to 16 V			110		dB
I_{DD}	Supply current	V_O = 2.5 V,	No load		1.7		mA

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLC2202Y operating characteristics at V_{DD} = 5 V, T_A = 25°C

PARAMETER		TEST CONDITIONS		TLC2202Y			UNIT
				MIN	TYP	MAX	
SR	Positive slew rate at unity gain	V_O = 0.5 V to 2.5 V, C_L = 100 pF	R_L = 10 kΩ,		2.5		V/μs
V_n	Equivalent input noise voltage	f = 10 Hz			18		nV/√Hz
		f = 10 kHz			8		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz			0.5		μV
		f = 0.1 to 10 Hz			0.7		
I_n	Equivalent input noise current				0.6		pA/√Hz
B_1	Gain-bandwidth product	f = 10 kHz, C_L = 100 pF	R_L = 10 kΩ,		1.9		MHz
ϕ_m	Phase margin at unity gain	R_L = 10 kΩ,	C_L = 100 pF		47°		

PARAMETER MEASUREMENT INFORMATION



Figure 1. Noise-Voltage Test Circuit



NOTE A: C_L includes fixture capacitance.

Figure 2. Phase-Margin Test Circuit



NOTE A: C_L includes fixture capacitance.

Figure 3. Slew-Rate Test Circuit



Figure 4. Input-Bias and Offset-Current Test Circuit

typical values

Typical values presented in this data sheet represent the median (50% point) of device parametric performance.

input bias and offset current

At the picoamp bias current level of the TLC220x, TLC220xA, and TLC220xB, accurate measurement of the bias current becomes difficult. Not only does this measurement require a picoammeter, but test socket leakages can easily exceed the actual device bias currents. To measure these small currents, Texas Instruments uses a two-step process. The socket leakage is measured using picoammeters with bias voltages applied but with no device in the socket. The device is then inserted in the socket, and a second test measuring both the socket leakage and the device input bias current is performed. The two measurements are then subtracted algebraically to determine the bias current of the device.

noise

Texas Instruments offers automated production noise testing to meet individual application requirements. Noise voltage at f = 10 Hz and f = 1 kHz is 100% tested on every TLC2201B device, while lot sample testing is performed on the TLC220xA. For other noise requirements, please contact the factory.

TYPICAL CHARACTERISTICS

Table of Graphs

			FIGURE
V_{IO}	Input offset voltage	Distribution	5, 6
I_{IB}	Input bias current	vs Common-mode input voltage vs Free-air temperature	7 8
V_{OM}	Maximum peak output voltage	vs Output current vs Free-air temperature	9 10
$V_{O(PP)}$	Maximum peak-to-peak output voltage	vs Frequency	11
V_{OH}	High-level output voltage	vs Frequency vs High-level output current vs Free-air temperature	12 13 14
V_{OL}	Low-level output voltage	vs Low-level output current vs Free-air temperature	15 16
A_{VD}	Large-signal differential voltage amplification	vs Frequency vs Free-air temperature	17 18
I_{OS}	Short-circuit output current	vs Supply voltage vs Free-air temperature	19 20
CMRR	Common-mode rejection ratio	vs Frequency	21
I_{DD}	Supply current	vs Supply voltage vs Free-air temperature	22 23, 24
	Pulse response	Small signal Large signal	25, 26 27, 28
SR	Slew rate	vs Supply voltage vs Free-air temperature	29 30
	Noise voltage (referred to input)	0.1 to 1 Hz 0.1 to 10 Hz	31 32
	Gain-bandwidth product	vs Supply voltage vs Free-air temperature	33, 34 35
ϕ_m	Phase margin	vs Supply voltage vs Free-air temperature	36, 37 38, 39
	Phase shift	vs Frequency	17

TYPICAL CHARACTERISTICS

DISTRIBUTION OF TLC2201 INPUT OFFSET VOLTAGE



Figure 5

TLC2202 DISTRIBUTION OF INPUT OFFSET VOLTAGE



Figure 6

INPUT BIAS CURRENT vs COMMON-MODE INPUT VOLTAGE



Figure 7

INPUT BIAS CURRENT† vs FREE-AIR TEMPERATURE



Figure 8

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

MAXIMUM PEAK OUTPUT VOLTAGE vs OUTPUT CURRENT



Figure 9

MAXIMUM PEAK OUTPUT VOLTAGE† vs FREE-AIR TEMPERATURE



Figure 10

MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE† vs FREQUENCY



Figure 11

HIGH-LEVEL OUTPUT VOLTAGE† vs FREQUENCY



Figure 12

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

HIGH-LEVEL OUTPUT VOLTAGE vs HIGH-LEVEL OUTPUT CURRENT



Figure 13

HIGH-LEVEL OUTPUT VOLTAGE† vs FREE-AIR TEMPERATURE



Figure 14

LOW-LEVEL OUTPUT VOLTAGE vs LOW-LEVEL OUTPUT CURRENT



Figure 15

LOW-LEVEL OUTPUT VOLTAGE† vs FREE-AIR TEMPERATURE



Figure 16

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION AND PHASE SHIFT vs FREQUENCY



Figure 17

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION† vs FREE-AIR TEMPERATURE



Figure 18

SHORT-CIRCUIT OUTPUT CURRENT vs SUPPLY VOLTAGE



Figure 19

SHORT-CIRCUIT OUTPUT CURRENT† vs FREE-AIR TEMPERATURE



Figure 20

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

COMMON-MODE REJECTION RATIO vs FREQUENCY



Figure 21

SUPPLY CURRENT† vs SUPPLY VOLTAGE



Figure 22

TLC2201 SUPPLY CURRENT† vs FREE-AIR TEMPERATURE



Figure 23

TLC2202 SUPPLY CURRENT† vs FREE-AIR TEMPERATURE



Figure 24

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

VOLTAGE-FOLLOWER
SMALL-SIGNAL
PULSE RESPONSE



Figure 25

VOLTAGE-FOLLOWER
SMALL-SIGNAL
PULSE RESPONSE



Figure 26

VOLTAGE-FOLLOWER
LARGE-SIGNAL
PULSE RESPONSE



Figure 27

VOLTAGE-FOLLOWER
LARGE-SIGNAL
PULSE RESPONSE



Figure 28

TYPICAL CHARACTERISTICS

**SLEW RATE
vs
SUPPLY VOLTAGE**



Figure 29

**SLEW RATE†
vs
FREE-AIR TEMPERATURE**



Figure 30

**NOISE VOLTAGE
(REFERRED TO INPUT)
OVER A 10-SECOND INTERVAL**



Figure 31

**NOISE VOLTAGE
(REFERRED TO INPUT)
OVER A 10-SECOND INTERVAL**



Figure 32

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

TLC2201
GAIN-BANDWIDTH PRODUCT
vs
SUPPLY VOLTAGE



Figure 33

TLC2202
GAIN-BANDWIDTH PRODUCT
vs
SUPPLY VOLTAGE



Figure 34

GAIN-BANDWIDTH PRODUCT†
vs
FREE-AIR TEMPERATURE



Figure 35

TLC2201
PHASE MARGIN
vs
SUPPLY VOLTAGE



Figure 36

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

TLC2202
PHASE MARGIN
vs
SUPPLY VOLTAGE



Figure 37

TLC2201
PHASE MARGIN†
vs
FREE-AIR TEMPERATURE



Figure 38

TLC2202
PHASE MARGIN†
vs
FREE-AIR TEMPERATURE



Figure 39

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

APPLICATION INFORMATION

latch-up avoidance

Because CMOS devices are susceptible to latch-up due to their inherent parasitic thyristors, the TLC220x, TLC220xA, and TLC220xB inputs and outputs are designed to withstand –100-mA surge currents without sustaining latch-up; however, techniques reducing the chance of latch-up should be used whenever possible. Internal protection diodes should not be forward biased in normal operation. Applied input and output voltages should not exceed the supply voltage by more than 300 mV. Care should be exercised when using capacitive coupling on pulse generators. Supply transients should be shunted by the use of decoupling capacitors (0.1 μF typical) located across the supply rails as close to the device as possible.

electrostatic discharge protection

These devices use internal ESD-protection circuits that prevent functional failures at voltages at or below 2000 V. Care should be exercised in handling these devices as exposure to ESD may result in degradation of the device parametric performance.

macromodel information

Macromodel information provided was derived using Microsim *Parts*™, the model generation software used with Microsim *PSpice*™. The Boyle macromodel (see Note 5) and subcircuit in Figure 40 were generated using the TLC220x typical electrical and operating characteristics at 25°C. Using this information, output simulations of the following key parameters can be generated to a tolerance of 20% (in most cases):

- Maximum positive output voltage swing
- Maximum negative output voltage swing
- Slew rate
- Quiescent power dissipation
- Input bias current
- Open-loop voltage amplification
- Unity-gain frequency
- Common-mode rejection ratio
- Phase margin
- DC output resistance
- AC output resistance
- Short-circuit output current limit

NOTE 5: G. R. Boyle, B. M. Cohn, D. O. Pederson, and J. E. Solomon, “Macromodeling of Integrated Circuit Operational Amplifiers”, *IEEE Journal of Solid-State Circuits*, SC-9, 353 (1974).

PSpice and *Parts* are trademarks of MicroSim Corporation.

APPLICATION INFORMATION

macromodel information (continued)




```
.subckt TLC220x  1 2 3 4 5
*
  c1   1   12 8.51E-12
  c2   6   7  50.00E-12
  cpsr 85  86 79.6E-9
  dcm+ 81  82 dx
  dcm- 83  81 dx
  dc   5   53 dx
  de   54  5  dx
  dlp  90  91 dx
  dln  92  90 dx
  dp   4   3  dx
  ecmr 84  99 (2,99) 1
  egnd 99  0  poly(2) (3,0) (4,0) 0 .5 .5
  epsr 85  0  poly(1) (3,4) -200E-6 20E-6
  ense 89  2  poly(1) (88,0) 100E-6 1
  fb   7   99 poly(6) vb vc ve vlp vln
+  vpsr 0 +    895.9E3 -90E3 90E3 90E3 -90E3 895E3
  ga   6   0  11 12 314.2E-6
  gcm  0   6  10 99 1.295E-9
  gpsr 85  86 (85,86) 100E-6
  grd1 60  11 (60,11) 3.141E-4
  grd2 60  12 (60,12) 3.141E-4
  hlim 90  0  vlim 1k
  hcmr 80  1  poly(2) vcm+ vcm- 0 1E2 1E2
  irp  3   4  965E-6
  iss  3   10 dc 135.0E-6
  iio  2   0  .5E-12
  i1   88  0  1E-21
  j1   11  89 10 jx
  j2   12  80 10 jx
  r2   6   9  100.0E3
  rcm  84  81 1k
  rn1  88  0  1500
  ro1  8   5  188
  ro2  7   99 187
  rss  10  99 1.481E6
  vad  60  4  -.3v
  vcm+ 82  99 2.2
  vcm- 83  99 -4.5
  vb   9   0  dc 0
  vc   3   53 dc .9
  ve   54  4  dc .8
  vlim 7   8  dc 0
  vlp  91  0  dc 2.8
  vln  0   92 dc 2.8
  vpsr 0   86 dc 0
.model dx  d(is=800.0E-18)
.model jx pjf(is=500.0E-15 beta=1.462E-3
+ vto=-.155 kf=1E-17)
.endsx
```

Figure 40. Boyle Macromodel and Subcircuit

MECHANICAL INFORMATION

D (R-PDSO-G)** **PLASTIC SMALL-OUTLINE PACKAGE**

14 PIN SHOWN



DIM \ PINS **	8	14	16
A MAX	0.197 (5,00)	0.344 (8,75)	0.394 (10,00)
A MIN	0.189 (4,80)	0.337 (8,55)	0.386 (9,80)

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion, not to exceed 0.006 (0,15).
D. Four center pins are connected to die mount pad.
E. Falls within JEDEC MS-012

MECHANICAL INFORMATION

FK (S-CQCC-N)** **LEADLESS CERAMIC CHIP CARRIER**

28 TERMINAL SHOWN



NO. OF TERMINALS **	A		B	
	MIN	MAX	MIN	MAX
20	0.342 (8,69)	0.358 (9,09)	0.307 (7,80)	0.358 (9,09)
28	0.442 (11,23)	0.458 (11,63)	0.406 (10,31)	0.458 (11,63)
44	0.640 (16,26)	0.660 (16,76)	0.495 (12,58)	0.560 (14,22)
52	0.739 (18,78)	0.761 (19,32)	0.495 (12,58)	0.560 (14,22)
68	0.938 (23,83)	0.962 (24,43)	0.850 (21,6)	0.858 (21,8)
84	1.141 (28,99)	1.165 (29,59)	1.047 (26,6)	1.063 (27,0)



4040140/D 10/96

NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a metal lid.
D. The terminals are gold plated.
E. Falls within JEDEC MS-004

MECHANICAL INFORMATION

JG (R-GDIP-T8) **CERAMIC DUAL-IN-LINE PACKAGE**



NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only
E. Falls within MIL-STD-1835 GDIP1-T8

MECHANICAL INFORMATION

P (R-PDIP-T8) **PLASTIC DUAL-IN-LINE PACKAGE**



NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS-001

MPDI001 – OCTOBER 1994

P (R-PDIP-T8) **PLASTIC DUAL-IN-LINE PACKAGE**



NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS-001