

External API Reference

REST API for property data, search, exports, skip-trace, and comp reports

Base URL: <https://landportal.com/wp-json/lp-rest-api/v1>

Current version: v1

Content-Type: application/json

CONTENTS

1. [Authentication](#)
2. [Usage Limits](#)
3. [Response Format](#)
4. [Error Handling](#)
5. [Versioning Policy](#)
6. [Endpoints](#)
 1. [GET /property-data](#)
 2. [GET /search](#)
 3. [GET /filter-data/filters-list](#)
 4. [GET /filter-data/filter-values](#)
 5. [POST /filter-data/filter](#)
 6. [GET /reports](#)
 7. [POST /reports](#)
 8. [POST /export](#)
 9. [GET /export](#)
 10. [GET /export/tasks](#)
 11. [POST /skip-trace](#)
7. [Technical Recommendations](#)
 1. [Async Polling](#)
 2. [Pagination](#)
 3. [Export Billing & Partial Match](#)
 4. [Rate Limits](#)
 5. [Retries](#)
 6. [Timeout Expectations](#)
8. [Changelog](#)

1. Authentication

Every endpoint requires an authenticated user with an **active subscription**. Authentication is performed via a JWT token included in every request header.

REQUEST HEADER

```
Authorization: Bearer <your_jwt_token>
```

JWT Token

- Available only after registration and activation of a paid subscription.
- Generated in your user profile page on LandPortal.
- Each token is tied to your account and must be kept secret — treat it like a password.
- Can be revoked at any time from your profile. Once revoked, all requests using that token will return **401** .
- The token remains valid only while your subscription has an **active** status. If the subscription expires or is cancelled, the token stops working and all requests return **403** .

EXAMPLE — CURL

```
curl -X GET "https://landportal.com/wp-json/lp-rest-api/v1/property-data?propertyid=123456789&fip  
-H "Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9..."
```

AUTHENTICATION ERRORS

Status	Message	Cause
401	User not authenticated	Token missing, expired, or invalid.
403	No active subscription	Token valid but account has no active subscription.

2. Usage Limits

Each user has a daily quota per endpoint type. Quotas reset at **midnight New York time (ET)**. When a limit is exhausted the API returns **403** with a descriptive message.

Quota counters are returned in `meta` as `requests_left` or `daily_requests_left` depending on endpoint.

Quota field	Applies to	Decrement rule
single_property_limit	GET /property-data	On every successful property fetch.
search_limit	GET /search	Only when the response contains at least one result.
comp_reports_limit	POST /reports (create)	On task creation, before the external service call.

Quota field	Applies to	Decrement rule
subscription export tokens	POST /export	Decrement by propertyid item count on task creation.
single_skip_trace_limit	POST /skip-trace — create_single	After successful lookup.
filter_data_limit	POST /filter-data/filter	Decrement by 1 only for successful responses with non-zero result set. Not decremented for overflow (count > 50000) or error responses.
slope_reports_limit	Reserved	—

Bulk skip-trace uses a separate token balance (not the daily quota system above). Tokens are deducted per record on task creation and partially refunded for any rows that fail processing.

3. Response Format

All endpoints return `application/json` . Successful responses use this envelope:

```
{
  "success": true,
  "data": { ... }
}
```

Error responses:

```
{
  "success": false,
  "message": "Human-readable description of the error"
}
```

Some endpoints return additional top-level fields alongside `success` (e.g. `message` on skip-trace responses). These are noted per-endpoint below.

4. Error Handling

HTTP Status Codes

Code	Meaning	Common causes
200	OK	Request succeeded.
400	Bad Request	Missing or invalid parameters, empty body, validation failure.
401	Unauthorized	JWT token missing, expired, or invalid.
403	Forbidden	No active subscription; daily usage limit reached; attempting to access another user's task.
404	Not Found	Property, report, or task does not exist.
500	Internal Server Error	Database error, external service unavailable.
502	Bad Gateway	Search service unreachable.

Error Response Examples

400 — VALIDATION

```
{
  "success": false,
  "message": "Property id must be a positive bigint"
}
```

400 — INSUFFICIENT TOKENS (BULK SKIP-TRACE)

```
{
  "success": false,
  "message": "Not enough tokens and overdraft is not allowed",
  "data": {
    "current_user_skip_trace_tokens": 10,
    "data_length": 250
  }
}
```

403 — DAILY LIMIT REACHED

```
{
  "success": false,
  "message": "Single property limit reached"
}
```

403 — NO SUBSCRIPTION

```
{
  "success": false,
```

```
"message": "No active subscription"
}
```

404 — NOT FOUND

```
{
  "success": false,
  "message": "Property not found"
}
```

500 — SERVER ERROR

```
{
  "success": false,
  "message": "Database error occurred"
}
```

5. Versioning Policy

The API is versioned via the URL path: `/wp-json/lp-rest-api/v1/...`

- **Non-breaking changes** (new optional fields in responses, new optional parameters) are added within the current version without notice.
- **Breaking changes** (removed fields, changed field types, renamed endpoints, new required parameters) trigger a new version (v2 , etc.).
- The previous version remains active for a **minimum of 90 days** after a new version is released, giving time to migrate.
- Deprecation notices are communicated via email to registered API users and included in the changelog below.
- v1 is currently the only active version.

Do not build integrations that rely on undocumented fields — they may be removed without notice.

6. Endpoints

GET /property-data

Returns a single property record. The set of fields returned depends on what the admin has enabled globally and what additional fields have been enabled for your specific account.

QUERY PARAMETERS

Parameter	Type	Required	Description
propertyid + fips	integer + string	ONE OF TWO	Primary lookup pair (Property ID + 5-digit FIPS).
lat + lng	number + number	ONE OF TWO	Alternative lookup pair by point.

Lookup rules:

- If `propertyid` and `fips` are provided, they take precedence.
- Otherwise, the request uses `lat + lng`.

Quota consumption order: the API consumes `single_property_limit` first; once it reaches 0, it consumes subscription export tokens (if available).

Meta counter: `meta.requests_left` is the combined remaining balance used by this endpoint (daily single-property quota + available export tokens).

SUCCESS RESPONSE — 200

```
{
  "success": true,
  "data": {
    "property": {
      "propertyid": 40444727,
      "apn": "2011-B-0002",
      "situsfullstreetaddress": "204 TOM WATSON AVE",
      "situscity": "IDEAL",
      "situszip5": "31041",
      "situsstate": "GA",
      "legaldescription": "LOT 3 AND NORTH HALF OF LOT 4 105 X 175",
      "situscounty": "Macon",
      "ownername1full": "NELSON BRYANT",
      "owner1firstname": "BRYANT",
      "owner1lastname": "NELSON",
      "mailingfullstreetaddress": "PO BOX 112"
    }
  },
  "meta": {
    "requests_left": 49
  }
}
```

The `property` object contains only the fields enabled for your account. Unused fields are omitted entirely (not returned as `null`).

The field set shown in the example above is the **standard set**. It can be extended on request — contact customer support to discuss the full list of available fields.

CURL EXAMPLE

```
curl -X GET \
  "https://landportal.com/wp-json/lp-rest-api/v1/property-data?propertyid=987654321&fips=06037" \
  -H "Authorization: Bearer <token>"
```

CURL EXAMPLE (BY POINT)

```
curl -X GET \
  "https://landportal.com/wp-json/lp-rest-api/v1/property-data?lat=30.2672&lng=-97.7431" \
  -H "Authorization: Bearer <token>"
```

ERROR RESPONSES

Status	Message	Cause
400	Property id must be a positive bigint	Invalid <code>propertyid</code> format.
400	Fips must be a 5-digit string	Invalid <code>fips</code> format.
400	Point lat/lng must be numeric	Invalid <code>lat</code> or <code>lng</code> format.
400	Either <code>propertyid+fips</code> or <code>lat+lng</code> is required	Missing required query parameters.
400	County not found for the given FIPS	FIPS code not in the database.
403	Single property limit reached	Both daily single-property quota and export tokens are exhausted (or export tokens are unavailable).
404	Property not found	No record for this <code>propertyid</code> + <code>fips</code> combination.

GET **/search**

Property search by parcel number or owner name. Returns a GeoJSON FeatureCollection. Designed for autocomplete — returns the top matches, not a paginated list.

QUERY PARAMETERS

Parameter	Type		Description
type	string	REQUIRED	Search mode: <code>parcelnumb</code> — match against the parcel/APN number. <code>owner</code> — match against owner name (full-text, case-insensitive).
query	string	REQUIRED	Search text. Minimum 2 characters. Supports both exact and partial match. Case-insensitive.
fips	string	OPTIONAL	5-digit FIPS code. Narrows results to a single county. Takes precedence over <code>state</code> when both are provided.
state	string	OPTIONAL	2-letter state abbreviation (e.g. <code>CA</code>). Narrows results to one state. Ignored when <code>fips</code> is present.

No pagination. The endpoint returns up to **10 best matching results**. To get more relevant results, narrow the search using `fips` or `state` .

RESPONSE SCHEMA — FEATURE PROPERTIES

Field	Type	Description
<code>propertyid</code>	integer null	Internal property identifier.
<code>apn</code>	string null	Assessor's Parcel Number.
<code>fips</code>	string null	5-digit FIPS county code.
<code>owner</code>	string null	Full owner name.
<code>address</code>	string null	Street address.
<code>city</code>	string null	City name.
<code>state</code>	string null	2-letter state abbreviation.
<code>zip</code>	string null	5-digit ZIP code.
<code>county</code>	string null	County name.

SUCCESS RESPONSE — 200

```
{
  "success": true,
  "data": {
    "type": "FeatureCollection",
```



```

"features": [
  {
    "type": "Feature",
    "geometry": {
      "type": "Point",
      "coordinates": [-118.2437, 34.0522]
    },
    "properties": {
      "propertyid": 987654321,
      "apn": "5149-021-013",
      "fips": "06037",
      "owner": "John Doe",
      "address": "123 Main St",
      "city": "Los Angeles",
      "state": "CA",
      "zip": "90012",
      "county": "Los Angeles"
    }
  }
],
"meta": {
  "requests_left": 24
}
}

```

The search quota is decremented **only when features is non-empty**. Searches that return zero results do not consume your daily limit.

About GeoJSON. The response follows the [GeoJSON](#) standard (RFC 7946) — a regular JSON format optimised for geographic data. Each feature includes a `geometry` object with coordinates that can be passed directly to any mapping library (Mapbox, Google Maps, Leaflet, etc.) to place a marker on the map without any additional transformation.

CURL EXAMPLES

```

# Search by parcel number, narrowed to a county
curl -X GET \
  "https://landportal.com/wp-json/lp-rest-api/v1/search?type=parcelnumb&query=5149-021&fips=06037" \
  -H "Authorization: Bearer <token>"

# Search by owner name, narrowed to a state
curl -X GET \
  "https://landportal.com/wp-json/lp-rest-api/v1/search?type=owner&query=John+Doe&state=CA" \
  -H "Authorization: Bearer <token>"

```

ERROR RESPONSES

Status	Message	Cause
400	Invalid search type. Allowed: parcelnumb, owner	Unknown type value.
400	Query must be at least 2 characters	query too short.
403	Search limit reached	Daily quota exhausted.
502	Search service error	Search service unreachable.

GET /filter-data/filters-list

Returns the list of supported filtering keys and their API examples.

Source of truth: use GET /filter-data/filters-list to retrieve the latest supported filters, operators, and dynamic request examples.

SUCCESS RESPONSE — 200 (SHORT EXAMPLE)

```
{
  "success": true,
  "data": {
    "filters": [
      {
        "key": "vacant",
        "label": "Vacant",
        "type": "boolean",
        "example": {
          "operator": "boolean",
          "value": true
        }
      },
      {
        "key": "currentsalerecordingdate",
        "label": "Last Sale Date",
        "type": "date",
        "example": {
          "operator": "date",
          "comparison": "is_between",
          "value": {
            "min": "2025-12-01",
            "max": "2026-05-18"
          },
          "nulls": false
        }
      }
    ]
  }
}
```

GET **/filter-data/filter-values**

Returns dictionary values for dictionary-based filters.

QUERY PARAMETERS

Parameter	Type	Required	Description
filter	string	REQUIRED	Filter key, for example: fips , landusecode , wf_near_water_types , taxdeliquent .

SUCCESS RESPONSE — 200 (FIPS)

```
{
  "success": true,
  "data": {
    "fips": {
      "TX": {
        "48113": "Dallas County",
        "48439": "Tarrant County"
      }
    }
  }
}
```

POST /filter-data/filter

Applies filters and returns matching properties. Supports county-scoped filtering by `fips` .

Scope rule: `filters.fips` is required only when neither `filters.polygon` nor `filters.bbox` is provided.

FIPS condition: for `filters.fips` , `comparison` is optional and defaults to `is` .

FIPS value format: `value` can be either a single 5-digit FIPS string or an array of 5-digit FIPS strings.

REQUEST BODY — APPLICATION/JSON

```
{
  "filters": {
    "fips": {
      "operator": "condition",
      "comparison": "is",
      "value": "39001"
    },
    "vacant": {
      "operator": "boolean",
      "value": true
    },
    "lotsizeacres": {
      "operator": "range",
      "value": {
        "min": 5,
        "max": 10
      },
      "nulls": false
    },
    "currentsalerecordingdate": {
      "operator": "date",
      "comparison": "is_between",
      "value": {
        "min": "2025-12-01",
        "max": "2026-05-18"
      },
      "nulls": true
    },
    "sum_up_to_5": {
      "operator": "range",
      "value": {
        "min": 50
      },
      "nulls": false
    }
  }
}
```

REQUEST BODY EXAMPLE — MULTIPLE FIPS IN FILTERS

```
{
  "filters": {
    "fips": {
      "operator": "condition",
      "comparison": "is",
      "value": ["39001", "39049", "39113"]
    },
    "vacant": {
      "operator": "boolean",
      "value": true
    }
  }
}
```

Date format: API accepts both YYYY-MM-DD and legacy YYYYMMDD .

nulls parameter: accepts true/false , "true"/"false" , and 1/0 .

Slope filters: min-only. If both min and max are sent, max is ignored. If only max is sent, request fails with 400 .

Operators: boolean , condition , range , date , equals , polygon , bbox .

GEOMETRY FILTERS — FILTERS.POLYGON AND FILTERS.BBOX

Key	Value format	Description
filters.polygon	string or string[]	One or more polygons. Each ring is a comma-separated list of "lon lat" pairs (min 4 pairs). Single string or array of strings; semicolon-separated string also accepted.
filters.bbox	string	Bounding box as exactly 2 "lon lat" pairs separated by a comma: top-left and bottom-right.

Scope: filters.fips is required only when neither filters.polygon nor filters.bbox is provided.

Multipolygon — semicolon-separated string: "ring1_coords;ring2_coords"

Multipolygon — array of strings: ["ring1_coords", "ring2_coords"]

Both formats produce the same Elasticsearch geo_shape multipolygon query. A single ring produces a polygon query.

EXAMPLE — SINGLE POLYGON

```
{
  "filters": {
    "polygon": {
      "value": "-83.9135 33.6435,-83.9169 33.6256,-83.9057 33.6193,-83.8946 33.6164,-83.8865 33.6
```

```

    },
    "vacant": { "operator": "boolean", "value": true }
  }
}

```

EXAMPLE — MULTIPOLYGON AS ARRAY OF STRINGS

```

{
  "filters": {
    "polygon": {
      "value": [
        "-83.9135 33.6435,-83.9169 33.6256,-83.9057 33.6193,-83.8946 33.6164,-83.9135 33.6435",
        "-84.1020 33.7510,-84.1150 33.7310,-84.0940 33.7200,-84.0800 33.7350,-84.1020 33.7510"
      ]
    }
  }
}

```

EXAMPLE — MULTIPOLYGON AS SEMICOLON-SEPARATED STRING

```

{
  "filters": {
    "polygon": {
      "value": "-83.9135 33.6435,-83.9169 33.6256,-83.9057 33.6193,-83.8946 33.6164,-83.9135 33.6
    }
  }
}

```

DEDUPLICATION PARAMETERS — TOP-LEVEL (NOT INSIDE FILTERS)

Parameter	Type	Default	Description
duplicates	boolean	true	When <code>false</code> , deduplicates results by <code>mailingfullstreetaddress</code> , keeping the record with the largest <code>lotsizeacres</code> per unique address.
empty_mailing_addresses	boolean	true	When <code>false</code> , excludes properties where <code>mailingfullstreetaddress</code> is empty or missing.

Accepted input forms: native boolean (`true` / `false`), string (`"true"` / `"false"`), or numeric (`1` / `0`).

Empty addresses with `duplicates: false` : when `empty_mailing_addresses` is `true` (default), properties with an empty or missing mailing address are not collapsed — each is returned as a unique entry.

count field: when `duplicates: false` , `count` reflects the actual post-deduplication number of returned properties, not the raw index total.

duplicates	empty_mailing_addresses	Behaviour
true (default)	true (default)	All matching results, no changes.
true	false	Empty/missing mailing address excluded; no deduplication.
false	true (default)	Deduplicated by mailing address (largest lotsizeacres kept); empty-mailing properties each returned as a unique entry.
false	false	Deduplicated by mailing address; empty/missing mailing address excluded entirely.

EXAMPLE — DEDUPLICATE, KEEP EMPTY-MAILING AS UNIQUE ENTRIES

```
{
  "duplicates": false,
  "filters": {
    "fips": {
      "operator": "condition",
      "value": "39001"
    },
    "lotsizeacres": {
      "operator": "range",
      "value": { "min": 5, "max": 50 }
    }
  }
}
```

EXAMPLE — DEDUPLICATE AND EXCLUDE EMPTY MAILING ADDRESSES

```
{
  "duplicates": false,
  "empty_mailing_addresses": false,
  "filters": {
    "fips": {
      "operator": "condition",
      "value": "39001"
    },
    "vacant": {
      "operator": "boolean",
      "value": true
    }
  }
}
```

SUCCESS RESPONSE — 200 (SHORT EXAMPLE)

```
{
  "success": true,
  "meta": {
    "requests_left": 145
  }
}
```

```
{,
  "data": {
    "count": 451,
    "properties": [
      {
        "fips": "39001",
        "apn": "048-13-03-018.000",
        "situsfullstreetaddress": "19257 STATE ROUTE 136"
      }
    ]
  }
}
```

SUCCESS RESPONSE WITH REJECTED FILTERS (EXAMPLE)

```
{
  "success": true,
  "meta": {
    "requests_left": 49,
    "rejected_filters": [
      {
        "key": "unknown_filter",
        "value": {
          "operator": "range",
          "value": {
            "min": 5,
            "max": 10
          }
        },
        "reason": "This filter is invalid. Use GET /filter-data/filters-list to retrieve the late
      ]
    ],
  },
  "data": {
    "count": 451,
    "properties": [
      {
        "fips": "39001",
        "apn": "048-13-03-018.000",
        "situsfullstreetaddress": "19257 STATE ROUTE 136"
      }
    ]
  }
}
```

LIMIT OVERFLOW RESPONSE

```
{
  "success": true,
  "meta": {
    "requests_left": 145,
    "message": "Result set is limited to 50000 records. Please narrow your filters."
  }
}
```



```
{,
  "data": {
    "count": 73412,
    "properties": []
  }
}
```

When result set exceeds 50000 , API returns empty `properties` and recommends narrowing filters. In this case, `filter_data_limit` is not decremented.

GET /reports

Fetch a previously generated comp report for a property.

QUERY PARAMETERS

Parameter	Type		Description
propertyid	integer	REQUIRED	Internal property identifier (positive bigint).
fips	string	REQUIRED	5-digit FIPS county code.

SUCCESS RESPONSE — 200

```
{
  "success": true,
  "data": {
    "property_id": 987654321,
    "fips": "06037",
    "report_url": "https://...",
    ...
  }
}
```

CURL EXAMPLE

```
curl -X GET \
  "https://landportal.com/wp-json/lp-rest-api/v1/reports?propertyid=987654321&fips=06037" \
  -H "Authorization: Bearer <token>"
```

ERROR RESPONSES

Status	Message	Cause
400	Property id must be a positive bigint	Invalid <code>propertyid</code> .
400	Wrong fips	FIPS code not in the database.
400	Report not found	No report exists for this property.

POST /reports

Queue a comp report generation task. Returns immediately with a `task_id` ; the report is generated asynchronously.
Decrements `comp_reports_limit` on success.

REQUEST BODY — APPLICATION/JSON

Field	Type		Description
propertyid	integer	REQUIRED	Internal property identifier (positive bigint).
fips	string	REQUIRED	5-digit FIPS county code.

SUCCESS RESPONSE — 200

```
{
  "success": true,
  "data": {
    "task_id": 4821,
    "property_id": 987654321,
    "fips": "06037",
    "timestamp": "2026-04-06 12:00:00"
  },
  "meta": {
    "daily_requests_left": 4
  }
}
```

CURL EXAMPLE

```
curl -X POST \
  "https://landportal.com/wp-json/lp-rest-api/v1/reports" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{"propertyid": 987654321, "fips": "06037"}'
```

ERROR RESPONSES

Status	Message	Cause
400	Empty request data	Request body is empty or not valid JSON.
400	Property id must be a positive bigint	Invalid <code>propertyid</code> .
400	Fips must be a 5-digit string	Invalid <code>fips</code> .
403	Comp report limit exhausted	Daily quota exhausted.
500	Database error occurred	Task could not be persisted.
500	Error creating comp report	Report generation service unavailable.

POST /export

Queue an asynchronous CSV export task for selected properties. The request is validated, charged against subscription export tokens, persisted as a task, and scheduled for background processing.

- Required conditions:** active API access and sufficient export tokens balance.
- Billing rule:** 1 propertyid = 1 export token . Tokens are debited immediately on task creation.
- Typing rule:** fips and propertyid items may be sent as strings or numbers. The API normalizes them to 5-digit FIPS strings and positive integers.

REQUEST BODY — APPLICATION/JSON

Field	Type		Description
fips	array<string number>	REQUIRED	County FIPS list used to resolve source tables. Each value must normalize to a 5-digit code.
propertyid	array<string number>	REQUIRED	Property IDs to export. Each value must normalize to a positive bigint.

REQUEST EXAMPLE

```
{
  "fips": ["12103", "06037"],
  "propertyid": [123456789, "987654321"]
}
```

SUCCESS RESPONSE — 200

```
{
  "success": true,
  "data": {
    "task_id": 65432,
    "export_tokens_left": 998,
    "message": "Export task queued"
  }
}
```

Personal cabinet behavior: in task lists and payload previews, the UI is focused on task metadata (status, counters, timestamps). Full input arrays are stored in the payload file; the cabinet provides a link/path to that payload file which contains complete fips / propertyid data.

CURL EXAMPLE

```
curl -X POST \
  "https://landportal.com/wp-json/lp-rest-api/v1/export" \
  -H "Authorization: Bearer <token>" \
```

```
-H "Content-Type: application/json" \  
-d '{  
  "fips": ["12103", "06037"],  
  "propertyid": [123456789, "987654321"]  
}'
```

ERROR RESPONSES

Status	Message	Cause
400	Invalid request body	Request body is not valid JSON object.
400	fips must be an array	Missing/invalid fips list.
400	propertyid must be an array	Missing/invalid propertyid list.
400	fips[i] invalid / propertyid[i] invalid	One or more items fail format validation.
400	fips and propertyid arrays are required	Both arrays are present but empty after validation.
403	Insufficient export tokens limit	Not enough subscription export tokens for requested propertyid count. Error payload includes required_export_tokens and available_export_tokens .
500	Failed to queue export task	Task persistence/scheduling failure.

GET /export

Get export task status by `task_id` . If task is completed, response includes a downloadable CSV URL.

QUERY PARAMETERS

Parameter	Type		Description
task_id	integer	REQUIRED	Task identifier returned by <code>POST /export</code> .

TASK STATUS VALUES

Status	Description
queued	Task accepted and waiting for background worker.
processing	Worker is building the CSV file.
completed	CSV uploaded to storage and ready for download.
failed	Task failed. See <code>error_message</code> .

SUCCESS RESPONSE — 200 (PROCESSING)

```
{
  "success": true,
  "data": {
    "task_id": 65432,
    "status": "processing"
  }
}
```

SUCCESS RESPONSE — 200 (COMPLETED)

```
{
  "success": true,
  "data": {
    "task_id": 65432,
    "status": "completed",
    "file_url": "https://landportal-exports.s3.us-east-2.amazonaws.com/exports/api_export_65432.csv",
    "rows": 2
  }
}
```

SUCCESS RESPONSE — 200 (FAILED)

```
{
  "success": true,
  "data": {
    "task_id": 65432,
    "status": "failed",
    "error_message": "The query returned no results"
  }
}
```

```
}  
}
```

CURL EXAMPLE

```
curl -X GET \  
  "https://landportal.com/wp-json/lp-rest-api/v1/export?task_id=65432" \  
  -H "Authorization: Bearer <token>"
```

ERROR RESPONSES

Status	Message	Cause
400	task_id is required	Missing or invalid task_id .
403	You are not authorized to access this task	Task belongs to another user.
404	Task not found	Unknown task_id .

GET **/export/tasks**

List your export tasks with statuses, timestamps, and result links (for completed tasks).

QUERY PARAMETERS

Parameter	Type		Description
page	integer	OPTIONAL	Page number. Default: 1 .
per_page	integer	OPTIONAL	Page size. Default: 50 , max: 200 .

SUCCESS RESPONSE — 200

```
{
  "success": true,
  "data": {
    "tasks": [
      {
        "task_id": 65433,
        "status": "completed",
        "created_at": "2026-05-23 13:58:01",
        "updated_at": "2026-05-23 13:58:45",
        "rows": 2,
        "file_url": "https://landportal-exports.s3.us-east-2.amazonaws.com/exports/api_export_654",
        "error_message": false
      },
      {
        "task_id": 65432,
        "status": "processing",
        "created_at": "2026-05-23 13:57:10",
        "updated_at": "2026-05-23 13:57:15",
        "rows": 0,
        "file_url": "",
        "error_message": false
      }
    ],
    "pagination": {
      "page": 1,
      "per_page": 50,
      "total": 17
    }
  }
}
```

`pagination.total` — total number of tasks for your account. See [Pagination](#) for details.

CURL EXAMPLE

```
curl -X GET \
  "https://landportal.com/wp-json/lp-rest-api/v1/export/tasks?page=1&per_page=50" \
```

```
-H "Authorization: Bearer <token>"
```


POST /skip-trace

All skip-trace operations share a single endpoint. The action is selected via the `method` field in the request body.

COMMON REQUIRED FIELD


Field	Type	Description
method	string	Action to perform. See sections below.

Two separate modes:

Single lookup (`create_single`) — synchronous, returns phone numbers with DNC status immediately. Uses the `single_skip_trace_limit` daily quota.

Bulk processing (`create`) — asynchronous task, deducts skip-trace tokens per record. Use `get` to poll for status, `finish` for completion.

Bulk Skip-Trace Lifecycle



Poll task status via `get` . The `finish` event is sent by the processing service when the task completes; you do not need to call it manually.

method: create

Start a new bulk skip-trace task. Provide either a URL to a CSV file (`input_file`) or an array of records (`json_data`). The number of records must not exceed your available token balance.

FIELDS

Field	Type		Description
input_file	string (URL)	OPTIONAL*	Publicly accessible URL to a CSV file. Supports Google Drive sharing links. Required when <code>json_data</code> is absent.
json_data	array	OPTIONAL*	Array of record objects. Required when <code>input_file</code> is absent.
has_header	boolean	OPTIONAL	Whether the CSV has a header row. Default: <code>false</code> . Automatically set to <code>true</code> when using <code>json_data</code> .
fields	object	REQUIRED	Column mapping. See table below.
emails_trace	boolean	OPTIONAL	Include email lookup in addition to phone. Default: <code>false</code> .

FIELDS — COLUMN MAPPING KEYS

Key	Description
last_name	Owner last name
first_name	Owner first name
mailing_address	Mailing street address
mailing_city	Mailing city
mailing_state	Mailing state (2-letter)
mailing_zip	Mailing ZIP code
property_address	Property street address
property_city	Property city
property_state	Property state
property_zip	Property ZIP code

SUCCESS RESPONSE — 200

```
{
  "success": true,
  "message": "Skip trace created successfully",
  "data": {
    "task_id": 12345,
    "data_length": 150,
    "input_file": "https://s3.amazonaws.com/...",
    "tokens_left": 850,
    "test_mode": false
  }
}
```

CURL EXAMPLE — JSON DATA

```
curl -X POST \
  "https://landportal.com/wp-json/lp-rest-api/v1/skip-trace" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "method": "create",
    "json_data": [
      {
        "first_name": "John", "last_name": "Doe",
        "mailing_address": "123 Main St", "mailing_city": "Austin",
        "mailing_state": "TX", "mailing_zip": "78701",
        "property_address": "123 Main St", "property_city": "Austin",
        "property_state": "TX", "property_zip": "78701"
      }
    ],
    "fields": {
```

```
    "first_name": "first_name", "last_name": "last_name",
    "mailing_address": "mailing_address", "mailing_city": "mailing_city",
    "mailing_state": "mailing_state", "mailing_zip": "mailing_zip",
    "property_address": "property_address", "property_city": "property_city",
    "property_state": "property_state", "property_zip": "property_zip"
  }
}'
```

method: get

Poll the status and result of a task. When `task_status` is `completed`, the response includes a URL to download the output CSV file.

FIELDS

Field	Type		Description
<code>task_id</code>	integer	REQUIRED	Task identifier returned by <code>create</code> .

TASK STATUS VALUES

Status	Description
<code>processing</code>	Task is actively being processed.
<code>paused</code>	Task has been paused.
<code>stopped</code>	Task was stopped before completion.
<code>completed</code>	Task finished successfully. Output file available.
<code>failed</code>	Task encountered a fatal error.

SUCCESS RESPONSE — 200

```
// While processing:
{
  "success": true,
  "message": "Skip trace data",
  "data": {
    "task_id": 12345,
    "task_status": "processing",
    "total_rows": 150,
    "success_rows": 62
  }
}

// When completed:
{
  "success": true,
  "message": "Skip trace data",
  "data": {
    "task_id": 12345,
```

```
{
  "task_status": "completed",
  "total_rows": 150,
  "success_rows": 143,
  "output_file_csv": "https://skip-trace.landportal.com/output/a1b2c3d4.csv"
}
```

CURL EXAMPLE

```
curl -X POST \
  "https://landportal.com/wp-json/lp-rest-api/v1/skip-trace" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{"method": "get", "task_id": 12345}'
```

method: pause / continue / stop

All three require only `task_id` . You can only operate on tasks you own.

Method	New status	Description
pause	paused	Temporarily suspends processing. Resume with <code>continue</code> .
continue	processing	Resumes a paused task.
stop	stopped	Permanently stops the task. Unused tokens are refunded. Cannot be resumed.

```
curl -X POST \
  "https://landportal.com/wp-json/lp-rest-api/v1/skip-trace" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{"method": "pause", "task_id": 12345}'
```

method: delete

Permanently deletes a task record. Requires `task_id` . You can only delete tasks you own.

method: finish

This method is called automatically by the processing service when a task completes. **You do not need to call it manually.**

Marks a task as completed or stopped, refunds tokens for failed rows, and sends a webhook notification to the URL configured in your profile (if set).

WEBHOOK PAYLOAD (SENT TO YOUR CALLBACK URL)

```
{
  "task_id": 12345,
  "task_status": "completed",
  "started_at": "2026-04-06T10:00:00+00:00",
  "completed_at": "2026-04-06T10:12:34+00:00",
  "total_rows": 150,
  "success_rows": 143,
  "credit_consumed": 143,
  "failed_rows": 7,
  "processing_time": 754,
  "average_hit_rate": 0.9533,
  "output_file_csv": "https://skip-trace.landportal.com/output/a1b2c3d4.csv"
}
```

The webhook includes an `X-Webhook-Signature` header with the signature you configured in your profile for request verification.

method: create_single

Synchronous single-person lookup. Returns phone numbers with DNC (Do Not Call) status immediately. Uses the `single_skip_trace_limit` daily quota.

This API service accepts a consumer first and last name, and any other known consumer contact information. The more fields provided, the more accurate the match.

FIELDS

Field	Type		Description
first	string	OPTIONAL	Owner first name.
last	string	OPTIONAL	Owner last name.
address	string	OPTIONAL	A house/building number and street.
city	string	OPTIONAL	City.
state	string	OPTIONAL	2-letter state abbreviation.
zip	string	OPTIONAL	ZIP code.

SUCCESS RESPONSE — 200

```
{
  "success": true,
  "meta": { "daily_requests_left": 9 },
  "data": {
    "task_id": 12345,
    "timestamp": "2026-04-06 12:00:00",
    "first": "John",
    "last": "Doe",
    "address": "123 Main St",
    "city": "Austin",
  }
}
```

```

    "state": "TX",
    "zip": "78701",
    "phones": [
      { "phone": "5125550100", "line_type": "Mobile", "dnc": false, "dnc_types": [] },
      { "phone": "5125550101", "line_type": "Landline", "dnc": true, "dnc_types": ["tcpa", "fede
    ]
  }
}

```

CURL EXAMPLE

```

curl -X POST \
  "https://landportal.com/wp-json/lp-rest-api/v1/skip-trace" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "method": "create_single",
    "first": "John",
    "last": "Doe",
    "address": "123 Main St",
    "city": "Austin",
    "state": "TX",
    "zip": "78701"
  }'

```

`dnc: true` means the phone number appears on the TCPA Litigator List and should not be contacted.

`dnc_types` lists the specific list types (e.g. `tcpa` , `federal_dnc`). Phones not found in the list are returned with `dnc: false` and an empty `dnc_types` array.

`line_type` is sourced from Versium and indicates the phone line type (e.g. `Mobile` , `Landline`). May be empty if not available.

COMMON ERROR RESPONSES — ALL SKIP-TRACE METHODS

Status	Message	Cause
400	Method is required	Missing <code>method</code> field.
400	Invalid method specified	Unknown <code>method</code> value.
400	Task ID is required	Missing <code>task_id</code> for task-based operations.
400	Input file or JSON data is required	<code>create</code> : neither <code>input_file</code> nor <code>json_data</code> provided.
400	Fields mapping is required and must be an array	<code>create</code> : missing <code>fields</code> .
400	Not enough tokens and overdraft is not allowed	Token balance insufficient for the requested record count.

Status	Message	Cause
403	User does not have an active subscription	Subscription inactive.
403	Single skip trace limit exhausted	Daily quota for <code>create_single</code> exhausted.
403	You are not authorized to ... this skip trace task	Attempting to operate on another user's task.
404	Task not found	Invalid <code>task_id</code> .
500	Database error occurred	DB write or read failure.
500	Internal server error occurred	Unexpected server-side error.

7. Technical Recommendations

Async Polling

Applies to: `POST /reports` , `POST /export` , bulk `POST /skip-trace (create)` .

Recommended interval: 3–5 seconds. Stop as soon as `status` is `completed` or `failed` . Polling more frequently does not speed up processing.

Terminal statuses: `completed` , `failed` , `stopped` — no further polling needed once reached.

Pagination

Endpoints that return lists include a `pagination` object:

```
{
  "pagination": {
    "page": 1,
    "per_page": 50,
    "total": 17
  }
}
```

`total` — total number of **items** (not pages). Calculate total pages as `ceil(total / per_page)` .

Requesting a page beyond the last page returns an empty result array (not an error).

Export Billing & Partial Match

Tokens are charged on task creation, before background processing starts. The charge equals the number of unique `propertyid` values after de-duplication.

Duplicate inputs: duplicate values in `fips` and `propertyid` are silently de-duplicated before billing and query execution.

Partial match: if some `propertyid` values do not exist in the county tables resolved from the given `fips`, only matching rows appear in the CSV. The task completes successfully (`status: completed`) with fewer rows than requested. Tokens are **not** refunded for unmatched IDs.

No match at all: if no `propertyid` values are found, the task transitions to `failed` with `error_message: "The query returned no results"`. Tokens are **not** refunded.

Rate Limits

Dedicated HTTP rate-limit headers (e.g. `X-RateLimit-*`) are not returned. Monitor remaining quota via response fields:

- `meta.requests_left` — filter data, property data, search
- `meta.daily_requests_left` — comp reports, skip-trace `create_single`
- `data.export_tokens_left` — export token balance after task creation

Retries

Retry: transient failures only — network errors, timeouts, `5xx` responses.

Do not retry: `4xx` errors (validation failures, quota exhausted, auth errors) — they will not resolve on retry.

Strategy: exponential backoff with jitter — e.g. `1s → 2s → 4s`, capped at 30s.

Timeout Expectations

Most filter, search, and property-data requests complete quickly. Exceptions:

- Large-area or complex polygon filter queries can take several seconds.
- Export and comp report tasks are asynchronous — use polling rather than waiting on the initial response.

8. Changelog

v1.3.5

May 2026

- `filters.polygon.value` now accepts an array of ring strings (`["ring1", "ring2"]`) in addition to the existing single-string and semicolon-separated formats.
- All three polygon input formats (single string, `;`-separated string, array) produce the same Elasticsearch `geo_shape` query — single ring becomes `polygon`, multiple rings become `multipolygon`.
- Input normalisation and per-ring validation moved to `FilterGeometryValidator`: new `parse_rings()` method handles format detection; `validate_polygon()` validates each ring individually.

v1.3.4

May 2026

- Added top-level `duplicates` parameter to `POST /filter-data/filter`. When `false`, results are deduplicated by `mailingfullstreetaddress`, keeping the record with the largest `lotsizeacres` per unique address.
- Added top-level `empty_mailing_addresses` parameter. When `false`, properties with an empty or missing `mailingfullstreetaddress` are excluded from results.
- When `duplicates: false` and `empty_mailing_addresses: true` (default), properties without a mailing address are each returned as a unique entry rather than collapsed.
- When `duplicates: false`, `count` in the response reflects the post-deduplication result count.
- Both parameters accept boolean, string (`"true"` / `"false"`), and numeric (`1` / `0`) forms.

v1.3.3

May 2026

- Added asynchronous export API endpoints: `POST /export`, `GET /export`, and `GET /export/tasks`.
- `POST /export` validates and normalizes mixed numeric/string payload inputs for `fips` and `propertyid`.
- Export tokens are pre-validated and charged on task creation; successful responses return remaining balance in `export_tokens_left`.
- `GET /export/tasks` always returns `error_message` for each task: string when failed, otherwise `false`.
- Export task lifecycle now exposes explicit statuses (`queued`, `processing`, `completed`, `failed`) and downloadable CSV URL on completion.

v1.3.2

May 2026

- Filtered API date filters now accept ISO 8601 format `YYYY-MM-DD` (legacy `YYYYMMDD` remains supported).
- Updated date examples returned by `GET /filter-data/filters-list` to use `YYYY-MM-DD`.
- Date filters support `nulls` in multiple input forms: boolean (`true` / `false`), string (`"true"` / `"false"` , `"yes"` / `"no"`), and numeric (`1` / `0` , or strings `"1"` / `"0"`).
- `nulls: true` includes records where date field is missing/null; `nulls: false` returns only records matching the date condition.
- Slope keys aligned with web filters: `percentage_of_land_with_flat_slope_0_05` , `sum_up_to_5` , `sum_up_to_10` , `sum_up_to_15` .
- Slope filter examples now include min-only usage (`value.min` without `value.max`) for all slope variants.
- Owner name filters now use owner-search-like matching (partial, case-insensitive) for `currentsaleseller1fullname` , `ownername1full` , and `ownername2full` .

v1.3.1

April 2026

- `GET /property-data` now supports lookup by `lat` + `lng` when `propertyid` + `fips` are not provided.
- `GET /property-data` returns combined remaining quota in `meta.requests_left` (daily single-property limit + export tokens, when available).
- `GET /property-data` now uses export tokens after daily quota is exhausted (when available) and reports remaining quota via combined `meta.requests_left` .
- `create_single` : all fields are now optional. The `address` field accepts any address associated with the consumer (not necessarily the mailing address).
- `create_single` : response now includes `line_type` (e.g. `Mobile` , `Landline`) and `dnc_types` array per phone number.

v1.3.0

April 2026

- Added `GET /reports` endpoint for fetching existing comp reports.
- Added `search_limit` daily quota for `GET /search` .
- Added `single_property_limit` enforcement in `GET /property-data` .
- Successful responses include remaining quota metadata where applicable (`requests_left` or `daily_requests_left` , depending on endpoint).
- Service URLs (Comp Report, Versium, TCPA) moved to admin settings — no longer hardcoded.
- Global daily limits moved from ACF to dedicated Usage Limits tab in API Settings.

v1.2.0

March 2026

- Introduced `create_single` skip-trace method with Versium + TCPA Litigator scrub.
- Skip-trace `finish` now sends a webhook callback to the URL set in the user profile.
- Webhook payload includes `processing_time` , `average_hit_rate` , `credit_consumed` , `failed_rows` .
- Added Elasticsearch index settings to admin panel (`Main Search Index` field).

v1.1.0

February 2026

- Added `GET /search` endpoint.
- Added per-user field selection for `GET /property-data`.
- Introduced daily usage limits with midnight ET reset.
- Added `pause / continue` skip-trace methods.

v1.0.0

January 2026

- Initial release.
- `GET /property-data`, `POST /reports`, `POST /skip-trace` (create, get, stop, update, delete, finish).
- JWT authentication.