

Cheat Sheet

Venice V 1.12.31



Overview

Primitives	Literals	Number	String	Char	Boolean	Keyword	Symbol	Nil	Just		
Collections	List	Vector	Set	Map	LazySeq	Stack	Queue	DelayQueue	DAG	Array	ByteBuf
Custom Types	Types	Protocols									
Concepts	Recursion	Destructuring									
Core Functions	Functions	Macros	Special Forms		Transducers	Namespaces		Exceptions			
Concurrency	Atoms	Locks	Locking	Futures	Promises	Delay	Agents	Scheduler	Volatiles	Parallel	
Threads	ThreadLocal		Threads								
System	System	System Vars		REPL	Sandbox	Load Paths					
Java	Java Interop		Java								
Util	Math	Time	Regex	INET	CIDR						
I/O	I/O	File	Zip/GZip								
Documents	JSON	JSON Lines		PDF	PDF Tools	CSV	XML	Excel	Images		
Modules	Kira Templates	Parsifal		Grep	Configuration	Component		ZipVault	Fonts	Cryptography	
	AsciiTable	Matrix	Shell	Geo IP	Mimetypes	Ansi	App	QR Ref	Semver		
Build Tools	Gradle Wrapper		Gradle	Maven	Installer						
Test & Debug	Test	Tracing	Tap	Hexdump	Timing	Benchmark					
Database	JDBC Core		JDBC PostgreSQL		Chinook Dataset						
Web	Http Client J8		Tomcat WebApp Server			Ring	Multipart	SSE			
LLM	OpenAI		JTokkit								
Docker	Docker	Cargo	Cargo/ArangoDB		Cargo/Qdrant		Cargo/PostgreSQL				
License	License										
Others	Embedding in Java		Venice Doc		Markdown						

Primitives

Literals

Nil	nil
Boolean	true, false
Integer	150I, 1_000_000I, 0x1FFI

Collections

Collections

Generic	count	compare	empty-to-nil	empty
	into	into!	cons	conj
	remove	repeat	repeatedly	cycle
	replace	range	group-by	sort

Long	1500, 1_000_000, 0x00A055FF
Float	3.569F, 2.0E+5F
Double	3.569, 2.0E+10
BigDecimal	6.897M, 2.345E+10M
BigInteger	1000N, 1_000_000N
Char	#\A, #\π, #\u03C0
	#\space, #\newline, #\return, #\tab, #\formfeed, #\backspace, #\lparen, #\rparen, #\quote
String	"abcd", "ab\"cd", "PI: \u03C0"
	""{ "age": 42 }""
String interpolation	"~{x}", ""~{x}""
	"~(inc x)", ""~(inc x)""

Numbers

Arithmetic	+	-	*	/
Convert	int decimal	long bigint	float	double
Compare	==	=	not=	< > <= >=
	compare			
Test	zero?	pos?	neg?	even? odd?
	number?	int?	long?	float?
	double?	decimal?		
NaN/Infinite	nan?	infinite?		
BigDecimal	dec/add dec/div	dec/sub dec/scale	dec/mul	

Strings

Create	str
Use	count first nlast reverse str/nfirst str/nrest str/butnlast str/pos str/reverse compare last nth seq shuffle str/nlast str/rest str/butlast str/chars str/repeat str/lorem-ipsum empty-to-nil nfirst butlast str/subs
Index	str/index-of str/index-of-not-char str/last-index-of
Split/Join	str/split str/split-at str/split-lines str/split-columns str/join
Replace	str/replace-first str/replace-last str/replace-all
Strip	

	sort-by reverse	frequencies shuffle	get-in	seq
Tests	empty? sequential? sorted-set? sequential? sorted-map?	not-empty? list? mutable-set? hash-map? mutable-map?	distinct? vector? map? ordered-map? bytebuf?	coll? set?
Process	map group-by flatten	map-indexed sort docoll	filter sort-by mapv	reduce keep run!

Lists

Create	()	list	list*	mutable-list
Access	first last nlast	second peek sublist	third rest some	fourth nth butlast nfirst
Modify	cons into dedupe partition-by cartesian-product mapcat take drop drop-while split-with	conj into! partition interpose combinations flatten take-while drop-last split-with	conj! concat distinct partition-all interleave sort take-last split-at	rest pop distinct partition-by combinations sort-by drop split-at
Test	list? sequential? any?	mutable-list? every? not-any?	coll? not-every?	

Vectors

Create	[]	vector	vector*	mutable-vector
	mapv			
Access	first peek subvec	second butlast some	third rest	nth nfirst nlast
Modify	cons into dedupe interpose cartesian-product mapcat take drop drop-while update!	conj into! partition interleave combinations flatten take-while drop-last update!	conj! concatv distinct partition-by interleave sort take-last update assoc assoc!	rest pop distinct partition-by combinations sort-by drop update split-with
Nested	get-in dissoc-in	assoc-in	update-in	
Test	vector? sequential? every?	mutable-vector? contains? not-every?	coll? not-contains? any?	

Sets

Create	#{} set	sorted-set	mutable-set
Modify			

	<code>str/strip-start</code> <code>str/strip-end</code> <code>str/strip-indent</code> <code>str/strip-margin</code>
Conversion	<code>str/lower-case</code> <code>str/upper-case</code> <code>str/cr-lf</code>
Regex	<code>match?</code> <code>not-match?</code>
Trim	<code>str/trim</code> <code>str/trim-to-empty</code> <code>str/trim-to-nil</code> <code>str/trim-left</code> <code>str/trim-right</code>
Format	<code>str/format</code> <code>str/quote</code> <code>str/double-quote</code> <code>str/double-unquote</code> <code>str/align</code> <code>str/wrap</code> <code>str/expand</code> <code>str/truncate</code>
Hex	<code>str/hex-to-bytebuf</code> <code>str/bytebuf-to-hex</code> <code>str/format-bytebuf</code>
Bytebuf	<code>bytebuf-from-string</code> <code>bytebuf-to-string</code>
Encode/Decode	<code>str/encode-base64</code> <code>str/decode-base64</code> <code>str/encode-url</code> <code>str/decode-url</code> <code>str/escape-html</code> <code>str/escape-xml</code>
Test	<code>string?</code> <code>empty?</code> <code>not-empty?</code> <code>str/blank?</code> <code>str/not-blank?</code> <code>str/starts-with?</code> <code>str/ends-with?</code> <code>str/contains?</code> <code>str/equal-ignore-case?</code> <code>str/quoted?</code> <code>str/double-quoted?</code>
Test char	<code>str/char?</code> <code>str/digit?</code> <code>str/hexdigit?</code> <code>str/letter?</code> <code>str/whitespace?</code> <code>str/linefeed?</code> <code>str/lower-case?</code> <code>str/upper-case?</code>
UTF	<code>str/normalize-utf</code>
Validation	<code>str/valid-email-addr?</code>
Other	<code>str/levenshtein</code>

Chars

Use	<code>char</code> <code>char?</code> <code>char-escaped</code> <code>char-literals</code>
Conversion	<code>str</code> <code>str/lower-case</code> <code>str/upper-case</code>
Test char	<code>str/char?</code> <code>str/digit?</code> <code>str/letter?</code> <code>str/whitespace?</code> <code>str/linefeed?</code> <code>str/lower-case?</code> <code>str/upper-case?</code>

Booleans

Boolean	<code>true</code> <code>false</code> <code>boolean</code> <code>not</code> <code>boolean?</code> <code>true?</code> <code>false?</code>
---------	---

	<code>into</code> <code>into!</code> <code>cons</code> <code>cons!</code> <code>conj</code> <code>conj!</code> <code>disj</code>
Algebra	<code>difference</code> <code>union</code> <code>intersection</code> <code>subset?</code> <code>superset?</code>
Test	<code>set?</code> <code>sorted-set?</code> <code>mutable-set?</code> <code>coll?</code> <code>contains?</code> <code>not-contains?</code> <code>every?</code> <code>not-every?</code> <code>any?</code> <code>not-any?</code>

Maps

Create	<code>{}</code> <code>hash-map</code> <code>ordered-map</code> <code>sorted-map</code> <code>mutable-map</code> <code>zipmap</code>
Access	<code>find</code> <code>get</code> <code>keys</code> <code>vals</code>
Modify	<code>cons</code> <code>conj</code> <code>conj!</code> <code>assoc</code> <code>assoc!</code> <code>update</code> <code>update!</code> <code>dissoc</code> <code>dissoc!</code> <code>into</code> <code>into!</code> <code>concat</code> <code>flatten</code> <code>filter-k</code> <code>filter-kv</code> <code>reduce-kv</code> <code>merge</code> <code>merge-with</code> <code>merge-deep</code> <code>map-invert</code> <code>map-keys</code> <code>map-vals</code> <code>select-keys</code>
Entries	<code>map-entry</code> <code>key</code> <code>val</code> <code>entries</code> <code>map-entry?</code>
Nested	<code>get-in</code> <code>assoc-in</code> <code>update-in</code> <code>dissoc-in</code>
Test	<code>map?</code> <code>hash-map?</code> <code>ordered-map?</code> <code>sorted-map?</code> <code>mutable-map?</code> <code>coll?</code> <code>contains?</code> <code>not-contains?</code>

Stack

Create	<code>stack</code>
Access	<code>peek</code> <code>pop!</code> <code>push!</code> <code>into!</code> <code>conj!</code> <code>count</code>
Test	<code>empty?</code> <code>stack?</code>

Queue

Create	<code>queue</code>
Access	<code>peek</code> <code>into!</code> <code>conj!</code> <code>count</code>
Sync	<code>put!</code> <code>take!</code>
Async	<code>offer!</code> <code>poll!</code>
Process	<code>docoll</code> <code>transduce</code> <code>reduce</code>
Test	<code>empty?</code> <code>queue?</code>

DelayQueue

Create	<code>delay-queue</code>
Access	<code>peek</code> <code>count</code>
Sync	<code>put!</code> <code>take!</code>
Async	<code>poll!</code>
Test	<code>empty?</code> <code>delay-queue?</code>

Keywords

Keyword	<code>:a</code> <code>:blue</code> <code>keyword?</code> <code>keyword</code>
---------	--

Symbols

Symbol	<code>'a</code> <code>'blue</code> <code>symbol?</code> <code>qualified-symbol?</code> <code>symbol</code>
--------	---

Nil

Nil	<code>nil</code> <code>nil?</code> <code>some?</code>
-----	--

Just

Just	<code>just</code> <code>just?</code>
------	--------------------------------------

Byte Buffer

Create	<code>bytebuf</code> <code>bytebuf-allocate</code> <code>bytebuf-allocate-random</code> <code>bytebuf-byte-order!</code> <code>bytebuf-byte-order</code> <code>bytebuf-merge</code>
Capacity	<code>bytebuf-capacity</code> <code>bytebuf-remaining</code> <code>bytebuf-limit</code> <code>bytebuf-ensure-free-capacity!</code> <code>bytebuf-limit!</code> <code>count</code>
Search	<code>bytebuf-index-of</code>
String	<code>bytebuf-from-string</code> <code>bytebuf-to-string</code>
Test	<code>empty?</code> <code>not-empty?</code> <code>bytebuf?</code>
Use	<code>bytebuf-to-list</code> <code>bytebuf-sub</code> <code>bytebuf-pos</code> <code>bytebuf-pos!</code>
Read	<code>bytebuf-get-byte</code> <code>bytebuf-get-int</code> <code>bytebuf-get-long</code> <code>bytebuf-get-float</code> <code>bytebuf-get-double</code>
Write	<code>bytebuf-put-byte!</code> <code>bytebuf-put-int!</code> <code>bytebuf-put-long!</code> <code>bytebuf-put-float!</code> <code>bytebuf-put-double!</code> <code>bytebuf-put-buf!</code>
Base64	<code>str/encode-base64</code> <code>str/decode-base64</code>
Hex	<code>str/hex-to-bytebuf</code> <code>str/bytebuf-to-hex</code> <code>str/format-bytebuf</code>

Regex

General	<code>regex/pattern</code> <code>regex/matcher</code> <code>regex/reset</code> <code>regex/matches?</code> <code>regex/matches-not?</code> <code>regex/matches</code> <code>regex/group</code> <code>regex/groups</code> <code>regex/count</code> <code>regex/find?</code> <code>regex/find</code> <code>regex/find-all</code> <code>regex/find+</code> <code>regex/find-all+</code>
---------	--

DAG (directed acyclic graph)

Create	<code>dag/dag</code> <code>dag/add-edges</code> <code>dag/add-nodes</code>
Access	<code>dag/nodes</code> <code>dag/edges</code> <code>dag/roots</code> <code>count</code>
Children	<code>dag/children</code> <code>dag/direct-children</code>
Parents	<code>dag/parents</code> <code>dag/direct-parents</code>
Sort	<code>dag/topological-sort</code> <code>dag/compare-fn</code>
Test	<code>dag/dag?</code> <code>dag/node?</code> <code>dag/edge?</code> <code>dag/parent-of?</code> <code>dag/child-of?</code> <code>empty?</code>

Lazy Sequences

Create	<code>lazy-seq</code>
Realize	<code>doall</code>
Test	<code>lazy-seq?</code>

Arrays

Create	<code>make-array</code> <code>object-array</code> <code>string-array</code> <code>int-array</code> <code>long-array</code> <code>float-array</code> <code>double-array</code>
Use	<code>aget</code> <code>aset</code> <code>alength</code> <code>asub</code> <code>acopy</code> <code>amap</code>

Concurrency

Atoms	<code>atom</code> <code>atom?</code> <code>deref</code> <code>deref?</code> <code>reset!</code> <code>swap!</code> <code>swap-vals!</code> <code>compare-and-set!</code> <code>add-watch</code> <code>remove-watch</code>
Locks	<code>lock</code> <code>lock?</code> <code>acquire</code> <code>try-acquire</code> <code>release</code> <code>locked?</code>
Locking	<code>locking</code>
Futures	<code>future</code> <code>future-task</code> <code>future?</code> <code>futures-fork</code> <code>futures-wait</code> <code>futures-thread-pool-info</code> <code>done?</code> <code>cancel</code> <code>cancelled?</code> <code>deref</code> <code>deref?</code> <code>realized?</code>
Promises	<code>promise</code> <code>promise?</code> <code>deliver</code> <code>deliver-ex</code> <code>realized?</code> <code>then-accept</code> <code>then-accept-both</code> <code>then-apply</code> <code>then-combine</code> <code>then-compose</code> <code>when-complete</code> <code>accept-either</code> <code>apply-to-either</code>

Math

Arithmetic	inc mod negate square log10	dec mod-floor floor pow	min abs ceil log	max sgn sqrt log2	clamp
Util	digits				
Random	rand-long rand-bigint	rand-double rand-gaussian			
Trigonometry	math/to-radians math/sin math/asin	math/to-degrees math/cos math/acos math/tan math/atan			
Statistics	math/mean math/quartiles math/standard-deviation	math/median math/quantile			
Algorithms	math/softmax				

Constants

E	math/E
PI	math/PI

Transducers

Use	transduce				
Functions	map drop-while take-while remove reverse	map-indexed drop-last take-last dedupe flatten	filter filter distinct halt-when	drop take keep sorted	
Reductions	rf-first rf-any?	rf-last	rf-every?		
Early	reduced	reduced?	deref	deref?	

Functions

Create	fn comp fn! constantly any-pred	defn partial trampoline every-pred	defn- memoize complement	identity juxt coalesce
Call	apply	->	->>	
Test	fn?			
Misc	nil?	some?	name qualified-name fn-name	namespace callstack
Load Source				

	all-of complete-on-timeout done?	any-of cancel	or-timeout timeout-after cancelled?	
Delay	delay force	delay? realized?	deref deref?	
Agents	agent restart-agent agent-error shutdown-agents await-termination-agents await-termination-agents? agent-send-thread-pool-info agent-send-off-thread-pool-info	send set-error-handler! await shutdown-agents?	send-off await-for shutdown-agents?	
Scheduler	schedule-delay schedule-at-fixed-rate			
Volatiles	volatile deref?	volatile? reset!	deref swap!	
ThreadLocal	thread-local thread-local-clear thread-local-map get binding	thread-local? assoc dissoc def-dynamic		
Threads	thread thread-daemon? thread-interrupted?	thread-id thread-interrupted?	thread-name	
Parallel	pcalls	pmap	preduce	

System

Venice	version	logo			
Logo					
System	system-prop	system-env	system-exit-code	shutdown-hook	charset-default-encoding
Java	java-version	java-version-info	java-major-version	java-source-location	
Java VM	pid	gc	total-memory	used-memory	
OS	os-type	os-type?	os-arch	os-name	os-version
Jansi	jansi-version				
Time	current-time-millis	nano-time	format-nano-time	format-micro-time	format-milli-time
Host	host-name	host-address	ip-private?	cpus	byte-order
User	user-name	io/user-home-dir			
Util	uuid	sleep			
Services	service	service?			
Shell					

	load-module load-file load-classpath-file read-string eval
Environment	set! resolve bound? var-get var-sym var-name var-ns var-sym-meta var-val-meta var-thread-local? var-local? var-global? name namespace
Tree Walker	prewalk postwalk prewalk-replace postwalk-replace
Meta	meta with-meta vary-meta
Documentation	doc finder modules
Definiton	fn-name fn-about fn-args fn-body fn-pre-conditions
Syntax	highlight

Macros

Create	def- defn defn- defmacro macroexpand macroexpand-all macro?
Test	macro? macroexpand-on-load?
Quoting	quote quasiquote
Branch	and or when when-not if-not if-let when-let letfn
Conditions	cond condp case
Loop	while dotimes list-comp doseq
Call	doto -> ->> -<> as-> cond-> cond->> some-> some->>
Load Code	load-module load-file load-classpath-file load-string loaded-modules
Assert	assert assert-false assert-eq assert-ne assert-throws assert-does-not-throw assert-throws-with-msg
Util	comment gensym time with-out-str with-err-str
Profiling	time perf

Special Forms

Forms	def defonce def-dynamic if do let binding fn set!
Multi Methods	defmulti defmethod
Protocols	defprotocol extend extends?

	sh with-sh-dir with-sh-env with-sh-throw
Shell Tools	sh/open sh/pwd

System Vars

System Vars	*version* *newline* *loaded-modules* *loaded-files* *ns* *run-mode* *ansi-term* *ARGV* *out* *err* *in*
-------------	--

Tap

Use	tap>
Add	add-tap
Remove	remove-tap clear-taps

Time

Date	time/date time/date?
Local Date	time/local-date time/local-date? time/local-date-parse
Local Date Time	time/local-date-time time/local-date-time? time/local-date-time-parse
Zoned Date Time	time/zoned-date-time time/zoned-date-time? time/zoned-date-time-parse
Unix Timestamp	time/unix-timestamp time/unix-timestamp-to-local-date-time
Fields	time/year time/month time/day-of-week time/day-of-month time/day-of-year time/hour time/minute time/second time/milli
Fields etc	time/length-of-year time/length-of-month time/first-day-of-month time/last-day-of-month
Zone	time/zone time/zone-offset
Format	time/formatter time/format
Test	time/after? time/not-after? time/before? time/not-before? time/within? time/leap-year?
Miscellaneous	

Recursion	loop	recur	tail-pos
Exception	throw	try	try-with
Profiling	dobench	dorun	prof

Exceptions

Throw/Catch	try	try-with	throw
Create	ex		
Test	ex?	ex-venice?	
Util	ex-message	ex-cause	ex-value
Stacktrace	ex-venice-stacktrace	ex-java-stacktrace	

Types

Util	type	supertype	supertypes
Test	instance-of?	deftype?	
Define	deftype	deftype-of	deftype-or
Create	..:		
Describe	deftype-describe		

Protocols

Core	Object
------	--------

Namespace

Open	ns		
Current	*ns*		
Remove	ns-unmap	ns-remove	
Test	ns?		
Util	ns-list	namespace	
Alias	ns-alias	ns-aliases	ns-unalias
Meta	ns-meta	alter-ns-meta!	reset-ns-meta!

Java Interoperability

Java	.	import	java-unwrap-optional	cast	class
Java	java-int-list	java-long-list	java-float-list	java-double-list	java-string-list

	time/with-time	time/plus
	time/minus	time/period
	time/earliest	time/latest
Util	time/zone-ids	time/to-millis

I/O

to	print	println	printf	flush
	newline	pr	prn	
to-str	pr-str	with-out-str		
from	read-line	read-char		
classpath	io/load-classpath-resource	io/classpath-resource?		
slurp	io/slurp	io/slurp-lines	io/slurp-stream	io/slurp-reader
	io/read-line	io/read-char		
spit	io/spit	io/spit-stream	io/spit-writer	io/print
	io/print-line			
stream	io/copy-stream	io/uri-stream	io/file-in-stream	io/file-out-stream
	io/string-in-stream	io/bytebuf-in-stream	io/bytebuf-out-stream	io/capturing-print-stream
	io/flush	io/close		
stream wrap	io/wrap-os-with-buffered-writer	io/wrap-os-with-print-writer	io/wrap-is-with-buffered-reader	io/wrap-is-with-gzip-input-stream
	io/wrap-os-with-gzip-output-stream	io/wrap-is-with-inflater-input-stream	io/wrap-os-with-deflater-output-stream	
reader/writer	io/buffered-reader	io/buffered-writer	io/string-reader	io/string-writer
	io/flush	io/close		
test	io/in-stream?	io/out-stream?	io/reader?	io/writer?
http	io/download	io/internet-avail?		
other	with-out-str	with-err-str	io/mime-type	io/default-charset
vars	*out*	*err*	*in*	

File I/O

file	io/file	io/file-parent
	io/file-name	io/file-basename
	io/file-path	io/file-path-slashify

	java-iterator-to-list java-enumeration-to-list
Proxify	proxify java/as-runnable java/as-callable java/as-predicate java/as-function java/as-consumer java/as-supplier java/as-bipredicate java/as-bifunction java/as-biconsumer java/as-unaryoperator java/as-binaryoperator
Test	java-obj? enum? instance-of? exists-class?
Classes	class class-of class-name class-version
Types	formal-type remove-formal-type class supers bases
Support	imports stacktrace classloader classloader-of
JARs	jar-maven-manifest-version java-package-version
Modules	module-name

REPL

Info	repl? repl/info
Terminal	repl/term-rows repl/term-cols
Dirs	repl/home-dir repl/libs-dir
Config	repl/prompt! repl/handler! repl/color-theme repl/color-theme!
Env Vars	repl/cat-env repl/get-env repl/add-env repl/remove-env

Sandbox

Sandbox	sandboxed? sandbox/type sandbox/functions
---------	--

Loadpaths

Load Paths	loadpath/paths loadpath/unrestricted? loadpath/normalize
------------	--

PDF

PDF	pdf/render pdf/text-to-pdf pdf/available? pdf/check-required-libs
-----	---

	io/file-absolute io/file-canonical io/file-ext io/file-ext? io/file-size io/file-last-modified io/file-normalize-utf
dir	io/mkdir io/mkdirs
slurp/spit	io/slurp io/slurp-lines io/spit
list	io/list-files io/list-files-glob io/list-file-tree io/list-file-tree-lazy
delete	io/delete-file io/delete-files-glob io/delete-file-tree io/delete-file-on-exit
copy	io/copy-file io/copy-files-glob io/copy-file-tree
move	io/move-file io/move-files-glob
touch	io/touch-file
permissions	io/file-can-read? io/file-can-write? io/file-can-execute? io/file-set-readable io/file-set-writable io/file-set-executable io/file-can-read? io/file-can-write? io/file-can-execute?
links	io/symbolic-link? io/create-symbolic-link io/create-hard-link
test	io/file? io/file-absolute? io/exists-file? io/exists-dir? io/file-hidden? io/symbolic-link? io/file-within-dir?
glob	io/glob-path-matcher io/file-matches-glob? io/list-files-glob io/copy-files-glob io/move-files-glob io/delete-files-glob
disk space	io/filesystem-total-space io/filesystem-usable-space
URL/URI	io/->url io/->uri
file watch	io/await-for io/watch-dir io/close-watcher
temporary	io/temp-file io/temp-dir io/tmp-dir
user dir	io/user-dir io/user-home-dir

JSON

read	json/read-str json/slurp
------	----------------------------

PDF Tools

`pdf/merge` `pdf/copy` `pdf/pages`
`pdf/watermark` `pdf/to-text`
`pdf/page-to-image` `pdf/page-count`

Install the required PDF libraries:

```
(do
  (load-module :pdf-install)
  (pdf-install/install :dir (repl/libs-dir)
    :silent false))
```

Zip/GZip

zip	<code>io/zip</code> <code>io/zip-file</code> <code>io/zip-list</code> <code>io/zip-list-entry-names</code> <code>io/zip-append</code> <code>io/zip-remove</code> <code>io/zip?</code> <code>io/unzip</code> <code>io/unzip-first</code> <code>io/unzip-nth</code> <code>io/unzip-all</code> <code>io/unzip-to-dir</code>
gzip	<code>io/gzip</code> <code>io/gzip-to-stream</code> <code>io/gzip?</code> <code>io/ungzip</code> <code>io/ungzip-to-stream</code>
zlib	<code>io/deflate</code> <code>io/inflate</code>

License

License	<code>license</code> <code>license-all</code>
---------	---

write

`json/write-str` `json/spit`

prettify

`json/pretty-print`

INET

Create	<code>inet/inet-addr</code>
--------	-----------------------------

Util	<code>inet/inet-addr-to-bytes</code> <code>inet/inet-addr-from-bytes</code>
------	--

Test	<code>inet/ip4?</code> <code>inet/ip6?</code> <code>inet/linklocal-addr?</code> <code>inet/sitelocal-addr?</code> <code>inet/multicast-addr?</code> <code>inet/reachable?</code>
------	---

CIDR (classless inter-domain routing)

CIDR	<code>cidr/parse</code> <code>cidr/in-range?</code> <code>cidr/start-inet-addr</code> <code>cidr/end-inet-addr</code>
------	---

CIDR Trie	<code>cidr/trie</code> <code>cidr/size</code> <code>cidr/insert</code> <code>cidr/lookup</code> <code>cidr/lookup-reverse</code>
-----------	---

CSV

read	<code>csv/read</code>
------	-----------------------

write	<code>csv/write</code> <code>csv/write-str</code>
-------	---

Modules

Kira

Templating system

```
(load-module :kira)
```

Kira	kira/eval	kira/fn
Escape	kira/escape-xml	kira/escape-html

Cryptography

```
(load-module :crypt)
```

Ciphers	crypt/ciphers	crypt/max-key-size crypt/provider? crypt/add-bouncy-castle-provider
Hashes	crypt/md5-hash	crypt/sha1-hash crypt/sha512-hash crypt/pbkdf2-hash
Encrypt	crypt/encrypt	crypt/decrypt
File encrypt	crypt/encrypt-file	crypt/decrypt-file
File hash	crypt/hash-file	crypt/verify-file-hash

JSON Lines

```
(load-module :jsonl)
```

read	jsonl/read-str	jsonl/slurp jsonl/lazy-seq-slurper
write	jsonl/write-str	jsonl/spit jsonl/spitln

Zip Vault

AES 256 encrypted and password protected zip file

```
(load-module :zipvault)
```

Create	zipvault/zip	zipvault/zip-folder
Add	zipvault/add-files zipvault/add-folder zipvault/add-stream	
Remove	zipvault/remove-files	
Extract	zipvault/extract-file zipvault/extract-all zipvault/extract-file-data	
Util		

Hexdump

```
(load-module :hexdump)
```

Hexdump	hexdump/dump
---------	------------------------------

Semver

Semantic versioning

```
(load-module :semver)
```

Semver	semver/parse	semver/version
Validation	semver/valid?	semver/valid-format?
Test	semver/newer? semver/equal?	semver/older? semver/cmp

Geo IP

Geolocation mapping for IP addresses

```
(load-module :geoip)
```

Lookup	geoip/ip-to-country-resolver geoip/ip-to-country-loc-resolver geoip/ip-to-city-loc-resolver geoip/ip-to-city-loc-resolver-mem-optimized
Databases	geoip/download-google-country-db-to-csvfile geoip/download-maxmind-db-to-zipfile geoip/download-maxmind-db
DB Parser	geoip/parse-maxmind-country-ip-db geoip/parse-maxmind-city-ip-db geoip/parse-maxmind-country-db geoip/parse-maxmind-city-db
Util	geoip/build-maxmind-country-db-url geoip/build-maxmind-city-db-url geoip/map-location-to-numeric geoip/country-to-location-resolver geoip/addr-ranges->trie

Excel

Read/Write Excel files

```
(load-module :excel)
```

Writer	excel/writer	excel/add-sheet excel/add-column excel/add-merge-region excel/freeze-pane	excel/sheet
--------	------------------------------	--	-----------------------------

```
zipvault/encrypted?
zipvault/valid-zip-file?
zipvault/entropy
```

XML

```
(load-module :xml)
```

XML	xml/parse-str	xml/parse	xml/path->
	xml/children	xml/text	

Java

```
(load-module :java)
```

Java	java/javadoc
------	--------------

Parsifal

A parser combinator

Parsifal is a port of Nate Young's Parsatron Clojure [parser combinators](#) project.

```
(load-module :parsifal)
```

Run	parsifal/run
Define	parsifal/defparser
Parsers	parsifal/any parsifal/many parsifal/many1 parsifal/times parsifal/either parsifal/choice parsifal/between parsifal/>>
Special Parsers	parsifal/eof parsifal/never parsifal/always parsifal/lookahead parsifal/attempt
Binding	parsifal/let->>
Char Parsers	parsifal/char parsifal/not-char parsifal/any-char parsifal/digit parsifal/hexdigit parsifal/letter parsifal/letter-or-digit parsifal/any-char-of parsifal/none-char-of parsifal/string
Token Parsers	parsifal/token
Protocols	parsifal/SourcePosition
Line Info	parsifal/lineno parsifal/pos

Gradle Wrapper

Uses the 'gradlew.sh' or 'gradlew.bat' shell scripts from a Gradle project to run Gradle commands on the project. For projects not based on the Gradle Wrapper use the :gradle module instead.

```
(load-module :gradlew)
```

Writer I/O

```
excel/write->file
  
excel/write->stream
  
excel/write->bytebuf
```

Writer Data

```
excel/write-data
excel/write-items
excel/write-item
excel/write-value
excel/write-values
excel/clear-row
excel/delete-row
excel/copy-row
excel/copy-row-to-end
excel/insert-empty-row
```

Writer Util

```
excel/sheet-count
excel/sheet-name
excel/sheet-index
excel/sheet-row-range
excel/sheet-col-range
excel/convert->reader
excel/col->string
excel/addr->string
```

Writer Formulas

```
excel/cell-formula
excel/sum-formula
excel/evaluate-formulas
```

Writer Styling

```
excel/add-font    excel/add-style
excel/add-merge-region
excel/row-height
excel/col-width
excel/cell-style
excel/bg-color
excel/auto-size-columns
excel/auto-size-column
excel/hide-columns
excel/freeze-pane
```

Writer Images

```
excel/add-image
```

Writer Charts

```
excel/add-line-chart
excel/add-bar-chart
excel/add-area-chart
excel/add-pie-chart
```

Writer Charts Util

```
excel/line-data-series
excel/bar-data-series
excel/area-data-series
excel/pie-data-series
excel/cell-address-range
```

Reader

```
excel/open    excel/sheet
excel/read-val
excel/read-string-val
excel/read-boolean-val
excel/read-long-val
excel/read-double-val
excel/read-date-val
excel/read-datetime-val
excel/read-error-code
```

Reader Util

```
excel/sheet-count
excel/sheet-name
excel/sheet-index
```

Gradle	<code>gradlew/version</code>	<code>gradlew/run</code>
	<code>gradlew/run*</code>	

Gradle

Uses the 'gradle.sh' or 'gradle.bat' shell scripts from a locally installed Gradle version to run Gradle commands on a project. For projects based on the Gradle Wrapper use the :gradlew module instead.

```
(load-module :gradle)
```

Gradle	<code>gradle/with-home</code>	<code>gradle/version</code>
	<code>gradle/task</code>	

```
excel/sheet-row-range
excel/sheet-col-range
excel/evaluate-formulas
excel/cell-empty?
excel/cell-type
excel/cell-formula-result-type
excel/convert->writer
```

Install the required Apache POI 5.x libraries:

```
(do
  (load-module :excel-install)
  (excel-install/install :dir (repl/libs-dir)
    :silent false))
```

Maven

```
(load-module :maven)
```

Artifact	<code>maven/parse-artifact</code>	
	<code>maven/artifact-filename</code>	
	<code>maven/artifact-uri</code>	
Download	<code>maven/download</code>	<code>maven/get</code>
Commands	<code>maven/home-dir</code>	<code>maven/mvn</code>
	<code>maven/version</code>	<code>maven/dependencies</code>
Install	<code>maven/install</code>	<code>maven/uninstall</code>

Docker

```
(load-module :docker)
```

Docker	<code>docker/version</code>	<code>docker/cmd</code>
	<code>docker/debug</code>	
Images	<code>docker/images</code>	<code>docker/image-pull</code>
	<code>docker/rmi</code>	<code>docker/image-rm</code>
	<code>docker/image-prune</code>	
Containers	<code>docker/run</code>	<code>docker/ps</code>
	<code>docker/start</code>	<code>docker/stop</code>
	<code>docker/exec</code>	<code>docker/exec&</code>
	<code>docker/rm</code>	<code>docker/prune</code>
	<code>docker/cp</code>	
	<code>docker/diff</code>	<code>docker/pause</code>
	<code>docker/unpause</code>	<code>docker/wait</code>
	<code>docker/logs</code>	
Volumes	<code>docker/volume-list</code>	
	<code>docker/volume-create</code>	
	<code>docker/volume-inspect</code>	
	<code>docker/volume-rm</code>	
	<code>docker/volume-prune</code>	
	<code>docker/volume-exists?</code>	
Utils	<code>docker/images-query-by-repo</code>	
	<code>docker/image-ready?</code>	
	<code>docker/container-find-by-name</code>	
	<code>docker/container-exists-with-name?</code>	
	<code>docker/container-running-with-name?</code>	
	<code>docker/container-start-by-name</code>	
	<code>docker/container-stop-by-name</code>	
	<code>docker/container-remove-by-name</code>	

Fonts

True Type Fonts

```
(load-module :fonts)
```

Download	<code>fonts/download-font-family</code>
	<code>fonts/download-demo-fonts</code>

Test

```
(load-module :test)
```

Define	<code>test/deftest</code>		
Fixture	<code>test/use-fixtures</code>		
Run	<code>test/run-tests</code>	<code>test/run-test-var</code>	
	<code>test/successful?</code>		
Assert	<code>assert</code>	<code>assert-false</code>	<code>assert-eq</code>
	<code>assert-ne</code>	<code>assert-throws</code>	
	<code>assert-does-not-throw</code>		
	<code>assert-throws-with-msg</code>		

Configuration

Manages configurations with system property & env var support

```
(load-module :config)
```

Build	<code>config/build</code>	
File	<code>config/file</code>	<code>config/resource</code>
Env	<code>config/env-var</code>	<code>config/env</code>
Properties	<code>config/property-var</code>	<code>config/properties</code>

Component

Managing lifecycle and dependencies of components

```
(load-module :component)
```

Build	<code>component/system-map</code>
	<code>component/system-using</code>

```
docker/container-status-by-name
docker/container-exec-by-name
docker/container-exec-by-name&
docker/container-logs
docker/container-purge-by-name
docker/container-image-info-by-name
```

Cargo

Docker Testcontainers

```
(load-module :cargo)
```

Cargo	cargo/start	cargo/stop
	cargo/running?	cargo/purge

Cargo ArangoDB

ArangoDB Testcontainers

```
(load-module :cargo-arangodb)
```

Lifecycle	cargo-arangodb/start cargo-arangodb/stop cargo-arangodb/running? cargo-arangodb/logs
Backup	cargo-arangodb/db-dump cargo-arangodb/db-restore cargo-arangodb/exists-db-dump? cargo-arangodb/remove-db-dump cargo-arangodb/list-db-dumps cargo-arangodb/upload-db-dump cargo-arangodb/download-db-dump

Cargo Qdrant Vector DB

Qdrant Testcontainers

```
(load-module :cargo-qdrant)
```

Lifecycle	cargo-qdrant/start	cargo-qdrant/stop
	cargo-qdrant/running?	cargo-qdrant/logs

PostgreSQL DB

PostgreSQL Testcontainers

```
(load-module :cargo-postgresql)
```

Lifecycle	cargo-postgresql/start cargo-postgresql/stop cargo-postgresql/running? cargo-postgresql/logs
-----------	---

Tomcat

Embedded Tomcat WebApp Server

```
(load-module :tomcat)
```

Protocol	component/Component
----------	-------------------------------------

Util	component/deps	component/dep
	component/id	

App

Venice application archive

```
(load-module :app)
```

Build	app/build
Manifest	app/manifest

Benchmark

```
(load-module :benchmark)
```

Utils	benchmark/benchmark
-------	-------------------------------------

Timing

Timing

```
(load-module :timing)
```

Timing	timing/run	timing/elapsed
--------	----------------------------	--------------------------------

Grep

Grep like search tool

```
(load-module :grep)
```

Grep	grep/grep	grep/grep-zip
------	---------------------------	-------------------------------

QR-Reference

Create, parse, and format QR references according to the Swiss payment standards.

```
(load-module :qrrref)
```

QR Ref	qrrref/qr-ref	qrrref/parse
	qrrref/format	

Ascii Table

Create and customize simple ASCII tables.

```
(load-module :ascii-table)
```

Render	ascii-table/render	ascii-table/print
--------	------------------------------------	-----------------------------------

Matrix

Simple matrix functions. To process large matrices use the "Efficient Java Matrix Library" (EJML) <http://ejml.org/wiki/> instead.

Tomcat	<code>tomcat/start</code> <code>tomcat/stop</code> <code>tomcat/destroy</code> <code>tomcat/shutdown</code> <code>tomcat/state</code>
Servlet	<code>tomcat/create-servlet</code> <code>tomcat/hello-world-servlet</code>
Install Java 3rd party libraries: <pre>(do (load-module :tomcat-install) (tomcat-install/install :dir (repl/libs-dir) :silent false))</pre>	

Ring

(load-module :ring)

Servlet	<code>ring/create-servlet</code>
Routing	<code>ring/match-routes</code>
Utils	<code>ring-util/redirect</code> <code>ring-util/not-found-response</code> <code>ring-util/get-request-header</code> <code>ring-util/get-request-header-accept-mimetypes</code> <code>ring-util/get-request-parameters</code> <code>ring-util/get-request-parameter</code> <code>ring-util/get-request-long-parameter</code> <code>ring-util/html-request?</code> <code>ring-util/json-request?</code> <code>ring-util/parse-charset</code> <code>ring-util/debug?</code>
Middleware	<code>ring-mw/mw-identity</code> <code>ring-mw/mw-debug</code> <code>ring-mw/mw-print-uri</code> <code>ring-mw/mw-request-counter</code> <code>ring-mw/mw-dump-request</code> <code>ring-mw/mw-dump-response</code>
Session	<code>ring-session/session-invalidate</code> <code>ring-session/session-clear</code> <code>ring-session/session-id</code> <code>ring-session/session-get-value</code> <code>ring-session/session-remove-value</code> <code>ring-session/session-creation-time</code>
Multipart	<code>ring-multipart/multipart-request?</code> <code>ring-multipart/parts</code> <code>ring-multipart/parts-delete-all</code>

Tracing

Tracing functions

(load-module :trace)

Tracing	<code>trace/trace</code> <code>trace/trace-var</code> <code>trace/untrace-var</code>
Test	<code>trace/traced?</code> <code>trace/traceable?</code>

(load-module :matrix)

Matrix	<code>matrix/validate</code> <code>matrix/vector2d</code> <code>matrix/empty?</code> <code>matrix/rows</code> <code>matrix/columns</code> <code>matrix/row</code> <code>matrix/column</code>
Format	<code>matrix/format</code>
Elements	<code>matrix/element</code> <code>matrix/assoc-element</code>
Add	<code>matrix/add-column-at-start</code> <code>matrix/add-column-at-end</code> <code>matrix/add-row-at-start</code> <code>matrix/add-row-at-end</code>
Remove	<code>matrix/remove-column</code> <code>matrix/remove-row</code>
LinAlg	<code>matrix/transpose</code>

Ansi

ANSI codes, styles, and colorization helper functions

(load-module :ansi)

Colors	<code>ansi/fg-color</code> <code>ansi/bg-color</code>
Styles	<code>ansi/style</code> <code>ansi/ansi</code> <code>ansi/with-ansi</code> <code>ansi/without-ansi</code>
Cursor	<code>ansi/without-cursor</code>
Progress	<code>ansi/progress</code> <code>ansi/progress-bar</code>

Mimetypes

(load-module :mimetypes)

Mimetypes	<code>mimetypes/probe-content-type</code>
-----------	---

Multipart

(load-module :multipart)

Multipart	<code>multipart/render</code> <code>multipart/parse</code> <code>multipart/http-content-type-header</code>
-----------	---

SSE

Server Side Events

(load-module :server-side-events)

Render/Parse	<code>server-side-events/render</code> <code>server-side-events/parse</code>
Read	<code>server-side-events/read-event</code> <code>server-side-events/read-events</code>

HTTP Client J8

Util	trace/trace-str-limit		
Tee	trace/tee->	trace/tee->>	trace/tee

Shell

Functions to deal with the operating system

```
(load-module :shell)
```

Open	shell/open	shell/open-macos-app
Process	shell/kill shell/kill-forcibly shell/wait-for-process-exit shell/alive? shell/pid shell/process-handle shell/process-handle? shell/process-info shell/processes shell/processes-info shell/descendant-processes shell/parent-process	
Util	shell/diff	

JDBC Core

```
(load-module :jdbc-core)
```

Create/Drop	jdbc-core/create-database jdbc-core/drop-database
Provider	jdbc-core/postgresql?
Meta Data	jdbc-core/meta-data jdbc-core/features jdbc-core/schemas jdbc-core/tables jdbc-core/columns
Connection	jdbc-core/closed?
Templates	jdbc-core/with-conn jdbc-core/with-tx
TX	jdbc-core/auto-commit? jdbc-core/auto-commit! jdbc-core/commit! jdbc-core/rollback! jdbc-core/tx-isolation jdbc-core/tx-isolation!
Statements	jdbc-core/create-statement jdbc-core/prepare-statement
Execute	jdbc-core/execute jdbc-core/execute-query jdbc-core/execute-query* jdbc-core/execute-update jdbc-core/generated-keys jdbc-core/count-rows
Prepared Stmt	jdbc-core/ps-clear-parameters jdbc-core/ps-string jdbc-core/ps-boolean jdbc-core/ps-int jdbc-core/ps-long

HTTP Client based on HttpURLConnection (Java 8+)

```
(load-module :http-client-j8)
```

HTTP Client	http-client-j8/send http-client-j8/upload-file http-client-j8/upload-multipart
Response	http-client-j8/slurp-response
SSE	http-client-j8/process-server-side-events
Tests	http-client-j8/status-ok-range? http-client-j8/status-redirect-range? http-client-j8/status-client-range? http-client-j8/status-server-error-range?

OpenAI Client

```
(load-module :openai)
```

Chat	openai/chat-completion openai/chat-completion-streaming openai/chat-process-streaming-events
Chat Functions	openai/exec-fn
Chat Response	openai/chat-finish-reason openai/chat-finish-reason-stop? openai/chat-finish-reason-tool-calls? openai/chat-extract-response-message openai/chat-extract-response-message-role openai/chat-extract-response-message-content openai/chat-extract-response-tool-calls-id openai/chat-extract-function-name
Image	openai/image-create openai/image-variants openai/image-edits openai/image-download
Audio	openai/audio-speech-generate openai/audio-speech-transcribe openai/audio-speech-translate openai/audio-file-ext
Files	openai/file-upload openai/file-list openai/file-retrieve openai/file-delete openai/file-retrieve-content
Models	openai/model-list openai/model-retrieve openai/model-delete
Embeddings	openai/embedding-create
Assistants	

	jdbc-core/ps-float jdbc-core/ps-double jdbc-core/ps-decimal jdbc-core/ps-date jdbc-core/ps-timestamp jdbc-core/ps-clob jdbc-core/ps-blob
Result Set	jdbc-core/rs-first! jdbc-core/rs-next! jdbc-core/rs-last! jdbc-core/collect-result-set jdbc-core/render-query-result jdbc-core/print-query-result
Result Set Data	jdbc-core/rs-string jdbc-core/rs-boolean jdbc-core/rs-int jdbc-core/rs-long jdbc-core/rs-float jdbc-core/rs-double jdbc-core/rs-decimal jdbc-core/rs-date jdbc-core/rs-timestamp jdbc-core/rs-clob jdbc-core/rs-blob
Clob	jdbc-core/clob? jdbc-core/clob-length jdbc-core/clob-reader jdbc-core/clob-free
Blob	jdbc-core/blob? jdbc-core/blob-length jdbc-core/blob-in-stream jdbc-core/blob-bytebuf jdbc-core/blob-free

Installer

A simple artifact installer for Venice. This not a package manager!

```
(load-module :installer)
```

Install	installer/install installer/install-module installer/install-libs
Demo	installer/install-demo installer/install-demo-fonts
Clean	installer/clean

JDBC PostgreSQL

```
(load-module :jdbc-postgresql)
```

Connection	jdbc-postgresql/create-connection
Meta Data	jdbc-postgresql/describe-table jdbc-postgresql/foreign-key-constraints

```

openai/assistant-create
openai/assistant-list
openai/assistant-retrieve
openai/assistant-modify
openai/assistant-delete

```

Threads	openai/thread-create openai/thread-retrieve
---------	--

Utils	openai/assert-response-http-ok openai/pretty-print-json
-------	--

JTokkit

A tokenizer designed for use with OpenAI models

```
(load-module :jtokkit)
```

Encoding	jtokkit/encoding jtokkit/encoding-types jtokkit/model-types jtokkit/encode jtokkit/count-tokens
----------	---

Install JTokkit 3rd party libraries:

```

(do
  (load-module :jtokkit-install)
  (jtokkit-install/install :dir (repl/libs-dir)
                           :silent false))

```

Images

```
(load-module :images)
```

Load/Save	images/load images/save
Create/Copy	images/create images/copy
Properties	images/dimension images/alpha-channel?
File Formats	images/format-names
Transform	images/rotate images/flip images/crop images/pad images/resize-fit images/resize images/shear images/translate images/apply-ops images/convert-to-rgba images/convert-to-rgb
G2D	images/g2d images/anti-alias images/stroke images/fg-color images/bg-color images/get-clip images/set-clip images/get-clip-bounds
Transform	images/set-transform images/get-transform images/transform images/tx-identity images/tx-translate images/tx-scale images/tx-shear images/tx-rotate
Drawing	

Chinook Dataset

Chinook dataset for PostgreSQL

(load-module :chinook-postgresql)

Data Model	chinook-postgresql/show-data-model
Data	chinook-postgresql/show-data
Load Data	chinook-postgresql/load-data
Download Data	chinook-postgresql/download-data

	images/copy-area	images/clear-rect
	images/draw-circle	
	images/draw-oval	images/draw-rect
	images/draw-round-rect	
	images/draw-polygon	
	images/draw-string	
	images/draw-line	images/draw-image
Filling	images/fill-circle	
	images/fill-oval	images/fill-rect
	images/fill-round-rect	
	images/fill-polygon	
Shapes	images/point	images/rectangle
	images/polygon	
Polygons	images/hexagon-poly	
	images/rectangle-poly	
	images/square-poly	
	images/scale-points	
	images/translate-points	
	images/rotate-points	

Embedding in Java

Eval

```
import com.github.jlangch.venice.Venice;

public class Example {
    public static void main(String[] args) {
        final Venice venice = new Venice();

        final Long result = (Long)venice.eval("(+ 1 2)");
    }
}
```

Passing parameters

```
import com.github.jlangch.venice.Parameters;
import com.github.jlangch.venice.Venice;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        final Long result = (Long)venice.eval(
            "(+ x y 3)",
            Parameters.of("x", 6, "y", 3L));
    }
}
```

Dealing with Java objects

```
import java.awt.Point;
import com.github.jlangch.venice.Parameters;
import com.github.jlangch.venice.Venice;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        // returns a string: "Point=(x: 100.0, y: 200.0)"
        String ret = (String)venice.eval(
            "(let [x (:x point)                \n" +
            "      y (:y point)]                \n" +
            "  (str \"Point=(x: \" x \"\", y: \" y \"\")\"))",
            Parameters.of("point", new Point(100, 200)));

        // returns a java.awt.Point: [x=110,y=220]
        Point point = (Point)venice.eval(
            "(. :java.awt.Point :new (+ x 10) (+ y 20))",
            Parameters.of("x", 100, "y", 200));
    }
}
```

Precompiling

```
import com.github.jlangch.venice.IPreCompiled;
import com.github.jlangch.venice.Parameters;
import com.github.jlangch.venice.Venice;

public class Example {
```

```

public static void main(String[] args) {
    Venice venice = new Venice();

    IPreCompiled precompiled = venice.precompile("example", "(+ 1 x)");

    for(int ii=0; ii<100; ii++) {
        venice.eval(precompiled, Parameters.of("x", ii));
    }
}
}

```

Java Interop

```

import java.time.ZonedDateTime;
import com.github.jlangch.venice.Venice;

public class Example {
    public static void main(String[] args) {
        Venice venice = new Venice();

        Long val = (Long)venice.eval("( . :java.lang.Math :min 20 30)");

        ZonedDateTime ts = (ZonedDateTime)venice.eval(
            "(. (. :java.time.ZonedDateTime :now) :plusDays 5)");
    }
}

```

Sandbox

```

import com.github.jlangch.venice.SecurityException;
import com.github.jlangch.venice.Venice;
import com.github.jlangch.venice.javainterop.SandboxInterceptor;
import com.github.jlangch.venice.javainterop.SandboxRules;

public class SandboxExample {
    public static void main(final String[] args) {
        final SandboxInterceptor sandbox =
            new SandboxRules()
                // Venice functions: blacklist all unsafe functions
                .rejectAllUnsafeFunctions()

                // Venice functions: whitelist rules for print functions to offset
                // blacklist rules by individual functions
                .whitelistVeniceFunctions("*print*")

                .sandbox();

        final Venice venice = new Venice(sandbox);

        // => OK, 'println' is part of the unsafe functions, but enabled by the 2nd rule
        venice.eval("(println 100)");

        // => FAIL, 'read-line' is part of the unsafe functions
        try {
            venice.eval("(read-line)");
        }
        catch(SecurityException ex) {
            System.out.println("REJECTED: (read-line)");
        }
    }
}

```

Recursion

Recursion

Functional languages support **Tail Call Optimization (TCO)** to provide memory efficient recursion. Venice supports *automatic Tail Call Optimization* and *Self Recursion* through the `loop..recur` syntax. Self recursion is a way to mimic TCO.

In addition Venice provides the *trampoline* function for mutual recursion for more involved forms of recursion.

Self-Recursive Calls (loop - recur)

Venice self-recursive calls do not consume a new stack frame for every new recursion iteration and have a constant memory usage. It's the only non-stack-consuming looping construct in Venice. To make it work the `recur` expression must be in *tail position*. This way Venice can turn the recursive `loop..recur` construct behind the scene into a plain loop.

Definition: The tail position is a position which an expression would return a value from. There are no more forms evaluated after the form in the tail position is evaluated.

Remember: Venice offers various alternative solutions to recursion to solve loops like `(+ 1 2 3 4 5 6)` to sum up a list of numbers or the powerful `reduce` function: `(reduce + [1 2 3 4 5])`. Many Venice functions accept an arbitrary number of arguments to prevent you from writing loops.

Example 1: Recursively sum up the numbers 0..n:

```
;; Definition:
;; sum 0 -> 0
;; sum n -> n + sum (n - 1)
(do
  (defn sum [n]
    ;; the transformed recursion uses an accumulator for intermediate results
    (loop [cnt n, acc 0]
      (if (zero? cnt)
        acc
        (recur (dec cnt) (+ acc cnt))))))

(sum 100000) ; => 5000050000
```

Example 2: Recursively compute the factorial of a number:

```
;; Definition:
;; factorial 1 -> 1
;; factorial n -> n * factorial (n - 1)
(do
  (defn factorial [x]
    ;; the transformed recursion uses an accumulator for intermediate results
    (loop [n x, acc 1N]
      (if (== n 1)
        acc
        (recur (dec n) (* acc n))))))

(factorial 5) ; => 120N
(factorial 10000) ; => 284625968091...00000N (35661 digits)
```

Example 3: Recursively compute the Fibonacci numbers (0 1 1 2 3 5 8 ...):

```
;; Definition:
;; fib 0 -> 0
;; fib 1 -> 1
;; fib n -> fib (n - 2) + fib (n - 1)
(do
  (defn fib [x]
    (loop [n x, a 0N, b 1N]
      (case n
        0 a
        1 b
        (recur (dec n) b (+ a b)))))

  (fib 6) ; => 8N
  (fib 100000) ; => 259740693472217...28746875N (20901 digits)
```

Recursion with lazy sequences

Example 1: Lazy Fibonacci number sequence computed by a recursive function:

```
(do
  (defn fib
    ([] (fib 0N 1N))
    ([a b] (cons a #(fib b (+ a b)))))

  (doall (take 7 (fib)))) ; => (0 1 1 2 3 5 8)
```

Example 2: Factorial numbers:

```
(do
  (defn factorial
    ([] (factorial 1 1N))
    ([x] (first (drop (dec x) (factorial))))
    ([n acc] (cons acc #(factorial (inc n) (* acc (inc n))))))

  (factorial 5) ; => 120N
  (factorial 10000) ; => 284625968091...00000N (35661 digits)
```

Mutually recursive calls (trampoline)

`trampoline` can be used to convert algorithms requiring mutual recursion without stack consumption. Calls `f`, if `f` returns a function, calls that function with no arguments, and continues to repeat, until the return value is not a function, then returns that non-function value.

The function `trampoline` is defined simplified as

```
(defn trampoline [f]
  (loop [f f]
    (let [ret (f)]
      (if (fn? ret) (recur ret) ret)))))
```

Examples:

```
(do
  (defn is-odd? [n]
    (if (zero? n) false #(is-even? (dec n))))

  (defn is-even? [n]
    (if (zero? n) true #(is-odd? (dec n))))

  (trampoline (is-odd? 10000)))
```

```
(do
  (defn factorial
    ([n] #(factorial n 1N))
    ([n acc] (if (< n 2)
                 acc
                 #(factorial (dec n) (* acc n)))))

  (trampoline (factorial 10000)))
```

Tail Call Optimization (TCO)

Venice has support for automatic *tail call optimization*. The recursive call must be in tail position.

```
(do
  (defn factorial
    ([n]      (factorial n 1N))
    ([n acc] (if (== n 1)
                 acc
                 (factorial (dec n) (* acc n)))))

  (factorial 5)      ; => 120N
  (factorial 10000) ; => 284625968091...00000N (35661 digits)
```

Recursion vs Folding

Tail call recursive functions, can always be written in terms of a reducing (folding) function. E.g.:

```
(do
  (defn factorial [n]
    ;; reducing factorial
    (reduce * 1N (range 1 (inc n))))

  (factorial 5)      ; => 120N
  (factorial 10000) ; => 284625968091...00000N (35661 digits)
```

But not all recursive functions can be transformed into a tail recursive function and translated into a loop. The [Ackermann's function](#) is such an example of a non [primitive recursive function](#) that can not be de-recursed into loops.

Recursion and Memoization

For some recursive algorithms *memoization* can speed up computation dramatically:

```
(do
  (def fibonacci
```

```

(memoize (fn [n]
           (if (< n 2)
               (max n 0)
               (+ (fibonacci (- n 1)) (fibonacci (- n 2)))))))

(fibonacci 30))

```

Please note that this naive memoization approach with recursive functions does **not** work as expected:

```

(do
  (defn fib-simple [n]
    (if (< n 2)
        (max n 0)
        (+ (fib-simple (- n 1)) (fib-simple (- n 2)))))

  (def fib-memoize (memoize fib-simple))

  (fib-memoize 30))

```

memoization is doing a good job in computing fibonacci numbers using simple recursion. It eliminates the recurring computation of the predecessors values.

Nevertheless there are recursive algorithms like the *Ackermann* function where memoization has to raise its arms.

Compare recursion efficiency

To see how efficient tail call optimization for recursion is we compare simple recursion with self recursion applied to computing Fibonacci numbers.

Note: all examples run with upfront macro expansion enabled.

```

(do
  (load-module :benchmark ['benchmark :as 'b])

  (defn fib-simple [n]
    (if (< n 2)
        n
        (+ (fib-simple (- n 1)) (fib-simple (- n 2)))))

  (defn fib-tco
    ([n]
     (fib-tco n 0N 1N))
    ([n a b]
     (case n
         0 a
         1 b
         (fib-tco (dec n) b (+ a b)))))

  (defn fib-loop-recur [x]
    (loop [n x, a 0N, b 1N]
      (case n
          0 a
          1 b
          (recur (dec n) b (+ a b)))))

  (def fib-memoize
    (memoize
     (fn [n]
       (if (< n 2)
           n
           (+ (fib-memoize (- n 1)) (fib-memoize (- n 2)))))))

```

```
;; (b/benchmark (fib-simple 30) 5 5)
;; (b/benchmark (fib-tco 30) 5000 1000)
;; (b/benchmark (fib-loop-recur 30) 5000 1000)
;; (time (fib-memoize 30)) ;; memoized functions can not be benchmarked
```

```
;; run on MacBook Air M2, with 'macroexpand' enabled
```

```
;; +-----+-----+
;; | (fib-simple 30)      | 1.171s |
;; | (fib-tco 30)        | 31.286μs |
;; | (fib-loop-recur 30) | 27.946μs |
;; | (fib-memoize 30)    | 2.540ms |
;; +-----+-----+
```


Destructuring

Destructuring

Sequential Destructuring

Sequential destructuring breaks up a sequential data structure as a Venice list or vector within a let binding

```
(do
  (let [[x y z] [1 2 3]]
    (println x y z))
  ;=> 1 2 3

  ;; for strings, the elements are destructured by character.
  (let [[x y z] "abc"]
    (println x y z))) ;; => a b c
```

or within function parameters

```
(do
  (defn position [[x y]]
    (println "x:" x "y:" y))

  (position [1 2])) ;; => x: 1 y: 2
```

The destructured collection must not be of same size as the number of binding names

```
(do
  (let [[a b c d e f] '(1 2 3)]
    (println a b c d e f)) ;=> 1 2 3 nil nil nil

  (let [[a b c] '(1 2 3 4 5 6 7 8 9)]
    (println a b c))) ;; => 1 2 3
```

Working with tail elements '&' and ignoring bindings '_'

```
(do
  (let [[a b c & z] '(1 2 3 4 5 6 7 8 9)]
    (println a b c z)) ;; => 1 2 3 (4 5 6 7 8 9)

  (let [[a _ b _ c & z] '(1 2 3 4 5 6 7 8 9)]
    (println a b c z))) ;; => 1 3 5 (6 7 8 9)
```

Binding the entire collection with ':as'

```
(do
  (let [[a b c & z :as all] '(1 2 3 4 5 6 7 8 9)]
    (println a b c z all))
  ;; => 1 2 3 (4 5 6 7 8 9) (1 2 3 4 5 6 7 8 9)
)
```

Nested bindings

```
(do
  (def line [[5 10] [10 20]])
  (let [[[x1 y1][x2 y2]] line]
    (printf "Line from (%d,%d) to (%d,%d)%n" x1 y1 x2 y2))
  ;; => "Line from (5,10) to (10,20)"
)
```

`:as` or `&` can be used at any level

```
(do
  (def line [[5 10] [10 20]])
  (let [[[a b :as group1] [c d :as group2]] line]
    (println a b group1)      ;; => 5 10 [5 10]
    (println c d group2)))   ;; => 10 20 [10 20]
```

Associative Destructuring

Associative destructuring breaks up an associative (key/value) data structure as a Venice map within a let binding.

```
(do
  (let [{a :a, b :b, c :c} {:a "A" :b "B" :d "D"}]
    (println a b c)))  ;; => A B nil
```

```
(do
  (def map_keyword {:a "A" :b "B" :c 3 :d 4})
  (def map_strings {"a" "A" "b" "B" "c" 3 "d" 4})

  (let [{:keys [a b c]} map_keyword]
    (println a b c))  ;; => A B 3

  (let [{:strs [a b c]} map_strings]
    (println a b c)))  ;; => A B 3
```

Binding the entire collection with `:as`

```
(do
  (def map_keyword {:a "A" :b "B" :c 3 :d 4})

  (let [{:keys [a b c] :as all} map_keyword]
    (println a b c all))
  ;; => A B 3 {:a A :b B :c 3 :d 4}
```

Binding with defaults `:or`

```
(do
  (defn configure [options]
    (let [{:keys [port debug verbose] :or {port 8000, debug false, verbose false}} options]
      (println "port =" port " debug =" debug " verbose =" verbose)))
    ;; => port 8000, debug false, verbose false

  (configure {:debug true}))
```

Nested destructuring

Associative destructuring can be nested and combined with sequential destructuring

```
(do
  (def users
    {:peter {:role "clerk"
              :branch "Zurich"
              :age 40}

     :magda {:role "head of HR"
              :branch "Bern"
              :age 45}

     :kurt  {:role "assistant"
              :branch "Lucerne"
              :age 32}})

  (let [{[:keys [role branch]] :peter} users]
    (println "Peter is a" role "located at" branch)))
;; => Peter is a clerk located at Zurich
```

VeniceDoc

VeniceDoc is a documentation generator for the *Venice* language for generating API documentation in HTML format from *Venice* source code. It is used internally for generating the PDF and HTML cheatsheets. The function `doc` makes use of it to display the documentation for functions.

Example

Define a function `add` with documentation:

```
(defn
  ^{ :arglists '(
      "(add)", "(add x)", "(add x y)", "(add x y & more)"
    :doc
      """
      Returns the sum of the numbers.
      `(add)` returns 0.
      """
    :examples '(
      "(add)",
      "(add 1)",
      "(add 1 2)",
      "(add 1 2 3 4)"
    :see-also '(
      "+", "-", "*", "/"
    ) }

  add

  ([] 0)
  ([x] x)
  ([x y] (+ x y))
  ([x y & xs] (+ x y xs)))
```

Show its documentation from the REPL:

```
venice> (doc add)
```

REPL Output:

```
(add), (add x), (add x y), (add x y & more)

Returns the sum of the numbers. (add) returns 0.

EXAMPLES:
  (add)

  (add 1)

  (add 1 2)

  (add 1 2 3 4)
```

SEE ALSO:

`+`, `-`, `*`, `/`

VeniceDoc Format

The documentation is defined as a Venice metadata `map`:

```
{ :arglists '("add)", "(add x)")
  :doc "Returns the sum of the numbers."
  :examples '("add 1)", "(add 1 2)")
  :see-also '("+", "-", "*", "/") }
```

key	description
:arglist	the optional arglist, a list of variadic arg specs
:doc	the documentation in Venice markdown format
:examples	optional examples, a list of Venice scripts. Use triple quotes for multi-line scripts
:see-also	an optional list of cross referenced functions

Markdown

Venice Markdown

Headings

To create a heading, add one to four `#` symbols before the heading text. The number of `#` will determine the size of the heading.

```
# The largest heading
## The second largest heading
### The third largest heading
#### The fourth largest heading
```

Paragraphs and Line Breaks

```
A paragraph is simply one or more consecutive lines of text, separated by
one or more blank lines (a line containing nothing but spaces or tabs).
```

```
Within a paragraph line breaks can be added by placing a `pilcrow`
```

```
Line 1¶Line 2¶
Line 3
```

A paragraph is simply one or more consecutive lines of text, separated by one or more blank lines (a line containing nothing but spaces or tabs).

Within a paragraph line breaks can be added by placing a `¶`

Line 1
Line 2
Line 3

Styling

Venice markdown supports *italic*, **bold**, and ***bold-italic*** styling

```
This is *italic*, **bold**, and ***bold-italic*** styled text.
```

This is *italic*, **bold**, and ***bold-italic*** styled text.

Lists

Unordered List

```
* item 1
* item 2
* item 3
```

- item 1
- item 2

- item 3

Ordered List

```
1. item 1
2. item 2
3. item 3
```

1. item 1
2. item 2
3. item 3

Multiline list items with explicit line breaks:

```
* item 1
* item 2
  next line
  next line
* item 3
```

- item 1
- item 2
next line
next line
- item 3

Multiline list items with auto line breaks:

```
* item 1
* Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod
  tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim
  veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex
  ea commodo consequat. Duis aute irure dolor in reprehenderit in
  voluptate velit esse cillum dolore eu fugiat nulla pariatur.
* item 3
```

- item 1
- Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur.
- item 3

Links

Links are created by wrapping link text in brackets `[]`, and then wrapping the URL in parentheses `()`.

```
[Venice](https://github.com/jlangch/venice)
```

[Venice](https://github.com/jlangch/venice)

Tables

A simple table

JAN	1
FEB	20
MAR	300

JAN	1
FEB	20
MAR	300

Column alignment

:---	:---:	---:
1	1	1
200	200	200
30000	30000	30000

1	1	1
200	200	200
30000	30000	30000

Width header

Col 1	Col 2	Col 3
:---	:---:	---:
1	1	1
200	200	200
30000	30000	30000

Col 1	Col 2	Col 3
1	1	1
200	200	200
30000	30000	30000

PDF rendered tables have always a width of 100%. In some use cases an additional left aligned column can trick the rendered table:

Col 1	Col 2	Col 3	
:---	:---:	---:	:---
1	1	1	
200	200	200	
30000	30000	30000	

Col 1	Col 2	Col 3
1	1	1
200	200	200
30000	30000	30000

Line breaks in cells

JAN	1 2 3
FEB	20
MAR	300

JAN	1
	2

	3
FEB	20
MAR	300

Column format using CSS styles

The Venice markdown supports a few CSS styles

Text alignment:

- `text-align: left`
- `text-align: center`
- `text-align: right`

Column width:

- `width: 15%`
- `width: 15pm`
- `width: 15em`
- `width: auto`

```
| Col 1 | Col 2 |
| [![text-align: left; width: 6em]] | [![text-align: left; width: 6em]] |
| 1      | 1      |
| 200    | 200    |
| 30000  | 30000  |
```

Col 1	Col 2
1	1
200	200
30000	30000

Code

Code can be called out within a text by enclosing it with single backticks.

```
To open a namespace use `(ns name)`.
```

To open a namespace use `(ns name)` .

Code block are enclosed with three backticks:

```
```
(defn hello []
 (println "Hello stranger"))

(hello)
```
```

producing

```
(defn hello []
  (println "Hello stranger"))

(hello)
```


Function Details

[top](#)

#{} ---

Creates a set.

```
#{10 20 30}  
=> #{10 20 30}
```

[top](#)

() ---

Creates a list.

```
'(10 20 30)  
=> (10 20 30)
```

[top](#)

* ---

```
(*)  
(* x)  
(* x y)  
(* x y & more)
```

Returns the product of numbers. (*) returns 1

```
(*)  
=> 1
```

```
(* 4)  
=> 4
```

```
(* 4 3)  
=> 12
```

```
(* 4 3 2)  
=> 24
```

```
(* 4I 3I)  
=> 12I
```

```
(* 6.0 2)  
=> 12.0
```

```
( * 6 1.5M )
=> 9.0M
```

SEE ALSO

[+](#)

Returns the sum of the numbers. (+) returns 0.

[-](#)

If one number is supplied, returns the negation, else subtracts the numbers from x and returns the result.

[/](#)

If no denominators are supplied, returns 1/numerator, else returns numerator divided by all of the denominators.

[dec/add](#)

Adds two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/sub](#)

Subtract y from x and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/mul](#)

Multiplies two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, ...

[dec/div](#)

Divides x by y and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/scale](#)

Scales a decimal. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

top

ARGV

A list of the supplied command line arguments, or `nil` if the instantiator of the Venice instance decided not to make the command line arguments available.

ARGV

```
=> nil
```

top

ansi-term

`true` if Venice runs in an ANSI terminal, otherwise `false`

ansi-term

```
=> false
```

top

err

A `:java.io.PrintStream` object representing standard error for print operations.

Defaults to `System.err`, wrapped in an `PrintStream`.

`*err*` is a dynamic var. Any `:java.io.PrintStream` can be dynamically bound to it:

```
(binding [*err* print-stream]
 (println "text"))
```

SEE ALSO

[with-err-str](#)

Evaluates `exprs` in a context in which `*err*` is bound to a capturing output stream. Returns the string created by any nested printing ...

[*out*](#)

A `:java.io.PrintStream` object representing standard output for print operations.

[*in*](#)

A `:java.io.Reader` object representing standard input for read operations.

[top](#)

`*in*`

A `:java.io.Reader` object representing standard input for read operations.

Defaults to `System.in`, wrapped in an `InputStreamReader`.

`*in*` is a dynamic var. Any `:java.io.Reader` can be dynamically bound to it:

```
(binding [*in* reader]
 (read-line))
```

SEE ALSO

[read-line](#)

Without `arg` reads the next line from the stream that is the current value of `*in*`. With `arg` reads the next line from the passed stream ...

[read-char](#)

Without `arg` reads the next char from the stream that is the current value of `*in*`. With `arg` reads the next char from the passed stream ...

[*out*](#)

A `:java.io.PrintStream` object representing standard output for print operations.

[*err*](#)

A `:java.io.PrintStream` object representing standard error for print operations.

[top](#)

`*loaded-files*`

The loaded files

```
*loaded-files*
=> #{} 
```

[top](#)

`*loaded-modules*`

The loaded modules

```
*loaded-modules*
=> #{:tomcat :ring :csv :jsonl :xchart :ring-multipart :ascii-table :java :xml :semver :ring-mw :pretty-print :
cargo :ring-session :app :gradlew :images :hexdump :test :inet :maven :io :timing :benchmark :str :core :openai
:regex :installer :parsifal :shell :multipart :jdbc-core :zipvault :math :http-client-j8 :kira :qrref :
mime-types :cargo-qdrant :crypt :cargo-postgresql :ring-util :matrix :docker :trace :fonts :chinook-postgresql :
json :cidr :jetty :geoip :server-side-events :jtokkit :grep :sandbox :jdbc-postgresql :ansi :gradle :excel :
http-client :component :cargo-arangodb :pdf :time :config}
```

top

newline

The system newline

```
*newline*
=> "\n"
```

top

ns

The current namespace

```
*ns*
=> user

(do
  (ns test)
  *ns*)
=> test
```

top

out

A `:java.io.PrintStream` object representing standard output for print operations.

Defaults to `System.out`, wrapped in an `PrintStream`.

`*out*` is a dynamic var. Any `:java.io.PrintStream` can be dynamically bound to it:

```
(binding [*out* print-stream]
  (println "text"))
```

SEE ALSO

[with-out-str](#)

Evaluates `exprs` in a context in which `*out*` is bound to a capturing output stream. Returns the string created by any nested printing ...

[*err*](#)

A `:java.io.PrintStream` object representing standard error for print operations.

[*in*](#)

A `:java.io.Reader` object representing standard input for read operations.

run-mode

The current run-mode one of `:repl`, `:script`, `:app`

```
*run-mode*  
=> :script
```

version

The Venice version

```
*version*  
=> "0.0.0"
```

+

```
(+)  
(+ x)  
(+ x y)  
(+ x y & more)
```

Returns the sum of the numbers. (+) returns 0.

```
(+)  
=> 0
```

```
(+ 1)  
=> 1
```

```
(+ 1 2)  
=> 3
```

```
(+ 1 2 3 4)  
=> 10
```

```
(+ 1I 2I)  
=> 3I
```

```
(+ 1 2.5)  
=> 3.5
```

```
(+ 1 2.5M)  
=> 3.5M
```

SEE ALSO

—

If one number is supplied, returns the negation, else subtracts the numbers from x and returns the result.

[*](#)

Returns the product of numbers. (*) returns 1

[/](#)

If no denominators are supplied, returns 1/numerator, else returns numerator divided by all of the denominators.

[dec/add](#)

Adds two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/sub](#)

Subtract y from x and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/mul](#)

Multiplies two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, ...

[dec/div](#)

Divides x by y and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/scale](#)

Scales a decimal. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[top](#)

[-](#)

```
(- x)
(- x y)
(- x y & more)
```

If one number is supplied, returns the negation, else subtracts the numbers from x and returns the result.

```
(- 4)
=> -4
```

```
(- 8 3 -2 -1)
=> 8
```

```
(- 5I 2I)
=> 3I
```

```
(- 8 2.5)
=> 5.5
```

```
(- 8 1.5M)
=> 6.5M
```

SEE ALSO

[+](#)

Returns the sum of the numbers. (+) returns 0.

[*](#)

Returns the product of numbers. (*) returns 1

[/](#)

If no denominators are supplied, returns 1/numerator, else returns numerator divided by all of the denominators.

[dec/add](#)

Adds two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/sub](#)

Subtract y from x and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/mul](#)

Multiplies two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, ...

[dec/div](#)

Divides x by y and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/scale](#)

Scales a decimal. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[top](#)

`-<>`

`(-<> x & forms)`

Threads the x through the forms. Inserts x at position of the `<>` symbol of the first form, making a list of it if it is not a list already. If there are more forms, inserts the first form at position of the `<>` symbol in second form, etc.

```
(-<> 5
  (+ <> 3)
  (/ 2 <>)
  (- <> 1))
=> -1
```

SEE ALSO

[->](#)

Threads the x through the forms. Inserts x as the second item in the first form, making a list of it if it is not a list already.

[->>](#)

Threads the x through the forms. Inserts x as the last item in the first form, making a list of it if it is not a list already. If ...

[as->](#)

Binds name to expr, evaluates the first form in the lexical context of that binding, then binds name to that result, repeating for ...

[top](#)

`->`

`(-> x & forms)`

Threads the x through the forms. Inserts x as the second item in the first form, making a list of it if it is not a list already. If there are more forms, inserts the first form as the second item in second form, etc.

```
(-> 5 (+ 3) (/ 2) (- 1))
=> 3
```

```
(do
  (def person
    {:name "Peter Meier"
     :address {:street "Lindenstrasse 45"
               :city "Bern"
               :zip 3000}})

  (-> person :address :street))
=> "Lindenstrasse 45"
```

SEE ALSO

[->>](#)

Threads the x through the forms. Inserts x as the last item in the first form, making a list of it if it is not a list already. If ...

[-<>](#)

Threads the x through the forms. Inserts x at position of the <> symbol of the first form, making a list of it if it is not a list already.

[as->](#)

Binds name to expr, evaluates the first form in the lexical context of that binding, then binds name to that result, repeating for ...

[top](#)

[->>](#)

(->> x & forms)

Threads the x through the forms. Inserts x as the last item in the first form, making a list of it if it is not a list already. If there are more forms, inserts the first form as the last item in second form, etc.

```
(->> 5 (+ 3) (/ 32) (- 1))
=> -3
```

```
(->> [ {:a 1 :b 2} {:a 3 :b 4} {:a 5 :b 6} {:a 7 :b 8} ]
     (map (fn [x] (get x :b)))
     (filter (fn [x] (> x 4)))
     (map inc)))
=> (7 9)
```

SEE ALSO

[->](#)

Threads the x through the forms. Inserts x as the second item in the first form, making a list of it if it is not a list already.

[-<>](#)

Threads the x through the forms. Inserts x at position of the <> symbol of the first form, making a list of it if it is not a list already.

[as->](#)

Binds name to expr, evaluates the first form in the lexical context of that binding, then binds name to that result, repeating for ...

[top](#)

•

```
(. classname :new args)
(. classname method-name args)
(. classname field-name)
```

```
(. classname :class)
(. object method-name args)
(. object field-name)
(. object :class)
```

Java interop. Calls a constructor or an class/object method or accesses a class/instance field. The function is sandboxed.

```
;; invoke constructor
(. :java.lang.Long :new 10)
=> 10

;; invoke static method
(. :java.time.ZonedDateTime :now)
=> 2024-08-27T22:13:12.015+02:00[Europe/Zurich]

;; invoke static method
(. :java.lang.Math :min 10 20)
=> 10

;; access static field
(. :java.lang.Math :PI)
=> 3.141592653589793

;; invoke method
(. (. :java.lang.Long :new 10) :toString)
=> "10"

;; get class name
(. :java.lang.Math :class)
=> class java.lang.Math

;; get class name
(. (. :java.io.File :new "/temp") :class)
=> class java.io.File
```

SEE ALSO

[import](#)

Imports one or multiple Java classes. Imports are bound to the current namespace.

[proxify](#)

Proxies a Java interface to be passed as a Callback object to Java functions. The interface's methods are implemented by Venice functions.

[java/as-runnable](#)

Wraps the function `f` in a `java.lang Runnable` (<https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html>)

[java/as-callable](#)

Wraps the function `f` in a `java.util.concurrent.Callable` (<https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html>)

[top](#)

```
::
```

```
(.: type-name args*)
```

Instantiates a custom type.

Note: Venice implicitly creates a builder function suffixed with a dot:

```
(deftype :complex [real :long, imaginary :long])
(complex. 200 300)
```

For readability prefer `(complex. 200 300)` over `(.: :complex 100 200)`.

```
(do
  (ns foo)
  (deftype :complex [real :long, imaginary :long])
  (def x (.: :complex 100 200))
  [(:real x) (:imaginary x)])
=> [100 200]
```

SEE ALSO

[deftype](#)

Defines a new custom record type for the name with the fields.

[deftype?](#)

Returns true if type is a custom type else false.

[deftype-of](#)

Defines a new custom wrapper type based on a base type.

[deftype-or](#)

Defines a new custom choice type.

[deftype-describe](#)

Describes a custom type.

[top](#)

/

```
(/ x)
(/ x y)
(/ x y & more)
```

If no denominators are supplied, returns 1/numerator, else returns numerator divided by all of the denominators.

```
(/ 2.0)
=> 0.5
```

```
(/ 12 2 3)
=> 2
```

```
(/ 12 3)
=> 4
```

```
(/ 12I 3I)
=> 4I
```

```
(/ 6.0 2)
=> 3.0
```

```
(/ 6 1.5M)
=> 4.0000000000000000M
```

SEE ALSO

[+](#)

Returns the sum of the numbers. (+) returns 0.

—

If one number is supplied, returns the negation, else subtracts the numbers from x and returns the result.

*

Returns the product of numbers. (*) returns 1

[dec/add](#)

Adds two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/sub](#)

Subtract y from x and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/mul](#)

Multiplies two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, ...

[dec/div](#)

Divides x by y and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/scale](#)

Scales a decimal. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[top](#)

<

```
(< x y)
(< x y & more)
```

Returns true if the numbers are in monotonically increasing order, otherwise false.

```
(< 2 3)
=> true
```

```
(< 2 3.0)
=> true
```

```
(< 2 3.0M)
=> true
```

```
(< 2 3 4 5 6 7)
=> true
```

```
(let [x 10]
  (< 0 x 100))
=> true
```

SEE ALSO

[<=](#)

Returns true if the numbers are in monotonically non-decreasing order, otherwise false.

[>](#)

Returns true if the numbers are in monotonically decreasing order, otherwise false.

[>=](#)

Returns true if the numbers are in monotonically non-increasing order, otherwise false.

<=

```
(<= x y)
(<= x y & more)
```

Returns true if the numbers are in monotonically non-decreasing order, otherwise false.

```
(<= 2 3)
=> true

(<= 3 3)
=> true

(<= 2 3.0)
=> true

(<= 2 3.0M)
=> true

(<= 2 3 4 5 6 7)
=> true

(let [x 10]
  (<= 0 x 100))
=> true
```

SEE ALSO

[<](#)

Returns true if the numbers are in monotonically increasing order, otherwise false.

[>](#)

Returns true if the numbers are in monotonically decreasing order, otherwise false.

[>=](#)

Returns true if the numbers are in monotonically non-increasing order, otherwise false.

=

```
(= x)
(= x y)
(= x y & more)
```

Returns true if both operands have equivalent type and value

```
(= "abc" "abc")
=> true

(= 0 0)
=> true
```

```
(= 0 1)
=> false

(= 0 0.0)
=> false

(= 0 0.0M)
=> false

(= "0" 0)
=> false

(= 4)
=> true

(= 4 4 4)
=> true
```

SEE ALSO

[==](#)

Returns true if both operands have equivalent value.

[not=](#)

Same as (not (= x y))

[top](#)

[==](#)

```
(== x)
(== x y)
(== x y & more)
```

Returns true if both operands have equivalent value.

Numbers of different types can be checked for value equality.

```
(== "abc" "abc")
=> true
```

```
(== 0 0)
=> true
```

```
(== 0 1)
=> false
```

```
(== 0 0.0)
=> true
```

```
(== 0 0.0M)
=> true
```

```
(== "0" 0)
=> false
```

```
(== 4)
=> true
```

```
(= 4I 4 4.0 4.0M 4N)  
=> true
```

SEE ALSO

[=](#)

Returns true if both operands have equivalent type and value

[not=](#)

Same as (not (= x y))

[top](#)

[>](#)

```
(> x y)  
(> x y & more)
```

Returns true if the numbers are in monotonically decreasing order, otherwise false.

```
(> 3 2)  
=> true
```

```
(> 3 3)  
=> false
```

```
(> 3.0 2)  
=> true
```

```
(> 3.0M 2)  
=> true
```

```
(> 7 6 5 4 3 2)  
=> true
```

SEE ALSO

[<](#)

Returns true if the numbers are in monotonically increasing order, otherwise false.

[<=](#)

Returns true if the numbers are in monotonically non-decreasing order, otherwise false.

[>=](#)

Returns true if the numbers are in monotonically non-increasing order, otherwise false.

[top](#)

[>=](#)

```
(>= x y)  
(>= x y & more)
```

Returns true if the numbers are in monotonically non-increasing order, otherwise false.


```
(>= 3 2)
=> true

(>= 3 3)
=> true

(>= 3.0 2)
=> true

(>= 3.0M 2)
=> true

(>= 7 6 5 4 3 2)
=> true
```

SEE ALSO

[<](#)

Returns true if the numbers are in monotonically increasing order, otherwise false.

[<=](#)

Returns true if the numbers are in monotonically non-decreasing order, otherwise false.

[>](#)

Returns true if the numbers are in monotonically decreasing order, otherwise false.

[top](#)

Object

Defines a protocol to customize the `toString` and/or the `compareTo` function of custom datatypes.

Definition:

```
(defprotocol Object
  (toString [this] (to-str false this))
  (compareTo [this other] (compare this other)))
```

`compareTo` returns a negative integer, zero, or a positive integer as *this* value is less than, equal to, or greater than the *other* value.

```
(do
  (deftype :point [x :long, y :long]
    Object
    (toString [this] (str/format "[%s %s]" (:x this) (:y this)))
    (compareTo [self other] (. (:x self) :compareTo (:x other))))

  ; custom `toString`
  (println "toString:" (point. 1 2))

  ; custom `compareTo`: sort by 'x' ascending
  (println "compareTo:"
    (sort [(point. 2 100) (point. 3 101) (point. 1 102)])))
toString: [1 2]
compareTo: [[1 102] [2 100] [3 101]]
=> nil
```

SEE ALSO

[defprotocol](#)

Defines a new protocol with the supplied function specs.

[deftype](#)

Defines a new custom record type for the name with the fields.

top

`[]`

Creates a vector.

```
[10 20 30]  
=> [10 20 30]
```

top

abs

`(abs x)`

Returns the absolute value of the number

```
(abs 10)  
=> 10
```

```
(abs -10)  
=> 10
```

```
(abs -10I)  
=> 10I
```

```
(abs -10.1)  
=> 10.1
```

```
(abs -10.12M)  
=> 10.12M
```

SEE ALSO

[sgn](#)
sgn function for a number.

[negate](#)
Negates x

top

accept-either

`(accept-either p p-other f)`

Returns a new promise that, when either this or the other given promise completeness normally, is executed with the corresponding result as argument to the supplied function f.

```
(-> (promise (fn [] (sleep 200) 200))  
    (accept-either (promise (fn [] (sleep 100) 100))
```

```
(deref)) (fn [v] (println (+ v 1))))
101
=> nil
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and set, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two ...

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[then-combine](#)

Applies a function `f` to the result of the previous stage of promise `p` and the result of another promise `p-other`

[then-compose](#)

Composes the result of two promises. `f` receives the result of the first promise `p` and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise `p` with the same result or exception at this stage, that executes the action `f`. Passes the current stage's result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

top

acopy

```
(acopy src src-pos dest dest-pos dest-len)
```

Copies an array from the `src` array, beginning at the specified position, to the specified position of the `dest` array. Returns the modified destination array

```
(acopy (long-array '(1 2 3 4 5)) 2 (long-array 20) 10 3)
=> [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 3, 4, 5, 0, 0, 0, 0, 0, 0, 0]
```

top

acquire

```
(acquire lock)
```

Acquires a lock, blocking until the lock is available.

```
(let [l (lock)]
  (acquire l)
  ;; do something)
```

```
(release l))  
=> nil
```

SEE ALSO

[lock](#)

Creates a new lock object.

[try-acquire](#)

Acquires a lock within the given timeout time. Without a timeout returns immediately if the lock is not available.

[release](#)

Releases a lock.

[locked?](#)

Returns true if the lock is in use else false.

[top](#)

add-tap

```
(add-tap f)
```

adds f, a fn of one argument, to the tap set. This function will be called with anything sent via `tap>`.

This function may (briefly) block, and will never impede calls to `tap>`, but blocking indefinitely may cause tap values to be dropped.

Remember f in order to `remove-tap`

```
(add-tap println)  
=> nil
```

SEE ALSO

[remove-tap](#)

Remove f from the tap set.

[clear-taps](#)

Removes all tap sets.

[tap>](#)

Sends x to any taps. Will not block. Returns true if there was room in the queue, false if not (x is dropped).

[top](#)

add-watch

```
(add-watch ref key fn)
```

Adds a watch function to an agent/atom reference. The watch fn must be a fn of 4 args: a key, the reference, its old-state, its new-state.

```
(do  
  (def x (agent 10))  
  (defn watcher [key ref old new]  
    (println "watcher: " key))  
  (add-watch x :test watcher))  
=> nil
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[top](#)

agent

(agent state & options)

Creates and returns an agent with an initial value of state and zero or more options.

Options:

:error-handler handler-fn
:error-mode mode-keyword
:validator validate-fn

The `handler-fn` is called if an action throws an exception. It's a function taking two args the agent and the exception. The mode-keyword may be either `:continue` (the default) or `:fail`. The `validate-fn` must be nil or a side-effect-free fn of one argument, which will be passed the intended new state on any state change. If the new state is unacceptable, the `validate-fn` should return false or throw an exception.

```
(do
  (def x (agent 100))
  (send x + 5)
  (sleep 100)
  (deref x))
=> 105
```

SEE ALSO

[send](#)

Dispatch an action to an agent. Returns the agent immediately.

[send-off](#)

Dispatch a potentially blocking action to an agent. Returns the agent immediately.

[await](#)

Blocks the current thread (indefinitely) until all actions dispatched thus far (from this thread or agent) to the agents have occurred.

[await-for](#)

Blocks the current thread until all actions dispatched thus far (from this thread or agent) to the agents have occurred, or the timeout ...

[deref](#)

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will ...

[set-error-handler!](#)

Sets the error-handler of an agent to handler-fn. If an action being run by the agent throws an exception handler-fn will be called ...

[agent-error](#)

Returns the exception thrown during an asynchronous action of the agent if the agent is failed. Returns nil if the agent is not failed.

[top](#)

agent-error

(agent-error agent)

Returns the exception thrown during an asynchronous action of the agent if the agent is failed. Returns `nil` if the agent is not failed.

```
(do
  (def x (agent 100 :error-mode :fail))
  (send x (fn [n] (/ n 0)))
  (sleep 500)
  (agent-error x))
=> com.github.jlangch.venice.VncException: / by zero
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[set-error-handler!](#)

Sets the error-handler of an agent to handler-fn. If an action being run by the agent throws an exception handler-fn will be called ...

[agent-error-mode](#)

Returns the agent's error mode

[top](#)

agent-send-off-thread-pool-info

```
(agent-send-off-thread-pool-info)
```

Returns the thread pool info of the ThreadPoolExecutor serving agent send-off.

<i>core-pool-size</i>	the number of threads to keep in the pool, even if they are idle
<i>maximum-pool-size</i>	the maximum allowed number of threads
<i>current-pool-size</i>	the current number of threads in the pool
<i>largest-pool-size</i>	the largest number of threads that have ever simultaneously been in the pool
<i>active-thread-count</i>	the approximate number of threads that are actively executing tasks
<i>scheduled-task-count</i>	the approximate total number of tasks that have ever been scheduled for execution
<i>completed-task-count</i>	the approximate total number of tasks that have completed execution

```
(agent-send-off-thread-pool-info)
```

```
=> {:core-pool-size 0 :maximum-pool-size 2147483647 :current-pool-size 2 :largest-pool-size 2 :active-thread-count 0 :scheduled-task-count 10 :completed-task-count 10}
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[send-off](#)

Dispatch a potentially blocking action to an agent. Returns the agent immediately.

[top](#)

agent-send-thread-pool-info

```
(agent-send-thread-pool-info)
```

Returns the thread pool info of the ThreadPoolExecutor serving agent send.

<i>core-pool-size</i>	the number of threads to keep in the pool, even if they are idle
<i>maximum-pool-size</i>	the maximum allowed number of threads

<i>current-pool-size</i>	the current number of threads in the pool
<i>largest-pool-size</i>	the largest number of threads that have ever simultaneously been in the pool
<i>active-thread-count</i>	the approximate number of threads that are actively executing tasks
<i>scheduled-task-count</i>	the approximate total number of tasks that have ever been scheduled for execution
<i>completed-task-count</i>	the approximate total number of tasks that have completed execution

([agent-send-thread-pool-info](#))

```
=> {:core-pool-size 10 :maximum-pool-size 10 :current-pool-size 9 :largest-pool-size 9 :active-thread-count 0 :
scheduled-task-count 9 :completed-task-count 9}
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[send](#)

Dispatch an action to an agent. Returns the agent immediately.

[top](#)

aget

([aget](#) array idx)

Returns the value at the index of an array of Java Objects

```
(aget (long-array '(1 2 3 4 5)) 1)
=> 2
```

[top](#)

alength

([alength](#) array)

Returns the length of an array

```
(alength (long-array '(1 2 3 4 5)))
=> 5
```

[top](#)

all-of

([all-of](#) p & ps)

Returns a new promise that is completed when all of the given promises complete. If any of the given promises complete exceptionally, then the returned promise also does so. Otherwise, the results, if any, of the given promises are not reflected in the returned promise, but may be obtained by inspecting them individually.

```
(-> (all-of (promise (fn [] (sleep 100) 1))
           (promise (fn [] (sleep 100) 2))
           (promise (fn [] (sleep 500) 3)))
    (deref))
=> nil
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[any-of](#)

Returns a new promise that is completed when any of the given promises complete, with the same result. Otherwise, if it completed exceptionally, ...

[top](#)

alter-ns-meta!

```
(alter-ns-meta! n f & args)
```

Alters the metadata for a namespace. `f` must be free of side-effects.

```
(do
  (ns foo)
  (alter-ns-meta! foo assoc :a 1))
=> {:a 1}

(do
  (ns foo)
  (def n 'foo)
  (alter-ns-meta! (var-get n) assoc :a 1)
  (pr-str (ns-meta (var-get n))))
=> "{:a 1}"
```

SEE ALSO

[ns-meta](#)

Returns the meta data of the namespace `n` or `nil` if `n` is not an existing namespace

[reset-ns-meta!](#)

Resets the metadata for a namespace

[ns](#)

Opens a namespace.

[top](#)

amap

```
(amap f arr)
```

Applies `f` to each item in the array `arr`. Returns a new array with the mapped values.

```
(str (amap (fn [x] (+ 1 x)) (long-array 6 0)))
=> "[1, 1, 1, 1, 1, 1]"
```


and

```
(and x)
(and x & next)
```

Ands the predicate forms

```
(and true true)
=> true
```

```
(and true false)
=> false
```

```
(and)
=> true
```

SEE ALSO

[or](#)

Ors the predicate forms

[not](#)

Returns true if x is logical false, false otherwise.

ansi/ansi

```
(ansi style)
```

Output an ANSI escape code using a style key.

If `*use-ansi*` is bound to false, outputs an empty string instead of an ANSI code.

```
(println (str (ansi/ansi :blue) "foo"))
```

```
(println (str (ansi/ansi :underline) "foo"))
```

```
(println (str (ansi/ansi (ansi/fg-color 33)) "foo"))
```

ansi/bg-color

```
(bg-color code)
(fg-color r g b)
```

Defines an extended background color from the 256-color extended color set. The code ranges from 0 to 255.

```
(ansi/bg-color 197)
```

SEE ALSO

[ansi/fg-color](#)

Defines an extended foreground color from the 256-color extended color set. The code ranges from 0 to 255.

[top](#)

ansi/fg-color

```
(fg-color code)
(fg-color r g b)
```

Defines an extended foreground color from the 256-color extended color set. The code ranges from 0 to 255.

The color range of a 256 color terminal consists of 4 parts in which case you actually get 258 colors:

- Color numbers 0 to 7 are the default terminal colors, the actual RGB value of which is not standardized and can often be configured.
- Color numbers 8 to 15 are the *bright* colors. Most of the time these are a lighter shade of the color with index - 8. They are also not standardized and can often be configured. Depending on terminal and shell, they are often used instead of or in conjunction with bold font faces.
- Color numbers 16 to 231 are RGB colors. These 216 colors are defined by 6 values on each of the three RGB axes. That is, instead of values 0 - 255, each color only ranges from 0 - 5.

The color number is then calculated like this

```
number = 16 + 36 * r + 6 * g + b
```

with `r` , `g` and `b` in the range 0 - 5.

- The color numbers 232 to 255 are grayscale with 24 shades of gray from dark to light.

```
(ansi/fg-color 197)
```

SEE ALSO

[ansi/bg-color](#)

Defines an extended background color from the 256-color extended color set. The code ranges from 0 to 255.

[top](#)

ansi/progress

```
(progress & options)
```

Returns a progress handler that renders the progress as a percentage string.

The returned progress handler takes two args:

- progress, a value 0..100 in :percent mode otherwise any value
- status , one of {start :progress :end :failed}

E.g: Download: 54%

Progress options:

:caption txt	A caption text. Defaults to empty.
:start-msg msg	A start message. Defaults to "{caption} started".
:end-msg msg	An end message. Defaults to "{caption} ok".
:end-col col	An end message ansi color code.

:failed-msg msg	A failed message. Defaults to "{caption} failed".
:failed-col col	A failed message ansi color code.
:mode m	A mode {;percent, :custom}. Defaults to :percent.

```
(let [pb (ansi/progress :caption "Test:")]
  (pb 0 :progress)
  (sleep 1 :seconds)
  (pb 50 :progress)
  (sleep 1 :seconds)
  (pb 100 :progress)
  (sleep 1 :seconds)
  (pb 100 :end))

(io/download "https://foo.org/image.png"
  :binary true
  :user-agent "Mozilla"
  :progress-fn (ansi/progress :caption "Download:"))
```

[top](#)

ansi/progress-bar

(progress-bar & options)

Returns a progress handler that renders a progress bar.

The returned progress handler takes two args:

- progress (0..100%)
- status {;start :progress :end :failed}

E.g:

- Download: [#####]
- Download: [#####] 70%

Progress bar options:

:caption txt	A caption text. Defaults to empty.
:width val	The width of the bar in chars. Defaults to 25.
:start-msg msg	A start message. Defaults to "{caption} started".
:end-msg msg	An end message. Defaults to "{caption} ok".
:end-col col	An end message ansi color code.
:failed-msg msg	A failed message. Defaults to "{caption} failed".
:failed-col col	A failed message ansi color code.
:show-percent bool	If true shows the percentage. Defaults to 'false'.

```
(let [pb (ansi/progress-bar
  :caption "Test:"
  :width 25
  :show-percent true)]
  (pb 0 :progress)
  (sleep 1 :seconds)
  (pb 50 :progress)
  (sleep 1 :seconds)
  (pb 100 :progress)
  (sleep 1 :seconds)
  (pb 100 :end))
```

```
(io/download "https://foo.org/image.png"
  :binary true
  :user-agent "Mozilla"
  :progress-fn (ansi/progress-bar
    :caption "Download:"
    :width 25
    :show-percent true))
```

[top](#)

ansi/style

```
(style text styles)
```

Applies ANSI color and style to a text string.

```
(println (ansi/style "foo" :green))

(println (ansi/style "foo" :green :underline))

(println (ansi/style "foo" :green :bg-yellow :underline))

(println (ansi/style "foo" (ansi/fg-color 21) (ansi/bg-color 221) :underline))

(println (ansi/style "foo" nil))
```

[top](#)

ansi/with-ansi

```
(with-ansi & forms)
```

Runs the given forms with the *use-ansi* variable temporarily bound to true, to enable the production of any ANSI color codes specified in the forms.

```
(ansi/with-ansi (println (ansi/style "foo" :green)))
```

[top](#)

ansi/without-ansi

```
(without-ansi & forms)
```

Runs the given forms with the *use-ansi* variable temporarily bound to false, to suppress the production of any ANSI color codes specified in the forms.

```
(ansi/without-ansi (println (ansi/style "foo" :green)))
```

[top](#)

ansi/without-cursor

(without-cursor & forms)

Runs the given forms with the cursor turned off.

[top](#)

any-of

(any-of p & ps)

Returns a new promise that is completed when any of the given promises complete, with the same result. Otherwise, if it completed exceptionally, the returned promise also does so.

```
(-> (any-of (promise (fn [] (sleep 300) 1))
           (promise (fn [] (sleep 100) 2))
           (promise (fn [] (sleep 500) 3)))
    (deref))
=> 2
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, ...

[all-of](#)

Returns a new promise that is completed when all of the given promises complete. If any of the given promises complete exceptionally, ...

[top](#)

any-pred

(any-pred p1 & p)

Takes a set of predicates and returns a function f that returns the first logical true value returned by one of its composing predicates against any of its arguments, else it returns logical false. Note that f is short-circuiting in that it will stop execution on the first argument that triggers a logical true result against the original predicates.

```
((any-pred number?) 1)
=> true

((any-pred number?) 1 "a")
=> true

((any-pred number? string?) 2 "a")
=> true
```

[top](#)

any?

```
(any? pred coll)
```

Returns true if the predicate is true for at least one collection item, false otherwise.

```
(any? number? nil)
=> false
```

```
(any? number? [])
=> false
```

```
(any? number? [1 :a :b])
=> true
```

```
(any? number? [1 2 3])
=> true
```

```
(any? #(== % 10) [10 20 30])
=> true
```

```
(any? #(>= % 10) [1 5 10])
=> true
```

SEE ALSO

[every?](#)

Returns true if coll is a collection and the predicate is true for all collection items, false otherwise.

[not-any?](#)

Returns false if the predicate is true for at least one collection item, true otherwise

[not-every?](#)

Returns true if coll is a collection and the predicate is not true for all collection items, false otherwise.

[top](#)

app/build

```
(app/build name main-file file-map dest-dir)
```

Creates a Venice application archive that can be distributed and executed as a single file.

The archive is stored as: {dest-dir}/{name}.zip

Returns a map with information on the created archive:

```
{ "file"    "{dest-dir}/{name}.zip",
  "name"    "{name}" }
```

Build example:

```
/staging
├─ billing.venice
├─ utils
│   ├── util.venice
│   └─ render.venice
└─ data
    ├── bill.template
    └─ logo.jpg
```

With these staged files the archive is built as:

```
(app/build
  "billing"
  "billing.venice"
  { "billing.venice"      "/staging/billing.venice"
    "utils/util.venice"   "/staging/utils/util.venice"
    "utils/render.venice" "/staging/utils/render.venice"
    "data/bill.template"  "/staging/data/bill.template"
    "data/logo.jpg"      "/staging/data/logo.jpg" }
  ".")
```

Loading Venice files works relative to the application. You can only load files that are in the app archive. If for instances "billing.venice" in the above example requires "utils/render.venice" just add `(load-file "utils/render.venice")` to "billing.venice".

The app can be run from the command line as:

```
> java -jar venice-1.12.31.jar -app billing.zip
```

Venice reads the archive and loads the archive's main file.

Or with additional Java libraries (all JARs in 'libs' dir):

```
> java -cp "libs/*" com.github.jlangch.venice.Launcher -app billing.zip
```

[top](#)

app/manifest

```
(app/manifest app)
```

Returns the manifest of a Venice application archive as a map.

[top](#)

apply

```
(apply f args* coll)
```

Applies f to all arguments composed of args and coll

```
(apply + [1 2 3])
=> 6
```

```
(apply + 1 2 [3 4 5])
=> 15
```

```
(apply str [1 2 3 4 5])
=> "12345"
```

```
(apply inc [1])
=> 2
```

[top](#)

apply-to-either

```
(apply-to-either p p-other f)
```

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result as argument to the supplied function f.

```
(-> (promise (fn [] (sleep 200) 200))
    (apply-to-either (promise (fn [] (sleep 100) 100))
                     (fn [v] (+ v 1))))
(deref))
=> 101
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function f with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function f with the two ...

[then-apply](#)

Applies a function f on the result of the previous stage of the promise p.

[then-combine](#)

Applies a function f to the result of the previous stage of promise p and the result of another promise p-other

[then-compose](#)

Composes the result of two promises. f receives the result of the first promise p and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise p with the same result or exception at this stage, that executes the action f. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

as->

```
(as-> expr name & forms)
```

Binds name to expr, evaluates the first form in the lexical context of that binding, then binds name to that result, repeating for each successive form, returning the result of the last form. This allows a value to thread into any argument position.

; allows to use arbitrary positioning of the argument

```
(as-> [:foo :bar] v
      (map name v)
      (first v)
      (str/subs v 1))
=> "oo"
```

; allows the use of if statements in the thread

```
(as-> {:a 1 :b 2} m
      (update m :a #(+ % 10))
      (if true
        (update m :b #(+ % 10))
```



```
m))  
=> {:a 11 :b 12}
```

SEE ALSO

->

Threads the x through the forms. Inserts x as the second item in the first form, making a list of it if it is not a list already.

->>

Threads the x through the forms. Inserts x as the last item in the first form, making a list of it if it is not a list already. If ...

-<>

Threads the x through the forms. Inserts x at position of the <> symbol of the first form, making a list of it if it is not a list already.

[top](#)

ascii-table/print

```
(ascii-table/print header data footer border padding)  
(ascii-table/print columns data border padding)
```

Renders and prints an ascii table.

Actually does:

```
(println (ascii-table/render ...))
```

```
(do  
  (load-module :ascii-table)  
  (ascii-table/print ["head 1" "head 2"]  
                    [["1 1" "1 2"] ["2 1" "2 2"]]  
                    ["foot 1" "foot 2"]  
                    :standard  
                    1))
```

```
+-----+-----+  
| head 1 | head 2 |  
+-----+-----+  
| 1 1    | 1 2    |  
+-----+-----+  
| 2 1    | 2 2    |  
+-----+-----+  
| foot 1 | foot 2 |  
+-----+-----+  
=> nil
```

SEE ALSO

[ascii-table/render](#)

Renders an ascii table.

[top](#)

ascii-table/render

```
(ascii-table/render header data footer border padding)  
(ascii-table/render columns data border padding)
```

Renders an ascii table.

Demo functions:

- `ascii-table/demo-styles`
- `ascii-table/demo-two-column-text`

```
(do
  (load-module :ascii-table)
  (println (ascii-table/render nil
                                [["1 1" "1 2"] ["2 1" "2 2"]]
                                nil
                                :standard
                                1)))
```

```
+-----+-----+
| 1 1 | 1 2 |
+-----+-----+
| 2 1 | 2 2 |
+-----+-----+
=> nil
```

```
(do
  (load-module :ascii-table)
  (println (ascii-table/render ["head 1" "head 2"]
                                [["1 1" "1 2"] ["2 1" "2 2"]]
                                ["foot 1" "foot 2"]
                                :standard
                                1)))
```

```
+-----+-----+
| head 1 | head 2 |
+-----+-----+
| 1 1    | 1 2    |
+-----+-----+
| 2 1    | 2 2    |
+-----+-----+
| foot 1 | foot 2 |
+-----+-----+
=> nil
```

```
(do
  (load-module :ascii-table)
  (println (ascii-table/render [{:width 6} {:width 6}]
                                [["1 1" "1 2"] ["2 1" "2 2"]]
                                :double
                                1)))
```

1 1	1 2
2 1	2 2

=> nil

```
(do
  (load-module :ascii-table)
  (println (ascii-table/render [{:header {:text "head 1"
                                           :align :left
                                           :overflow :newline }
                                :footer {:text "4"
                                           :align :left
                                           :overflow :newline}
                                :body {:align :left
                                       :overflow :newline}
                                :width 8}
                                {:header {:text "head 2"
                                           :align :left
                                           :overflow :newline }
                                :body {:align :left
                                       :overflow :newline}
                                :width 8}
                                1)))
```

```

      :align :right
      :overflow :newline}
:footer {:text "6"
      :align :right
      :overflow :newline}
:body   {:align :right
      :overflow :newline}
      :width 8}}
[["1" "2"] ["3" "4"]]
:double
1)))

```

head 1	head 2
1	2
3	4
4	6

=> nil

SEE ALSO

[ascii-table/print](#)

Renders and prints an ascii table.

top

aset

```
(aset array idx val)
```

Sets the value at the index of an array

```
(aset (long-array '(1 2 3 4 5)) 1 20)
=> [1, 20, 3, 4, 5]
```

top

assert

```
(assert expr)
(assert expr message)
```

Evaluates expr and throws an `:AssertionException` exception if it does not evaluate to logical true.

```
(assert (= 3 (+ 1 2)))
=> true
```

```
(assert (= 4 (+ 1 2)))
=> AssertionError: Assert failed.
Expression:
(= 4 (+ 1 2))
```

SEE ALSO

[assert-false](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical false.

[assert-eq](#)

Assert that expected and actual are equal. Throws an `:AssertionException` exception if they are not equal.

[assert-ne](#)

Assert that unexpected and actual are not equal. Throws an `:AssertionException` exception if they are equal.

[assert-throws](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not throw the expected exception of type `ex-type`.

[assert-does-not-throw](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does throw any kind of exception.

[test/deftest](#)

Defines a test function with no arguments.

[top](#)

assert-does-not-throw

```
(assert-does-not-throw expr)
(assert-does-not-throw expr message)
```

Evaluates `expr` and throws an `:AssertionException` exception if it does throw any kind of exception.

```
(assert-does-not-throw (/ 2 1))
=> true

(assert-does-not-throw (/ 2 0))
=> AssertionError: Assert failed.
Unexpected exception: :com.github.jlangch.venice.VncException
Expression:
(/ 2 0)
```

SEE ALSO

[assert](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical true.

[assert-false](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical false.

[assert-eq](#)

Assert that expected and actual are equal. Throws an `:AssertionException` exception if they are not equal.

[assert-ne](#)

Assert that unexpected and actual are not equal. Throws an `:AssertionException` exception if they are equal.

[assert-throws](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not throw the expected exception of type `ex-type`.

[test/deftest](#)

Defines a test function with no arguments.

[top](#)

assert-eq

```
(assert-eq expected actual)
(assert-eq expected actual message)
```

Assert that expected and actual are equal. Throws an `:AssertionException` exception if they are not equal.

```
(assert-eq 3 (+ 1 2))
=> true

(assert-eq 4 (+ 1 2))
=> AssertionError: Assert failed.
Expected: 4
Actual:   3
Expression:
(+ 1 2)
```

SEE ALSO

[assert](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical true.

[assert-false](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical false.

[assert-ne](#)

Assert that unexpected and actual are not equal. Throws an `:AssertionException` exception if they are equal.

[assert-throws](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not throw the expected exception of type `ex-type`.

[assert-does-not-throw](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does throw any kind of exception.

[test/deftest](#)

Defines a test function with no arguments.

[top](#)

assert-false

```
(assert-false expr)
(assert-false expr message)
```

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical false.

```
(assert-false (= 3 (+ 1 3)))
=> true

(assert-false (= 4 (+ 1 3)))
=> AssertionError: Assert failed.
Expression:
(= 4 (+ 1 3))
```

SEE ALSO

[assert](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical true.

[assert-eq](#)

Assert that expected and actual are equal. Throws an `:AssertionException` exception if they are not equal.

[assert-ne](#)

Assert that unexpected and actual are not equal. Throws an `:AssertionException` exception if they are equal.

[assert-throws](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not throw the expected exception of type `ex-type`.

[assert-does-not-throw](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does throw any kind of exception.

[test/deftest](#)

Defines a test function with no arguments.

[top](#)

assert-ne

```
(assert-ne unexpected actual)
(assert-ne unexpected actual message)
```

Assert that unexpected and actual are not equal. Throws an `:AssertionException` exception if they are equal.

```
(assert-ne :foo :bar)
=> true

(assert-ne :foo :foo)
=> AssertionError: Assert failed.
Unexpected: :foo
Actual:    :foo
Expression:
:foo
```

SEE ALSO

[assert](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical true.

[assert-false](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not evaluate to logical false.

[assert-eq](#)

Assert that expected and actual are equal. Throws an `:AssertionException` exception if they are not equal.

[assert-throws](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does not throw the expected exception of type `ex-type`.

[assert-does-not-throw](#)

Evaluates `expr` and throws an `:AssertionException` exception if it does throw any kind of exception.

[test/deftest](#)

Defines a test function with no arguments.

[top](#)

assert-throws

```
(assert-throws ex-type expr)
(assert-throws ex-type expr message)
```

Evaluates `expr` and throws an `:AssertionException` exception if it does not throw the expected exception of type `ex-type`.

```
(assert-throws :VncException (/ 2 0))
=> true

(assert-throws :VncException (/ 2 1))
=> AssertionError: Assert failed.
Expected: :VncException
But no exception has been thrown!
Expression:
(/ 2 1)
```

SEE ALSO

[assert](#)

Evaluates expr and throws an :AssertionException exception if it does not evaluate to logical true.

[assert-false](#)

Evaluates expr and throws an :AssertionException exception if it does not evaluate to logical false.

[assert-eq](#)

Assert that expected and actual are equal. Throws an :AssertionException exception if they are not equal.

[assert-ne](#)

Assert that unexpected and actual are not equal. Throws an :AssertionException exception if they are equal.

[assert-does-not-throw](#)

Evaluates expr and throws an :AssertionException exception if it does throw any kind of exception.

[test/deftest](#)

Defines a test function with no arguments.

[top](#)

assert-throws-with-msg

```
(assert-throws-with-msg ex-type ex-msg-regex expr)
(assert-throws-with-msg ex-type ex-msg-regex expr message)
```

Evaluates expr and throws an `:AssertionException` exception if it does not throw the expected exception of type ex-type.

```
(assert-throws-with-msg :VncException #" / by zero" (/ 2 0))
=> true
```

SEE ALSO

[assert](#)

Evaluates expr and throws an :AssertionException exception if it does not evaluate to logical true.

[assert-false](#)

Evaluates expr and throws an :AssertionException exception if it does not evaluate to logical false.

[assert-eq](#)

Assert that expected and actual are equal. Throws an :AssertionException exception if they are not equal.

[assert-ne](#)

Assert that unexpected and actual are not equal. Throws an :AssertionException exception if they are equal.

[assert-does-not-throw](#)

Evaluates expr and throws an :AssertionException exception if it does throw any kind of exception.

[test/deftest](#)

Defines a test function with no arguments.

[top](#)

assoc

```
(assoc coll key val)
(assoc coll key val & kvs)
```

When applied to a map, returns a new map of the same type, that contains the mapping of key(s) to val(s). When applied to a vector, returns a new vector that contains val at index. Note - index must be <= (count vector). When applied to a custom type, returns a new custom type with passed fields changed.

```
(assoc {} :a 1 :b 2)
=> {:a 1 :b 2}

(assoc nil :a 1 :b 2)
=> {:a 1 :b 2}

(assoc [1 2 3] 0 10)
=> [10 2 3]

(assoc [1 2 3] 3 10)
=> [1 2 3 10]

(assoc [1 2 3] 6 10)
=> [1 2 3 10]

(do
  (deftype :complex [real :long, imaginary :long])
  (def x (complex. 100 200))
  (def y (assoc x :real 110))
  (pr-str y))
=> "{:custom-type* :user/complex :real 110 :imaginary 200}"
```

SEE ALSO

[dissoc](#)

Returns a new coll of the same type, that does not contain a mapping for key(s)

[update](#)

Updates a value in an associative structure, where k is a key and f is a function that will take the old value and any supplied fargs ...

[top](#)

assoc!

```
(assoc! coll key val)
(assoc! coll key val & kvs)
```

Associates key/vals with a mutable map, returns the map

```
(assoc! nil :a 1 :b 2)
=> {:a 1 :b 2}

(assoc! (mutable-map) :a 1 :b 2)
=> {:a 1 :b 2}
```



```
(assoc! (mutable-vector 1 2 3) 0 10)
=> [10 2 3]
```

```
(assoc! (mutable-vector 1 2 3) 3 10)
=> [1 2 3 10]
```

```
(assoc! (mutable-vector 1 2 3) 6 10)
=> [1 2 3 10]
```

SEE ALSO

[dissoc!](#)

Dissociates keys from a mutable map, returns the map

[update!](#)

Updates a value in a mutable associative structure, where k is a key and f is a function that will take the old value and any supplied ...

[top](#)

assoc-in

```
(assoc-in m ks v)
```

Associates a value in a nested associative structure, where ks is a sequence of keys and v is the new value and returns a new nested structure. If any levels do not exist, hash-maps or vectors will be created.

```
(do
  (def users [ {:name "James" :age 26}
                {:name "John" :age 43}])
  (assoc-in users [1 :age] 44))
=> [{:name "James" :age 26} {:name "John" :age 44}]
```

```
(do
  (def users [ {:name "James" :age 26}
                {:name "John" :age 43}])
  (assoc-in users [2] {:name "Jack" :age 19}))
=> [{:name "James" :age 26} {:name "John" :age 43} {:name "Jack" :age 19}]
```

```
(assoc-in [[1 2] [3 4]] [0 0] 9)
=> [[9 2] [3 4]]
```

[top](#)

asub

```
(asub array start len)
```

Returns a sub array

```
(asub (long-array '(1 2 3 4 5)) 2 3)
=> [3, 4, 5]
```

[top](#)

atom

```
(atom x)
(atom x & options)
```

Creates an atom with the initial value x.

Options:

- :meta metadata-map
- :validator validate-fn

If metadata-map is supplied, it will become the metadata on the atom. validate-fn must be nil or a side-effect-free fn of one argument, which will be passed the intended new state on any state change. If the new state is unacceptable, the validate-fn should return false or throw an exception.

```
(do
  (def counter (atom 0))
  (swap! counter inc)
  (deref counter))
=> 1
```

```
(do
  (def counter (atom 0))
  (reset! counter 9)
  @counter)
=> 9
```

SEE ALSO

[deref](#)

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will ...

[reset!](#)

Sets the value of an atom or a volatile to newval without regard for the current value. Returns newval.

[swap!](#)

Atomically swaps the value of an atom or a volatile to be: (apply f current-value-of-box args). Note that f may be called multiple ...

[compare-and-set!](#)

Atomically sets the value of atom to newval if and only if the current value of the atom is identical to oldval. Returns true if set ...

[add-watch](#)

Adds a watch function to an agent/atom reference. The watch fn must be a fn of 4 args: a key, the reference, its old-state, its new-state.

[remove-watch](#)

Removes a watch function from an agent/atom reference.

[top](#)

atom?

```
(atom? x)
```

Returns true if x is an atom, otherwise false

```
(do
  (def counter (atom 0))
  (atom? counter))
=> true
```

await

```
(await agents)
```

Blocks the current thread (indefinitely) until all actions dispatched thus far (from this thread or agent) to the agents have occurred.

```
(do
  (def x1 (agent 100))
  (def x2 (agent {}))
  (send-off x1 + 5)
  (send-off x2 (fn [state]
                 (sleep 100)
                 (assoc state :done true))))
;; blocks till the agent actions are finished
(await x1 x2))
=> true
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[await-for](#)

Blocks the current thread until all actions dispatched thus far (from this thread or agent) to the agents have occurred, or the timeout ...

await-for

```
(await-for timeout-ms agents)
```

Blocks the current thread until all actions dispatched thus far (from this thread or agent) to the agents have occurred, or the timeout (in milliseconds) has elapsed. Returns logical false if returning due to timeout, logical true otherwise.

```
(do
  (def x1 (agent 100))
  (def x2 (agent {}))
  (send-off x1 + 5)
  (send-off x2 (fn [state]
                 (sleep 100)
                 (assoc state :done true))))
;; blocks till the agent actions are finished
(await-for 500 x1 x2))
=> true
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[await](#)

Blocks the current thread (indefinitely) until all actions dispatched thus far (from this thread or agent) to the agents have occurred.

await-termination-agents

(shutdown-agents)

Blocks until all actions have completed execution after a shutdown request, or the timeout occurs, or the current thread is interrupted, whichever happens first.

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (shutdown-agents)
  (await-termination-agents 1000))
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[top](#)

await-termination-agents?

(await-termination-agents?)

Returns true if all tasks have been completed following agent shut down

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (shutdown-agents)
  (await-termination-agents 1000)
  (sleep 300)
  (await-termination-agents?))
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[top](#)

bases

(bases class)

Returns the immediate superclass and interfaces of class, if any.

```
(bases :java.util.ArrayList)
=> (:java.util.AbstractList :java.util.List :java.util.RandomAccess :java.lang.Cloneable :java.io.Serializable)
```

[top](#)

benchmark/benchmark

```
(benchmark expr warmup-iterations iterations & options)
```

Benchmarks the given expression.

Note: All macros in the expression are expanded before running the benchmark phases.

Runs the benchmark in 4 phases:

1. Run the expression in a warm-up phase to allow the JIT compiler to do optimizations
2. Run the garbage collector to isolate timings from GC state prior to testing
3. Runs the expression benchmark
4. Analyzes and prints the benchmark statistics

Options:

:chart b If true generates a chart and saves it to 'benchmark.png'. Defaults to false.
:steps n the number of steps for the quantization, defaults to 100
:median b show the median value in the chart {true/false}, defaults to false
:outlier b show the outlier range in the chart {true/false}, defaults to false
:gc n the number of GC runs

```
(do
  (load-module :benchmark ['benchmark :as 'b])

  (b/benchmark (+ 1 2) 120000 10000)

  (b/benchmark (+ 1 2) 120000 10000 :chart true :median true)

  (b/benchmark (+ 1 2) 120000 10000 :chart true :outlier true)

  (b/benchmark (+ 1 2) 120000 10000 :chart true :steps 100))
```

[top](#)

bigint

```
(bigint x)
```

Converts to big integer.

```
(bigint 2000)
=> 2000N

(bbigint 34897.65)
=> 34897N

(bbigint 34897.65F)
=> 34897N

(bbigint "56760000000000")
=> 56760000000000N

(bbigint nil)
=> 0N
```

binding

```
(binding [bindings*] exprs*)
```

Evaluates the expressions and binds the values to dynamic (thread-local) symbols

```
(do
  (binding [x 100]
    (println x)
    (binding [x 200]
      (println x))
    (println x)))
100
200
100
=> nil

;; binding-introduced bindings are thread-locally mutable:
(binding [x 1]
  (set! x 2)
  x)
=> 2

;; binding can use qualified names :
(binding [user/x 1]
  user/x)
=> 1
```

SEE ALSO

[def-dynamic](#)

Creates a dynamic variable that starts off as a global variable and can be bound with 'binding' to a new value on the local thread.

[let](#)

Evaluates the expressions and binds the values to symbols in the new local context.

boolean

```
(boolean x)
```

Converts to boolean. Everything except 'false' and 'nil' is true in boolean context.

```
(boolean false)
=> false
```

```
(boolean true)
=> true
```

```
(boolean nil)
=> false
```

```
(boolean 100)
=> true
```

[top](#)

boolean?

```
(boolean? n)
```

Returns true if n is a boolean

```
(boolean? true)
=> true
```

```
(boolean? false)
=> true
```

```
(boolean? nil)
=> false
```

```
(boolean? 0)
=> false
```

[top](#)

bound?

```
(bound? s)
```

Returns true if the symbol is bound to a value else false

```
(bound? 'test)
=> false
```

```
(let [test 100]
  (bound? 'test))
=> true
```

```
(do
  (def a 100)
  (bound? 'a))
=> true
```

SEE ALSO

[let](#)

Evaluates the expressions and binds the values to symbols in the new local context.

[def](#)

Creates a global variable.

[defonce](#)

Creates a global variable that can not be overwritten

[top](#)

butlast

```
(butlast coll)
```

Returns a collection with all but the last list element

```
(butlast nil)  
=> nil
```

```
(butlast [])  
=> []
```

```
(butlast [1])  
=> []
```

```
(butlast [1 2 3])  
=> [1 2]
```

```
(butlast '())  
=> ()
```

```
(butlast '(1))  
=> ()
```

```
(butlast '(1 2 3))  
=> (1 2)
```

```
(butlast "1234")  
=> (#\1 #\2 #\3)
```

SEE ALSO

[str/butlast](#)

Returns a possibly empty string of the characters without the last.

[top](#)

byte-order

```
(byte-order)
```

Returns the CPU's byte order.

```
(byte-order)  
=> :big-endian
```

[top](#)

bytebuf

```
(bytebuf x)
```


Converts x to bytebuf. x can be a bytebuf, a list/vector of longs, a string

```
(bytebuf [0 1 2])  
=> [0 1 2]
```

```
(bytebuf '(0 1 2))  
=> [0 1 2]
```

```
(bytebuf "abc")  
=> [97 98 99]
```

SEE ALSO

[io/bytebuf-out-stream](#)

Returns a new java.io.ByteArrayOutputStream.

[top](#)

bytebuf-allocate

```
(bytebuf-allocate length)  
(bytebuf-allocate length init-val)
```

Allocates a new bytebuf. The values will be all zero or preset with init-val id init-val is supplied.

```
(bytebuf-allocate 20)  
=> [0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0]
```

```
(bytebuf-allocate 20 0x55)  
=> [20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20 20]
```

[top](#)

bytebuf-allocate-random

```
(bytebuf-allocate-random length)
```

Allocates a new bytebuf. The values will be all preset with randombytes

```
(bytebuf-allocate-random 20)  
=> [180 15 85 10 111 228 14 191 252 212 175 227 219 33 209 158 142 167 148 229]
```

[top](#)

bytebuf-byte-order

```
(bytebuf-byte-order buf endian)
```

Returns the bytebuf's byte order.

```
(bytebuf-byte-order (bytebuf-allocate 10))  
=> :big-endian
```

SEE ALSO

[bytebuf-byte-order!](#)
Sets the bytebuf's byte order.

[top](#)

bytebuf-byte-order!

```
(bytebuf-byte-order! buf endian)
```

Sets the bytebuf's byte order.

```
(-> (bytebuf-allocate 10)  
    (bytebuf-byte-order! :big-endian)  
    (bytebuf-byte-order))  
=> :big-endian  
  
(-> (bytebuf-allocate 10)  
    (bytebuf-byte-order! :little-endian)  
    (bytebuf-byte-order))  
=> :little-endian
```

SEE ALSO

[bytebuf-byte-order](#)
Returns the bytebuf's byte order.

[top](#)

bytebuf-capacity

```
(bytebuf-capacity buf)
```

Returns the capacity of a bytebuf.

```
(bytebuf-capacity (bytebuf-allocate 100))  
=> 100
```

SEE ALSO

[bytebuf-remaining](#)
Returns the number of bytes between the current position and the limit.

[bytebuf-limit](#)
Returns the limit of a bytebuf.

[bytebuf-pos](#)
Returns the buffer's current position.

[bytebuf-ensure-free-capacity!](#)
Ensure that the bytebuf has a free capacity. Returns the widened bytebuf.

[bytebuf-limit!](#)

Set a new limit for the buffer. The new limit must not be larger than the capacity.

bytebuf-ensure-free-capacity!

```
(bytebuf-ensure-capacity! buf capacity)
```

Ensure that the bytearray has a free capacity. Returns the widened bytearray.

[illegible]

SEE ALSO

bytebuf-remaining
Returns the number of bytes between the current position and the limit

Returns the number of bytes between the current position and the limit.

bytebuf-capacity

Returns the capacity of a bytearray.

bytebuf-limit

Returns the limit of a bytearray.

bytebuf-pos

Returns the buffer's current position.

bytebuf-limit!

Set a new limit for the buffer. The new limit must not be larger than the capacity.

bytebuf-from-string

```
(bytebuf-from-string s)
```

```
(bytebuf-from-string s encoding)
(bytebuf-from-string s encoding buf length fillbyte)
```

```
(bytebuf-from-string s encoding buf-length fillbyte)
```

Converts a string to a bytearray using an optional encoding. The encoding defaults to :UTF-8

```
(bytebuf-from-string "abcdef")  
=> [97 98 99 100 101 102]
```

```
(bytebuf-from-string "abcdef" :UTF-8)
=> [97 98 99 100 101 102]
```

```
(bytebuf-from-string "abcdef" :UTF-8 16 0x00)
=> [97 98 99 100 101 102 0 0 0 0 0 0 0 0 0 0]
```

SEE ALSO

Converts a bytearray to a string using an optional encoding. The encoding defaults to :UTF-8

bytebuf-get-byte

```
(bytebuf-get-byte buf)
(bytebuf-get-byte buf pos)
```

Reads a byte from the buffer. Without a pos reads from the current position and increments the position by one. With a position reads the byte from that position.

```
(-> (bytebuf-allocate 4)
    (bytebuf-put-byte! 1)
    (bytebuf-put-byte! 2)
    (bytebuf-get-byte 0))
=> 1I
```

[top](#)

bytebuf-get-double

```
(bytebuf-get-double buf)
(bytebuf-get-double buf pos)
```

Reads a double from the buffer. Without a pos reads from the current position and increments the position by eight. With a position reads the double from that position.

```
(-> (bytebuf-allocate 16)
    (bytebuf-put-double! 20.0)
    (bytebuf-put-double! 40.0)
    (bytebuf-get-double 0))
=> 20.0
```

[top](#)

bytebuf-get-float

```
(bytebuf-get-float buf)
(bytebuf-get-float buf pos)
```

Reads a float from the buffer. Without a pos reads from the current position and increments the position by four. With a position reads the float from that position.

```
(-> (bytebuf-allocate 16)
    (bytebuf-put-float! 20.0)
    (bytebuf-put-float! 40.0)
    (bytebuf-get-float 0))
=> 20.0
```

[top](#)

bytebuf-get-int

```
(bytebuf-get-int buf)
```

```
(bytebuf-get-int buf pos)
```

Reads an integer from the buffer. Without a pos reads from the current position and increments the position by four. With a position reads the integer from that position.

```
(-> (bytebuf-allocate 8)
    (bytebuf-put-int! 1I)
    (bytebuf-put-int! 2I)
    (bytebuf-get-int 0))
=> 1I
```

[top](#)

bytebuf-get-long

```
(bytebuf-get-long buf)
(bytebuf-get-long buf pos)
```

Reads a long from the buffer. Without a pos reads from the current position and increments the position by eight. With a position reads the long from that position.

```
(-> (bytebuf-allocate 16)
    (bytebuf-put-long! 20)
    (bytebuf-put-long! 40)
    (bytebuf-get-long 0))
=> 20
```

[top](#)

bytebuf-index-of

```
(bytebuf-index-of buf pattern)
(bytebuf-index-of buf pattern from-index)
(bytebuf-index-of buf pattern from-index to-index)
```

Returns the index within a byte buf of the first occurrence of the specified byte pattern.

The search is based on the Knuth-Morris-Pratt (KMP) pattern matching algorithm.

The KMP algorithm is an efficient method for finding the occurrence of a substring (a pattern) within a larger string (or in this case, a sequence of bytes)

```
(bytebuf-index-of (bytebuf [1 2 3 4 5]) (bytebuf [3 4]))
=> 2
```

```
(bytebuf-index-of (bytebuf [1 2 3 4 5 3 4]) (bytebuf [3 4]) 4)
=> 5
```

SEE ALSO

[bytebuf](#)

Converts x to bytebuf. x can be a bytebuf, a list/vector of longs, a string

[top](#)

bytebuf-limit

```
(bytebuf-limit buf)
```

Returns the limit of a bytebuf.

```
(bytebuf-limit (bytebuf-allocate 100))  
=> 100
```

SEE ALSO

[bytebuf-remaining](#)

Returns the number of bytes between the current position and the limit.

[bytebuf-capacity](#)

Returns the capacity of a bytebuf.

[bytebuf-pos](#)

Returns the buffer's current position.

[bytebuf-ensure-free-capacity!](#)

Ensure that the bytebuf has a free capacity. Returns the widened bytebuf.

[bytebuf-limit!](#)

Set a new limit for the buffer. The new limit must not be larger than the capacity.

[top](#)

bytebuf-limit!

```
(bytebuf-limit! buf new-limit)
```

Set a new limit for the buffer. The new limit must not be larger than the capacity.

Returns the new limit of a bytebuf.

```
(bytebuf-limit! (bytebuf-allocate 100) 50)  
=> 50
```

SEE ALSO

[bytebuf-remaining](#)

Returns the number of bytes between the current position and the limit.

[bytebuf-capacity](#)

Returns the capacity of a bytebuf.

[bytebuf-limit](#)

Returns the limit of a bytebuf.

[bytebuf-pos](#)

Returns the buffer's current position.

[bytebuf-ensure-free-capacity!](#)

Ensure that the bytebuf has a free capacity. Returns the widened bytebuf.

[top](#)

bytebuf-merge

```
(bytebuf-merge buffers)
```

Merges bytebufs.

```
(bytebuf-merge (bytebuf [1 2]) (bytebuf [3 4]))  
=> [1 2 3 4]
```

SEE ALSO

[bytebuf](#)

Converts x to bytebuf. x can be a bytebuf, a list/vector of longs, a string

[top](#)

bytebuf-pos

```
(bytebuf-pos buf)
```

Returns the buffer's current position.

```
(bytebuf-pos (bytebuf-allocate 10))  
=> 0
```

SEE ALSO

[bytebuf-capacity](#)

Returns the capacity of a bytebuf.

[bytebuf-remaining](#)

Returns the number of bytes between the current position and the limit.

[bytebuf-limit](#)

Returns the limit of a bytebuf.

[bytebuf-ensure-free-capacity!](#)

Ensure that the bytebuf has a free capacity. Returns the widened bytebuf.

[bytebuf-limit!](#)

Set a new limit for the buffer. The new limit must not be larger than the capacity.

[top](#)

bytebuf-pos!

```
(bytebuf-pos! buf pos)
```

Sets the buffer's position.

```
(-> (bytebuf-allocate 10)  
    (bytebuf-pos! 4)  
    (bytebuf-put-byte! 1)
```

```
(bytebuf-pos! 8)
(bytebuf-put-byte! 2))
=> [0 0 0 0 1 0 0 0 2 0]
```

[top](#)

bytebuf-put-buf!

```
(bytebuf-put-buf! dst src src-offset length)
```

This method transfers bytes from the src to the dst buffer at the current position, and then increments the position by length.

```
(> (bytebuf-allocate 10)
  (bytebuf-pos! 4)
  (bytebuf-put-buf! (bytebuf [1 2 3]) 0 2))
=> [0 0 0 0 1 2 0 0 0 0]
```

[top](#)

bytebuf-put-byte!

```
(bytebuf-put-byte! buf b)
```

Writes a byte to the buffer at the current position, and then increments the position by one.

```
(> (bytebuf-allocate 4)
  (bytebuf-put-byte! 1)
  (bytebuf-put-byte! 2I))
=> [1 2 0 0]
```

[top](#)

bytebuf-put-double!

```
(bytebuf-put-double! buf d)
```

Writes a double (8 bytes) to buffer at the current position, and then increments the position by eight.

```
(> (bytebuf-allocate 16)
  (bytebuf-put-double! 64.0)
  (bytebuf-put-double! 200.0))
=> [64 80 0 0 0 0 0 0 64 105 0 0 0 0 0 0]
```

[top](#)

bytebuf-put-float!

```
(bytebuf-put-float! buf d)
```

Writes a float (4 bytes) to buffer at the current position, and then increments the position by four.


```
(-> (bytebuf-allocate 8)
    (bytebuf-put-float! 64.0)
    (bytebuf-put-float! 200.0))
=> [66 128 0 0 67 72 0 0]
```

[top](#)

bytebuf-put-int!

```
(bytebuf-put-int! buf i)
```

Writes an integer (4 bytes) to buffer at the current position, and then increments the position by four.

```
(-> (bytebuf-allocate 8)
    (bytebuf-put-int! 4I)
    (bytebuf-put-int! 8I))
=> [0 0 0 4 0 0 0 8]
```

[top](#)

bytebuf-put-long!

```
(bytebuf-put-long! buf l)
```

Writes a long (8 bytes) to buffer at the current position, and then increments the position by eight.

```
(-> (bytebuf-allocate 16)
    (bytebuf-put-long! 4)
    (bytebuf-put-long! 8))
=> [0 0 0 0 0 0 0 4 0 0 0 0 0 0 0 8]
```

[top](#)

bytebuf-remaining

```
(bytebuf-remaining buf)
```

Returns the number of bytes between the current position and the limit.

```
(bytebuf-capacity (bytebuf-allocate 100))
=> 100
```

SEE ALSO

[bytebuf-capacity](#)

Returns the capacity of a bytebuf.

[bytebuf-limit](#)

Returns the limit of a bytebuf.

[bytebuf-pos](#)

Returns the buffer's current position.

[bytebuf-ensure-free-capacity!](#)

Ensure that the bytebuf has a free capacity. Returns the widened bytebuf.

[bytebuf-limit!](#)

Set a new limit for the buffer. The new limit must not be larger than the capacity.

[top](#)

bytebuf-sub

`(bytebuf-sub x start) (bytebuf-sub x start end)`

Returns a byte buffer of the items in buffer from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count bytebuffer)

```
(bytebuf-sub (bytebuf [1 2 3 4 5 6]) 2)
=> [3 4 5 6]
```

```
(bytebuf-sub (bytebuf [1 2 3 4 5 6]) 4)
=> [5 6]
```

[top](#)

bytebuf-to-list

`(bytebuf-to-list buf)`

Returns the bytebuf as lazy list of integers

```
(doall (bytebuf-to-list (bytebuf [97 98 99])))
=> (97I 98I 99I)
```

[top](#)

bytebuf-to-string

`(bytebuf-to-string buf)`
`(bytebuf-to-string buf encoding)`

Converts a bytebuf to a string using an optional encoding. The encoding defaults to :UTF-8

```
(bytebuf-to-string (bytebuf [97 98 99]) :UTF-8)
=> "abc"
```

SEE ALSO

[bytebuf-from-string](#)

Converts a string to a bytebuf using an optional encoding. The encoding defaults to :UTF-8

[top](#)

bytebuf?

```
(bytebuf? x)
```

Returns true if x is a bytebuf

```
(bytebuf? (bytebuf [1 2]))  
=> true
```

```
(bytebuf? [1 2])  
=> false
```

```
(bytebuf? nil)  
=> false
```

[top](#)

callstack

```
(callstack)
```

Returns the current callstack.

```
(do  
  (defn f1 [x] (f2 x))  
  (defn f2 [x] (f3 x))  
  (defn f3 [x] (f4 x))  
  (defn f4 [x] (callstack))  
  (f1 100))  
=> [{:fn-name "callstack" :file "example" :line 60 :col 18} {:fn-name "user/f4" :file "example" :line 59 :col 18}  
{:fn-name "user/f3" :file "example" :line 58 :col 18} {:fn-name "user/f2" :file "example" :line 57 :col 18}  
{:fn-name "user/f1" :file "example" :line 61 :col 5}]
```

[top](#)

cancel

```
(cancel f)
```

Cancels a future or a promise

```
(do  
  (def wait (fn [] (sleep 400) 100))  
  (let [f (future wait)]  
    (sleep 50)  
    (printf "After 50ms: cancelled=%b\n" (cancelled? f))  
    (cancel f)  
    (sleep 100)  
    (printf "After 150ms: cancelled=%b\n" (cancelled? f))))  
After 50ms: cancelled=false  
After 150ms: cancelled=true  
=> nil
```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[done?](#)

Returns true if the future or promise is done otherwise false

[cancelled?](#)

Returns true if the future or promise is cancelled otherwise false

[top](#)

cancelled?

```
(cancelled? f)
```

Returns true if the future or promise is cancelled otherwise false

```
(cancelled? (future (fn [] 100)))  
=> false
```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[done?](#)

Returns true if the future or promise is done otherwise false

[cancel](#)

Cancels a future or a promise

[top](#)

cargo-arangodb/db-dump

```
(cargo-arangodb/db-dump cname db-name db-user db-passwd dump-name log)
```

Dumps an ArangoDB database.

The DB dump is written to container's directory `"/var/lib/arangodb3/{dump-name}"`. If the directory does not exist it is created automatically.

Example:

```
(do  
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])  
  
  ;; (cargo-arangodb/exists-db-dump? "db-test" "dump-001")  
  ;; (cargo-arangodb/remove-db-dump "db-test" "dump-001")  
  
  ;; Dump the 'people' database to 'dump-001'  
  (ca/db-dump "db-test" "people" "root" "xxx" "dump-001" nil))
```

Args:

<code>cname</code>	The container name
<code>db-name</code>	The name of the DB to dump

db-user	The DB user
db-passwd	The DB password
dump-name	The dump name. e.g "dump-001"
log	A log function, may be <i>nil</i> . E.g: <code>(fn [s] (println "ArangoDB:" s))</code>

Dumps an ArangoDB database using this commands on the container:

```
mkdir /var/lib/arangodb3/dump-001

arangodump
  --output-directory /var/lib/arangodb3/dump-001
  --overwrite true
  --include-system-collections true
  --server.database "people"
  --server.endpoint tcp://127.0.0.1:8529
  --server.username "root"
  --server.password "xxx"
```

Open an interactive docker shell to check the dump:

```
docker exec -it {container-id} sh
```

ZIP a dump

```
docker exec -it {container-id}
  zip -r
    /var/lib/arangodb3/dump-001.zip
    /var/lib/arangodb3/dump-001
```

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])

  (ca/db-dump "db-test" "people" "root" "xxx" "dump-001" nil))
```

SEE ALSO

[cargo-arangodb/db-restore](#)

Restores an ArangoDB database from a dump

[cargo-arangodb/exists-db-dump?](#)

Returns true if the dump with the given name exists otherwise false.

[cargo-arangodb/remove-db-dump](#)

Removes an existing DB dump.

[cargo-arangodb/download-db-dump](#)

Downloads an existing the DB dump 'dump-name' from the container to the local filesystem. The export directory in the local filesystem ...

[cargo-arangodb/upload-db-dump](#)

Uploads an existing DB dump with the name 'dump-name' from the local filesystem to the container. The import directory on local filesystem ...

[top](#)

cargo-arangodb/db-restore

```
(cargo-arangodb/db-restore cname db-name db-user db-passwd dump-name log)
```

Restores an ArangoDB database from a dump

The DB dump is read from container's directory `"/var/lib/arangodb3/{dump-name}"`.

Example:

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])

  ;; (cargo-arangodb/exists-db-dump? "db-test" "dump-001")
  ;; (cargo-arangodb/remove-db-dump "db-test" "dump-001")

  ;; Restore the 'people' database from 'dump-001'
  (ca/db-restore "db-test" "people" "root" "xxx" "dump-001" nil))
```

Args:

cname	The container name
db-name	The name of the DB to dump
db-user	The DB user
db-passwd	The DB password
dump-name	The dump name. e.g "dump-001"
log	A log function, may be <i>nil</i> . E.g: <code>(fn [s] (println "ArangoDB:" s))</code>

Restores an ArangoDB database using this command on the container:

```
arangorestore
--input-directory /var/lib/arangodb3/dump-001
--force-same-database
--create-database true
--include-system-collections true
--server.database "people"
--server.endpoint tcp://127.0.0.1:8529
--server.username "root"
--server.password "xxx"
```

Open an interactive docker shell to check the dump:

```
docker exec -it {container-id} sh
```

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])
  (ca/db-restore "db-test" "people" "root" "xxx" "dump-001" nil))
```

SEE ALSO

[cargo-arangodb/db-dump](#)

Dumps an ArangoDB database.

[cargo-arangodb/exists-db-dump?](#)

Returns true if the dump with the given name exists otherwise false.

[cargo-arangodb/remove-db-dump](#)

Removes an existing DB dump.

[cargo-arangodb/download-db-dump](#)

Downloads an existing the DB dump 'dump-name' from the container to the local filesystem. The export directory in the local filesystem ...

[cargo-arangodb/upload-db-dump](#)

Uploads an existing DB dump with the name 'dump-name' from the local filesystem to the container. The import directory on local filesystem ...

[top](#)

cargo-arangodb/download-db-dump

```
(cargo-arangodb/download-db-dump cname dump-name export-dir log)
```

Downloads an existing the DB dump 'dump-name' from the container to the local filesystem. The export directory in the local filesystem must be an existing directory.

Args:

cname	The container name
dump-name	The dump name
export-dir	The export dir. E.g.: <code>(io/file (io/user-home-dir) "dump")</code>
log	A log function, may be <i>nil</i> . E.g.: <code>(fn [s] (println "ArangoDB:" s))</code>

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])

  ;; create a DB dump
  (ca/db-dump "db-test" "people" "root" "xxx" "dump-001" nil)

  ;; downloads the DB dump to the local filesystem
  (let [dir (io/user-home-dir)]
    (ca/download-db-dump "db-test" "dump-001" dir nil)))
```

SEE ALSO

[cargo-arangodb/upload-db-dump](#)

Uploads an existing DB dump with the name 'dump-name' from the local filesystem to the container. The import directory on local filesystem ...

[cargo-arangodb/db-dump](#)

Dumps an ArangoDB database.

[cargo-arangodb/db-restore](#)

Restores an ArangoDB database from a dump

[cargo-arangodb/exists-db-dump?](#)

Returns true if the dump with the given name exists otherwise false.

top

cargo-arangodb/exists-db-dump?

```
(cargo-arangodb/exists-db-dump? cname dump-name)
```

Returns true if the dump with the given name exists otherwise false.

Args:

cname	The container name
dump-name	The dump name

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])
  (ca/exists-db-dump? "db-test" "dump-001"))
```

SEE ALSO

[cargo-arangodb/db-dump](#)

Dumps an ArangoDB database.

[cargo-arangodb/db-restore](#)

Restores an ArangoDB database from a dump

[cargo-arangodb/remove-db-dump](#)

Removes an existing DB dump.

top

cargo-arangodb/list-db-dumps

```
(cargo-arangodb/list-db-dumps cname)
```

List the created DB dumps.

Args:

cname The container name

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])
  (ca/list-db-dumps "db-test"))
```

SEE ALSO

[cargo-arangodb/db-dump](#)

Dumps an ArangoDB database.

[cargo-arangodb/db-restore](#)

Restores an ArangoDB database from a dump

[cargo-arangodb/exists-db-dump?](#)

Returns true if the dump with the given name exists otherwise false.

[top](#)

cargo-arangodb/logs

```
(cargo-arangodb/logs cname)
(cargo-arangodb/logs cname lines)
```

Prints the ArangoDB docker container logs

Args:

cname A unique container name

lines The number of tail lines

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])
  (ca/logs "db-test"))

(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])
  (ca/logs "db-test" 100))
```

SEE ALSO

[cargo-arangodb/start](#)

Starts an ArangoDB container.

[cargo-arangodb/running?](#)

Returns true if a container with the specified name is running.

[top](#)

cargo-arangodb/remove-db-dump

```
(cargo-arangodb/remove-db-dump cname dump-name)
```

Removes an existing DB dump.

Args:

cname The container name

dump-name The dump name

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])
  (ca/remove-db-dump "db-test" "dump-001"))
```

SEE ALSO

[cargo-arangodb/db-dump](#)

Dumps an ArangoDB database.

[cargo-arangodb/db-restore](#)

Restores an ArangoDB database from a dump

[cargo-arangodb/exists-db-dump?](#)

Returns true if the dump with the given name exists otherwise false.

[top](#)

cargo-arangodb/running?

```
(cargo-arangodb/running? cname)
```

Returns true if a container with the specified name is running.

Args:

cname A unique container name

```
;; Test if ArangoDB container is running
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])
  (ca/running? "db-test"))
```

SEE ALSO

[cargo-arangodb/logs](#)

Prints the ArangoDB docker container logs

[cargo-arangodb/start](#)

Starts an ArangoDB container.

[cargo-arangodb/stop](#)

Stops an ArangoDB container

[top](#)

cargo-arangodb/start

```
(cargo-arangodb/start cname version mapped-port root-passwd memory cores log)
(cargo-arangodb/start cname version volumes mapped-port root-passwd memory cores log)
```

Starts an ArangoDB container.

Start rules:

- If a container with another version exists for the container name remove the container and the image
- Pull the image if not yet locally available
- If the container already runs - use it
- If the container is available but does not run - start it `(docker/start ...)`
- If the container is not available - run it `(docker/run ...)`
- Finally check for a successful startup. The container log must contain the string *".is ready for business. Have fun."* on the last line.

Args:

cname	A unique container name
version	The ArangoDB version to use. E.g.: 3.11.4
mapped-port	The published (mapped) ArangoDB port on the host
root-passwd	The ArangoDB root password
memory	The detected memory ArangoDB is to use. E.g.: 8GB, 8000MB
cores	The detected number of cores ArangoDB is to use
log	A log function, may be <i>nil</i> . E.g: <code>(fn [s] (println "ArangoDB:" s))</code>

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])

  ;; Run an ArangoDB container labeled as "db-test"
  (ca/start "db-test" "3.11.4" 8500 "test" "8GB" 1 nil))
```

SEE ALSO

[cargo-arangodb/logs](#)

Prints the ArangoDB docker container logs

[cargo-arangodb/stop](#)

Stops an ArangoDB container

[cargo-arangodb/running?](#)

Returns true if a container with the specified name is running.

[top](#)

cargo-arangodb/stop

```
(cargo-arangodb/stop cname)
(cargo-arangodb/stop cname log)
```

Stops an ArangoDB container

Args:

cname	A unique container name
log	A log function, may be <i>nil</i> . E.g: <code>(fn [s] (println "ArangoDB:" s))</code>

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])
```

```
;; Stop the ArangoDB container labeled as "db-test"
(ca/stop "db-test" nil))
```

SEE ALSO

[cargo-arangodb/start](#)

Starts an ArangoDB container.

[cargo-arangodb/running?](#)

Returns true if a container with the specified name is running.

[top](#)

cargo-arangodb/upload-db-dump

```
(cargo-arangodb/upload-db-dump cname dump-name import-dir log)
```

Uploads an existing DB dump with the name 'dump-name' from the local filesystem to the container. The import directory on local filesystem must be an existing non empty directory.

Args:

cname	The container name
dump-name	The dump name
import-dir	The import dir. E.g.: <code>(io/file (io/user-home-dir) "dump")</code>
log	A log function, may be <i>nil</i> . E.g: <code>(fn [s] (println "ArangoDB:" s))</code>

```
(do
  (load-module :cargo-arangodb ['cargo-arangodb :as 'ca])

  ;; upload the dump to the container's filesystem
  (let [dir (io/file (io/user-home-dir) "dump-001")]
    (ca/upload-db-dump "db-test" "dump-001" dir nil))

  ;; restore the DB dump
  (ca/db-restore "db-test" "people" "root" "xxx" "dump-001" nil))
```

SEE ALSO

[cargo-arangodb/download-db-dump](#)

Downloads an existing DB dump 'dump-name' from the container to the local filesystem. The export directory in the local filesystem ...

[cargo-arangodb/db-dump](#)

Dumps an ArangoDB database.

[cargo-arangodb/db-restore](#)

Restores an ArangoDB database from a dump

[cargo-arangodb/exists-db-dump?](#)

Returns true if the dump with the given name exists otherwise false.

[top](#)

cargo-postgresql/logs

```
(cargo-postgresql/logs cname)
(cargo-postgresql/logs cname lines)
```

Prints the PostgreSQL docker container logs

Args:

cname A unique container name
lines The number of tail lines

```
(do
  (load-module :cargo-postgresql ['cargo-postgresql :as 'pg])
  (pg/logs "postgres"))

(do
  (load-module :cargo-postgresql ['cargo-postgresql :as 'pg])
  (pg/logs "postgres" 100))
```

SEE ALSO

[cargo-postgresql/start](#)

Starts a PostgreSQL container.

[cargo-postgresql/running?](#)

Returns true if a container with the specified name is running.

[top](#)

cargo-postgresql/running?

```
(cargo-postgresql/running? cname)
```

Returns true if a container with the specified name is running.

Args:

cname A unique container name

```
;; Test if PostgreSQL container is running
(do
  (load-module :cargo-postgresql ['cargo-postgresql :as 'pg])
  (pg/running? "postgres"))
```

SEE ALSO

[cargo-postgresql/logs](#)

Prints the PostgreSQL docker container logs

[cargo-postgresql/start](#)

Starts a PostgreSQL container.

[cargo-postgresql/stop](#)

Stops a PostgreSQL container

[top](#)

cargo-postgresql/start

```
(cargo-postgresql/start cname version storage-dir)
(cargo-postgresql/start cname version storage-dir user password)
(cargo-postgresql/start cname version storage-dir user password log)
```

```
(cargo-postgresql/start cname version mapped-port storage-dir user password log)
```

Starts a PostgreSQL container.

Start rules:

- If a container with another version exists for the container name remove the container and the image
- Pull the image if not yet locally available
- If the container already runs - use it
- If the container is available but does not run - start it `(docker/start ...)`
- If the container is not available - run it `(docker/run ...)`
- Finally check for a successful startup. The container error log must contain the string *"database system is ready to accept connections."* on the last few lines.

Args:

cname	A unique container name
version	The PostgreSQL version to use. E.g.: "16.2", "16"
mapped-port	The published (mapped) port on the host. Defaults to 5432
storage-dir	Directory where PostgreSQL persists all the data.
user	A user. Defaults to "postgres"
password	A password. Defaults to "postgres"
log	A log function, may be <i>nil</i> . E.g: <code>(fn [s] (println "PostgreSQL:" s))</code>

```
(do
  (load-module :cargo-postgresql ['cargo-postgresql :as 'pg])

  ;; Run a PostgreSQL container labeled as "postgres"
  (pg/start "postgres" "16.2" " ./postgres-storage"))
```

SEE ALSO

[cargo-postgresql/stop](#)

Stops a PostgreSQL container

[cargo-postgresql/running?](#)

Returns true if a container with the specified name is running.

[cargo-postgresql/logs](#)

Prints the PostgreSQL docker container logs

[top](#)

cargo-postgresql/stop

```
(cargo-postgresql/stop cname)
(cargo-postgresql/stop cname log)
```

Stops a PostgreSQL container

Args:

cname	A unique container name
-------	-------------------------

```
(do
  (load-module :cargo-postgresql ['cargo-postgresql :as 'pg])

  ;; Stop the PostgreSQL container labeled as "postgres"
  (pg/stop "postgres"))
```

SEE ALSO

[cargo-postgresql/start](#)

Starts a PostgreSQL container.

[cargo-postgresql/running?](#)

Returns true if a container with the specified name is running.

[top](#)

cargo-qdrant/logs

```
(cargo-qdrant/logs cname)
(cargo-qdrant/logs cname lines)
```

Prints the Qdrant docker container logs

Args:

cname A unique container name

lines The number of tail lines

```
(do
  (load-module :cargo-qdrant ['cargo-qdrant :as 'cq])
  (cq/logs "qdrant"))

(do
  (load-module :cargo-qdrant ['cargo-qdrant :as 'cq])
  (cq/logs "qdrant" 100))
```

SEE ALSO

[cargo-qdrant/start](#)

Starts a Qdrant container.

[cargo-qdrant/running?](#)

Returns true if a container with the specified name is running.

[top](#)

cargo-qdrant/running?

```
(cargo-qdrant/running? cname)
```

Returns true if a container with the specified name is running.

Args:

cname A unique container name

```
;; Test if Qdrant container is running
(do
  (load-module :cargo-qdrant ['cargo-qdrant :as 'cq])
  (cq/running? "qdrant"))
```

SEE ALSO

[cargo-qdrant/logs](#)

Prints the Qdrant docker container logs

[cargo-qdrant/start](#)

Starts a Qdrant container.

[cargo-qdrant/stop](#)

Stops a Qdrant container

[top](#)

cargo-qdrant/start

```
(cargo-qdrant/start cname version storage-dir)
```

```
(cargo-qdrant/start cname version storage-dir config-file log)
```

```
(cargo-qdrant/start cname version mapped-rest-port mapped-grpc-port storage-dir config-file log)
```

Starts a Qdrant container.

Qdrant is vector database often used for LLM embeddings.

Telemetry reporting is disabled by setting the env variable QDRANT__TELEMETRY_DISABLED to `true`.

Start rules:

- If a container with another version exists for the container name remove the container and the image
- Pull the image if not yet locally available
- If the container already runs - use it
- If the container is available but does not run - start it `(docker/start ...)`
- If the container is not available - run it `(docker/run ...)`
- Finally check for a successful startup. The container log must contain the string *"Qdrant HTTP listening on."* on the last line.

Args:

cname	A unique container name
version	The Qdrant version to use. E.g.: "1.8.3"
mapped-rest-port	The published (mapped) Qdrant REST port on the host. Defaults to 6333
mapped-grpc-port	The published (mapped) Qdrant GRPC port on the host. Defaults to 6334
storage-dir	Directory where Qdrant persists all the data.
config-file	An optional custom configuration yaml file
log	A log function, may be <i>nil</i> . E.g: <code>(fn [s] (println "Qdrant:" s))</code>

```
(do
  (load-module :cargo-qdrant ['cargo-qdrant :as 'cq])

  ;; Run a Qdrant container labeled as "qdrant"
  (cq/start "qdrant" "1.8.3" "./qdrant-storage"))
```

SEE ALSO

[cargo-qdrant/stop](#)

Stops a Qdrant container

[cargo-qdrant/running?](#)

Returns true if a container with the specified name is running.

[cargo-qdrant/logs](#)

Prints the Qdrant docker container logs

[top](#)

cargo-qdrant/stop

```
(cargo-qdrant/stop cname)
(cargo-qdrant/stop cname log)
```

Stops a Qdrant container

Args:

cname A unique container name

```
(do
  (load-module :cargo-qdrant ['cargo-qdrant :as 'cq])

  ;; Stop the Qdrant container labeled as "qdrant"
  (cq/stop "qdrant"))
```

SEE ALSO

[cargo-qdrant/start](#)

Starts a Qdrant container.

[cargo-qdrant/running?](#)

Returns true if a container with the specified name is running.

[top](#)

cargo/purge

```
(cargo/purge cname)
```

Removes a container and its image. The container must not be running.

Args:

cname A unique container name

```
;; Purge an ArangoDB container
(cargo/purge "arangodb-test")
```

SEE ALSO

[cargo/start](#)

Starts a container.

[cargo/stop](#)

Stops a container

[cargo/running?](#)

Returns true if a container with the specified name is running.

[top](#)

cargo/running?

```
(cargo/running? cname)
```


Returns true if a container with the specified name is running.

Args:

cname A unique container name

```
;; Test if ArangoDB container is running
(cargo/running? "arangodb-test")
```

SEE ALSO

[cargo/start](#)

Starts a container.

[cargo/stop](#)

Stops a container

[cargo/purge](#)

Removes a container and its image. The container must not be running.

[top](#)

cargo/start

```
(cargo/start cname repo version publish envs args ready? log)
(cargo/start cname repo version publish envs args ready? log wait-after-start-secs ready-check-max-secs)
```

Starts a container.

Start rules:

- If a container with the passed name exists or is running in another version, stop that container and remove it together with the image
- Pull the image if it is not yet locally available
- If the container runs with the requested version already - use it
- If the container is available but does not run - start it using `(docker/start ...)`
- If the container is not available - run it using `(docker/run ...)`
- Finally check for a successful startup using the supplied `ready?` function. E.g.: `ready?` may scan the container logs for a successful startup message.

Args:

cname	A unique container name
repo	The image repository
version	The image version
publish	Publish a container's ports to the host. To expose port 8080 inside the container to port 3000 outside the container, pass <code>["3000:8080"]</code>
envs	A vector of env variables
vols	A vector of volume mounts
args	A vector of arguments for the process run in the container
ready?	A function to decide if the container is ready (may be <i>nil</i>). The function takes the unique container name as its single argument. It returns true if the container is ready else false
log	A log function (may be <i>nil</i>). The function takes a single string argument
wait-after-start-secs	Wait n seconds after starting the container (may be <i>nil</i>)
ready-check-max-secs	Try max n seconds for ready check (defaults to 30s if <i>nil</i>)

```
;; Run an ArangoDB container
(cargo/start "arangodb-test")
```

```

"arangodb/arangodb"
"3.11.4"
["8500:8529"]
["ARANGO_ROOT_PASSWORD=test"
"ARANGODB_OVERRIDE_DETECTED_TOTAL_MEMORY=8GB"
"ARANGODB_OVERRIDE_DETECTED_NUMBER_OF_CORES=1"]
[]
["--server.endpoint tcp://0.0.0.0:8529"]
(fn [cname]
  (-> (docker/container-logs cname :tail 1)
    (str/trim)
    (match? #".*is ready for business. Have fun.*"))))
(fn [s] (println "ArangoDB:" s))
3
30)

```

SEE ALSO

[cargo/stop](#)

Stops a container

[cargo/running?](#)

Returns true if a container with the specified name is running.

[cargo/purge](#)

Removes a container and its image. The container must not be running.

top

cargo/stop

```
(cargo/stop cname log)
```

Stops a container

Args:

cname A unique container name

log A log function (may be *nil*). The function takes a single string argument

```

;; Stop an ArangoDB container
(cargo/stop "arangodb-test"
  (fn [s] (println "ArangoDB:" s)))

```

SEE ALSO

[cargo/start](#)

Starts a container.

[cargo/running?](#)

Returns true if a container with the specified name is running.

[cargo/purge](#)

Removes a container and its image. The container must not be running.

top

cartesian-product

```
(cartesian-product coll1 coll2 coll*)
```

Returns the cartesian product of two or more collections.

Removes all duplicates items in the collections before computing the cartesian product.

```
(cartesian-product [1 2 3] [1 2 3])
=> ((1 1) (1 2) (1 3) (2 1) (2 2) (2 3) (3 1) (3 2) (3 3))
```

```
(cartesian-product [0 1] [0 1] [0 1])
=> ((0 0 0) (0 0 1) (0 1 0) (0 1 1) (1 0 0) (1 0 1) (1 1 0) (1 1 1))
```

SEE ALSO

[combinations](#)

All the unique ways of taking n different elements from the items in the collection

[top](#)

case

```
(case expr & clauses)
```

Takes an expression and a set of clauses. Each clause takes the form of test-constant result-expr

```
(case (+ 1 9)
  10 :ten
  20 :twenty
  30 :thirty
  :dont-know)
=> :ten
```

SEE ALSO

[cond](#)

Takes a set of test/expr pairs. It evaluates each test one at a time. If a test returns logical true, cond evaluates and returns the ...

[condp](#)

Takes a binary predicate, an expression, and a set of clauses.

[top](#)

cast

```
(cast class object)
```

Casts a Java object to a specific type

Note: Casting a Java object will change the object's *formal type*. See the `formal-type` function for detailed information.

```
(do
  (import :java.awt.Point)
  (import :java.awt.geom.Point2D)

  ;; upcasting :java.awt.Point to :java.awt.geom.Point2D
  ;; Point2D does not define the translate method!
  (let [p1 (. :Point :new 1.0 1.0)
```

```

    p2 (cast :Point2D p1])
  (println "p1 ->" p1)
  (println "p2 ->" p2)
  (println "Formal type p1 ->" (formal-type p1))
  (println "Formal type p2 ->" (formal-type p2))
  (println "p1' ->" (doto p1 (. :translate 2.0 2.0)))
  ;; the translate method is not defined by Point2D
  ;; and will fail with a JavaMethodInvocationException!
  ;; (doto p2 (. :translate 2.0 2.0))
))
p1 -> java.awt.Point[x=1,y=1]
p2 -> java.awt.Point[x=1,y=1]
Formal type p1 -> :java.awt.Point
Formal type p2 -> :java.awt.geom.Point2D
p1' -> java.awt.Point[x=3,y=3]
=> nil

```

SEE ALSO

[formal-type](#)

Returns the formal type of a Java object.

[remove-formal-type](#)

Removes the formal type from a Java object.

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

top

ceil

```
(ceil x)
```

Returns the largest integer that is greater than or equal to x

```
(ceil 1.4)
=> 2.0
```

```
(ceil -1.4)
=> -1.0
```

```
(ceil 1.23M)
=> 2.00M
```

```
(ceil -1.23M)
=> -1.00M
```

SEE ALSO

[floor](#)

Returns the largest integer that is less than or equal to x

top

char

(char c)

Converts a number or s single char string to a char.

```
(char 65)
```

```
=> #\A
```

```
(char "A")
```

```
=> #\A
```

```
(long (char "A"))
```

```
=> 65
```

```
(str/join (map char [65 66 67 68]))
```

```
=> "ABCD"
```

```
(map #(- (long %) (long (char "0"))) (str/chars "123456"))
```

```
=> (1 2 3 4 5 6)
```

SEE ALSO

[char?](#)

Returns true if s is a char.

[top](#)

char-escaped

(char-escaped c)

Returns the ASCII escaped character for c.

- `\'` single quote
- `\"` double quote
- `\\` backslash
- `\n` new line
- `\r` carriage return
- `\t` tab
- `\b` backspace
- `\f` form feed
- `\0` null character
- in all other cases returns the character c

```
(char-escaped #\n)
```

```
=> #\newline
```

```
(char-escaped #\a)
```

```
=> #\a
```

SEE ALSO

[char](#)

Converts a number or s single char string to a char.

[char?](#)

Returns true if s is a char.

char-literals

(char-literals)

Returns all defined char literals.

Char Literal	Unicode	Char
#\space	\u0020	#\space
#\newline	\u000A	#\newline
#\tab	\u0009	#\tab
#\formfeed	\u000C	#\formfeed
#\return	\u000D	#\return
#\backspace	\u0008	#\backspace
#\lparen	\u0028	#\lparen
#\rparen	\u0029	#\rparen
#\quote	\u0022	#\quote
#\backslash	\u005C	#\backslash
#\pilcrow	\u00B6	#\pilcrow
#\middle-dot	\u00B7	#\middle-dot
#\right-guillemet	\u00BB	#\right-guillemet
#\left-guillemet	\u00AB	#\left-guillemet
#\copyright	\u00A9	#\copyright
#\bullet	\u2022	#\bullet
#\horz-ellipsis	\u2026	#\horz-ellipsis
#\per-mille-sign	\u2030	#\per-mille-sign
#\diameter-sign	\u2300	#\diameter-sign
#\check-mark	\u2713	#\check-mark
#\cross-mark	\u2717	#\cross-mark
#\pi	\u03C0	#\pi
#\nbsp	\u00A0	#\nbsp
#\en-space	\u2002	#\en-space
#\em-space	\u2003	#\em-space
#\three-per-em-space	\u2004	#\three-per-em-space
#\four-per-em-space	\u2005	#\four-per-em-space
#\six-per-em-space	\u2006	#\six-per-em-space

(char-literals)

SEE ALSO

[char](#)

Converts a number or s single char string to a char.

[char?](#)

Returns true if s is a char.

char?

```
(char? s)
```

Returns true if s is a char.

```
(char? #\a)  
=> true
```

SEE ALSO

[char](#)

Converts a number or s single char string to a char.

top

charset-default-encoding

```
(charset-default-encoding)
```

Returns the default charset of this Java virtual machine.

```
(charset-default-encoding)  
=> :UTF-8
```

top

chinook-postgresql/download-data

```
(download-data)
```

Download the Chinook dataset for PostgreSQL.

The data set is downloaded from [GitHub/lerocha](#)

The data set is published under the [License](#)

```
(do  
  (load-module :chinook-postgresql ['chinook-postgresql :as 'chinook])  
  (chinook/download-data))
```

SEE ALSO

[chinook-postgresql/show-data-model](#)

Opens a browser to show the Chinook data model (<https://github.com/lerocha/chinook-database/tree/master#data-model>)

[chinook-postgresql/load-data](#)

Load the Chinook dataset to a PostgreSQL database.

top

chinook-postgresql/load-data

```
(load-data)
```

Load the Chinook dataset to a PostgreSQL database.

The data set is loaded from [GitHub/lerocha](#)

[Data Model](#) published under the [License](#)

The Chinook sample database has 11 tables as follows:

employees	stores employee data such as id, last name, first name, etc. It also has a field named ReportsTo to specify who reports to whom
customers	stores customer data
invoices	stores invoice header data
invoice_items	stores the invoice line items data
artists	stores artist data. It is a simple table that contains the id and name
albums	stores data about a list of tracks. Each album belongs to one artist. However, one artist may have multiple albums
media_types	stores media types such as MPEG audio and AAC audio files
genres	stores music types such as rock, jazz, metal, etc.
tracks	stores the data of songs. Each track belongs to one album
playlists	stores data about playlists. Each playlist contains a list of tracks. Each track may belong to multiple playlists. The relationship between the playlists and tracks tables is many-to-many. The playlist_track table is used to reflect this relationship
playlist_track	reflect the many-to-many relationship between playlist and tracks

Start the PostgreSQL docker container:

```
(do
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (jdbp/start "postgres" "16.2" 5432 "./postgres-storage" "postgres" "postgres"))
```

Note: The storage directory (e.g. "./postgres-storage") must exist!

```
(do
  (load-module :chinook-postgresql ['chinook-postgresql :as 'chinook])
  (chinook/load-data "localhost" 5432 "postgres" "postgres"))

(do
  (load-module :chinook-postgresql ['chinook-postgresql :as 'chinook])
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost"
                                          5432
                                          chinook/database
                                          "postgres"
                                          "postgres")]
    (-> (jdbc/execute-query conn "SELECT * FROM album WHERE title LIKE '%Mozart%')
        (jdbc/print-query-result))))
```

SEE ALSO

[chinook-postgresql/show-data-model](#)

Opens a browser to show the Chinook data model (<https://github.com/lerocha/chinook-database/tree/master#data-model>)

[chinook-postgresql/download-data](#)

Download the Chinook dataset for PostgreSQL.

[top](#)

chinook-postgresql/show-data

(show-data)

Opens a browser to show the [Chinook data](#)

```
(do
  (load-module :chinook-postgresql ['chinook-postgresql :as 'chinook])
  (chinook/show-data))
```

SEE ALSO

[chinook-postgresql/show-data-model](#)

Opens a browser to show the Chinook data model (<https://github.com/lerocha/chinook-database/tree/master#data-model>)

[chinook-postgresql/download-data](#)

Download the Chinook dataset for PostgreSQL.

[chinook-postgresql/load-data](#)

Load the Chinook dataset to a PostgreSQL database.

top

chinook-postgresql/show-data-model

```
(show-data-model)
```

Opens a browser to show the [Chinook data model](#)

```
(do
  (load-module :chinook-postgresql ['chinook-postgresql :as 'chinook])
  (chinook/show-data-model))
```

SEE ALSO

[chinook-postgresql/show-data](#)

Opens a browser to show the Chinook data ([https://raw.githubusercontent.com/lerocha/chinook-database/master/ChinookDatabase/DataSources/Chin ...](https://raw.githubusercontent.com/lerocha/chinook-database/master/ChinookDatabase/DataSources/Chin...))

[chinook-postgresql/download-data](#)

Download the Chinook dataset for PostgreSQL.

[chinook-postgresql/load-data](#)

Load the Chinook dataset to a PostgreSQL database.

top

cidr/end-inet-addr

```
(cidr/end-inet-addr cidr)
```

Returns the end inet address of a CIDR IP block.

```
(cidr/end-inet-addr "222.192.0.0/11")
=> /222.223.255.255
```

```
(cidr/end-inet-addr "2001:0db8:85a3:08d3:1319:8a2e:0370:7347/64")
=> /2001:db8:85a3:8d3:ffff:ffff:ffff:ffff
```

```
(cidr/end-inet-addr (cidr/parse "222.192.0.0/11"))
=> /222.223.255.255
```

cidr/in-range?

```
(cidr/in-range? ip cidr)
```

Returns true if the ip adress is within the ip range of the cidr else false. ip may be a string or a :java.net.InetAddress, cidr may be a string or a CIDR Java object obtained from 'cidr/parse'.

```
(cidr/in-range? "222.220.0.0" "222.220.0.0/11")  
=> true
```

```
(cidr/in-range? (inet/inet-addr "222.220.0.0") "222.220.0.0/11")  
=> true
```

```
(cidr/in-range? "222.220.0.0" (cidr/parse "222.220.0.0/11"))  
=> true
```

cidr/insert

```
(cidr/insert trie cidr value)
```

Insert a new CIDR / value relation into trie. Works with IPv4 and IPv6. Please keep IPv4 and IPv6 CIDRs in different tries.

```
(do  
  (let [trie (cidr/trie)]  
    (cidr/insert trie  
                 (cidr/parse "192.16.10.0/24")  
                 "Germany")  
    (cidr/lookup trie "192.16.10.15")))  
=> "Germany"
```

cidr/lookup

```
(cidr/lookup trie ip)
```

Lookup the associated value of a CIDR in the trie. A cidr "192.16.10.0/24" or an inet address "192.16.10.15" can be passed as ip.

```
(do  
  (let [trie (cidr/trie)]  
    (cidr/insert trie  
                 (cidr/parse "192.16.10.0/24")  
                 "Germany")  
    (cidr/lookup trie "192.16.10.15")))  
=> "Germany"
```

cidr/lookup-reverse

```
(cidr/lookup-reverse trie ip)
```

Reverse lookup a CIDR in the trie given an IP address

```
(do
  (let [trie (cidr/trie)]
    (cidr/insert trie
      (cidr/parse "192.16.10.0/24")
      "Germany")
    (cidr/lookup-reverse trie "192.16.10.15")))
=> 192.16.10.0/24: [/192.16.10.0 .. /192.16.10.255]
```

[top](#)

cidr/parse

```
(cidr/parse cidr)
```

Parses CIDR IP blocks to an IP address range. Supports both IPv4 and IPv6.

```
(cidr/parse "222.192.0.0/11")
=> 222.192.0.0/11: [/222.192.0.0 .. /222.223.255.255]

(cidr/parse "2001:0db8:85a3:08d3:1319:8a2e:0370:7347/64")
=> 2001:0db8:85a3:08d3:1319:8a2e:0370:7347/64: [/2001:db8:85a3:8d3:0:0:0:0 .. /2001:db8:85a3:8d3:ffff:ffff:ffff:ffff]
```

[top](#)

cidr/size

```
(cidr/size trie)
```

Returns the size of the trie.

```
(do
  (let [trie (cidr/trie)]
    (cidr/insert trie
      (cidr/parse "192.16.10.0/24")
      "Germany")
    (cidr/size trie)))
=> 1
```

[top](#)

cidr/start-inet-addr

```
(cidr/start-inet-addr cidr)
```

Returns the start inet address of a CIDR IP block.

```
(cidr/start-inet-addr "222.192.0.0/11")  
=> /222.192.0.0
```

```
(cidr/start-inet-addr "2001:0db8:85a3:08d3:1319:8a2e:0370:7347/64")  
=> /2001:db8:85a3:8d3:0:0:0:0
```

```
(cidr/start-inet-addr (cidr/parse "222.192.0.0/11"))  
=> /222.192.0.0
```

[top](#)

cidr/trie

```
(cidr/trie)
```

Create a new mutable concurrent CIDR trie.

```
(do  
  (let [trie (cidr/trie)]  
    (cidr/insert trie  
                 (cidr/parse "192.16.10.0/24")  
                 "Germany")  
    (cidr/lookup trie "192.16.10.15")))  
=> "Germany"
```

[top](#)

clamp

```
(clamp x min max)
```

Restricts a given value between a lower and upper bound. In this way, it acts like a combination of the `min` and `max` functions.

```
(clamp 1 10 20)  
=> 10
```

```
(clamp 1I 10I 20I)  
=> 10I
```

```
(clamp 1.0 10.0 20.0)  
=> 10.0
```

SEE ALSO

[min](#)

Returns the smallest of the values

[max](#)

Returns the greatest of the values

[top](#)

class

(class name)

Returns the Java class for the given name. Throws an exception if the class is not found.

```
(class :java.util.ArrayList)
=> class java.util.ArrayList
```

SEE ALSO

[class-of](#)

Returns the Java class of a value.

[class-name](#)

Returns the Java class name of a class.

[class-version](#)

Returns the major version of a Java class.

[cast](#)

Casts a Java object to a specific type

[formal-type](#)

Returns the formal type of a Java object.

[remove-formal-type](#)

Removes the formal type from a Java object.

[top](#)

class-name

(class-name class)

Returns the Java class name of a class.

```
(class-name (class :java.util.ArrayList))
=> "java.util.ArrayList"
```

SEE ALSO

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[class-of](#)

Returns the Java class of a value.

[class-version](#)

Returns the major version of a Java class.

[top](#)

class-of

(class-of x)

Returns the Java class of a value.

```
(class-of 100)
=> class com.github.jlangch.venice.impl.types.VncLong

(class-of (. :java.awt.Point :new 10 10))
=> class java.awt.Point
```

SEE ALSO

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[class-name](#)

Returns the Java class name of a class.

[class-version](#)

Returns the major version of a Java class.

[top](#)

class-version

```
(class-version class)
```

Returns the major version of a Java class.

Java major versions:

- Java 8 uses major version 52
- Java 9 uses major version 53
- Java 10 uses major version 54
- Java 11 uses major version 55
- Java 12 uses major version 56
- Java 13 uses major version 57
- Java 14 uses major version 58
- Java 15 uses major version 59

```
(class-version :com.github.jlangch.venice.Venice)
=> 52
```

SEE ALSO

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[class-of](#)

Returns the Java class of a value.

[class-name](#)

Returns the Java class name of a class.

[top](#)

classloader

```
(classloader)
(classloader type)
```

Returns the classloader.

```
;; Returns the current classloader
(classloader)
=> class sun.misc.Launcher$AppClassLoader

;; Returns the system classloader
(classloader :system)
=> sun.misc.Launcher$AppClassLoader@4e0e2f2a

;; Returns the classloader which loaded the Venice classes
(classloader :application)
=> sun.misc.Launcher$AppClassLoader@4e0e2f2a

;; Returns the thread-context classloader
(classloader :thread-context)
=> sun.misc.Launcher$AppClassLoader@4e0e2f2a
```

SEE ALSO

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[classloader-of](#)

Returns the classloader of a value or a Java class.

[top](#)

classloader-of

(classloader-of x)

Returns the classloader of a value or a Java class.

Note:

Some Java VM implementations may use 'null' to represent the bootstrap class loader. This method will return 'nil' in such implementations if this class was loaded by the bootstrap class loader.

```
(classloader-of (class :java.awt.Point))
=> nil

(classloader-of (. :java.awt.Point :new 10 10))
=> nil

(classloader-of (class-of "abcdef"))
=> sun.misc.Launcher$AppClassLoader@4e0e2f2a

(classloader-of "abcdef")
=> sun.misc.Launcher$AppClassLoader@4e0e2f2a
```

SEE ALSO

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[classloader](#)

Returns the classloader.

clear-taps

```
(clear-taps)
```

Removes all tap sets.

```
(do
  (add-tap prn)
  (clear-taps))
=> nil
```

SEE ALSO

[remove-tap](#)

Remove f from the tap set.

[add-tap](#)

adds f, a fn of one argument, to the tap set. This function will be called with anything sent via tap>.

[tap>](#)

Sends x to any taps. Will not block. Returns true if there was room in the queue, false if not (x is dropped).

coalesce

```
(coalesce args*)
```

Returns nil if all of its arguments are nil, otherwise it returns the first non nil argument. The arguments are evaluated lazy.

```
(coalesce)
=> nil
```

```
(coalesce 2)
=> 2
```

```
(coalesce nil 1 2)
=> 1
```

coll?

```
(coll? coll)
```

Returns true if coll is a collection

```
(coll? {:a 1})
=> true
```



```
(coll? [1 2])  
=> true
```

[top](#)

combinations

```
(combinations coll n)
```

All the unique ways of taking n different elements from the items in the collection

```
(combinations [0 1 2 3] 1)  
=> ([0] [1] [2] [3])
```

```
(combinations [0 1 2 3] 2)  
=> ([0 1] [0 2] [0 3] [1 2] [1 3] [2 3])
```

```
(combinations [0 1 2 3] 3)  
=> ([0 1 2] [0 1 3] [1 2 3])
```

```
(combinations [0 1 2 3] 4)  
=> ([0 1 2 3])
```

SEE ALSO

[cartesian-product](#)

Returns the cartesian product of two or more collections.

[top](#)

comment

```
(comment & body)
```

Ignores body, yields nil

```
(comment  
  (println 1)  
  (println 5))  
=> nil
```

[top](#)

comp

```
(comp f*)
```

Takes a set of functions and returns a function that is the composition of those functions. The returned function takes a variable number of args, applies the rightmost of the functions to the args, applies the next function (right-to-left) to the result, etc.

Functions composition builds complex functions by combining simpler ones. Functions are composed by passing the output of one function as the input to another.

```
h(x) = (g ° f)(x) = g(f(x))
```

The composition operator `°` can be understood as *after*. In other words, the function `g` is applied after the function `f` has been applied to `x`.

If you have two functions `f` and `g`, function composition allows you to create a new function `h` such that `h(x) = g(f(x))`.

```
((comp str +) 8 8 8)
=> "24"

(map (comp - (partial + 3) (partial * 2)) [1 2 3 4])
=> (-5 -7 -9 -11)

((reduce comp [(partial + 1) (partial * 2) (partial + 3)]) 100)
=> 207

(filter (comp not zero?) [0 1 0 2 0 3 0 4])
=> (1 2 3 4)

(do
  (def fifth (comp first rest rest rest rest))
  (fifth [1 2 3 4 5]))
=> 5
```

[top](#)

compare

```
(compare x y)
```

Comparator. Returns -1, 0, or 1 when x is logically 'less than', 'equal to', or 'greater than' y. For list and vectors the longer sequence is always 'greater' regardless of its contents. For sets and maps only the size of the collection is compared.

```
(compare nil 0)
=> -1

(compare 0 nil)
=> 1

(compare 1 0)
=> 1

(compare 1 1)
=> 0

(compare 1M 2M)
=> -1

(compare 1 nil)
=> 1

(compare nil 1)
=> -1

(compare "aaa" "bbb")
=> -1
```

```
(compare [0 1 2] [0 1 2])
=> 0

(compare [0 1 2] [0 9 2])
=> -1

(compare [0 9 2] [0 1 2])
=> 1

(compare [1 2 3] [0 1 2 3])
=> -1

(compare [0 1 2] [3 4])
=> 1
```

[top](#)

compare-and-set!

```
(compare-and-set! atom oldval newval)
```

Atomically sets the value of atom to newval if and only if the current value of the atom is identical to oldval. Returns true if set happened, else false.

```
(do
  (def counter (atom 2))
  (compare-and-set! counter 2 4)
  @counter)
=> 4
```

SEE ALSO

[atom](#)

Creates an atom with the initial value x.

[top](#)

complement

```
(complement f)
```

Takes a fn f and returns a fn that takes the same arguments as f, has the same effects, if any, and returns the opposite truth value.

```
(complement even?)
=> anonymous-448290a7-cda1-4497-b0d8-3a673da0f5e7

(filter (complement even?) '(1 2 3 4))
=> (1 3)
```

[top](#)

complete-on-timeout

```
(complete-on-timeout p value time time-unit)
```

Completes the promise with the given value if not otherwise completed before the given timeout.

```
(-> (promise (fn [] (sleep 100) "The quick brown fox"))
      (complete-on-timeout "The fox did not jump" 500 :milliseconds)
      (deref))
=> "The quick brown fox"
```

```
(-> (promise (fn [] (sleep 500) "The quick brown fox"))
      (complete-on-timeout "The fox did not jump" 100 :milliseconds)
      (deref))
=> "The fox did not jump"
```

```
(-> (promise (fn [] (sleep 500) "The quick brown fox"))
      (complete-on-timeout "The fox did not jump" 100 :milliseconds)
      (then-apply str/upper-case)
      (deref))
=> "THE FOX DID NOT JUMP"
```

```
(-> (promise (fn [] (sleep 50) 100))
      (complete-on-timeout 888 100 :milliseconds)
      (then-apply #(do (sleep 200) (* % 3)))
      (complete-on-timeout 999 220 :milliseconds)
      (deref))
=> 999
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two ...

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[then-combine](#)

Applies a function `f` to the result of the previous stage of promise `p` and the result of another promise `p-other`

[then-compose](#)

Composes the result of two promises. `f` receives the result of the first promise `p` and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise `p` with the same result or exception at this stage, that executes the action `f`. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completest normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[top](#)

Defines a protocol for components.

Definition:

```
(defprotocol Component
  (start [component] component)
  (stop [component] component))
```

Function `start` :

Begins operation of this component. Synchronous, does not return until the component is started. Returns an updated version of this component.

Function `stop` :

Ceases operation of this component. Synchronous, does not return until the component is stopped. Returns an updated version of this component.

[top](#)

component/dep

```
(dep c k)
```

Returns a dependency given by its key 'k' from the component 'c' dependencies.

```
(do
  (load-module :component ['component :as 'c])

  (deftype :server []
    c/Component
    (start [this] (println "Store: " (c/dep this :store)) this)
    (stop [this] this))

  (deftype :database []
    c/Component
    (start [this] this)
    (stop [this] this))

  (defn create-system []
    (-> (c/system-map
        "test"
        :server (server. )
        :store (database. ))
      (c/system-using {:server [:store]})))

  (-> (create-system)
    (c/start)
    (c/stop))

  nil)
Store: {:custom-type* :user/database}
=> nil
```

SEE ALSO

[component/deps](#)

Returns the dependencies of the component 'c' or nil if there aren't any dependencies.

[component/id](#)

Returns id of the component 'c'.

[top](#)

component/deps

(deps c)

Returns the dependencies of the component 'c' or `nil` if there aren't any dependencies.

```
(do
  (load-module :component ['component :as 'c])

  (deftype :server []
    c/Component
    (start [this] (println "Dependencies: " (c/deps this)) this)
    (stop [this] this))

  (deftype :database []
    c/Component
    (start [this] this)
    (stop [this] this))

  (defn create-system []
    (-> (c/system-map
        "test"
        :server (server. )
        :store (database. ))
      (c/system-using {:server [:store]})))

  (-> (create-system)
    (c/start)
    (c/stop))

  nil)
Dependencies: {:store {:custom-type* :user/database} :component-info {:custom-type* :component/component-info :
id :server :system-name test :components {}}}
=> nil
```

SEE ALSO

[component/dep](#)

Returns a dependency given by its key 'k' from the component 'c' dependencies.

[component/id](#)

Returns id of the component 'c'.

[top](#)

component/id

(id c)

Returns id of the component 'c'.

```
(do
  (load-module :component ['component :as 'c])

  (deftype :server []
    c/Component
    (start [this] (println "ID: " (c/id this)) this)
```

```

      (stop [this] this))

(defn create-system []
  (-> (c/system-map
        "test"
        :server (server. ))
      (c/system-using {:server []})))

(-> (create-system)
    (c/start)
    (c/stop))

nil)
ID: :server
=> nil

```

SEE ALSO

[component/dep](#)

Returns a dependency given by its key 'k' from the component 'c' dependencies.

[component/deps](#)

Returns the dependencies of the component 'c' or nil if there aren't any dependencies.

[top](#)

component/system-map

```
(system-map name keyval*)
```

Returns a system constructed of components given as key/value pairs. The 'key' is a `keyword` (the component's id) referencing the component given as 'value'.

The system has default implementations of the Lifecycle 'start' and 'stop' methods which recursively starts/stops all components in the system.

Note:

`system-map` just creates a raw system without any dependencies between the components. Use `system-using` after creating the system map to establish the dependencies.

```

(do
  (load-module :component ['component :as 'c])

  (deftype :server [port :long]
    c/Component
    (start [this] (println "server started") this)
    (stop [this] (println "server stopped") this))

  (deftype :database [user      :string
                     password :string]
    c/Component
    (start [this] (println "database started") this)
    (stop [this] (println "database stopped") this))

  (c/system-map
    "test"
    :server (server. 4600)
    :store (database. "foo" "123"))

nil)

```

SEE ALSO

component/system-using

```
(system-using system dependency-map)
```

Associates a component dependency graph with the 'system' that has been created through a call to `system-map`. 'dependency-map' is a map of keys to maps or vectors specifying the dependencies of the component at that key in the system.

Throws an exception if a component dependency circle is detected.

The system is started and stopped calling the lifecycle `start` or `stop` method on the system component.

Upon successfully starting a component the flag `{:started true}` is added to the component's meta data. It's up to the components lifecycle `start` method to decide what to do with multiple start requests. The lifecycle `start` method can for instance simply return the unaltered component if it has already been started.

Upon successfully stopping a component the flag `{:started false}` is added to the component's meta data. It's up to the components lifecycle `stop` method to decide what to do with multiple stop requests. The lifecycle `stop` method can for instance simply return the unaltered component if it has not been started or has already been stopped.

```
(do
  (load-module :component ['component :as 'c])

  (deftype :server [port :long]
    c/Component
    (start [this]
      (let [store1 (-> (c/dep this :store1) :name)
            store2 (-> (c/dep this :store2) :name)]
        (println "server started. using the stores" store1 "," store2))
      this)
    (stop [this]
      (println "server stopped")
      this))

  (deftype :database [name      :string
                     user       :string
                     password   :string]
    c/Component
    (start [this]
      (println "database" (:name this) "started")
      this)
    (stop [this]
      (println "database" (:name this) "stopped")
      this))

  (defn create-system []
    (-> (c/system-map
          "test"
          :server (server. 4600)
          :store1 (database. "store1" "foo" "123")
          :store2 (database. "store2" "foo" "123"))
        (c/system-using {:server [:store1 :store2]})))

  (defn start []
    (-> (create-system)
        (c/start)))

  (let [system (start)]
```



```

    server (-> system :components :server)]
; access server component
(println "Accessing the system...")
(c/stop system)

nil)
database store1 started
database store2 started
server started. using the stores store1 , store2
Accessing the system...
server stopped
database store2 stopped
database store1 stopped
=> nil

```

SEE ALSO

[component/system-map](#)

Returns a system constructed of components given as key/value pairs. The 'key' is a keyword (the component's id) referencing the component ...

top

concat

```

(concat coll)
(concat coll & colls)

```

Returns a list of the concatenation of the elements in the supplied collections.

```

(concat [1 2])
=> (1 2)

(concat [1 2] [4 5 6])
=> (1 2 4 5 6)

(concat '(1 2))
=> (1 2)

(concat '(1 2) [4 5 6])
=> (1 2 4 5 6)

(concat {:a 1})
=> ([:a 1])

(concat {:a 1} {:b 2 :c 3})
=> ([:a 1] [:b 2] [:c 3])

(concat "abc")
=> (#\a #\b #\c)

(concat "abc" "def")
=> (#\a #\b #\c #\d #\e #\f)

```

SEE ALSO

[concatv](#)

Returns a vector of the concatenation of the elements in the supplied collections.

[into](#)

Returns a new coll consisting of to coll with all of the items of from coll conjoined.

[merge](#)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from ...

[top](#)

concatv

```
(concatv coll)
(concatv coll & colls)
```

Returns a vector of the concatenation of the elements in the supplied collections.

```
(concatv [1 2])
=> [1 2]

(concatv [1 2] [4 5 6])
=> [1 2 4 5 6]

(concatv '(1 2))
=> [1 2]

(concatv '(1 2) [4 5 6])
=> [1 2 4 5 6]

(concatv {:a 1})
=> [[:a 1]]

(concatv {:a 1} {:b 2 :c 3})
=> [[:a 1] [:b 2] [:c 3]]

(concatv "abc")
=> [#\a #\b #\c]

(concatv "abc" "def")
=> [#\a #\b #\c #\d #\e #\f]
```

SEE ALSO

[concat](#)

Returns a list of the concatenation of the elements in the supplied collections.

[into](#)

Returns a new coll consisting of to coll with all of the items of from coll conjoined.

[merge](#)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from ...

[top](#)

cond

```
(cond & clauses)
```

Takes a set of test/expr pairs. It evaluates each test one at a time. If a test returns logical true, cond evaluates and returns the value of the corresponding expr and doesn't evaluate any of the other tests or exprs. (cond) returns nil.

```
(let [n 5]
  (cond
    (< n 0) "negative"
    (> n 0) "positive"
    :else "zero"))
=> "positive"
```

SEE ALSO

[condp](#)

Takes a binary predicate, an expression, and a set of clauses.

[case](#)

Takes an expression and a set of clauses. Each clause takes the form of test-constant result-expr

[top](#)

cond->

```
(cond-> expr & clauses)
```

Takes an expression and a set of test/form pairs. Threads expr (via ->) through each form for which the corresponding test expression is true. Note that, unlike cond branching, cond-> threading does not short circuit after the first true test expression.

It is useful in situations where you want selectively assoc, update, or dissoc something from a map.

```
(cond-> m
  (some-pred? q) (assoc :key :value))
```

```
(cond-> 1 ; we start with 1
  true inc ; the condition is true so (inc 1) => 2
  false (* 42) ; the condition is false so the operation is skipped
  (= 2 2) (* 3)) ; (= 2 2) is true so (* 2 3) => 6
=> 6
```

SEE ALSO

[cond->>](#)

Takes an expression and a set of test/form pairs. Threads expr (via ->>) through each form for which the corresponding test expression ...

[top](#)

cond->>

```
(cond->> expr & clauses)
```

Takes an expression and a set of test/form pairs. Threads expr (via ->>) through each form for which the corresponding test expression is true. Note that, unlike cond branching, cond->> threading does not short circuit after the first true test expression.

```
(cond->> 1 ; we start with 1
  true inc ; the condition is true so (inc 1) => 2
  false (* 42) ; the condition is false so the operation is skipped
  (= 2 2) (* 3)) ; (= 2 2) is true so (* 3 2) => 6
=> 6
```

SEE ALSO

[cond->](#)

Takes an expression and a set of test/form pairs. Threads expr (via ->) through each form for which the corresponding test expression ...

[top](#)

condp

(condp pred expr & clauses)

Takes a binary predicate, an expression, and a set of clauses.

Each clause can take the form of either:

```
test-expr result-expr
test-expr :>> result-fn
```

Note `:>>` is an ordinary keyword.

For each clause, (pred test-expr expr) is evaluated. If it returns logical true, the clause is a match. If a binary clause matches, the result-expr is returned, if a ternary clause matches, its result-fn, which must be a unary function, is called with the result of the predicate as its argument, the result of that call being the return value of condp. A single default expression can follow the clauses, and its value will be returned if no clause matches. If no default expression is provided and no clause matches, a VncException is thrown.

```
(condp some [1 2 3 4]
  #{0 6 7} :>> inc
  #{4 5 9} :>> dec
  #{1 2 3} :>> #(* % 10))
=> 3
```

```
(condp some [-10 -20 0 10]
  pos? 1
  neg? -1
  (constantly true) 0)
=> 1
```

SEE ALSO

[cond](#)

Takes a set of test/expr pairs. It evaluates each test one at a time. If a test returns logical true, cond evaluates and returns the ...

[case](#)

Takes an expression and a set of clauses. Each clause takes the form of test-constant result-expr

[top](#)

config/build

(build & parts)

Merges given configuration parts and returns it as a map.

Configuration parts:

- JSON classpath resource file
- JSON file
- Environment variables
- System properties

Example:

```
(do
  (load-module :config)

  (def cfg (config/build
    (config/env "java")
    (config/env-var "SERVER_PORT" [:http :port] "8080")))

  (println "home:" (-> cfg :11 :zulu :home))
  ; => home: /Library/Java/JavaVirtualMachines/zulu-11.jdk/Contents/Home

  (println "port:" (-> cfg :http :port)))
  ; => port: 8080
```

```
;; -----
;; Example I) Configuration builder
(do
  (load-module :config ['config :as 'cfg])

  (cfg/build
    (cfg/resource "config-defaults.json" :key-fn keyword)
    (cfg/file "./config-local.json" :key-fn keyword)
    (cfg/env-var "SERVER_PORT" [:http :port])
    (cfg/env-var "SERVER_THREADS" [:http :threads])
    (cfg/property-var "MASTER_PWD" [:app :master-pwd])))

;; -----
;; Example II) Using configurations with the component module
(do
  (load-module :config ['config :as 'cfg])
  (load-module :component ['component :as 'cmp])

  ;; define the server component
  (deftype :server []
    cmp/Component
    (start [this]
      (let [config (cmp/dep this :config)
            port (get-in config [:server :port])]
        (println (cmp/id this) "started at port" port)
        this))
    (stop [this]
      (println (cmp/id this) "stopped")
      this))

  ;; note that the configuration is a plain vanilla Venice map and
  ;; does not implement the protocol 'Component'
  (defn create-system []
    (-> (cmp/system-map
      "test"
      :config (cfg/build
        (cfg/env-var "SERVER_PORT" [:server :port] "8800"))
      :server (server. ))
      (cmp/system-using
        {:server [:config]})))

  (-> (create-system)
    (cmp/start)
    (cmp/stop))

  nil)
```

SEE ALSO

[config/file](#)

Reads a JSON configuration part from given file `f`.

[config/resource](#)

Reads a JSON configuration part from given path in classpath.

[config/env-var](#)

Reads a configuration value from an environment variable and associates it to the given path in a map.

[config/property-var](#)

Reads a configuration value from a system property and associates it to the given path in a map.

[config/env](#)

Reads configuration part from environment variables, filtered by a prefix. `nil` may be passed as prefix to get env vars.

[config/properties](#)

Reads configuration part from system properties, filtered by a prefix. `nil` may be passed as prefix to get property vars.

[top](#)

config/env

(`env prefix`)

Reads configuration part from environment variables, filtered by a prefix. `nil` may be passed as prefix to get env vars.

The reader splits the environment variable names on the underscores to build a map.

```
(base) $ env | grep JAVA_
JAVA_11_OPENJDK_HOME=/Library/Java/JavaVirtualMachines/adoptopenjdk-11.jdk/Contents/Home
JAVA_11_ZULU_HOME=/Library/Java/JavaVirtualMachines/zulu-11.jdk/Contents/Home
JAVA_11_HOME=/Library/Java/JavaVirtualMachines/adoptopenjdk-11.jdk/Contents/Home
JAVA_8_ZULU_HOME=/Library/Java/JavaVirtualMachines/zulu-8.jdk/Contents/Home
JAVA_8_OPENJDK_HOME=/Library/Java/JavaVirtualMachines/adoptopenjdk-8.jdk/Contents/Home
JAVA_8_HOME=/Library/Java/JavaVirtualMachines/adoptopenjdk-8.jdk/Contents/Home
JAVA_HOME=/Library/Java/JavaVirtualMachines/adoptopenjdk-8.jdk/Contents/Home

venice> (config/env "java")
=> {
  :11 {
    :zulu { :home "/Library/Java/JavaVirtualMachines/zulu-11.jdk/Contents/Home" }
    :openjdk { :home "/Library/Java/JavaVirtualMachines/adoptopenjdk-11.jdk/Contents/Home" }
    :home "/Library/Java/JavaVirtualMachines/adoptopenjdk-11.jdk/Contents/Home"
  }

  :8 {
    :zulu { :home "/Library/Java/JavaVirtualMachines/zulu-8.jdk/Contents/Home" }
    :openjdk { :home "/Library/Java/JavaVirtualMachines/adoptopenjdk-8.jdk/Contents/Home" }
    :home "/Library/Java/JavaVirtualMachines/adoptopenjdk-8.jdk/Contents/Home"
  }

  :home "/Library/Java/JavaVirtualMachines/adoptopenjdk-8.jdk/Contents/Home"
}
```

(`config/env "DATABASE_"`)

SEE ALSO

[config/env-var](#)

Reads a configuration value from an environment variable and associates it to the given path in a map.

[config/properties](#)

Reads configuration part from system properties, filtered by a prefix. `nil` may be passed as prefix to get property vars.

[config/build](#)

Merges given configuration parts and returns it as a map.

[top](#)

config/env-var

```
(env-var name path)
(env-var name path default-val)
```

Reads a configuration value from an environment variable and associates it to the given path in a map.

```
(config/env-var "JAVA_HOME" [:java-home])
=> {:java-home "/Library/Java/JavaVirtualMachines/zulu-8.jdk/Contents/Home"}

(config/env-var "SERVER_PORT" [:http :port])
=> nil

(config/env-var "SERVER_PORT" [:http :port] "8080")
=> {:http {:port "8080"}}
```

SEE ALSO

[config/property-var](#)

Reads a configuration value from a system property and associates it to the given path in a map.

[config/env](#)

Reads configuration part from environment variables, filtered by a prefix. nil may be passed as prefix to get env vars.

[config/build](#)

Merges given configuration parts and returns it as a map.

[top](#)

config/file

```
(file f)
(file f reader-opts)
```

Reads a JSON configuration part from given file f.

f may be a:

- string file path, e.g: "/temp/foo.json"
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.InputStream`
- `java.io.Reader`
- `java.net.URL`
- `java.net.URI`

The optional 'reader-opts' are defined by `json/read-str`.

E.g.: `:key-fn keyword` will convert all config keys to keywords

```
(config/file "/foo/app/config-production.json" :key-fn keyword)
```

```
(do
  (def cfg-json ""
    { "db" : {
      "classname" : "com.mysql.jdbc.Driver",
      "subprotocol" : "mysql",
      "subname" : "//127.0.0.1:3306/test",
      "user" : "test",
      "password" : "123"
    }
  })

  (-> (io/buffered-reader cfg-json)
    (config/file :key-fn keyword)))
```

SEE ALSO

[config/resource](#)

Reads a JSON configuration part from given path in classpath.

[config/build](#)

Merges given configuration parts and returns it as a map.

[json/read-str](#)

Reads a JSON string and returns it as a Venice datatype.

top

config/properties

(properties prefix)

Reads configuration part from system properties, filtered by a prefix. `nil` may passed as prefix to get property vars.

The reader splits the property names on the underscores to build a map.

```
(config/properties "DATABASE_")
```

SEE ALSO

[config/property-var](#)

Reads a configuration value from an system property and associates it to the given path in a map.

[config/build](#)

Merges given configuration parts and returns it as a map.

top

config/property-var

(property-var name path)

(property-var name path default-val)

Reads a configuration value from an system property and associates it to the given path in a map.

```
(config/property-var "java.vendor" [:java :vendor])
=> {:java {:vendor "Azul Systems, Inc."}}
```



```
(config/property-var "java.version" [:java :version])
=> {:java {:version "1.8.0_392"}}

(config/property-var "SERVER_PORT" [:http :port])
=> nil

(config/property-var "SERVER_PORT" [:http :port] "8080")
=> {:http {:port "8080"}}
```

SEE ALSO

[config/env-var](#)

Reads a configuration value from an environment variable and associates it to the given path in a map.

[config/properties](#)

Reads configuration part from system properties, filtered by a prefix. nil may passed as prefix to get property vars.

[config/build](#)

Merges given configuration parts and returns it as a map.

[top](#)

config/resource

```
(resource path)
(resource path reader-opts)
```

Reads a JSON configuration part from given path in classpath.

The optional 'reader-opts' are defined by `json/read-str`.

E.g.: `:key-fn keyword` will convert all config keys to keywords

```
(config/resource "com/github/jlangch/venice/examples/database-config.json"
  :key-fn keyword)
=> {:db {:classname "com.mysql.jdbc.Driver" :subname "//127.0.0.1:3306/test" :user "test" :subprotocol "mysql" :
password "123"}}
```

SEE ALSO

[config/file](#)

Reads a JSON configuration part from given file f.

[config/build](#)

Merges given configuration parts and returns it as a map.

[json/read-str](#)

Reads a JSON string and returns it as a Venice datatype.

[top](#)

conj

```
(conj)
(conj x)
(conj coll x)
(conj coll x & xs)
```

Returns a new collection with the x, xs 'added'. `(conj nil item)` returns `(item)` and `(conj item)` returns `item`.

For ordered collections like list, vectors and ordered sets/maps the value is added at the end. For all other collections the position is undefined.

```
(conj [1 2 3] 4)
=> [1 2 3 4]

(conj [1 2 3] 4 5)
=> [1 2 3 4 5]

(conj [1 2 3] [4 5])
=> [1 2 3 [4 5]]

(conj '(1 2 3) 4)
=> (1 2 3 4)

(conj '(1 2 3) 4 5)
=> (1 2 3 4 5)

(conj '(1 2 3) '(4 5))
=> (1 2 3 (4 5))

(conj (set 1 2 3) 4)
=> #{1 2 3 4}

(conj {:a 1 :b 2} [:c 3])
=> {:a 1 :b 2 :c 3}

(conj {:a 1 :b 2} {:c 3})
=> {:a 1 :b 2 :c 3}

(conj {:a 1 :b 2} (map-entry :c 3))
=> {:a 1 :b 2 :c 3}

(conj)
=> []

(conj 4)
=> 4
```

SEE ALSO

[cons](#)

Returns a new collection where x is the first element and coll is the rest.

[into](#)

Returns a new coll consisting of to coll with all of the items of from coll conjoined.

[concat](#)

Returns a list of the concatenation of the elements in the supplied collections.

[list*](#)

Creates a new list containing the items prepended to the rest, the last of which will be treated as a collection.

[vector*](#)

Creates a new vector containing the items prepended to the rest, the last of which will be treated as a collection.

[top](#)

conj!

```
(conj!)
(conj! x)
(conj! coll x)
(conj! coll x & xs)
```

Returns a new mutable collection with the x, xs 'added'. `(conj! nil item)` returns `(item)` and `(conj! item)` returns `item`.

For mutable ordered collections like lists the value is added at the end. For all other mutable collections the position is undefined.

```
(conj! (mutable-list 1 2 3) 4)
=> (1 2 3 4)

(conj! (mutable-list 1 2 3) 4 5)
=> (1 2 3 4 5)

(conj! (mutable-list 1 2 3) '(4 5))
=> (1 2 3 (4 5))

(conj! (mutable-set 1 2 3) 4)
=> #{1 2 3 4}

(conj! (mutable-map :a 1 :b 2) [:c 3])
=> {:a 1 :b 2 :c 3}

(conj! (mutable-map :a 1 :b 2) {:c 3})
=> {:a 1 :b 2 :c 3}

(conj! (mutable-map :a 1 :b 2) (map-entry :c 3))
=> {:a 1 :b 2 :c 3}

(conj! (stack) 1 2 3)
=> (3 2 1)

(conj! (queue) 1 2 3)
=> (1 2 3)

(conj!)
=> ()

(conj! 4)
=> 4
```

[top](#)

cons

```
(cons x coll)
```

Returns a new collection where x is the first element and coll is the rest.

For ordered collections like list, vectors and ordered sets/maps the value is added at the beginning. For all other collections the position is undefined.

```
(cons 1 '(2 3 4 5 6))
=> (1 2 3 4 5 6)
```

```

(cons 1 nil)
=> (1)

(cons [1 2] [4 5 6])
=> [[1 2] 4 5 6]

(cons 3 (set 1 2))
=> #{1 2 3}

(cons {:c 3} {:a 1 :b 2})
=> {:a 1 :b 2 :c 3}

(cons (map-entry :c 3) {:a 1 :b 2})
=> {:a 1 :b 2 :c 3}

; cons a value to a lazy sequence
(->> (cons -1 (lazy-seq 0 #(+ % 1)))
      (take 5)
      (doall)))
=> (-1 0 1 2 3)

; recursive lazy sequence (fibonacci example)
(do
  (defn fib
    ([ ] (fib 1 1))
    ([a b] (cons a (fn [] (fib b (+ a b))))))

    (doall (take 6 (fib))))
=> (1 1 2 3 5 8)

```

SEE ALSO

[conj](#)

Returns a new collection with the x, xs 'added'. (conj nil item) returns (item) and (conj item) returns item.

[list*](#)

Creates a new list containing the items prepended to the rest, the last of which will be treated as a collection.

[vector*](#)

Creates a new vector containing the items prepended to the rest, the last of which will be treated as a collection.

[top](#)

cons!

```
(cons! x coll)
```

Adds x to the mutable collection coll.

For mutable ordered collections like lists the value is added at the beginning. For all other mutable collections the position is undefined.

```

(cons! 1 (mutable-list 2 3))
=> (1 2 3)

(cons! 3 (mutable-set 1 2))
=> #{1 2 3}

(cons! {:c 3} (mutable-map :a 1 :b 2))
=> {:a 1 :b 2 :c 3}

```

```
(cons! (map-entry :c 3) (mutable-map :a 1 :b 2))
=> {:a 1 :b 2 :c 3}
```

```
(cons! 1 (stack))
=> (1)
```

```
(cons! 1 (queue))
=> (1)
```

[top](#)

constantly

```
(constantly x)
```

Returns a function that takes any number of arguments and returns always the value x.

```
(do
  (def fix (constantly 10))
  (fix 1 2 3)
  (fix 1)
  (fix ))
=> 10
```

SEE ALSO

[repeat](#)

Returns a lazy sequence of x values or a collection with the value x repeated n times.

[repeatedly](#)

Takes a function of no args, presumably with side effects, and returns a collection of n calls to it

[dotimes](#)

Repeatedly executes body with name bound to integers from 0 through n-1.

[top](#)

contains?

```
(contains? coll key)
```

Returns true if key is present in the given collection, otherwise returns false.

Note: To test if a value is in a vector or list use `any?`

```
(contains? #{:a :b} :a)
=> true
```

```
(contains? {:a 1 :b 2} :a)
=> true
```

```
(contains? [10 11 12] 1)
=> true
```

```
(contains? [10 11 12] 5)
=> false
```

```
(contains? "abc" 1)
=> true
```

```
(contains? "abc" 5)
=> false
```

SEE ALSO

[not-contains?](#)

Returns true if key is not present in the given collection, otherwise returns false.

[any?](#)

Returns true if the predicate is true for at least one collection item, false otherwise.

[top](#)

count

```
(count coll)
```

Returns the number of items in the collection. `(count nil)` returns 0. Also works on strings, and Java Collections

```
(count {:a 1 :b 2})
=> 2
```

```
(count [1 2])
=> 2
```

```
(count "abc")
=> 3
```

[top](#)

cpus

```
(cpus)
```

Returns the number of available processors or number of hyperthreads if the CPU supports hyperthreads.

```
(cpus)
=> 8
```

[top](#)

crypt/add-bouncy-castle-provider

```
(crypt/add-bouncy-castle-provider
```

Adds the BouncyCastle provider to the Java security.

```
(do
  (load-module :crypt)
  (crypt/add-bouncy-castle-provider))
```

SEE ALSO

[crypt/provider?](#)

Returns true if the Java security provider with name exists, else false.

[top](#)

crypt/ciphers

```
(crypt/ciphers)
(crypt/ciphers opt)
```

Returns a list of the ciphers the Java VM supports

Argument opt

:default returns the names of the cipher suites which are enabled by default.

:available returns the names of the cipher suites which could be enabled for use on an SSL connection created by this `SSLServerSocketFactory` .

```
(do
  (load-module :crypt)
  (crypt/ciphers :default))

(do
  (load-module :crypt)
  (crypt/ciphers :available))

(do
  (load-module :crypt)
  (docoll println (crypt/ciphers :available)))
```

[top](#)

crypt/decrypt

```
(crypt/decrypt algorithm passphrase & options)
```

Returns a new thread safe function to decrypt a string or a bytebuf given the algorithm and passphrase. If a string is passed it is base64 decoded, decrypted, and returned as string. If a bytebuf is passed the decrypted bytebuf is returned.

Supported algorithms: DES, 3DES, AES256

Options:

:url-safe The boolean option directs the base64 decoder to decode standard or URL safe base64 encoded strings. If enabled (true) the base64 decoder will convert '-' and '_' characters back to '+' and '/' before decoding. Defaults to false.

:salt An optional salt. A bytebuf or a string. DES and 3DES require exactly 8 bytes, AES256 1 or more bytes

```
(do
  (load-module :crypt)
  (def encrypt (crypt/encrypt "AES256" "secret" :url-safe true))
  (def decrypt (crypt/decrypt "AES256" "secret" :url-safe true))
  (encrypt "hello") ; => "e4m1qe6Fyx3Rr7NTIZe97g=="
  (decrypt "e4m1qe6Fyx3Rr7NTIZe97g==") ; => "hello"
  (encrypt (bytebuf [128 216 205]))) ; => [43 195 99 118 231 225 142 76 132 194 129 237 158 12 12 203]
=> [43 195 99 118 231 225 142 76 132 194 129 237 158 12 12 203]
```

```
(do
  (load-module :crypt)
  (def encrypt (crypt/encrypt "AES256" "secret" :salt "salty"))
  (def decrypt (crypt/decrypt "AES256" "secret" :salt "salty"))
  (-> "hello"
    (encrypt)
    (decrypt)))
=> "hello"
```

SEE ALSO

[crypt/encrypt](#)

Returns a new thread safe function to encrypt a string or a bytebuf given the algorithm and passphrase. If a string is passed it is ...

[top](#)

crypt/decrypt-file

```
(crypt/decrypt-file algorithm passphrase in)
(crypt/decrypt-file algorithm passphrase in out)
```

Decrypts an encrypted file that has been created by `crypt/encrypt-file`.

Returns a byte buffer with the decrypted data if the 'out' argument is missing. Otherwise returns nil and writes the decrypted file data to the destination given by 'out'.

The arg 'algorithm' is one of: "AES256-GCM", "AES256-CBC", "ChaCha20"

The arg 'in' may be a:

- string file path, e.g: "/temp/foo.json"
- bytebuf
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.InputStream`

The arg 'out' may be a:

- string file path, e.g: "/temp/foo.json"
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.OutputStream`

```
(do
  (load-module :crypt)
  (let [file-in (io/temp-file "test-", ".data")
        file-out (io/temp-file "test-", ".data.enc")
        passphrase "42"]
    (io/delete-file-on-exit file-in file-out)
    (io/spit file-in "1234567890")
    (crypt/encrypt-file "AES256-GCM" passphrase file-in file-out)
```



```
(-> (crypt/decrypt-file "AES256-GCM" passphrase file-out)
    (bytebuf-to-string :UTF-8)))
=> "1234567890"
```

SEE ALSO

[crypt/encrypt-file](#)

Encrypts a file.

top

crypt/encrypt

(crypt/encrypt algorithm passphrase & options)

Returns a new thread safe function to encrypt a string or a bytebuf given the algorithm and passphrase. If a string is passed it is encrypted and returned as a base64 encoded string. If a bytebuf is passed the encrypted bytebuf is returned.

Supported algorithms: "DES", "3DES", "AES256"

Options:

:url-safe	The boolean option directs the base64 encoder to emit standard or URL safe base64 encoded strings. If <code>true</code> the base64 encoder will emit '-' and '_' instead of the usual '+' and '/' characters. Defaults to false. Note: no padding is added when encoding using the URL-safe alphabet.
:salt	An optional salt. A bytebuf or a string. DES and 3DES require exactly 8 bytes, AES256 1 or more bytes

```
(do
  (load-module :crypt)
  (def encrypt (crypt/encrypt "3DES" "secret" :url-safe true))
  (encrypt "hello") ; => "ndmW1NLsDHA="
  (encrypt "world") ; => "KPYjndkZ8vM="
  (encrypt (bytebuf [1 2 3 4]))) ; => [128 216 205 163 62 43 52 82]
=> [128 216 205 163 62 43 52 82]

(do
  (load-module :crypt)
  (def encrypt (crypt/encrypt "3DES" "secret" :url-safe true :salt "salty"))
  (encrypt "hello") ; => "3MrQGcgbv00="
  (encrypt "world") ; => "a6UyBZUnK4I="
  (encrypt (bytebuf [1 2 3 4]))) ; => [86 66 56 135 239 120 10 150]
=> [86 66 56 135 239 120 10 150]
```

SEE ALSO

[crypt/decrypt](#)

Returns a new thread safe function to decrypt a string or a bytebuf given the algorithm and passphrase. If a string is passed it is ...

top

crypt/encrypt-file

(crypt/encrypt-file algorithm passphrase in)
(crypt/encrypt-file algorithm passphrase in out)

Encrypts a file.

Returns a byte buffer with the encrypted data if the 'out' argument is missing. Otherwise returns nil and writes the encrypted file data to the destination given by 'out'.

Supported algorithms:

- AES256-GCM ¹
- AES256-CBC ²
- ChaCha20 ³
- ChaCha20-BC ⁴

¹ Recommended by NIST

² AES256-CBC is regarded as a broken or risky cryptographic algorithm (CWE-327, CWE-328). Use AES256-GCM in production!

³ 256 bit key, only available with Java 11+

⁴ 256 bit key, only available with BouncyCastle libraries but works with Java 8+

Warning: files encrypted with ChaCha20 cannot be decrypted by ChaCha20-BC (and vice versa) due to different initial counter handling and the IV size (96bit vs 64bit)

The ChaCha family of ciphers are an order of magnitude more efficient on servers that do not provide hardware acceleration. Apple Silicon does not seem to have AES hardware acceleration probably due to its RISC nature.

The arg 'in' may be a:

- string file path, e.g: `"/temp/foo.json"`
- `bytebuf`
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.InputStream`

The arg 'out' may be a:

- string file path, e.g: `"/temp/foo.json"`
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.OutputStream`

The 256 bit encryption key is derived from the passphrase using a `PBKDF2WithHmacSHA256` secret key factory with a 16 byte random salt and 65536 iterations. Carefully choose a long enough passphrase.

Salt, *IV*, *Nonce* and/or *Counter* are random and unique for every call of `crypt/encrypt-file`.

While encrypting a file the random *Salt* (when a passphrase is used), *IV*, *Nonce* and/or *Counter* are written to the start of the encrypted file and read before decrypting the file:

AES256-GCM	AES256-CBC	ChaCha20
AES/GCM/NoPadding	AES/CBC/PKCS5Padding	
+-----+	+-----+	+-----+
salt (16)	salt (16)	salt (16)
+-----+	+-----+	+-----+
iv (12)	iv (12)	nonce (12)
+-----+	+-----+	+-----+
data (n)	data (n)	counter (4)
+-----+	+-----+	+-----+
		data (n)
		+-----+

```
(do
  (load-module :crypt)
  (load-module :hexdump)
  (let [file-in (io/temp-file "test-", ".data")
        file-out (io/temp-file "test-", ".data.enc")]
    (io/delete-file-on-exit file-in file-out)
    (io/spit file-in "1234567890")
    (crypt/encrypt-file "AES256-GCM" "42" file-in file-out)
    (-> (io/slurp file-out :binary false)
        (bytebuf)))
```

```
(hexdump/dump)))
00000000: efbf bdef bfbf efbf bdef bfbf 2eef bfbf .....
00000010: 5a08 efbf bd5a efbf bdef bfbf efbf bdef Z....Z.....
00000020: bfbf 1b5a cbafe7 bfbf 0cef bfbf 1830 ...Z..r.....0
00000030: efbf bdef bfbf efbf bd37 efbf bdef bfbf .....7.....
00000040: efbf bd6b 45ef bfbf efbf bdef bfbf cc82 ...kE.....
00000050: 533d efbf bdef bfbf 73ef bfbf 6c6d efbf S=.....s...lm..
00000060: bd61 efbf bd1d 06ef bfbf 1c .....a.....
=> nil
```

SEE ALSO

[crypt/decrypt-file](#)

Decrypts an encrypted file that has been created by `crypt/encrypt-file`.

[top](#)

crypt/hash-file

(crypt/hash-file algorithm salt file)

Computes a hash for a file. The hash is used together with the function `crypt/verify-file-hash` to detect file modifications.

Returns the hash Base64 encoded.

The functions uses the fast MD5 hash algorithm.

The arg 'file' may be a:

- string file path, e.g: `"/temp/foo.json"`
- `bytebuf`
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.InputStream`

Supported hash algorithms:

- MD5 (default)
- SHA-1
- SHA-512

MD5 is the fastest hash algorithm and precise enough to detect file changes.

```
(do
  (load-module :crypt)
  (let [file (io/temp-file "test-", ".data")
        data (bytebuf-allocate-random 1000)]
    (io/delete-file-on-exit file)
    (io/spit file data)
    (crypt/hash-file "SHA-256" "-salt-" file)))
=> "CnZ/ZLWa5gCSlWVEmAw0psuratYwvod/cPN9GqWYSi4="
```

SEE ALSO

[crypt/verify-file-hash](#)

Verifies a file against a hash (Base64 encoded). Returns true if the file's actual hash is equal to the given hash otherwise false.

[top](#)

crypt/max-key-size

```
(crypt/max-key-size algorithm)
```

Returns the max allowed key size

```
(do
  (load-module :crypt)
  (crypt/max-key-size "AES"))
=> 2147483647I
```

[top](#)

crypt/md5-hash

```
(crypt/md5-hash data)
(crypt/md5-hash data salt)
```

Hashes a string or a bytebuf using MD5 with an optional salt.

Note: MD5 is not safe any more use PBKDF2 to hash passwords!

```
(> (crypt/md5-hash "hello world")
   (str/bytebuf-to-hex :upper))
=> "5EB63BBE01EEED093CB22BB8F5ACDC3"
```

```
(> (crypt/md5-hash "hello world" "-salt-")
   (str/bytebuf-to-hex :upper))
=> "C40C4EAC3C1B87B6877E21FEBA087D0A"
```

SEE ALSO

[crypt/sha1-hash](#)

Hashes a string or a bytebuf using SHA1 with an optional salt.

[crypt/sha512-hash](#)

Hashes a string or a bytebuf using SHA512 with an optional salt.

[crypt/pbkdf2-hash](#)

Hashes a string using PBKDF2. iterations defaults to 1000, key-length defaults to 256.

[top](#)

crypt/pbkdf2-hash

```
(crypt/pbkdf2-hash data salt)
(crypt/pbkdf2-hash data salt iterations key-length)
```

Hashes a string using PBKDF2. iterations defaults to 1000, key-length defaults to 256.

```
(> (crypt/pbkdf2-hash "hello world" "-salt-")
   (str/bytebuf-to-hex :upper))
=> "54F2B4411E8817C2A0743B2A7DD7EAE5AA3F748D1DDDC00766380914AFFE995"
```

```
(> (crypt/pbkdf2-hash "hello world" "-salt-" 1000 256)
   (str/bytebuf-to-hex :upper))
=> "54F2B4411E8817C2A0743B2A7DD7EAE5AA3F748D1DDDC00766380914AFFE995"
```

SEE ALSO

[crypt/md5-hash](#)

Hashes a string or a bytebuf using MD5 with an optional salt.

[crypt/sha1-hash](#)

Hashes a string or a bytebuf using SHA1 with an optional salt.

[crypt/sha512-hash](#)

Hashes a string or a bytebuf using SHA512 with an optional salt.

[top](#)

crypt/provider?

```
(crypt/provider? name)
```

Returns true if the Java security provider with name exists, else false.

```
(do
  (load-module :crypt)
  (crypt/provider? "BC"))
=> false
```

SEE ALSO

[crypt/add-bouncy-castle-provider](#)

Adds the BouncyCastle provider to the Java security.

[top](#)

crypt/sha1-hash

```
(crypt/sha1-hash data)
(crypt/sha1-hash data salt)
```

Hashes a string or a bytebuf using SHA1 with an optional salt.

```
(-> (crypt/sha1-hash "hello world")
    (str/bytebuf-to-hex :upper))
=> "2AAE6C35C94FCFB415DBE95F408B9CE91EE846ED"

(-> (crypt/sha1-hash "hello world" "-salt-")
    (str/bytebuf-to-hex :upper))
=> "90AECEDB9423CC9BC5BB7CBAFB88380BE5745B3D"
```

SEE ALSO

[crypt/md5-hash](#)

Hashes a string or a bytebuf using MD5 with an optional salt.

[crypt/sha512-hash](#)

Hashes a string or a bytebuf using SHA512 with an optional salt.

[crypt/pbkdf2-hash](#)

Hashes a string using PBKDF2. iterations defaults to 1000, key-length defaults to 256.

crypt/sha512-hash

```
(crypt/sha512-hash data)
(crypt/sha512-hash data salt)
```

Hashes a string or a bytebuf using SHA512 with an optional salt.

```
(let [s (-> (crypt/sha512-hash "hello world")
             (str/bytebuf-to-hex :upper))]
      (str (str/nfirst s 32) "... " (str/nlast s 32)))
=> "309ECC489C12D6EB4CC40F50C902F2B4...D830E81F605DCF7DC5542E93AE9CD76F"

(let [s (-> (crypt/sha512-hash "hello world" "-salt-")
             (str/bytebuf-to-hex :upper))]
      (str (str/nfirst s 32) "... " (str/nlast s 32)))
=> "316EBB70239D9480E91089D5D5BC6428...03095F186B19FC33C93D60282F3314A2"
```

SEE ALSO

[crypt/md5-hash](#)

Hashes a string or a bytebuf using MD5 with an optional salt.

[crypt/sha1-hash](#)

Hashes a string or a bytebuf using SHA1 with an optional salt.

[crypt/pbkdf2-hash](#)

Hashes a string using PBKDF2. iterations defaults to 1000, key-length defaults to 256.

crypt/verify-file-hash

```
(crypt/verify-file-hash algorithm salt file hash)
```

Verifies a file against a hash (Base64 encoded). Returns true if the file's actual hash is equal to the given hash otherwise false.

The arg 'file' may be a:

- string file path, e.g: `"/temp/foo.json"`
- bytebuf
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.InputStream`

Supported hash algorithms:

- MD5
- SHA-1
- SHA-512

Warning: The MD5 hash function's security is considered to be severely compromised. Collisions can be found within seconds, and they can be used for malicious purposes.

```
(do
  (load-module :crypt)
  (let [file (io/temp-file "test-", ".data")
```

```
data (bytebuf-allocate-random 1000)
salt "salt"]
(io/delete-file-on-exit file)
(io/spit file data)
(let [hash (crypt/hash-file "SHA-256" "-salt-" file)]
  (crypt/verify-file-hash "SHA-256" "-salt-" file hash)))
=> true
```

SEE ALSO

[crypt/hash-file](#)

Computes a hash for a file. The hash is used together with the function `crypt/verify-file-hash` to detect file modifications.

[top](#)

csv/read

(csv/read source & options)

Reads CSV-data from a source.

The source may be a:

- `string`
- `bytebuf`
- `java.io.File`, e.g. `(io/file "/temp/foo.json")`
- `java.nio.Path`, `
- `java.io.InputStream`
- `java.io.Reader`

Options:

`:encoding enc` used when reading from a binary data source e.g `:encoding :utf-8`, defaults to `:utf-8`

`:separator val` e.g. `,`, defaults to a comma

`:quote val` e.g. `""`, defaults to a double quote

```
(csv/read ""1,"ab",false"")
```

```
=> (("1" "ab" "false"))
```

```
(csv/read "1|||'ab'|false" :separator "|" :quote "'")
```

```
=> (("1" nil nil "ab" "false"))
```

[top](#)

csv/write

(csv/write sink records & options)

Spits data to a sink in CSV format.

The sink may be a:

- `java.io.File`, e.g. `(io/file "/temp/foo.json")`
- `java.nio.Path`
- `java.io.OutputStream`
- `java.io.Writer`

Options:

:separator val e.g. ",", defaults to a comma
:quote val e.g. "\"", defaults to a double quote
:newline val :lf (default) or :cr+lf
:encoding enc used when writing to a binary data sink. e.g :encoding :utf-8, defaults to :utf-8

```
(csv/write (io/file "test.csv") [[1 "AC" false] [2 "WS" true]])
```

top

csv/write-str

(csv/write-str records & options)

Writes data to a string in CSV format.

All fields containing a quote char, a separator char or a newline are quoted.

Options:

:separator val e.g. ",", defaults to a comma
:quote val e.g. "\"", defaults to a double quote
:newline val :lf (default) or :cr+lf

```
(csv/write-str [[1 "AC" false] [2 "WS" true]])  
=> "1,AC,false\n2,WS,true"
```

```
(csv/write-str [[1 "AC" false] [2 "WS, '-1'" true]]  
               :quote "\"" :separator "," :newline :cr+lf)  
=> "1,AC,false\r\n2,WS, '-1'',true"
```

top

current-time-millis

(current-time-millis)

Returns the current time in milliseconds.

```
(current-time-millis)  
=> 1724789633256
```

SEE ALSO

[nano-time](#)

Returns the current value of the running Java Virtual Machine's high-resolution time source, in nanoseconds.

top

cycle


```
(cycle coll)
```

Returns a lazy (infinite!) sequence of repetitions of the items in coll.

```
(doall (take 5 (cycle [1 2])))  
=> (1 2 1 2 1)
```

SEE ALSO

[repeat](#)

Returns a lazy sequence of x values or a collection with the value x repeated n times.

[repeatedly](#)

Takes a function of no args, presumably with side effects, and returns a collection of n calls to it

[dotimes](#)

Repeatedly executes body with name bound to integers from 0 through n-1.

[constantly](#)

Returns a function that takes any number of arguments and returns always the value x.

[top](#)

dag/add-edges

```
(add-edges edges*)
```

Add edges to a DAG. Returns a new DAG with added edges.

An edge is a vector of two nodes forming a parent/child relationship. Any *Venice* value can be used for a node.

Note: The graph is reconstructed after adding edges. To have best performance pass the edges with a single `add-edges` call to the DAG.

```
(dag/add-edges (dag/dag) ["A" "B"] ["B" "C"])  
=> (["A" "B"] ["B" "C"])
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/topological-sort](#)

Topological sort of a DAG using Kahn's algorithm (https://en.wikipedia.org/wiki/Topological_sorting)

[top](#)

dag/add-nodes

```
(add-nodes nodes*)
```

Add nodes to a DAG. Returns a new DAG with added nodes.

Any *Venice* value can be used for a node.

Note: The graph is reconstructed after adding nodes. To have best performance pass the nodes with a single `add-nodes` call to the DAG.

```
(dag/add-nodes (dag/dag) "A")
=> ("A")

(-> (dag/dag)
    (dag/add-nodes "A")
    (dag/add-edges ["A" "B"]))
=> (["A" "B"])

(-> (dag/dag)
    (dag/add-nodes "A")
    (dag/add-edges ["B" "C"]))
=> ("A" ["B" "C"])
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/topological-sort](#)

Topological sort of a DAG using Kahn's algorithm (https://en.wikipedia.org/wiki/Topological_sorting)

[top](#)

dag/child-of?

```
(child-of? dag c v)
```

Returns `true` if `c` is a transitive child of `v`

```
(-> (dag/dag ["A", "B"] ; A E
      ["B", "C"] ; | |
      ["C", "D"] ; B F
      ["E", "F"] ; | / \
      ["F", "C"] ; C G
      ["F", "G"] ; \ /
      ["G", "D"]) ; D
    (dag/child-of? "G" "E"))
=> true
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/children](#)

Returns the transitive child nodes

[dag/parent-of?](#)

Returns true if `p` is a transitive parent of `v`

[top](#)

dag/children

```
(children dag node)
```

Returns the transitive child nodes

```
(dag/children (dag/dag ["A" "B"] ["B" "C"]) "A")
=> ("B" "C")
```

```
(-> (dag/dag ["A", "B"] ; A E
      ["B", "C"] ; | |
      ["C", "D"] ; B F
      ["E", "F"] ; | / \
      ["F", "C"] ; C G
      ["F", "G"] ; \ /
      ["G", "D"] ; D
    (dag/children "F")))
=> ("C" "G" "D")
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/direct-children](#)

Returns the direct child nodes

[dag/parents](#)

Returns the transitive parent nodes

[dag/direct-parents](#)

Returns the direct parent nodes

[dag/roots](#)

Returns the root nodes of a DAG

[top](#)

dag/compare-fn

```
(compare-fn dag)
```

Returns a comparator fn which produces a topological sort based on the dependencies in the graph. Nodes not present in the graph will sort after nodes in the graph.

```
(let [g (dag/dag ["A", "B"] ; A E
      ["B", "C"] ; | |
      ["C", "D"] ; B F
      ["E", "F"] ; | / \
      ["F", "C"] ; C G
      ["F", "G"] ; \ /
      ["G", "D"] ; D
    (sort (dag/compare-fn g) ["D" "F" "A" "Z"]))]
=> ["F" "A" "D" "Z"]
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/topological-sort](#)

Topological sort of a DAG using Kahn's algorithm (https://en.wikipedia.org/wiki/Topological_sorting)

[top](#)

dag/dag

```
(dag)
(dag edges*)
```

Creates a new DAG (directed acyclic graph) built from edges

An edge is a vector of two nodes forming a parent/child relationship.

```
(dag/dag)
```

```
=> ()
```

```
(dag/dag ["A" "B"] ["B" "C"])
```

```
=> (["A" "B"] ["B" "C"])
```

```
(dag/dag ["A", "B"] ; A E
          ["B", "C"] ; | |
          ["C", "D"] ; B F
          ["E", "F"] ; | / \
          ["F", "C"] ; C G
          ["F", "G"] ; \ /
          ["G", "D"] ; D)
```

```
=> (["A" "B"] ["B" "C"] ["C" "D"] ["E" "F"] ["F" "C"] ["F" "G"] ["G" "D"])
```

SEE ALSO

[dag/dag?](#)

Returns true if coll is a DAG

[dag/add-edges](#)

Add edges to a DAG. Returns a new DAG with added edges.

[dag/add-nodes](#)

Add nodes to a DAG. Returns a new DAG with added nodes.

[dag/topological-sort](#)

Topological sort of a DAG using Kahn's algorithm (https://en.wikipedia.org/wiki/Topological_sorting)

[dag/edges](#)

Returns the edges of a DAG

[dag/edge?](#)

Returns true if the edge given by its parent and child node is part of the DAG

[dag/nodes](#)

Returns the nodes of a DAG

[dag/node?](#)

Returns true if v is a node in the DAG

[dag/roots](#)

Returns the root nodes of a DAG

[dag/children](#)

Returns the transitive child nodes

[dag/direct-children](#)

Returns the direct child nodes

[dag/child-of?](#)

Returns true if c is a transitive child of v

[dag/parents](#)

Returns the transitive parent nodes

[dag/direct-parents](#)

Returns the direct parent nodes

[dag/parent-of?](#)

Returns true if p is a transitive parent of v

[empty?](#)

Returns true if x is empty. Accepts strings, collections and bytebufs.

[count](#)

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

[top](#)

[dag/dag?](#)

```
(dag? coll)
```

Returns true if coll is a DAG

```
(dag/dag? (dag/dag))  
=> true
```

[top](#)

[dag/direct-children](#)

```
(direct-children dag node)
```

Returns the direct child nodes

```
(-> (dag/dag ["A", "B"] ; A E  
          ["B", "C"] ; | |  
          ["C", "D"] ; B F  
          ["E", "F"] ; | / \  
          ["F", "C"] ; C G  
          ["F", "G"] ; \ /  
          ["G", "D"] ; D  
    (dag/direct-children "F"))  
=> ("C" "G")
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/children](#)

Returns the transitive child nodes

[dag/parents](#)

Returns the transitive parent nodes

[dag/direct-parents](#)

Returns the direct parent nodes

[dag/roots](#)

Returns the root nodes of a DAG

dag/direct-parents

```
(direct-parents dag node)
```

Returns the direct parent nodes

```
(dag/parents (dag/dag ["A" "B"] ["B" "C"]) "C")
=> ("B" "A")
```

```
(-> (dag/dag ["A", "B"] ; A E
      ["B", "C"] ; | |
      ["C", "D"] ; B F
      ["E", "F"] ; | / \
      ["F", "C"] ; C G
      ["F", "G"] ; \ /
      ["G", "D"]) ; D
      (dag/direct-parents "C"))
=> ("B" "F")
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/parents](#)

Returns the transitive parent nodes

[dag/children](#)

Returns the transitive child nodes

[dag/direct-children](#)

Returns the direct child nodes

[dag/roots](#)

Returns the root nodes of a DAG

dag/edge?

```
(edge? dag parent child)
```

Returns `true` if the edge given by its parent and child node is part of the DAG

```
(-> (dag/dag ["A", "B"] ; A E
      ["B", "C"] ; | |
      ["C", "D"] ; B F
      ["E", "F"] ; | / \
      ["F", "C"] ; C G
      ["F", "G"] ; \ /
      ["G", "D"]) ; D
      (dag/edge? "C", "D"))
=> true
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/edges](#)

Returns the edges of a DAG

[top](#)

[dag/edges](#)

```
(edges dag)
```

Returns the edges of a DAG

```
(dag/edges (dag/dag ["A" "B"] ["B" "C"]))  
=> (["A" "B"] ["B" "C"])
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/add-edges](#)

Add edges to a DAG. Returns a new DAG with added edges.

[dag/nodes](#)

Returns the nodes of a DAG

[top](#)

[dag/node?](#)

```
(node? dag v)
```

Returns `true` if `v` is a node in the DAG

```
(-> (dag/dag ["A", "B"] ; A E  
           ["B", "C"] ; | |  
           ["C", "D"] ; B F  
           ["E", "F"] ; | / \  
           ["F", "C"] ; C G  
           ["F", "G"] ; \ /  
           ["G", "D"] ; D  
    (dag/node? "G"))  
=> true
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/nodes](#)

Returns the nodes of a DAG

[top](#)

dag/nodes

```
(nodes dag)
```

Returns the nodes of a DAG

```
(dag/nodes (dag/dag ["A" "B"] ["B" "C"]))  
=> ("A" "B" "C")
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/node?](#)

Returns true if v is a node in the DAG

[dag/add-edges](#)

Add edges to a DAG. Returns a new DAG with added edges.

[dag/edges](#)

Returns the edges of a DAG

[top](#)

dag/parent-of?

```
(parent-of? dag p v)
```

Returns `true` if p is a transitive parent of v

```
(-> (dag/dag ["A", "B"] ; A E  
          ["B", "C"] ; | |  
          ["C", "D"] ; B F  
          ["E", "F"] ; | / \  
          ["F", "C"] ; C G  
          ["F", "G"] ; \ /  
          ["G", "D"]) ; D  
  (dag/parent-of? "E" "G"))  
=> true
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/parents](#)

Returns the transitive parent nodes

[dag/child-of?](#)

Returns true if c is a transitive child of v

[top](#)

dag/parents


```
(parents dag node)
```

Returns the transitive parent nodes

```
(dag/parents (dag/dag ["A" "B"] ["B" "C"]) "C")  
=> ("B" "A")
```

```
(-> (dag/dag ["A", "B"] ; A E  
      ["B", "C"] ; | |  
      ["C", "D"] ; B F  
      ["E", "F"] ; | / \  
      ["F", "C"] ; C G  
      ["F", "G"] ; \ /  
      ["G", "D"] ; D  
      (dag/parents "C"))  
=> ("B" "F" "A" "E")
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/direct-parents](#)

Returns the direct parent nodes

[dag/children](#)

Returns the transitive child nodes

[dag/direct-children](#)

Returns the direct child nodes

[dag/roots](#)

Returns the root nodes of a DAG

[top](#)

dag/roots

```
(roots dag)
```

Returns the root nodes of a DAG

```
(dag/roots (dag/dag ["A" "B"] ["B" "C"]))  
=> ("A")
```

```
(-> (dag/dag ["A", "B"] ; A E  
      ["B", "C"] ; | |  
      ["C", "D"] ; B F  
      ["E", "F"] ; | / \  
      ["F", "C"] ; C G  
      ["F", "G"] ; \ /  
      ["G", "D"] ; D  
      (dag/roots))  
=> ("A" "E")
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/parents](#)

Returns the transitive parent nodes

[dag/children](#)

Returns the transitive child nodes

[top](#)

[dag/topological-sort](#)

(topological-sort dag)

Topological sort of a DAG using [Kahn's algorithm](#)

```
(dag/topological-sort (dag/dag ["A" "B"] ["B" "C"]))  
=> ["A" "B" "C"]
```

```
(-> (dag/dag ["A", "B"] ; A E  
      ["B", "C"] ; | |  
      ["C", "D"] ; B F  
      ["E", "F"] ; | / \  
      ["F", "C"] ; C G  
      ["F", "G"] ; \ /  
      ["G", "D"] ; D  
      (dag/topological-sort))  
=> ["E" "F" "G" "A" "B" "C" "D"]
```

SEE ALSO

[dag/dag](#)

Creates a new DAG (directed acyclic graph) built from edges

[dag/compare-fn](#)

Returns a comparator fn which produces a topological sort based on the dependencies in the graph. Nodes not present in the graph will ...

[dag/add-edges](#)

Add edges to a DAG. Returns a new DAG with added edges.

[top](#)

[dec](#)

(dec x)

Decrements the number x

```
(dec 10)  
=> 9
```

```
(dec 10I)  
=> 9I
```

```
(dec 10.1)  
=> 9.1
```

```
(dec 10.12M)
=> 9.12M
```

SEE ALSO

[inc](#)

Increments the number x

[top](#)

dec/add

```
(dec/add x y scale rounding-mode)
```

Adds two decimals and scales the result. rounding-mode is one of `:CEILING`, `:DOWN`, `:FLOOR`, `:HALF_DOWN`, `:HALF_EVEN`, `:HALF_UP`, `:UNNECESSARY`, or `:UP`

```
(dec/add 2.44697M 1.79882M 3 :HALF_UP)
=> 4.246M
```

SEE ALSO

[dec/sub](#)

Subtract y from x and scales the result. rounding-mode is one of `:CEILING`, `:DOWN`, `:FLOOR`, `:HALF_DOWN`, `:HALF_EVEN`, `:HALF_UP`, `:UNNECESSARY`, or `:UP`

[dec/mul](#)

Multiplies two decimals and scales the result. rounding-mode is one of `:CEILING`, `:DOWN`, `:FLOOR`, `:HALF_DOWN`, `:HALF_EVEN`, `:HALF_UP`, `:UNNECESSARY`, ...

[dec/div](#)

Divides x by y and scales the result. rounding-mode is one of `:CEILING`, `:DOWN`, `:FLOOR`, `:HALF_DOWN`, `:HALF_EVEN`, `:HALF_UP`, `:UNNECESSARY`, or `:UP`

[dec/scale](#)

Scales a decimal. rounding-mode is one of `:CEILING`, `:DOWN`, `:FLOOR`, `:HALF_DOWN`, `:HALF_EVEN`, `:HALF_UP`, `:UNNECESSARY`, or `:UP`

[top](#)

dec/div

```
(dec/div x y scale rounding-mode)
```

Divides x by y and scales the result. rounding-mode is one of `:CEILING`, `:DOWN`, `:FLOOR`, `:HALF_DOWN`, `:HALF_EVEN`, `:HALF_UP`, `:UNNECESSARY`, or `:UP`

```
(dec/div 2.44697M 1.79882M 5 :HALF_UP)
=> 1.36032M
```

SEE ALSO

[dec/add](#)

Adds two decimals and scales the result. rounding-mode is one of `:CEILING`, `:DOWN`, `:FLOOR`, `:HALF_DOWN`, `:HALF_EVEN`, `:HALF_UP`, `:UNNECESSARY`, or `:UP`

[dec/sub](#)

Subtract y from x and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/mul](#)

Multiplies two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, ...

[dec/scale](#)

Scales a decimal. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[top](#)

dec/mul

(dec/mul x y scale rounding-mode)

Multiplies two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

```
(dec/mul 2.44697M 1.79882M 5 :HALF_UP)
=> 4.40166M
```

SEE ALSO

[dec/add](#)

Adds two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/sub](#)

Subtract y from x and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/div](#)

Divides x by y and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/scale](#)

Scales a decimal. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[top](#)

dec/scale

(dec/scale x scale rounding-mode)

Scales a decimal. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

```
(dec/scale 2.44697M 0 :HALF_UP)
=> 2M
```

```
(dec/scale 2.44697M 1 :HALF_UP)
=> 2.4M
```

```
(dec/scale 2.44697M 2 :HALF_UP)
=> 2.45M
```

```
(dec/scale 2.44697M 3 :HALF_UP)
=> 2.447M
```

```
(dec/scale 2.44697M 10 :HALF_UP)
=> 2.4469700000M
```

SEE ALSO

[dec/add](#)

Adds two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/sub](#)

Subtract y from x and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/mul](#)

Multiplies two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, ...

[dec/div](#)

Divides x by y and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[top](#)

dec/sub

```
(dec/sub x y scale rounding-mode)
```

Subtract y from x and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

```
(dec/sub 2.44697M 1.79882M 3 :HALF_UP)
=> 0.648M
```

SEE ALSO

[dec/add](#)

Adds two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/mul](#)

Multiplies two decimals and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, ...

[dec/div](#)

Divides x by y and scales the result. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[dec/scale](#)

Scales a decimal. rounding-mode is one of :CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, or :UP

[top](#)

decimal

```
(decimal x) (decimal x scale rounding-mode)
```

Converts to decimal. rounding-mode is one of (:CEILING, :DOWN, :FLOOR, :HALF_DOWN, :HALF_EVEN, :HALF_UP, :UNNECESSARY, :UP)

```
(decimal 2)  
=> 2M
```

```
(decimal 2 3 :HALF_UP)  
=> 2.000M
```

```
(decimal 2.5787 3 :HALF_UP)  
=> 2.579M
```

```
(decimal 2.5787F 3 :HALF_UP)  
=> 2.579M
```

```
(decimal 2.5787M 3 :HALF_UP)  
=> 2.579M
```

```
(decimal "2.5787" 3 :HALF_UP)  
=> 2.579M
```

```
(decimal nil)  
=> 0M
```

[top](#)

decimal?

```
(decimal? n)
```

Returns true if n is a decimal

```
(decimal? 4.0M)  
=> true
```

```
(decimal? 4.0)  
=> false
```

```
(decimal? 3)  
=> false
```

```
(decimal? 3I)  
=> false
```

[top](#)

dedupe

```
(dedupe coll)
```

Returns a collection with all consecutive duplicates removed.
Returns a stateful transducer when no collection is provided.

```
(dedupe [1 2 2 2 3 4 4 2 3])
=> [1 2 3 4 2 3]
```

```
(dedupe '(1 2 2 2 3 4 4 2 3))
=> (1 2 3 4 2 3)
```

SEE ALSO

[distinct](#)

Returns a collection with all duplicates removed.

[top](#)

def

```
(def name expr)
```

Creates a global variable.

```
(def x 5)
=> user/x
```

```
(def sum (fn [x y] (+ x y)))
=> user/sum
```

```
(def ^{:private true} x 100)
=> user/x
```

SEE ALSO

[def](#)

Creates a global variable.

[def-](#)

Same as `def`, yielding non-public `def`

[defonce](#)

Creates a global variable that can not be overwritten

[def-dynamic](#)

Creates a dynamic variable that starts off as a global variable and can be bound with 'binding' to a new value on the local thread.

[set!](#)

Sets a global or thread-local variable to the value of the expression.

[top](#)

def-

```
(def- name expr)
```

Same as `def`, yielding non-public `def`

```
(def- x 100)
```

```
(do
  (ns foo)
  (def- x 100)
  (ns bar)
  foo/x) ; Illegal access of private symbol
```

SEE ALSO

[def](#)

Creates a global variable.

[top](#)

def-dynamic

```
(def-dynamic name expr)
```

Creates a dynamic variable that starts off as a global variable and can be bound with 'binding' to a new value on the local thread.

```
(do
  (def-dynamic x 100)
  (println x)
  (binding [x 200]
    (println x))
  (println x))
100
200
100
=> nil

(def-dynamic ^{:private true} x 100)
=> user/x
```

SEE ALSO

[binding](#)

Evaluates the expressions and binds the values to dynamic (thread-local) symbols

[def](#)

Creates a global variable.

[defonce](#)

Creates a global variable that can not be overwritten

[set!](#)

Sets a global or thread-local variable to the value of the expression.

[top](#)

defmacro

```
(defmacro name [params*] body)
```

Macro definition


```
(defmacro unless [pred a b]
  `(if (not ~pred) ~a ~b))
=> user/unless
```

SEE ALSO

[macroexpand](#)

If form represents a macro form, returns its expansion, else returns form.

[macroexpand-all](#)

Recursively expands all macros in the form.

[top](#)

defmethod

```
(defmethod multifn-name dispatch-val & fn-tail)
```

Creates a new method for a multimethod associated with a dispatch-value.

```
(do
  ;;defmulti with dispatch function
  (defmulti salary (fn [amount] (amount :t)))

  ;;defmethod provides a function implementation for a particular value
  (defmethod salary "com" [amount] (+ (:b amount) (/ (:b amount) 2)))
  (defmethod salary "bon" [amount] (+ (:b amount) 99))
  (defmethod salary :default [amount] (:b amount))

  [(salary {:t "com" :b 1000})
   (salary {:t "bon" :b 1000})
   (salary {:t "xxx" :b 1000})]
)
=> [1500 1099 1000]
```

SEE ALSO

[defmulti](#)

Creates a new multimethod with the associated dispatch function.

[top](#)

defmulti

```
(defmulti name dispatch-fn)
```

Creates a new multimethod with the associated dispatch function.

```
(do
  ;;defmulti with dispatch function
  (defmulti salary (fn [amount] (amount :t)))

  ;;defmethod provides a function implementation for a particular value
  (defmethod salary "com" [amount] (+ (:b amount) (/ (:b amount) 2)))
  (defmethod salary "bon" [amount] (+ (:b amount) 99))
  (defmethod salary :default [amount] (:b amount))
)
```

```

[(salary {:t "com" :b 1000})
 (salary {:t "bon" :b 1000})
 (salary {:t "xxx" :b 1000})]
)
=> [1500 1099 1000]

(do
  ;;dispatch on type
  (defmulti test (fn [x] (type x)))

  (defmethod test :core/number [x] [x :number])
  (defmethod test :core/string [x] [x :string])
  (defmethod test :core/boolean [x] [x :boolean])
  (defmethod test :default      [x] [x :default])

  [(test 1)
   (test 1.0)
   (test 1.0M)
   (test "abc")
   (test [1])]
)
=> [[1 :number] [1.0 :number] [1.0M :number] ["abc" :string] [[1] :default]]

```

SEE ALSO

[defmethod](#)

Creates a new method for a multimethod associated with a dispatch-value.

[top](#)

defn

```

(defn name [args*] condition-map? expr*)
(defn name ([args*] condition-map? expr*)+)

```

Same as `(def name (fn name [args*] condition-map? expr*))` or `(def name (fn name ([args*] condition-map? expr*)+))`

```

(defn sum [x y] (+ x y))
=> user/sum

```

```

(defn sum [x y] { :pre [< x 0] } (+ x y))
=> user/sum

```

```

(defn sum
  ([] 0)
  ([x] x)
  ([x y] (+ x y)))
=> user/sum

```

SEE ALSO

[defn-](#)

Same as `defn`, yielding non-public `def`

[fn](#)

Defines an anonymous function.

[def](#)

Creates a global variable.

defn-

```
(defn- name [args*] condition-map? expr*)  
(defn- name ([args*] condition-map? expr*)+)
```

Same as `defn`, yielding non-public `def`

```
(defn- sum [x y] (+ x y))  
=> user/sum
```

SEE ALSO

[defn](#)

Same as (def name (fn name [args*] condition-map? expr*)) or (def name (fn name ([args*] condition-map? expr*)+))

[fn](#)

Defines an anonymous function.

[def](#)

Creates a global variable.

defonce

```
(defonce name expr)
```

Creates a global variable that can not be overwritten

```
(defonce x 5)  
=> user/x  
  
(defonce ^{:private true} x 5)  
=> user/x
```

SEE ALSO

[def](#)

Creates a global variable.

[def-dynamic](#)

Creates a dynamic variable that starts off as a global variable and can be bound with 'binding' to a new value on the local thread.

defprotocol

```
(defprotocol protocol fn-spec*)
```

Defines a new protocol with the supplied function specs.

Formats:

- `(defprotocol P (foo [x]))`
- `(defprotocol P (foo [x] [x y]))`
- `(defprotocol P (foo [x] [x y] nil))`
- `(defprotocol P (foo [x] [x y] 100))`
- `(defprotocol P (foo [x]) (bar [x] [x y]))`

```
(do
  (ns foo)
  (deftype :complex [re :long, im :long])
  (defprotocol XMath (+ [x y]
                       (- [x y]))
    (extend :foo/complex XMath
      (+ [x y] (complex. (core/+ (:re x) (:re y))
                          (core/+ (:im x) (:im y))))
      (- [x y] (complex. (core/- (:re x) (:re y))
                          (core/- (:im x) (:im y)))))

  (extend :core/long XMath
    (+ [x y] (core/+ x y))
    (- [x y] (core/- x y)))
  (foo/+ (complex. 1 1) (complex. 4 5)))
=> {:custom-type* :foo/complex :re 5 :im 6}
```

```
(do
  (ns foo)
  (defprotocol Lifecycle (start [c]) (stop [c]))
  (deftype :component [name :string]
    Lifecycle (start [c] (println "'~(:name c)' started"))
              (stop [c] (println "'~(:name c)' stopped")))
  (let [c (component. "test")
        lifecycle? (extends? (type c) Lifecycle)]
    (println "'~(:name c)' extends Lifecycle protocol: ~{lifecycle?}")
    (start c)
    (stop c)))
'test' extends Lifecycle protocol: true
'test' started
'test' stopped
=> nil
```

SEE ALSO

[extend](#)

Extends protocol for type with the supplied functions.

[extends?](#)

Returns true if the type extends the protocol.

[defmulti](#)

Creates a new multimethod with the associated dispatch function.

[top](#)

deftype

```
(deftype name fields)
(deftype name fields validator)
```

Defines a new custom *record* type for the name with the fields.

The optional validator is a single arg function receiving the value as the argument and throwing an an exception if the value is not valid.

Venice implicitly creates a builder and a type check function suffixed with a dot and a question mark:

```
(deftype :point [x :long, y :long])

(point. 200 300)          ; builder
(point? (point. 200 300)) ; type check
```

The builder accepts values of any subtype of the field's type.

Validation example:

```
(deftype :point
  [x :long, y :long]
  (fn [t]
    (assert (pos? (:x t)) "x must be positive!"))))
```

```
(do
  (ns foo)
  (deftype :point [x :long, y :long])
  ; explicitly creating a custom type value
  (def x (. :point 100 200))
  ; Venice implicitly creates a builder function
  ; suffixed with a '.'
  (def y (point. 200 300))
  ; ... and a type check function
  (point? y)
  y)
=> {:custom-type* :foo/point :x 200 :y 300}
```

```
(do
  (ns foo)
  (deftype :point [x :long, y :long])
  (def x (point. 100 200))
  (type x))
=> :foo/point
```

```
(do
  (ns foo)
  (deftype :point [x :long, y :long]
    (fn [p]
      (assert (pos? (:x p)) "x must be positive")
      (assert (pos? (:y p)) "y must be positive"))))
  (def p (point. 100 200))
  [(:x p) (:y p)])
=> [100 200]
```

```
(do
  (ns foo)
  (deftype :named [name :string, value :any])
  (def x (named. "count" 200))
  (def y (named. "seq" [1 2]))
  [x y])
=> [{:custom-type* :foo/named :name "count" :value 200} {:custom-type* :foo/named :name "seq" :value [1 2]}]
```

;; modifying a custom type field

```
(do
  (deftype :point [x :long, y :long])
  (def p (point. 0 0))
  (def q (assoc p :x 1 :y 2)) ; q is a 'point'
  (pr-str q))
=> "{:custom-type* :user/point :x 1 :y 2}"
```

;; removing a custom type field

```
(do
```

```
(deftype :point [x :long, y :long])
(def p (point. 100 200))
(def q (dissoc p :x)) ; q is just a map now
(pr-str q)
=> "{:y 200}"
```

SEE ALSO

[deftype?](#)

Returns true if type is a custom type else false.

[deftype-of](#)

Defines a new custom wrapper type based on a base type.

[deftype-or](#)

Defines a new custom choice type.

[.](#)

Instantiates a custom type.

[deftype-describe](#)

Describes a custom type.

[Object](#)

Defines a protocol to customize the toString and/or the compareTo function of custom datatypes.

[assoc](#)

When applied to a map, returns a new map of the same type, that contains the mapping of key(s) to val(s). When applied to a vector, ...

[dissoc](#)

Returns a new coll of the same type, that does not contain a mapping for key(s)

[top](#)

deftype-describe

(deftype-describe type)

Describes a custom type.

```
(do
  (ns foo)
  (deftype :complex [real :long, imaginary :long])
  (deftype-describe :complex))

=> {:type :foo/complex :custom-type :record :field-defs ({:name :real :type :core/long :index 0I :nillable
false} {:name :imaginary :type :core/long :index 1I :nillable false}) :validation-fn nil}

(do
  (ns foo)
  (deftype-of :port :long)
  (deftype-describe :port))

=> {:custom-type :wrapping :base-type :core/long :type :foo/port :validation-fn nil}

(do
  (ns foo)
  (deftype-or :digit 0 1 2 3 4 5 6 7 8 9)
  (deftype-describe :digit))

=> {:type :foo/digit :custom-type :choice :values #{0 1 2 3 4 5 6 7 8 9}}
```

SEE ALSO

deftype

Defines a new custom record type for the name with the fields.

deftype?

Returns true if type is a custom type else false.

deftype-or

Defines a new custom choice type.

deftype-of

Defines a new custom wrapper type based on a base type.

..

Instantiates a custom type.

[top](#)

deftype-of

```
(deftype-of name base-type)
```

```
(deftype-of name base-type validator)
```

Defines a new custom *wrapper* type based on a base type.

Venice implicitly creates a builder and a type check function suffixed with a dot and a question mark:

```
(deftype-of :port :long)
```

```
(port. 8080) ; builder
```

```
(port? (port. 8080)) ; type check
```

```
(do
  (ns foo)
  (deftype-of :email-address :string)
  ; explicitly creating a wrapper type value
  (def x (. :email-address "foo@foo.org"))
  ; Venice implicitly creates a builder function
  ; suffixed with a '.'
  (def y (email-address. "foo@foo.org"))
  ; ... and a type check function
  (email-address? y)
  y)
=> "foo@foo.org"
```

```
(do
  (ns foo)
  (deftype-of :email-address :string)
  (str "Email: " (email-address. "foo@foo.org")))
=> "Email: foo@foo.org"
```

```
(do
  (ns foo)
  (deftype-of :email-address :string)
  (def x (email-address. "foo@foo.org"))
  [(type x) (supertype x)])
=> [:foo/email-address :core/string]
```

```
(do
  (ns foo)
  (deftype-of :email-address
              :string
```

```
      str/valid-email-addr?)
  (email-address. "foo@foo.org"))
=> "foo@foo.org"
```

```
(do
  (ns foo)
  (deftype-of :contract-id :long)
  (contract-id. 100000))
=> 100000
```

```
(do
  (ns foo)
  (deftype-of :my-long :long)
  (+ 10 (my-long. 100000)))
=> 100010
```

SEE ALSO

[deftype](#)

Defines a new custom record type for the name with the fields.

[deftype?](#)

Returns true if type is a custom type else false.

[deftype-or](#)

Defines a new custom choice type.

[.:](#)

Instantiates a custom type.

[deftype-describe](#)

Describes a custom type.

[top](#)

deftype-or

```
(deftype-or name val*)
```

Defines a new custom *choice* type.

Venice implicitly creates a builder and a type check function suffixed with a dot and a question mark:

```
(deftype-or :color :red :green :blue)

(color. :blue)           ; builder
(color? (color. :blue)) ; type check
```

```
(do
  (ns foo)
  (deftype-or :color :red :green :blue)
  ; explicitly creating a wrapper type value
  (def x (.: :color :red))
  ; Venice implicitly creates a builder function
  ; suffixed with a '.'
  (def y (color. :blue))
  ; ... and a type check function
  (color? y)
  y)
=> "blue"
```



```
(do
  (ns foo)
  (deftype-or :digit 0 1 2 3 4 5 6 7 8 9)
  (digit. 1))
=> 1

(do
  (ns foo)
  (deftype-or :long-or-double :long :double)
  (long-or-double. 1000))
=> 1000
```

SEE ALSO

[deftype](#)

Defines a new custom record type for the name with the fields.

[deftype?](#)

Returns true if type is a custom type else false.

[deftype-of](#)

Defines a new custom wrapper type based on a base type.

[..](#)

Instantiates a custom type.

[deftype-describe](#)

Describes a custom type.

[top](#)

deftype?

```
(deftype? type)
```

Returns true if `type` is a custom type else false.

```
(do
  (ns foo)
  (deftype :complex [real :long, imaginary :long])
  (deftype? :complex))
=> true

(do
  (ns foo)
  (deftype-of :email-address :string)
  (deftype? :email-address))
=> true

(do
  (ns foo)
  (deftype :complex [real :long, imaginary :long])
  (def x (complex. 100 200))
  (deftype? (type x)))
=> true
```

SEE ALSO

[deftype](#)

Defines a new custom record type for the name with the fields.

[deftype-of](#)

Defines a new custom wrapper type based on a base type.

[deftype-or](#)

Defines a new custom choice type.

[::](#)

Instantiates a custom type.

[deftype-describe](#)

Describes a custom type.

[top](#)

delay

`(delay & body)`

Takes a body of expressions and yields a Delay object that will invoke the body only the first time it is forced (with `force` or `deref / @`), and will cache the result and return it on all subsequent force calls.

```
(do
  (def x (delay (println "working...") 100))
  (deref x))
working...
=> 100
```

SEE ALSO

[deref](#)

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will ...

[force](#)

If x is a delay, returns its value, else returns x

[realized?](#)

Returns true if a value has been produced for a promise, delay, or future.

[delay?](#)

Returns true if x is a Delay created with delay

[memoize](#)

Returns a memoized version of a referentially transparent function.

[top](#)

delay-queue

`(delay-queue)`

Creates a new delay queue.

A delay-queue is an unbounded blocking queue of delayed elements, in which an element can only be taken when its delay has expired. The head of the queue is that delayed element whose delay expired furthest in the past. If no delay has expired there is no head and `poll!` will return nil. Unexpired elements cannot be removed using `take!` or `poll!`, they are otherwise treated as normal elements. For example, the `count` method returns the count of both expired and unexpired elements. This queue does not permit `nil` elements.

Example rate limiter:

```

(do
  (defprotocol RateLimiter (init [x]) (acquire [x]))

  (deftype :rate-limiter [queue                :core/delay-queue
                        limit-for-period      :long
                        limit-refresh-period :long]

    RateLimiter
    (init [this] (let [q (:queue this)
                      n (:limit-for-period this)]
                  (empty q)
                  (repeatedly n #(put! q :token 0))
                  this))
    (acquire [this] (let [q (:queue this)
                         p (:limit-refresh-period this)]
                      (take! q)
                      (put! q :token p)))))

;; create a limiter with a limit of 5 actions within a 2s period
(def limiter (init (rate-limiter. (delay-queue) 5 2000)))

;; test the limiter
(doseq [x (range 1 26)]
  (acquire limiter)
  (printf "%s: run %2d%n" (time/local-date-time) x)))

```

```

(let [q (delay-queue)]
  (put! q 1 100)
  (put! q 1 200)
  (take! q))
=> 1

```

SEE ALSO

[peek](#)

For a list, same as first, for a vector, same as last, for a stack the top element (or nil if the stack is empty), for a queue the ...

[put!](#)

Puts an item to a queue. The operation is synchronous, it waits indefinitely until the value can be placed on the queue. Returns always nil.

[take!](#)

Retrieves and removes the head value of the queue, waiting if necessary until a value becomes available.

[poll!](#)

Polls an item from a queue with an optional timeout in milliseconds. For an indefinite timeout pass the timeout value :indefinite.

[empty](#)

Returns an empty collection of the same category as coll, or nil if coll is nil. If the collection is mutable clears the collection ...

[empty?](#)

Returns true if x is empty. Accepts strings, collections and bytebufs.

[count](#)

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

[delay-queue?](#)

Returns true if coll is a delay-queue

[top](#)

delay-queue?

```
(delay-queue? coll)
```

Returns true if coll is a delay-queue

```
(delay-queue? (delay-queue))  
=> true
```

[top](#)

delay?

```
(delay? x)
```

Returns true if x is a Delay created with delay

```
(do  
  (def x (delay (println "working...") 100))  
  (delay? x))  
=> true
```

SEE ALSO

[delay](#)

Takes a body of expressions and yields a Delay object that will invoke the body only the first time it is forced (with force or deref ...

[deref](#)

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will ...

[realized?](#)

Returns true if a value has been produced for a promise, delay, or future.

[top](#)

deliver

```
(deliver ref value)
```

Delivers the supplied value to the promise, releasing any pending derefs. A subsequent call to deliver on a promise will have no effect.

```
(do  
  (def p (promise))  
  (deliver p 10)  
  (deliver p 20) ; no effect  
  @p)  
=> 10
```

SEE ALSO

[deliver-ex](#)

Delivers the supplied exception to the promise, releasing any pending derefs. A subsequent call to deliver on a promise will have no effect.

[promise](#)

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, ...

[realized?](#)

Returns true if a value has been produced for a promise, delay, or future.

[top](#)

deliver-ex

```
(deliver-ex ref ex)
```

Delivers the supplied exception to the promise, releasing any pending derefs. A subsequent call to deliver on a promise will have no effect.

```
(do
  (def p (promise))
  (deliver-ex p (ex :VncException "error"))
  (deliver p 20) ; no effect
  (try
    @p
    (catch :VncException e (ex-message e))))
=> "error"
```

SEE ALSO

[deliver](#)

Delivers the supplied value to the promise, releasing any pending derefs. A subsequent call to deliver on a promise will have no effect.

[promise](#)

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, ...

[realized?](#)

Returns true if a value has been produced for a promise, delay, or future.

[top](#)

deref

```
(deref x)
(deref x timeout-ms timeout-val)
```

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will block if computation is not complete. The variant taking a timeout can be used for futures and will return `timeout-val` if the timeout (in milliseconds) is reached before a value is available. If a future is deref'd and the waiting thread is interrupted the futures are cancelled.

```
(do
  (def counter (atom 10))
  (deref counter))
=> 10
```

```
(do
  (def counter (atom 10))
  @counter)
=> 10
```

```
(do
  (defn task [] 100)
  (let [f (future task)]
    (deref f)))
=> 100
```

```
(do
  (defn task [] 100)
```

```

(let [f (future task)]
  @f))
=> 100

(do
  (defn task [] 100)
  (let [f (future task)]
    (deref f 300 :timeout)))
=> 100

(do
  (def x (delay (println "working...") 100))
  @x)
working...
=> 100

(do
  (def p (promise))
  (deliver p 10)
  @p)
=> 10

(do
  (def x (agent 100))
  @x)
=> 100

(do
  (def counter (volatile 10))
  @counter)
=> 10

```

[top](#)

deref?

```
(deref? x)
```

Returns true if x is dereferencable.

```
(deref? (atom 10))
=> true
```

```
(deref? (delay 100))
=> true
```

```
(deref? (promise))
=> true
```

```
(deref? (future (fn [] 10)))
=> true
```

```
(deref? (volatile 100))
=> true
```

```
(deref? (agent 100))
=> true
```

```
(deref? (just 100))  
=> true
```

[top](#)

difference

```
(difference s1)  
(difference s1 s2)  
(difference s1 s2 & sets)
```

Return a set that is the first set without elements of the remaining sets

```
(difference (set 1 2 3))  
=> #{1 2 3}  
  
(difference (set 1 2) (set 2 3))  
=> #{1}  
  
(difference (set 1 2) (set 1) (set 1 4) (set 3))  
=> #{2}
```

SEE ALSO

[union](#)

Return a set that is the union of the input sets

[intersection](#)

Return a set that is the intersection of the input sets

[cons](#)

Returns a new collection where x is the first element and coll is the rest.

[conj](#)

Returns a new collection with the x, xs 'added'. (conj nil item) returns (item) and (conj item) returns item.

[disj](#)

Returns a new set with the x, xs removed.

[top](#)

digits

```
(digits x)
```

Returns the number of digits of x. The number x must be of type integer, long, or bigint

```
(digits 124)  
=> 3  
  
(digits -10)  
=> 2  
  
(digits 11111111111111111111111111111111N)  
=> 32
```

disj

```
(disj set x)
(disj set x & xs)
```

Returns a new set with the x, xs removed.

```
(disj (set 1 2 3) 3)
=> #{1 2}
```

dissoc

```
(dissoc coll key)
(dissoc coll key & ks)
```

Returns a new coll of the same type, that does not contain a mapping for key(s)

```
(dissoc {:a 1 :b 2 :c 3} :b)
=> {:a 1 :c 3}
```

```
(dissoc {:a 1 :b 2 :c 3} :c :b)
=> {:a 1}
```

```
(dissoc [1 2 3] 0)
=> [2 3]
```

```
(do
  (deftype :complex [real :long, imaginary :long])
  (def x (complex. 100 200))
  (def y (dissoc x :real))
  (pr-str y))
=> "{:imaginary 200}"
```

SEE ALSO

[assoc](#)

When applied to a map, returns a new map of the same type, that contains the mapping of key(s) to val(s). When applied to a vector, ...

[update](#)

Updates a value in an associative structure, where k is a key and f is a function that will take the old value and any supplied fargs ...

dissoc!

```
(dissoc! coll key)
(dissoc! coll key & ks)
```

Dissociates keys from a mutable map, returns the map


```
(dissoc! (mutable-map :a 1 :b 2 :c 3) :b)
=> {:a 1 :c 3}

(dissoc! (mutable-map :a 1 :b 2 :c 3) :c :b)
=> {:a 1}

(dissoc! (mutable-vector 1 2 3) 0)
=> [2 3]
```

SEE ALSO

[assoc!](#)

Associates key/vals with a mutable map, returns the map

[update!](#)

Updates a value in a mutable associative structure, where k is a key and f is a function that will take the old value and any supplied ...

[top](#)

dissoc-in

```
(dissoc-in m ks)
```

Dissociates an entry in a nested associative structure, where ks is a sequence of keys and returns a new nested structure.

```
(do
  (def users [ {:name "James" :age 26}
                {:name "John" :age 43} ])
  (dissoc-in users [1]))
=> [{:name "James" :age 26}]

(do
  (def users [ {:name "James" :age 26}
                {:name "John" :age 43} ])
  (dissoc-in users [1 :age]))
=> [{:name "James" :age 26} {:name "John"}]
```

[top](#)

distinct

```
(distinct coll)
```

Returns a collection with all duplicates removed.
Returns a stateful transducer when no collection is provided.

```
(distinct [1 2 3 4 2 3 4])
=> [1 2 3 4]

(distinct '(1 2 3 4 2 3 4))
=> (1 2 3 4)
```

SEE ALSO

[dedupe](#)

Returns a collection with all consecutive duplicates removed.

[distinct?](#)

Returns true if no two of the arguments are equal

[top](#)

distinct?

```
(distinct? x) (distinct? x y) (distinct? x y & more)
```

Returns true if no two of the arguments are equal

```
(distinct? 1 2 3)  
=> true
```

```
(distinct? 1 2 3 3)  
=> false
```

```
(distinct? 1 2 3 1)  
=> false
```

SEE ALSO

[distinct](#)

Returns a collection with all duplicates removed.

[top](#)

do

```
(do exprs)
```

Evaluates the expressions in order and returns the value of the last.

```
(do (println "Test...") (+ 1 1))  
Test...  
=> 2
```

[top](#)

doall

```
(doall coll)  
(doall n coll)
```

When lazy sequences are produced `doall` can be used to force any effects and realize the lazy sequence. Returns the realized items in a list!

```
(->> (lazy-seq #(rand-long 100))  
      (take 4)  
      (doall))  
=> (20 30 90 92)
```

```
(->> (lazy-seq #(rand-long 100))
      (doall 4))
=> (30 46 37 40)
```

SEE ALSO

lazy-seq

Creates a new lazy sequence.

cycle

Returns a lazy (infinite!) sequence of repetitions of the items in coll.

repeat

Returns a lazy sequence of x values or a collection with the value x repeated n times.

cons

Returns a new collection where x is the first element and coll is the rest.

top

dobench

```
(dobench iterations expr)
(dobench warm-up-iterations gc-runs iterations expr)
```

Runs the expr iterations times in the most effective way and returns a list of elapsed nanoseconds for each invocation. It's main purpose is supporting benchmark tests.

Note: For best performance enable `macroexpand-on-load` !

[illegible][illegible]

top

doc

(doc x)

Prints documentation for a var or special form given `x` as its name. Prints the definition of custom types.

Displays the source of a module if `x` is a module: (doc :ansi)

If the var could not be found, searches for a similar var with the **Levenshtein distance 1**.

E.g:

```
> (doc dac)
Symbol 'dac' not found!
```

Did you mean?

- dag/dag
- dec

(doc +)

```
(doc def)
```

```
(do
  (deftype :complex [real :long, imaginary :long])
  (doc :complex))
```

SEE ALSO

[ns-list](#)

Without arg lists the loaded namespaces, else lists all the symbols in the specified namespace ns.

[modules](#)

Lists the available Venice modules

[finder](#)

Finds symbols that match one more glob patterns or regular expressions.

top

docker/cmd

```
(docker/cmd & args)
```

Runs any Docker command.

```
(println (docker/cmd "ps" "--all"))

;; a single string argument works as well
(println (docker/cmd "ps --all"))

;; run a command with JSON output and parse the JSON output into
;; Venice data
;; use `apply` to apply a vector of arguments
(-<> (apply docker/cmd ["ps" "--all" "--format" "json"]))
  (:out <>)
  (str/split-lines <>)
  (str/join "," <>)
  (str "[" <> "]")
  (json/read-str <>))
```

top

docker/container-exec-by-name

```
(docker/container-exec-by-name name command)
```

Execute a command in the running container with the specified name (always in non detached mode).

Returns the captured stdout text if the command succeeds.

Throws `ShellException` if the command fails. The exception carries the exit code and the captured stderr text.

```
(docker/container-exec-by-name "myapp" "touch /tmp/execWorks")
```

SEE ALSO

[docker/container-exec-by-name&](#)

Execute a command in the running container with the specified name (always in detached mode).

[docker/run](#)

Create and run a new container from an image.

[docker/container-running-with-name?](#)

Checks if there is container with the specified name in 'running' state.

[docker/container-exec-by-name](#)

Execute a command in the running container with the specified name (always in non detached mode).

[docker/container-logs](#)

Returns the container logs.

[top](#)

docker/container-exec-by-name&

```
(docker/container-exec-by-name& name command)
```

Execute a command in the running container with the specified name (always in detached mode).

Returns always an empty string because the command is run in detached mode. To get the commands captured stdout text use `docker /container-exec-by-name` instead.

Throws a `ShellException` if the command fails. The `ShellException` carries the exit code, stdout, and stderr text.

```
(docker/container-exec-by-name& "myapp" "touch /tmp/execWorks")
```

SEE ALSO

[docker/container-exec-by-name](#)

Execute a command in the running container with the specified name (always in non detached mode).

[docker/run](#)

Create and run a new container from an image.

[docker/container-running-with-name?](#)

Checks if there is container with the specified name in 'running' state.

[docker/container-exec-by-name](#)

Execute a command in the running container with the specified name (always in non detached mode).

[docker/container-logs](#)

Returns the container logs.

[top](#)

docker/container-exists-with-name?

```
(docker/container-exists-with-name? name)
```

Returns true if there is container with the specified name else false.

```
(docker/container-exists-with-name? "myapp")
```

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-find-by-name](#)

Find all containers with a specified name

[top](#)

docker/container-find-by-name

([docker/container-find-by-name](#) name)

Find all containers with a specified name

([docker/container-find-by-name](#) "myapp")

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-exists-with-name?](#)

Returns true if there is container with the specified name else false.

[top](#)

docker/container-image-info-by-name

([docker/container-image-info-by-name](#) name)

Returns the image info for a container given by its name.

Returns a map (e.g.): { :image "arangodb/arangodb:3.10.10" :repo "arangodb/arangodb" :tag "3.10.10" }

([docker/container-image-info-by-name](#) "myapp")

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-find-by-name](#)

Find all containers with a specified name

[docker/container-exists-with-name?](#)

Returns true if there is container with the specified name else false.

[docker/container-status-by-name](#)

Returns the status of container with the specified name.

[top](#)

docker/container-logs

([docker/container-logs](#) name & options)

Returns the container logs.

Options:

<code>:tail n</code>	Number of lines to show from the end of the logs
<code>:since ts</code>	Show logs since timestamp or relative (e.g. "42m" for 42 minutes)
<code>:until ts</code>	Show logs until timestamp or relative (e.g. "42m" for 42 minutes)
<code>:follow {true, false}</code>	Follow log output
<code>:details {true, false}</code>	Show extra details provided to logs

```
(docker/container-logs "myapp")
```

```
(docker/container-logs "myapp" :since "2m")
```

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/logs](#)

Get the logs of a container

[docker/container-running-with-name?](#)

Checks if there is container with the specified name in 'running' state.

[top](#)

docker/container-purge-by-name

```
(docker/container-purge-by-name name)
```

Removes a container and its image.

```
(docker/container-purge-by-name "myapp")
```

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-find-by-name](#)

Find all containers with a specified name

[docker/container-exists-with-name?](#)

Returns true if there is container with the specified name else false.

[docker/container-status-by-name](#)

Returns the status of container with the specified name.

[top](#)

docker/container-remove-by-name

```
(docker/container-remove-by-name name)
```

Removes a container with the specified name.

([docker/container-remove-by-name](#) "myapp")

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-find-by-name](#)

Find all containers with a specified name

[docker/container-exists-with-name?](#)

Returns true if there is container with the specified name else false.

[docker/container-status-by-name](#)

Returns the status of container with the specified name.

[top](#)

docker/container-running-with-name?

([docker/container-running-with-name?](#) name)

Checks if there is container with the specified name in 'running' state.

Returns true if running else false.

([docker/container-running-with-name?](#) "myapp")

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-start-by-name](#)

Starts a container with the specified name.

[docker/container-stop-by-name](#)

Stops a container with the specified name.

[top](#)

docker/container-start-by-name

([docker/container-start-by-name](#) name)

Starts a container with the specified name.

([docker/container-start-by-name](#) "myapp")

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-running-with-name?](#)

Checks if there is container with the specified name in 'running' state.

[docker/container-stop-by-name](#)

Stops a container with the specified name.

[docker/container-remove-by-name](#)

Removes a container with the specified name.

[docker/container-status-by-name](#)

Returns the status of container with the specified name.

[docker/container-logs](#)

Returns the container logs.

[top](#)

docker/container-status-by-name

([docker/container-status-by-name](#) name)

Returns the status of container with the specified name.

([docker/container-status-by-name](#) "myapp")

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-find-by-name](#)

Find all containers with a specified name

[docker/container-exists-with-name?](#)

Returns true if there is container with the specified name else false.

[docker/container-remove-by-name](#)

Removes a container with the specified name.

[top](#)

docker/container-stop-by-name

([docker/container-stop-by-name](#) name)

([docker/container-stop-by-name](#) name time)

Stops a container with the specified name.

([docker/container-stop-by-name](#) "myapp")

SEE ALSO

[docker/run](#)

Create and run a new container from an image.

[docker/container-running-with-name?](#)

Checks if there is container with the specified name in 'running' state.

[docker/container-stop-by-name](#)

Stops a container with the specified name.

[docker/container-remove-by-name](#)

Removes a container with the specified name.

[docker/container-status-by-name](#)

Returns the status of container with the specified name.

[docker/container-logs](#)
Returns the container logs.

[top](#)

docker/cp

(docker/cp src-path dst-path & options)

Copy files/folders between a container and the local filesystem

Options:

:archive {true, false}	Archive mode (copy all uid/gid information)
:follow-link {true, false}	Always follow symbol link in SRC_PATH
:quiet {true, false}	Suppress progress output during copy. Progress output is automatically suppressed if no terminal is attached

```
;; Copy file from host to docker container
(docker/cp "data.txt" "74789744g489:/data.txt")

;; Copy file from docker container to host
(docker/cp "74789744g489:/data.txt" "data.txt")

;; Copy a folder from host to docker container
(docker/cp "Desktop/images" "74789744g489:/root/img_files/car_photos/images")

;; Copy a folder from docker container to host
(docker/cp "74789744g489:/root/img_files/car_photos/images Desktop/images")
```

SEE ALSO

[docker/diff](#)
Inspect changes to files or directories on a container's filesystem.

[docker/ps](#)
List containers.

[docker/run](#)
Create and run a new container from an image.

[top](#)

docker/debug

(docker/debug mode)

Sets the debugging mode.

Without argument returns the current debug mode.

Mode:

:off	No debug output
:on	Prints the raw docker command line to the current stdout channel ahead of running the command
:on-no-exec	Prints the raw docker command line to the current stdout channel without running the command

```
(docker/debug :on)
```

```
(docker/debug :on-no-exec)
```

```
(docker/debug :off)
```

[top](#)

docker/diff

```
(docker/diff container & options)
```

Inspect changes to files or directories on a container's filesystem.

Options:

:format {string, json} Returns the output either as a string or as JSON data

```
(println (docker/diff "74789744g489"))
```

```
(docker/diff "74789744g4892" :format :json)
```

SEE ALSO

[docker/cp](#)

Copy files/folders between a container and the local filesystem

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/exec

```
(docker/exec container command args)
```

Execute a command in a running container (always in non detached mode).

Returns the captured stdout text if the command succeeds.

Throws `ShellException` if the command fails. The exception carries the exit code and the captured stderr text.

```
(docker/exec "74789744g489" "touch" "/tmp/execWorks")
```

```
(println (docker/exec "74789744g489" "ls" "-la" "/var"))
```

SEE ALSO

[docker/exec&](#)

Execute a command in a running container (always in detached mode).

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

[docker/exec&](#)

([docker/exec&](#) container command args)

Execute a command in a running container (always in detached mode).

Returns always an empty string because the command is run in detached mode. To get the commands captured stdout text use `docker/exec` instead.

Throws `ShellException` if the command fails. The `ShellException` carries the exit code, stdout, and stderr text.

```
(docker/exec& "74789744g489" "touch" "/tmp/execWorks")
```

```
(docker/exec& "74789744g489" "ls" "/var")
```

SEE ALSO

[docker/exec](#)

Execute a command in a running container (always in non detached mode).

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

[docker/image-prune](#)

([docker/image-prune](#) & options)

Remove unused images.

If `:all true` is specified, will also remove all images not referenced by any container. This is what you usually expect

Returns the stdout text from the command.

Options:

`:all {true, false}` Remove all unused images, not just dangling ones

```
(println (docker/image-prune))
```

```
(println (docker/image-prune :all true))
```

SEE ALSO

[docker/images](#)

List images.

[docker/image-pull](#)

Download an image from a registry.

[docker/rmi](#)

Remove an image.

[docker/image-rm](#)

Remove an image.

[top](#)

docker/image-pull

(docker/image-pull name & options)

Download an image from a registry.

Images can be pulled by name, name and tag, or digest

Returns the stdout text from the command.

Options:

:quiet {true, false} Suppress verbose output

```
(println (docker/image-pull "arangodb/arangodb:3.10.10"))
```

```
(println (docker/image-pull "arangodb/arangodb"))
```

SEE ALSO

[docker/images](#)

List images.

[docker/rmi](#)

Remove an image.

[docker/image-rm](#)

Remove an image.

[docker/image-prune](#)

Remove unused images.

[top](#)

docker/image-ready?

(docker/image-ready? repo tag)

Returns true if the image exists locally (is pulled) else false.

```
(docker/image-ready? "arangodb/arangodb" "3.10.10")
```

SEE ALSO

[docker/images](#)

List images.

[docker/images-query-by-repo](#)

Returns all pulled local images for a given repo.

[top](#)

docker/image-rm

```
(docker/image-rm image)
```

Remove an image.

```
(println (docker/image-rm "184e47dd1c58"))
```

SEE ALSO

[docker/images](#)

List images.

[docker/image-pull](#)

Download an image from a registry.

[docker/rmi](#)

Remove an image.

[docker/image-prune](#)

Remove unused images.

[top](#)

docker/images

```
(docker/images & options)
```

List images.

Options:

:all {true, false}	Show all images (default hides intermediate images)
:digests {true, false}	Show digests
:quiet {true, false}	If true only display image IDs
:no-trunc {true, false}	Don't truncate output
:format f	Returns the output either as a table string or as JSON data. The format is one of {table, json}

```
(println (docker/images :format :table))
```

```
(docker/images :quiet true :no-trunc true :format :json)
```

```
(println (docker/images :format :json))
```

SEE ALSO

[docker/image-pull](#)

Download an image from a registry.

[docker/rmi](#)

Remove an image.

[docker/image-rm](#)

Remove an image.

[docker/image-prune](#)

Remove unused images.

[docker/run](#)

Create and run a new container from an image.

[docker/images-query-by-repo](#)

Returns all pulled local images for a given repo.

[docker/image-ready?](#)

Returns true if the image exists locally (is pulled) else false.

[top](#)

docker/images-query-by-repo

```
(docker/images-query-by-repo repo)
```

Returns all pulled local images for a given repo.

```
(docker/images-query-by-repo "arangodb/arangodb")
```

```
;; return a list of ids for "arangodb/arangodb" images
(->> (docker/images-query-by-repo "arangodb/arangodb")
      (map #(get % "ID")))
```

SEE ALSO

[docker/images](#)

List images.

[docker/image-ready?](#)

Returns true if the image exists locally (is pulled) else false.

[top](#)

docker/logs

```
(docker/logs container & options)
```

Get the logs of a container

Options:

:tail n	Number of lines to show from the end of the logs
:since ts	Show logs since timestamp or relative (e.g. "42m" for 42 minutes)
:until ts	Show logs until timestamp or relative (e.g. "42m" for 42 minutes)
:	Show timestamps
timestamps {true, false}	
:follow {true, false}	Follow log output
:details {true, false}	Show extra details provided to logs
:stream {: out, :err, : out+err}	Return the :out and/or :err stream from the logs. Defaults to :out

```
(docker/logs "74789744g489")
```

```
(docker/logs "74789744g489" :tail 100 :timestamps true :stream :out+err)
```

```
(docker/logs "74789744g489" :since "60m" :until "30m")
```

SEE ALSO

[docker/pause](#)

Pause all processes within a container

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/pause

```
(docker/pause container)
```

Pause all processes within a container

```
(docker/pause "74789744g489")
```

SEE ALSO

[docker/unpause](#)

Unpause all processes within a container

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/prune

```
(docker/prune)
```

Remove all stopped containers.

```
(docker/prune)
```

SEE ALSO

[docker/rm](#)

Remove a container.

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

docker/ps

(docker/ps & options)

List containers.

Options:

:all {true, false}	Show all containers (default shows just running)
:last n	Show n last created containers
:quiet {true, false}	If true only display container IDs
:no-trunc {true, false}	Don't truncate output
:format {;table, ;json}	Returns the output either as a table string or as JSON data

```
(println (docker/ps :all true :format :table))

(docker/ps :all true :format :json)

(docker/ps :all true :no-trunc true :format :json)

(docker/ps :all true :no-trunc true :last 3 :format :json)

(println (docker/ps :all true :format :json))
```

SEE ALSO

[docker/start](#)

Start a stopped container.

[docker/stop](#)

Stop a container.

[docker/rm](#)

Remove a container.

[docker/run](#)

Create and run a new container from an image.

docker/rm

(docker/rm container & options)

Remove a container.

Options:

:force {true, false}	Force the removal of a running container (uses SIGKILL)
:link link	Remove the specified link
:volumes {true, false}	Remove anonymous volumes associated with the container

```
(docker/rm "74789744g489")
```

SEE ALSO

[docker/prune](#)

Remove all stopped containers.

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/rmi

(docker/rmi image & options)

Remove an image.

Images can be removed by name, name and tag, or image id

Options:

:force {true, false}	Force removal of the image
:no-prune {true, false}	Do not delete untagged parents

```
(println (docker/rmi "arangodb/arangodb:3.10.10" :force true))
```

SEE ALSO

[docker/images](#)

List images.

[docker/image-pull](#)

Download an image from a registry.

[docker/image-rm](#)

Remove an image.

[docker/image-prune](#)

Remove unused images.

[top](#)

docker/run

(docker/run image & options)

Create and run a new container from an image.

Images can be run by name, name and tag, or image id

Options:

:detach {true, false}	Run container in background and return container ID
:attach s	Attach to STDIN, STDOUT or STDERR. Use one of {:stdin, :stdout, :stderr}
:publish port	Publish a container's port to the host. To expose port 8080 inside the container to port 3000 outside the container, pass "3000:8080"
:envs vars	Set environment variable (a sequence of env var defs)
:memory limit	Memory limit

<code>:name name</code>	Assign a name to the container
<code>:quiet {true, false}</code>	Suppress the pull output
<code>:volumes vol</code>	Bind mount a volume (a sequence of volume defs)
<code>:workdir dir</code>	Working directory inside the container
<code>:args args</code>	Arguments passed to container process (a sequence of args or a string)

See also `cargo/start` / `cargo/stop` for a smarter way to start/stop a container.

```
;; Run an ArangoDB container (use bind mounts, very slow on macOSX)
(docker/run "arangodb/arangodb:3.10.10"
  :name "myapp"
  :publish [ "8529:8529" ]
  :detach true
  :envs [ "ARANGO_ROOT_PASSWORD=xxxxxx"
    "ARANGODB_OVERRIDE_DETECTED_TOTAL_MEMORY=8G"
    "ARANGODB_OVERRIDE_DETECTED_NUMBER_OF_CORES=1"]
  :volumes [ "/Users/foo/arangodb/db:/var/lib/arangodb3"
    "/Users/foo/arangodb/apps:/var/lib/arangodb3-apps" ])

;; Run an ArangoDB container (use docker volume, faster than bind mount)
(do
  (docker/volume-create "arangodb-db")
  (docker/volume-create "arangodb-apps")
  (docker/run "arangodb/arangodb:3.10.10"
    :name "myapp"
    :publish [ "8529:8529" ]
    :detach true
    :envs [ "ARANGO_ROOT_PASSWORD=xxxxxx"
      "ARANGODB_OVERRIDE_DETECTED_TOTAL_MEMORY=8G"
      "ARANGODB_OVERRIDE_DETECTED_NUMBER_OF_CORES=1"]
    :volumes [ "arangodb-db:/var/lib/arangodb3"
      "arangodb-apps:/var/lib/arangodb3-apps" ]
    :args [ "--database.auto-upgrade" ]))
```

SEE ALSO

[cargo/start](#)

Starts a container.

[docker/images](#)

List images.

[docker/ps](#)

List containers.

[docker/start](#)

Start a stopped container.

[docker/stop](#)

Stop a container.

[docker/rm](#)

Remove a container.

[docker/prune](#)

Remove all stopped containers.

[docker/exec](#)

Execute a command in a running container (always in non detached mode).

[docker/cp](#)

Copy files/folders between a container and the local filesystem

[docker/diff](#)

Inspect changes to files or directories on a container's filesystem.

[docker/pause](#)

Pause all processes within a container

[docker/unpause](#)

Unpause all processes within a container

[docker/cp](#)

Copy files/folders between a container and the local filesystem

[docker/logs](#)

Get the logs of a container

[docker/container-find-by-name](#)

Find all containers with a specified name

[docker/container-exists-with-name?](#)

Returns true if there is container with the specified name else false.

[docker/container-running-with-name?](#)

Checks if there is container with the specified name in 'running' state.

[docker/container-start-by-name](#)

Starts a container with the specified name.

[docker/container-stop-by-name](#)

Stops a container with the specified name.

[docker/container-remove-by-name](#)

Removes a container with the specified name.

[docker/container-status-by-name](#)

Returns the status of container with the specified name.

[docker/container-exec-by-name](#)

Execute a command in the running container with the specified name (always in non detached mode).

[docker/container-logs](#)

Returns the container logs.

[docker/container-purge-by-name](#)

Removes a container and its image.

[docker/container-image-info-by-name](#)

Returns the image info for a container given by its name.

[top](#)

docker/start

(docker/start container & options)

Start a stopped container.

Options:

:attach {true, false} Attach STDOUT/STDERR and forward signals

See also [cargo/start](#) / [cargo/stop](#) for a smarter way to start/stop a container.

([docker/start](#) "74789744g489")

SEE ALSO

[cargo/start](#)

Starts a container.

[docker/container-start-by-name](#)

Starts a container with the specified name.

[docker/stop](#)

Stop a container.

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/stop

(`docker/stop` container & options)

Stop a container.

Options:

:signal name Signal to send to the container

:time n Seconds to wait before killing the container

See also [cargo/start](#) / [cargo/stop](#) for a smarter way to start/stop a container.

(`docker/stop` "74789744g489" :time 30)

SEE ALSO

[cargo/stop](#)

Stops a container

[docker/container-stop-by-name](#)

Stops a container with the specified name.

[docker/start](#)

Start a stopped container.

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/unpause

(`docker/unpause` container)

Unpause all processes within a container

(`docker/unpause` "74789744g489")

SEE ALSO

[docker/pause](#)

Pause all processes within a container

[docker/ps](#)

List containers.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/version

(docker/version & options)

Returns the Docker version.

Options:

:format f Returns the output either as a string or as JSON data. The format is one of {string, json}

:version v Returns full (default), server, or client version. The version is one of {full, server, client}

(docker/version)

(docker/version :version :client)

(docker/version :version :server)

(docker/version :format :json)

(println (docker/version :format :string))

SEE ALSO

[docker/images](#)

List images.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/volume-create

(docker/volume-create vname & options)

Create a volume.

(docker/volume-create "hello")

SEE ALSO

[docker/volume-list](#)

List all the volumes known to Docker.

[docker/volume-inspect](#)

Inspects a volume.

[docker/volume-rm](#)

Remove a volume.

[docker/volume-prune](#)

Remove all unused local volumes. Unused local volumes are those which are not referenced by any containers. Removes both named and ...

[docker/volume-exists?](#)

Returns true if the volume with the specified name exists.

[top](#)

docker/volume-exists?

```
(docker/volume-exists? name)
```

Returns true if the volume with the specified name exists.

```
(docker/volume-exists? "hello")
```

SEE ALSO

[docker/volume-list](#)

List all the volumes known to Docker.

[top](#)

docker/volume-inspect

```
(docker/volume-inspect vname & options)
```

Inspects a volume.

Options:

:format {;string ;json} Returns the output either as a ascii or as JSON data

```
(docker/volume-inspect "hello")
```

SEE ALSO

[docker/volume-list](#)

List all the volumes known to Docker.

[docker/volume-create](#)

Create a volume.

[docker/volume-inspect](#)

Inspects a volume.

[docker/volume-prune](#)

Remove all unused local volumes. Unused local volumes are those which are not referenced by any containers. Removes both named and ...

[docker/volume-exists?](#)

Returns true if the volume with the specified name exists.

[top](#)

docker/volume-list

([docker/volume-list](#) & options)

List all the volumes known to Docker.

Options:

`:quiet {true, false}` Only display volume names
`:format {;table, ;json}` Returns the output either as a ascii table or as JSON data

([docker/volume-list](#))

SEE ALSO

[docker/volume-create](#)

Create a volume.

[docker/volume-inspect](#)

Inspects a volume.

[docker/volume-rm](#)

Remove a volume.

[docker/volume-prune](#)

Remove all unused local volumes. Unused local volumes are those which are not referenced by any containers. Removes both named and ...

[docker/volume-exists?](#)

Returns true if the volume with the specified name exists.

[docker/images](#)

List images.

[docker/run](#)

Create and run a new container from an image.

[top](#)

docker/volume-prune

([docker/volume-prune](#))

Remove all unused local volumes. Unused local volumes are those which are not referenced by any containers. Removes both named and anonymous volumes!

([docker/volume-prune](#))

SEE ALSO

[docker/volume-list](#)

List all the volumes known to Docker.

[docker/volume-create](#)

Create a volume.

[docker/volume-inspect](#)

Inspects a volume.

[docker/volume-rm](#)

Remove a volume.

[docker/volume-exists?](#)

Returns true if the volume with the specified name exists.

docker/volume-rm

(docker/volume-rm name)

Remove a volume.

(docker/volume-remove "hello")

SEE ALSO

[docker/volume-list](#)

List all the volumes known to Docker.

[docker/volume-create](#)

Create a volume.

[docker/volume-inspect](#)

Inspects a volume.

[docker/volume-prune](#)

Remove all unused local volumes. Unused local volumes are those which are not referenced by any containers. Removes both named and ...

[docker/volume-exists?](#)

Returns true if the volume with the specified name exists.

docker/wait

(docker/wait & containers)

Block until one or more containers stop, then return their exit codes

(docker/wait "74789744g4892" "2341428e53535")

SEE ALSO

[docker/ps](#)

List containers.

[docker/rm](#)

Remove a container.

[docker/run](#)

Create and run a new container from an image.

docoll

(docoll f coll)

Applies f to the items of the collection presumably for side effects. Returns nil.

If `coll` is a lazy sequence, `docoll` iterates over the lazy sequence and realizes value by value while calling function `f` on the realized values.

```
(docoll #(println %) [1 2 3 4])
1
2
3
4
=> nil

(docoll (fn [[k v]] (println (pr-str k v)))
  {:a 1 :b 2 :c 3 :d 4})
:a 1
:b 2
:c 3
:d 4
=> nil

;; docoll all elements of a queue. calls (take! queue) to get the
;; elements of the queue.
;; note: use nil to mark the end of the queue otherwise docoll will
;; block forever!
(let [q (conj! (queue) 1 2 3 nil)]
  (docoll println q))
1
2
3
=> nil

;; lazy sequence
(let [q (conj! (queue) 1 2 3 nil)]
  (defn f []
    (let [v (poll! q)]
      (println "Producing " v)
      v))
    (docoll #(println "Collecting" %)
      (lazy-seq f)))
Producing 1
Collecting 1
Producing 2
Collecting 2
Producing 3
Collecting 3
Producing nil
=> nil
```

SEE ALSO

[mapv](#)

Returns a vector consisting of the result of applying `f` to the set of first items of each `coll`, followed by applying `f` to the set of ...

[top](#)

done?

```
(done? f)
```

Returns true if the future or promise is done otherwise false

```
(do
  (def wait (fn [] (sleep 200) 100))
  (let [f (future wait)]
    (sleep 50)
    (printf "After 50ms: done=%b\n" (done? f))
    (sleep 300)
    (printf "After 300ms: done=%b\n" (done? f))))
After 50ms: done=false
After 300ms: done=true
=> nil
```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[realized?](#)

Returns true if a value has been produced for a promise, delay, or future.

[cancel](#)

Cancels a future or a promise

[cancelled?](#)

Returns true if the future or promise is cancelled otherwise false

[top](#)

dorun

```
(dorun count expr)
```

Runs the `expr` `count` times in the most effective way. It's main purpose is supporting benchmark tests. Returns the expression result of the last invocation.

Note:

For best performance enable `macroexpand-on-load` ! The expression is evaluated for every run. Alternatively a zero or one arg function referenced by a symbol can be passed:

```
(let [f (fn [] (+ 1 1))]
  (dorun 10 f))
```

When passing a one arg function `dorun` passes the incrementing counter value (0..N) to the function:

```
(let [f (fn [x] (+ x 1))]
  (dorun 10 f))
```

```
(dorun 10 (+ 1 1))
=> 2
```

[top](#)

doseq

```
(doseq seq-exprs & body)
```

Repeatedly executes `body` (presumably for side-effects) with bindings and filtering as provided by `list-comp` . Does not retain the head of the sequence. Returns `nil` .

Supported modifiers are: `:when` predicate

```
(doseq [x (range 10)] (print x))
0123456789
=> nil

(doseq [x (range 10)] (print x) (print "-"))
0-1-2-3-4-5-6-7-8-9-
=> nil

(doseq [x (range 5)] (print (* x 2)))
02468
=> nil

(doseq [x (range 10) :when (odd? x)] (print x))
13579
=> nil

(doseq [x (range 10) :when (odd? x)] (print (* x 2)))
26101418
=> nil

(doseq [x [1 2 3] y [1 2 3]] (println [x y]))
[1 1]
[1 2]
[1 3]
[2 1]
[2 2]
[2 3]
[3 1]
[3 2]
[3 3]
=> nil

(doseq [[x y] [[0 1] [1 2]]] (println [x y]))
[0 1]
[1 2]
=> nil

(doseq [[k v] {:a 1 :b 2}] (println [k v]))
[:a 1]
[:b 2]
=> nil

(doseq [[c vals] (group-by count ["a" "as" "asd" "aa" "asdf" "qwer"])]
  (println c vals))
1 [a]
2 [as aa]
3 [asd]
4 [asdf qwer]
=> nil
```

SEE ALSO

[list-comp](#)

List comprehension. Takes a vector of one or more binding-form or collection-expr pairs, each followed by zero or more modifiers, and ...

[dotimes](#)

Repeatedly executes body with name bound to integers from 0 through n-1.

dotimes

```
(dotimes bindings & body)
```

Repeatedly executes body with name bound to integers from 0 through n-1.

```
(dotimes [n 3] (println (str "n is " n)))  
n is 0  
n is 1  
n is 2  
=> nil
```

SEE ALSO

[repeat](#)

Returns a lazy sequence of x values or a collection with the value x repeated n times.

[repeatedly](#)

Takes a function of no args, presumably with side effects, and returns a collection of n calls to it

[doseq](#)

Repeatedly executes body (presumably for side-effects) with bindings and filtering as provided by list-comp. Does not retain the head ...

[list-comp](#)

List comprehension. Takes a vector of one or more binding-form or collection-expr pairs, each followed by zero or more modifiers, and ...

[top](#)

doto

```
(doto x & forms)
```

Evaluates x then calls all of the methods and functions with the value of x supplied at the front of the given arguments. The forms are evaluated in order. Returns x.

```
(doto (. :java.util.HashMap :new)  
      (. :put :a 1)  
      (. :put :b 2))  
=> {"a" 1 "b" 2}
```

[top](#)

double

```
(double x)
```

Converts to double

```
(double 1)  
=> 1.0
```

```
(double nil)  
=> 0.0
```

```
(double false)
=> 0.0

(double true)
=> 1.0

(double 1.2)
=> 1.2

(double 1.2F)
=> 1.2000000476837158

(double 1.2M)
=> 1.2

(double "1.2")
=> 1.2
```

[top](#)

double-array

```
(double-array coll)
(double-array len)
(double-array len init-val)
```

Returns an array of Java primitive doubles containing the contents of coll or returns an array with the given length and optional init value.

To create an array of :java.lang.Double use:

```
(make-array :java.lang.Long 3)
```

```
(double-array '(1.0 2.0 3.0))
=> [1.0, 2.0, 3.0]

(double-array '(1I 2 3.2 3.56M))
=> [1.0, 2.0, 3.2, 3.56]

(double-array 10)
=> [0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0]

(double-array 10 42.0)
=> [42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0]
```

SEE ALSO

[java-double-list](#)

Converts a Venice list/vector to a Java Double list

[top](#)

double?

```
(double? n)
```

Returns true if n is a double

```
(double? 4.0)
=> true

(double? 4.0F)
=> false

(double? 3)
=> false

(double? 3I)
=> false

(double? 3.0M)
=> false

(double? true)
=> false

(double? nil)
=> false

(double? {})
=> false
```

[top](#)

drop

(drop n coll)

Returns a collection of all but the first n items in coll.
Returns a stateful transducer when no collection is provided.

```
(drop 3 [1 2 3 4 5])
=> [4 5]

(drop 10 [1 2 3 4 5])
=> []
```

[top](#)

drop-last

(drop-last n coll)

Return a sequence of all but the last n items in coll.
Returns a stateful transducer when no collection is provided.

```
(drop-last 3 [1 2 3 4 5])
=> [1 2]
```

```
(drop-last 10 [1 2 3 4 5])  
=> []
```

[top](#)

drop-while

```
(drop-while predicate coll)
```

Returns a list of the items in coll starting from the first item for which `(predicate item)` returns logical false.
Returns a stateful transducer when no collection is provided.

```
(drop-while neg? [-2 -1 0 1 2 3])  
=> [0 1 2 3]
```

[top](#)

empty

```
(empty coll)
```

Returns an empty collection of the same category as coll, or nil if coll is nil. If the collection is mutable clears the collection and returns the emptied collection.

```
(empty {:a 1})  
=> {}
```

```
(empty [1 2])  
=> []
```

```
(empty '(1 2))  
=> ()
```

[top](#)

empty-to-nil

```
(empty-to-nil x)
```

Returns nil if x is empty

```
(empty-to-nil "")  
=> nil
```

```
(empty-to-nil [])  
=> nil
```

```
(empty-to-nil '())  
=> nil
```



```
(empty-to-nil {})  
=> nil
```

[top](#)

empty?

```
(empty? x)
```

Returns true if x is empty. Accepts strings, collections and bytebufs.

```
(empty? {})  
=> true
```

```
(empty? [])  
=> true
```

```
(empty? '())  
=> true
```

```
(empty? nil)  
=> true
```

```
(empty? "")  
=> true
```

SEE ALSO

[not-empty?](#)

Returns true if x is not empty. Accepts strings, collections and bytebufs.

[top](#)

entries

```
(entries m)
```

Returns a collection of the map's entries.

```
(entries {:a 1 :b 2 :c 3})  
=> ([:a 1] [:b 2] [:c 3])
```

```
(let [e (entries {:a 1 :b 2 :c 3})]  
  (println (map key e))  
  (println (map val e)))  
(:a :b :c)  
(1 2 3)  
=> nil
```

```
;; compare to 'into'  
(let [e (into [] {:a 1 :b 2 :c 3})]  
  (println (map first e))  
  (println (map second e)))
```

```
(:a :b :c)
(1 2 3)
=> nil
```

SEE ALSO

[map](#)

Applies *f* to the set of first items of each coll, followed by applying *f* to the set of second items in each coll, until any one of the ...

[key](#)

Returns the key of the map entry.

[val](#)

Returns the val of the map entry.

[keys](#)

Returns a collection of the map's keys.

[vals](#)

Returns a collection of the map's values.

[map-entry](#)

Creates a new map entry

[top](#)

enum?

```
(enum? class)
```

Returns true if class is a Java *enum*.

Get all values of a Java *enum*:

```
(. :java.time.Month :values)
```

Get a Java *enum* value:

```
(let [jan (. :java.time.Month :JANUARY)]
  (. :java.time.LocalDate :of 1994 jan 21))
```

This can be simplified to:

```
(. :java.time.LocalDate :of 1994 :JANUARY 21)
```

```
(enum? :java.time.Month)
=> true
```

[top](#)

eval

```
(eval form)
```

Evaluates the form data structure (not text!) and returns the result.

```
(eval '(let [a 10] (+ 3 4 a)))
=> 17
```

```
(eval (list + 1 2 3))
=> 6
```

```
(let [s "(+ 2 x)" x 10]
  (eval (read-string s)))
=> 12
```

SEE ALSO

[read-string](#)

Reads Venice source from a string and transforms its content into a Venice data structure, following the rules of the Venice syntax.

[top](#)

even?

```
(even? n)
```

Returns true if n is even, throws an exception if n is not an integer

```
(even? 4)
=> true
```

```
(even? 3)
=> false
```

```
(even? 3I)
=> false
```

SEE ALSO

[odd?](#)

Returns true if n is odd, throws an exception if n is not an integer

[top](#)

every-pred

```
(every-pred p1 & p)
```

Takes a set of predicates and returns a function f that returns true if all of its composing predicates return a logical true value against all of its arguments, else it returns false. Note that f is short-circuiting in that it will stop execution on the first argument that triggers a logical false result against the original predicates.

```
((every-pred number?) 1)
=> true
```

```
((every-pred number?) 1 2)
=> true
```

```
((every-pred number? even?) 2 4 6)
=> true
```

[top](#)

every?

```
(every? pred coll)
```

Returns true if coll is a collection and the predicate is true for all collection items, false otherwise.

```
(every? number? nil)
=> false
```

```
(every? number? [])
=> true
```

```
(every? number? [1 2 3 4])
=> true
```

```
(every? number? [1 2 3 :a])
=> false
```

```
(every? #(>= % 10) [10 11 12])
=> true
```

SEE ALSO

[any?](#)

Returns true if the predicate is true for at least one collection item, false otherwise.

[not-any?](#)

Returns false if the predicate is true for at least one collection item, true otherwise

[not-every?](#)

Returns true if coll is a collection and the predicate is not true for all collection items, false otherwise.

[top](#)

ex

```
(ex class)
(ex class args*)
```

Creates an exception of type *class* with optional *args*. The *class* must be a subclass of :java.lang.Exception

The exception types:

- :java.lang.Exception
- :java.lang.RuntimeException
- :com.github.jlangch.venice.VncException
- :com.github.jlangch.venice.ValueException

are imported implicitly so its alias :Exception, :RuntimeException, :VncException, and :ValueException can be used.

Checked vs unchecked exceptions

All exceptions in Venice are *unchecked*.

If *checked* exceptions are thrown in Venice they are immediately wrapped in a :RuntimeException before being thrown!

If Venice catches a *checked* exception from a Java Interop call it wraps it in a :RuntimeException before handling it by the catch block selectors.

```

(try
  (throw (ex :VncException))
  (catch :VncException e "caught :VncException"))
=> "caught :VncException"

(try
  (throw (ex :RuntimeException "#test"))
  (catch :Exception e
    "msg: ~(ex-message e)"))
=> "msg: #test"

(try
  (throw (ex :ValueException 100))
  (catch :ValueException e
    "value: ~(ex-value e)"))
=> "value: 100"

(do
  (defn throw-ex-with-cause []
    (try
      (throw (ex :java.io.IOException "I/O failure"))
      (catch :Exception e
        (throw (ex :VncException "failure" (ex-cause e))))))
    (try
      (throw-ex-with-cause)
      (catch :Exception e
        "msg: ~(ex-message e), cause: ~(ex-message (ex-cause e))")))
=> "msg: failure, cause: I/O failure"

```

SEE ALSO

[throw](#)

Throws an exception.

[try](#)

Exception handling: try - catch - finally

[try-with](#)

try-with-resources allows the declaration of resources to be used in a try block with the assurance that the resources will be closed ...

[ex?](#)

Returns true if x is a an instance of :java.lang.Throwable

[ex-venice?](#)

Returns true if x is a an instance of :VncException

[top](#)

ex-cause

```
(ex-cause x)
```

Returns the exception cause or nil

```
(ex-cause (ex :VncException "a message" (ex :RuntimeException "..cause..")))
=> java.lang.RuntimeException: ..cause..
```

```
(ex-cause (ex :VncException "a message"))
=> nil
```

SEE ALSO

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of :java.lang.Exception

[ex-message](#)

Returns the message of the exception

[ex-value](#)

Returns the value associated with a :ValueException or nil if the exception is not a :ValueException

[top](#)

ex-java-stacktrace

```
(ex-java-stacktrace x)
(ex-java-stacktrace x format)
```

Returns the Java stacktrace for an exception.

The optional format (:string or :list) controls the format of the returned stacktrace. The default format is :string.

```
(println (ex-java-stacktrace (ex :RuntimeException "message")))

(println (ex-java-stacktrace (ex :VncException "message") :list))
```

SEE ALSO

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of :java.lang.Exception

[ex-venice-stacktrace](#)

Returns the Venice stacktrace for an exception or nil if the exception is not a venice exception.

[top](#)

ex-message

```
(ex-message x)
```

Returns the message of the exception

```
(ex-message (ex :VncException "a message"))
=> "a message"

(ex-message (ex :RuntimeException))
=> nil
```

SEE ALSO

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of :java.lang.Exception

[ex-cause](#)

Returns the exception cause or nil

[ex-value](#)

Returns the value associated with a :ValueException or nil if the exception is not a :ValueException

ex-value

```
(ex-value x)
```

Returns the value associated with a :ValueException or nil if the exception is not a :ValueException

```
(ex-value (ex :ValueException [10 20]))  
=> (10 20)
```

```
(ex-value (ex :RuntimeException))  
=> nil
```

SEE ALSO

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of :java.lang.Exception

[ex-message](#)

Returns the message of the exception

[ex-cause](#)

Returns the exception cause or nil

ex-venice-stacktrace

```
(ex-venice-stacktrace x)  
(ex-venice-stacktrace x format)
```

Returns the Venice stacktrace for an exception or nil if the exception is not a venice exception.

The optional format (:string or :list) controls the format of the returned stacktrace. The default format is :string.

```
(println (ex-venice-stacktrace (ex :ValueException [10 20])))  
Exception in thread "main" ValueException:
```

```
[Callstack]  
  at: ex (example: line 56, col 43)  
=> nil
```

```
(println (ex-venice-stacktrace (ex :RuntimeException "message")))  
nil  
=> nil
```

```
(println (ex-venice-stacktrace (ex :ValueException [10 20]) :list))  
({:fn ex :file example :line 56 :col 43})  
=> nil
```

SEE ALSO

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of :java.lang.Exception

[ex-java-stacktrace](#)

Returns the Java stacktrace for an exception.

[top](#)

[ex-venice?](#)

```
(ex-venice? x)
```

Returns true if x is a an instance of :VncException

```
(ex-venice? (ex :VncException))  
=> true
```

```
(ex-venice? (ex :RuntimeException))  
=> false
```

SEE ALSO

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of :java.lang.Exception

[ex?](#)

Returns true if x is a an instance of :java.lang.Throwable

[top](#)

[ex?](#)

```
(ex? x)
```

Returns true if x is a an instance of :java.lang.Throwable

```
(ex? (ex :RuntimeException))  
=> true
```

SEE ALSO

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of :java.lang.Exception

[ex-venice?](#)

Returns true if x is a an instance of :VncException

[top](#)

[excel/add-area-chart](#)

```
(add-area-chart sheet chart-title  
                chart-addr-range  
                legend-position  
                category-axis-title  
                category-axis-position  
                value-axis-title)
```



```
value-axis-position
three-dimensional?
categories-addr-range
series)
```

Adds an area chart.

Arguments:

chart-title	The chart title
chart-addr-range	The chart position in the Excel
legend-position	The legend position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
category-axis-title	The category axis title
category-axis-position	The category axis position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
value-axis-title	The value axis title
value-axis-position	The value axis position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
three-dimensional?	Render in 3D: <code>true</code> or <code>false</code>
categories-addr-range	The category names in the Excel
series	The value series data. 1 to N series

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")
        data  [ ["Year"   "Bears" "Dolphins" "Whales"]
                  ["2017"   8       150       80 ]
                  ["2018"  54       77       54 ]
                  ["2019"  93       32      100 ]
                  ["2020" 116       11       76 ]
                  ["2021" 137        6       93 ]
                  ["2022" 184        1       72 ]]]
    (excel/write-data sheet data)

    (excel/add-area-chart sheet
      "Bears Population"
      (excel/cell-address-range 10 25 1 7)
      :RIGHT
      "Year"
      :BOTTOM
      "Population"
      :LEFT
      false
      (excel/cell-address-range 2 7 1 1)
      [ (excel/area-data-series
          "Bears"
          (excel/cell-address-range 2 7 2 2)) ] ])

    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/add-line-chart](#)

Adds a line chart.

[excel/add-bar-chart](#)

Adds a bar chart.

[excel/add-pie-chart](#)

Adds a pie chart.

[excel/area-data-series](#)

Build an area chart data series

excel/add-bar-chart

```
(add-bar-chart sheet chart-title
               chart-addr-range
               legend-position
               category-axis-title
               category-axis-position
               value-axis-title
               value-axis-position
               three-dimensional?
               direction-bar?
               grouping
               vary-colors?
               categories-addr-range
               series)
```

Adds a bar chart.

Arguments:

chart-title	The chart title
chart-addr-range	The chart position in the Excel
legend-position	The legend position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
category-axis-title	The category axis title
category-axis-position	The category axis position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
value-axis-title	The value axis title
value-axis-position	The value axis position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
three-dimensional?	Render in 3D: <code>true</code> or <code>false</code>
direction-bar?	Render as horizontal bars or vertical columns: <code>true</code> or <code>false</code>
grouping	Bar grouping: <code>:STANDARD</code> , <code>:CLUSTERED</code> , <code>:STACKED</code> , <code>:PERCENT_STACKED</code>
vary-colors?	Vary the colors: <code>true</code> or <code>false</code>
categories-addr-range	The category names in the Excel
series	The value series data. 1 to N series

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")
        data [
          ["Year"   "Bears" "Dolphins" "Whales"]
          ["2017"   8       150       80 ]
          ["2018"   54      77        54 ]
          ["2019"   93      32        100 ]
          ["2020"   116     11        76 ]
          ["2021"   137     6         93 ]
          ["2022"   184     1         72 ]]]
    (excel/write-data sheet data)

    (excel/add-bar-chart sheet
                        "Bears Population"
                        (excel/cell-address-range 10 25 1 7)
                        :RIGHT
                        "Year")
```

```

:BOTTOM
"Population"
:LEFT
false
false
:STANDARD
false
(excel/cell-address-range 2 7 1 1)
[ (excel/bar-data-series
  "Bears"
  (excel/cell-address-range 2 7 2 2))
  (excel/bar-data-series
  "Dolphins"
  (excel/cell-address-range 2 7 3 3))
  (excel/bar-data-series
  "Whales"
  (excel/cell-address-range 2 7 4 4)) ])

(excel/write->file wbook "sample.xlsx"))

```

SEE ALSO

[excel/add-line-chart](#)

Adds a line chart.

[excel/add-area-chart](#)

Adds an area chart.

[excel/add-pie-chart](#)

Adds a pie chart.

[excel/bar-data-series](#)

Build a bar chart data series

[excel/cell-address-range](#)

Build a cell address range

[top](#)

excel/add-column

```

(add-column sheet title)
(add-column sheet title options)

```

Defines a column with optional attributes on the sheet.

Note: The column cell value is just read from the passed tabular dataset. If there is any mapping or conversion needed it has to be applied to the dataset before writing it to the sheet!

Options:

:id id	a column id
:field f	a field, e.g. :first-name
:width n	width in points, e.g. 100
:skip s	skip column, e.g. true, false
:header-style r	style name for header row, e.g. :header
:body-style r	style name for body rows, e.g. :body
:footer-style r	style name for footer row, e.g. :footer
:footer-value v	explicit text or numeric value for the column's footer cell, e.g. "done", 10000.00M, nil
:footer-aggregate e	aggregation mode for the column's footer cell value, e.g. {:min, :max, :avg, :sum, :none}

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :weight 70.5 }
                {:first "Sue" :last "Ford" :weight 54.2 } ]
        wbook (excel/writer :xlsx)]
    (excel/add-font wbook :header { :bold true })
    (excel/add-style wbook :header { :font :header
                                      :bg-color :GREY_25_PERCENT
                                      :h-align :center })
    (excel/add-style wbook :weight { :format, "#,##0.0"
                                      :h-align :right })

    (let [sheet (excel/add-sheet wbook "Sheet 1"
                                  { :no-header-row false
                                    :default-header-style :header })]
      (excel/add-column sheet "First Name" { :field :first })
      (excel/add-column sheet "Last Name" { :field :last })
      (excel/add-column sheet "Weight" { :field :weight
                                          :body-style :weight })

      (excel/write-items sheet data)
      (excel/auto-size-columns sheet)
      (excel/write->file wbook "sample.xlsx"))))
```

SEE ALSO

[excel/add-sheet](#)

Adds a sheet with optional attributes to an Excel.

[excel/add-font](#)

Add font with optional attributes to an Excel.

[excel/add-style](#)

Add a style with optional attributes to an Excel.

[top](#)

excel/add-font

```
(add-font wbook font-id)
(add-font wbook font-id options)
```

Add font with optional attributes to an Excel.

Options:

:name s	font name, e.g. 'Arial'
:height n	height in points, e.g. 12
:bold b	bold, e.g. true, false
:italic b	italic, e.g. true, false
:color c	color, either an Excel indexed color or a HTML color, e.g. :BLUE, "#00FF00" note: only XLSX supports 24 bit colors

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)]
    (excel/add-font wbook :header { :height 12
                                      :bold true
                                      :italic false
                                      :color :BLUE })
    (excel/add-style wbook :header { :font :header })
```

```
(let [sheet (excel/add-sheet wbook "Sheet 1"
                             { :no-header-row false
                               :default-header-style :header })]
  (excel/add-column sheet "First Name" { :field :first })
  (excel/add-column sheet "Last Name" { :field :last })
  (excel/add-column sheet "Age" { :field :age })
  (excel/write-items sheet data)
  (excel/auto-size-columns sheet)
  (excel/write->file wbook "sample.xlsx"))))
```

SEE ALSO

[excel/add-style](#)

Add a style with optional attributes to an Excel.

[excel/add-sheet](#)

Adds a sheet with optional attributes to an Excel.

[top](#)

excel/add-image

```
(add-image sheet row col data type)
(add-image sheet row col data type scale-X scale-Y)
```

Adds an image given by its binary data (a `bytebuf`) to a specific anchor cell given by its row and col. Optionally the image can be scaled by an X and Y axis factor. The image types `:PNG` and `:JPEG` are supported.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")
        image "com/github/jlangch/venice/images/venice.png"
        data (io/load-classpath-resource image)]
    (excel/add-image sheet 2 2 data :PNG)
    (excel/write->file wbook "sample.xlsx")))

(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")
        image "com/github/jlangch/venice/images/venice.png"
        data (io/load-classpath-resource image)]
    (excel/add-image sheet 2 2 data :PNG 0.5 0.5)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

[excel/add-line-chart](#)

```
(add-line-chart sheet chart-title
                chart-addr-range
                legend-position
                category-axis-title
                category-axis-position
                value-axis-title
                value-axis-position
                three-dimensional?
                vary-colors?
                categories-addr-range
                series)
```

Adds a line chart.

Arguments:

chart-title	The chart title
chart-addr-range	The chart position in the Excel
legend-position	The legend position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
category-axis-title	The category axis title
category-axis-position	The category axis position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
value-axis-title	The value axis title
value-axis-position	The value axis position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
three-dimensional?	Render in 3D: <code>true</code> or <code>false</code>
vary-colors?	Vary the colors: <code>true</code> or <code>false</code>
categories-addr-range	The category names in the Excel
series	The value series data. 1 to N series

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")
        data [["Year" "Bears" "Dolphins" "Whales"]
               ["2017" 8 150 80 ]
               ["2018" 54 77 54 ]
               ["2019" 93 32 100 ]
               ["2020" 116 11 76 ]
               ["2021" 137 6 93 ]
               ["2022" 184 1 72 ]]])
  (excel/write-data sheet data)

  (excel/add-line-chart sheet
    "Wildlife Population"
    (excel/cell-address-range 10 25 1 10)
    :RIGHT
    "Year"
    :BOTTOM
    "Population")
```

```

:LEFT
false
true
(excel/cell-address-range 2 7 1 1)
[ (excel/line-data-series
  "Bears"
  true
  :CIRCLE
  (excel/cell-address-range 2 7 2 2))
(excel/line-data-series
  "Dolphins"
  true
  :CIRCLE
  (excel/cell-address-range 2 7 3 3))
(excel/line-data-series
  "Whales"
  true
  :CIRCLE
  (excel/cell-address-range 2 7 4 4)) ]

(excel/write->file wbook "sample.xlsx"))

```

SEE ALSO

[excel/add-bar-chart](#)

Adds a bar chart.

[excel/add-area-chart](#)

Adds an area chart.

[excel/add-pie-chart](#)

Adds a pie chart.

[excel/line-data-series](#)

Build a line chart data series

[excel/cell-address-range](#)

Build a cell address range

[top](#)

excel/add-merge-region

```
(add-merge-region sheet row-from row-to col-from col-to)
```

Add a merge region to the sheet.

```

(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Population")]
    (excel/column-width sheet 2 70)
    (excel/column-width sheet 3 70)
    (excel/add-merge-region sheet 2 2 2 3)
    (excel/write-value sheet 2 2 "Contry Population")
    (excel/write-value sheet 3 2 "Country")
    (excel/write-value sheet 3 3 "Population")
    (excel/write-value sheet 4 2 "Germany")
    (excel/write-value sheet 4 3 83_783_942)
    (excel/write-value sheet 5 2 "Italy")
    (excel/write-value sheet 5 3 60_461_826)
    (excel/write-value sheet 6 2 "Austria")
  )

```

```
(excel/write-value sheet 6 3 9_006_398)
(excel/write->file wbook "sample.xlsx"))
```

SEE ALSO

[excel/add-sheet](#)

Adds a sheet with optional attributes to an Excel.

[top](#)

excel/add-pie-chart

```
(add-pie-chart sheet chart-title
                chart-addr-range
                legend-position
                three-dimensional?
                vary-colors?
                categories-addr-range
                series)
```

Adds a pie chart.

Arguments:

chart-title	The chart title
chart-addr-range	The chart position in the Excel
legend-position	The legend position: <code>:TOP</code> , <code>:TOP_RIGHT</code> , <code>:RIGHT</code> , <code>:BOTTOM</code> , <code>:LEFT</code>
three-dimensional?	Render in 3D: <code>true</code> or <code>false</code>
vary-colors?	Vary the colors: <code>true</code> or <code>false</code>
categories-addr-range	The category names in the Excel
series	The value series data. 1 series required

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")
        data [ ["Year" "Bears" "Dolphins" "Whales"]
                ["2017" 8 150 80 ]
                ["2018" 54 77 54 ]
                ["2019" 93 32 100 ]
                ["2020" 116 11 76 ]
                ["2021" 137 6 93 ]
                ["2022" 184 1 72 ]]]
    (excel/write-data sheet data)

    (excel/add-pie-chart sheet
                        "Wildlife Population 2017"
                        (excel/cell-address-range 10 25 1 7)
                        :RIGHT
                        false
                        true
                        (excel/cell-address-range 1 1 2 4)
                        [ (excel/pie-data-series
                          (excel/cell-address-range 2 2 2 4)) ] )

    (excel/write->file wbook "sample.xlsx"))
```

SEE ALSO

[excel/add-line-chart](#)

Adds a line chart.

[excel/add-bar-chart](#)

Adds a bar chart.

[excel/add-area-chart](#)

Adds an area chart.

[excel/pie-data-series](#)

Build a pie chart data series

[excel/cell-address-range](#)

Build a cell address range

[top](#)

excel/add-sheet

(add-sheet wbook title)

(add-sheet wbook title options)

Adds a sheet with optional attributes to an Excel.

Options:

:no-header-row b	without header row, e.g. true, false
:default-column-width n	default column width in points, e.g. 100
:default-header-style s	default header style, e.g. :header
:default-body-style s	default body style, e.g. :body
:default-footer-style s	default footer style, e.g. :footer
:merged-region r	merged region [row-from row-to col-from col-to], e.g. [1 1 4 10]
:display-zeros b	display zeros, e.g. true, false. Defines if a cell should show 0 (zero) when containing zero value. When false, cells with zero value appear blank instead of showing the number zero.

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)]
    (excel/add-font wbook :bold { :bold true })
    (excel/add-font wbook :italic { :italic true })
    (excel/add-style wbook :header { :font :bold })
    (excel/add-style wbook :body { :font :italic })
    (excel/add-style wbook :footer { :font :bold })

    (let [sheet (excel/add-sheet wbook "Sheet 1"
                                { :no-header-row false
```

```

:default-column-width 100
:default-header-style :header
:default-body-style :body
:default-footer-style :footer
:display-zeros true}}]
(excel/add-column sheet "First Name" { :field :first })
(excel/add-column sheet "Last Name" { :field :last })
(excel/add-column sheet "Age" { :field :age })
(excel/write-items sheet data)
(excel/auto-size-column sheet 1)
(excel/auto-size-column sheet 2)
(excel/auto-size-column sheet 3)
(excel/write->file wbook "sample.xlsx"))))

```

SEE ALSO

[excel/add-column](#)

Defines a column with optional attributes on the sheet.

[excel/add-merge-region](#)

Add a merge region to the sheet.

[top](#)

excel/add-style

```

(add-style wbook style-id)
(add-style wbook style-id options)

```

Add a style with optional attributes to an Excel.

Options:

:format s	cell format, e.g. "#0" Default formats: - long: "###0" - integer: "###0" - float: "###0.00" - double: "###0.00" - date: "d.m.yyyy" - datetime: "d.m.yyyy hh:mm:ss"
:font r	font name, e.g. :header
:bg-color c	background color, either an Excel indexed color or a HTML color, e.g. :PLUM, "#00FF00" Note: only XLSX supports 24 bit colors
:wrap-text b	wrap text, e.g. true, false
:h-align e	horizontal alignment {:left, :center, :right}
:v-align e	vertical alignment {:top, :middle, :bottom}
:rotation r	rotation angle [degree], e.g. 45
:border-top s	border top style, e.g. :thin
:border-right s	border right style, e.g. :none
:border-bottom s	border bottom style, e.g. :thin
:border-left s	border left style, e.g. :none

Available border styles:

:none	:dotted	:medium-dashed	:medium-dash-dot-dot
:thin	:thick	:dash-dot	:slanted-dash-dot
:medium	:double	:medium-dash-dot	
:dashed	:hair	:dash-dot-dot	

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :weight 70.5 }
                {:first "Sue" :last "Ford" :weight 54.2 } ]
        wbook (excel/writer :xlsx)]
    (excel/add-font wbook :header { :bold true })
    (excel/add-style wbook :header { :font :header
                                      :bg-color :GREY_25_PERCENT
                                      :h-align :center
                                      :rotation 0
                                      :border-top :thin
                                      :border-bottom :thin })
    (excel/add-style wbook :weight { :format "#,##0.0"
                                      :h-align :right })

    (let [sheet (excel/add-sheet wbook "Sheet 1"
                                  { :no-header-row false
                                    :default-header-style :header })]
      (excel/add-column sheet "First Name" { :field :first })
      (excel/add-column sheet "Last Name" { :field :last })
      (excel/add-column sheet "Weight" { :field :weight
                                          :body-style :weight })

      (excel/write-items sheet data)
      (excel/auto-size-columns sheet)
      (excel/write->file wbook "sample.xlsx"))))
```

SEE ALSO

[excel/add-font](#)

Add font with optional attributes to an Excel.

[excel/add-sheet](#)

Adds a sheet with optional attributes to an Excel.

[top](#)

excel/addr->string

```
(addr->string row col)
```

Returns an Excel A1-style cell address string representation for a row and column address

```
(excel/addr->string 1 3)
```

```
(excel/addr->string 30 56)
```

```
(do
  (load-module :excel)
  (let [data [ {:a 100 :b 200 }
                {:a 101 :b 201 }
                {:a 102 :b 202 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1" { :no-header-row true })
        addr #(excel/addr->string %1 %2)
        sum #(str "SUM(" %1 "," %2 ")")]
    (excel/add-column sheet "A" { :field :a })
    (excel/add-column sheet "B" { :field :b })
    (excel/add-column sheet "C" { :field :c })
    (excel/write-items sheet data))
```

```
(excel/cell-formula sheet 1 3 (sum (addr 1 1) (addr 1 2)))
(excel/cell-formula sheet 2 3 (sum (addr 2 1) (addr 2 2)))
(excel/cell-formula sheet 3 3 (sum (addr 3 1) (addr 3 2)))
(excel/evaluate-formulas wbook)
(excel/auto-size-columns sheet)
(excel/write->file wbook "sample.xlsx"))
```

SEE ALSO

[excel/col->string](#)

Returns an Excel A-style column number string representation for a column number

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[top](#)

excel/area-data-series

```
(area-data-series title data-address-range)
```

Build an area chart data series

Arguments:

title The series title

data-address-range The series data in the Excel

```
(excel/area-data-series "Countries" (excel/cell-address-range 2 2 1 5))
```

SEE ALSO

[excel/cell-address-range](#)

Build a cell address range

[top](#)

excel/auto-size-column

```
(auto-size-column sheet col)
```

Auto size the width of column col (1..n) in the sheet.

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-column sheet 1)
    (excel/auto-size-column sheet 2)
    (excel/auto-size-column sheet 3)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/auto-size-columns

```
(auto-size-columns sheet)
```

Auto size the width of all columns in the sheet.

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/bar-data-series

```
(bar-data-series title data-address-range)
```

Build a bar chart data series

Arguments:

title	The series title
data-address-range	The series data in the Excel

```
(excel/bar-data-series "Countries" (excel/cell-address-range 2 2 1 5))
```

SEE ALSO

[excel/cell-address-range](#)

Build a cell address range

[top](#)

excel/bg-color

```
(bg-color sheet row col color)
(bg-color sheet row col-start col-end color)
(bg-color sheet row-start row-end col-start col-end color & colors)
```

Sets a background color for a single cell, a range of columns within a row, or region of cells.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Data")]

    ;; single cells
    (excel/bg-color sheet 1 1 "#27ae60")
    (excel/bg-color sheet 1 2 "#52be80")
    (excel/bg-color sheet 1 3 "#7dcea0")

    ;; range of cells in row
    (excel/bg-color sheet 1 4 6 "#3498db")

    ;; area of cells
    (excel/bg-color sheet 1 6 7 9 "#aed6f1")
    (excel/bg-color sheet 1 6 10 12 "#bb8fce" "#d2b4de")
    (excel/bg-color sheet 1 6 13 15 "#f1c40f" "#f4d03f" "#f7dc6f")
    (excel/write->file wbook "sample.xlsx"))

  (do
    (load-module :excel)
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101 102]
                                [200 201 203]
                                [300 301 303]
                                [400 401 403]
                                [500 501 503]
                                [600 601 603]]))
```

```
(excel/bg-color sheet 1 6 1 3 "#a9caf5" "#d9e7fc")
(excel/write->file wbook "sample.xlsx"))
```

SEE ALSO

[excel/add-style](#)

Add a style with optional attributes to an Excel.

[excel/add-font](#)

Add font with optional attributes to an Excel.

[excel/cell-style](#)

Apply a defined cell style to a cell

[top](#)

excel/cell-address-range

```
(cell-address-range row-first row-last col-first col-last)
```

Build a cell address range

```
(excel/cell-address-range 1 2 1 10)
```

SEE ALSO

[excel/cell-address](#)

Returns the cell address in A1 style for a cell at row/col in a sheet

[top](#)

excel/cell-empty?

```
(cell-empty? sheet row col)
```

Returns true if the sheet cell given by row/col is empty.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101 102] [200 201 202]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    [(excel/cell-empty? sheet 1 1)
     (excel/cell-empty? sheet 2 1)
     (excel/cell-empty? sheet 3 1)]))
```

SEE ALSO

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

excel/read-string-val

Returns the sheet cell value as string.

excel/read-boolean-val

Returns the sheet cell value as boolean.

excel/read-long-val

Returns the sheet cell value as long.

excel/read-double-val

Returns the sheet cell value as double.

excel/read-date-val

Returns the sheet cell value as a date (:java.time.LocalDate).

excel/read-datetime-val

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[top](#)

excel/cell-formula

(cell-formula sheet row col formula)

Set a formula for a specific cell given by its row and col.

```
(do
  (load-module :excel)
  (let [data [ {:a 100 :b 200 }
                {:a 101 :b 201 }
                {:a 102 :b 202 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1" { :no-header-row true })]
    (excel/add-column sheet "A" { :field :a })
    (excel/add-column sheet "B" { :field :b })
    (excel/add-column sheet "C" { :field :c })
    (excel/write-items sheet data)
    (excel/cell-formula sheet 1 3 "SUM(A1,B1)")
    (excel/cell-formula sheet 2 3 "SUM(A2,B2)")
    (excel/cell-formula sheet 3 3 "SUM(A3,B3)")
    (excel/evaluate-formulas wbook)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

```
(do
  (load-module :excel)
  (let [data [ {:a 100 :b 200 }
                {:a 101 :b 201 }
                {:a 102 :b 202 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1" { :no-header-row true })]
    (excel/add-font wbook :bold { :bold true })
    (excel/add-style wbook :bold { :font :bold })
    (excel/add-column sheet "A" { :field :a })
    (excel/add-column sheet "B" { :field :b })
    (excel/add-column sheet "C" { :field :c })
    (excel/write-items sheet data)
    (excel/cell-formula sheet 1 3 "SUM(A1,B1)" :bold)
    (excel/cell-formula sheet 2 3 "SUM(A2,B2)" :bold)
    (excel/cell-formula sheet 3 3 "SUM(A3,B3)" :bold))
```



```
(excel/evaluate-formulas wbook)
(excel/auto-size-columns sheet)
(excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/addr->string](#)

Returns an Excel A1-style cell address string representation for a row and column address

[excel/sum-formula](#)

Returns a sum formula for the given cell area

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/cell-formula-result-type

```
(cell-formula-result-type sheet row col)
```

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown } after formula cell evaluation. For non formula cells this function is the same as the `cell-type` function.

```
(do
  (load-module :excel)

  (defn create-excel []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[10 20.123 {:formula "SUM(A1,B1)}]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (create-excel))
        sheet (excel/sheet wbook "Data")]
    (excel/evaluate-formulas wbook)
    (printf "Cell (1,3): %s\n" (excel/cell-type sheet 1 3))
    (printf "Cell (1,3): %s (formula result type)\n"
      (excel/cell-formula-result-type sheet 1 3))))
```

SEE ALSO

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

excel/read-string-val

Returns the sheet cell value as string.

excel/read-boolean-val

Returns the sheet cell value as boolean.

excel/read-long-val

Returns the sheet cell value as long.

excel/read-double-val

Returns the sheet cell value as double.

excel/read-date-val

Returns the sheet cell value as a date (:java.time.LocalDate).

excel/read-datetime-val

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[top](#)

excel/cell-style

(cell-style sheet row col style-id)

(cell-style sheet row-from row-to col-from col-to style-id)

Apply a defined cell style to a cell

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1" { :no-header-row false })]
    (excel/add-font wbook :bold { :bold true
                                   :color "#54039c" })
    (excel/add-style wbook :style-1 { :font :bold
                                       :h-align :left
                                       :rotation 0 })
    (excel/add-style wbook :style-2 { :bg-color "#cae1fa"
                                       :h-align :center
                                       :rotation 0
                                       :border-top :thin
                                       :border-left :thin
                                       :border-bottom :thin
                                       :border-right :thin})
    (excel/add-style wbook :style-3 { :h-align :right
                                       :format "#,##0.00" })

    (excel/write-value sheet 2 1 100)
    (excel/write-value sheet 2 2 200)
    (excel/write-value sheet 2 3 300)

    (excel/cell-style sheet 2 1 :style-1)
    (excel/cell-style sheet 2 2 :style-2)
    (excel/cell-style sheet 2 3 :style-3)

    (excel/write->file wbook "sample.xlsx"))))

(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1" { :no-header-row false })]
    (excel/add-style wbook :style { :bg-color "#cae1fa"
                                     :h-align :center
```

```

      :format "#,##0.00" })

(excel/write-value sheet 2 2 100)
(excel/write-value sheet 2 3 200)
(excel/write-value sheet 2 4 300)
(excel/write-value sheet 3 2 101)
(excel/write-value sheet 3 3 201)
(excel/write-value sheet 3 4 301)

(excel/cell-style sheet 2 3 2 4 :style)

(excel/write->file wbook "sample.xlsx"))))

```

SEE ALSO

[excel/add-style](#)

Add a style with optional attributes to an Excel.

[excel/add-font](#)

Add font with optional attributes to an Excel.

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[top](#)

excel/cell-type

```
(cell-type sheet row col)
```

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

Note:

1. Excel returns cells containing long, double, date or datetime values as `:numeric`. The reader decides how to read a numeric cell using either of `excel/read-long-val`, `excel/read-double-val`, or `excel/read-date-val`.
2. To evaluate formulas to values call `excel/evaluate-formulas` on the workbook the right after opening the excel document.

```

(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 "101" 102.0]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    [(excel/cell-type sheet 1 1)
     (excel/cell-type sheet 1 2)
     (excel/cell-type sheet 1 3)
     (excel/cell-type sheet 1 4)]))

```

SEE ALSO

[excel/cell-formula-result-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown } after formula ...

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-datetime-val](#)

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[top](#)

excel/clear-row

```
(clear-row sheet row)
```

Clears the values in a specific row in a sheet.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/write-value sheet 1 1 "John")
    (excel/write-value sheet 1 2 "Doe")
    (excel/write-value sheet 1 3 28)
    (excel/write-value sheet 2 1 "Sue")
    (excel/write-value sheet 2 2 "Ford")
    (excel/write-value sheet 2 3 26)
    (excel/clear-row sheet 2)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/delete-row](#)

Deletes a specific row from a sheet.

[excel/copy-row](#)

Copies a specific row in a sheet.

[excel/copy-row-to-end](#)

Copies a specific row from a sheet to end of the sheet.

[excel/insert-empty-row](#)

Inserts an empty row or multiple empty rows to a sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/col->string

```
(col->string col)
```

Returns an Excel A-style column number string representation for a column number

```
(excel/col->string 1)
```

```
(excel/col->string 56)
```

SEE ALSO

[excel/addr->string](#)

Returns an Excel A1-style cell address string representation for a row and column address

[top](#)

excel/col-width

```
(col-width sheet col width)
```

Set the width of a column (1..n) in the sheet.

```
(do
  (load-module :excel)
  (let [os      (io/file-out-stream "sample.xlsx")
        data    [ { :first "John" :last "Doe"   :age 28 }
                   { :first "Sue"  :last "Ford"   :age 26 } ]
        wbook    (excel/writer :xlsx)
        sheet    (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name"  { :field :last })
    (excel/add-column sheet "Age"        { :field :age })
    (excel/write-items sheet data)
    (excel/col-width sheet 1 80)
    (excel/col-width sheet 2 80)
    (excel/col-width sheet 3 60)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[top](#)

excel/convert->reader

(convert->reader builder)

Converts an excel or sheet builder to the corresponding reader.

```
(do
  (load-module :excel)
  (let [data [ {:a 100 :b 200 }
                {:a 101 :b 201 }
                {:a 102 :b 202 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1"
                                { :no-header-row true })]
    (excel/add-column sheet "A" { :field :a })
    (excel/add-column sheet "B" { :field :b })
    (excel/add-column sheet "C" { :field :c })
    (excel/write-items sheet data)
    (excel/cell-formula sheet 1 3 "SUM(A1,B1)")
    (excel/cell-formula sheet 2 3 "SUM(A2,B2)")
    (excel/cell-formula sheet 3 3 "SUM(A3,B3)")
    (let [reader (excel/convert->reader sheet)]
      (excel/evaluate-formulas reader)
      (excel/read-long-val reader 1 3))))
```

[top](#)

excel/convert->writer

(convert->writer reader)

Converts an excel or sheet reader to the corresponding writer.

```
(do
  (load-module :excel)

  (let [wbook-rd (excel/open "sample.xlsx")
        wbook-wr (excel/convert->writer wbook-rd)
        sheet-wr (excel/sheet wbook-wr 1) ]
    (excel/write-value sheet-wr 1 1 "foo")
    (excel/auto-size-columns sheet-wr)
    (excel/write->file wbook-wr "sample.xlsx")))
```

excel/copy-row

```
(copy-row sheet row-from row-to)
```

Copies a specific row in a sheet.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/write-value sheet 1 1 "John")
    (excel/write-value sheet 1 2 "Doe")
    (excel/write-value sheet 1 3 28)
    (excel/write-value sheet 2 1 "Sue")
    (excel/write-value sheet 2 2 "Ford")
    (excel/write-value sheet 2 3 26)
    (excel/copy-row sheet 1 2)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/clear-row](#)

Clears the values in a specific row in a sheet.

[excel/delete-row](#)

Deletes a specific row from a sheet.

[excel/copy-row-to-end](#)

Copies a specific row from a sheet to end of the sheet.

[excel/insert-empty-row](#)

Inserts an empty row or multiple empty rows to a sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

excel/copy-row-to-end

```
(copy-row-to-end sheet row)
```

Copies a specific row from a sheet to end of the sheet.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/write-value sheet 1 1 "John")
    (excel/write-value sheet 1 2 "Doe")
    (excel/write-value sheet 1 3 28)
    (excel/write-value sheet 2 1 "Sue")
    (excel/write-value sheet 2 2 "Ford")
    (excel/write-value sheet 2 3 26)
    (excel/copy-row-to-end sheet 1)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/clear-row](#)

Clears the values in a specific row in a sheet.

[excel/delete-row](#)

Deletes a specific row from a sheet.

[excel/copy-row](#)

Copies a specific row in a sheet.

[excel/insert-empty-row](#)

Inserts an empty row or multiple empty rows to a sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/delete-row

```
(delete-row sheet row)
```

Deletes a specific row from a sheet.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/write-value sheet 1 1 "John")
    (excel/write-value sheet 1 2 "Doe")
    (excel/write-value sheet 1 3 28)
```



```
(excel/write-value sheet 2 1 "Sue")
(excel/write-value sheet 2 2 "Ford")
(excel/write-value sheet 2 3 26)
(excel/delete-row sheet 1)
(excel/auto-size-columns sheet)
(excel/write->file wbook "sample.xlsx"))
```

SEE ALSO

[excel/clear-row](#)

Clears the values in a specific row in a sheet.

[excel/copy-row](#)

Copies a specific row in a sheet.

[excel/copy-row-to-end](#)

Copies a specific row from a sheet to end of the sheet.

[excel/insert-empty-row](#)

Inserts an empty row or multiple empty rows to a sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/evaluate-formulas

```
(evaluate-formulas it)
```

Evaluate all formulas in the Excel.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101 102] [200 201 202]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))]
    (excel/evaluate-formulas wbook)))
```

SEE ALSO

[excel/writer](#)

Creates a new Excel writer for the given type :xls or :xlsx or opens an existing Excel to modify it.

excel/freeze-pane

```
(freeze-pane sheet rows cols)
```

Creates a split (freezepane). Any existing freezepane or split pane is overwritten.

If both rows and cols are 0 then the existing freeze pane is removed.

rows: the number of rows to freeze (starting from the first row) cols: the number of columns to freeze (starting from the first column)

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1" { :no-header-row false })]
    (excel/write-data sheet [(map #(str "Col " %) (range 1 11))])
    (excel/write-data sheet (partition 10 (range 100 500)) 2 1)
    (excel/freeze-pane sheet 1 0)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/add-merge-region](#)

Add a merge region to the sheet.

excel/hide-columns

```
(hide-columns sheet & columns)
```

Hide columns in the sheet.

```
;; hide column by column index (1..n)
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/hide-columns sheet 2) ;; hide column #2
    (excel/write->file wbook "sample.xlsx")))
```

```
;; hide column by column id
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
```

```
(excel/add-column sheet "Last Name" { :field :last, :id "lastname"})
(excel/add-column sheet "First Name" { :field :first, :id "firstname"})
(excel/add-column sheet "Age" { :field :age, :id "age" })
(excel/write-items sheet data)
(excel/auto-size-columns sheet)
(excel/hide-columns sheet "firstname") ;; hide column "firstname"
(excel/write->file wbook "sample.xlsx"))
```

SEE ALSO

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/insert-empty-row

```
(insert-empty-row sheet row)
(insert-empty-row sheet row count)
```

Inserts an empty row or multiple empty rows to a sheet.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/write-value sheet 1 1 "John")
    (excel/write-value sheet 1 2 "Doe")
    (excel/write-value sheet 1 3 28)
    (excel/write-value sheet 2 1 "Sue")
    (excel/write-value sheet 2 2 "Ford")
    (excel/write-value sheet 2 3 26)
    (excel/insert-empty-row sheet 2)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/clear-row](#)

Clears the values in a specific row in a sheet.

[excel/delete-row](#)

Deletes a specific row from a sheet.

[excel/copy-row](#)

Copies a specific row in a sheet.

[excel/copy-row-to-end](#)

Copies a specific row from a sheet to end of the sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/line-data-series

(line-data-series title smooth? marker data-address-range)

Build a line chart data series

Arguments:

title	The series title
smooth?	Smooth rendering (splines): <code>true</code> or <code>false</code>
marker	The marker type: <code>:CIRCLE</code> , <code>:DASH</code> , <code>:DIAMOND</code> , <code>:DOT</code> , <code>:NONE</code> , <code>:PLUS</code> , <code>:SQUARE</code> , <code>:STAR</code> , <code>:TRIANGLE</code>
data-address-range	The series data in the Excel

```
(excel/line-data-series "Countries"
  false
  :SQUARE
  (excel/cell-address-range 2 2 1 5))
```

SEE ALSO

[excel/cell-address-range](#)

Build a cell address range

[top](#)

excel/open

(open source)

Opens an Excel from a source and returns an Excel reader.

Supported sources are string file path, bytebuf, `:java.io.File` , or `:java.io.InputStream` .

```
(do
  (load-module :excel))
```

```
(let [wbook (excel/open "sample.xlsx")]
  (println "Sheet count: " (excel/sheet-count wbook)))
```

SEE ALSO

[excel/sheet-count](#)

Returns the number of sheets in the Excel.

[excel/sheet](#)

Returns a sheet from the Excel reader or writer referenced by its name or sheet index.

[excel/evaluate-formulas](#)

Evaluate all formulas in the Excel.

[top](#)

excel/pie-data-series

```
(pie-data-series data-address-range)
```

Build a pie chart data series

Arguments:

data-address-range The series data in the Excel

```
(excel/pie-data-series (excel/cell-address-range 2 2 1 5))
```

SEE ALSO

[excel/cell-address-range](#)

Build a cell address range

[top](#)

excel/read-boolean-val

```
(read-boolean-val sheet row col)
```

Returns the sheet cell value as boolean.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 true 102]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/read-boolean-val sheet 1 2)))
```

SEE ALSO

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-datetime-val](#)

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[excel/read-val](#)

Returns the sheet cell value.

[top](#)

excel/read-date-val

```
(read-date-val sheet row col)
```

Returns the sheet cell value as a date (:java.time.LocalDate).

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")
          dt1   (time/local-date 2021 1 1)
          dt2   (time/local-date 2022 4 15)]
      (excel/write-data sheet [[100 dt1 dt2 102]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    [(excel/read-date-val sheet 1 2)
     (excel/read-date-val sheet 1 3)]))
```

SEE ALSO

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-datetime-val](#)

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[excel/read-val](#)

Returns the sheet cell value.

[top](#)

excel/read-datetime-val

```
(read-datetime-val sheet row col)
```

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")
          ts1   (time/local-date-time 2021 1 1 15 30 45)
          ts2   (time/local-date-time 2021 1 31 08 00 00)]
      (excel/write-data sheet [[100 ts1 ts2 102]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    [(excel/read-datetime-val sheet 1 2)
     (excel/read-datetime-val sheet 1 3)])))
```

SEE ALSO

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-val](#)

Returns the sheet cell value.

[top](#)

excel/read-double-val

```
(read-double-val sheet row col)
```

Returns the sheet cell value as double.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101.23 102]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/read-double-val sheet 1 2)))
```

SEE ALSO

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-val](#)

Returns the sheet cell value.

[top](#)

excel/read-error-code

```
(read-error-code sheet row col)
```

Reads the error code from a cell. Returns a string indicating the error or nil if the cell is not in error state.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 200 {:formula "1 / 0"}]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/read-error-code sheet 1 2)))
```



```
(let [wbook (excel/open (test-xls))
      sheet (excel/sheet wbook "Data")]
  (excel/evaluate-formulas wbook)
  (excel/read-error-code sheet 1 3))) ;; #DIV/0!
```

SEE ALSO

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-datetime-val](#)

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[top](#)

excel/read-long-val

```
(read-long-val sheet row col)
```

Returns the sheet cell value as long.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101 102]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/read-long-val sheet 1 2)))

(do
  (load-module :excel)

  (defn test-xls []
    (let [data [ {:a 100 :b 200 } ]
          wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data"
                                { :no-header-row true })]
      (excel/add-column sheet "A" { :field :a })
      (excel/add-column sheet "B" { :field :b })))
```

```
(excel/write-items sheet data)
(excel/cell-formula sheet 1 3 "SUM(A1,B1)")
(excel/write->bytebuf wbook))

(let [wbook (excel/open (test-xls))
      sheet (excel/sheet wbook "Data")]
  (excel/read-long-val sheet 1 3))
```

SEE ALSO

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-datetime-val](#)

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[excel/read-val](#)

Returns the sheet cell value.

[top](#)

excel/read-string-val

```
(read-string-val sheet row col)
```

Returns the sheet cell value as string.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 "101" 102.0]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/read-string-val sheet 1 2)))
```

SEE ALSO

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-datetime-val](#)

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[excel/read-val](#)

Returns the sheet cell value.

[top](#)

excel/read-val

```
(read-val sheet row col)
```

Returns the sheet cell value.

Returns a *nil*, *string*, *boolean*, or *double* value depending on the cell's excel type *:blank*, *:string*, *:boolean*, or *:numeri*.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 "101" 102.0]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/read-val sheet 1 2)))
```

SEE ALSO

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-datetime-val](#)

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[top](#)

excel/row-height

(row-height sheet row height)

Set the height of a row (1..n) in the sheet.

```
(do
  (load-module :excel)
  (let [os      (io/file-out-stream "sample.xlsx")
        data   [ {:first "John" :last "Doe"   :age 28 }
                  {:first "Sue"  :last "Ford"  :age 26 } ]
        wbook  (excel/writer :xlsx)
        sheet  (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name"  { :field :last })
    (excel/add-column sheet "Age"        { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/row-height sheet 2 50)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/col-width](#)

Set the width of a column (1..n) in the sheet.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[top](#)

excel/sheet

(sheet wbook ref)

Returns a sheet from the Excel reader or writer referenced by its name or sheet index.

```
(do
  (load-module :excel)
```

```

(defn test-xls []
  (let [wbook (excel/writer :xlsx)
        sheet1 (excel/add-sheet wbook "Data1")
        sheet2 (excel/add-sheet wbook "Data2")]
    (excel/write-data sheet1 [[100 101 102] [200 201 202]])
    (excel/write-data sheet2 [[100 101 102] [200 201 202]])
    (excel/write->bytebuf wbook)))

(let [wbook (excel/open (test-xls))
      sheet1 (excel/sheet wbook "Data1")
      sheet2 (excel/sheet wbook 2)]
  ))

```

SEE ALSO

[excel/sheet-count](#)

Returns the number of sheets in the Excel.

[excel/evaluate-formulas](#)

Evaluate all formulas in the Excel.

[excel/sheet-name](#)

Returns the name of a sheet.

[excel/sheet-row-range](#)

Returns the first and the last row with data in a sheet as vector. Returns -1 values if no row exists.

[excel/sheet-col-range](#)

Returns the first and the last col with data in a sheet row as vector. Returns -1 values if the row does not exist or the row does ...

[excel/cell-empty?](#)

Returns true if the sheet cell given by row/col is empty.

[excel/cell-type](#)

Returns the sheet cell type as one of { :notfound, :blank, :string, :boolean, :numeric, :formula, :error, or :unknown }

[excel/read-string-val](#)

Returns the sheet cell value as string.

[excel/read-boolean-val](#)

Returns the sheet cell value as boolean.

[excel/read-long-val](#)

Returns the sheet cell value as long.

[excel/read-double-val](#)

Returns the sheet cell value as double.

[excel/read-date-val](#)

Returns the sheet cell value as a date (:java.time.LocalDate).

[excel/read-datetime-val](#)

Returns the sheet cell value as a datetime (:java.time.LocalDateTime).

[top](#)

excel/sheet-col-range

```
(sheet-col-range sheet)
```

Returns the first and the last col with data in a sheet row as vector. Returns -1 values if the row does not exist or the row does not have any columns.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101 102] [200 201 202]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/sheet-col-range sheet 1)))
```

SEE ALSO

[excel/sheet-row-range](#)

Returns the first and the last row with data in a sheet as vector. Returns -1 values if no row exists.

top

excel/sheet-count

```
(sheet-count wbook)
```

Returns the number of sheets in the Excel.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101 102] [200 201 202]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))]
    (excel/sheet-count wbook)))
```

SEE ALSO

[excel/sheet](#)

Returns a sheet from the Excel reader or writer referenced by its name or sheet index.

[excel/evaluate-formulas](#)

Evaluate all formulas in the Excel.

top

excel/sheet-index

```
(sheet-index sheet)
```

Returns the index of a sheet.

```
(do
  (load-module :excel))
```

```
(defn test-xls []
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Data")]
    (excel/write-data sheet [[100 101 102] [200 201 202]])
    (excel/write->bytebuf wbook)))

(let [wbook (excel/open (test-xls))
      sheet (excel/sheet wbook "Data")]
  (excel/sheet-index sheet))
```

top

excel/sheet-name

(sheet-name sheet)

Returns the name of a sheet.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101 102] [200 201 202]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/sheet-name sheet)))
```

top

excel/sheet-row-range

(sheet-row-range sheet)

Returns the first and the last row with data in a sheet as vector. Returns -1 values if no row exists.

```
(do
  (load-module :excel)

  (defn test-xls []
    (let [wbook (excel/writer :xlsx)
          sheet (excel/add-sheet wbook "Data")]
      (excel/write-data sheet [[100 101 102] [200 201 202]])
      (excel/write->bytebuf wbook)))

  (let [wbook (excel/open (test-xls))
        sheet (excel/sheet wbook "Data")]
    (excel/sheet-row-range sheet)))
```

SEE ALSO

[excel/sheet-col-range](#)

Returns the first and the last col with data in a sheet row as vector. Returns -1 values if the row does not exist or the row does ...

excel/sum-formula

(sum-formula sheet row-from row-to col-from col-to)

Returns a sum formula for the given cell area

```
(do
  (load-module :excel)
  (let [data [ {:a 100 :b 200 }
                {:a 101 :b 201 }
                {:a 102 :b 202 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1" { :no-header-row true })]
    (excel/add-column sheet "A" { :field :a })
    (excel/add-column sheet "B" { :field :b })
    (excel/add-column sheet "C" { :field :c })
    (excel/write-items sheet data)
    (excel/cell-formula sheet 1 3 (excel/sum-formula sheet 1 1 1 2))
    (excel/cell-formula sheet 2 3 (excel/sum-formula sheet 2 2 1 2))
    (excel/cell-formula sheet 3 3 (excel/sum-formula sheet 3 3 1 2))
    (excel/evaluate-formulas wbook)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/addr->string](#)

Returns an Excel A1-style cell address string representation for a row and column address

excel/write->bytebuf

(write->bytebuf wbook)

Writes the excel to a bytebuf. Returns the bytebuf.

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/write->bytebuf wbook)))
```

SEE ALSO

[excel/write->file](#)

Writes the excel to a file.

[excel/write->stream](#)

Writes the excel to a Java :OutputStream.

[top](#)

excel/write->file

```
(write->file wbook f)
```

Writes the excel to a file.

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/write->stream](#)

Writes the excel to a Java :OutputStream.

[excel/write->bytebuf](#)

Writes the excel to a bytebuf. Returns the bytebuf.

[top](#)

excel/write->stream

```
(write->stream wbook os)
```

Writes the excel to a Java :OutputStream.

```
(do
  (load-module :excel)
  (let [os (io/file-out-stream "sample.xlsx")
        data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/write->stream wbook os)))
```

SEE ALSO

[excel/write->file](#)

Writes the excel to a file.

[excel/write->bytebuf](#)

Writes the excel to a bytebuf. Returns the bytebuf.

[top](#)

excel/write-data

```
(write-data sheet data)
(write-data sheet data row col)
```

Writes the data of a 2D array to an excel sheet.

Optionally the data can written to a region starting at a row/col position.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Data")
        dt     (time/local-date 2021 1 1)
        ts     (time/local-date-time 2021 1 1 15 30 45)
        data   [[100 101 102 103 104 105]
                 [200 "ab" 1.23 dt ts false]]]
    (excel/write-data sheet data)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))

(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Data")]
    (excel/write-data sheet [[100 101 102] [200 201 203]])
    (excel/write-data sheet [[300 301 302] [400 401 403]] 3 4)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/write->stream](#)

Writes the excel to a java :OutputStream.

[excel/write->bytebuf](#)

Writes the excel to a bytebuf. Returns the bytebuf.

[top](#)

excel/write-item

```
(write-item sheet item)
```

Render a single data item to the sheet

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
```

```
(excel/add-column sheet "First Name" { :field :first })
(excel/add-column sheet "Last Name" { :field :last })
(excel/add-column sheet "Age" { :field :age })
(excel/write-item sheet {:first "John" :last "Doe" :age 28 })
(excel/write-item sheet {:first "Sue" :last "Ford" :age 26 })
(excel/auto-size-columns sheet)
(excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/write-items

```
(write-items sheet items)
```

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

```
(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
               {:first "Sue" :last "Ford" :age 26 } ]
        wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/write-item](#)

Render a single data item to the sheet

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/write-value

```
(write-value sheet row col val)
(write-value sheet row col val style)
```

Writes a value with an optional to a specific cell given by its row and col.

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/write-value sheet 1 1 "John")
    (excel/write-value sheet 1 2 "Doe")
    (excel/write-value sheet 1 3 28)
    (excel/write-value sheet 2 1 "Sue")
    (excel/write-value sheet 2 2 "Ford")
    (excel/write-value sheet 2 3 26)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))

(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/add-font wbook :italic { :italic true })
    (excel/add-font wbook :bold { :bold true })
    (excel/add-style wbook :italic { :font :italic })
    (excel/add-style wbook :bold { :font :bold })
    (excel/write-value sheet 1 1 "John" :italic)
    (excel/write-value sheet 1 2 "Doe" :italic)
    (excel/write-value sheet 1 3 28 :bold)
    (excel/write-value sheet 2 1 "Sue" :italic)
    (excel/write-value sheet 2 2 "Ford" :italic)
    (excel/write-value sheet 2 3 26 :bold)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/write-values](#)

Writes multiples value to a row starting at col and incrementing col for each value

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/write-values

(write-values sheet row col & vals)

Writes multiples value to a row starting at col and incrementing col for each value

```
(do
  (load-module :excel)
  (let [wbook (excel/writer :xlsx)
        sheet (excel/add-sheet wbook "Sheet 1")]
    (excel/write-values sheet 1 1 "John" "Doe" 28)
    (excel/write-values sheet 2 1 "Sue" "Ford" 26)
    (excel/auto-size-columns sheet)
    (excel/write->file wbook "sample.xlsx")))
```

SEE ALSO

[excel/write-value](#)

Writes a value with an optional to a specific cell given by its row and col.

[excel/write-items](#)

Writes the passed data items, a sequence of maps of name/value pairs, to the sheet.

[excel/write-item](#)

Render a single data item to the sheet

[excel/cell-formula](#)

Set a formula for a specific cell given by its row and col.

[excel/auto-size-columns](#)

Auto size the width of all columns in the sheet.

[excel/auto-size-column](#)

Auto size the width of column col (1..n) in the sheet.

[excel/row-height](#)

Set the height of a row (1..n) in the sheet.

[top](#)

excel/writer

(writer type)
(writer source)

Creates a new Excel writer for the given type :xls or :xlsx or opens an existing Excel to modify it.

Supported sources are string file path, bytebuf, `:java.io.File`, or `:java.io.InputStream`.

```
(do
  (load-module :excel))
```

```

(let [data [ {:first "John" :last "Doe" :age 28 }
              {:first "Sue" :last "Ford" :age 26 } ]
      workbook (excel/writer :xlsx)
      sheet (excel/add-sheet workbook "Sheet 1")]
  (excel/add-column sheet "First Name" { :field :first })
  (excel/add-column sheet "Last Name" { :field :last })
  (excel/add-column sheet "Age" { :field :age })
  (excel/write-items sheet data)
  (excel/auto-size-columns sheet)
  (excel/write->file workbook "sample.xlsx"))

(do
  (load-module :excel)
  (let [data [ {:first "John" :last "Doe" :age 28 }
                {:first "Sue" :last "Ford" :age 26 } ]
        workbook (excel/writer "sample.xlsx")
        sheet (excel/add-sheet workbook "Sheet 1")]
    (excel/add-column sheet "First Name" { :field :first })
    (excel/add-column sheet "Last Name" { :field :last })
    (excel/add-column sheet "Age" { :field :age })
    (excel/write-items sheet data)
    (excel/auto-size-columns sheet)
    (excel/write->file workbook "sample.xlsx"))

```

SEE ALSO

[excel/add-sheet](#)

Adds a sheet with optional attributes to an Excel.

[excel/add-font](#)

Add font with optional attributes to an Excel.

[excel/add-style](#)

Add a style with optional attributes to an Excel.

[excel/write->file](#)

Writes the excel to a file.

[excel/write->stream](#)

Writes the excel to a Java :OutputStream.

[excel/write->bytebuf](#)

Writes the excel to a bytebuf. Returns the bytebuf.

[excel/evaluate-formulas](#)

Evaluate all formulas in the Excel.

[top](#)

exists-class?

```
(exists-class? name)
```

Returns true the Java class for the given name exists otherwise returns false.

```
(exists-class? :java.util.ArrayList)
=> true
```

[top](#)

exp

```
(exp x)
```

Returns Euler's number e raised to the power of a value.

```
(exp 10)
=> 22026.465794806718
```

```
(exp 10.23)
=> 27722.51006805505
```

```
(exp 10.23M)
=> 27722.51006805505
```

SEE ALSO

[exp](#)

Returns Euler's number e raised to the power of a value.

[top](#)

extend

```
(extend type protocol fns*)
```

Extends protocol for type with the supplied functions.

Formats:

- `(extend :core/long P (foo [x] x))`
- `(extend :core/long P (foo [x] x) (foo [x y] x))`
- `(extend :core/long P (foo [x] x) (bar [x] x))`

```
(do
  (ns foo)
  (deftype :complex [re :long, im :long])
  (defprotocol XMath (+ [x y])
                    (- [x y]))
  (extend :foo/complex XMath
    (+ [x y] (complex. (core/+ (:re x) (:re y))
                       (core/+ (:im x) (:im y)))))
    (- [x y] (complex. (core/- (:re x) (:re y))
                       (core/- (:im x) (:im y)))))

  (extend :core/long XMath
    (+ [x y] (core/+ x y))
    (- [x y] (core/- x y)))
  (foo/+ (complex. 1 1) (complex. 4 5)))
=> {:custom-type* :foo/complex :re 5 :im 6}
```

SEE ALSO

[defprotocol](#)

Defines a new protocol with the supplied function specs.

[extends?](#)

Returns true if the type extends the protocol.

extends?

```
(extends? type protocol)
```

Returns true if the type extends the protocol.

```
(do
  (ns foo)
  (deftype :complex [re :long, im :long])
  (defprotocol XMath (+ [x y])
                    (- [x y]))
  (extend :foo/complex XMath
    (+ [x y] (complex. (core/+ (:re x) (:re y))
                       (core/+ (:im x) (:im y)))))
    (- [x y] (complex. (core/- (:re x) (:re y))
                       (core/- (:im x) (:im y)))))

  (extend :core/long XMath
    (+ [x y] (core/+ x y))
    (- [x y] (core/- x y)))
  (extends? :foo/complex XMath))
=> true
```

SEE ALSO

[defprotocol](#)

Defines a new protocol with the supplied function specs.

[extend](#)

Extends protocol for type with the supplied functions.

false?

```
(false? x)
```

Returns true if x is false, false otherwise

```
(false? true)
=> false

(false? false)
=> true

(false? nil)
=> false

(false? 0)
=> false

(false? (== 1 2))
=> true
```


SEE ALSO

[true?](#)

Returns true if x is true, false otherwise

[not](#)

Returns true if x is logical false, false otherwise.

[top](#)

filter

```
(filter predicate coll)
```

Returns a collection of the items in coll for which `(predicate item)` returns logical true.
Returns a transducer when no collection is provided.

```
(filter even? [1 2 3 4 5 6 7])  
=> (2 4 6)
```

```
(filter #(even? (val %)) {:a 1 :b 2})  
=> ([:b 2])
```

```
(filter even? #{1 2 3})  
=> (2)
```

SEE ALSO

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[reduce](#)

f should be a function of 2 arguments. If val is not supplied, returns the result of applying f to the first 2 items in coll, then ...

[top](#)

filter-k

```
(filter-k f map)
```

Returns a map with entries for which the predicate (f key) returns logical true. f is a function with one arguments.

```
(filter-k #(= % :a) {:a 1 :b 2 :c 3})  
=> {:a 1}
```

SEE ALSO

[filter-kv](#)

Returns a map with entries for which the predicate (f key value) returns logical true. f is a function with two arguments.

[top](#)

filter-kv

(filter-kv f map)

Returns a map with entries for which the predicate (f key value) returns logical true. f is a function with two arguments.

```
(filter-kv (fn [k v] (= k :a)) {:a 1 :b 2 :c 3})
=> {:a 1}
```

```
(filter-kv (fn [k v] (= v 2)) {:a 1 :b 2 :c 3})
=> {:b 2}
```

SEE ALSO

[filter-k](#)

Returns a map with entries for which the predicate (f key) returns logical true. f is a function with one arguments.

[top](#)

find

(find map key)

Returns the map entry for key, or nil if key not present.

```
(find {:a 1 :b 2} :b)
=> [:b 2]
```

```
(find {:a 1 :b 2} :z)
=> nil
```

[top](#)

finder

(finder & args)

Finds symbols that match one more glob patterns or regular expressions.

Filters the symbol names by 0 to n glob patterns or regular expressions.

Glob patterns and regular expressions are ANDed, flags are ORed.

Flags:

- | | |
|---------------|---|
| :function | filter functions |
| :macro | filter macros |
| :special-form | filter special forms |
| :protocol | filter protocols |
| :value | filter values |
| :machine | return the result as Venice data otherwise print it in table format |

```
(finder "io/zip*")
io/zip           :core/function
io/zip-append    :core/function
io/zip-file      :core/function
io/zip-list      :core/function
```

```

io/zip-list-entry-names :core/function
io/zip-remove           :core/function
io/zip-size             :core/function
io/zip?                 :core/function
=> nil

(finder "*delete-file*")
io/delete-file           :core/function
io/delete-file-on-exit   :core/function
io/delete-file-tree      :core/function
io/delete-files-glob     :core/function
=> nil

(finder "io/zip*" :machine)
=> ([io/zip :core/function] [io/zip-append :core/function] [io/zip-file :core/function] [io/zip-list :core
/function] [io/zip-list-entry-names :core/function] [io/zip-remove :core/function] [io/zip-size :core/function]
[io/zip? :core/function])

(finder #"io/zip.*")
io/zip                   :core/function
io/zip-append            :core/function
io/zip-file              :core/function
io/zip-list              :core/function
io/zip-list-entry-names  :core/function
io/zip-remove            :core/function
io/zip-size              :core/function
io/zip?                  :core/function
=> nil

(finder #".*delete-file*.")
io/delete-file           :core/function
io/delete-file-on-exit   :core/function
io/delete-file-tree      :core/function
io/delete-files-glob     :core/function
=> nil

(finder #"io/zip.*" :machine)
=> ([io/zip :core/function] [io/zip-append :core/function] [io/zip-file :core/function] [io/zip-list :core
/function] [io/zip-list-entry-names :core/function] [io/zip-remove :core/function] [io/zip-size :core/function]
[io/zip? :core/function])

(finder zip)
geoup/download-maxmind-db-to-zipfile :core/function
grep/grep-zip                       :core/function
io/gzip                             :core/function
io/gzip-to-stream                    :core/function
io/gzip?                             :core/function
io/ungzip                            :core/function
io/ungzip-to-stream                   :core/function
io/unzip                             :core/function
io/unzip-all                         :core/function
io/unzip-first                        :core/function
io/unzip-nth                         :core/function
io/unzip-to-dir                       :core/function
io/wrap-is-with-gzip-input-stream    :core/function
io/wrap-os-with-gzip-output-stream   :core/function
io/zip                               :core/function
io/zip-append                         :core/function
io/zip-file                           :core/function
io/zip-list                           :core/function
io/zip-list-entry-names               :core/function
io/zip-remove                         :core/function

```

io/zip-size	:core/function
io/zip?	:core/function
zipmap	:core/function
zipvault/add-files	:core/function
zipvault/add-folder	:core/function
zipvault/add-stream	:core/function
zipvault/encrypted?	:core/function
zipvault/entries	:core/function
zipvault/entropy	:core/function
zipvault/extract-all	:core/function
zipvault/extract-file	:core/function
zipvault/extract-file-data	:core/function
zipvault/remove-files	:core/function
zipvault/valid-zip-file?	:core/function
zipvault/zip	:core/function
zipvault/zip-folder	:core/function

```
=> nil
```

SEE ALSO

[doc](#)

Prints documentation for a var or special form given x as its name. Prints the definition of custom types.

[ns-list](#)

Without arg lists the loaded namespaces, else lists all the symbols in the specified namespace ns.

[modules](#)

Lists the available Venice modules

top

first

```
(first coll)
```

Returns the first element of coll or nil if coll is nil or empty.

```
(first nil)  
=> nil
```

```
(first [])  
=> nil
```

```
(first [1 2 3])  
=> 1
```

```
(first '())  
=> nil
```

```
(first '(1 2 3))  
=> 1
```

```
(first "abc")  
=> #\a
```

top

flatten

```
(flatten coll)
```

Takes any nested combination of collections (lists, vectors, etc.) and returns their contents as a single, flat sequence. `(flatten nil)` returns an empty list.

Returns a transducer when no collection is provided.

```
(flatten [])
```

```
=> []
```

```
(flatten [[1 2 3] [4 [5 6]] [7 [8 [9]]]])
```

```
=> [1 2 3 4 5 6 7 8 9]
```

```
(flatten [1 2 {:a 3 :b [4 5 6]}])
```

```
=> [1 2 {:a 3 :b [4 5 6]}]
```

```
(flatten (seq {:a 1 :b 2}))
```

```
=> (:a 1 :b 2)
```

SEE ALSO

[mapcat](#)

Returns the result of applying concat to the result of applying map to fn and colls. Thus function fn should return a collection.

[top](#)

float

```
(float x)
```

Converts x to `:java.lang.Float`.

Note: Venice does not have a built-in float type!

```
(float 1.2F)
```

```
=> 1.2F
```

```
(float 1)
```

```
=> 1.0F
```

```
(float nil)
```

```
=> 0.0F
```

```
(float false)
```

```
=> 0.0F
```

```
(float true)
```

```
=> 1.0F
```

```
(float 1.2)
```

```
=> 1.2F
```

```
(float 1.2M)
```

```
=> 1.2F
```

```
(float "1.2")  
=> 1.2F
```

[top](#)

float-array

```
(float-array coll)  
(float-array len)  
(float-array len init-val)
```

Returns an array of Java primitive floats containing the contents of coll or returns an array with the given length and optional init value.

To create an array of :java.lang.Float use:

```
(make-array :java.lang.Long 3)
```

```
(float-array '(1.0F 2.0F 3.0F))  
=> [1.0, 2.0, 3.0]
```

```
(float-array '(1I 2 3.2 3.56M))  
=> [1.0, 2.0, 3.2, 3.56]
```

```
(float-array 10)  
=> [0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0]
```

```
(float-array 10 42.0F)  
=> [42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0, 42.0]
```

SEE ALSO

[java-float-list](#)

Converts a Venice list/vector to a Java Float list

[top](#)

float?

```
(float? n)
```

Returns true if n is a float

```
(float? 4.0F)  
=> true
```

```
(float? 4.0)  
=> false
```

```
(float? 3)  
=> false
```

```
(float? 3I)  
=> false
```

```
(float? 3.0M)
=> false

(float? true)
=> false

(float? nil)
=> false

(float? {})
=> false
```

[top](#)

floor

```
(floor x)
```

Returns the largest integer that is less than or equal to x

```
(floor 1.4)
=> 1.0

(floor -1.4)
=> -2.0

(floor 1.23M)
=> 1.00M

(floor -1.23M)
=> -2.00M
```

SEE ALSO

[ceil](#)

Returns the largest integer that is greater than or equal to x

[top](#)

flush

```
(flush)
(flush os)
```

Without arg flushes the output stream that is the current value of `*out*`. With arg flushes the passed stream that must be a subclass of either `:java.io.OutputStream` OR `:java.io.Writer`.

Returns `nil`.

```
(flush)
=> nil

(flush *out*)
=> nil
```

```
(flush *err*)  
=> nil
```

SEE ALSO

[io/flush](#)

Flushes a :java.io.OutputStream or a :java.io.Writer.

[io/close](#)

Closes a :java.io.InputStream, :java.io.OutputStream, :java.io.Reader, or a :java.io.Writer.

top

fn

```
(fn name? [params*] condition-map? expr*)
```

Defines an anonymous function.

```
(do  
  (def sum (fn [x y] (+ x y)))  
  (sum 2 3))  
=> 5
```

```
;; multi-arity anonymous function  
(let [f (fn ([x] x) ([x y] (+ x y)))]  
  [(f 1) (f 4 6)])  
=> [1 10]
```

```
(map (fn double [x] (* 2 x)) (range 1 5))  
=> (2 4 6 8)
```

```
(map #(* 2 %) (range 1 5))  
=> (2 4 6 8)
```

```
(map #(* 2 %1) (range 1 5))  
=> (2 4 6 8)
```

```
;; anonymous function with two params, the second is destructured  
(reduce (fn [m [k v]] (assoc m v k)) {} {:b 2 :a 1 :c 3})  
=> {1 :a 2 :b 3 :c}
```

```
;; defining a pre-condition  
(do  
  (def square-root  
    (fn [x]  
      { :pre [(>= x 0)] }  
      (. :java.lang.Math :sqrt x)))  
  (square-root 4))  
=> 2.0
```

```
;; closures  
(do  
  (defn pow [n]  
    (fn [x] (apply * (repeat n x)))) ; closes over n
```

```
;; n is provided here as 2 and 3, then n goes out of scope  
(def square (pow 2))
```



```
(def cubic (pow 3))
(square 4))
=> 16

;; higher-order function
(do
  (def discount
    (fn [percentage]
      { :pre [(and (>= percentage 0) (<= percentage 100))] }
        (fn [price] (- price (* price percentage 0.01))))))
  ((discount 50) 300))
=> 150.0
```

SEE ALSO

[defn](#)

Same as (def name (fn name [args*] condition-map? expr*)) or (def name (fn name ([args*] condition-map? expr*)))

[defn-](#)

Same as defn, yielding non-public def

[def](#)

Creates a global variable.

[top](#)

fn-about

```
(fn-about f)
```

Returns the meta information about a function

```
(fn-about and)
=> {:name "and" :ns "core" :type :macro :visibility :public :native false :class :VncMultiArityFunction :source
{:file "core" :line 482 :column 3}}
```

```
(fn-about println)
=> {:name "println" :ns "core" :type :function :visibility :public :native false :class :VncMultiArityFunction :
source {:file "core" :line 1480 :column 3}}
```

```
(fn-about +)
=> {:name "+" :ns "core" :type :function :visibility :public :native true :class :VncFunction :source {}}
```

SEE ALSO

[fn-name](#)

Returns the qualified name of a function or macro

[fn-body](#)

Returns the body (a list of forms) of a function.

[fn-args](#)

Returns the argument list of a function.

[fn-pre-conditions](#)

Returns the pre-conditions (a vector of forms) of a function.

[top](#)

fn-args

```
(fn-args fn)
```

Returns the argument list of a function.

Returns `nil` if `fn` is not a function or if `fn` is a native function.

```
;; single arity
(do
  (defn sum [x y]
    (+ x y))
  (fn-args (var-get sum)))
=> ({:params ["x" "y"] :variadic false})

;; single arity, vargs
(do
  (defn sum [x & z]
    (apply + x z))
  (fn-args (var-get sum)))
=> ({:params ["x"] :variadic true :variadic-name "z"})

;; multi arity
(do
  (defn sum
    ([x] x)
    ([x y] (+ x y)))

  (fn-args (var-get sum)))
=> ({:params ["x"] :variadic false} {:params ["x" "y"] :variadic false})
```

SEE ALSO

[fn-name](#)

Returns the qualified name of a function or macro

[fn-about](#)

Returns the meta information about a function

[fn-body](#)

Returns the body (a list of forms) of a function.

[fn-pre-conditions](#)

Returns the pre-conditions (a vector of forms) of a function.

[top](#)

fn-body

```
(fn-body fn)
(fn-body fn arity)
```

Returns the body (a list of forms) of a function.

Returns `nil` if `fn` is not a function or if `fn` is a native function.

```
(do
  (defn calc [& x]
```

```
(->> x
  (filter even?)
  (map #(* % 10))))
(fn-body (var-get calc))
=> ((->> x (filter even?) (map (fn [%] (* % 10)))))
```

SEE ALSO

[fn-name](#)

Returns the qualified name of a function or macro

[fn-about](#)

Returns the meta information about a function

[fn-args](#)

Returns the argument list of a function.

[fn-pre-conditions](#)

Returns the pre-conditions (a vector of forms) of a function.

[top](#)

fn-name

```
(fn-name f)
```

Returns the qualified name of a function or macro

```
(fn-name (fn sum [x y] (+ x y)))
=> "user/sum"
```

```
(let [f str/digit?]
  (fn-name f))
=> "str/digit?"
```

SEE ALSO

[name](#)

Returns the name string of a string, symbol, keyword, or function. If applied to a string it returns the string itself.

[namespace](#)

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

[fn-about](#)

Returns the meta information about a function

[fn-body](#)

Returns the body (a list of forms) of a function.

[fn-pre-conditions](#)

Returns the pre-conditions (a vector of forms) of a function.

[top](#)

fn-pre-conditions

```
(fn-pre-conditions fn)
(fn-pre-conditions fn arity)
```

Returns the pre-conditions (a vector of forms) of a function.

Returns `nil` if `fn` is not a function.

```
(do
  (defn sum [x y]
    { :pre [(> x 0) (> y 0)] }
      (+ x y))
  (fn-pre-conditions (var-get sum)))
=> [(> x 0) (> y 0)]
```

SEE ALSO

[fn-name](#)

Returns the qualified name of a function or macro

[fn-about](#)

Returns the meta information about a function

[fn-body](#)

Returns the body (a list of forms) of a function.

[top](#)

fn?

```
(fn? x)
```

Returns true if `x` is a function

```
(do
  (def sum (fn [x] (+ 1 x)))
  (fn? sum))
=> true
```

[top](#)

fnil

```
(fnil f x)
(fnil f x y)
(fnil f x y z)
```

Takes a function `f`, and returns a function that calls `f`, replacing a `nil` first argument to `f` with the supplied value `x`. Higher arity versions can replace arguments in the second and third positions (`y`, `z`). Note that the function `f` can take any number of arguments, not just the one(s) being `nil`-patched.

```
;; e.g.: change the `str/lower-case` handling of nil arguments by
;; returning an empty string instead of nil.
((fnil str/lower-case "") nil)
=> ""
```

```
((fnil + 10) nil)
=> 10
```

```
((fnil + 10) nil 1)
=> 11
```

```
((fnil + 10) nil 1 2)
=> 13

((fnil + 10) 20 1 2)
=> 23

((fnil + 10) nil 1 2 3 4)
=> 20

((fnil + 1000 100) nil nil)
=> 1100

((fnil + 1000 100) 2000 nil 1)
=> 2101

((fnil + 1000 100) nil 200 1 2)
=> 1203

((fnil + 1000 100) nil nil 1 2 3 4)
=> 1110
```

top

fonts/download-demo-fonts

```
(fonts/download-demo-fonts dir)
(fonts/download-demo-fonts dir silent)
```

Downloads the Venice demo fonts

Family	Download family ref	Type	License
Open Sans	open-sans	TTF	Apache License v2
Roboto	roboto	TTF	Apache License v2
Source Code Pro	source-code-pro	OTF	SIL Open Font License v1.10
JetBrains Mono	jetbrains-mono	TTF	Apache License v2

to the specified dir.

Downloads the font families from the [Font Squirrel](https://www.fontsquirrel.com/) repository

```
(do
  (load-module :fonts)
  (fonts/download-demo-fonts (repl/libs-dir) false))
```

SEE ALSO

[fonts/download-font-family](#)

Downloads a font family from the Font Squirrel (<https://www.fontsquirrel.com/>) repository

top

fonts/download-font-family

```
(fonts/download-font-family family-name options*)
```

Downloads a font family from the [Font Squirrel](#) repository

Some useful font families:

Family	Download family ref	Type	License
Open Sans	open-sans	TTF	Apache License v2
Roboto	roboto	TTF	Apache License v2
Source Code Pro	source-code-pro	OTF	SIL Open Font License v1.10
JetBrains Mono	jetbrains-mono	TTF	Apache License v2

Options:

:extract {true,false}	if true extract the TTF files from the font family ZIP, else just download the ZIP
:dir path	download dir, defaults to "."
:silent {true,false}	if silent is true does not print download info, defaults to true

```
(do
  (load-module :fonts)

  (fonts/download-font-family "open-sans"
    :dir (repl/libs-dir)
    :extract true
    :glob-pattern "*.ttf"
    :silent false)

  (fonts/download-font-family "roboto"
    :dir (repl/libs-dir)
    :extract true
    :glob-pattern "*.ttf"
    :silent false)

  (fonts/download-font-family "source-code-pro"
    :dir (repl/libs-dir)
    :extract true
    :glob-pattern "*.otf"
    :silent false)

  (fonts/download-font-family "jetbrains-mono"
    :dir (repl/libs-dir)
    :extract true
    :glob-pattern "*.ttf"
    :silent false))
```

SEE ALSO

[fonts/download-demo-fonts](#)

Downloads the Venice demo fonts

[top](#)

force

```
(force x)
```

If x is a delay, returns its value, else returns x

```
(do
  (def x (delay (println "working...") 100))
  (force x))
```

```
working...
```

```
=> 100
```

```
(force (+ 1 2))
```

```
=> 3
```

SEE ALSO

[delay](#)

Takes a body of expressions and yields a Delay object that will invoke the body only the first time it is forced (with force or deref ...

[deref](#)

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will ...

[realized?](#)

Returns true if a value has been produced for a promise, delay, or future.

[top](#)

formal-type

(formal-type object)

Returns the *formal type* of a Java object.

The *formal type* of an object is defined as the explicit Java return type given by the function's definition. The *formal type* may differ from the real type of the returned Java object. A type cast will also change the object's formal type and set it to the cast type.

Venice must honor Java's static type system while interacting with Java objects. Therefore Venice adheres to *formal types* strictly when calling methods of Java objects.

Venice

```
;; The Circle constructor returns an object of type Circle
(let [c (. :Circle :new 1.5)]
  (. c :area)      ;; OK    Circle::area()
  (. c :radius))   ;; OK    Circle::radius()

;; Builder::circle returns an object of the formal type Shape
(let [c (. :Builder :circle 1.5)]
  (. c :area)      ;; OK    Shape::area()
  (. c :radius))   ;; FAIL   Shape::radius(), undefined method
```

Java

```
public class Builder {
  public static Shape circle(double radius) {
    return new Circle(radius);
  }
}

public interface Shape {
  double area();
}

public class Circle implements Shape {
  public Circle(double radius) {...}
  public double area() {...}
  public double radius() {...}
}
```

```
(do
  (import :java.awt.Point)
  (import :java.awt.geom.Point2D)
```

```
;; upcasting :java.awt.Point to :java.awt.geom.Point2D
;; Point2D does not define the translate method!
(let [p1 (. :Point :new 1.0 1.0)
      p2 (cast :Point2D p1)]
  (println "p1 ->" p1)
  (println "p2 ->" p2)
  (println "Formal type p1 ->" (formal-type p1))
  (println "Formal type p2 ->" (formal-type p2))
  (println "p1' ->" (doto p1 (. :translate 2.0 2.0)))
  ;; the translate method is not defined by Point2D
  ;; and will fail with a JavaMethodInvocationException!
  ;; (doto p2 (. :translate 2.0 2.0))
))
p1 -> java.awt.Point[x=1,y=1]
p2 -> java.awt.Point[x=1,y=1]
Formal type p1 -> :java.awt.Point
Formal type p2 -> :java.awt.geom.Point2D
p1' -> java.awt.Point[x=3,y=3]
=> nil
```

SEE ALSO

[remove-formal-type](#)

Removes the formal type from a Java object.

[cast](#)

Casts a Java object to a specific type

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[top](#)

format-micro-time

```
(format-micro-time time)
(format-micro-time time & options)
```

Formats a time given in microseconds as long or double.

Options:

:precision p e.g :precision 4 (defaults to 3)

```
(format-micro-time 203)
=> "203µs"
```

```
(format-micro-time 20389.0 :precision 2)
=> "0.02ms"
```

```
(format-micro-time 20389 :precision 2)
=> "0.02ms"
```

```
(format-micro-time 20389 :precision 0)
=> "0ms"
```

```
(format-micro-time 20386766)
=> "20.387s"
```



```
(format-micro-time 20386766 :precision 2)
=> "20.39s"
```

```
(format-micro-time 20386766 :precision 6)
=> "20.386766s"
```

SEE ALSO

[format-milli-time](#)

Formats a time given in milliseconds as long or double.

[format-nano-time](#)

Formats a time given in nanoseconds as long or double.

[top](#)

format-milli-time

```
(format-milli-time time)
(format-milli-time time & options)
```

Formats a time given in milliseconds as long or double.

Options:

:precision p e.g :precision 4 (defaults to 3)

```
(format-milli-time 203)
=> "203ms"
```

```
(format-milli-time 20389.0 :precision 2)
=> "20.39s"
```

```
(format-milli-time 20389 :precision 2)
=> "20.39s"
```

```
(format-milli-time 20389 :precision 0)
=> "20s"
```

SEE ALSO

[format-micro-time](#)

Formats a time given in microseconds as long or double.

[format-nano-time](#)

Formats a time given in nanoseconds as long or double.

[top](#)

format-nano-time

```
(format-nano-time time)
(format-nano-time time & options)
```

Formats a time given in nanoseconds as long or double.

Options:

`:precision p` e.g `:precision 4` (defaults to 3)

```
(format-nano-time 203)
=> "203ns"

(format-nano-time 20389.0 :precision 2)
=> "20.39µs"

(format-nano-time 20389 :precision 2)
=> "20.39µs"

(format-nano-time 20389 :precision 0)
=> "20µs"

(format-nano-time 203867669)
=> "203.868ms"

(format-nano-time 20386766988 :precision 2)
=> "20.39s"

(format-nano-time 20386766988 :precision 6)
=> "20.386767s"
```

SEE ALSO

[format-milli-time](#)

Formats a time given in milliseconds as long or double.

[format-micro-time](#)

Formats a time given in microseconds as long or double.

[nano-time](#)

Returns the current value of the running Java Virtual Machine's high-resolution time source, in nanoseconds.

[top](#)

fourth

```
(fourth coll)
```

Returns the fourth element of coll.

```
(fourth nil)
=> nil

(fourth [])
=> nil

(fourth [1 2 3 4 5])
=> 4

(fourth '())
=> nil

(fourth '(1 2 3 4 5))
=> 4
```

frequencies

```
(frequencies coll)
```

Returns a map from distinct items in coll to the number of times they appear.

```
(frequencies [:a :b :a :a])
=> {:a 3 :b 1}

;; Turn a frequency map back into a coll.
(mapcat (fn [[x n]] (repeat n x)) {:a 2 :b 1 :c 3})
=> (:a :a :b :c :c :c)
```

future

```
(future fn)
```

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result and return it on all subsequent calls to deref. If the computation has not yet finished, calls to deref will block, unless the variant of deref with timeout is used.

Thread local vars will be inherited by the future child thread. Changes of the child's thread local vars will not be seen on the parent.

```
(do
  (defn wait [] (sleep 300) 100)
  (let [f (future wait)]
    (deref f)))
=> 100

(let [f (future #(do (sleep 300) 100))]
  (deref f))
=> 100

(do
  (defn wait [x] (sleep 300) (+ x 100))
  (let [f (future (partial wait 10))]
    (deref f)))
=> 110

(do
  (defn sum [x y] (+ x y))
  (let [f (future (partial sum 3 4))]
    (deref f)))
=> 7

;; demonstrates the use of thread locals with futures
(do
  ;; parent thread locals
  (binding [a 10 b 20]
    ;; future with child thread locals
```

```
(let [f (future (fn [] (binding [b 90] {:a a :b b})))
      {:child @f :parent {:a a :b b}})])
=> {:parent {:a 10 :b 20} :child {:a 10 :b 90}}
```

SEE ALSO

[deref](#)

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will ...

[realized?](#)

Returns true if a value has been produced for a promise, delay, or future.

[done?](#)

Returns true if the future or promise is done otherwise false

[cancel](#)

Cancels a future or a promise

[cancelled?](#)

Returns true if the future or promise is cancelled otherwise false

[future-task](#)

Takes a function f without arguments and yields a future object that will invoke the function in another thread.

[promise](#)

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, ...

[futures-fork](#)

Creates a list of count futures. The worker factory is single argument function that gets the worker index (0..count-1) as argument ...

[futures-wait](#)

Waits for all futures to get terminated. If the waiting thread is interrupted the futures are cancelled.

[top](#)

future-task

```
(future-task f completed-fn)
(future-task f success-fn failure-fn)
```

Takes a function f without arguments and yields a future object that will invoke the function in another thread.

If a single completed function is passed it will be called with the future as its argument as soon as the future has completed. If a success and a failure function are passed either the success or failure function will be called as soon as the future has completed. Upon success the success function will be called with the future's result as its argument, upon failure the failure function will be called with the exception as its argument.

In combination with a queue a completion service can be built. The tasks appear in the queue in the order they have completed.

Thread local vars will be inherited by the future child thread. Changes of the child's thread local vars will not be seen on the parent.

```
;; building a completion service
;; CompletionService = incoming worker queue + worker threads + output data queue
(do
  (def q (queue 10))
  (defn process [s v] (sleep s) v)
  (defn failure [s m] (sleep s) (throw (ex :VncException m)))
  (future-task (partial process 200 2) #(offer! q %) #(offer! q %))
  (future-task (partial process 400 4) #(offer! q %) #(offer! q %))
  (future-task (partial process 100 1) #(offer! q %) #(offer! q %))
  (future-task (partial failure 300 "Failed 3") #(offer! q %) #(offer! q %))
  (println (poll! q 1000))
  (println (poll! q 1000))
  (println (poll! q 1000))
  (println (poll! q 1000)))
```

```

1
2
com.github.jlangch.venice.VncException: Failed 3
4
=> nil

;; building a completion service (future-task API variant)
(do
  (def q (queue 10))
  (defn process [s v] (sleep s) v)
  (defn failure [s m] (sleep s) (throw (ex :VncException m)))
  (defn print_result [f] (try (println @f) (catch :Exception e (println e))))
  (future-task (partial process 200 2) #(offer! q %))
  (future-task (partial process 400 4) #(offer! q %))
  (future-task (partial process 100 1) #(offer! q %))
  (future-task (partial failure 300 "Failed 3") #(offer! q %))
  (print_result (poll! q 1000))
  (print_result (poll! q 1000))
  (print_result (poll! q 1000))
  (print_result (poll! q 1000)))
1
2
com.github.jlangch.venice.VncException: Failed 3
4
=> nil

```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[top](#)

future?

```
(future? f)
```

Returns true if f is a Future otherwise false

```

(future? (future (fn [] 100)))
=> true

```

[top](#)

futures-fork

```
(futures-fork count worker-factory-fn)
```

Creates a list of count futures. The worker factory is single argument function that gets the worker index (0..count-1) as argument and returns a worker function. Returns a list with the created futures.

```

(do
  (def mutex 0)
  (defn log [& xs]
    (locking mutex (println (apply str xs))))
  (defn factory [n]

```

```
(fn [] (log "Worker" n)))
(apply futures-wait (futures-fork 3 factory)))
Worker0
Worker2
Worker1
=> nil
```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[futures-wait](#)

Waits for all futures to get terminated. If the waiting thread is interrupted the futures are cancelled.

[top](#)

futures-thread-pool-info

```
(futures-thread-pool-info)
```

Returns the thread pool info of the ThreadPoolExecutor serving the futures.

<i>core-pool-size</i>	the number of threads to keep in the pool, even if they are idle
<i>maximum-pool-size</i>	the maximum allowed number of threads
<i>current-pool-size</i>	the current number of threads in the pool
<i>largest-pool-size</i>	the largest number of threads that have ever simultaneously been in the pool
<i>active-thread-count</i>	the approximate number of threads that are actively executing tasks
<i>scheduled-task-count</i>	the approximate total number of tasks that have ever been scheduled for execution
<i>completed-task-count</i>	the approximate total number of tasks that have completed execution

```
(futures-thread-pool-info)
```

```
=> {:core-pool-size 0 :maximum-pool-size 200 :current-pool-size 4 :largest-pool-size 4 :active-thread-count 0 :
scheduled-task-count 24 :completed-task-count 24}
```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[top](#)

futures-wait

```
(futures-wait & futures)
```

Waits for all futures to get terminated. If the waiting thread is interrupted the futures are cancelled.

```
(do
  (def mutex 0)
  (defn log [& xs]
    (locking mutex (println (apply str xs))))
  (defn factory [n]
    (fn [] (log "Worker" n)))
  (apply futures-wait (futures-fork 3 factory)))
```

```
Worker0  
Worker2  
Worker1  
=> nil
```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[futures-fork](#)

Creates a list of count futures. The worker factory is single argument function that gets the worker index (0..count-1) as argument ...

[top](#)

gc

```
(gc)
```

Run the Java garbage collector. Runs the finalization methods of any objects pending finalization prior to the GC.

```
(gc)  
=> nil
```

[top](#)

gensym

```
(gensym)  
(gensym prefix)
```

Generates a symbol.

```
(gensym)  
=> G__31234
```

```
(gensym "prefix_")  
=> prefix_31263
```

[top](#)

geoip/addr-ranges->trie

```
(geoip/addr-ranges->trie ranges)
```

Creates a trie map from a sequence of address ranges.

```
(do  
  (def private-ip4-trie (geoip/addr-ranges->trie geoip/private-ip4-addresses))  
  
  (defn private-ip? [ip]  
    (some? (cidr/lookup-reverse private-ip4-trie ip))))
```

```
(private-ip? "192.168.0.1"))
=> true
```

[top](#)

geoip/build-maxmind-city-db-url

(geoip/build-maxmind-city-db-url)

Build the URL for downloading the MaxMind city GEO IP database.

The download requires an account ID and a license key that is sent as part of the basic authentication.

The license key to download the free MaxMind GeoLite databases can be obtained from the [MaxMind](#) home page.

```
(do
  (load-module :geoip)
  (geoip/build-maxmind-city-db-url))
=> "https://download.maxmind.com/geoip/databases/GeoLite2-City-CSV/download?suffix=zip"
```

SEE ALSO

[geoip/download-maxmind-db](#)

Downloads the MaxMind country or city GEO IP database. Returns the DB as bytearray. The type is either :country or :city.

[geoip/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[top](#)

geoip/build-maxmind-country-db-url

(geoip/build-maxmind-country-db-url)

Build the URL for the MaxMind country GEO IP database.

The download requires an account ID and a license key that is sent as part of the basic authentication.

The license key to download the free MaxMind GeoLite databases can be obtained from the [MaxMind](#) home page.

```
(do
  (load-module :geoip)
  (geoip/build-maxmind-country-db-url))
=> "https://download.maxmind.com/geoip/databases/GeoLite2-Country-CSV/download?suffix=zip"
```

SEE ALSO

[geoip/download-maxmind-db](#)

Downloads the MaxMind country or city GEO IP database. Returns the DB as bytearray. The type is either :country or :city.

[geoip/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[top](#)

geoip/country-to-location-resolver


```
(geoup/country-to-location-resolver location-csv)
```

Returns a resolve function that resolves countries given by a country 2-digit ISO code to its latitude/longitude location. The resolve function returns the latitude/longitude or nil if the country is not supported.

The resolver loads Google country database and caches the data for location resolves.

```
(do
  (def rv (geoup/country-to-location-resolver geoup/download-google-country-db))
  (rv "PL")) ;; => ["51.919438", "19.145136"]
```

SEE ALSO

[geoup/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geoup/ip-to-country-resolver](#)

Returns a resolve function that resolves an IP addresses to its associated country. The resolve function returns the country information ...

[geoup/ip-to-country-loc-resolver](#)

Returns a resolve function that resolves an IP address to its associated country and latitude/longitude location. The resolve function ...

[geoup/ip-to-city-loc-resolver](#)

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function ...

[geoup/ip-to-city-loc-resolver-mem-optimized](#)

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function ...

[top](#)

geoup/download-google-country-db-to-csvfile

```
(geoup/download-google-country-db-to-csvfile csvfile)
```

Downloads the Google country GPS database to the given CSV file location. The database holds a mapping from country to location (latitude /longitude).

The Google country database URL is defined in the global var 'geoup/google-country-url'.

```
(do
  (load-module :geoup)
  (geoup/download-google-country-db-to-csvfile "./country-gps.csv"))
```

SEE ALSO

[geoup/download-google-country-db](#)

Downloads the Google country database. The database holds a mapping from country to location (latitude/longitude).

[top](#)

geoup/download-maxmind-db

```
(geoup/download-maxmind-db type account-id lic-key)
```

Downloads the MaxMind country or city GEO IP database. Returns the DB as bytearray. The type is either :country or :city.

The download requires an account ID and a license key that is sent as part of the basic authentication.

The license key to download the free MaxMind GeoLite databases can be obtained from the [MaxMind](#) home page.

Please ensure that your servers can make HTTPS connections to the following hostname:
mm-prod-geoip-databases.a2649acb697e2c09b632799562c076f2.r2.cloudflarestorage.com

```
(do
  (load-module :geoip)
  (geoip/download-maxmind-db :country
    "YOUR-MAXMIND-ACCOUNT-ID"
    "YOUR-MAXMIND-LIC-KEY"))
```

SEE ALSO

[geoip/build-maxmind-country-db-url](#)

Build the URL for the MaxMind country GEO IP database.

[geoip/build-maxmind-city-db-url](#)

Build the URL for downloading the MaxMind city GEO IP database.

top

geoip/download-maxmind-db-to-zipfile

```
(geoip/download-maxmind-db-to-zipfile zipfile type account-id lic-key)
```

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

The download requires your personal MaxMind license key. The license to download the free MaxMind GeoLite databases can be obtained from the [MaxMind](#) home page.

```
(do
  (load-module :geoip)
  (geoip/download-maxmind-db-to-zipfile "./geoip-country.zip"
    :country
    "YOUR-MAXMIND-ACCOUNT-ID"
    "YOUR-MAXMIND-LIC-KEY"))
```

SEE ALSO

[geoip/build-maxmind-country-db-url](#)

Build the URL for the MaxMind country GEO IP database.

[geoip/build-maxmind-city-db-url](#)

Build the URL for downloading the MaxMind city GEO IP database.

top

geoip/ip-to-city-loc-resolver

```
(geoip/ip-to-city-loc-resolver geoip-zip)
```

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function returns the city and the latitude/longitude or nil if no data is found.

The MindMax city geoip-zip may be a bytebuf, a file, a string (file path) or an InputStream.

The resolver loads the MindMax IPv4 and IPv6 city database and caches the data for IP address resolves.

As of July 2020 the MaxMind city database has:

2'917'097 IPv4 blocks

459'294	IPv6 blocks
118'189	cities

Note:

The MaxMind city IPv4 and IPv6 databases have 220MB of size on disk. It takes considerable time to load the data. Preprocessed and ready to work in the GEO IP modules ~3GB of memory is required.

Once the resolver has loaded the data the lookups are very fast.

```
(do
  (def rv (geoip/ip-to-city-loc-resolver "./geoip-city.zip"))

  (rv "192.241.235.46")) ;; => {:ip "192.241.235.46"
                                ;;   :loc ["37.7353" "-122.3732"]
                                ;;   :country-name "United States"
                                ;;   :country-iso "US"
                                ;;   :region "California"
                                ;;   :city "San Francisco"}
```

SEE ALSO

[geoip/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geoip/ip-to-country-resolver](#)

Returns a resolve function that resolves an IP addresses to its associated country. The resolve function returns the country information ...

[geoip/ip-to-country-loc-resolver](#)

Returns a resolve function that resolves an IP address to its associated country and latitude/longitude location. The resolve function ...

[geoip/ip-to-city-loc-resolver-mem-optimized](#)

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function ...

[geoip/country-to-location-resolver](#)

Returns a resolve function that resolves countries given by a country 2-digit ISO code to its latitude/longitude location. The resolve ...

top

geoip/ip-to-city-loc-resolver-mem-optimized

```
(geoip/ip-to-city-loc-resolver-mem-optimized geoip-zip)
```

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function returns the city and the latitude/longitude or nil if no data is found.

The MindMax city geoip-zip may be a bytebuf, a file, a string (file path) or an InputStream.

The resolver loads the MindMax IPv4 and IPv6 city database and caches the data for IP address resolves.

As of July 2020 the MaxMind city database has:

2'917'097	IPv4 blocks
459'294	IPv6 blocks
118'189	cities

Note:

The MaxMind city IPv4 and IPv6 databases have 220MB of size on disk. It takes considerable time to load the data. This is a memory optimized resolver version on the cost of performance.

For best performance on the cost of memory use the resolver 'geoip/ip-to-city-loc-resolver' instead!

```
(do
  (def rv (geoip/ip-to-city-loc-resolver-mem-optimized "./geoip-city.zip"))
```

```
(rv "192.241.235.46")) ;; => {:ip "192.241.235.46"
                               ;;      :loc ["37.7353" "-122.3732"]
                               ;;      :country-name "United States"
                               ;;      :country-iso "US"
                               ;;      :region "California"
                               ;;      :city "San Francisco"}
```

SEE ALSO

[geop/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geop/ip-to-country-resolver](#)

Returns a resolve function that resolves an IP addresses to its associated country. The resolve function returns the country information ...

[geop/ip-to-country-loc-resolver](#)

Returns a resolve function that resolves an IP address to its associated country and latitude/longitude location. The resolve function ...

[geop/ip-to-city-loc-resolver](#)

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function ...

[geop/country-to-location-resolver](#)

Returns a resolve function that resolves countries given by a country 2-digit ISO code to its latitude/longitude location. The resolve ...

top

geop/ip-to-country-loc-resolver

```
(geop/ip-to-country-loc-resolver geop-zip location-csv)
```

Returns a resolve function that resolves an IP address to its associated country and latitude/longitude location. The resolve function returns the country and the latitude/longitude or nil if no data is found.

The MindMax country geop-zip may be a bytebuf, a file, a string (file path) or an InputStream.

The resolver loads the MindMax IPv4 and IPv6 country and the Google country database and caches the data for IP address resolves.

```
(do
  (def rv (geop/ip-to-country-loc-resolver
           "./geop-country.zip"
           (geop/download-google-country-db)))

  (rv "91.223.55.1")) ;; => {:ip "91.223.55.6"
                             ;;      :loc ["51.919438" "19.145136"]
                             ;;      :country-name "Poland"
                             ;;      :country-iso "PL"}
```

SEE ALSO

[geop/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geop/ip-to-country-resolver](#)

Returns a resolve function that resolves an IP addresses to its associated country. The resolve function returns the country information ...

[geop/ip-to-city-loc-resolver](#)

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function ...

[geop/ip-to-city-loc-resolver-mem-optimized](#)

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function ...

[geop/country-to-location-resolver](#)

Returns a resolve function that resolves countries given by a country 2-digit ISO code to its latitude/longitude location. The resolve ...

geoip/ip-to-country-resolver

```
(geoip/ip-to-country-resolver geoip-zip)
```

Returns a resolve function that resolves an IP addresses to its associated country. The resolve function returns the country information for a given IP address.

The MindMax country geoip-zip may be a bytebuf, a file, a string (file path) or an InputStream.

The resolver loads the MindMax IPv4 and IPv6 country databases and caches the data for subsequent IP resolves.

As of July 2020 the MaxMind country database has:

```
303'448   IPv4 blocks
107'641   IPv6 blocks
    253    countries
```

```
(do
  (def rv (geoip/ip-to-country-resolver "./geoip-country.zip"))
  (rv "91.223.55.1")) ;; => { :country-name "Poland"
                             ;;      :country-iso "PL" }
```

SEE ALSO

[geoip/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geoip/ip-to-country-loc-resolver](#)

Returns a resolve function that resolves an IP address to its associated country and latitude/longitude location. The resolve function ...

[geoip/ip-to-city-loc-resolver](#)

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function ...

[geoip/ip-to-city-loc-resolver-mem-optimized](#)

Returns a resolve function that resolves an IP address to its associated city and latitude/longitude location. The resolve function ...

[geoip/country-to-location-resolver](#)

Returns a resolve function that resolves countries given by a country 2-digit ISO code to its latitude/longitude location. The resolve ...

geoip/map-location-to-numeric

```
(map-location-to-numeric loc)
```

Maps a location to numerical coordinates. A location is given as a vector of a latitude and a longitude.

Returns a location vector with a numerical latitude and a longitude.

```
(do
  (load-module :geoip)
  (geoip/map-location-to-numeric ["51.919438", "19.145136"]))
=> [51.919438 19.145136]
```

geoip/parse-maxmind-city-db

```
(geoip/parse-maxmind-city-db zip)
```

Parses the MaxMind city-location CSV file. Returns a map with the city geoname-id as key and the city/country data as value.

Return:

```
{ "2643743" {:country-iso "GB" :country-name "England"
              :region "England" :city "London"}}
  "2661881" {:country-iso "CH" :country-name "Switzerland"
              :region "Aargau" :city "Aarau"} }
```

```
(do
  (load-module :geoip)
  (geoip/download-maxmind-db-to-zipfile "./geoip-city.zip"
    :city
    "YOUR-MAXMIND-ACCOUNT-ID"
    "YOUR-MAXMIND-LIC-KEY")
  (geoip/parse-maxmind-city-db "./geoip-city.zip"))
```

SEE ALSO

[geoip/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geoip/parse-maxmind-country-db](#)

Parses the MaxMind country-location CSV file. Returns a map with the country geoname-id as key and the country data as value.

[top](#)

geoip/parse-maxmind-city-ip-db

```
(geoip/parse-maxmind-city-ip-db ip-type zip maxmind-cities)
```

Parses the MaxMind city IP blocks database. Expects a MaxMind city IP database zip. ip-type is either :IPv4 or :IPv6. The zip may be a bytebuf, a file, a string (file path) or an InputStream.

The maxmind-countries are optional and map the geoname-id to country data.

Returns a trie datastructure with the CIDR address as the key and a map with city/country data as the value.

maxmind-cities:

```
{ "2643743" {:country-iso "GB" :country-name "England"
              :region "England" :city "London"}}
  "2661881" {:country-iso "CH" :country-name "Switzerland"
              :region "Aargau" :city "Aarau"} }
```

```
(do
  (load-module :geoip)
  (geoip/download-maxmind-db-to-zipfile "./geoip-city.zip"
    :city
    "YOUR-MAXMIND-ACCOUNT-ID"
    "YOUR-MAXMIND-LIC-KEY")
  (geoip/parse-maxmind-city-ip-db
    :IPv4
    "./geoip-city.zip"
    nil))
```

```
(do
  (load-module :geoip)
  (geoip/download-maxmind-db-to-zipfile "./geoip-city.zip"
    :city
    "YOUR-MAXMIND-ACCOUNT-ID"
    "YOUR-MAXMIND-LIC-KEY")

  (geoip/parse-maxmind-city-ip-db
    :IPv6
    "./geoip-city.zip"
    (geoip/parse-maxmind-city-db "./geoip-city.zip")))
```

SEE ALSO

[geoip/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geoip/parse-maxmind-city-db](#)

Parses the MaxMind city-location CSV file. Returns a map with the city geoname-id as key and the city/country data as value.

[geoip/parse-maxmind-country-ip-db](#)

Parses the MaxMind country IP blocks database. Expects a Maxmind country IP database zip. ip-type is either :IPv4 or :IPv6. The zip ...

[top](#)

geoip/parse-maxmind-country-db

```
(geoip/parse-maxmind-country-db zip)
```

Parses the MaxMind country-location CSV file. Returns a map with the country geoname-id as key and the country data as value.

Return:

```
{ "49518" {:country-iso "RW" :country-name "Rwanda"}
  "51537" {:country-iso "SO" :country-name "Somalia"} }
```

```
(do
  (load-module :geoip)
  (geoip/download-maxmind-db-to-zipfile "./geoip-country.zip"
    :country
    "YOUR-MAXMIND-ACCOUNT-ID"
    "YOUR-MAXMIND-LIC-KEY")

  (geoip/parse-maxmind-country-db "./geoip-country.zip"))
```

SEE ALSO

[geoip/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geoip/parse-maxmind-city-db](#)

Parses the MaxMind city-location CSV file. Returns a map with the city geoname-id as key and the city/country data as value.

[top](#)

geoip/parse-maxmind-country-ip-db

```
(geoip/parse-maxmind-country-ip-db ip-type zip maxmind-countries)
```

Parses the MaxMind country IP blocks database. Expects a Maxmind country IP database zip. ip-type is either :IPv4 or :IPv6. The zip may be a bytebuf, a file, a string (file path) or an InputStream.

The maxmind-countries are optional and map the geoname-id to country data.

Returns a trie datastructure with the CIDR address as the key and a map with country data as the value.

maxmind-countries:

```
{ "49518" {:country-iso "RW" :country-name "Rwanda"}
  "51537" {:country-iso "SO" :country-name "Somalia"} }
```

Return:

```
{ 223 [ [(cidr-parse "223.255.254.0/24") {:country-iso "SG"
                                           :country-name "Singapore"}]
         [(cidr-parse "223.255.255.0/24") {:country-iso "AU"
                                           :country-name "Australia"}]
      ] }
```

```
(do
  (load-module :geoiip)
  (geoiip/download-maxmind-db-to-zipfile "./geoiip-country.zip"
    :country
    "YOUR-MAXMIND-ACCOUNT-ID"
    "YOUR-MAXMIND-LIC-KEY")

  (geoiip/parse-maxmind-country-ip-db
    :IPv4
    "./geoiip-country.zip"
    nil))

(do
  (load-module :geoiip)
  (geoiip/download-maxmind-db-to-zipfile "./geoiip-country.zip"
    :country
    "YOUR-MAXMIND-ACCOUNT-ID"
    "YOUR-MAXMIND-LIC-KEY")

  (geoiip/parse-maxmind-country-ip-db
    :IPv6
    "./geoiip-country.zip"
    (geoiip/parse-maxmind-country-db "./geoiip-country.zip")))
```

SEE ALSO

[geoiip/download-maxmind-db-to-zipfile](#)

Downloads the MaxMind country or city GEO IP database to the given ZIP file. The type is either :country or :city.

[geoiip/parse-maxmind-country-db](#)

Parses the MaxMind country-location CSV file. Returns a map with the country geoname-id as key and the country data as value.

[geoiip/parse-maxmind-city-ip-db](#)

Parses the MaxMind city IP blocks database. Expects a MaxMind city IP database zip. ip-type is either :IPv4 or :IPv6. The zip may be ...

top

get

```
(get map key)
(get map key not-found)
```

Returns the value mapped to key, not-found or nil if key not present.

Note: `(get :x foo)` is almost twice as fast as `(:x foo)`

```
(get {:a 1 :b 2} :b)
=> 2
```



```
(get [0 1 2 3] 1)
=> 1
```

```
;; keywords act like functions on maps
(:b {:a 1 :b 2})
=> 2
```

top

get-in

```
(get-in m ks)
(get-in m ks not-found)
```

Returns the value in a nested associative structure, where ks is a sequence of keys. Returns nil if the key is not present, or the not-found value if supplied.

```
(get-in {:a 1 :b {:c 2 :d 3}} [:b :c])
=> 2
```

```
(get-in [:a :b :c] [0])
=> :a
```

```
(get-in [:a :b [:c :d :e]] [2 1])
=> :d
```

```
(get-in {:a 1 :b {:c [4 5 6]}} [:b :c 1])
=> 5
```

top

gradle/task

```
(gradle/task name & options)
(gradle/task name out-fn & options)
(gradle/task name out-fn err-fn throw-ex & options)
```

Runs a gradle task

```
(gradle/with-home "/Users/foo/Documents/Tools/gradle-5.6.2"
                  "/Users/foo/Documents/Projects/my-project"
  (gradle/task compile)
  (gradle/task compile "--warning-mode=all" "--stacktrace")
  (gradle/task compile println)
  (gradle/task compile println println true)
  (gradle/task compile println println true "--stacktrace"))
```

top

gradle/version

```
(gradle/version)
```

Returns the Gradle version

```
(gradle/with-home "/Users/foo/Documents/Tools/gradle-5.6.2"
                  "/Users/foo/Documents/Projects/my-project"
  (gradle/version))
```

[top](#)

gradle/with-home

(with-home gradle-dir proj-dir & forms)

Sets the Gradle home and the project directory for all subsequent forms.

```
(gradle/with-home "/Users/foo/Documents/Tools/gradle-5.6.2"
                  "/Users/foo/Documents/Projects/my-project"
  (gradle/version))
```

[top](#)

gradlew/run

(gradlew/run proj-home out-fn err-fn & args)

Runs one or more Gradle tasks.

Note: Use this module only for projects based on the Gradle wrapper

Arguments:

proj-home	The project directory
out-fn	a function with a single string argument that receives line by line from the process' stdout.
err-fn	a function with a single string argument that receives line by line from the process' stderr.
args	Any number of task names and Gradle options

```
(do
  (load-module :gradlew)
  (let [java-home (system-env :JAVA_11_HOME)]
    (gradlew/run "/Users/foo/projects/bar"
      println
      println
      ;; tasks
      "clean"
      "build"
      ;; options
      "--warning-mode=all"
      "--console=plain"
      "--stacktrace"
      (str "-Dorg.gradle.java.home=\"" java-home "\""))
```

[top](#)

gradlew/run*

```
(gradlew/run* proj-home out-fn err-fn & args)
```

Runs one or more Gradle tasks and prints a list of the tasks and the options taken from the passed arguments.

Note: Use this module only for projects based on the Gradle wrapper

Apart from printing the passed tasks and options the function is identical to `gradlew/run`.

Arguments:

proj-home	The project directory
out-fn	a function with a single string argument that receives line by line from the process' stdout. May be nil.
err-fn	a function with a single string argument that receives line by line from the process' stderr. May be nil.
args	Any number of task names and Gradle options

```
(do
  (load-module :gradlew)
  (let [java-home (system-env :JAVA_11_HOME)]
    (gradlew/run* "/Users/foo/projects/bar"
      println
      println
      ;; tasks
      "clean"
      "build"
      ;; options
      "--warning-mode=all"
      "--console=plain"
      "--stacktrace"
      (str "-Dorg.gradle.java.home=\"" java-home "\"")))
  )
```

[top](#)

gradlew/version

```
(gradlew/version)
```

Returns the Gradle version

Note: Use this module only for projects based on the Gradle wrapper

```
(do
  (load-module :gradlew)
  (gradlew/version "/Users/foo/projects/bar"))
```

[top](#)

grep/grep

```
(grep dir file-glob line-pattern & options)
```

Search for lines that match a regular expression in text files. The search starts from a base directory and chooses all files that match a globbing pattern.

Options:

:print b e.g :print false, defaults to true

With the print option `:print true`, `grep` prints the matches in a human readable form, one line per match in the format `"{{filename}}:{{lineno}}:{{line}}"`.

With the print option `:print false`, `grep` prints the matches in a machine readable form. It returns a list of tuples `[[{{filename}}, {{lineno}}, {{line}}]`.

```
(do
  (load-module :grep)
  (grep/grep "/Users/foo/logs" "*.log" ".*Error.*"))
```

SEE ALSO

[grep/grep-zip](#)

Search for lines that match a regular expression in text files within ZIP files. The search chooses all files in the ZIP that match ...

[io/file-matches-glob?](#)

Returns true if the file `f` matches the glob pattern. `f` must be a file or a string (file path).

[top](#)

grep/grep-zip

```
(grep/grep-zip dir zipfile-glob file-glob line-pattern & options)
```

Search for lines that match a regular expression in text files within ZIP files. The search chooses all files in the ZIP that match a globbing pattern. The search starts from a base directory and chooses all ZIP files that match the zipfile globbing pattern.

Options:

`:print b` e.g `:print false`, defaults to `true`

With the print option `:print true`, `grep-zip` prints the matches in a human readable form, one line per match in the format `"{{zipfile}}!{{filename}}:{{lineno}}:{{line}}"`.

With the print option `:print false`, `grep-zip` prints the matches in a machine readable form. It returns a list of tuples `[[{{zipname}}, {{filename}}, {{lineno}}, {{line}}]`.

```
(do
  (load-module :grep)
  (grep/grep-zip "/Users/foo/logs" "logs*.zip" "**/*.log" ".*Error.*"))
```

SEE ALSO

[grep/grep](#)

Search for lines that match a regular expression in text files. The search starts from a base directory and chooses all files that ...

[io/file-matches-glob?](#)

Returns true if the file `f` matches the glob pattern. `f` must be a file or a string (file path).

[top](#)

group-by

```
(group-by f coll)
```

Returns a map of the elements of `coll` keyed by the result of `f` on each element. The value at each key will be a vector of the corresponding elements, in the order they appeared in `coll`.

```
(group-by count ["a" "as" "asd" "aa" "asdf" "qwer"])
=> {1 ["a"] 2 ["as" "aa"] 3 ["asd"] 4 ["asdf" "qwer"]}

(group-by odd? (range 10))
=> {false [0 2 4 6 8] true [1 3 5 7 9]}

(group-by identity (seq "abracadabra"))
=> {#\a [\a \a \a \a \a] #\b [#\b \b] #\r [#\r \r] #\c [#\c] #\d [#\d]}
```

[top](#)

halt-when

```
(halt-when pred)
(halt-when pred retf)
```

Returns a transducer that ends transduction when pred returns true for an input. When retf is supplied it must be a fn of 2 arguments - it will be passed the (completed) result so far and the input that triggered the predicate, and its return value (if it does not throw an exception) will be the return value of the transducer. If retf is not supplied, the input that triggered the predicate will be returned. If the predicate never returns true the transduction is unaffected.

```
(do
  (def xf (comp (halt-when #(<= % 10)) (filter odd?)))
  (transduce xf conj [1 2 3 4 5 6 7 8 9]))
=> [1 3 5 7 9]

(do
  (def xf (comp (halt-when #(> % 5)) (filter odd?)))
  (transduce xf conj [1 2 3 4 5 6 7 8 9]))
=> 6
```

[top](#)

hash-map

```
(hash-map & keyvals)
(hash-map map)
```

Creates a new hash map containing the items.

```
(hash-map :a 1 :b 2)
=> {:a 1 :b 2}

(hash-map (sorted-map :a 1 :b 2))
=> {:a 1 :b 2}
```

[top](#)

hash-map?

```
(hash-map? obj)
```

Returns true if obj is a hash map

```
(hash-map? (hash-map :a 1 :b 2))
=> true
```

[top](#)

hexdump/dump

(dump s & opts)

Prints a hexdump of the given argument to `*out*`. Optionally supply byte offset (:offset, default: 0) and size (:size, default: :all) arguments. Can create hexdump from a collection of values, a bytebuf, a java.io.File, or a string representing a path to a file.

Example: (hexdump/dump (range 100))

```
00000000: 0001 0203 0405 0607 0809 0a0b 0c0d 0e0f  ....
00000010: 1011 1213 1415 1617 1819 1a1b 1c1d 1e1f  ....
00000020: 2021 2223 2425 2627 2829 2a2b 2c2d 2e2f  !"#$%&'()*+,-./
00000030: 3031 3233 3435 3637 3839 3a3b 3c3d 3e3f  0123456789;<=>?
00000040: 4041 4243 4445 4647 4849 4a4b 4c4d 4e4f  @ABCDEFGHJKLMNO
00000050: 5051 5253 5455 5657 5859 5a5b 5c5d 5e5f  PQRSTUVWXYZ[\]^_
00000060: 6061 6263                                `abc
```

```
(hexdump/dump [0 1 2 3])
```

```
(hexdump/dump (range 1000))
```

```
(hexdump/dump (range 10000) :offset 9000 :size 256)
```

```
(hexdump/dump "./img.png")
```

```
(hexdump/dump "./img.png" :offset 0 :size 64)
```

```
(try-with [ps (io/capturing-print-stream)]
  (binding [*out* ps]
    (hexdump/dump [0 1 2 3])
    (str ps)))
```

[top](#)

highlight

(highlight form)

Syntax highlighting. Reads the form and returns a list of (token, token-class) tuples.

Token classes:

:comment	; ...
:whitespaces	" ", "\n", " \n"
:string	"lorem", """"lorem""""
:number	100, 100I, 100.0, 100.23M
:constant	nil, true, false
:keyword	:alpha
:symbol	alpha

:symbol-special-form	def, loop, ...
:symbol-function-name	+, println, ...
:quote	'
:quasi-quote	`
:unquote	~
:unquote-splicing	~@
:meta	^private, ^{:arglist '() :doc "..."}
:at	@
:hash	#
:brace-begin	{
:brace-end	}
:bracket-begin	[
:bracket-end]
:parenthesis-begin	(
:parenthesis-end)
:unknown	anything that could not be classified

```
(highlight "(+ 10 20)")
=> (("(" :parenthesis-begin) ("+" :symbol-function-name) (" " :whitespaces) ("10" :number) (" " :whitespaces)
("20" :number) (")" :parenthesis-end))

(highlight "(if (= 1 2) true false)")
=> (("(" :parenthesis-begin) ("if" :symbol-special-form) (" " :whitespaces) "(" :parenthesis-begin) ("=" :
symbol-function-name) (" " :whitespaces) ("1" :number) (" " :whitespaces) ("2" :number) (")" :parenthesis-end)
(" " :whitespaces) ("true" :constant) (" " :whitespaces) ("false" :constant) (")" :parenthesis-end))
```

[top](#)

host-address

(host-address)

Returns this host's ip address.

```
(host-address)
=> "192.168.178.26"
```

SEE ALSO

[host-name](#)

Returns this host's name.

[top](#)

host-name

(host-name)

Returns this host's name.

```
(host-name)
=> "pluto.fritz.box"
```

SEE ALSO

[host-address](#)

Returns this host's ip address.

[top](#)

http-client-j8/process-server-side-events

(process-server-side-events response handler)

Processes server side events (SSE) and calls for every event the handler 'handler'.

Note: The response must be of the mimetype "text/event-stream" otherwise the processor throws an exception!

The event handler is a three argument function:

```
(defn handler [type event event-count] ...)
```

type the notification type:
:opened - streaming started
:data - streamed event
:closed - streaming closed by the server

event the streamed event, available only if the notification type is :data, else nil

event-count the streamed event count, starting with 1 and incremented with every event sent

If the event handler returns the value :stop the processor stops handling any further events and closes the data stream to signal the server not to send any further events and close the server side stream as well.

If the event handler throws an exception while processing a data event the event processing will be stopped.

The handler blocks until the stream is either closed by the server or by the client. The timeout can be controlled via the connections' :read-timeout parameter.

Server side events are passed as maps to the handler. E.g. :

```
{ :id      "1"
  :event   "score"
  :data    [ "GOAL Liverpool 1 - 1 Arsenal"
            "GOAL Manchester United 3 - 3 Manchester City" ] }
```

Warning:

When not used over HTTP/2, SSE suffers from a limitation to the maximum number of open connections, which can be especially painful when opening multiple tabs, as the limit is per browser and is set to a very low number (6). The issue has been marked as "Won't fix" in Chrome and Firefox. This limit is per browser + domain, which means that you can open 6 SSE connections across all of the tabs.

When using HTTP/2, the maximum number of simultaneous HTTP streams is negotiated between the server and the client (defaults to 100).

The Java 8 Http Client does not support HTTP/2!

```
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/send :get
                        "http://localhost:8080/events"
                        :headers { "Accept"      "text/event-stream"
                                   "Cache-Control" "no-cache"
                                   "Connection"   "keep-alive"}
                        :conn-timeout 0
                        :read-timeout 0
                        :debug true)]
    (println "Status:" (:http-status response))

    ;; process the first 10 events and close the stream
```



```
(hc/process-server-side-events
  response
  (fn [type event event-count]
    (case type
      :opened (do (println "\nStreaming started")
                  :ok)
      :data   (do (println "Event: " (pr-str event))
                  ;; only process 10 events
                  (if (< event-count 10) :ok :stop))
      :closed (do (println "Streaming closed")
                  :ok))))))
```

SEE ALSO

[http-client-j8/slurp-response](#)

Slurps the response data from the response' input stream.

[http-client-j8/send](#)

Send a request

top

http-client-j8/send

(send method uri & options)

Send a request

Request Options:

:headers	A map of request headers. Headers can be single- or multi-value (comma separated): { "X-Header-1" "value1" "X-Header-2" "value1, value2, value3" }
:body	An optional body to send with the request The body may be of type <i>string</i> , <i>bytebuf</i> , <code>:java.io.InputStream</code>
:conn-timeout	An optional connection timeout in milliseconds
:read-timeout	An optional read timeout in milliseconds
:follow-redirects	Sets whether HTTP redirects (requests with response code 3xx) should be automatically followed.
:hostname-verifier	Sets the hostname verifier. An object of type <code>:javax.net.ssl.HostnameVerifier</code> . Use only for HTTPS requests
:ssl-socket-factory	Sets the SSL socket factory. An object of type <code>:javax.net.ssl.SSLSocketFactory</code> . Use only for HTTPS requests
:use-caches	A boolean indicating whether or not to allow caching. Defaults to false
:user-agent	User agent. Defaults to "Venice HTTP client (legacy)"
:debug	Debug true/false. Defaults to false. In debug mode prints the HTTP request and response data

Returns a map with the response fields:

:http-status	The HTTP status (a long)
:content-type	The content type. E.g.: "text/plain; charset=utf8"
:content-type-mimetype	The content type's mimetype. E.g.: "text/plain"
:content-type-charset	The content type's charset. E.g.: :utf-8
:content-encoding	The content transfer encoding (a keyword), if available else nil. E.g.: :gzip or :deflate
:content-length	The content length (a long), if available else -1

<code>:headers</code>	A map of headers. key: header name, value: list of header values
<code>:data-stream</code>	<p>The response data input stream.</p> <p>If the response content encoding is 'gzip' due to a request header "Accept-Encoding: gzip" wrap the data stream with a gzip input stream:</p> <pre>(io/wrap-is-with-gzip-input-stream (:data-stream response))</pre> <p>to uncompress the data.</p> <p>See <code>http-client-j8/slurp-response</code> to painlessly process responses.</p>

```
;; GET (get)
;;
;; 1/ Start the example REST Server {Venice}/doc/examples/scripts/rest-webapp.venice
;;   (drag & drop the file into a REPL and HIT [RET] to start it)
;; 2/ Run the Http Client commands listed in these examples
;;   (run the Http Client commands from a 2nd REPL)
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/send :get
                        "http://localhost:8080/employees"
                        :headers { "Accept" "application/json, text/plain" }
                        :debug true)
        status    (:http-status response)]
    (println "Status:" status)
    (println (slurp-response response :json-parse-mode :pretty-print))))

;; POST (create)
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/send :post
                        "http://localhost:8080/employees"
                        :headers {"Accept" "application/json, text/plain"
                                   "Content-Type" "application/json"}
                        :body (json/write-str { "name" "hanna",
                                                "role" "secretary" })
                        :debug true)
        status    (:http-status response)]
    (println "Status:" status)
    (println (hc/slurp-response response :json-parse-mode :pretty-print))))

;; PUT (update)
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/send :put
                        "http://localhost:8080/employees/1001"
                        :headers {"Accept" "application/json, text/plain"
                                   "Content-Type" "application/json"}
                        :body (json/write-str { "id" "1001",
                                                "name" "john",
                                                "role" "clerk" })
                        :debug true)
        status    (:http-status response)]
    (println "Status:" status)
    (println (hc/slurp-response response :json-parse-mode :pretty-print))))

;; DELETE (delete)
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/send :delete
                        "http://localhost:8080/employees/1000"
```

```

        :headers { "Accept" "text/plain" }
        :debug true)
    status (:http-status response)]
    (println "Status:" status)
    (println (hc/slurp-response response)))

;; GET over SSL
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])
  (load-module :java ['java :as 'j])

  (import :com.github.jlangch.venice.util.ssl.CustomHostnameVerifier)
  (import :com.github.jlangch.venice.util.ssl.Server_X509TrustManager)
  (import :com.github.jlangch.venice.util.ssl.TrustAll_X509TrustManager)
  (import :com.github.jlangch.venice.util.ssl.SSLSocketFactory)
  (import :java.security.cert.X509Certificate)

  (defn verify-host [hostname]
    (case hostname
      "localhost" true
      "foo.org" true
      false))

  (defn check-trust-server [certs auth-type]
    (doseq [c certs] (. c :checkValidity))
    (any? #(= "Foo" (. (% :getIssuerDN) :getName)) certs))

  (let [trust-manager-all (. :TrustAll_X509TrustManager :new)
        trust-manager-server (. :Server_X509TrustManager :new (j/as-bipredicate check-trust-server))
        hostname-verifier (. :CustomHostnameVerifier :new verify-host)
        response (hc/send :get
                          "https://localhost:8080/employees"
                          :headers { "Accept" "application/json, text/plain" }
                          :hostname-verifier hostname-verifier
                          :ssl-socket-factory (. :SSLSocketFactory trust-manager-all)
                          :debug true)
        status (:http-status response)]
    (println "Status:" status)
    (println (hc/slurp-response response)))

;; OAuth blueprint
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (defn get-access-token [api-key api-key-secret]
    (let [encoded-secret (-> (str api-key ":" api-key-secret)
                             (bytebuf-from-string :utf-8)
                             (str/encode-base64))
          response (hc/send :post
                           "https://.../oauth2/token"
                           :headers { "Accept" "application/json, text/plain"
                                       "Authorization" (str "Basic " encoded-secret)
                                       "Content-Type" "application/x-www-form-urlencoded" }
                           :body "grant_type=client_credentials")
          status (:http-status response)
          mimetype (:content-type-mimetype response)
          charset (:content-type-charset response)]
      (if (and (= 200 status) (= "application/json" mimetype))
        (as-> (:data-stream response) v
              (hc/slurp-json v charset)
              (get v "access_token"))
        (throw (ex VncException "Failed to get OAuth access token")))))

```

```
(defn list-member [access-token list-id]
  (let [response (hc/send :get
    (str "https://.../1.1/lists/members.json?list_id=" list-id)
    :headers { "Accept" "application/json, text/plain"
      "Authorization" (str "Bearer " accessToken)}}
    status (:http-status response)]
    (println "Status:" status)
    (println (hc/slurp-response response :json-parse-mode :pretty-print))))))
```

SEE ALSO

[http-client-j8/upload-file](#)

Upload a file.

[http-client-j8/upload-multipart](#)

Upload multiple parts.

[http-client-j8/slurp-response](#)

Slurps the response data from the response' input stream.

[top](#)

http-client-j8/slurp-response

```
(slurp-response response & options)
```

Slurps the response data from the response' input stream.

Returns the data according to the mimetype and charset of the 'Content-Type' response header.

Handles a 'Content-Encoding' transparently. Supports the encodings 'gzip' and 'deflate'. Other encodings are rejected with an exception.

application/xml	Returns a string according to the content type charset
application/json	Returns the JSON response according to the content type charset. Depending on the option <code>:json-parse-mode</code> returns the JSON parsed to a Venice map, as a JSON pretty printed string, or as a raw JSON string
text/plain	Returns a string according to the content type charset
text/html	Returns a string according to the content type charset
text/xml	Returns a string according to the content type charset
text/csv	Returns a string according to the content type charset
text/css	Returns a string according to the content type charset
text/json	Returns the JSON response according to the content type charset. Depending on the option <code>:json-parse-mode</code> returns the JSON parsed to a Venice map, as a JSON pretty printed string, or as a raw JSON string
text/event-stream	Throws an exception. An event stream can not be slurped. Use the function <code>process-server-side-events</code> instead!
<i>else</i>	Returns the response data as a byte buffer

Options:

<code>:json-parse-mode</code>	The option is used with JSON mimetypes. <code>:data</code> - parse the response to a Venice data map <code>:raw</code> - return the reponse as received <code>:pretty-print</code> - return a pretty print JSON string Defaults to <code>:data</code>
<code>:json-key-fn</code>	A single argument function that transforms JSON property names. This option is only available in <code>:data</code> parse mode E.g.: <code>:json-key-fn keyword</code>

```
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/send :get
                        "http://localhost:8080/employees"
                        :headers {"Accept" "application/json, text/plain"})
        status   (:http-status response)]
    (println "Status:" status)
    (println (hc/slurp-response response :json-parse-mode :pretty-print))))

(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/send :get
                        "http://localhost:8080/employees"
                        :headers {"Accept" "application/json, text/plain"})
        status   (:http-status response)]
    (println "Status:" status)
    (prn (hc/slurp-response response :json-parse-mode :data :json-key-fn keyword)))))
```

SEE ALSO

[http-client-j8/process-server-side-events](#)

Processes server side events (SSE) and calls for every event the handler 'handler'.

[http-client-j8/send](#)

Send a request

[top](#)

http-client-j8/status-client-range?

```
(status-client-range? status)
```

Returns true if the passed HTTP status code is in the range of the CLIENT codes (400 ... 499) else false.

```
(http-client-j8/status-client-range? 400)
=> true
```

SEE ALSO

[http-client-j8/status-ok-range?](#)

Returns true if the passed HTTP status code is in the range of the OK codes (200 ... 299) else false.

[http-client-j8/status-redirect-range?](#)

Returns true if the passed HTTP status code is in the range of the REDIRECT codes (300 ... 399) else false.

[http-client-j8/status-server-error-range?](#)

Returns true if the passed HTTP status code is in the range of the SERVER ERROR codes (500 ... 599) else false.

[top](#)

http-client-j8/status-ok-range?

```
(status-ok-range? status)
```

Returns true if the passed HTTP status code is in the range of the OK codes (200 ... 299) else false.

```
(http-client-j8/status-ok-range? 200)
=> true
```

SEE ALSO

[http-client-j8/status-redirect-range?](#)

Returns true if the passed HTTP status code is in the range of the REDIRECT codes (300 ... 399) else false.

[http-client-j8/status-client-range?](#)

Returns true if the passed HTTP status code is in the range of the CLIENT codes (400 ... 499) else false.

[http-client-j8/status-server-error-range?](#)

Returns true if the passed HTTP status code is in the range of the SERVER ERROR codes (500 ... 599) else false.

[top](#)

http-client-j8/status-redirect-range?

```
(status-redirect-range? status)
```

Returns true if the passed HTTP status code is in the range of the REDIRECT codes (300 ... 399) else false.

```
(http-client-j8/status-redirect-range? 300)
=> true
```

SEE ALSO

[http-client-j8/status-ok-range?](#)

Returns true if the passed HTTP status code is in the range of the OK codes (200 ... 299) else false.

[http-client-j8/status-client-range?](#)

Returns true if the passed HTTP status code is in the range of the CLIENT codes (400 ... 499) else false.

[http-client-j8/status-server-error-range?](#)

Returns true if the passed HTTP status code is in the range of the SERVER ERROR codes (500 ... 599) else false.

[top](#)

http-client-j8/status-server-error-range?

```
(status-server-error-range? status)
```

Returns true if the passed HTTP status code is in the range of the SERVER ERROR codes (500 ... 599) else false.

```
(http-client-j8/status-server-error-range? 500)
=> true
```

SEE ALSO

[http-client-j8/status-ok-range?](#)

Returns true if the passed HTTP status code is in the range of the OK codes (200 ... 299) else false.

[http-client-j8/status-redirect-range?](#)

Returns true if the passed HTTP status code is in the range of the REDIRECT codes (300 ... 399) else false.

[http-client-j8/status-client-range?](#)

Returns true if the passed HTTP status code is in the range of the CLIENT codes (400 ... 499) else false.

http-client-j8/upload-file

(upload-file file uri & options)

Upload a file.

Sets an implicit "Content-Type" header that is derived from the file's mimetype.

Request Options:

:headers	A map of request headers. Headers can be single- or multi-value (comma separated): {"X-Header-1" "value1" "X-Header-2" "value1, value2, value3"}
:conn-timeout	An optional connection timeout in milliseconds
:read-timeout	An optional read timeout in milliseconds
:follow-redirects	Sets whether HTTP redirects (requests with response code 3xx) should be automatically followed.
:hostname-verifier	Sets the hostname verifier. An object of type <code>:javax.net.ssl.HostnameVerifier</code> . Use only for HTTPS requests
:ssl-socket-factory	Sets the SSL socket factory. An object of type <code>:javax.net.ssl.SSLSocketFactory</code> . Use only for HTTPS requests
:use-caches	A boolean indicating whether or not to allow caching. Defaults to false
:user-agent	User agent. Defaults to "Venice HTTP client (legacy)"
:debug	Debug true/false. Defaults to false. In debug mode prints the HTTP request and response data and info on the uploaded file

Returns a map with the response fields:

:http-status	The HTTP status (a long)
:content-type-mimetype	The content type's mimetype. E.g.: "text/plain"
:content-type-charset	The content type's charset. E.g.: utf-8
:content-encoding	The content transfer encoding (a keyword), if available else nil. E.g.: <code>:gzip</code> or <code>:deflate</code>
:content-length	The content length (a long), if available else -1
:headers	A map of headers. key: header name, value: list of header values
:data-stream	The response data input stream. See <code>http-client-j8/slurp-response</code> to painlessly process responses.

```
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/upload-file
                  (io/file "/Users/foo/image.png")
                  "http://localhost:8080/upload"
                  :headers { "Accept" "text/plain" }
                  :debug true)
        status   (:http-status response)]
    (println "Status:" status)))
```

SEE ALSO

[http-client-j8/send](#)

Send a request

[http-client-j8/upload-multipart](#)

http-client-j8/upload-multipart

(upload-multipart parts uri & options)

Upload multiple parts.

The upload supports string parts, file parts, and generic parts. Any number of parts can be uploaded.

Sets the "Content-Type" header to "multipart/form-data".

The parts are passed as a map of part data:

```
{ ;; a string part
  "Part-1" "xxxxxxxxxxx"

  ;; a file part
  "Part-2" (io/file "/Users/juerg/Desktop/image.png")

  ;; a x-www-form-urlencoded (generic) part
  "Part-3" { :mimetype "application/x-www-form-urlencoded"
             :charset  :utf-8
             :data      "color=blue" }

  ;; a generic part
  ;; The charset of a generic part is only required for text based
  ;; data. When passing binary data the charset can be left out.
  "Part-4" { :filename "data.xml"
             :mimetype "application/xml"
             :charset  :utf-8
             :data      "<user><name>foo</name></user>" }}
```

Request Options:

:headers	A map of request headers. Headers can be single- or multi-value (comma separated): { "X-Header-1" "value1" "X-Header-2" "value1, value2, value3" }
:conn-timeout	An optional connection timeout in milliseconds
:read-timeout	An optional read timeout in milliseconds
:follow-redirects	Sets whether HTTP redirects (requests with response code 3xx) should be automatically followed.
:hostname-verifier	Sets the hostname verifier. An object of type <code>:javax.net.ssl.HostnameVerifier</code> . Use only for HTTPS requests
:ssl-socket-factory	Sets the SSL socket factory. An object of type <code>:javax.net.ssl.SSLSocketFactory</code> . Use only for HTTPS requests
:use-caches	A boolean indicating whether or not to allow caching. Defaults to false
:user-agent	User agent. Defaults to "Venice HTTP client (legacy)"
:debug	Debug true/false. Defaults to false. In debug mode prints the HTTP request (multipart data included) and the response data

Returns a map with the response fields:

:http-status	The HTTP status (a long)
:content-type-mimetype	The content type's mimetype. E.g.: "text/plain"
:content-type-charset	The content type's charset. E.g.: :utf-8

:content-encoding	The content transfer encoding (a keyword), if available else nil. E.g.: <code>:gzip</code> or <code>:deflate</code>
:content-length	The content length (a long), if available else -1
:headers	A map of headers. key: header name, value: list of header values
:data-stream	The response data input stream. See <code>http-client-j8/slurp-response</code> to painlessly process responses.

```
(do
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [response (hc/upload-multipart
    { "image1" (io/file "/Users/foo/image1.png")
      "image2" (io/file "/Users/foo/image2.png") }
    "http://localhost:8080/upload"
    :headers { "Accept" "text/plain" }
    :debug true)
    status (:http-status response)]
    (println "Status:" status)))
```

SEE ALSO

[http-client-j8/upload-file](#)

Upload a file.

[http-client-j8/upload-multipart](#)

Upload multiple parts.

top

identity

```
(identity x)
```

Returns its argument.

```
(identity 4)
=> 4
```

```
(filter identity [1 2 3 nil 4 false true 1234])
=> (1 2 3 4 true 1234)
```

top

if

```
(if test then else)
(if test then)
```

Evaluates test. If logical true, evaluates and returns then expression, otherwise else expression, if supplied, else nil.

```
(if (< 10 20) "yes" "no")
=> "yes"
```

```
(if true "yes")
=> "yes"
```

```
(if false "yes")  
=> nil
```

SEE ALSO

[if-let](#)

bindings is a vector with 2 elements: binding-form test.

[if-not](#)

Evaluates test. If logical false, evaluates and returns then expression, otherwise else expression, if supplied, else nil.

[when](#)

Evaluates test. If logical true, evaluates body in an implicit do.

[when-not](#)

Evaluates test. If logical false, evaluates body in an implicit do.

[when-let](#)

bindings is a vector with 2 elements: binding-form test.

top

if-let

```
(if-let bindings then)  
(if-let bindings then else)
```

bindings is a vector with 2 elements: binding-form test.
If test is true, evaluates then with binding-form bound to the value of test, if not, yields else

```
(if-let [value (* 100 2)]  
  (str "The expression is true. value=" value)  
  (str "The expression is false."))  
=> "The expression is true. value=200"
```

SEE ALSO

[when-let](#)

bindings is a vector with 2 elements: binding-form test.

[let](#)

Evaluates the expressions and binds the values to symbols in the new local context.

top

if-not

```
(if-not test then else)  
(if-not test then)
```

Evaluates test. If logical false, evaluates and returns then expression, otherwise else expression, if supplied, else nil.

```
(if-not (== 1 2) 100 0)  
=> 100
```

```
(if-not false 100)  
=> 100
```

```
(if-not true 100)
=> nil
```

SEE ALSO

[if](#)

Evaluates test. If logical true, evaluates and returns then expression, otherwise else expression, if supplied, else nil.

[if-let](#)

bindings is a vector with 2 elements: binding-form test.

[when](#)

Evaluates test. If logical true, evaluates body in an implicit do.

[when-not](#)

Evaluates test. If logical false, evaluates body in an implicit do.

[when-let](#)

bindings is a vector with 2 elements: binding-form test.

[top](#)

images/alpha-channel?

```
(alpha-channel? img)
```

Returns `true` if the image supports an alpha channel else `false`. 'img' is a `:java.awt.Image`.

```
(do
  (load-module :images)
  (->> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
    (images/alpha-channel?)))
```

[top](#)

images/anti-alias

```
(anti-alias g2d on)
```

Turns anti-alias on/off on the Graphics2D context

`(images/anti-alias on)` is a short form of:

```
(let [key (. :RenderingHints :KEY_ANTIALIASING)
      val (. :RenderingHints :VALUE_ANTIALIAS_ON)]
  (. g2d :setRenderingHint key val))

(let [key (. :RenderingHints :KEY_TEXT_ANTIALIASING)
      val (. :RenderingHints :VALUE_TEXT_ANTIALIAS_ON)]
  (. g2d :setRenderingHint key val))
```

See: [Rendering Quality](#)

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
```

```
(images/anti-alias g true) ;; enable anti-alias
(images/fg-color g images/blue)
(images/fill-round-rect g 80 60 100 50 12 12)

(images/anti-alias g false) ;; disable anti-alias
(images/fg-color g images/red)
(images/fill-round-rect g 220 60 100 50 12 12)

(images/dispose g)
(images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/dispose](#)

Disposes of this graphics context and releases any system resources that it is using.

[images/stroke](#)

Sets a new stroke on the graphics context

[images/fg-color](#)

Sets the foreground color on the graphics context.

[images/bg-color](#)

Sets the background color on the graphics context.

[images/set-clip](#)

Sets the current clip to the rectangle specified by the given coordinates.

[images/get-clip](#)

Returns the current clip shape.

[images/get-clip-bounds](#)

Returns the current clip bounds as a `:java.awt.Rectangle`.

[top](#)

images/apply-ops

```
(apply-ops img ops)
```

Applies one or multiple image operators (`:java.awt.image.BufferedImageOp`) to the image. Returns a new image.

Examples for image operators:

```
(import :java.awt.color.ColorSpace
        :java.awt.image.ColorConvertOp
        :java.awt.image.ConvolveOp
        :java.awt.image.Kernel
        :java.awt.image.RescaleOp)

(def convolve-op-antialias (. :ConvolveOp
                             :new
                             (. :Kernel :new 3 3
                                [ 0.00F, 0.08F, 0.00F,
                                  0.08F, 0.68F, 0.08F,
                                  0.00F, 0.08F, 0.00F ]))
                             (. :ConvolveOp :EDGE_NO_OP)
                             nil))
```

```

(def rescale-op-darker (. :RescaleOp :new 0.9F 0 nil))

(def rescale-op-brighter (. :RescaleOp :new 1.1F 0 nil))

(def color-convert-op-grayscale (as-> (. :ColorSpace :CS_GRAY) cs
                                       (. :ColorSpace :getInstance cs)
                                       (. :ColorConvertOp :new cs nil)))

;; make the image brighter
(do
  (load-module :images)
  (import :java.awt.image.RescaleOp)

  (let [op-brighter (. :RescaleOp :new 1.3F 0 nil)]
    (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
        (images/apply-ops [op-brighter])
        (images/save "jpg" (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg")))))

;; convert the image to grayscale
(do
  (load-module :images)
  (import :java.awt.color.ColorSpace)
  (import :java.awt.image.ColorConvertOp)

  (let [op-grayscale (as-> (. :ColorSpace :CS_GRAY) cs
                           (. :ColorSpace :getInstance cs)
                           (. :ColorConvertOp :new cs nil))]
    (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
        (images/apply-ops [op-grayscale])
        (images/save "jpg" (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg")))))

```

[top](#)

images/bg-color

```
(bg-color g2d color)
```

Sets the background color on the graphics context.

```

(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (images/bg-color g images/blue)
    (images/clear-rect g 150 80 100 50)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))

```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/dispose](#)

Disposes of this graphics context and releases any system resources that it is using.

[images/anti-alias](#)

Turns anti-alias on/off on the Graphics2D context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/fg-color](#)

Sets the foreground color on the graphics context.

[images/set-clip](#)

Sets the current clip to the rectangle specified by the given coordinates.

[images/get-clip](#)

Returns the current clip shape.

[images/get-clip-bounds](#)

Returns the current clip bounds as a :java.awt.Rectangle.

[top](#)

images/clear-rect

```
(clear-rect g2d x y width height)
```

Clears the specified rectangle by filling it with the current background color.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (images/bg-color g images/blue)
    (images/clear-rect g 150 80 100 50)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/bg-color](#)

Sets the background color on the graphics context.

[images/copy-area](#)

Copies an area of the component by a distance specified by dx and dy.

[top](#)

images/convert-to-rgb

```
(convert-to-rgb img)
```

Convert an image to RGB.

Returns a new image.

```
(do
  (load-module :images)
  (let [src (io/file "/Users/foo/Desktop/Pink-Forest.jpg")
        dst (io/file "/Users/foo/Desktop/Pink-Forest.png")]
    (-> (images/load src)
        (images/convert-to-rgba)
        (images/save "png" dst))))
```

SEE ALSO

[images/resize-fit](#)

Resizes an image to a new size, a square of width and height the image should fit within the size.

[top](#)

images/convert-to-rgba

```
(convert-to-rgba img)
```

Convert an image to RGBA.

Returns a new image.

```
(do
  (load-module :images)
  (let [src (io/file "/Users/foo/Desktop/Pink-Forest.jpg")
        dst (io/file "/Users/foo/Desktop/Pink-Forest.png")]
    (-> (images/load src)
        (images/convert-to-rgba)
        (images/save "png" dst))))
```

SEE ALSO

[images/resize-fit](#)

Resizes an image to a new size, a square of width and height the image should fit within the size.

[top](#)

images/copy

```
(copy img)
```

Creates a copy of `:java.awt.image.BufferedImage`.

```
(do
  (load-module :images)
  (-> (images/create 400 200 images/TYPE_INT_ARGB)
      (images/copy)
      (images/save :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/load](#)

Loads an image from a `:java.io.File`, a `:java.io.InputStream`, or a `:java.net.URL`.

[images/save](#)

Saves an image to `'java.io.File'` or an `'java.io.OutputStream'`.

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[top](#)

images/copy-area

`(copy-area g2d x y with height dx dy)`

Copies an area of the component by a distance specified by `dx` and `dy`.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/fill-circle g 100 100 100)
    (images/copy-area g 50 50 100 100 200 30)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png")))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/clear-rect](#)

Clears the specified rectangle by filling it with the current background color.

[top](#)

images/create

`(create width height type)`

`(create width height type color)`

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

Without color, creates a transparent image (type 'TYPE_INT_ARGB') or black image (type 'TYPE_INT_RGB').

```
(do
  (load-module :images)
  (-> (images/create 400 200 images/TYPE_INT_ARGB)
      (images/save :png (io/file "/Users/foo/Desktop/test.png")))))

(do
  (load-module :images)
  (-> (images/create 400 200 images/TYPE_INT_ARGB images/white)
      (images/save :png (io/file "/Users/foo/Desktop/test.png")))))
```


SEE ALSO

[images/load](#)

Loads an image from a `:java.io.File`, a `:java.io.InputStream`, or a `:java.net.URL`.

[images/save](#)

Saves an image to `:java.io.File` or an `:java.io.OutputStream`.

[images/copy](#)

Creates a copy of `:java.awt.image.BufferedImage`.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[top](#)

images/crop

`(crop img x y width height)`

Crops an image. Returns a new image.

```
(do
  (load-module :images)
  (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
    (images/crop 1000 1000 400 200)
    (images/save "jpg" (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg")))))
```

[top](#)

images/dimension

`(dimension f)`

Returns the images dimensions as a vector `[width height]`. 'f' may be a `:java.io.File` or a `:java.awt.Image`.

Note: Do not load a file first to get the dimension, passing a `:java.io.File` is much faster!

```
(do
  (load-module :images)
  (images/dimension (io/file "/Users/foo/Desktop/Pink-Forest.jpg")))
```

[top](#)

images/draw-circle

`(draw-circle g2d x y radius)`

Draws a circle.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
```

```
      g (images/g2d img)]
      (images/fg-color g images/blue)
      (images/draw-circle g 200 100 100)
      (images/dispose g)
      (images/save img :png (io/file "/Users/foo/Desktop/test.png")))))

;; create a mask
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g (images/g2d img)]
    (. g :setComposite (. :java.awt.AlphaComposite :Clear))
    (images/stroke g 10.0)
    (images/draw-circle g 200 100 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png")))))
```

SEE ALSO

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the Graphics2D context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/draw-oval](#)

Draws an oval.

[images/draw-rect](#)

Draws a rectangle.

[images/draw-round-rect](#)

Draws a rounded rectangle.

[images/draw-polygon](#)

Draws a polygon.

[images/draw-string](#)

Draws text with an optional size at the given position.

[images/draw-line](#)

Draws a line.

[images/draw-image](#)

Draws an image to the position x,y in the graphics context.

[top](#)

images/draw-image

```
(draw-image g2d x y)
(draw-image g2d x y width height)
```

Draws an image to the position x,y in the graphics context.

```
(do
  (load-module :images)

  (let [img1 (images/create 50 50 images/TYPE_INT_ARGB images/blue)
        img2 (images/create 50 50 images/TYPE_INT_ARGB images/magenta)
        img  (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g     (images/g2d img)]

    (images/draw-image g img1 100 30)
    (images/draw-image g img2 130 60)
    (images/draw-image g img1 160 90)

    (images/draw-image g img1 250 30 30 30)
    (images/draw-image g img2 280 60 30 30)
    (images/draw-image g img1 310 90 30 30)

    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/draw-circle](#)

Draws a circle.

[images/draw-oval](#)

Draws an oval.

[images/draw-rect](#)

Draws a rectangle.

[images/draw-round-rect](#)

Draws a rounded rectangle.

[images/draw-polygon](#)

Draws a polygon.

[images/draw-string](#)

Draws text with an optional size at the given position.

[images/draw-line](#)

Draws a line.

[top](#)

images/draw-line

```
(draw-line g2d x1 y1 x2 y2)
```

Draws a line.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
```

```
g (images/g2d img)]
(images/anti-alias g true) ;; enable anti-alias
(images/stroke g 10.0 images/cap-round images/join-miter)
(images/fg-color g images/blue)
(images/draw-line g 50 50 350 150)
(images/dispose g)
(images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/draw-circle](#)

Draws a circle.

[images/draw-oval](#)

Draws an oval.

[images/draw-rect](#)

Draws a rectangle.

[images/draw-round-rect](#)

Draws a rounded rectangle.

[images/draw-polygon](#)

Draws a polygon.

[images/draw-string](#)

Draws text with an optional size at the given position.

[images/draw-image](#)

Draws an image to the position x,y in the graphics context.

[top](#)

images/draw-oval

```
(draw-oval g2d center-x center-y width height)
```

Draws an oval.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g (images/g2d img)]
    (images/stroke g 10.0)
    (images/fg-color g images/blue)
    (images/draw-oval g 200 100 200 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/draw-circle](#)

Draws a circle.

[images/draw-rect](#)

Draws a rectangle.

[images/draw-round-rect](#)

Draws a rounded rectangle.

[images/draw-polygon](#)

Draws a polygon.

[images/draw-string](#)

Draws text with an optional size at the given position.

[images/draw-line](#)

Draws a line.

[images/draw-image](#)

Draws an image to the position `x,y` in the graphics context.

[top](#)

images/draw-polygon

`(draw-polygon g2d polygon)`

Draws a polygon.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
    (images/stroke g 5.0 images/cap-round images/join-miter)

    ;; hexagon
    (->> (images/hexagon-poly)
          (images/scale-points 80)
          (images/translate-points 200 100)
          (images/polygon)
          (images/draw-polygon g))

    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))

(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
```

```

      g (images/g2d img)]
(images/fg-color g images/blue)
(images/anti-alias g true) ;; enable anti-alias

;; draw an arc of hexagons
(let [anchor-x 200, anchor-y 170]
  (doseq [angle (range 0 190 10)]
    (->> (images/hexagon-poly)
      (images/scale-points 20)
      (images/rotate-points 90)
      (images/translate-points 50 170)
      (images/rotate-points angle anchor-x anchor-y)
      (images/polygon)
      (images/draw-polygon g))))

(images/dispose g)
(images/save img :png (io/file "/Users/foo/Desktop/test.png"))))

```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/draw-circle](#)

Draws a circle.

[images/draw-oval](#)

Draws an oval.

[images/draw-rect](#)

Draws a rectangle.

[images/draw-round-rect](#)

Draws a rounded rectangle.

[images/draw-string](#)

Draws text with an optional size at the given position.

[images/draw-line](#)

Draws a line.

[images/draw-image](#)

Draws an image to the position `x,y` in the graphics context.

[top](#)

images/draw-rect

```

(draw-rect g2d x y width height)
(draw-rect g2d x y width height color)

```

Draws a rectangle.

```

(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)

```

```
g (images/g2d img)]
(images/stroke g 10.0)
(images/fg-color g images/blue)
(images/draw-rect g 150 70 100 50)
(images/dispose g)
(images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/draw-circle](#)

Draws a circle.

[images/draw-oval](#)

Draws an oval.

[images/draw-round-rect](#)

Draws a rounded rectangle.

[images/draw-polygon](#)

Draws a polygon.

[images/draw-string](#)

Draws text with an optional size at the given position.

[images/draw-line](#)

Draws a line.

[images/draw-image](#)

Draws an image to the position `x,y` in the graphics context.

[top](#)

images/draw-round-rect

`(draw-round-rect g2d x y width height arc-width arc-height)`

Draws a rounded rectangle.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g (images/g2d img)]

    (images/stroke g 10.0)

    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
    (images/draw-round-rect g 80 60 100 50 12 12)

    (images/fg-color g images/red)
    (images/anti-alias g false) ;; disable anti-alias
```

```
(images/draw-round-rect g 220 60 100 50 12 12)

(images/dispose g)
(images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the Graphics2D context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/draw-circle](#)

Draws a circle.

[images/draw-oval](#)

Draws an oval.

[images/draw-rect](#)

Draws a rectangle.

[images/draw-polygon](#)

Draws a polygon.

[images/draw-string](#)

Draws text with an optional size at the given position.

[images/draw-line](#)

Draws a line.

[images/draw-image](#)

Draws an image to the position x,y in the graphics context.

[top](#)

images/draw-string

```
(draw-string g2d text x y)
(draw-string g2d text x y size)
```

Draws text with an optional size at the given position.

```
(do
  (load-module :images)
  (import :java.awt.Font)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g (images/g2d img)]
    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
    (images/draw-string g "Hello, world!" 50 120 50)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/draw-circle](#)

Draws a circle.

[images/draw-oval](#)

Draws an oval.

[images/draw-rect](#)

Draws a rectangle.

[images/draw-round-rect](#)

Draws a rounded rectangle.

[images/draw-polygon](#)

Draws a polygon.

[images/draw-line](#)

Draws a line.

[images/draw-image](#)

Draws an image to the position `x,y` in the graphics context.

[top](#)

images/fg-color

```
(fg-color g2d color)
```

Sets the foreground color on the graphics context.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/fill-oval g 200 100 200 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/dispose](#)

Disposes of this graphics context and releases any system resources that it is using.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/fg-color](#)

Sets the foreground color on the graphics context.

[images/set-clip](#)

Sets the current clip to the rectangle specified by the given coordinates.

[images/get-clip](#)

Returns the current clip shape.

[images/get-clip-bounds](#)

Returns the current clip bounds as a `:java.awt.Rectangle`.

[top](#)

images/fill-circle

`(fill-circle g2d x y radius)`

Draws a filled circle.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/fill-circle g 200 100 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))

;; create a mask (fill circle with transparent pixels)
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (. g :setComposite (. :java.awt.AlphaComposite :Clear))
    (images/fill-circle g 200 100 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/fill-oval](#)

Draws a filled oval.

[images/fill-rect](#)

Draws a filled rectangle.

[images/fill-round-rect](#)

Draws a filled rounded rectangle.

[images/fill-polygon](#)

Draws a filled polygon.

[top](#)

images/fill-oval

```
(fill-oval g2d center-x center-y width height)
```

Draws a filled oval.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/fill-oval g 200 100 200 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the Graphics2D context

[images/fill-circle](#)

Draws a filled circle.

[images/fill-rect](#)

Draws a filled rectangle.

[images/fill-round-rect](#)

Draws a filled rounded rectangle.

[images/fill-polygon](#)

Draws a filled polygon.

[top](#)

images/fill-polygon

```
(fill-polygon g2d polygon)
```

Draws a filled polygon.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
```

```
;; hexagon
(->> (images/hexagon-poly)
      (images/scale-points 80)
      (images/translate-points 200 100)
      (images/polygon)
      (images/fill-polygon g))

(images/dispose g)
(images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/fill-circle](#)

Draws a filled circle.

[images/fill-oval](#)

Draws a filled oval.

[images/fill-rect](#)

Draws a filled rectangle.

[images/fill-round-rect](#)

Draws a filled rounded rectangle.

[top](#)

images/fill-rect

```
(fill-rect g2d x y width height)
```

Draws a filled rectangle.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/fill-rect g 150 80 100 50)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/fill-circle](#)

Draws a filled circle.

[images/fill-oval](#)

Draws a filled oval.

[images/fill-round-rect](#)

Draws a filled rounded rectangle.

[images/fill-polygon](#)

Draws a filled polygon.

[top](#)

images/fill-round-rect

(fill-round-rect g2d x y width height arc-width arc-height)

Draws a filled rounded rectangle.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
    (images/fill-round-rect g 80 60 100 50 12 12)

    (images/fg-color g images/red)
    (images/anti-alias g false) ;; disable anti-alias
    (images/fill-round-rect g 220 60 100 50 12 12)

    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/anti-alias](#)

Turns anti-alias on/off on the Graphics2D context

[images/fill-circle](#)

Draws a filled circle.

[images/fill-oval](#)

Draws a filled oval.

[images/fill-rect](#)

Draws a filled rectangle.

[images/fill-polygon](#)

Draws a filled polygon.

[top](#)

images/flip

```
(flip img mode)
```

Flips an image vertically or horizontally. Returns a new image.

Mode is either :vertical or :horizontal.

```
(do
  (load-module :images)
  (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
    (images/flip :vertical)
    (images/save "jpg" (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg"))))
```

[top](#)

images/format-names

```
(format-names)
```

Returns a list of format that the image writer supports.

```
(do
  (load-module :images)
  (images/format-names))
=> ["JPG" "jpg" "bmp" "BMP" "gif" "GIF" "WBMP" "png" "PNG" "jpeg" "wbmp" "JPEG"]
```

[top](#)

images/g2d

```
(g2d img)
```

Creates a Graphics2D context from an image.

See: [Rendering Quality](#)

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g   (images/g2d img)]
    (images/stroke g 10.0)
    (images/fg-color g images/blue)
    (images/fill-oval g 200 100 200 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/dispose](#)

Disposes of this graphics context and releases any system resources that it is using.

[images/anti-alias](#)

Turns anti-alias on/off on the Graphics2D context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/fg-color](#)

Sets the foreground color on the graphics context.

[images/bg-color](#)

Sets the background color on the graphics context.

[images/set-clip](#)

Sets the current clip to the rectangle specified by the given coordinates.

[images/get-clip](#)

Returns the current clip shape.

[images/get-clip-bounds](#)

Returns the current clip bounds as a :java.awt.Rectangle.

[top](#)

images/get-clip

```
(get-clip g2d)
```

Returns the current clip shape.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)
        old (images/get-clip g)]
    (images/anti-alias g true) ;; enable anti-alias
    (images/fg-color g images/blue)
    (images/set-clip g 0 0 200 200) ;; left half of the img
    (images/fill-oval g 200 100 300 150)
    (images/set-clip g old) ;; restore previous clipping
    (images/stroke g 10.0 images/cap-round images/join-miter)
    (images/fg-color g images/red)
    (images/draw-line g 50 50 350 150)

    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png")))))
```

SEE ALSO

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/dispose](#)

Disposes of this graphics context and releases any system resources that it is using.

[images/anti-alias](#)

Turns anti-alias on/off on the Graphics2D context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/fg-color](#)

Sets the foreground color on the graphics context.

[images/bg-color](#)

Sets the background color on the graphics context.

[images/set-clip](#)

Sets the current clip to the rectangle specified by the given coordinates.

[images/get-clip-bounds](#)

Returns the current clip bounds as a :java.awt.Rectangle.

[top](#)

images/get-clip-bounds

```
(get-clip-bounds g2d)
```

Returns the current clip bounds as a :java.awt.Rectangle.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (images/get-clip-bounds g)))
```

SEE ALSO

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/dispose](#)

Disposes of this graphics context and releases any system resources that it is using.

[images/anti-alias](#)

Turns anti-alias on/off on the Graphics2D context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/fg-color](#)

Sets the foreground color on the graphics context.

[images/bg-color](#)

Sets the background color on the graphics context.

[images/set-clip](#)

Sets the current clip to the rectangle specified by the given coordinates.

[images/get-clip](#)

Returns the current clip shape.

[top](#)

images/get-transform

```
(get-transform g2d)
```


Returns a copy of the current Transform in the Graphics2D context.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/fill-oval g 200 100 200 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/set-transform](#)

Overwrites the Transform in the Graphics2D context. 'tx' may be nil.

[images/tx-identity](#)

Create identity transformer.

[images/tx-translate](#)

Create a translate transformer.

[images/tx-scale](#)

Create a scale transformer.

[images/tx-rotate](#)

Create a rotate transformer.

[images/tx-shear](#)

Create a shear transformer.

[top](#)

images/hexagon-poly

(hexagon-poly)

Creates a normalized (center at (0,0), radius 1) hexagon polygon point list.

```
(do
  (load-module :images)
  (images/hexagon-poly))
```

[top](#)

images/load

(load file)

Loads an image from a `java.io.File`, a `java.io.InputStream`, or a `java.net.URL`.

```
(do
  (load-module :images)
  (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))))
```

SEE ALSO

[images/save](#)

Saves an image to 'java.io.File' or an 'java.io.OutputStream'.

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/copy](#)

Creates a copy of :java.awt.image.BufferedImage.

[images/g2d](#)

Creates a Graphics2D context from an image.

[top](#)

images/pad

```
(pad img padding color)
(pad img pad-top pad-right pad-bottom pad-left color)
```

Pads an image. Returns a new image.

```
(do
  (load-module :images)
  (import :java.awt.Color)
  (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
    (images/pad 200 images/white)
    (images/save "jpg" (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg"))))
```

[top](#)

images/point

```
(point x y)
```

Creates a :java.awt.Point

```
(do
  (load-module :images)
  (images/point 0 0))
```

[top](#)

images/polygon

```
(polygon points)
```

Creates a :java.awt.Polygon

```
(do
  (load-module :images)
  (images/polygon [[0 0] [0 100] [100 100] [100 0] [0 0]]))
```

[top](#)

images/rectangle

(rectangle x y width height)

Creates a `:java.awt.Rectangle`

```
(do
  (load-module :images)
  (images/rectangle 0 0 200 100))
```

[top](#)

images/rectangle-poly

(rectangle-poly x y width height)

Creates a rectangle polygon point list.

```
(do
  (load-module :images)
  (images/rectangle-poly 0 0 200 100))
```

[top](#)

images/resize

(resize img width height)
(resize img width height resize-mode)

Resizes an image to a new width and height.

Resize modes:

<code>:resize-auto</code>	(default) chooses best mode
<code>:resize-performance</code>	resize for best performance
<code>:resize-balanced</code>	balance between performance and quality
<code>:resize-quality</code>	resize for quality
<code>:resize-high-quality</code>	resize for high quality

Returns a new image.

```
(do
  (load-module :images)
  (let [src (io/file "/Users/foo/Desktop/Pink-Forest.jpg")
        dst (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg")]
    (-> (images/load src)
      (images/resize 500 200 :resize-balanced)))
```

```
(images/save "jpg" dst))
```

```
(println (io/file-name src) ":" (images/dimension src))  
(println (io/file-name dst) ":" (images/dimension dst)))
```

SEE ALSO

[images/resize-fit](#)

Resizes an image to a new size, a square of width and height the image should fit within the size.

[top](#)

images/resize-fit

```
(resize-fit img size fit-mode)  
(resize img size fit-mode resize-mode)
```

Resizes an image to a new size, a square of width and height the image should fit within the size.

Resize modes:

<code>:fit-best</code>	(default), fit within a square box of size 'size', keeps width / height ratio
<code>:fit-exact</code>	fit exactly to a square of size 'size', causes distortions
<code>:fit-width</code>	fit to width, keeps width / height ratio
<code>:fit-height</code>	fit to height, keeps width / height ratio

Resize modes:

<code>:resize-auto</code>	(default) chooses best mode
<code>:resize-performance</code>	resize for best performance
<code>:resize-balanced</code>	balance between performance and quality
<code>:resize-quality</code>	resize for quality
<code>:resize-high-quality</code>	resize for high quality

Returns a new image.

```
(do  
  (load-module :images)  
  (let [src (io/file "/Users/foo/Desktop/Pink-Forest.jpg")  
        dst (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg")]  
    (-> (images/load src)  
        (images/resize-fit 500 :fit-best :resize-balanced)  
        (images/save "jpg" dst))  
  
    (println (io/file-name src) ":" (images/dimension src))  
    (println (io/file-name dst) ":" (images/dimension dst))))
```

SEE ALSO

[images/resize](#)

Resizes an image to a new width and height.

[top](#)

images/rotate

```
(rotate img angle)
```

Rotates an image by 0°, 90°, 180°, or 270° clockwise. Returns a new image.

```
(do
  (load-module :images)
  (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
    (images/rotate 90)
    (images/save "jpg" (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg")))))
```

[top](#)

images/rotate-points

```
(rotate-points angle points)
(rotate-points angle anchor-x anchor-y points)
```

Rotate the points of a polygon point list with an angle in degrees [0..360] around an anchor point. The default anchor point is (0,0)

```
(do
  (load-module :images)
  (-> (images/rectangle-poly 0 0 200 100)
    (images/rotate-points 45 (square-poly 100 100 100 100))))
```

[top](#)

images/save

```
(save img format-name f)
```

Saves an image to 'java.io.File' or an 'java.io.OutputStream'.

Supported formats: "png", "jpg", "jpeg", "gif", "bmp", ...

```
(do
  (load-module :images)
  (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
    (images/save img :png (io/file "/Users/foo/Desktop/Pink-Forest.png")))))
```

SEE ALSO

[images/load](#)

Loads an image from a :java.io.File, a :java.io.InputStream, or a :java.net.URL.

[images/create](#)

Creates a new :java.awt.image.BufferedImage with the given width, height, and type.

[images/copy](#)

Creates a copy of :java.awt.image.BufferedImage.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/format-names](#)

Returns a list of format that the image writer supports.

[top](#)

images/scale-points

```
(scale-points factor points)
(scale-points factor-x factor-y points)
```

Scales the points of a polygon point list with factor.

```
(do
  (load-module :images)
  (->> (images/rectangle-poly 0 0 200 100)
        (images/scale-points 4.0 100 50)))
```

[top](#)

images/set-clip

```
(set-clip g2d shape)
(set-clip g2d x y width height)
```

Sets the current clip to the rectangle specified by the given coordinates.

A shape can be `nil` to remove any clipping.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/set-clip g 0 0 200 200) ;; left half of the img
    (images/fill-oval g 200 100 300 150)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/dispose](#)

Disposes of this graphics context and releases any system resources that it is using.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/stroke](#)

Sets a new stroke on the graphics context

[images/fg-color](#)

Sets the foreground color on the graphics context.

[images/bg-color](#)

Sets the background color on the graphics context.

[images/get-clip](#)

Returns the current clip shape.

[images/get-clip-bounds](#)

Returns the current clip bounds as a `:java.awt.Rectangle`.

[top](#)

images/set-transform

```
(set-transform g2d tx)
```

Overwrites the Transform in the Graphics2D context. 'tx' may be `nil`.

Note: This function should **never** be used to apply a new coordinate transform on top of an existing transform. It should only be used to restore the original transform of the graphics.

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g   (images/g2d img)]
    (images/fg-color g images/blue)
    (images/fill-oval g 200 100 200 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/get-transform](#)

Returns a copy of the current Transform in the Graphics2D context.

[images/tx-identity](#)

Create identity transformer.

[images/tx-translate](#)

Create a translate transformer.

[images/tx-scale](#)

Create a scale transformer.

[images/tx-rotate](#)

Create a rotate transformer.

[images/tx-shear](#)

Create a shear transformer.

[top](#)

images/shear

```
(shear img shx shy)
(shear img shx shy color)
```

Shears an image vertically and/or horizontally. Returns a new image.

```
(do
  (load-module :images)
  (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
    (images/shear 0.05 0.0)
    (images/save "jpg" (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg")))))
```

top

images/square-poly

```
(square-poly x y length)
```

Creates a square polygon point list.

```
(do
  (load-module :images)
  (images/square-poly 0 0 100))
```

top

images/stroke

```
(stroke g2d)
(stroke g2d width)
(stroke g2d width cap join)
(stroke g2d width cap join meter-limit)
(stroke g2d width cap join meter-limit dash dash-phase)
```

Sets a new stroke on the graphics context

See: [BasicStroke](#)

```
(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g (images/g2d img)]
    (images/fg-color g images/blue)
    (images/stroke g 10.0 images/cap-round images/join-miter)
    (images/draw-oval g 100 50 200 100)
    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))

(do
  (load-module :images)

  (let [img (images/create 400 200 images/TYPE_INT_ARGB)
        g (images/g2d img)]
    (images/fg-color g images/blue)
    (images/stroke g
      10.0
      images/cap-round
      images/join-miter
      5.0
      [20.0]
      20.0)
    (images/draw-oval g 200 100 200 100))
```



```
(images/dispose g)
(images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/dispose](#)

Disposes of this graphics context and releases any system resources that it is using.

[images/anti-alias](#)

Turns anti-alias on/off on the `Graphics2D` context

[images/fg-color](#)

Sets the foreground color on the graphics context.

[images/bg-color](#)

Sets the background color on the graphics context.

[images/set-clip](#)

Sets the current clip to the rectangle specified by the given coordinates.

[images/get-clip](#)

Returns the current clip shape.

[images/get-clip-bounds](#)

Returns the current clip bounds as a `java.awt.Rectangle`.

[top](#)

images/transform

[top](#)

images/translate

```
(translate img x y)
(translate img x y color)
```

Translates from (0, 0) to the current (x, y) position. Returns a new image.

```
(do
  (load-module :images)
  (-> (images/load (io/file "/Users/foo/Desktop/Pink-Forest.jpg"))
    (images/translate 200 100)
    (images/save "jpg" (io/file "/Users/foo/Desktop/Pink-Forest-1.jpg"))))
```

[top](#)

images/translate-points

```
(translate-points dx dy points)
```

Translate the points of a polygon point list.

```
(do
  (load-module :images)
  (->> (images/rectangle-poly 0 0 200 100)
    (images/translate-points 4.0)))
```

[top](#)

images/tx-identity

```
(tx-identity )
```

Create identity transformer.

Note: The last specified transform on the graphics context is applied first!

```
(do
  (load-module :images)

  (let [img      (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g        (images/g2d img)
        square [[30 30] [50 30] [50 50] [30 50]]]
    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
    (images/stroke g 5.0 images/cap-round images/join-miter)
    (images/transform g (images/tx-identity))
    (images/draw-polygon g (images/polygon square))

    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/set-transform](#)

Overwrites the Transform in the `Graphics2D` context. 'tx' may be nil.

[images/get-transform](#)

Returns a copy of the current Transform in the `Graphics2D` context.

[images/tx-scale](#)

Create a scale transformer.

[images/tx-rotate](#)

Create a rotate transformer.

[images/tx-shear](#)

Create a shear transformer.

[top](#)

images/tx-rotate

```
(tx-rotate angle)
(tx-rotate angle anchor-x anchor-y)
```

Create a rotate transformer.

Note: The last specified transform on the graphics context is applied first!

```
(do
  (load-module :images)

  (let [img      (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g        (images/g2d img)
        square [[-1 -1] [1 -1] [1 1] [-1 1]]]
    (images/fg-color g images/blue)
    (images/anti-alias g true)    ;; enable anti-alias
    (images/stroke g 5.0 images/cap-round images/join-miter)
    (images/transform g (images/tx-translate 200 100))
    (images/transform g (images/tx-rotate 45))
    (images/transform g (images/tx-scale 15))
    (images/draw-polygon g (images/polygon square))

    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/set-transform](#)

Overwrites the Transform in the `Graphics2D` context. 'tx' may be nil.

[images/get-transform](#)

Returns a copy of the current Transform in the `Graphics2D` context.

[images/tx-identity](#)

Create identity transformer.

[images/tx-translate](#)

Create a translate transformer.

[images/tx-scale](#)

Create a scale transformer.

[images/tx-shear](#)

Create a shear transformer.

[top](#)

images/tx-scale

```
(tx-scale s)
(tx-scale sx sy)
```

Create a scale transformer.

Take care for strokes when scaling up/down. A stroke width will be scaled as well!

Note: The last specified transform on the graphics context is applied first!

```
(do
  (load-module :images)

  (let [img      (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g        (images/g2d img)
        square [[-1 -1] [1 -1] [1 1] [-1 1]]]
    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
    (images/stroke g 5.0 images/cap-round images/join-miter)
    (images/transform g (images/tx-translate 200 100))
    (images/transform g (images/tx-scale 15))
    (images/draw-polygon g (images/polygon square))

    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/set-transform](#)

Overwrites the `Transform` in the `Graphics2D` context. 'tx' may be nil.

[images/get-transform](#)

Returns a copy of the current `Transform` in the `Graphics2D` context.

[images/tx-identity](#)

Create identity transformer.

[images/tx-translate](#)

Create a translate transformer.

[images/tx-rotate](#)

Create a rotate transformer.

[images/tx-shear](#)

Create a shear transformer.

[top](#)

images/tx-shear

```
(tx-shear sx sy)
```

Create a shear transformer.

Note: The last specified transform on the graphics context is applied first!

```
(do
  (load-module :images)

  (let [img      (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g        (images/g2d img)
        square [[-1 -1] [1 -1] [1 1] [-1 1]]]
    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
    (images/stroke g 5.0 images/cap-round images/join-miter)
    (images/transform g (images/tx-translate 200 100))
    (images/transform g (images/tx-shear -0.3 0.0)))
```

```
(images/transform g (images/tx-scale 15))
(images/draw-polygon g (images/polygon square))

(images/dispose g)
(images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a `Graphics2D` context from an image.

[images/set-transform](#)

Overwrites the Transform in the `Graphics2D` context. 'tx' may be nil.

[images/get-transform](#)

Returns a copy of the current Transform in the `Graphics2D` context.

[images/tx-identity](#)

Create identity transformer.

[images/tx-translate](#)

Create a translate transformer.

[images/tx-scale](#)

Create a scale transformer.

[images/tx-rotate](#)

Create a rotate transformer.

[top](#)

images/tx-translate

```
(tx-translate x y)
```

Create a translate transformer.

Note: The last specified transform on the graphics context is applied first!

```
(do
  (load-module :images)

  (let [img      (images/create 400 200 images/TYPE_INT_ARGB images/white)
        g        (images/g2d img)
        square [[-1 -1] [1 -1] [1 1] [-1 1]]]
    (images/fg-color g images/blue)
    (images/anti-alias g true) ;; enable anti-alias
    (images/stroke g 5.0 images/cap-round images/join-miter)
    (images/transform g (images/tx-translate 200 100))
    (images/transform g (images/tx-scale 15))
    (images/draw-polygon g (images/polygon square))

    (images/dispose g)
    (images/save img :png (io/file "/Users/foo/Desktop/test.png"))))
```

SEE ALSO

[images/create](#)

Creates a new `:java.awt.image.BufferedImage` with the given width, height, and type.

[images/g2d](#)

Creates a Graphics2D context from an image.

[images/set-transform](#)

Overwrites the Transform in the Graphics2D context. 'tx' may be nil.

[images/get-transform](#)

Returns a copy of the current Transform in the Graphics2D context.

[images/tx-identity](#)

Create identity transformer.

[images/tx-scale](#)

Create a scale transformer.

[images/tx-rotate](#)

Create a rotate transformer.

[images/tx-shear](#)

Create a shear transformer.

[top](#)

import

```
(import class & classes)
(import class :as alias)
```

Imports one or multiple Java classes. Imports are bound to the current namespace.

Example

Without import

```
(. :java.lang.Math :max 2 10)
```

With import

```
(do
  (import :java.lang.Math)
  (. :Math :max 2 10))
```

Aliases

Aliases are helpful if Java classes have the same name but different packages like `java.util.Date` and `java.sql.Date`:

```
(do
  (import :java.util.Date)
  (import :java.sql.Date :as :SqlDate)

  (println (. :Date :new))
  (println (. :SqlDate :valueOf "2022-06-24")))
```

Static nested classes

Venice

```
(do
  (import :foo.OuterClass)
  (import :foo.OuterClass$NestedStaticClass)

  (-> (. :OuterClass :new)
    (. :message))
  (-> (. :OuterClass$NestedStaticClass :new)
    (. :message)))
```

Java

```

package foo;

public class OuterClass {
    public String message() {
        return "OuterClass::message()";
    }

    public static class NestedStaticClass {
        public String message() {
            return "NestedStaticClass::message()";
        }
    }
}

```

```

(do
  (import :java.lang.Math)
  (. :Math :max 2 10))
=> 10

```

```

(do
  (import :java.awt.Point
          :java.lang.Math)
  (. :Math :max 2 10))
=> 10

```

```

(do
  (import :java.awt.Color :as :AwtColor)
  (. :AwtColor :new 200I 230I 255I 180I))
=> java.awt.Color[r=200,g=230,b=255]

```

```

(do
  (ns util)
  (defn import? [clazz ns_]
    (any? #(<= % clazz) (map first (imports ns_)))))

  (ns alpha)
  (import :java.lang.Math)
  (println "alpha:" (util/import? :java.lang.Math 'alpha))

  (ns beta)
  (println "beta:" (util/import? :java.lang.Math 'beta))

  (ns alpha)
  (println "alpha:" (util/import? :java.lang.Math 'alpha))
)
alpha: true
beta: false
alpha: true
=> nil

```

SEE ALSO

[imports](#)

Without namespace arg returns a list with the registered imports for the current namespace. With namespace arg returns a list with ...

[top](#)

imports

```

(imports & options)
(imports ns & options)

```

Without namespace arg returns a list with the registered imports for the current namespace. With namespace arg returns a list with the registered imports for the given namespace.

Options:

:print print the import list to the current value of `*out*`

```
(do
  (import :java.lang.Math)
  (imports))
=> ([:com.github.jlangch.venice.AssertionException :AssertionException] [:com.github.jlangch.venice.
SecurityException :SecurityException] [:com.github.jlangch.venice.ValueException :ValueException] [:com.github.
jlangch.venice.VncException :VncException] [:java.lang.Exception :Exception] [:java.lang.
IllegalArgumentException :IllegalArgumentException] [:java.lang.Math :Math] [:java.lang.NullPointerException :
NullPointerException] [:java.lang.RuntimeException :RuntimeException] [:java.lang.Throwable :Throwable])

(do
  (import :java.lang.Math)
  (imports :print))
:com.github.jlangch.venice.AssertionException :as :AssertionException
:com.github.jlangch.venice.SecurityException :as :SecurityException
:com.github.jlangch.venice.ValueException :as :ValueException
:com.github.jlangch.venice.VncException :as :VncException
:java.lang.Exception :as :Exception
:java.lang.IllegalArgumentException :as :IllegalArgumentException
:java.lang.Math :as :Math
:java.lang.NullPointerException :as :NullPointerException
:java.lang.RuntimeException :as :RuntimeException
:java.lang.Throwable :as :Throwable
=> nil

(do
  (ns foo)
  (import :java.lang.Math)
  (ns bar)
  (imports 'foo))
=> ([:com.github.jlangch.venice.AssertionException :AssertionException] [:com.github.jlangch.venice.
SecurityException :SecurityException] [:com.github.jlangch.venice.ValueException :ValueException] [:com.github.
jlangch.venice.VncException :VncException] [:java.lang.Exception :Exception] [:java.lang.
IllegalArgumentException :IllegalArgumentException] [:java.lang.Math :Math] [:java.lang.NullPointerException :
NullPointerException] [:java.lang.RuntimeException :RuntimeException] [:java.lang.Throwable :Throwable])
```

SEE ALSO

[import](#)

Imports one or multiple Java classes. Imports are bound to the current namespace.

[top](#)

inc

```
(inc x)
```

Increments the number x

```
(inc 10)
=> 11
```



```
(inc 10I)
=> 11I

(inc 10.1)
=> 11.1

(inc 10.12M)
=> 11.12M
```

SEE ALSO

[dec](#)
Decrements the number x

[top](#)

inet/inet-addr

```
(inet/inet-addr addr)
```

Converts a stringified IPv4 or IPv6 to a Java InetAddress.

```
(inet/inet-addr "222.192.0.0")
=> /222.192.0.0

(inet/inet-addr "2001:0db8:85a3:08d3:1319:8a2e:0370:7347")
=> /2001:db8:85a3:8d3:1319:8a2e:370:7347
```

[top](#)

inet/inet-addr-from-bytes

```
(inet/inet-addr-bytes addr)
```

Converts a IPv4 or IPv6 byte address (a vector of unsigned integers) to a Java InetAddress.

```
(inet/inet-addr-from-bytes [222I 192I 12I 0I])
=> /222.192.12.0

(inet/inet-addr-from-bytes [32I 1I 13I 184I 133I 163I 8I 211I 19I 25I 138I 46I 3I 112I 115I 71I])
=> /2001:db8:85a3:8d3:1319:8a2e:370:7347
```

[top](#)

inet/inet-addr-to-bytes

```
(inet/inet-addr-to-bytes addr)
```

Converts a stringified IPv4/IPv6 address or a Java InetAddress to an InetAddress byte vector.

```
(inet/inet-addr-to-bytes "222.192.12.0")
=> [222I 192I 12I 0I]
```

```
(inet/inet-addr-to-bytes "2001:0db8:85a3:08d3:1319:8a2e:0370:7347")
=> [32I 1I 13I 184I 133I 163I 8I 211I 19I 25I 138I 46I 3I 112I 115I 71I]

(inet/inet-addr-to-bytes (inet/inet-addr "222.192.0.0"))
=> [222I 192I 0I 0I]
```

[top](#)

inet/ip4?

```
(inet/ip4? addr)
```

Returns true if addr is an IPv4 address.

```
(inet/ip4? "222.192.0.0")
=> true

(inet/ip4? (inet/inet-addr "222.192.0.0"))
=> true
```

[top](#)

inet/ip6?

```
(inet/ip6? addr)
```

Returns true if addr is an IPv6 address.

```
(inet/ip6? "2001:0db8:85a3:08d3:1319:8a2e:0370:7347")
=> true

(inet/ip6? (inet/inet-addr "2001:0db8:85a3:08d3:1319:8a2e:0370:7347"))
=> true
```

[top](#)

inet/linklocal-addr?

```
(inet/linklocal-addr? addr)
```

Returns true if addr is a link local address.

```
(inet/linklocal-addr? "169.254.0.0")
=> true

(inet/linklocal-addr? (inet/inet-addr "169.254.0.0"))
=> true
```

[top](#)

inet/multicast-addr?

```
(inet/multicast-addr? addr)
```

Returns true if addr is a multicast address.

```
(inet/multicast-addr? "224.0.0.1")  
=> true
```

```
(inet/multicast-addr? (inet/inet-addr "224.0.0.1"))  
=> true
```

[top](#)

inet/reachable?

```
(inet/reachable? addr timeout)
```

Test whether that address is reachable. Best effort is made by the implementation to try to reach the host, but firewalls and server configuration may block requests resulting in an unreachable status while some specific ports may be accessible. A typical implementation will use ICMP ECHO REQUESTs if the privilege can be obtained, otherwise it will try to establish a TCP connection on port 7 (Echo) of the destination host.

The timeout value, in milliseconds, indicates the maximum amount of time the try should take. If the operation times out before getting an answer, the host is deemed unreachable.

```
(inet/reachable? "google.com" 500)  
=> false
```

```
(inet/reachable? "74.125.193.113" 500)  
=> false
```

[top](#)

inet/sitelocal-addr?

```
(inet/sitelocal-addr? addr)
```

Returns true if addr is a site local address.

```
(inet/sitelocal-addr? "192.168.0.0")  
=> true
```

```
(inet/sitelocal-addr? (inet/inet-addr "192.168.0.0"))  
=> true
```

[top](#)

infinite?

```
(infinite? x)
```

Returns true if x is infinite else false. x must be a double!

```
(infinite? 1.0E300)
=> false
```

```
(infinite? (* 1.0E300 1.0E100))
=> true
```

```
(infinite? (/ 1.0 0))
=> true
```

```
(pr (/ 4.1 0))
:Infinite
=> nil
```

SEE ALSO

[nan?](#)

Returns true if x is a NaN else false. x must be a double!

[double](#)

Converts to double

[top](#)

installer/clean

```
(clean dir)
```

Remove Java libraries (except any Jansi library) and TTF font files from the specified directory.

The removal does NOT recursively traverse the directory tree.

```
(do
  (load-module :installer)
  (installer/clean (repl/libs-dir)))
```

SEE ALSO

[installer/install-libs](#)

Install Java libraries (artifacts). Does not install the library's dependencies!

[top](#)

installer/install

```
(install artifacts options*)
```

Install Java artifacts and its dependencies.

Options:

:dir path	download dir, defaults to "." except when run in a REPL where it defaults to the value of <code>(repl/libs-dir)</code>
:silent {true,false}	if silent is true does not show a progress bar, defaults to true

`:force {true,false}` if force is true download the artifact even if it exist already on the download dir, else skip the download if it exists.
Defaults to true.

```
(do
  (load-module :installer)
  (installer/install [ "dev.langchain4j:langchain4j:0.30.0"
                      "dev.langchain4j:langchain4j-open-ai:0.30.0" ]
    :dir (repl/libs-dir)
    :silent false))
```

SEE ALSO

[installer/install-libs](#)

Install Java libraries (artifacts). Does not install the library's dependencies!

[installer/install-module](#)

Install the 3rdparty libraries for a Venice extension module.

[top](#)

installer/install-demo

`(install-demo options*)`

Install all demo fonts and the 3rdparty libraries for all Venice extension modules that require Java libraries:

- `:jansi`
- `:bouncycastle`
- `:chatgpt`
- `:excel`
- `:pdf`
- `:qrbill`
- `:tomcat`
- `:xchart`
- `:jtokkit`
- `:langchain`
- `:postgresql-jdbc`

Options:

`:dir path` download dir, defaults to "." except when run in a REPL where it defaults to the value of `(repl/libs-dir)`
`:silent {true,false}` if silent is true does not show a progress bar, defaults to true
`:clean {true,false}` if clean is true cleans the install dir before installing, defaults to false
`:force {true,false}` if force is true download the artifact even if it exist already on the download dir, else skip the download if it exists.
Defaults to true.

In the REPL run:

```
venice> (load-module :installer)
venice> (installer/install-demo)
venice> !restart
```

The installed libraries and fonts can be cleaned with:

```
(installer/clean (repl/libs-dir))
```

This removes all JAR lib and the fonts, except the JAnsi and the Venice libs.

```
;; install the demo modules
(do
  (load-module :installer)
  (installer/install-demo :dir (repl/libs-dir) :silent false))

;; clean install dir before installing the demo modules
(do
  (load-module :installer)
  (installer/install-demo :dir (repl/libs-dir) :silent false :clean true))
```

SEE ALSO

[installer/install-demo-fonts](#)

Install the Venice demo fonts.

[installer/clean](#)

Remove Java libraries (except any Jansi library) and TTF font files from the specified directory.

[top](#)

installer/install-demo-fonts

```
(install-demo-fonts options*)
```

Install the Venice demo fonts.

Installs the open source font families from

Family	Download family ref	Type	License
Open Sans	open-sans	TTF	Apache License v2
Roboto	roboto	TTF	Apache License v2
Source Code Pro	source-code-pro	OTF	SIL Open Font License v1.10
JetBrains Mono	jetbrains-mono	TTF	Apache License v2

Downloads the font families from the [Font Squirrel](#) repository

Options:

:dir path download dir, defaults to "." except when run in a REPL where it defaults to the value of `(repl/libs-dir)`

:silent {true,false} if silent is true does not show a progress bar, defaults to true

In the REPL run:

```
venice> (load-module :installer)
venice> (installer/install-demo-fonts)
venice> !restart
```

The installed libraries and fonts can be cleaned with:

```
(installer/clean (repl/libs-dir))
```

```
(do
  (load-module :installer)
  (installer/install-demo-fonts :dir (repl/libs-dir) :silent false))
```

SEE ALSO

[installer/install-demo](#)

Install all demo fonts and the 3rdparty libraries for all Venice extension modules that require Java libraries:

[installer/clean](#)

Remove Java libraries (except any Jansi library) and TTF font files from the specified directory.

[top](#)

installer/install-libs

```
(install-libs libs options*)
```

Install Java libraries (artifacts). Does not install the library's dependencies!

Options:

:dir path	download dir, defaults to "." except when run in a REPL where it defaults to the value of <code>(repl/libs-dir)</code>
:silent {true,false}	if silent is true does not show a progress bar, defaults to true
:force {true,false}	if force is true download the artifact even if it exist already on the download dir, else skip the download if it exists. Defaults to true.

```
(do
  (load-module :installer)
  (installer/install-libs ["org.fusesource.jansi:jansi:2.4.1"]
    :dir (repl/libs-dir)
    :silent false))
```

SEE ALSO

[installer/install](#)

Install Java artifacts and its dependencies.

[installer/install-module](#)

Install the 3rdparty libraries for a Venice extension module.

[top](#)

installer/install-module

```
(install-module name options*)
```

Install the 3rdparty libraries for a Venice extension module.

Options:

:dir path	download dir, defaults to "." except when run in a REPL where it defaults to the value of <code>(repl/libs-dir)</code>
:silent {true,false}	if silent is true does not show a progress bar, defaults to true
:force {true,false}	if force is true download the artifact even if it exist already on the download dir, else skip the download if it exists. Defaults to true.

```
(do
  (load-module :installer)
  (installer/install-module :pdf :dir (repl/libs-dir) :silent false))
```

SEE ALSO

[installer/install](#)

Install Java artifacts and its dependencies.

[installer/install-libs](#)

Install Java libraries (artifacts). Does not install the library's dependencies!

top

instance-of?

`(instance-of? type x)`

Returns true if x is an instance of the given type

```
(instance-of? :long 500)
=> true
```

```
(instance-of? :java.math.BigInteger 500)
=> false
```

SEE ALSO

[type](#)

Returns the type of x.

[supertype](#)

Returns the super type of x.

[supertypes](#)

Returns the super types of x.

top

int

`(int x)`

Converts to int

```
(int 1)
=> 1I
```

```
(int nil)
=> 0I
```

```
(int false)
=> 0I
```

```
(int true)
=> 1I
```

```
(int 1.2)
=> 1I
```

```
(int 1.2F)
=> 1I
```

```
(int 1.2M)
=> 1I
```



```
(int "1")  
=> 1I
```

```
(int (char "A"))  
=> 65I
```

[top](#)

int-array

```
(int-array coll)  
(int-array len)  
(int-array len init-val)
```

Returns an array of Java primitive ints containing the contents of coll or returns an array with the given length and optional init value.

To create an array of :java.lang.Integer use:

```
(make-array :java.lang.Integer 3)
```

```
(int-array '(1I 2I 3I))  
=> [1, 2, 3]
```

```
(int-array '(1I 2 3.2 3.56M))  
=> [1, 2, 3, 3]
```

```
(int-array 10)  
=> [0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

```
(int-array 10 42I)  
=> [42, 42, 42, 42, 42, 42, 42, 42, 42, 42]
```

SEE ALSO

[java-int-list](#)

Converts a Venice list/vector to a Java Integer list

[top](#)

int?

```
(int? n)
```

Returns true if n is an int

```
(int? 4I)  
=> true
```

```
(int? 4)  
=> false
```

```
(int? 3.1)  
=> false
```

```
(int? true)
=> false

(int? nil)
=> false

(int? {})
=> false
```

[top](#)

interleave

```
(interleave c1 c2)
(interleave c1 c2 & colls)
```

Returns a collection of the first item in each coll, then the second etc.

Supports lazy sequences as long as at least one collection is not a lazy sequence.

```
(interleave [:a :b :c] [1 2])
=> (:a 1 :b 2)

(interleave [:a :b :c] (lazy-seq 1 inc))
=> (:a 1 :b 2 :c 3)

(interleave (lazy-seq (constantly :v)) [1 2 3])
=> (:v 1 :v 2 :v 3)
```

[top](#)

interpose

```
(interpose sep coll)
```

Returns a collection of the elements of coll separated by sep.

```
(interpose ", " [1 2 3])
=> (1 ", " 2 ", " 3)

(apply str (interpose ", " [1 2 3]))
=> "1, 2, 3"
```

[top](#)

intersection

```
(intersection s1)
(intersection s1 s2)
(intersection s1 s2 & sets)
```

Return a set that is the intersection of the input sets

```
(intersection (set 1))
=> #{1}

(intersection (set 1 2) (set 2 3))
=> #{2}

(intersection (set 1 2) (set 3 4))
=> #{} 
```

SEE ALSO

[union](#)

Return a set that is the union of the input sets

[difference](#)

Return a set that is the first set without elements of the remaining sets

[cons](#)

Returns a new collection where x is the first element and coll is the rest.

[conj](#)

Returns a new collection with the x, xs 'added'. (conj nil item) returns (item) and (conj item) returns item.

[disj](#)

Returns a new set with the x, xs removed.

[top](#)

into

```
(into)
(into to)
(into to from) 
```

Returns a new coll consisting of to coll with all of the items of from coll conjoined.

```
(into (sorted-map) [ [:a 1] [:c 3] [:b 2] ])
=> {:a 1 :b 2 :c 3}

(into (sorted-map) [ {:a 1} {:c 3} {:b 2} ])
=> {:a 1 :b 2 :c 3}

(into (sorted-map) [(map-entry :b 2) (map-entry :c 3) (map-entry :a 1)])
=> {:a 1 :b 2 :c 3}

(into (sorted-map) {:b 2 :c 3 :a 1})
=> {:a 1 :b 2 :c 3}

(into [] {:a 1, :b 2})
=> [[:a 1] [:b 2]]

(into [] '(1 2 3))
=> [1 2 3]

(into '() '(1 2 3))
=> (3 2 1) 
```

```

(into [1 2 3] '(4 5 6))
=> [1 2 3 4 5 6]

(into '(1 2 3) '(4 5 6))
=> (6 5 4 1 2 3)

(into [] (bytebuf [0 1 2]))
=> [0 1 2]

(into '() (bytebuf [0 1 2]))
=> (0 1 2)

(into [] "abc")
=> [#\a #\b #\c]

(into '() "abc")
=> (#\a #\b #\c)

```

SEE ALSO

[concat](#)

Returns a list of the concatenation of the elements in the supplied collections.

[merge](#)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from ...

[top](#)

into!

```

(into!)
(into! to)
(into! to from)

```

Adds all of the items of 'from' conjoined to the mutable 'to' collection

```

(into! (queue) [1 2 3 4])
=> (1 2 3 4)

(into! (stack) [1 2 3 4])
=> (4 3 2 1)

(do
  (into! (. :java.util.concurrent.CopyOnWriteArrayList :new)
    (doto (. :java.util.ArrayList :new)
      (. :add 3)
      (. :add 4))))
=> (3 4)

(do
  (into! (. :java.util.concurrent.CopyOnWriteArrayList :new)
    '(3 4)))
=> (3 4)

```

SEE ALSO

[concat](#)

Returns a list of the concatenation of the elements in the supplied collections.

[merge](#)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from ...

[top](#)

[io/->uri](#)

```
(io/->uri s)
(io/->uri scheme user-info host port path)
(io/->uri scheme user-info host port path query)
(io/->uri scheme user-info host port path query fragment)
```

Converts `s` to an URI or builds an URI from its spec elements.

`s` may be:

- a string (a spec string to be parsed as a URI.)
- a `java.io.File`
- a `java.nio.file.Path`
- a `java.net.URL`

Arguments:

scheme Scheme name
userInfo User name and authorization information
host Host name
port Port number
path Path
query Query
fragment Fragment

```
(io/->uri "file:/tmp/test.txt")
=> file:/tmp/test.txt

(io/->uri (io/file "/tmp/test.txt"))
=> file:/tmp/test.txt

(io/->uri (io/->url (io/file "/tmp/test.txt")))
=> file:/tmp/test.txt

(str (io/->uri (io/file "/tmp/test.txt")))
=> "file:/tmp/test.txt"

;; to create an URL from spec details:
(io/->uri "http" nil "foo.org" 8080 "/info.html" nil nil)
=> http://foo.org:8080/info.html
```

SEE ALSO

[io/file](#)

Returns a `java.io.File` from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

[io/->url](#)

Converts `s` to an URL or builds an URL from its spec elements.

[top](#)

io/->url

```
(io/->url s)
(io/->url protocol host port file)
```

Converts *s* to an URL or builds an URL from its spec elements.

s may be:

- a string (a spec string to be parsed as a URL.)
- a `java.io.File`
- a `java.nio.file.Path`
- a `java.net.URI`

Arguments:

protocol the name of the protocol to use.

host the name of the host.

port the port number on the host.

file the file on the host

```
(io/->url "file:/tmp/test.txt")
=> file:/tmp/test.txt

(io/->url (io/file "/tmp/test.txt"))
=> file:/tmp/test.txt

(io/->url (io/->uri (io/file "/tmp/test.txt")))
=> file:/tmp/test.txt

(str (io/->url (io/file "/tmp/test.txt")))
=> "file:/tmp/test.txt"

;; to create an URL from spec details:
(io/->url "http" "foo.org" 8080 "/info.html")
=> http://foo.org:8080/info.html
```

SEE ALSO

[io/file](#)

Returns a `java.io.File` from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

[io/->uri](#)

Converts *s* to an URI or builds an URI from its spec elements.

[top](#)

io/await-for

```
(io/await-for timeout time-unit file & modes)
```

Blocks the current thread until the file has been created, deleted, or modified according to the passed modes `{:created, :deleted, :modified}`, or the timeout has elapsed. Returns logical false if returning due to timeout, logical true otherwise.

Supported time units are: `{:milliseconds, :seconds, :minutes, :hours, :days}`

```
(io/await-for 10 :seconds "/tmp/data.json" :created)
```

SEE ALSO

[io/watch-dir](#)

Watch a directory for changes, and call the function event-fn when it does. Calls the optional failure-fn if errors occur. On closing ...

[top](#)

io/buffered-reader

(io/buffered-reader f & options)

Create a `java.io.Reader` from f.

f may be a:

- string
- bytebuffer
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.nio.file.Path`
- `java.io.InputStream`
- `java.io.Reader`
- `java.net.URL`
- `java.net.URI`

Options:

:encoding enc e.g.: :encoding :utf-8 , defaults to :utf-8

`io/buffered-reader` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

Note: The caller is responsible for closing the reader!

```
(let [data (bytebuf [108 105 110 101 32 49 10 108 105 110 101 32 50])]
  (try-with [rd (io/buffered-reader data :encoding :utf-8)]
    (println (read-line rd))
    (println (read-line rd))))
line 1
line 2
=> nil
```

```
(try-with [rd (io/buffered-reader "1\n2\n3\n4")]
  (println (read-line rd))
  (println (read-line rd)))
1
2
=> nil
```

SEE ALSO

[read-line](#)

Without arg reads the next line from the stream that is the current value of *in*. With arg reads the next line from the passed stream ...

[io/string-reader](#)

Creates a `java.io.StringReader` from a string.

[io/buffered-writer](#)

Creates a `java.io.Writer` for f.

[top](#)

io/buffered-writer

(io/buffered-writer f & options)

Creates a `java.io.Writer` for `f`.

`f` may be a:

- `java.io.File`, e.g.: `(io/file "/temp/foo.json")`
- `java.nio.file.Path`
- `java.io.OutputStream`
- `java.io.Writer` Options:

:append true/false e.g.: `:append true`, defaults to false

:encoding enc e.g.: `:encoding :utf-8`, defaults to `:utf-8`

`io/buffered-writer` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

SEE ALSO

[println](#)

Prints the values `xs` to the stream that is the current value of `*out*` or to the passed output stream `os` if given followed by a (newline).

[io/string-writer](#)

Creates a `java.io.StringWriter`.

[io/buffered-reader](#)

Create a `java.io.Reader` from `f`.

[top](#)

io/bytebuf-in-stream

(io/bytebuf-in-stream buf)

Returns a `java.io.InputStream` from a `bytebuf`.

Note: The caller is responsible for closing the stream!

```
(try-with [is (io/bytebuf-in-stream (bytebuf [97 98 99]))]  
  ; do something with is  
  )
```

SEE ALSO

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` `is`. Supports the option `:binary` to either slurp binary or string data. For ...

[io/file-in-stream](#)

Returns a `java.io.InputStream` for the file `f`.

[io/string-in-stream](#)

Returns a `java.io.InputStream` for the string `s`.

[top](#)

io/bytebuf-out-stream

(io/bytebuf-out-stream)

Returns a new `java.io.ByteArrayOutputStream`.

Dereferencing a `:ByteArrayOutputStream` returns the captured bytebuf.

Note: The caller is responsible for closing the stream!

```
(try-with [os (io/bytebuf-out-stream)]
  (io/spit-stream os (bytebuf [97 98 99]) :flush true)
  (str/format-bytebuf @os ", " :prefix0x))
=> "0x61, 0x62, 0x63"
```

SEE ALSO

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` is. Supports the option `:binary` to either slurp binary or string data. For ...

[io/file-in-stream](#)

Returns a `java.io.InputStream` for the file `f`.

[io/string-in-stream](#)

Returns a `java.io.InputStream` for the string `s`.

[top](#)

io/capturing-print-stream

(io/capturing-print-stream)

Creates a new capturing print stream.

Dereferencing a capturing print stream returns the captured string.

Note: The caller is responsible for closing the stream!

```
(try-with [ps (io/capturing-print-stream)]
  (binding [*out* ps]
    (println 100)
    (println 200)
    (flush)
    @ps))
=> "100\n200\n"
```

```
(try-with [ps (io/capturing-print-stream)]
  (println ps 100)
  (println ps 200)
  (flush ps)
  @ps)
=> "100\n200\n"
```

[top](#)

io/classpath-resource?

```
(io/classpath-resource? name)
```

Returns true if the classpath resource exists otherwise false.

```
(io/classpath-resource? "com/github/jlangch/venice/images/venice.png")  
=> true
```

SEE ALSO

[io/load-classpath-resource](#)

Loads a classpath resource. Returns a bytebuf

[top](#)

io/close

```
(io/close s)
```

Closes a `:java.io.InputStream`, `:java.io.OutputStream`, `:java.io.Reader`, or a `:java.io.Writer`.

Often it is more elegant to use try-with to let Venice implicitly close the stream when its leaves the scope:

```
(let [file (io/file "foo.txt")]  
  (try-with [is (io/file-in-stream file)]  
    (io/slurp-stream is :binary false)))
```

SEE ALSO

[io/flush](#)

Flushes a `:java.io.OutputStream` or a `:java.io.Writer`.

[top](#)

io/close-watcher

```
(io/close-watcher watcher)
```

Closes a watcher created from 'io/watch-dir'.

SEE ALSO

[io/watch-dir](#)

Watch a directory for changes, and call the function event-fn when it does. Calls the optional failure-fn if errors occur. On closing ...

[top](#)

io/copy-file

```
(io/copy-file source dest & options)
```

Copies source to dest. Returns nil or throws a `VncException`. Source must be a file or a string (file path), dest must be a file, a string (file path), or an `java.io.OutputStream`.

Options:

:replace true/false	e.g.: if true replace an existing file, defaults to false
:copy-attributes true/false	e.g.: if true copy attributes to the new file, defaults to false
:no-follow-links true/false	e.g.: if true do not follow symbolic links, defaults to false

SEE ALSO

[io/copy-files-glob](#)

Copies all files that match the glob pattern from a source to a destination directory. src-dir and dst-dir must be a file or a string ...

[io/copy-file-tree](#)

Copies a file tree from source to dest. Returns nil or throws a VncException. Source must be a file or a string (file path), dest must ...

[io/move-file](#)

Moves source to target. Returns nil or throws a VncException. Source and target must be a file or a string (file path).

[io/delete-file](#)

Deletes one or multiple files. Silently skips delete if the file does not exist. If f is a directory the directory must be empty. f ...

[io/touch-file](#)

Updates the lastModifiedTime of the file to the current time, or creates a new empty file if the file doesn't already exist. File must ...

[io/copy-stream](#)

Copies the input stream to the output stream. Returns nil on sucess or throws a VncException on failure. Input and output must be a ...

top

io/copy-file-tree

(io/copy-file-tree source dest & options)

Copies a file tree from source to dest. Returns nil or throws a VncException. Source must be a file or a string (file path), dest must be a file, a string (file path), or an `java.io.OutputStream` .

Options:

:replace true/false	e.g.: if true replace an existing file, defaults to false
:copy-attributes true/false	e.g.: if true copy attributes to the new file, defaults to false
:no-follow-links true/false	e.g.: if true do not follow symbolic links, defaults to false

SEE ALSO

[io/copy-file](#)

Copies source to dest. Returns nil or throws a VncException. Source must be a file or a string (file path), dest must be a file, a ...

[io/copy-files-glob](#)

Copies all files that match the glob pattern from a source to a destination directory. src-dir and dst-dir must be a file or a string ...

[io/move-file](#)

Moves source to target. Returns nil or throws a VncException. Source and target must be a file or a string (file path).

[io/delete-file](#)

Deletes one or multiple files. Silently skips delete if the file does not exist. If f is a directory the directory must be empty. f ...

[io/touch-file](#)

Updates the lastModifiedTime of the file to the current time, or creates a new empty file if the file doesn't already exist. File must ...

[io/copy-stream](#)

Copies the input stream to the output stream. Returns nil on sucess or throws a VncException on failure. Input and output must be a ...

top

io/copy-files-glob

```
(io/copy-files-glob src-dir dst-dir glob & options)
```

Copies all files that match the glob pattern from a source to a destination directory. `src-dir` and `dst-dir` must be a file or a string (file path).

Options:

<code>:replace true/false</code>	e.g.: if true replace an existing file, defaults to false
<code>:copy-attributes true/false</code>	e.g.: if true copy attributes to the new file, defaults to false
<code>:no-follow-links true/false</code>	e.g.: if true do not follow symbolic links, defaults to false

Globbing patterns

<code>*.txt</code>	Matches a path that represents a file name ending in <code>.txt</code>
<code>*.*</code>	Matches file names containing a dot
<code>*.{txt,xml}</code>	Matches file names ending with <code>.txt</code> or <code>.xml</code>
<code>foo.?[xy]</code>	Matches file names starting with <code>foo.</code> and a single character extension followed by a 'x' or 'y' character
<code>/home/*/*</code>	Matches <code>/home/gus/data</code> on UNIX platforms
<code>/home/**</code>	Matches <code>/home/gus</code> and <code>/home/gus/data</code> on UNIX platforms
<code>C:*</code>	Matches <code>C:\\foo</code> and <code>C:\\bar</code> on the Windows platform

Ranges

The pattern `[A-E]` would match any character that included ABCDE. Ranges can be used in conjunction with each other to make powerful patterns. Alphanumerical strings are matched by `[A-Za-z0-9]`. This would match the following:

- `[A-Z]` All uppercase letters from A to Z
- `[a-z]` All lowercase letters from a to z
- `[0-9]` All numbers from 0 to 9

Complementation

Globs can be used in complement with special characters that can change how the pattern works. The two complement characters are exclamation marks `(!)` and backslashes `(\\)`.

The exclamation mark can negate a pattern that it is put in front of. As `[CBR]at` matches Cat, Bat, or Rat the negated pattern `[!CBR]at` matches anything like Kat, Pat, or Vat.

Backslashes are used to remove the special meaning of single characters `'?'`, `'*'`, and `'['`, so that they can be used in patterns.

```
(io/copy-files-glob "from" "to" "*.log")
```

SEE ALSO

[io/copy-file](#)

Copies source to dest. Returns nil or throws a `VncException`. Source must be a file or a string (file path), dest must be a file, a ...

[io/copy-file-tree](#)

Copies a file tree from source to dest. Returns nil or throws a `VncException`. Source must be a file or a string (file path), dest must ...

[io/move-files-glob](#)

Move all files that match the glob pattern from a source to a destination directory. `src-dir` and `dst-dir` must be a file or a string (file path).

[io/delete-files-glob](#)

Removes all files in a directory that match the glob pattern. `dir` must be a file or a string (file path).

[io/list-files-glob](#)

Lists all files in a directory that match the glob pattern. `dir` must be a file or a string (file path). Returns files as `java.io.File`

io/copy-stream

```
(io/copy-stream in-stream out-stream)
```

Copies the input stream to the output stream. Returns `nil` on success or throws a `VncException` on failure. Input and output must be a `java.io.InputStream` and `java.io.OutputStream`.

SEE ALSO

[io/copy-file](#)

Copies source to dest. Returns `nil` or throws a `VncException`. Source must be a file or a string (file path), dest must be a file, a ...

[top](#)

io/create-hard-link

```
(io/create-hard-link link target)
```

Creates a hard link to a target. link and target must be a file or a string (file path).

```
(io/create-hard-link "/tmp/hard-link" "/tmp/test.txt")
```

SEE ALSO

[io/create-symbolic-link](#)

Creates a symbolic link to a target. link and target must be a file or a string (file path).

[io/symbolic-link?](#)

Returns true if the file `f` exists and is a symbolic link. `f` must be a file or a string (file path).

[top](#)

io/create-symbolic-link

```
(io/create-symbolic-link link target)
```

Creates a symbolic link to a target. link and target must be a file or a string (file path).

```
(io/create-symbolic-link "/tmp/sym-link" "/tmp/test.txt")
```

SEE ALSO

[io/create-hard-link](#)

Creates a hard link to a target. link and target must be a file or a string (file path).

[io/symbolic-link?](#)

Returns true if the file `f` exists and is a symbolic link. `f` must be a file or a string (file path).

[top](#)

io/default-charset

(io/default-charset)

Returns the default charset.

top

io/deflate

(io/deflate bytebuf)

deflates (compresses) a bytebuf using ZLIB compression.

```
(-> (bytebuf-from-string "abcdef" :utf-8)
  (io/deflate))
=> [120 156 75 76 74 78 73 77 3 0 8 30 2 86]
```

SEE ALSO

[io/inflate](#)

inflates (decompresses) a bytebuf using ZLIB compression.

top

io/delete-file

(io/delete-file f & files)

Deletes one or multiple files. Silently skips delete if the file does not exist. If f is a directory the directory must be empty. f must be a file or a string (file path).

SEE ALSO

[io/delete-files-glob](#)

Removes all files in a directory that match the glob pattern. dir must be a file or a string (file path).

[io/delete-file-tree](#)

Deletes a file or a directory with all its content. Silently skips delete if the file or directory does not exist. f must be a file ...

[io/delete-file-on-exit](#)

Requests that the files or directories be deleted when the virtual machine terminates. Files (or directories) are deleted in the reverse ...

[io/copy-file](#)

Copies source to dest. Returns nil or throws a VncException. Source must be a file or a string (file path), dest must be a file, a ...

[io/move-file](#)

Moves source to target. Returns nil or throws a VncException. Source and target must be a file or a string (file path).

top

io/delete-file-on-exit

(io/delete-file-on-exit f & fs)

Requests that the files or directories be deleted when the virtual machine terminates. Files (or directories) are deleted in the reverse order that they are registered. Invoking this method to delete a file or directory that is already registered for deletion has no effect. Deletion will be attempted only for normal termination of the virtual machine, as defined by the Java Language Specification.

f must be a file or a string (file path).

```
(let [file1 (io/temp-file "test-", ".data")
      file2 (io/temp-file "test-", ".data")]
  (io/delete-file-on-exit file1 file2)
  (io/spit file1 "123")
  (io/spit file2 "ABC"))
```

SEE ALSO

- [io/delete-file](#)
Deletes one or multiple files. Silently skips delete if the file does not exist. If f is a directory the directory must be empty. f ...
- [io/delete-file-tree](#)
Deletes a file or a directory with all its content. Silently skips delete if the file or directory does not exist. f must be a file ...
- [io/delete-files-glob](#)
Removes all files in a directory that match the glob pattern. dir must be a file or a string (file path).

top

io/delete-file-tree

```
(io/delete-file-tree f & files)
```

Deletes a file or a directory with all its content. Silently skips delete if the file or directory does not exist. f must be a file or a string (file path)

SEE ALSO

- [io/delete-files-glob](#)
Removes all files in a directory that match the glob pattern. dir must be a file or a string (file path).
- [io/delete-file](#)
Deletes one or multiple files. Silently skips delete if the file does not exist. If f is a directory the directory must be empty. f ...
- [io/delete-file-on-exit](#)
Requests that the files or directories be deleted when the virtual machine terminates. Files (or directories) are deleted in the reverse ...

top

io/delete-files-glob

```
(io/delete-files-glob dir glob)
```

Removes all files in a directory that match the glob pattern. dir must be a file or a string (file path).

Globbing patterns

<code>*.txt</code>	Matches a path that represents a file name ending in .txt
<code>*.*</code>	Matches file names containing a dot
<code>*.{txt,xml}</code>	Matches file names ending with .txt or .xml
<code>foo.?[xy]</code>	Matches file names starting with foo. and a single character extension followed by a 'x' or 'y' character
<code>/home/*/*</code>	Matches <code>/home/gus/data</code> on UNIX platforms

`/home/**` Matches `/home/gus` and `/home/gus/data` on UNIX platforms

`C:*` Matches `C:\\foo` and `C:\\bar` on the Windows platform

Ranges

The pattern `[A-E]` would match any character that included ABCDE. Ranges can be used in conjunction with each other to make powerful patterns. Alphanumerical strings are matched by `[A-Za-z0-9]`. This would match the following:

- `[A-Z]` All uppercase letters from A to Z
- `[a-z]` All lowercase letters from a to z
- `[0-9]` All numbers from 0 to 9

Complementation

Globs can be used in complement with special characters that can change how the pattern works. The two complement characters are exclamation marks `(!)` and backslashes `(\\)`.

The exclamation mark can negate a pattern that it is put in front of. As `[CBR]at` matches Cat, Bat, or Rat the negated pattern `[!CBR]at` matches anything like Kat, Pat, or Vat.

Backslashes are used to remove the special meaning of single characters `'?'`, `'*'`, and `'['`, so that they can be used in patterns.

```
(io/delete-files-glob "." "*.log")
```

SEE ALSO

[io/delete-file](#)

Deletes one or multiple files. Silently skips delete if the file does not exist. If `f` is a directory the directory must be empty. `f ...`

[io/delete-file-tree](#)

Deletes a file or a directory with all its content. Silently skips delete if the file or directory does not exist. `f` must be a file ...

[io/move-files-glob](#)

Move all files that match the glob pattern from a source to a destination directory. `src-dir` and `dst-dir` must be a file or a string (file path).

[io/copy-files-glob](#)

Copies all files that match the glob pattern from a source to a destination directory. `src-dir` and `dst-dir` must be a file or a string ...

[io/list-files-glob](#)

Lists all files in a directory that match the glob pattern. `dir` must be a file or a string (file path). Returns files as `java.io.File`

[top](#)

io/download

```
(io/download uri & options)
```

Downloads the content from the `uri` and reads it as text (string) or binary (bytebuf). Supports http and https protocols!

Options:

<code>:binary b</code>	e.g.: <code>:binary true</code> , defaults to false
<code>:user-agent agent</code>	e.g.: <code>:user-agent "Mozilla"</code> , defaults to nil
<code>:encoding enc</code>	e.g.: <code>:encoding :utf-8</code> , defaults to <code>:utf-8</code>
<code>:user u</code>	optional user for basic authentication
<code>:password p</code>	optional password for basic authentication
<code>:follow-redirects b</code>	e.g.: <code>:follow-redirects true</code> , defaults to false
<code>:conn-timeout val</code>	e.g.: <code>:conn-timeout 10000</code> , connection timeout in milliseconds. 0 is interpreted as an infinite timeout.
<code>:read-timeout val</code>	e.g.: <code>:read-timeout 10000</code> , read timeout in milliseconds. 0 is interpreted as an infinite timeout.

`:progress-fn fn` an optional progress function that takes 2 args
 [1] progress (0..100%)
 [2] status {:start :progress :end :failed}

`:debug-fn fn` an optional debug function that takes a message as argument

Note:

If the server returns the HTTP response status code 403 (*Access Denied*) sending a user agent like "Mozilla" may fool the website and solve the problem.

To debug pass a printing function like: `(io/download https://foo.org/bar :debug-fn println)`

```
(-<> "https://live.staticflickr.com/65535/51007202541_ea453871d8_o_d.jpg"
  (io/download <> :binary true :user-agent "Mozilla")
  (io/spit "space-x.jpg" <>))

(do
  (load-module :ansi)
  (-<> "https://live.staticflickr.com/65535/51007202541_ea453871d8_o_d.jpg"
    (io/download <> :binary true
                  :user-agent "Mozilla"
                  :progress-fn (ansi/progress :caption "Download:"))
    (io/spit "space-x.jpg" <>)))
```

[top](#)

io/exists-dir?

```
(io/exists-dir? f)
```

Returns true if the file `f` exists and is a directory. `f` must be a file or a string (file path).

```
(io/exists-dir? (io/file "/temp"))
=> false
```

SEE ALSO

[io/exists-file?](#)

Returns true if the file `f` exists and is a file. `f` must be a file or a string (file path).

[io/symbolic-link?](#)

Returns true if the file `f` exists and is a symbolic link. `f` must be a file or a string (file path).

[top](#)

io/exists-file?

```
(io/exists-file? f)
```

Returns true if the file `f` exists and is a file. `f` must be a file or a string (file path).

```
(io/exists-file? "/tmp/test.txt")
=> false
```

SEE ALSO

[io/exists-dir?](#)

Returns true if the file `f` exists and is a directory. `f` must be a file or a string (file path).

[io/symbolic-link?](#)

Returns true if the file `f` exists and is a symbolic link. `f` must be a file or a string (file path).

[top](#)

io/file

```
(io/file path)
(io/file parent child)
(io/file parent child & children)
```

Returns a `java.io.File` from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string (file path), child and children must be strings.

```
(io/file "/tmp/test.txt")
=> /tmp/test.txt

(io/file "/temp" "test.txt")
=> /temp/test.txt

(io/file "/" "temp" "test" "test.txt")
=> /temp/test/test.txt

(io/file (io/file "/" "temp") "test" "test.txt")
=> /temp/test/test.txt

(io/file (. :java.io.File :new "/tmp/test.txt"))
=> /tmp/test.txt

;; Windows:
;; (io/file "C:\\tmp\\test.txt")
;; (io/file "C:/tmp/test.txt")

;; (io/file "C:" "temp" "test.txt")
```

SEE ALSO

[io/file-name](#)

Returns the name of the file `f` as a string. `f` must be a file or a string (file path).

[io/file-parent](#)

Returns the parent file of the file `f`. `f` must be a file or a string (file path).

[io/file-path](#)

Returns the path of the file `f` as a string. `f` must be a file or a string (file path).

[io/file-absolute](#)

Returns the absolute path of the file `f`. `f` must be a file or a string (file path).

[io/file-canonical](#)

Returns the canonical path of the file `f`. `f` must be a file or a string (file path).

[str/normalize-utf](#)

Normalizes an UTF string.

[top](#)

io/file-absolute

```
(io/file-absolute f)
```

Returns the absolute path of the file `f`. `f` must be a file or a string (file path).

```
(io/file-absolute (io/file "/tmp/test/x.txt"))  
=> /tmp/test/x.txt
```

SEE ALSO

[io/file-path](#)

Returns the path of the file `f` as a string. `f` must be a file or a string (file path).

[io/file-canonical](#)

Returns the canonical path of the file `f`. `f` must be a file or a string (file path).

[io/file](#)

Returns a `java.io.File` from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

[io/file-absolute?](#)

Returns true if file `f` has an absolute path else false. `f` must be a file or a string (file path).

[str/normalize-utf](#)

Normalizes an UTF string.

[top](#)

io/file-absolute?

```
(io/file-absolute? f)
```

Returns true if file `f` has an absolute path else false. `f` must be a file or a string (file path).

```
(io/file-absolute? (io/file "/tmp/test/x.txt"))  
=> true
```

SEE ALSO

[io/file-path](#)

Returns the path of the file `f` as a string. `f` must be a file or a string (file path).

[io/file-canonical](#)

Returns the canonical path of the file `f`. `f` must be a file or a string (file path).

[io/file](#)

Returns a `java.io.File` from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

[io/file-absolute](#)

Returns the absolute path of the file `f`. `f` must be a file or a string (file path).

[top](#)

io/file-basename

```
(io/file-basename f)
```

Returns the base name (file name without file extension) of the file `f` as a string. `f` must be a file or a string (file path).

```
(io/file-basename (io/file "/tmp/test/x.txt"))  
=> "x"
```

SEE ALSO

[io/file-name](#)

Returns the name of the file `f` as a string. `f` must be a file or a string (file path).

[io/file-parent](#)

Returns the parent file of the file `f`. `f` must be a file or a string (file path).

[io/file-ext](#)

Returns the file extension of a file. `f` must be a file or a string (file path).

[io/file](#)

Returns a `java.io.File` from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

[str/normalize-utf](#)

Normalizes an UTF string.

[top](#)

io/file-can-execute?

```
(io/file-can-execute? f)
```

Returns true if the file or directory `f` exists and can be executed. `f` must be a file or a string (file path).

```
(io/file-can-execute? "/tmp/test.txt")
```

SEE ALSO

[io/file-set-executable](#)

Set the owner's execute permission to the file or directory `f`. `f` must be a file or a string (file path).

[io/file-can-read?](#)

Returns true if the file or directory `f` exists and can be read. `f` must be a file or a string (file path).

[io/file-can-write?](#)

Returns true if the file or directory `f` exists and can be written. `f` must be a file or a string (file path).

[io/file-hidden?](#)

Returns true if the file or directory `f` exists and is hidden. `f` must be a file or a string (file path).

[io/symbolic-link?](#)

Returns true if the file `f` exists and is a symbolic link. `f` must be a file or a string (file path).

[top](#)

io/file-can-read?

```
(io/file-can-read? f)
```

Returns true if the file or directory `f` exists and can be read. `f` must be a file or a string (file path).

```
(io/file-can-read? "/tmp/test.txt")
```

SEE ALSO

[io/file-set-readable](#)

Set the owner's read permission to the file or directory *f*. *f* must be a file or a string (file path).

[io/file-can-write?](#)

Returns true if the file or directory *f* exists and can be written. *f* must be a file or a string (file path).

[io/file-can-execute?](#)

Returns true if the file or directory *f* exists and can be executed. *f* must be a file or a string (file path).

[io/file-hidden?](#)

Returns true if the file or directory *f* exists and is hidden. *f* must be a file or a string (file path).

[io/symbolic-link?](#)

Returns true if the file *f* exists and is a symbolic link. *f* must be a file or a string (file path).

[top](#)

io/file-can-write?

```
(io/file-can-write? f)
```

Returns true if the file or directory *f* exists and can be written. *f* must be a file or a string (file path).

```
(io/file-can-write? "/tmp/test.txt")
```

SEE ALSO

[io/file-set-writable](#)

Set the owner's write permission to the file or directory *f*. *f* must be a file or a string (file path).

[io/file-can-read?](#)

Returns true if the file or directory *f* exists and can be read. *f* must be a file or a string (file path).

[io/file-can-execute?](#)

Returns true if the file or directory *f* exists and can be executed. *f* must be a file or a string (file path).

[io/file-hidden?](#)

Returns true if the file or directory *f* exists and is hidden. *f* must be a file or a string (file path).

[io/symbolic-link?](#)

Returns true if the file *f* exists and is a symbolic link. *f* must be a file or a string (file path).

[top](#)

io/file-canonical

```
(io/file-canonical f)
```

Returns the canonical path of the file *f*. *f* must be a file or a string (file path).

```
(io/file-canonical (io/file "/tmp/test/../x.txt"))  
=> /private/tmp/x.txt
```

SEE ALSO

[io/file-path](#)

Returns the path of the file *f* as a string. *f* must be a file or a string (file path).

[io/file-absolute](#)

Returns the absolute path of the file `f`. `f` must be a file or a string (file path).

[io/file](#)

Returns a `java.io.File` from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

[str/normalize-utf](#)

Normalizes an UTF string.

[top](#)

io/file-ext

```
(io/file-ext f)
```

Returns the file extension of a file. `f` must be a file or a string (file path).

```
(io/file-ext "some.txt")  
=> "txt"
```

```
(io/file-ext "/tmp/test/some.txt")  
=> "txt"
```

```
(io/file-ext "/tmp/test/some")  
=> nil
```

SEE ALSO

[io/file-ext?](#)

Returns true if the file `f` has the extension `ext`. `f` must be a file or a string (file path).

[io/file-basename](#)

Returns the base name (file name without file extension) of the file `f` as a string. `f` must be a file or a string (file path).

[top](#)

io/file-ext?

```
(io/file-ext? f ext & exts)
```

Returns true if the file `f` has the extension `ext`. `f` must be a file or a string (file path).

```
(io/file-ext? "/tmp/test/x.txt" "txt")  
=> true
```

```
(io/file-ext? (io/file "/tmp/test/x.txt") ".txt")  
=> true
```

```
(io/file-ext? "/tmp/test/x.docx" "doc" "docx")  
=> false
```

SEE ALSO

[io/file-ext](#)

Returns the file extension of a file. `f` must be a file or a string (file path).

io/file-hidden?

```
(io/file-hidden? f)
```

Returns true if the file or directory `f` exists and is hidden. `f` must be a file or a string (file path).

```
(io/file-hidden? "/tmp/test.txt")
```

SEE ALSO

[io/file-can-read?](#)

Returns true if the file or directory `f` exists and can be read. `f` must be a file or a string (file path).

[io/file-can-write?](#)

Returns true if the file or directory `f` exists and can be written. `f` must be a file or a string (file path).

[io/file-can-execute?](#)

Returns true if the file or directory `f` exists and can be executed. `f` must be a file or a string (file path).

[io/symbolic-link?](#)

Returns true if the file `f` exists and is a symbolic link. `f` must be a file or a string (file path).

io/file-in-stream

```
(io/file-in-stream f)
```

Returns a `java.io.InputStream` for the file `f`.

`f` may be a:

- string file path, e.g: `"/temp/foo.json"`
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`

`io/file-in-stream` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

Note: The caller is responsible for closing the stream!

SEE ALSO

[io/slurp](#)

Reads the content of file `f` as text (string) or binary (bytebuf).

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` is. Supports the option `:binary` to either slurp binary or string data. For ...

[io/string-in-stream](#)

Returns a `java.io.InputStream` for the string `s`.

[io/bytebuf-in-stream](#)

Returns a `java.io.InputStream` from a bytebuf.

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

io/file-last-modified

```
(io/file-last-modified f)
```

Returns the last modification time (a Java LocalDateTime) of `f` or nil if `f` does not exist. `f` must be a file or a string (file path).

```
(io/file-last-modified "/tmp/test.txt")
```

SEE ALSO

[io/file-can-read?](#)

Returns true if the file or directory `f` exists and can be read. `f` must be a file or a string (file path).

[io/file-can-write?](#)

Returns true if the file or directory `f` exists and can be written. `f` must be a file or a string (file path).

[io/file-can-execute?](#)

Returns true if the file or directory `f` exists and can be executed. `f` must be a file or a string (file path).

[top](#)

io/file-matches-glob?

```
(io/file-matches-glob? glob f)
```

Returns true if the file `f` matches the glob pattern. `f` must be a file or a string (file path).

Globbing patterns

<code>*.txt</code>	Matches a path that represents a file name ending in <code>.txt</code>
<code>*.*</code>	Matches file names containing a dot
<code>*.{txt,xml}</code>	Matches file names ending with <code>.txt</code> or <code>.xml</code>
<code>foo.[xy]</code>	Matches file names starting with <code>foo.</code> and a single character extension followed by a 'x' or 'y' character
<code>/home/*/*</code>	Matches <code>/home/gus/data</code> on UNIX platforms
<code>/home/**</code>	Matches <code>/home/gus</code> and <code>/home/gus/data</code> on UNIX platforms
<code>C:*</code>	Matches <code>C:\\foo</code> and <code>C:\\bar</code> on the Windows platform

Ranges

The pattern `[A-E]` would match any character that included ABCDE. Ranges can be used in conjunction with each other to make powerful patterns. Alphanumerical strings are matched by `[A-Za-z0-9]`. This would match the following:

- `[A-Z]` All uppercase letters from A to Z
- `[a-z]` All lowercase letters from a to z
- `[0-9]` All numbers from 0 to 9

Complementation

Globs can be used in complement with special characters that can change how the pattern works. The two complement characters are exclamation marks `(!)` and backslashes `(\\)`.

The exclamation mark can negate a pattern that it is put in front of. As `[CBR]at` matches Cat, Bat, or Rat the negated pattern `[!CBR]at` matches anything like Kat, Pat, or Vat.

Backslashes are used to remove the special meaning of single characters `'?'`, `'*'`, and `'['`, so that they can be used in patterns.


```
(io/file-matches-glob? "*.log" "file.log")
=> true

(io/file-matches-glob? "**/*.log" "x/y/file.log")
=> true

(io/file-matches-glob? "**/*.log" "file.log") ; take care, doesn't match!
=> false

(io/file-matches-glob? (io/glob-path-matcher "*.log") (io/file "file.log"))
=> true

(io/file-matches-glob? (io/glob-path-matcher "**/*.log") (io/file "x/y/file.log"))
=> true
```

SEE ALSO

[io/glob-path-matcher](#)

Returns a file matcher for glob file patterns.

[io/list-files-glob](#)

Lists all files in a directory that match the glob pattern. dir must be a file or a string (file path). Returns files as java.io.File

[top](#)

io/file-name

```
(io/file-name f)
```

Returns the name of the file f as a string. f must be a file or a string (file path).

```
(io/file-name (io/file "/tmp/test/x.txt"))
=> "x.txt"
```

SEE ALSO

[io/file-basename](#)

Returns the base name (file name without file extension) of the file f as a string. f must be a file or a string (file path).

[io/file-parent](#)

Returns the parent file of the file f. f must be a file or a string (file path).

[io/file](#)

Returns a java.io.File from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

[str/normalize-utf](#)

Normalizes an UTF string.

[top](#)

io/file-normalize-utf

```
(io/file-normalize-utf file)
(io/file-normalize-utf file form)
```

Normalizes the UTF string of a file path.

On MacOS file names with umlauts like ä are just encoded as 'a' plus the combining dieresis character. Therefore an 'ä' (\u00FC) and an 'ä' (a + \u0308) from a MacOS file name are different! Under normal circumstances this not problem. But as soon as some file name processing is in place (comparing, matching, ...) this can result in strange behaviour due of the two different technical representations of umlaut characters.

The *form* argument defaults to :NFC and is one of:

- :NFD Canonical decomposition
- :NFC Canonical decomposition, followed by canonical composition
- :NFKD Compatibility decomposition
- :NFKC Compatibility decomposition, followed by canonical composition

Returns an UTF normalized java.io.File from a file path

See the function `str/normalize-utf` for details on UTF normalization.

```
(io/file-normalize-utf "/tmp/test_u\u0308.txt")
```

```
(io/file-normalize-utf (io/file "/tmp/test_u\u0308.txt"))
```

SEE ALSO

[str/normalize-utf](#)

Normalizes an UTF string.

[top](#)

io/file-out-stream

```
(io/file-out-stream f options)
```

Returns a `java.io.OutputStream` for the file `f`.

`f` may be a:

- string file path, e.g: `"/temp/foo.json"`
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`

Options:

:append true/false e.g.: `:append true`, defaults to false

:encoding enc e.g.: `:encoding :utf-8`, defaults to :utf-8

`io/file-out-stream` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

Note: The caller is responsible for closing the stream!

SEE ALSO

[io/slurp](#)

Reads the content of file `f` as text (string) or binary (bytebuf).

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` is. Supports the option `:binary` to either slurp binary or string data. For ...

[io/string-in-stream](#)

Returns a `java.io.InputStream` for the string `s`.

[io/bytebuf-in-stream](#)

Returns a `java.io.InputStream` from a bytebuf.

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

io/file-parent

```
(io/file-parent f)
```

Returns the parent file of the file *f*. *f* must be a file or a string (file path).

```
(io/file-path (io/file-parent (io/file "/tmp/test/x.txt")))
=> "/tmp/test"
```

SEE ALSO

[io/file-name](#)

Returns the name of the file *f* as a string. *f* must be a file or a string (file path).

[io/file](#)

Returns a java.io.File from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

io/file-path

```
(io/file-path f)
```

Returns the path of the file *f* as a string. *f* must be a file or a string (file path).

```
(io/file-path (io/file "/tmp/test/x.txt"))
=> "/tmp/test/x.txt"
```

SEE ALSO

[io/file-absolute](#)

Returns the absolute path of the file *f*. *f* must be a file or a string (file path).

[io/file-canonical](#)

Returns the canonical path of the file *f*. *f* must be a file or a string (file path).

[io/file](#)

Returns a java.io.File from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

[str/normalize-utf](#)

Normalizes an UTF string.

io/file-path-slashify

```
(io/file-path-slashify f)
```

Returns the path of the file *f* as a string, turns backslashes into slashes.

f must be a file or a string (file path).

C:\Users\foo\image.png -> C:/Users/foo/image.png

Note: Windows only. On other OSs works identical to 'io/file-path'.

```
(io/file-path-slashify (io/file "C:" "Users" "foo" "image.png"))  
=> "C:/Users/foo/image.png"
```

SEE ALSO

[io/file-path](#)

Returns the path of the file *f* as a string. *f* must be a file or a string (file path).

[top](#)

io/file-set-executable

```
(io/file-set-executable f executable owner-only)
```

Set the owner's execute permission to the file or directory *f*. *f* must be a file or a string (file path).

Returns true if and only if the operation succeeded. The operation will fail if the user does not have permission to change the access permissions of this abstract pathname. If 'readable' is false and the underlying file system does not implement a read permission, then the operation will fail.

If 'executable' is true sets the access permission to allow execute operations; if false to disallow execute operations.

If 'owner-only' is true the execute permission applies only to the owner's execute permission; otherwise, it applies to everybody. If the underlying file system can not distinguish the owner's execute permission from that of others, then the permission will apply to everybody, regardless of this value.

```
(io/file-set-executable "/tmp/test.txt" true true)
```

SEE ALSO

[io/file-can-execute?](#)

Returns true if the file or directory *f* exists and can be executed. *f* must be a file or a string (file path).

[io/file-set-readable](#)

Set the owner's read permission to the file or directory *f*. *f* must be a file or a string (file path).

[io/file-set-writable](#)

Set the owner's write permission to the file or directory *f*. *f* must be a file or a string (file path).

[top](#)

io/file-set-readable

```
(io/file-set-readable f readable owner-only)
```

Set the owner's read permission to the file or directory *f*. *f* must be a file or a string (file path).

Returns true if and only if the operation succeeded. The operation will fail if the user does not have permission to change the access permissions of this abstract pathname. If 'readable' is false and the underlying file system does not implement a read permission, then the operation will fail.

If 'readable' is true sets the access permission to allow read operations; if false to disallow read operations.

If 'owner-only' is true the read permission applies only to the owner's read permission; otherwise, it applies to everybody. If the underlying file system can not distinguish the owner's read permission from that of others, then the permission will apply to everybody, regardless of this value.

```
(io/file-set-readable "/tmp/test.txt" true true)
```

SEE ALSO

[io/file-can-read?](#)

Returns true if the file or directory *f* exists and can be read. *f* must be a file or a string (file path).

[io/file-set-writable](#)

Set the owner's write permission to the file or directory *f*. *f* must be a file or a string (file path).

[io/file-set-executable](#)

Set the owner's execute permission to the file or directory *f*. *f* must be a file or a string (file path).

[top](#)

io/file-set-writable

```
(io/file-set-writable f writable owner-only)
```

Set the owner's write permission to the file or directory *f*. *f* must be a file or a string (file path).

Returns true if and only if the operation succeeded. The operation will fail if the user does not have permission to change the access permissions of this abstract pathname. If 'writable' is false and the underlying file system does not implement a read permission, then the operation will fail.

If 'writable' is true sets the access permission to allow write operations; if false to disallow write operations.

If 'owner-only' is true the write permission applies only to the owner's write permission; otherwise, it applies to everybody. If the underlying file system can not distinguish the owner's write permission from that of others, then the permission will apply to everybody, regardless of this value.

```
(io/file-set-writable "/tmp/test.txt" true true)
```

SEE ALSO

[io/file-can-write?](#)

Returns true if the file or directory *f* exists and can be written. *f* must be a file or a string (file path).

[io/file-set-readable](#)

Set the owner's read permission to the file or directory *f*. *f* must be a file or a string (file path).

[io/file-set-executable](#)

Set the owner's execute permission to the file or directory *f*. *f* must be a file or a string (file path).

[top](#)

io/file-size

```
(io/file-size f)
```

Returns the size of the file *f*. *f* must be a file or a string (file path).

```
(io/file-size "/tmp/test.txt")
```

SEE ALSO

[io/file](#)

Returns a java.io.File from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

io/file-within-dir?

```
(io/file-within-dir? dir file)
```

Returns true if the file is within the dir else false.

The file and dir args must be absolute paths.

```
(io/file-within-dir? (io/file "/temp/foo")
                     (io/file "/temp/foo/img.png"))
=> true

(io/file-within-dir? (io/file "/temp/foo")
                     (io/file "/temp/foo/../bar/img.png"))
=> false
```

SEE ALSO

[io/file](#)

Returns a java.io.File from file path, or from a parent path and one or multiple children. The path and parent may be a file or a string ...

io/file?

```
(io/file? f)
```

Returns true if x is a java.io.File.

```
(io/file? (io/file "/tmp/test.txt"))
=> true
```

io/filesystem-total-space

```
(io/filesystem-total-space)
(io/filesystem-total-space file)
```

Returns the total disk space in bytes. With no args returns the total disk space of the current working directory's file store. With a file argument returns the total disk space of the file store the file is located.

```
(io/filesystem-total-space)
```

SEE ALSO

[io/filesystem-usable-space](#)

Returns the usable disk space in bytes. With no args returns the usable disk space of the current working directory's file store. With ...

io/filesystem-usable-space

(io/filesystem-usable-space)
(io/filesystem-usable-space file)

Returns the usable disk space in bytes. With no args returns the usable disk space of the current working directory's file store. With a file argument returns the usable disk space of the file store the file is located.

(io/filesystem-usable-space)

SEE ALSO

[io/filesystem-total-space](#)

Returns the total disk space in bytes. With no args returns the total disk space of the current working directory's file store. With ...

top

io/flush

(io/flush s)

Flushes a :java.io.OutputStream or a :java.io.Writer .

SEE ALSO

[io/close](#)

Closes a :java.io.InputStream, :java.io.OutputStream, :java.io.Reader, or a :java.io.Writer.

top

io/glob-path-matcher

(io/glob-path-matcher pattern)

Returns a file matcher for glob file patterns.

Globbering patterns

*.txt	Matches a path that represents a file name ending in .txt
.	Matches file names containing a dot
*.{txt,xml}	Matches file names ending with .txt or .xml
foo.?[xy]	Matches file names starting with foo. and a single character extension followed by a 'x' or 'y' character
/home/*/*	Matches /home/gus/data on UNIX platforms
/home/**	Matches /home/gus and /home/gus/data on UNIX platforms
C:*	Matches C:\\foo and C:\\bar on the Windows platform

Ranges

The pattern [A-E] would match any character that included ABCDE. Ranges can be used in conjunction with each other to make powerful patterns. Alphanumerical strings are matched by [A-Za-z0-9] . This would match the following:

- [A-Z] All uppercase letters from A to Z

- `[a-z]` All lowercase letters from a to z
- `[0-9]` All numbers from 0 to 9

Complementation

Globs can be used in complement with special characters that can change how the pattern works. The two complement characters are exclamation marks `(!)` and backslashes `(\)`.

The exclamation mark can negate a pattern that it is put in front of. As `[CBR]at` matches Cat, Bat, or Rat the negated pattern `[!CBR]at` matches anything like Kat, Pat, or Vat.

Backslashes are used to remove the special meaning of single characters `'?'`, `'*'`, and `'['`, so that they can be used in patterns.

```
(io/glob-path-matcher "*.log")
```

```
(io/glob-path-matcher "**/*.log")
```

SEE ALSO

[io/file-matches-glob?](#)

Returns true if the file `f` matches the glob pattern. `f` must be a file or a string (file path).

[io/list-files-glob](#)

Lists all files in a directory that match the glob pattern. `dir` must be a file or a string (file path). Returns files as `java.io.File`

top

io/gzip

```
(io/gzip f)
```

`gzipt f`. `f` may be a file, a string (file path), a bytebuf or an `InputStream`. Returns a bytebuf.

```
(->> (io/gzip "a.txt")
      (io/spit "a.gz"))
```

```
(io/gzip (bytebuf-from-string "abcdef" :utf-8))
```

SEE ALSO

[io/gzip?](#)

Returns true if `f` is a gzipped file. `f` may be a file, a string (file path), a bytebuf, or an `InputStream`

[io/ungzip](#)

`ungzipt f`. `f` may be a file, a string (file path), a bytebuf, or an `InputStream`. Returns a bytebuf.

[io/zip](#)

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

[io/spit](#)

Opens file `f`, writes content, and then closes `f`. `f` may be a file or a string (file path). The content may be a string or a bytebuf.

top

io/gzip-to-stream

```
(io/gzip f os)
```


gzipt f to the OutputStream os. f may be a file, a string (file path), a bytebuf, or an InputStream.

```
(do
  (import :java.io.ByteArrayOutputStream)
  (try-with [os (. :ByteArrayOutputStream :new)]
    (-> (bytebuf-from-string "abcdef" :utf-8)
      (io/gzip-to-stream os))
    (-> (. os :toByteArray)
      (io/ungzip)
      (bytebuf-to-string :utf-8))))
=> "abcdef"
```

SEE ALSO

[io/gzip](#)

gzipt f. f may be a file, a string (file path), a bytebuf or an InputStream. Returns a bytebuf.

top

io/gzip?

```
(io/gzip? f)
```

Returns true if f is a gzipped file. f may be a file, a string (file path), a bytebuf, or an InputStream

```
(-> (io/gzip (bytebuf-from-string "abc" :utf-8))
  (io/gzip?))
=> true
```

SEE ALSO

[io/gzip](#)

gzipt f. f may be a file, a string (file path), a bytebuf or an InputStream. Returns a bytebuf.

top

io/in-stream?

```
(io/in-stream? is)
```

Returns true if 'is' is a `java.io.InputStream`

```
(try-with [is (io/string-in-stream "123")]
  (io/in-stream? is))
=> true
```

SEE ALSO

[io/out-stream?](#)

Returns true if 'os' is a `java.io.OutputStream`

top

io/inflate

```
(io/inflate bytebuf)
```

inflates (decompresses) a bytebuf using ZLIB compression.

```
(> (bytebuf-from-string "abcdef" :utf-8)
  (io/deflate)
  (io/inflate))
=> [97 98 99 100 101 102]
```

SEE ALSO

[io/deflate](#)

deflates (compresses) a bytebuf using ZLIB compression.

top

io/internet-avail?

```
(io/internet-avail?)
(io/internet-avail? url)
```

Checks if an internet connection is present for a given url. Defaults to URL *http://www.google.com*.

```
(io/internet-avail?)

(io/internet-avail? "http://www.google.com")
```

top

io/list-file-tree

```
(io/list-file-tree dir)
(io/list-file-tree dir filter-fn)
```

Lists all files in a directory tree. `dir` must be a file or a string (file path). `filter-fn` is an optional filter that filters the files found. The filter gets a `java.io.File` as argument.

Returns files as `java.io.File`

```
(io/list-file-tree "/tmp")

(io/list-file-tree "/tmp" #(io/file-ext? % ".log"))
```

SEE ALSO

[io/list-file-tree-lazy](#)

Returns a lazy sequence of all the files in a directory tree. `dir` must be a file or a string (file path). `filter-fn` is an optional ...

[io/list-files](#)

Lists files in a directory. `dir` must be a file or a string (file path). `filter-fn` is an optional filter that filters the files found.

[io/list-files-glob](#)

Lists all files in a directory that match the glob pattern. `dir` must be a file or a string (file path). Returns files as `java.io.File`

io/list-file-tree-lazy

```
(io/list-file-tree-lazy dir)
(io/list-file-tree-lazy dir filter-fn)
```

Returns a lazy sequence of all the files in a directory tree. `dir` must be a file or a string (file path). `filter-fn` is an optional filter that filters the files found. The filter gets a `java.io.File` as argument.

The lazy sequence returns files as `java.io.File`

```
(->> (io/list-file-tree-lazy "/tmp")
      (docoll println))

(->> (io/list-file-tree-lazy "/tmp" #(io/file-ext? % ".log"))
      (docoll println))
```

SEE ALSO

[io/list-file-tree](#)

Lists all files in a directory tree. `dir` must be a file or a string (file path). `filter-fn` is an optional filter that filters the files ...

[io/list-files](#)

Lists files in a directory. `dir` must be a file or a string (file path). `filter-fn` is an optional filter that filters the files found.

[io/list-files-glob](#)

Lists all files in a directory that match the glob pattern. `dir` must be a file or a string (file path). Returns files as `java.io.File`

io/list-files

```
(io/list-files dir)
(io/list-files dir filter-fn)
```

Lists files in a directory. `dir` must be a file or a string (file path). `filter-fn` is an optional filter that filters the files found. The filter gets a `java.io.File` as argument.

Returns files as `java.io.File`

```
(io/list-files "/tmp")

(io/list-files "/tmp" #(io/file-ext? % ".log"))
```

SEE ALSO

[io/list-files-glob](#)

Lists all files in a directory that match the glob pattern. `dir` must be a file or a string (file path). Returns files as `java.io.File`

[io/list-file-tree](#)

Lists all files in a directory tree. `dir` must be a file or a string (file path). `filter-fn` is an optional filter that filters the files ...

[io/list-file-tree-lazy](#)

Returns a lazy sequence of all the files in a directory tree. `dir` must be a file or a string (file path). `filter-fn` is an optional ...

io/list-files-glob

```
(io/list-files-glob dir glob)
```

Lists all files in a directory that match the glob pattern. dir must be a file or a string (file path). Returns files as `java.io.File`

Globbing patterns

<code>*.txt</code>	Matches a path that represents a file name ending in .txt
<code>*.*</code>	Matches file names containing a dot
<code>*.{txt,xml}</code>	Matches file names ending with .txt or .xml
<code>foo.?[xy]</code>	Matches file names starting with foo. and a single character extension followed by a 'x' or 'y' character
<code>/home/*/*</code>	Matches <code>/home/gus/data</code> on UNIX platforms
<code>/home/**</code>	Matches <code>/home/gus</code> and <code>/home/gus/data</code> on UNIX platforms
<code>C:*</code>	Matches <code>C:\\foo</code> and <code>C:\\bar</code> on the Windows platform

Ranges

The pattern `[A-E]` would match any character that included ABCDE. Ranges can be used in conjunction with each other to make powerful patterns. Alphanumerical strings are matched by `[A-Za-z0-9]`. This would match the following:

- `[A-Z]` All uppercase letters from A to Z
- `[a-z]` All lowercase letters from a to z
- `[0-9]` All numbers from 0 to 9

Complementation

Globs can be used in complement with special characters that can change how the pattern works. The two complement characters are exclamation marks `(!)` and backslashes `(\\)`.

The exclamation mark can negate a pattern that it is put in front of. As `[CBR]at` matches Cat, Bat, or Rat the negated pattern `[!CBR]at` matches anything like Kat, Pat, or Vat.

Backslashes are used to remove the special meaning of single characters `'?'`, `'*'`, and `'['`, so that they can be used in patterns.

```
(io/list-files-glob "." "sample*.txt")
```

SEE ALSO

[io/list-files](#)

Lists files in a directory. dir must be a file or a string (file path). filter-fn is an optional filter that filters the files found.

[io/list-file-tree](#)

Lists all files in a directory tree. dir must be a file or a string (file path). filter-fn is an optional filter that filters the files ...

[io/list-file-tree-lazy](#)

Returns a lazy sequence of all the files in a directory tree. dir must be a file or a string (file path). filter-fn is an optional ...

[top](#)

io/load-classpath-resource

```
(io/load-classpath-resource name)
```

Loads a classpath resource. Returns a bytebuf

```
(io/load-classpath-resource "com/github/jlangch/venice/images/venice.png")
=> [137 80 78 71 13 10 26 10 0 0 0 13 73 72 68 82 0 0 3 254 0 0 0 242 8 6 0 0 0 244 182 30 43 0 0 12 70 105 67
67 80 73 67 67 32 80 114 111 102 105 108 101 0 0 72 137 149 87 7 88 83 201 22 158 91 82 73 104 129 8 72 9 189
137 82 164 75 9 161 69 16 144 42 216 8 73 32 161 196 144 16 68 236 46 203 42 184 118 17 1 ...]
```

SEE ALSO

[io/classpath-resource?](#)

Returns true if the classpath resource exists otherwise false.

top

io/mime-type

```
(io/mime-type file)
```

Returns the mime-type for the file if available else nil.

```
(io/mime-type "document.pdf")
=> "application/pdf"

(io/mime-type (io/file "document.pdf"))
=> "application/pdf"
```

top

io/mkdir

```
(io/mkdir dir)
```

Creates the directory. dir must be a file or a string (file path).

SEE ALSO

[io/mkdirs](#)

Creates the directory including any necessary but nonexistent parent directories. dir must be a file or a string (file path).

top

io/mkdirs

```
(io/mkdirs dir)
```

Creates the directory including any necessary but nonexistent parent directories. dir must be a file or a string (file path).

SEE ALSO

[io/mkdir](#)

Creates the directory. dir must be a file or a string (file path).

top

io/move-file

```
(io/move-file source target & options)
```

Moves source to target. Returns nil or throws a VncException. Source and target must be a file or a string (file path).

Options:

:replace true/false e.g.: if true replace an existing file, defaults to false
:atomic-move true/false e.g.: if true move the file as an atomic file system operation, defaults to false

SEE ALSO

[io/copy-file](#)

Copies source to dest. Returns nil or throws a VncException. Source must be a file or a string (file path), dest must be a file, a ...

[io/delete-file](#)

Deletes one or multiple files. Silently skips delete if the file does not exist. If f is a directory the directory must be empty. f ...

[io/touch-file](#)

Updates the lastModifiedTime of the file to the current time, or creates a new empty file if the file doesn't already exist. File must ...

[top](#)

io/move-files-glob

```
(io/move-files-glob src-dir dst-dir glob & options)
```

Move all files that match the glob pattern from a source to a destination directory. src-dir and dst-dir must be a file or a string (file path).

Options:

:replace true/false e.g.: if true replace an existing file, defaults to false
:atomic-move true/false e.g.: if true move the file as an atomic file system operation, defaults to false

Globbing patterns

<code>*.txt</code>	Matches a path that represents a file name ending in .txt
<code>*.*</code>	Matches file names containing a dot
<code>*.{txt,xml}</code>	Matches file names ending with .txt or .xml
<code>foo.?[xy]</code>	Matches file names starting with foo. and a single character extension followed by a 'x' or 'y' character
<code>/home/*/*</code>	Matches <code>/home/gus/data</code> on UNIX platforms
<code>/home/**</code>	Matches <code>/home/gus</code> and <code>/home/gus/data</code> on UNIX platforms
<code>C:*</code>	Matches <code>C:\\foo</code> and <code>C:\\bar</code> on the Windows platform

Ranges

The pattern `[A-E]` would match any character that included ABCDE. Ranges can be used in conjunction with each other to make powerful patterns. Alphanumerical strings are matched by `[A-Za-z0-9]`. This would match the following:

- `[A-Z]` All uppercase letters from A to Z
- `[a-z]` All lowercase letters from a to z
- `[0-9]` All numbers from 0 to 9

Complementation

Globs can be used in complement with special characters that can change how the pattern works. The two complement characters are exclamation marks `(!)` and backslashes `(\\)`.

The exclamation mark can negate a pattern that it is put in front of. As `[CBR]at` matches Cat, Bat, or Rat the negated pattern `[!CBR]at` matches anything like Kat, Pat, or Vat.

Backslashes are used to remove the special meaning of single characters `'?'`, `'*'`, and `'['`, so that they can be used in patterns.

```
(io/move-files-glob "from" "to" "*.log")
```

SEE ALSO

[io/move-file](#)

Moves source to target. Returns nil or throws a VncException. Source and target must be a file or a string (file path).

[io/move-files-glob](#)

Move all files that match the glob pattern from a source to a destination directory. src-dir and dst-dir must be a file or a string (file path).

[io/copy-files-glob](#)

Copies all files that match the glob pattern from a source to a destination directory. src-dir and dst-dir must be a file or a string ...

[io/delete-files-glob](#)

Removes all files in a directory that match the glob pattern. dir must be a file or a string (file path).

[io/list-files-glob](#)

Lists all files in a directory that match the glob pattern. dir must be a file or a string (file path). Returns files as java.io.File

top

io/out-stream?

```
(io/out-stream? os)
```

Returns true if 'os' is a `java.io.OutputStream`

```
(try-with [os (io/bytebuf-out-stream)]
  (io/out-stream? os))
=> true
```

SEE ALSO

[io/in-stream?](#)

Returns true if 'is' is a java.io.InputStream

top

io/print

```
(io/print os s)
```

Prints a string s to an output stream. The output stream may be a `:java.io.Writer` or a `:java.io.PrintStream`!

top

io/print-line

```
(io/print-line os)
```

```
(io/print-line os s)
```

Prints a string `s` to an output stream. The output stream may be a `:java.io.Writer` or a `:java.io.PrintStream` !

[top](#)

io/read-char

```
(io/read-char is)
```

With `arg` reads the next char from the passed stream that must be a subclass of `:java.io.Reader` .

Returns `nil` if the end of the stream is reached.

SEE ALSO

[io/read-line](#)

Reads the next line from the passed stream that must be a subclass of `:java.io.BufferedReader`.

[top](#)

io/read-line

```
(io/read-line is)
```

Reads the next line from the passed stream that must be a subclass of `:java.io.BufferedReader` .

Returns `nil` if the end of the stream is reached.

SEE ALSO

[io/read-char](#)

With `arg` reads the next char from the passed stream that must be a subclass of `:java.io.Reader`.

[top](#)

io/reader?

```
(io/reader? rd)
```

Returns true if 'rd' is a `:java.io.Reader`

```
(try-with [rd (io/string-reader "123")]  
  (io/reader? rd))  
=> true
```

SEE ALSO

[io/writer?](#)

Returns true if 'rd' is a `:java.io.Writer`

[top](#)

io/slurp

(io/slurp f & options)

Reads the content of file f as text (string) or binary (bytebuf).

f may be a:

- string file path, e.g: "/temp/foo.json"
- bytebuffer
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.InputStream`
- `java.io.Reader`
- `java.nio.file.Path`
- `java.net.URL`
- `java.net.URI`

Returns a `bytebuf` or string depending on the passed `:binary` option.

Options:

`:binary true/false` e.g.: `:binary true`, defaults to false

`:encoding enc` e.g.: `:encoding :utf-8`, defaults to `:utf-8`

`io/slurp` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

Note: For HTTP and HTTPS downloads prefer to use `io/download`.

SEE ALSO

[io/slurp-lines](#)

Read all lines from f.

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` is. Supports the option `:binary` to either slurp binary or string data. For ...

[io/slurp-reader](#)

Slurps string data from a `java.io.Reader` rd. Note:

[io/spit](#)

Opens file f, writes content, and then closes f. f may be a file or a string (file path). The content may be a string or a bytebuf.

[io/download](#)

Downloads the content from the uri and reads it as text (string) or binary (bytebuf). Supports http and https protocols!

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

top

io/slurp-lines

(io/slurp-lines f & options)

Read all lines from f.

f may be a:

- string file path, e.g: "/temp/foo.json"

- `bytebuffer`
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.io.InputStream`
- `java.io.Reader`
- `java.nio.file.Path`
- `java.net.URL`
- `java.net.URI`

Returns the a list of strings.

Options:

`:encoding enc` e.g.: `:encoding :utf-8`, defaults to `:utf-8`

`io/slurp-lines` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

```
(->> "1\n2\n3"
      io/string-in-stream
      io/slurp-lines)
=> ("1" "2" "3")
```

SEE ALSO

[str/split-lines](#)

Splits `s` into lines.

[io/slurp](#)

Reads the content of file `f` as text (string) or binary (bytebuf).

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` `is`. Supports the option `:binary` to either slurp binary or string data. For ...

[io/spit](#)

Opens file `f`, writes content, and then closes `f`. `f` may be a file or a string (file path). The content may be a string or a bytebuf.

[io/string-in-stream](#)

Returns a `java.io.InputStream` for the string `s`.

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

[top](#)

io/slurp-reader

```
(io/slurp-reader rd)
```

Slurps string data from a `java.io.Reader` `rd`. Note:

`io/slurp-reader` offers the same functionality as `io/slurp` but it opens more flexibility with sandbox configuration. `io/slurp` can be blacklisted to prevent reading data from the filesystem and still having `io/slurp-reader` for readers input available!

```
(do
  (let [file (io/temp-file "test-", ".txt")]
    (io/delete-file-on-exit file)
    (io/spit file "123456789" :append true)
    (try-with [rd (io/buffered-reader file :encoding :utf-8)]
      (io/slurp-reader rd)))
  )
=> "123456789"
```

SEE ALSO

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` is. Supports the option `:binary` to either slurp binary or string data. For ...

[io/slurp](#)

Reads the content of file `f` as text (string) or binary (bytebuf).

[io/slurp-lines](#)

Read all lines from `f`.

[io/spit](#)

Opens file `f`, writes content, and then closes `f`. `f` may be a file or a string (file path). The content may be a string or a bytebuf.

[io/uri-stream](#)

Returns a `java.io.InputStream` from the uri.

[io/file-in-stream](#)

Returns a `java.io.InputStream` for the file `f`.

[io/string-in-stream](#)

Returns a `java.io.InputStream` for the string `s`.

[io/bytebuf-in-stream](#)

Returns a `java.io.InputStream` from a bytebuf.

[top](#)

io/slurp-stream

(`io/slurp-stream is & options`)

Slurps binary or string data from a `java.io.InputStream` is. Supports the option `:binary` to either slurp binary or string data. For string data an optional encoding can be specified.

Returns the result as a `bytebuf` or string depending on the passed `:binary` option.

Options:

`:binary true/false` e.g.: `:binary true`, defaults to false

`:encoding enc` e.g.: `:encoding :utf-8`, defaults to `:utf-8`

Note:

`io/slurp-stream` offers the same functionality as `io/slurp` but it opens more flexibility with sandbox configuration. `io/slurp` can be blacklisted to prevent reading data from the filesystem and still having `io/slurp-stream` for stream input available!

```
(do
  (let [file (io/temp-file "test-", ".txt")]
    (io/delete-file-on-exit file)
    (io/spit file "123456789" :append true)
    (try-with [is (io/file-in-stream file)]
      (io/slurp-stream is :binary false)))
  )
=> "123456789"
```

SEE ALSO

[io/slurp-reader](#)

Slurps string data from a `java.io.Reader` `rd`. Note:

[io/slurp](#)

Reads the content of file `f` as text (string) or binary (bytebuf).

[io/slurp-lines](#)

Read all lines from `f`.

[io/spit](#)

Opens file `f`, writes content, and then closes `f`. `f` may be a file or a string (file path). The content may be a string or a bytebuf.

[io/uri-stream](#)

Returns a `java.io.InputStream` from the uri.

[io/file-in-stream](#)

Returns a `java.io.InputStream` for the file `f`.

[io/string-in-stream](#)

Returns a `java.io.InputStream` for the string `s`.

[io/bytebuf-in-stream](#)

Returns a `java.io.InputStream` from a bytebuf.

[top](#)

io/spit

`(io/spit f content & options)`

Opens file `f`, writes content, and then closes `f`. `f` may be a file or a string (file path). The content may be a string or a bytebuf.

Options:

`:append true/false` e.g.: `:append true`, defaults to false

`:encoding enc` e.g.: `:encoding :utf-8`, defaults to `:utf-8`

`io/spit` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

SEE ALSO

[io/spit-stream](#)

Writes content (string or bytebuf) to the `java.io.OutputStream` `os`. If content is of type string an optional encoding (defaults to UTF-8) ...

[io/spit-writer](#)

Writes text to the `java.io.Writer` `wr`. The writer can optionally be flushed after the operation.

[io/slurp](#)

Reads the content of file `f` as text (string) or binary (bytebuf).

[io/slurp-lines](#)

Read all lines from `f`.

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

[top](#)

io/spit-stream

`(io/spit-stream os content & options)`

Writes content (string or bytebuf) to the `java.io.OutputStream` `os`. If content is of type string an optional encoding (defaults to UTF-8) is supported. The stream can optionally be flushed after the operation.

Options:

`:flush true/false` e.g.: `:flush true`, defaults to false

e.g.: :encoding :utf-8, defaults to :utf-8

:encoding enc

Note:

`io/spit-stream` offers the same functionality as `io/spit` but it opens more flexibility with sandbox configuration. `io/spit` can be blacklisted to prevent writing data to the filesystem and still having `io/spit-stream` for stream output available!

```
(do
  (let [file (io/temp-file "test-", ".txt")]
    (io/delete-file-on-exit file)
    (try-with [os (io/file-out-stream file)]
      (io/spit-stream os "123456789" :flush true))))
=> nil
```

SEE ALSO

[io/spit-writer](#)

Writes text to the `java.io.Writer` `wr`. The writer can optionally be flushed after the operation.

[io/spit](#)

Opens file `f`, writes content, and then closes `f`. `f` may be a file or a string (file path). The content may be a string or a `bytebuf`.

top

io/spit-writer

```
(io/spit-writer wr text)
```

Writes text to the `java.io.Writer` `wr`. The writer can optionally be flushed after the operation.

Options:

:flush true/false e.g.: :flush true, defaults to false

Note:

`io/spit-writer` offers the same functionality as `io/spit` but it opens more flexibility with sandbox configuration. `io/spit` can be blacklisted to prevent writing data to the filesystem and still having `io/spit-writer` for stream output available!

```
(do
  (let [file (io/temp-file "test-", ".txt")
        os (io/file-out-stream file)]
    (io/delete-file-on-exit file)
    (try-with [wr (io/buffered-writer os :encoding :utf-8)]
      (io/spit-writer wr "123456789" :flush true))))
=> nil
```

SEE ALSO

[io/spit-stream](#)

Writes content (string or `bytebuf`) to the `java.io.OutputStream` `os`. If content is of type string an optional encoding (defaults to UTF-8) ...

[io/spit](#)

Opens file `f`, writes content, and then closes `f`. `f` may be a file or a string (file path). The content may be a string or a `bytebuf`.

top

io/string-in-stream

```
(io/string-in-stream s & options)
```

Returns a `java.io.InputStream` for the string `s`.

Options:

:encoding `enc` e.g.: `:encoding :utf-8`, defaults to `:utf-8`

Note: The caller is responsible for closing the stream!

```
(let [text "The quick brown fox jumped over the lazy dog"]
  (try-with [is (io/string-in-stream text)]
    ; do something with is
  ))
```

SEE ALSO

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` `is`. Supports the option `:binary` to either slurp binary or string data. For ...

[io/file-in-stream](#)

Returns a `java.io.InputStream` for the file `f`.

[io/bytebuf-in-stream](#)

Returns a `java.io.InputStream` from a `bytebuf`.

[top](#)

io/string-reader

```
(io/string-reader s)
```

Creates a `java.io.StringReader` from a string.

Note: The caller is responsible for closing the reader!

```
(try-with [rd (io/string-reader "1234")]
  (println (read-char rd))
  (println (read-char rd))
  (println (read-char rd)))
```

```
1
2
3
=> nil
```

```
(let [rd (io/string-reader "1\n2\n3\n4")]
  (try-with [br (io/buffered-reader rd)]
    (println (read-line br))
    (println (read-line br))
    (println (read-line br))))
```

```
1
2
3
=> nil
```

SEE ALSO

[read-line](#)

Without `arg` reads the next line from the stream that is the current value of `*in*`. With `arg` reads the next line from the passed stream ...

[io/buffered-reader](#)

Create a `java.io.Reader` from `f`.

[io/string-writer](#)

Creates a `java.io.StringWriter`.

[top](#)

io/string-writer

(`io/string-writer`)

Creates a `java.io.StringWriter` .

Dereferencing a string writer returns the captured string.

Note: The caller is responsible for closing the writer!

```
(try-with [sw (io/string-writer)])
  (print sw 100)
  (print sw "-")
  (print sw 200)
  (flush sw)
  (println @sw))
100-200
=> nil
```

SEE ALSO

[println](#)

Prints the values `xs` to the stream that is the current value of `*out*` or to the passed output stream `os` if given followed by a (newline).

[io/buffered-writer](#)

Creates a `java.io.Writer` for `f`.

[io/buffered-reader](#)

Create a `java.io.Reader` from `f`.

[top](#)

io/symbolic-link?

(`io/symbolic-link?` `f`)

Returns true if the file `f` exists and is a symbolic link. `f` must be a file or a string (file path).

```
(io/symbolic-link? "/tmp/test.txt")
```

SEE ALSO

[io/file-hidden?](#)

Returns true if the file or directory `f` exists and is hidden. `f` must be a file or a string (file path).

[io/file-can-read?](#)

Returns true if the file or directory `f` exists and can be read. `f` must be a file or a string (file path).

[io/file-can-write?](#)

Returns true if the file or directory `f` exists and can be written. `f` must be a file or a string (file path).

[io/file-can-execute?](#)

Returns true if the file or directory `f` exists and can be executed. `f` must be a file or a string (file path).

top

io/temp-dir

(io/temp-dir prefix)

Creates a new temp directory with prefix. Returns a `:java.io.File`.

```
(io/temp-dir "test-")  
=> /var/folders/q0/gg9f6pqx5079cfvp9g5lqbzh0000gn/T/test-121651478767830494
```

SEE ALSO

[io/tmp-dir](#)

Returns the tmp dir as a `java.io.File`.

[io/temp-file](#)

Creates an empty temp file with the given prefix and suffix. Returns a `:java.io.File`.

top

io/temp-file

(io/temp-file prefix suffix)

Creates an empty temp file with the given prefix and suffix. Returns a `:java.io.File`.

```
(do  
  (let [file (io/temp-file "test-", ".txt")]  
    (io/spit file "123456789" :append true)  
    (io/slurp file :binary false :remove true))  
)  
=> "123456789"
```

SEE ALSO

[io/temp-dir](#)

Creates a new temp directory with prefix. Returns a `:java.io.File`.

[io/delete-file-on-exit](#)

Requests that the files or directories be deleted when the virtual machine terminates. Files (or directories) are deleted in the reverse ...

top

io/tmp-dir

(io/tmp-dir)

Returns the tmp dir as a `java.io.File`.


```
(io/tmp-dir)
=> /var/folders/q0/gg9f6pqx5079cfvp9g5lqbzh0000gn/T
```

SEE ALSO

[io/user-dir](#)

Returns the user dir (current working dir) as a java.io.File.

[io/user-home-dir](#)

Returns the user's home dir as a java.io.File.

[io/temp-dir](#)

Creates a new temp directory with prefix. Returns a :java.io.File.

[top](#)

io/touch-file

```
(io/touch-file file)
```

Updates the *lastModifiedTime* of the file to the current time, or creates a new empty file if the file doesn't already exist. File must be a file or a string (file path). Returns the file

SEE ALSO

[io/move-file](#)

Moves source to target. Returns nil or throws a VncException. Source and target must be a file or a string (file path).

[io/copy-file](#)

Copies source to dest. Returns nil or throws a VncException. Source must be a file or a string (file path), dest must be a file, a ...

[io/delete-file](#)

Deletes one or multiple files. Silently skips delete if the file does not exist. If f is a directory the directory must be empty. f ...

[top](#)

io/ungzip

```
(io/ungzip f)
```

ungzips f. f may be a file, a string (file path), a bytebuf, or an InputStream. Returns a bytebuf.

```
(-> (bytebuf-from-string "abcdef" :utf-8)
  (io/gzip)
  (io/ungzip))
=> [97 98 99 100 101 102]
```

SEE ALSO

[io/gzip](#)

gzips f. f may be a file, a string (file path), a bytebuf or an InputStream. Returns a bytebuf.

[io/gzip?](#)

Returns true if f is a gzipped file. f may be a file, a string (file path), a bytebuf, or an InputStream

[io/ungzip-to-stream](#)

ungzips a bytebuf returning an InputStream to read the deflated data from.

io/ungzip-to-stream

```
(io/ungzip-to-stream buf)
```

ungzips a bytebuf returning an InputStream to read the deflated data from.

```
(-> (bytebuf-from-string "abcdef" :utf-8)
     (io/gzip)
     (io/ungzip-to-stream)
     (io/slurp-stream :binary false :encoding :utf-8))
=> "abcdef"
```

SEE ALSO

[io/gzip](#)

gzips f. f may be a file, a string (file path), a bytebuf or an InputStream. Returns a bytebuf.

io/unzip

```
(io/unzip f entry-name)
```

Unzips an entry from zip f the entry's data as a bytebuf. f may be a bytebuf, a file, a string (file path) or an InputStream.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abcdef" :utf-8))
     (io/unzip "a.txt"))
=> [97 98 99 100 101 102]
```

SEE ALSO

[io/zip](#)

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

[io/zip?](#)

Returns true if f is a zipped file. f may be a file, a string (file path), a bytebuf, or an InputStream

io/unzip-all

```
(io/unzip-all f)
(io/unzip-all glob f)
```

Unzips all entries of the zip f returning a map with the entry names as key and the entry data as bytebuf values. f may be a bytebuf, a file, a string (file path) or an InputStream.

An optional globbing pattern can be passed to filter the files to be unzipped.

Note: globbing patterns with unzip are always relative. E.g. `static/**/*.png`

Globbing patterns:

`*.txt` Matches a path that represents a file name ending in .txt

<code>*.*</code>	Matches file names containing a dot
<code>*.{txt,xml}</code>	Matches file names ending with .txt or .xml
<code>foo.?</code>	Matches file names starting with foo. and a single character extension
<code>/home/*/*</code>	Matches <code>/home/gus/data</code> on UNIX platforms
<code>/home/**</code>	Matches <code>/home/gus</code> and <code>/home/gus/data</code> on UNIX platforms
<code>C:*</code>	Matches <code>C:\\foo</code> and <code>C:\\bar</code> on the Windows platform

```
(-> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
      "b.txt" (bytebuf-from-string "def" :utf-8)
      "c.txt" (bytebuf-from-string "ghi" :utf-8))
  (io/unzip-all))
=> {"a.txt" [97 98 99] "b.txt" [100 101 102] "c.txt" [103 104 105]}
```

```
(->> (io/zip "foo/a.txt" (bytebuf-from-string "abc" :utf-8)
      "bar/b.txt" (bytebuf-from-string "def" :utf-8)
      "bar/c.log" (bytebuf-from-string "ghi" :utf-8))
  (io/unzip-all "bar/*.txt"))
=> {"bar/b.txt" [100 101 102]}
```

SEE ALSO

[io/unzip-to-dir](#)

Unzips the zip `f` to a directory. `f` may be a file, a string (file path), a bytebuf, or an InputStream.

[io/unzip-nth](#)

Unzips the `nth` (zero.based) entry of the zip `f` returning its data as a bytebuf. `f` may be a bytebuf, a file, a string (file path) or ...

[io/unzip-first](#)

Unzips the first entry of the zip `f` returning its data as a bytebuf. `f` may be a bytebuf, a file, a string (file path) or an InputStream.

[io/zip](#)

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

[io/zip?](#)

Returns true if `f` is a zipped file. `f` may be a file, a string (file path), a bytebuf, or an InputStream

top

io/unzip-first

```
(io/unzip-first zip)
```

Unzips the first entry of the zip `f` returning its data as a bytebuf. `f` may be a bytebuf, a file, a string (file path) or an InputStream.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
      "b.txt" (bytebuf-from-string "def" :utf-8))
  (io/unzip-first))
=> [97 98 99]
```

SEE ALSO

[io/unzip-to-dir](#)

Unzips the zip `f` to a directory. `f` may be a file, a string (file path), a bytebuf, or an InputStream.

[io/unzip-nth](#)

Unzips the `nth` (zero.based) entry of the zip `f` returning its data as a bytebuf. `f` may be a bytebuf, a file, a string (file path) or ...

[io/unzip-all](#)

Unzips all entries of the zip `f` returning a map with the entry names as key and the entry data as bytebuf values. `f` may be a bytebuf, ...

[io/zip](#)

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

[io/zip?](#)

Returns true if f is a zipped file. f may be a file, a string (file path), a bytebuf, or an InputStream

[top](#)

io/unzip-nth

```
(io/unzip-nth zip n)
```

Unzips the nth (zero.based) entry of the zip f returning its data as a bytebuf. f may be a bytebuf, a file, a string (file path) or an InputStream.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
          "b.txt" (bytebuf-from-string "def" :utf-8)
          "c.txt" (bytebuf-from-string "ghi" :utf-8))
    (io/unzip-nth 1))
=> [100 101 102]
```

SEE ALSO

[io/unzip-to-dir](#)

Unzips the zip f to a directory. f may be a file, a string (file path), a bytebuf, or an InputStream.

[io/unzip-first](#)

Unzips the first entry of the zip f returning its data as a bytebuf. f may be a bytebuf, a file, a string (file path) or an InputStream.

[io/unzip-all](#)

Unzips all entries of the zip f returning a map with the entry names as key and the entry data as bytebuf values. f may be a bytebuf, ...

[io/zip](#)

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

[io/zip?](#)

Returns true if f is a zipped file. f may be a file, a string (file path), a bytebuf, or an InputStream

[top](#)

io/unzip-to-dir

```
(io/unzip-to-dir f dir)
```

Unzips the zip f to a directory. f may be a file, a string (file path), a bytebuf, or an InputStream.

```
(-> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)
          "b.txt" (bytebuf-from-string "def" :utf-8)
          "c.txt" (bytebuf-from-string "ghi" :utf-8))
    (io/unzip-to-dir "."))
```

SEE ALSO

[io/unzip](#)

Unzips an entry from zip f the entry's data as a bytebuf. f may be a bytebuf, a file, a string (file path) or an InputStream.

[io/unzip-nth](#)

Unzips the nth (zero.based) entry of the zip f returning its data as a bytebuf. f may be a bytebuf, a file, a string (file path) or ...

[io/unzip-first](#)

Unzips the first entry of the zip `f` returning its data as a bytebuf. `f` may be a bytebuf, a file, a string (file path) or an `InputStream`.

[io/unzip-all](#)

Unzips all entries of the zip `f` returning a map with the entry names as key and the entry data as bytebuf values. `f` may be a bytebuf, ...

[io/zip](#)

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

[io/zip?](#)

Returns true if `f` is a zipped file. `f` may be a file, a string (file path), a bytebuf, or an `InputStream`

[top](#)

io/uri-stream

```
(io/uri-stream uri)
```

Returns a `java.io.InputStream` from the uri.

Note: The caller is responsible for closing the stream!

```
(let [url "https://www.w3schools.com/xml/books.xml"]
  (try-with [is (io/uri-stream url)]
    (io/slurp-stream is :binary false :encoding :utf-8)))
```

SEE ALSO

[io/slurp-stream](#)

Slurps binary or string data from a `java.io.InputStream` `is`. Supports the option `:binary` to either slurp binary or string data. For ...

[top](#)

io/user-dir

```
(io/user-dir)
```

Returns the user dir (current working dir) as a `java.io.File`.

SEE ALSO

[io/tmp-dir](#)

Returns the tmp dir as a `java.io.File`.

[io/user-home-dir](#)

Returns the user's home dir as a `java.io.File`.

[top](#)

io/user-home-dir

```
(io/user-home-dir)
```

Returns the user's home dir as a `java.io.File`.

SEE ALSO

[user-name](#)

Returns the logged-in's user name.

[io/user-dir](#)

Returns the user dir (current working dir) as a `java.io.File`.

[io/tmp-dir](#)

Returns the tmp dir as a `java.io.File`.

[top](#)

io/watch-dir

```
(io/watch-dir dir event-fn)
(io/watch-dir dir event-fn failure-fn)
(io/watch-dir dir event-fn failure-fn termination-fn)
```

Watch a directory for changes, and call the function `event-fn` when it does. Calls the optional `failure-fn` if errors occur. On closing the watcher `termination-fn` is called.

`event-fn` is a two argument function that receives the path and mode `{:created, :deleted, :modified}` of the changed file.

`failure-fn` is a two argument function that receives the watch dir and the failure exception.

`termination-fn` is a one argument function that receives the watch dir.

Returns a *watcher* that is actively watching a directory. The *watcher* is a resource which should be closed with `(io/close-watcher w)`.

```
(do
  (defn log [msg] (locking log (println msg)))

  (let [w (io/watch-dir "/tmp"
                        #(log (str %1 " " %2))
                        (sleep 30 :seconds)
                        (io/close-watcher w)))]

    (do
      (defn log [msg] (locking log (println msg)))

      (let [w (io/watch-dir "/tmp"
                            #(log (str %1 " " %2))
                            #(log (str "failure " (:message %2)))
                            #(log (str "terminated watching " %1)))]

        (sleep 30 :seconds)
        (io/close-watcher w))))
```

SEE ALSO

[io/close-watcher](#)

Closes a watcher created from 'io/watch-dir'.

[io/await-for](#)

Blocks the current thread until the file has been created, deleted, or modified according to the passed modes `{:created, :deleted, ...`

[top](#)

io/wrap-is-with-buffered-reader

```
(io/wrap-is-with-buffered-reader is encoding?)
```

Wraps an `java.io.InputStream` `is` with a `java.io.BufferedReader` using an optional encoding (defaults to `:utf-8`).

Note: The caller is responsible for closing the reader!

```
(let [data (bytebuf [108 105 110 101 32 49 10 108 105 110 101 32 50])]
  (try-with [is (io/bytebuf-in-stream data)
             rd (io/wrap-is-with-buffered-reader is :utf-8)]
    (println (read-line rd))
    (println (read-line rd))))
line 1
line 2
=> nil
```

SEE ALSO

[io/buffered-reader](#)

Create a `java.io.Reader` from `f`.

top

io/wrap-is-with-gzip-input-stream

```
(io/wrap-is-with-gzip-input-stream is)
```

Wraps a `:java.io.InputStream` `is` with a `:java.io.GZIPInputStream` to read compressed data in the GZIP format.

Note: The caller is responsible for closing the reader!

```
(let [text      "hello, hello, hello"
      gzip-buf  (-> (bytebuf-from-string text :utf-8)
                    (io/gzip))]
  (try-with [is (-> (io/bytebuf-in-stream gzip-buf)
                  (io/wrap-is-with-gzip-input-stream))]
    (-> (io/slurp is :binary true)
        (bytebuf-to-string :utf-8))))
=> "hello, hello, hello"
```

SEE ALSO

[io/wrap-os-with-gzip-output-stream](#)

Wraps a `java.io.OutputStream` `is` with a `java.io.GZIPOutputStream` to write compressed data in the GZIP format.

top

io/wrap-is-with-inflater-input-stream

```
(io/wrap-is-with-inflater-input-stream is)
```

Wraps a `:java.io.InputStream` `is` with a `:java.io.InflaterInputStream` to read compressed data in the 'zlib' format.

Note: The caller is responsible for closing the reader!

```
(let [text      "hello, hello, hello"
      zlib-buf  (-> (bytebuf-from-string text :utf-8)
                    (io/deflate))]
  (try-with [is (-> (io/bytebuf-in-stream zlib-buf)
                  (io/wrap-is-with-inflater-input-stream))]
    (-> (io/slurp is :binary true)
        (bytebuf-to-string :utf-8))))
```

```
(try-with [is (-> (io/bytebuf-in-stream zlib-buf)
                  (io/wrap-is-with-inflater-input-stream))]
  (-> (io/slurp is :binary true)
      (bytebuf-to-string :utf-8))))
=> "hello, hello, hello"
```

SEE ALSO

[io/wrap-os-with-deflater-output-stream](#)

Wraps a `java.io.OutputStream` is with a `java.io.DeflaterOutputStream` to write compressed data in the 'zlib' format.

[top](#)

io/wrap-os-with-buffered-writer

```
(io/wrap-os-with-buffered-writer os encoding?)
```

Wraps a `java.io.OutputStream` `os` with a `java.io.BufferedWriter` using an optional encoding (defaults to `:utf-8`).

Note: The caller is responsible for closing the writer!

```
(try-with [os (io/bytebuf-out-stream)
            wr (io/wrap-os-with-buffered-writer os :utf-8)]
  (println wr "100")
  (println wr "200")
  (flush wr)
  (bytebuf-to-string @os :utf-8))
=> "100\n200\n"
```

SEE ALSO

[io/wrap-os-with-print-writer](#)

Wraps an `java.io.OutputStream` `os` with a `java.io.PrintWriter` using an optional encoding (defaults to `:utf-8`).

[top](#)

io/wrap-os-with-deflater-output-stream

```
(io/wrap-os-with-deflater-output-stream is)
```

Wraps a `java.io.OutputStream` `is` with a `java.io.DeflaterOutputStream` to write compressed data in the 'zlib' format.

Note: The caller is responsible for closing the reader!

```
(let [text "hello, hello, hello"
      bos (io/bytebuf-out-stream)]
  (try-with [gos (io/wrap-os-with-deflater-output-stream bos)]
    (io/spit gos text :encoding :utf-8)
    (io/flush gos)
    (io/close gos)
    (-> (io/inflate @bos)
        (bytebuf-to-string :utf-8))))
=> "hello, hello, hello"
```

SEE ALSO

[io/wrap-is-with-inflater-input-stream](#)

Wraps a `:java.io.InputStream` is with a `:java.io.InflaterInputStream` to read compressed data in the 'zlib' format.

top

io/wrap-os-with-gzip-output-stream

(io/wrap-os-with-gzip-output-stream is)

Wraps a `:java.io.OutputStream` is with a `:java.io.GZIPOutputStream` to write compressed data in the GZIP format.

Note: The caller is responsible for closing the reader!

```
(let [text "hello, hello, hello"
      bos (io/bytebuf-out-stream)]
  (try-with [gos (io/wrap-os-with-gzip-output-stream bos)]
    (io/spit gos text :encoding :utf-8)
    (io/flush gos)
    (io/close gos)
    (-> (io/ungzip @bos)
        (bytebuf-to-string :utf-8))))
=> "hello, hello, hello"
```

SEE ALSO

[io/wrap-is-with-gzip-input-stream](#)

Wraps a `:java.io.InputStream` is with a `:java.io.GZIPInputStream` to read compressed data in the GZIP format.

top

io/wrap-os-with-print-writer

(io/wrap-os-with-print-writer os encoding?)

Wraps an `java.io.OutputStream` os with a `java.io.PrintWriter` using an optional encoding (defaults to :utf-8).

Note: The caller is responsible for closing the writer!

```
(let [os (io/bytebuf-out-stream)]
  (try-with [pr (io/wrap-os-with-print-writer os :utf-8)]
    (println pr "line 1")
    (println pr "line 2")
    (flush pr)
    @os))
=> [108 105 110 101 32 49 10 108 105 110 101 32 50 10]
```

SEE ALSO

[io/wrap-os-with-buffered-writer](#)

Wraps a `java.io.OutputStream` os with a `java.io.BufferedWriter` using an optional encoding (defaults to :utf-8).

top

io/writer?

```
(io/writer? rd)
```

Returns true if 'rd' is a `java.io.Writer`

```
(try-with [wr (io/string-writer)]  
  (io/writer? wr))  
=> true
```

SEE ALSO

[io/reader?](#)

Returns true if 'rd' is a `java.io.Reader`

[top](#)

io/zip

```
(io/zip & entries)
```

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string (file path), or an InputStream.

An entry name with a trailing '/' creates a directory. Returns the zip as bytebuf.

```
; single entry  
(->> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8))  
      (io/spit "test.zip"))  
  
; multiple entries  
(->> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)  
          "b.txt" (bytebuf-from-string "def" :utf-8)  
          "c.txt" (bytebuf-from-string "ghi" :utf-8))  
      (io/spit "test.zip"))  
  
; multiple entries with subdirectories  
(->> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)  
          "x/b.txt" (bytebuf-from-string "def" :utf-8)  
          "x/y/c.txt" (bytebuf-from-string "ghi" :utf-8))  
      (io/spit "test.zip"))  
  
; empty directory z/  
(->> (io/zip "a.txt" (bytebuf-from-string "abc" :utf-8)  
          "z/" nil)  
      (io/spit "test.zip"))
```

SEE ALSO

[io/zip-file](#)

Zips files and directories recursively. Does not zip hidden files and does not follow symbolic links. The zip-file may be a file, a ...

[io/unzip](#)

Unzips an entry from zip f the entry's data as a bytebuf. f may be a bytebuf, a file, a string (file path) or an InputStream.

[io/gzip](#)

gzips f. f may be a file, a string (file path), a bytebuf or an InputStream. Returns a bytebuf.

[io/spit](#)

Opens file f, writes content, and then closes f. f may be a file or a string (file path). The content may be a string or a bytebuf.

[io/zip-list](#)

List the content of a the zip f and prints it to the current value of out. f may be a bytebuf, a file, a string (file path), or an ...

[io/zip-list-entry-names](#)

Returns a list of the zip's entry names.

[io/zip-append](#)

Appends entries to an existing zip file *f*. Overwrites existing entries. An entry is given by a name and data. The entry data may be ...

[io/zip-remove](#)

Remove entries from a zip file *f*.

[top](#)

io/zip-append

```
(io/zip-append f & entries)
```

Appends entries to an existing zip file *f*. Overwrites existing entries. An entry is given by a name and data. The entry data may be *nil*, a *bytebuf*, a file, a string (file path), or an *InputStream*.

An entry name with a trailing '/' creates a directory.

```
(let [data (bytebuf-from-string "abc" :utf-8)]
  ; create the zip with a first file
  (->> (io/zip "a.txt" data)
    (io/spit "test.zip"))
  ; add text files
  (io/zip-append "test.zip" "b.txt" data "x/c.txt" data)
  ; add an empty directory
  (io/zip-append "test.zip" "x/y/" nil))
```

SEE ALSO

[io/zip-file](#)

Zips files and directories recursively. Does not zip hidden files and does not follow symbolic links. The zip-file may be a file, a string

[io/zip-remove](#)

Remove entries from a zip file *f*.

[top](#)

io/zip-file

```
(io/zip-file options* zip-file & files)
```

Zips files and directories recursively. Does not zip hidden files and does not follow symbolic links. The zip-file may be a file, a string (file path) or an *OutputStream*.

Options:

- | | |
|---------------|---|
| :filter-fn fn | a predicate function that filters the files to be added to the zip. |
| :mapper-fn fn | a mapper function that can map the file content of a file before it gets zipped. Returns <i>nil</i> or a <i>:java.io.InputStream</i> . The real file is used when <i>nil</i> is returned. |
| :silent b | if false prints the added entries to <i>out</i> , defaults to false |

Example:

```
venice> (io/zip-file :silent false "test.zip" "dirA" "dirB")
Output:
  adding: dirA/
  adding: dirA/a1.png
  adding: dirA/a2.png
```

```
adding: dirB/
adding: dirB/b1.png
```

```
; zip files
(io/zip-file "test.zip" "a.txt" "x/b.txt")

; zip all files from a directory
(io/zip-file "test.zip" "dir")

; zip all files in from two directories
(io/zip-file "test.zip" "dirA" "dirB")

; zip all files in from two directories and print the added entries
(io/zip-file :silent false "test.zip" "dirA" "dirB")

; zip all *.txt files from a directory
(io/zip-file :filter-fn (fn [dir name] (str/ends-with? name ".txt"))
  "test.zip"
  "dir")
```

SEE ALSO

[io/zip](#)

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

[io/zip-list](#)

List the content of a the zip *f* and prints it to the current value of *out*. *f* may be a bytebuf, a file, a string (file path), or an ...

[top](#)

io/zip-list

```
(io/zip-list options* f)
```

List the content of a the zip *f* and prints it to the current value of *out*. *f* may be a bytebuf, a file, a string (file path), or an InputStream. Returns nil in print mode otherwise returns a list with attributes for each zip file entry.

Options:

:verbose *b* if true print verbose output, defaults to false

:print *b* if true print the entries to *out*, defaults to true

Example:

```
venice> (io/zip-list "test.zip")
  Length      Date/Time  Name
-----
    0  2021-01-05 10:32  dirA/
 309977 2021-01-05 10:32  dirA/a1.png
 309977 2021-01-05 10:32  dirA/a2.png
    0  2021-01-05 10:32  dirB/
 309977 2021-01-05 10:32  dirB/b1.png
-----
 929931                      5 files
=> nil
```

```
venice> (io/zip-list :verbose true "test.zip")
  Length  Method      Size  Cmpr      Date/Time    CRC-32  Name
-----
    0  Stored         0    0%  2021-01-05 10:32  00000000  dirA/
 309977  Defl:N    297691    4%  2021-01-05 10:32  C7F24B5C  dirA/a1.png
```

309977

Defl:N

297691

4%

2021-01-05 10:32

C7F24B5C

dirA/a2.png

0

Stored

0

0%

2021-01-05 10:32

00000000

dirB/

309977

Defl:N

297691

4%

2021-01-05 10:32

C7F24B5C

dirB/b1.png

929931

null

893073

4%

5 files

=> nil

venice> (io/zip-list :print false "test.zip")

=> ({:size 0 :method "Stored" :name "dirA/" ...} ...)

(io/zip-list "test-file.zip")

(io/zip-list :verbose true "test-file.zip")

SEE ALSO

io/zip-list-entry-names

Returns a list of the zip's entry names.

io/zip-file

Zips files and directories recursively. Does not zip hidden files and does not follow symbolic links. The zip-file my be a file, a ...

io/zip

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

io/unzip

Unzips an entry from zip f the entry's data as a bytebuf. f may be a bytebuf, a file, a string (file path) or an InputStream.

top

io/zip-list-entry-names

(io/zip-list-entry-names)

Returns a list of the zip's entry names.

(io/zip-list-entry-names "test-file.zip")

SEE ALSO

io/zip-list

List the content of a the zip f and prints it to the current value of out. f may be a bytebuf, a file, a string (file path), or an ...

io/zip

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

io/unzip

Unzips an entry from zip f the entry's data as a bytebuf. f may be a bytebuf, a file, a string (file path) or an InputStream.

top

io/zip-remove

(io/zip-remove f & entry-names)

Remove entries from a zip file f.

```
; remove files from zip
(io/zip-remove "test.zip" "x/a.txt" "x/b.txt")
```

```
; remove directory from zip
(io/zip-remove "test.zip" "x/y/")
```

SEE ALSO

[io/zip-file](#)

Zips files and directories recursively. Does not zip hidden files and does not follow symbolic links. The zip-file may be a file, a ...

[io/zip-append](#)

Appends entries to an existing zip file f. Overwrites existing entries. An entry is given by a name and data. The entry data may be ...

[top](#)

io/zip?

```
(io/zip? f)
```

Returns true if f is a zipped file. f may be a file, a string (file path), a bytebuf, or an InputStream

```
(> (io/zip "a" (bytebuf-from-string "abc" :utf-8))
  (io/zip?))
=> true
```

SEE ALSO

[io/zip-file](#)

Zips files and directories recursively. Does not zip hidden files and does not follow symbolic links. The zip-file may be a file, a ...

[io/zip](#)

Creates a zip containing the entries. An entry is given by a name and data. The entry data may be nil, a bytebuf, a file, a string ...

[top](#)

ip-private?

```
(ip-private? addr)
```

Returns true if the IP address is private.

IPv4 addresses reserved for private networks:

- 192.168.0.0 - 192.168.255.255
- 172.16.0.0 - 172.31.255.255
- 10.0.0.0 - 10.255.255.255

```
(ip-private? "192.168.170.181")
=> true
```

[top](#)

jansi-version

(jansi-version)

Returns the Jansi version or nil if not available.

[top](#)

jar-maven-manifest-version

(jar-maven-manifest-version group-id artefact-id)

Returns the Maven version for a loaded JAR's manifest or nil if there is no Maven manifest.

Reads the version from the JAR's Maven 'pom.properties' file at:
/META-INF/maven/{group-id}/{artefact-id}/pom.properties

A 'pom.properties' may look like:

- artifactId=xchart
- groupId=org.knowm.xchart
- version=3.8.0

```
(jar-maven-manifest-version :com.github.librepdf :openpdf)  
=> "1.3.35"
```

SEE ALSO

[java-package-version](#)

Returns version information for a Java package or nil if the package does not exist or is not visible.

[top](#)

java-double-list

(java-double-list l)

Converts a Venice list/vector to a Java `Double` list

```
(java-double-list '(1.0 2.0 3.0))  
=> [1.0, 2.0, 3.0]
```

```
(java-double-list '(1 2 3.2 3.56M))  
=> [1.0, 2.0, 3.2, 3.56]
```

SEE ALSO

[java-float-list](#)

Converts a Venice list/vector to a Java Float list

[double-array](#)

Returns an array of Java primitive doubles containing the contents of coll or returns an array with the given length and optional init value.

[top](#)

java-enumeration-to-list

```
(java-enumeration-to-list e)
```

Converts a Java enumeration to a list

[top](#)

java-float-list

```
(java-float-list l)
```

Converts a Venice list/vector to a Java `Float` list

```
(java-float-list '(1.0F 2.0F 3.0F))  
=> [1.0, 2.0, 3.0]
```

```
(java-float-list '(1I 2 3.2 3.56M))  
=> [1.0, 2.0, 3.2, 3.56]
```

SEE ALSO

[java-double-list](#)

Converts a Venice list/vector to a Java Double list

[float-array](#)

Returns an array of Java primitive floats containing the contents of coll or returns an array with the given length and optional init value.

[top](#)

java-int-list

```
(java-int-list l)
```

Converts a Venice list/vector to a Java `Integer` list

```
(java-int-list '(1I 2I 3I))  
=> [1, 2, 3]
```

```
(java-int-list '(1I 2 3.2 3.56M))  
=> [1, 2, 3, 3]
```

SEE ALSO

[int-array](#)

Returns an array of Java primitive ints containing the contents of coll or returns an array with the given length and optional init value.

[top](#)

java-iterator-to-list

```
(java-iterator-to-list e)
```


Converts a Java iterator to a list

[top](#)

java-long-list

(java-long-list l)

Converts a Venice list/vector to a Java `Long` list

```
(java-long-list '(1 2 3))  
=> [1, 2, 3]
```

```
(java-long-list '(1I 2 3.2 3.56M))  
=> [1, 2, 3, 3]
```

SEE ALSO

[long-array](#)

Returns an array of Java primitive longs containing the contents of coll or returns an array with the given length and optional init value.

[top](#)

java-major-version

(java-major-version)

Returns the Java major version (8, 9, 11, ...).

```
(java-major-version)  
=> 8
```

SEE ALSO

[java-version](#)

Returns the Java VM version (1.8.0_252, 11.0.7, ...)

[java-version-info](#)

Returns the Java VM version info.

[top](#)

java-obj?

(java-obj? obj)

Returns true if obj is a Java object

```
(java-obj? (. :java.math.BigInteger :new "0"))  
=> true
```

[top](#)

java-package-version

(java-package-version class)

Returns version information for a Java package or nil if the package does not exist or is not visible.

```
(java-package-version :java.lang.String)
=> {:implementation-title "Java Runtime Environment" :implementation-vendor "Azul Systems, Inc." :
implementation-version "1.8.0_392" :specification-title "Java Platform API Specification" :specification-vendor
"Oracle Corporation" :specification-version "1.8"}
```

```
(java-package-version (class :java.lang.String))
=> {:implementation-title "Java Runtime Environment" :implementation-vendor "Azul Systems, Inc." :
implementation-version "1.8.0_392" :specification-title "Java Platform API Specification" :specification-vendor
"Oracle Corporation" :specification-version "1.8"}
```

SEE ALSO

[jar-maven-manifest-version](#)

Returns the Maven version for a loaded JAR's manifest or nil if there is no Maven manifest.

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[top](#)

java-source-location

(java-source-location class)

Returns the path of the source location of a class (fully qualified class name).

```
(java-source-location :com.github.jlangch.venice.Venice)
```

[top](#)

java-string-list

(java-string-list l)

Converts a Venice list/vector to a Java `String` list

```
(java-string-list '("ab" "cd" "ef"))
=> [ab, cd, ef]
```

```
(java-string-list '("ab" 1I 2 3.2 3.56M))
=> [ab, 1, 2, 3.2, 3.56]
```

SEE ALSO

[string-array](#)

Returns an array of Java strings containing the contents of coll or returns an array with the given length and optional init value

java-unwrap-optional

```
(java-unwrap-optional val)
```

Unwraps a Java `java.util.Optional` to its contained value or nil

java-version

```
(java-version)
```

Returns the Java VM version (1.8.0_252, 11.0.7, ...)

```
(java-version)  
=> "1.8.0_392"
```

SEE ALSO

[java-major-version](#)

Returns the Java major version (8, 9, 11, ...).

[java-version-info](#)

Returns the Java VM version info.

java-version-info

```
(java-version-info)
```

Returns the Java VM version info.

```
(java-version-info)  
=> {:version "1.8.0_392" :vendor "Azul Systems, Inc." :vm-version "25.392-b08" :vm-name "OpenJDK 64-Bit Server VM" :vm-vendor "Azul Systems, Inc."}
```

SEE ALSO

[java-version](#)

Returns the Java VM version (1.8.0_252, 11.0.7, ...)

[java-major-version](#)

Returns the Java major version (8, 9, 11, ...).

java/as-biconsumer

```
(as-biconsumer f)
```

Wraps the function f in a [java.util.function.BiConsumer](#)

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static void testBiConsumer(BiConsumer<Long,Long> f, Long t, Long u) {
  ;;   f.accept(t,u);
  ;; }

  (defn op [t u] (println "consumed" t u))
  (. :FunctionalInterfaces :testBiConsumer (j/as-biconsumer op) 1 2))
consumed 1 2
=> nil
```

SEE ALSO

[java/as-bipredicate](#)

Wraps the function f in a [java.util.function.BiPredicate](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiPredicate.html>)

[java/as-bifunction](#)

Wraps the function f in a [java.util.function.BiFunction](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiFunction.html>)

[java/as-unaryoperator](#)

Wraps the function f in a [java.util.function.UnnaryOperator](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/UnaryOperator.html>)

[java/as-binaryoperator](#)

Wraps the function f in a [java.util.function.BinaryOperator](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BinaryOperator.html>)

[top](#)

java/as-bifunction

```
(as-bifunction f)
```

Wraps the function f in a [java.util.function.BiFunction](#)

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static Long testBiFunction(BiFunction<Long,Long,Long> f, Long t, Long u) {
  ;;   return f.apply(t,u);
  ;; }

  (defn op [t u] (+ t u))
  (. :FunctionalInterfaces :testBiFunction (j/as-bifunction op) 1 2))
=> 3
```

SEE ALSO

[java/as-bipredicate](#)

Wraps the function f in a [java.util.function.BiPredicate](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiPredicate.html>)

[java/as-biconsumer](#)

Wraps the function f in a [java.util.function.BiConsumer](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiConsumer.html>)

[java/as-unaryoperator](#)

Wraps the function f in a [java.util.function.UnnaryOperator](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/UnaryOperator.html>)

[java/as-binaryoperator](#)

Wraps the function f in a [java.util.function.BinaryOperator](https://docs.oracle.com/javase/8/docs/api/java/util/function/BinaryOperator.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BinaryOperator.html>)

[top](#)

java/as-binaryoperator

(as-binaryoperator f)

Wraps the function f in a [java.util.function.BinaryOperator](#)

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static Long testBinaryOperator(BinaryOperator<Long> f, Long t, Long u) {
  ;;   return f.apply(t,u);
  ;; }

  (defn op [t u] (+ t u))
  (. :FunctionalInterfaces :testBinaryOperator (j/as-binaryoperator op) 1 2))
=> 3
```

SEE ALSO

[java/as-bipredicate](#)

Wraps the function f in a [java.util.function.BiPredicate](https://docs.oracle.com/javase/8/docs/api/java/util/function/BiPredicate.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiPredicate.html>)

[java/as-bifunction](#)

Wraps the function f in a [java.util.function.BiFunction](https://docs.oracle.com/javase/8/docs/api/java/util/function/BiFunction.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiFunction.html>)

[java/as-biconsumer](#)

Wraps the function f in a [java.util.function.BiConsumer](https://docs.oracle.com/javase/8/docs/api/java/util/function/BiConsumer.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiConsumer.html>)

[java/as-unaryoperator](#)

Wraps the function f in a [java.util.function.UnaryOperator](https://docs.oracle.com/javase/8/docs/api/java/util/function/UnaryOperator.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/UnaryOperator.html>)

[top](#)

java/as-bipredicate

(as-bipredicate f)

Wraps the function f in a [java.util.function.BiPredicate](#)

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static boolean testBiPredicate(BiPredicate<Long,Long> f, Long t, Long u) {
  ;;   return f.test(t,u);
  ;; }

  (defn op [t u] (> t u))
  (. :FunctionalInterfaces :testBiPredicate (j/as-bipredicate op) 1 2))
=> false
```

SEE ALSO

[java/as-bifunction](#)

Wraps the function `f` in a `java.util.function.BiFunction` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiFunction.html>)

[java/as-biconsumer](#)

Wraps the function `f` in a `java.util.function.BiConsumer` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiConsumer.html>)

[java/as-unaryoperator](#)

Wraps the function `f` in a `java.util.function.UnnaryOperator` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/UnaryOperator.html>)

[java/as-binaryoperator](#)

Wraps the function `f` in a `java.util.function.BinaryOperator` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BinaryOperator.html>)

[top](#)

java/as-callable

`(as-callable f)`

Wraps the function `f` in a `java.util.concurrent.Callable`

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static Long testCallable(Callable<Long> c) throws Exception {
  ;;   return c.call();
  ;; }

  (defn op [] 4)
  (. :FunctionalInterfaces :testCallable (j/as-callable op)))
=> 4
```

SEE ALSO

[java/as-runnable](#)

Wraps the function `f` in a `java.lang.Runnable` (<https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html>)

[java/as-predicate](#)

Wraps the function `f` in a `java.util.function.Predicate` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Predicate.html>)

[java/as-function](#)

Wraps the function `f` in a `java.util.function.Function` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Function.html>)

[java/as-consumer](#)

Wraps the function `f` in a `java.util.function.Consumer` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Consumer.html>)

[java/as-supplier](#)

Wraps the function `f` in a `java.util.function.Supplier` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html>)

[top](#)

java/as-consumer

`(as-consumer f)`

Wraps the function `f` in a `java.util.function.Consumer`

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static void testConsumer(Consumer<Long> f, Long t) {
  ;;   f.accept(t);
  ;; }

  (defn op [t] (println "consumed" t))
  (. :FunctionalInterfaces :testConsumer (j/as-consumer op) 4))
consumed 4
=> nil
```

SEE ALSO

[java/as-runnable](#)

Wraps the function f in a [java.lang.Runnable](https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html) (<https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html>)

[java/as-callable](#)

Wraps the function f in a [java.util.concurrent.Callable](https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html>)

[java/as-predicate](#)

Wraps the function f in a [java.util.function.Predicate](https://docs.oracle.com/javase/8/docs/api/java/util/function/Predicate.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Predicate.html>)

[java/as-function](#)

Wraps the function f in a [java.util.function.Function](https://docs.oracle.com/javase/8/docs/api/java/util/function/Function.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Function.html>)

[java/as-supplier](#)

Wraps the function f in a [java.util.function.Supplier](https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html>)

[top](#)

java/as-function

```
(as-function f)
```

Wraps the function f in a [java.util.function.Function](#)

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static Long testFunction(Function<Long,Long> f, Long t) {
  ;;   return f.apply(t);
  ;; }

  (defn op [t] (+ t 1))
  (. :FunctionalInterfaces :testFunction (j/as-function op) 4))
=> 5
```

SEE ALSO

[java/as-runnable](#)

Wraps the function f in a [java.lang.Runnable](https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html) (<https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html>)

[java/as-callable](#)

Wraps the function f in a [java.util.concurrent.Callable](https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html>)

[java/as-predicate](#)

Wraps the function f in a [java.util.function.Predicate](https://docs.oracle.com/javase/8/docs/api/java/util/function/Predicate.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Predicate.html>)

[java/as-consumer](#)

Wraps the function f in a [java.util.function.Consumer](https://docs.oracle.com/javase/8/docs/api/java/util/function/Consumer.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Consumer.html>)

java/as-supplier

Wraps the function f in a [java.util.function.Supplier](https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html>)

top

java/as-predicate

(as-predicate f)

Wraps the function f in a [java.util.function.Predicate](#)

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static boolean testPredicate(Predicate<Long> p, Long t) {
  ;;   return p.test(t);
  ;; }

  (defn op [t] (pos? t))
  (. :FunctionalInterfaces :testPredicate (j/as-predicate op) 4))
=> true
```

SEE ALSO

[java/as-runnable](#)

Wraps the function f in a [java.lang.Runnable](https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html) (<https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html>)

[java/as-callable](#)

Wraps the function f in a [java.util.concurrent.Callable](https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html>)

[java/as-function](#)

Wraps the function f in a [java.util.function.Function](https://docs.oracle.com/javase/8/docs/api/java/util/function/Function.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Function.html>)

[java/as-consumer](#)

Wraps the function f in a [java.util.function.Consumer](https://docs.oracle.com/javase/8/docs/api/java/util/function/Consumer.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Consumer.html>)

[java/as-supplier](#)

Wraps the function f in a [java.util.function.Supplier](https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html>)

top

java/as-runnable

(as-runnable f)

Wraps the function f in a [java.lang.Runnable](#)

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static void testRunnable(final Runnable r) {
  ;;   r.run();
  ;; }

  (defn op [] (println "running"))
```



```
(. :FunctionalInterfaces :testRunnable (j/as-runnable op)))
running
=> nil
```

SEE ALSO

[java/as-callable](#)

Wraps the function f in a [java.util.concurrent.Callable](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html>)

[java/as-predicate](#)

Wraps the function f in a [java.util.function.Predicate](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Predicate.html>)

[java/as-function](#)

Wraps the function f in a [java.util.function.Function](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Function.html>)

[java/as-consumer](#)

Wraps the function f in a [java.util.function.Consumer](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Consumer.html>)

[java/as-supplier](#)

Wraps the function f in a [java.util.function.Supplier](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html>)

[top](#)

java/as-supplier

```
(as-supplier f)
```

Wraps the function f in a [java.util.function.Supplier](#)

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static Long testSupplier(Supplier<Long> f) {
  ;;   return f.get();
  ;; }

  (defn op [] 5)
  (. :FunctionalInterfaces :testSupplier (j/as-supplier op)))
=> 5
```

SEE ALSO

[java/as-runnable](#)

Wraps the function f in a [java.lang.Runnable](#) (<https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html>)

[java/as-callable](#)

Wraps the function f in a [java.util.concurrent.Callable](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html>)

[java/as-predicate](#)

Wraps the function f in a [java.util.function.Predicate](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Predicate.html>)

[java/as-function](#)

Wraps the function f in a [java.util.function.Function](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Function.html>)

[java/as-consumer](#)

Wraps the function f in a [java.util.function.Consumer](#) (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Consumer.html>)

[top](#)

java/as-unaryoperator

```
(as-unaryoperator f)
```

Wraps the function `f` in a `java.util.function.UnnaryOperator`

```
(do
  (load-module :java ['java :as 'j])
  (import :com.github.jlangch.venice.demo.FunctionalInterfaces)

  ;; public static Long testUnaryOperator(UnaryOperator<Long> f, Long t) {
  ;;   return f.apply(t);
  ;; }

  (defn op [t] (+ t 1))
  (. :FunctionalInterfaces :testUnaryOperator (j/as-unaryoperator op) 1))
=> 2
```

SEE ALSO

[java/as-bipredicate](#)

Wraps the function `f` in a `java.util.function.BiPredicate` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiPredicate.html>)

[java/as-bifunction](#)

Wraps the function `f` in a `java.util.function.BiFunction` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiFunction.html>)

[java/as-biconsumer](#)

Wraps the function `f` in a `java.util.function.BiConsumer` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiConsumer.html>)

[java/as-binaryoperator](#)

Wraps the function `f` in a `java.util.function.BinaryOperator` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BinaryOperator.html>)

[top](#)

java/javadoc

```
(javadoc class-or-object)
```

Opens a browser window displaying the javadoc for argument.

```
(java/javadoc :java.lang.String)
```

[top](#)

jdbc-core/auto-commit!

```
(auto-commit! conn on)
```

Activate/Deactivate auto commit on a connection

```
(jdbc-core/auto-commit! conn true)
(jdbc-core/auto-commit! conn false)
(jdbc-core/auto-commit! conn :on)
(jdbc-core/auto-commit! conn :off)
```

SEE ALSO

[jdbc-core/tx-isolation](#)

Returns transaction isolation level of the connection

[jdbc-core/tx-isolation!](#)

Set the transaction isolation level for the connection

[jdbc-core/auto-commit?](#)

Returns true if auto commit is enabled on the connection else false

[jdbc-core/commit!](#)

Commit the current transaction on the connection

[jdbc-core/rollback!](#)

Rollback the current transaction on the connection

[top](#)

[jdbc-core/auto-commit?](#)

```
(auto-commit? conn)
```

Returns true if auto commit is enabled on the connection else false

```
(jdbc-core/auto-commit? conn)
```

SEE ALSO

[jdbc-core/tx-isolation](#)

Returns transaction isolation level of the connection

[jdbc-core/tx-isolation!](#)

Set the transaction isolation level for the connection

[jdbc-core/auto-commit!](#)

Activate/Deactivate auto commit on a connection

[jdbc-core/commit!](#)

Commit the current transaction on the connection

[jdbc-core/rollback!](#)

Rollback the current transaction on the connection

[top](#)

[jdbc-core/blob-bytebuf](#)

```
(blob-bytebuf blob)
```

Returns the blob data as a bytebuf

```
(jdbc-core/blob-bytebuf b)
```

SEE ALSO

[jdbc-core/blob?](#)

Returns true if val is a java.sql.Blob

[jdbc-core/blob-length](#)

Returns the length of a blob

[jdbc-core/blob-in-stream](#)

Returns a :java.io.InputStream to read the blob data

[jdbc-core/blob-free](#)

Frees the Blob object and releases the resources the resources that it holds.

[top](#)

jdbc-core/blob-free

(blob-free blob)

Frees the Blob object and releases the resources the resources that it holds.

([jdbc-core/blob-free](#) b)

SEE ALSO

[jdbc-core/blob?](#)

Returns true if val is a:java.sql.Blob

[jdbc-core/blob-length](#)

Returns the length of a blob

[jdbc-core/blob-in-stream](#)

Returns a :java.io.InputStream to read the blob data

[jdbc-core/blob-bytebuf](#)

Returns the blob data as a bytebuf

[top](#)

jdbc-core/blob-in-stream

(blob-in-stream blob)

Returns a :java.io.InputStream to read the blob data

([jdbc-core/blob-in-stream](#) b)

SEE ALSO

[jdbc-core/blob?](#)

Returns true if val is a:java.sql.Blob

[jdbc-core/blob-length](#)

Returns the length of a blob

[jdbc-core/blob-bytebuf](#)

Returns the blob data as a bytebuf

[jdbc-core/blob-free](#)

Frees the Blob object and releases the resources the resources that it holds.

[top](#)

jdbc-core/blob-length

(blob-length blob)

Returns the length of a blob

([jdbc-core/blob-length](#) b)

SEE ALSO

[jdbc-core/blob?](#)

Returns true if val is a:java.sql.Blob

[jdbc-core/blob-in-stream](#)

Returns a :java.io.InputStream to read the blob data

[jdbc-core/blob-bytebuf](#)

Returns the blob data as a bytebuf

[jdbc-core/blob-free](#)

Frees the Blob object and releases the resources the resources that it holds.

top

jdbc-core/blob?

(blob? val)

Returns true if val is a:java.sql.Blob

([jdbc-core/blob?](#) v)

SEE ALSO

[jdbc-core/blob-length](#)

Returns the length of a blob

[jdbc-core/blob-in-stream](#)

Returns a :java.io.InputStream to read the blob data

[jdbc-core/blob-bytebuf](#)

Returns the blob data as a bytebuf

[jdbc-core/blob-free](#)

Frees the Blob object and releases the resources the resources that it holds.

top

jdbc-core/clob-free

(clob-free clob)

Frees the Clob object and releases the resources the resources that it holds.

([jdbc-core/clob-free](#) c)

SEE ALSO

[jdbc-core/clob?](#)

Returns true if val is a:java.sql.Clob

[jdbc-core/clob-length](#)

Returns the length of a clob

[jdbc-core/clob-reader](#)

Returns a :java.io.Reader to read the clob data

[top](#)

jdbc-core/clob-length

(clob-length clob)

Returns the length of a clob

([jdbc-core/clob-length](#) vc

SEE ALSO

[jdbc-core/clob?](#)

Returns true if val is a:java.sql.Clob

[jdbc-core/clob-reader](#)

Returns a :java.io.Reader to read the clob data

[jdbc-core/clob-free](#)

Frees the Clob object and releases the resources the resources that it holds.

[top](#)

jdbc-core/clob-reader

(clob-reader clob)

Returns a :java.io.Reader to read the clob data

([jdbc-core/clob-reader](#) c)

SEE ALSO

[jdbc-core/clob?](#)

Returns true if val is a:java.sql.Clob

[jdbc-core/clob-length](#)

Returns the length of a clob

[jdbc-core/clob-free](#)

Frees the Clob object and releases the resources the resources that it holds.

[top](#)

jdbc-core/clob?

(clob? val)

Returns true if val is a `java.sql.Clob`

([jdbc-core/clob?](#) v)

SEE ALSO

[jdbc-core/clob-length](#)

Returns the length of a clob

[jdbc-core/clob-reader](#)

Returns a `java.io.Reader` to read the clob data

[jdbc-core/clob-free](#)

Frees the Clob object and releases the resources the resources that it holds.

[top](#)

[jdbc-core/closed?](#)

([closed?](#) conn)

Returns true the connections is closed else false.

[top](#)

[jdbc-core/collect-result-set](#)

([collect-result-set](#) rs)

Collects data form a JDBC `java.sql.ResultSet` returns it as map with the column names and a vector of row values.

Row values may be of type:

- string
- boolean
- int
- long
- double
- decimal
- `java.sql.Clob`
- `java.sql.Blob`

```
{ :col-names ["name" "age"]  
  :rows [ ["john" 29]  
          ["mary" 32] ] }
```

```
(do  
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])  
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])  
  
  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")  
                stmt (jdbc/create-statement conn)  
                rs (jdbc/execute-query* stmt "SELECT * FROM foo")]  
    (jdbc/collect-result-set rs)))
```

SEE ALSO

[jdbc-core/render-query-result](#)

Renders the result from an execute-query in an ascii table format. Returns an ascii table formatted string.

[jdbc-core/print-query-result](#)

Prints the result from a execute-query in an ascii table format. Returns nil.

[jdbc-core/execute](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[jdbc-core/execute-query](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement or connection.

[jdbc-core/execute-update](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[top](#)

jdbc-core/columns

```
(columns conn table)
```

List the columns of a database table

Example PostgreSQL Chinook database "genre" table:

```
[ { :name "genre_id"
    :type :INTEGER
    :size "10"
    :nullable? "NO"
    :auto-inc? "YES" }
  { :name "name"
    :type :VARCHAR
    :size "120"
    :nullable? "YES"
    :auto-inc? "NO" } ]
```

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (try-with [conn (jdbp/create-connection "localhost" 5432 "chinook" "pg" "pg")
    (jdbc/columns conn "genre")]))
```

[top](#)

jdbc-core/commit!

```
(commit! conn)
```

Commit the current transaction on the connection

```
(jdbc-core/auto-commit! conn false)
```

SEE ALSO

[jdbc-core/tx-isolation](#)

Returns transaction isolation level of the connection

[jdbc-core/tx-isolation!](#)

Set the transaction isolation level for the connection

[jdbc-core/auto-commit?](#)

Returns true if auto commit is enabled on the connection else false

[jdbc-core/auto-commit!](#)

Activate/Deactivate auto commit on a connection

[jdbc-core/rollback!](#)

Rollback the current transaction on the connection

[top](#)

jdbc-core/count-rows

```
(count-rows conn table)
```

Returns the row count of a table.

```
;; using a prepared statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")]
    (jdbc/count-rows conn "Albums")))
```

SEE ALSO

[jdbc-core/execute-query](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement or connection.

[top](#)

jdbc-core/create-database

```
(create-database conn database)
(create-database conn database force)
```

Creates a new database. If force flag is true drops the database first if it exists.

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (try-with [conn (jdbp/create-connection "pg" "pg")]
    (jdbc/create-database conn "test"))))

(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (try-with [conn (jdbp/create-connection "pg" "pg")]
    (jdbc/create-database conn "test" true)))
```

SEE ALSO

[jdbc-core/drop-database](#)

Drops a database if it exists.

top

jdbc-core/create-statement

```
(create-statement conn)
```

Create a statement

```
(jdbc-core/create-statement conn)
```

SEE ALSO

[jdbc-core/prepare-statement](#)

Create a prepared statement

top

jdbc-core/drop-database

```
(drop-database conn database)
(drop-database conn database force)
```

Drops a database if it exists.

The force option will attempt to terminate all existing connections to the database.

Note: The force option is supported for PostgreSQL only and disconnects all connections prior to dropping the database!

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (try-with [conn (jdbp/create-connection "pg" "pg")]
    (jdbc/drop-database conn "test")))
```

SEE ALSO

[jdbc-core/create-database](#)

Creates a new database. If force flag is true drops the database first if it exists.

top

jdbc-core/execute

```
(execute pstmt)
(execute stmt sql)
```

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

```
;; using a prepared statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
```

```
(try-with [conn (jdbc/create-connection "localhost" 5432 "test" "pg" "pg")
            pstmt (jdbc/prepare-statement conn "INSERT INTO foo VALUES(?,?)")]
  (jdbc/ps-int pstmt 1 1I)
  (jdbc/ps-string pstmt 2 "Harry Potter")
  (jdbc/execute pstmt)))

;; running an SQL statement on a JDBC statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbc/create-connection "localhost" 5432 "test" "pg" "pg")
              stmt (jdbc/create-statement conn)]
    (jdbc/execute stmt "INSERT INTO foo VALUES(1, 'Harry Potter')")))
```

SEE ALSO

[jdbc-core/execute-query](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement or connection.

[jdbc-core/execute-query*](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[jdbc-core/execute-update](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[top](#)

jdbc-core/execute-query

```
(execute-query pstmt)
(execute-query stmt sql)
```

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement or connection.

Returns the JDBC `:java.sql.ResultSet` parsed as map with the column names and a vector of row values.

Row values may be of type:

- string
- boolean
- int
- long
- double
- decimal
- :java.sql.Clob
- :java.sql.Blob

```
{ :col-names ["name" "age"]
  :rows [ ["john" 29]
          ["mary" 32] ] }
```

```
;; using a prepared statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
```

```
(try-with [conn (jdbc/create-connection "localhost" 5432 "test" "pg" "pg")
            pstmt (jdbc/prepare-statement conn "SELECT * FROM foo")]
  (jdbc/execute-query pstmt)))

;; running an SQL statement on a JDBC statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbc/create-connection "localhost" 5432 "test" "pg" "pg")
            stmt (jdbc/create-statement conn)]
    (-> (jdbc/execute-query stmt "SELECT * FROM foo")
      (jdbc-core/print-query-result))))
```

SEE ALSO

[jdbc-core/render-query-result](#)

Renders the result from an execute-query in an ascii table format. Returns an ascii table formatted string.

[jdbc-core/print-query-result](#)

Prints the result from a execute-query in an ascii table format. Returns nil.

[jdbc-core/execute](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[jdbc-core/execute-update](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[top](#)

jdbc-core/execute-query*

```
(execute-query* pstmt)
(execute-query* stmt sql)
```

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

Returns a JDBC `:java.sql.ResultSet`.

Note: The returned ResultSet has to be closed after use!

```
;; using a prepared statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbc/create-connection "localhost" 5432 "test" "pg" "pg")
            pstmt (jdbc/prepare-statement conn "SELECT * FROM foo")
            rs (jdbc/execute-query* pstmt)]
    (while (jdbc/rs-next! rs)
      (println (jdbc/rs-string rs 1)))))

;; running an SQL statement on a JDBC statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbc/create-connection "localhost" 5432 "test" "pg" "pg")
            stmt (jdbc/create-statement conn)
            rs (jdbc/execute-query* stmt "SELECT * FROM foo")]
    (while (jdbc/rs-next! rs)
      (println (jdbc/rs-string rs 1)))))
```

```
;; running an SQL statement on a JDBC statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")
              stmt (jdbc/create-statement conn)
              rs   (jdbc/execute-query* stmt "SELECT * FROM foo")]
    (jdbc/print-query-result rs)))
```

SEE ALSO

[jdbc-core/collect-result-set](#)

Collects data from a JDBC `java.sql.ResultSet` returns it as map with the column names and a vector of row values.

[jdbc-core/render-query-result](#)

Renders the result from an execute-query in an ascii table format. Returns an ascii table formatted string.

[jdbc-core/print-query-result](#)

Prints the result from a execute-query in an ascii table format. Returns nil.

[jdbc-core/execute](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[jdbc-core/execute-query](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement or connection.

[jdbc-core/execute-update](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[top](#)

jdbc-core/execute-update

```
(execute-update pstmt)
(execute-update stmt sql & options)
```

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

Returns an integer value that reports the number of rows affected by the SQL statement.

Options:

`:gen-key` Provide access to the generated keys.
The generated keys can be retrieved by a call to `(jdbc-core/generated-keys stmt)`.

Values:

`true` Return all generated keys
`["id"]` Return only the generated keys in the specified list

```
;; using a prepared statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")
              pstmt (jdbc/prepare-statement conn "INSERT INTO foo VALUES(?,?)")
              (jdbc/ps-int pstmt 1 1I)
              (jdbc/ps-string pstmt 2 "Harry Potter")
              (jdbc/execute-update pstmt)])
```

```
;; running an SQL statement on a JDBC statement
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")
                stmt (jdbc/create-statement conn)]
    (jdbc/execute-update stmt "INSERT INTO foo VALUES(1, 'Harry Potter')")))
```

SEE ALSO

[jdbc-core/execute](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[jdbc-core/execute-query](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement or connection.

[jdbc-core/execute-query*](#)

Executes the SQL statement in prepared statement or executes an SQL statement on a JDBC statement.

[top](#)

jdbc-core/features

```
(features conn)
```

List the database' features

Example PostgreSQL features:

```
{ :supports-stored-procedures true
  :supports-full-outer-joins true
  :supports-savepoints true
  :supports-batch-updates true
  :supports-transactions true }
```

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (try-with [conn (jdbp/create-connection "localhost" 5432 "pg" "pg")]
    (jdbc/features conn)))
```

[top](#)

jdbc-core/generated-keys

```
(generated-keys stmt)
```

Return a vector with generated keys.

```
(jdbc-core/generated-keys stmt)
```

SEE ALSO

[jdbc-core/create-statement](#)

Create a statement

[jdbc-core/prepare-statement](#)

Create a prepared statement

top

jdbc-core/meta-data

(meta-data conn)

List the meta data of a database

Example PostgreSQL meta data:

```
{ :product-name "PostgreSQL"
  :driver-name "PostgreSQL JDBC Driver"
  :driver-version "42.7.3"
  :product-version "16.2 (Debian 16.2-1.pgdg120+2)" }
```

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (try-with [conn (jdbp/create-connection "localhost" 5432 "pg" "pg")]
    (jdbc/meta-data conn)))
```

top

jdbc-core/postgresql?

(postgresql? conn)

Returns true if 'conn' is a PostgreSQL connection else false.

top

jdbc-core/prepare-statement

(prepare-statement conn sql)
(prepare-statement conn sql & options)

Create a prepared statement

Options:

:gen-key Provide access to the generated keys.
 The generated keys can be retrieved by a call to (jdbc-core/generated-keys stmt) .

Values:

true Return all generated keys
["id"] Return only the generated keys in the specified list

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
```

```
(try-with [conn (jdbc/create-connection "localhost" 5432 "test" "pg" "pg")
            pstmt (jdbc/prepare-statement conn "INSERT INTO foo VALUES(?,?)")]
  (jdbc/ps-int pstmt 1 1I)
  (jdbc/ps-string pstmt 2 "Harry Potter")
  (jdbc/execute pstmt)))
```

SEE ALSO

[jdbc-core/create-statement](#)

Create a statement

[top](#)

jdbc-core/print-query-result

```
(print-query-result data)
(print-query-result data max-col-width)
```

Prints the result from a `execute-query` in an ascii table format. Returns `nil`.

The function accepts a JDBC `java.sql.ResultSet` or a collected result set as returned from [jdbc-core/collect-result-set](#).

max-col-width is limited to the range [5..200]

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbc/create-connection "localhost" 5432 "test" "pg" "pg")
              stmt (jdbc/create-statement conn)
              rs (jdbc/execute-query* stmt "SELECT * FROM foo")]
    (jdbc/print-query-result rs)))
```

SEE ALSO

[jdbc-core/collect-result-set](#)

Collects data from a JDBC `java.sql.ResultSet` returns it as map with the column names and a vector of row values.

[jdbc-core/render-query-result](#)

Renders the result from an `execute-query` in an ascii table format. Returns an ascii table formatted string.

[top](#)

jdbc-core/ps-blob

```
(ps-blob ps idx val)
```

Sets the prepared statement parameter to the given blob value.

The value may be a `bytebuf` or a `java.io.InputStream`.

```
(jdbc-core/ps-decimal ps 1 (bytebuf [1 2 3]))

(jdbc-core/ps-decimal ps 1 (io/bytebuf-in-stream (bytebuf [1 2 3])))
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-boolean

```
(ps-boolean ps idx val)
```

Sets the prepared statment parameter to the given boolean value.

```
(jdbc-core/ps-boolean ps 1 true)
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-clear-parameters

```
(ps-clear-parameters ps)
```

Clears the prepared statment parameter.

```
(jdbc-core/ps-clear-parameters ps)
```

SEE ALSO

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-clob

```
(ps-clob ps idx val)
```

Sets the prepared statment parameter to the given clob value.

The value may be a `string` or a `:java.io.Reader`.

```
(jdbc-core/ps-decimal ps 1 "123456")
```

```
(jdbc-core/ps-decimal ps 1 (io/string-reader "123456"))
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-date

```
(ps-date ps idx val)
```

Sets the prepared statment parameter to the given date value.

```
(jdbc-core/ps-date ps 1 (time/date))
```

```
(jdbc-core/ps-date ps 1 (time/local-date 2020 1 1))
```

```
(jdbc-core/ps-date ps 1 (time/local-date-time 2020 1 1 14 0 0))
```

```
(jdbc-core/ps-date ps 1 (time/zoned-date-time "UTC" 2020 1 1 14 0 0))
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-decimal

```
(ps-decimal ps idx val)
```

Sets the prepared statment parameter to the given decimal value.

```
(jdbc-core/ps-decimal ps 1 3.1415M)
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-double

```
(ps-double ps idx val)
```

Sets the prepared statment parameter to the given double value.

```
(jdbc-core/ps-double ps 1 1.24)
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-float

```
(ps-float ps idx val)
```

Sets the prepared statment parameter to the given double value.

```
(jdbc-core/ps-float ps 1 1.24)
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-int

```
(ps-int ps idx val)
```

Sets the prepared statment parameter to the given int value.

```
(jdbc-core/ps-int ps 1 10I)
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

[top](#)

jdbc-core/ps-long

```
(ps-long ps idx val)
```

Sets the prepared statment parameter to the given long value.

```
(jdbc-core/ps-long ps 1 10)
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

jdbc-core/ps-string

```
(ps-string ps idx val)
```

Sets the prepared statment parameter to the given string value.

```
(jdbc-core/ps-string ps 1 "abcdef")
```

SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[jdbc-core/ps-timestamp](#)

Sets the prepared statment parameter to the given timestamp value.

jdbc-core/ps-timestamp

```
(ps-timestamp ps idx val)
```

Sets the prepared statment parameter to the given timestamp value.

```
(jdbc-core/ps-timestamp ps 1 (time/date))
```

```
(jdbc-core/ps-timestamp ps 1 (time/local-date 2020 1 1))
```

```
(jdbc-core/ps-timestamp ps 1 (time/local-date-time 2020 1 1 14 0 0))
```

```
(jdbc-core/ps-timestamp ps 1 (time/zoned-date-time "UTC" 2020 1 1 14 0 0))
```


SEE ALSO

[jdbc-core/ps-clear-parameters](#)

Clears the prepared statment parameter.

[jdbc-core/ps-blob](#)

Sets the prepared statment parameter to the given blob value.

[jdbc-core/ps-clob](#)

Sets the prepared statment parameter to the given clob value.

[jdbc-core/ps-decimal](#)

Sets the prepared statment parameter to the given decimal value.

[jdbc-core/ps-boolean](#)

Sets the prepared statment parameter to the given boolean value.

[jdbc-core/ps-double](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-float](#)

Sets the prepared statment parameter to the given double value.

[jdbc-core/ps-int](#)

Sets the prepared statment parameter to the given int value.

[jdbc-core/ps-long](#)

Sets the prepared statment parameter to the given long value.

[jdbc-core/ps-string](#)

Sets the prepared statment parameter to the given string value.

[jdbc-core/ps-date](#)

Sets the prepared statment parameter to the given date value.

[top](#)

jdbc-core/render-query-result

```
(render-query-result data)
(render-query-result data max-col-width)
```

Renders the result from an `execute-query` in an ascii table format. Returns an ascii table formatted string.

The functions accepts a JDBC `'java.sql.ResultSet'` or a collected result set as returned from `jdbc-core/collect-result-set`.

max-col-width is limited to the range [15..200]

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")
               stmt (jdbc/create-statement conn)
               rs   (jdbc/execute-query* stmt "SELECT * FROM foo")]
    (jdbc/render-query-result rs)))
```

SEE ALSO

[jdbc-core/collect-result-set](#)

Collects data form a JDBC `'java.sql.ResultSet'` returns it as map with the column names and a vector of row values.

[jdbc-core/print-query-result](#)

Prints the result from a `execute-query` in an ascii table format. Returns nil.

jdbc-core/rollback!

```
(rollback! conn)
```

Rollback the current transaction on the connection

```
(jdbc-core/rollback! conn)
```

SEE ALSO

[jdbc-core/tx-isolation](#)

Returns transaction isolation level of the connection

[jdbc-core/tx-isolation!](#)

Set the transaction isolation level for the connection

[jdbc-core/auto-commit?](#)

Returns true if auto commit is enabled on the connection else false

[jdbc-core/auto-commit!](#)

Activate/Deactivate auto commit on a connection

[jdbc-core/commit!](#)

Commit the current transaction on the connection

jdbc-core/rs-blob

```
(rs-blob rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.sql.Blob`.

```
(jdbc-core/rs-blob rs 1)
```

```
(jdbc-core/rs-blob rs "data")
```

SEE ALSO

[jdbc-core/blob-length](#)

Returns the length of a blob

[jdbc-core/blob-in-stream](#)

Returns a `:java.io.InputStream` to read the blob data

[jdbc-core/blob-bytebuf](#)

Returns the blob data as a bytebuf

[jdbc-core/blob-free](#)

Frees the Blob object and releases the resources the resources that it holds.

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDateTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Clob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/rs-boolean

```
(rs-boolean rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `boolean` .

```
(jdbc-core/rs-boolean rs 1)
```

```
(jdbc-core/rs-boolean rs "openBill")
```

SEE ALSO

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDateTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDateTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Clob`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/rs-clob

```
(rs-clob rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Clob`.

```
(jdbc-core/rs-clob rs 1)
```

```
(jdbc-core/rs-clob rs "remarks")
```

SEE ALSO

[jdbc-core/clob-length](#)

Returns the length of a clob

[jdbc-core/clob-reader](#)

Returns a `java.io.Reader` to read the clob data

[jdbc-core/clob-free](#)

Frees the Clob object and releases the resources the resources that it holds.

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as an int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDateTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDateTime`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/rs-date

```
(rs-date rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDate`.

```
(jdbc-core/rs-date rs 1)
```

```
(jdbc-core/rs-date rs "birthDate")
```

SEE ALSO

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDateTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Clob`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/rs-decimal

```
(rs-decimal rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `decimal` .

```
(jdbc-core/rs-decimal rs 1)
```

```
(jdbc-core/rs-decimal rs "billAmount")
```

SEE ALSO

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalDateTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.sql.Clob`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/rs-double

```
(rs-double rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `double` .

```
(jdbc-core/rs-double rs 1)
```

```
(jdbc-core/rs-double rs "weight")
```

SEE ALSO

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDateTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Clob`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/rs-first!

```
(rs-first! rs)
```

Moves the cursor to the first row in this ResultSet object.

Returns true if the cursor is on a valid row; false if there are no rows in the result set

```
(jdbc-core/rs-first! rs)
```

SEE ALSO

[jdbc-core/rs-next!](#)

Moves the cursor forward one row from its current position. A ResultSet cursor is initially positioned before the first row; the first ...

[jdbc-core/rs-last!](#)

Moves the cursor to the last row in this ResultSet object.

[top](#)

jdbc-core/rs-float

```
(rs-float rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `double`.

```
(jdbc-core/rs-float rs 1)
```

```
(jdbc-core/rs-float rs "weight")
```

SEE ALSO

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a :java.time.LocalDate.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a :java.time.LocalTime.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a :java.time.LocalDateTime.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a :java.sql.Clob.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a :java.sql.Blob.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/rs-int

```
(rs-int rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `int`.

```
(jdbc-core/rs-int rs 1)
```

```
(jdbc-core/rs-int rs "age")
```

SEE ALSO

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDateTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Clob`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to `string`, `boolean`, `int`, `long`, `double`, ...

[top](#)

jdbc-core/rs-last!

```
(rs-last! rs)
```

Moves the cursor to the last row in this ResultSet object.

Returns true if the cursor is on a valid row; false if there are no rows in the result set

```
(jdbc-core/rs-last! rs)
```

SEE ALSO

[jdbc-core/rs-first!](#)

Moves the cursor to the first row in this ResultSet object.

[jdbc-core/rs-next!](#)

Moves the cursor forward one row from its current position. A ResultSet cursor is initially positioned before the first row; the first ...

[top](#)

jdbc-core/rs-long

```
(rs-long rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `Long` .

```
(jdbc-core/rs-long rs 1)
```

```
(jdbc-core/rs-long rs "age")
```

SEE ALSO

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a int.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalDateTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.sql.Clob`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/rs-next!

```
(rs-next! rs)
```

Moves the cursor forward one row from its current position. A ResultSet cursor is initially positioned before the first row; the first call to the method `next` makes the first row the current row; the second call makes the second row the current row, and so on.

Returns true if the new current row is valid; false if there are no more rows

```
(jdbc-core/rs-next! rs)
```

SEE ALSO

[jdbc-core/rs-first!](#)

Moves the cursor to the first row in this ResultSet object.

[jdbc-core/rs-last!](#)

Moves the cursor to the last row in this ResultSet object.

[top](#)

jdbc-core/rs-string

```
(rs-string rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `string` .

```
(jdbc-core/rs-string rs 1)
```

```
(jdbc-core/rs-string rs "firstName")
```

SEE ALSO

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalTime`.

[jdbc-core/rs-timestamp](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalDateTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.sql.Clob`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to `string`, `boolean`, `int`, `long`, `double`, ...

[top](#)

jdbc-core/rs-timestamp

```
(rs-timestamp rs name-or-index)
```

Retrieves the value of the designated column in the current row of the ResultSet object as a `:java.time.LocalDateTime` .

```
(jdbc-core/rs-timestamp rs 1)
```

```
(jdbc-core/rs-timestamp rs "createdAt")
```

SEE ALSO

[jdbc-core/rs-string](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a string.

[jdbc-core/rs-boolean](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a boolean.

[jdbc-core/rs-int](#)

Retrieves the value of the designated column in the current row of the ResultSet object as an int.

[jdbc-core/rs-long](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a long.

[jdbc-core/rs-float](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-double](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a double.

[jdbc-core/rs-decimal](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a decimal.

[jdbc-core/rs-date](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalDate`.

[jdbc-core/rs-time](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.time.LocalTime`.

[jdbc-core/rs-clob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Clob`.

[jdbc-core/rs-blob](#)

Retrieves the value of the designated column in the current row of the ResultSet object as a `java.sql.Blob`.

[jdbc-core/rs-object](#)

Retrieves the value of the designated column in the current row of the ResultSet object converted to string, boolean, int, long, double, ...

[top](#)

jdbc-core/schemas

(schemas conn)

List the schemas of a database

Example PostgreSQL schemas:

```
[ { :schem "information_schema"
  :catalog nil
}
{ :schem "pg_catalog"
  :catalog nil
}
{ :schem "public"
  :catalog nil
} ]
```

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (try-with [conn (jdbp/create-connection "localhost" 5432 "pg" "pg")]
    (jdbc/schemas conn)))
```

jdbc-core/tables

```
(tables conn)
```

List the tables of a database

Example PostgreSQL Chinook database:

```
[ "album"
  "artist"
  "customer"
  "employee"
  "genre"
  "invoice"
  "invoice_line"
  "media_type"
  "playlist"
  "playlist_track"
  "track" ]
```

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
  (try-with [conn (jdbp/create-connection "localhost" 5432 "chinook" "pg" "pg")]
    (jdbc/tables conn)))
```

jdbc-core/tx-isolation

```
(tx-isolation conn)
```

Returns transaction isolation level of the connection

Levels:

- `:tx-none`
- `:tx-read-committed`
- `:tx-read-uncommitted`
- `:tx-repeatable-read`
- `:tx-serializable`

```
(jdbc-core/tx-isolation conn)
```

SEE ALSO

[jdbc-core/tx-isolation!](#)

Set the transaction isolation level for the connection

[jdbc-core/auto-commit?](#)

Returns true if auto commit is enabled on the connection else false

[jdbc-core/auto-commit!](#)

Activate/Deactivate auto commit on a connection

[jdbc-core/commit!](#)

Commit the current transaction on the connection

[jdbc-core/rollback!](#)

Rollback the current transaction on the connection

[top](#)

jdbc-core/tx-isolation!

(tx-isolation! conn level)

Set the transaction isolation level for the connection

Levels:

- `:tx-none`
- `:tx-read-committed`
- `:tx-read-uncommitted`
- `:tx-repeatable-read`
- `:tx-serializable`

([jdbc-core/tx-isolation!](#) conn `:tx-repeatable-read`)

SEE ALSO

[jdbc-core/tx-isolation](#)

Returns transaction isolation level of the connection

[jdbc-core/auto-commit?](#)

Returns true if auto commit is enabled on the connection else false

[jdbc-core/auto-commit!](#)

Activate/Deactivate auto commit on a connection

[jdbc-core/commit!](#)

Commit the current transaction on the connection

[jdbc-core/rollback!](#)

Rollback the current transaction on the connection

[top](#)

jdbc-core/with-conn

(with-conn conn & forms)

Sets the thread local var `conn` to the passed connection, wraps the connection in a `try-with` form to close the connection automatically at the end of the template and runs the forms.

The forms have access to the connection via the `conn` thread local var.

While thread local vars may work fine (most ORMs like *Hibernate* or *JPA* rely on thread local vars), using Venice *Components* for connection management give a cleaner and more functional architecture.

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])
```

```
(jdbc/with-conn [conn (jdbp/create-connection "localhost" 5432
                                              "test" "pg" "pg")]]
  (try-with [stmt (jdbc/create-statement *conn*)])
    (-> (jdbc/execute-update stmt "INSERT INTO foo VALUES(100,3.1456)")
      (jdbc-core/print-query-result))))
```

SEE ALSO

[jdbc-core/with-tx](#)

Runs the forms within a JDBC transaction, commits the transaction at the end or rolls the transaction back if the forms throw an exception.

top

jdbc-core/with-tx

```
(with-tx conn & forms)
```

Runs the forms within a JDBC transaction, commits the transaction at the end or rolls the transaction back if the forms throw an exception.

Restores the auto-commit mode on the connection at the end of the successful or failed transaction.

Throws a `:com.github.jlangch.venice.TransactionException` after rolling back.

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")]]
    (jdbc/with-tx conn
      (try-with [stmt (jdbc/create-statement conn)]
        (-> (jdbc/execute-update stmt "INSERT INTO foo VALUES(100,3.1415)")
          (jdbc-core/print-query-result))))))
```

SEE ALSO

[jdbc-core/with-conn](#)

Sets the thread local var `conn` to the passed connection, wraps the connection in a try-with form to close the connection automatically ...

top

jdbc-postgresql/create-connection

```
(create-connection user password)
(create-connection host port user password)
(create-connection host port database user password)
(create-connection host port database user password properties)
```

Creates a PostgreSQL connection.

Arguments:

<i>user</i>	A mandatory ser name
<i>password</i>	A mandatory password
<i>host</i>	An optional host. Defaults to "localhost"
<i>port</i>	An optional port. Defaults to 5432
<i>database</i>	A mandatory database name
<i>properties</i>	Optional properties (a map).

E.g.: { "ssl" "true", "options" "-c statement_timeout=90000" }

```
(do
  (load-module :jdbc-core ['jdbc-core :as 'jdbc])
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")]
    (-> (jdbc/execute-query conn "SELECT * FROM mytable WHERE foo = 500")
      (jdbc/print-query-result))))
```

SEE ALSO

[jdbc-core/create-database](#)

Creates a new database. If force flag is true drops the database first if it exists.

[jdbc-core/drop-database](#)

Drops a database if it exists.

[top](#)

jdbc-postgresql/describe-table

```
(describe-table conn table & options)
```

Describe the schema of a table.

Options:

:mode In :print mode prints the table description, in :data mode returns the description as a data structure. Defaults to :print .

Example PostgreSQL Chinook database "album" table:

column_name	data_type	character_maximum_length	is_nullable	column_default
album_id	integer	<null>	NO	<null>
artist_id	integer	<null>	NO	<null>
title	character varying	160	NO	<null>

```
(do
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")]
    (jdbp/describe-table conn "album")))
```

SEE ALSO

[jdbc-postgresql/foreign-key-constraints](#)

List the foreign key constraints in a database

[top](#)

jdbc-postgresql/foreign-key-constraints

```
(foreign-key-constraints conn & options)
```


List the foreign key constraints in a database

Options:

:mode In :print mode prints the foreign key constraints, in :data mode returns the constraints as a data structure. Defaults to :print.

Example PostgreSQL Chinook database foreign key constraints:

table_name	foreign_key	pg_get_constraintdef
album	album_artist_id_fkey	FOREIGN KEY (artist_id) REFERENCES artist(artist_id)
customer	customer_support_rep_id_fkey	FOREIGN KEY (support_rep_id) REFERENCES employee(employee_id)
employee	employee_reports_to_fkey	FOREIGN KEY (reports_to) REFERENCES employee(employee_id)
invoice	invoice_customer_id_fkey	FOREIGN KEY (customer_id) REFERENCES customer(customer_id)
invoice_line	invoice_line_invoice_id_fkey	FOREIGN KEY (invoice_id) REFERENCES invoice(invoice_id)
invoice_line	invoice_line_track_id_fkey	FOREIGN KEY (track_id) REFERENCES track(track_id)
playlist_track	playlist_track_playlist_id_fkey	FOREIGN KEY (playlist_id) REFERENCES playlist(playlist_id)
playlist_track	playlist_track_track_id_fkey	FOREIGN KEY (track_id) REFERENCES track(track_id)
track	track_album_id_fkey	FOREIGN KEY (album_id) REFERENCES album(album_id)
track	track_genre_id_fkey	FOREIGN KEY (genre_id) REFERENCES genre(genre_id)
track	track_media_type_id_fkey	FOREIGN KEY (media_type_id) REFERENCES media_type(media_type_id)

```
(do
  (load-module :jdbc-postgresql ['jdbc-postgresql :as 'jdbp])

  (try-with [conn (jdbp/create-connection "localhost" 5432 "test" "pg" "pg")]
    (jdbp/foreign-key-constraints conn)))
```

SEE ALSO

[jdbc-postgresql/describe-table](#)

Describe the schema of a table.

[top](#)

json/pretty-print

(json/pretty-print s & options)

Pretty prints a JSON string

Options:

:indent s The indent for indented output. Must contain spaces or tabs only. Defaults to two spaces.

```
(> (json/write-str {:a 100 :b 100 :c [1 2 3]})
(json/pretty-print)
(println))
{
  "a": 100,
  "b": 100,
  "c": [1,2,3]
}
=> nil
```

```
(-> (json/write-str {:a 100 :b 100 :c [1 2 {:x 7 :y 8}] :d {:z 9}})
    (json/pretty-print :indent "  ")
    (println))
{
  "a": 100,
  "b": 100,
  "c": [1,2,{
    "x": 7,
    "y": 8
  }],
  "d": {
    "z": 9
  }
}
=> nil
```

SEE ALSO

[json/write-str](#)

Writes the val to a JSON string.

[json/read-str](#)

Reads a JSON string and returns it as a Venice datatype.

[json/spit](#)

Spits the JSON converted val to the output.

[json/slurp](#)

Slurps a JSON data from a source and returns it as a Venice data.

[top](#)

json/read-str

```
(json/read-str s & options)
```

Reads a JSON string and returns it as a Venice datatype.

Options:

- :key-fn fn Single argument function called on JSON property names; return value will replace the property names in the output. Default is 'identity', use 'keyword' to get keyword properties.
- :value-fn fn Function to transform values in JSON objects in the output. For each JSON property, value-fn is called with two arguments: the property name (transformed by key-fn) and the value. The return value of value-fn will replace the value in the output. The default value-fn returns the value unchanged.
- :decimal b If true use BigDecimal for decimal numbers instead of Double. Default is false.

```
(json/read-str (json/write-str {:a 100 :b 100}))
=> {"a" 100 "b" 100}
```

```
(json/read-str (json/write-str {:a 100 :b 100}) :key-fn keyword)
=> {:a 100 :b 100}
```

```
(json/read-str (json/write-str {:a 100 :b 100})
  :value-fn (fn [k v] (if (== "a" k) (inc v) v)))
=> {"a" 101 "b" 100}
```

SEE ALSO

[json/write-str](#)

Writes the val to a JSON string.

[json/spit](#)

Spits the JSON converted val to the output.

[json/slurp](#)

Slurps a JSON data from a source and returns it as a Venice data.

[json/pretty-print](#)

Pretty prints a JSON string

[top](#)

json/slurp

(`json/slurp` source & options)

Slurps a JSON data from a source and returns it as a Venice data.

The source may be a:

- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.nio.Path`
- `java.io.InputStream`
- `java.io.Reader`

Options:

`:key-fn` fn Single-argument function called on JSON property names; return value will replace the property names in the output. Default is 'identity', use 'keyword' to get keyword properties.

`:value-fn` fn Function to transform values in JSON objects in the output. For each JSON property, value-fn is called with two arguments: the property name (transformed by key-fn) and the value. The return value of value-fn will replace the value in the output. The default value-fn returns the value unchanged.

`:decimal` b If true use BigDecimal for decimal numbers instead of Double. Default is false.

`:encoding` e e.g :encoding :utf-8, defaults to :utf-8

```
(let [json (json/write-str {:a 100 :b 100 :c 1.233})]
  (try-with [in (io/string-reader json)]
    (pr-str (json/slurp in))))
=> "{ \"a\" 100 \"b\" 100 \"c\" 1.233}"

(let [json (json/write-str {:a 100 :b 100 :c 1.233})]
  (try-with [in (io/string-reader json)]
    (pr-str (json/slurp in :decimal true :key-fn keyword)))))
=> "{:a 100 :b 100 :c 1.233M}"
```

SEE ALSO

[json/write-str](#)

Writes the val to a JSON string.

[json/read-str](#)

Reads a JSON string and returns it as a Venice datatype.

[json/spit](#)

Spits the JSON converted val to the output.

[json/pretty-print](#)

Pretty prints a JSON string

[top](#)

json/spit

```
(json/spit out val & options)
```

Spits the JSON converted val to the output.

The out may be a:

- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.nio.Path`
- `java.io.OutputStream`
- `java.io.Writer`

Options:

:pretty b Enables/disables pretty printing. Defaults to false.
:decimal-as-double b If true emit a decimal as double else as string. Defaults to false.
:encoding e e.g :encoding :utf-8, defaults to :utf-8

```
(try-with [out (io/bytebuf-out-stream)]  
  (json/spit out {:a 100 :b 100 :c [10 20 30]}))  
(flush out)  
(bytebuf-to-string @out :utf-8))  
=> "{\"a\":100,\"b\":100,\"c\":[10,20,30]}"
```

SEE ALSO

[json/write-str](#)

Writes the val to a JSON string.

[json/read-str](#)

Reads a JSON string and returns it as a Venice datatype.

[json/slurp](#)

Slurps a JSON data from a source and returns it as a Venice data.

[json/pretty-print](#)

Pretty prints a JSON string

[top](#)

json/write-str

```
(json/write-str val & options)
```

Writes the val to a JSON string.

Options:

:pretty b Enables/disables pretty printing. Defaults to false.
:decimal-as-double b If true emit a decimal as double else as string. Defaults to false.

```
(json/write-str {:a 100 :b 100})  
=> "{\"a\":100,\"b\":100}"  
  
(json/write-str {:a 100 :b 100} :pretty true)  
=> "{\n  \"a\": 100,\n  \"b\": 100\n}"
```

SEE ALSO

[json/read-str](#)

Reads a JSON string and returns it as a Venice datatype.

[json/spit](#)

Spits the JSON converted val to the output.

[json/slurp](#)

Slurps a JSON data from a source and returns it as a Venice data.

[json/pretty-print](#)

Pretty prints a JSON string

[top](#)

jsonl/lazy-seq-slurper

(jsonl/lazy-seq-slurper in & options)

Returns a lazy sequence of the parsed JSON line strings from the input 'in'.

'in' may be a:

- `java.io.InputStream`
- `java.io.Reader`

Note: The caller is responsible for closing the in stream/reader!

Options:

:key-fn fn Single argument function called on JSON property names; return value will replace the property names in the output. Default is 'identity', use 'keyword' to get keyword properties.

:value-fn fn Function to transform values in JSON objects in the output. For each JSON property, value-fn is called with two arguments: the property name (transformed by key-fn) and the value. The return value of value-fn will replace the value in the output. The default value-fn returns the value unchanged.

:decimal b If true use BigDecimal for decimal numbers instead of Double. Default is false.

:filter-fn fn Single argument function called on every read value from a JSON line. If it returns true the value will be kept otherwise it will be skipped

:encoding e e.g :encoding :utf-8, defaults to :utf-8

`jsonl/lazy-seq-slurper` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

```
;; use a lazy sequence to read the JSON lines data
(do
  (load-module :jsonl)
  (let [file (io/temp-file "data-" ".jsonl")]
    (io/delete-file-on-exit file)
    (try-with [wr (io/buffered-writer file)]
      (jsonl/spit wr [{:a 100 :b 200} {:a 101 :b 201} {:a 102 :b 202}]))
    (flush wr))
    (try-with [rd (io/buffered-reader file)]
      (let [slurper (jsonl/lazy-seq-slurper rd :key-fn keyword)]
        ;; realize the lazy sequence
        (doall slurper))))))
```

```
=> ({:a 100 :b 200} {:a 101 :b 201} {:a 102 :b 202})
```

```
;; use a transducer to efficiently map and filter the JSON lines data
(do
  (load-module :jsonl)
```

```

(defn test-data []
  (try-with [sw (io/string-writer)]
    (println sw (json/write-str {:a 100 :b 200 :c 300}))
    (println sw (json/write-str {:a 101 :b 201 :c 301}))
    (println sw (json/write-str {:a 100 :b 202 :c 302}))
    (flush sw)
    @sw))

(def xform (comp (map #(dissoc % :c))
  (map #(update % :b (fn [x] (+ x 5))))
  (filter #(= 100 (:a %)))))

(let [json (test-data)]
  (try-with [rd (io/buffered-reader json)]
    (let [slurper (jsonl/lazy-seq-slurper rd :key-fn keyword)]
      ;; transduce the lazy sequence
      (pr-str (transduce xform conj slurper))))))
=> "[{:a 100 :b 205} {:a 100 :b 207}]"

```

SEE ALSO

[jsonl/slurp](#)

Slurps a list of JSON line strings from the input 'in' and returns it as a list of Venice data types.

[jsonl/read-str](#)

Reads a JSON line string 's' and returns it as a Venice data type.

[top](#)

jsonl/read-str

(jsonl/read-str s & options)

Reads a JSON line string 's' and returns it as a Venice data type.

Options:

- :key-fn fn Single argument function called on JSON property names; return value will replace the property names in the output. Default is 'identity', use 'keyword' to get keyword properties.
- :value-fn fn Function to transform values in JSON objects in the output. For each JSON property, value-fn is called with two arguments: the property name (transformed by key-fn) and the value. The return value of value-fn will replace the value in the output. The default value-fn returns the value unchanged.
- :decimal b If true use BigDecimal for decimal numbers instead of Double. Default is false.

```

(do
  (load-module :jsonl)
  (let [json (jsonl/write-str {:a 100 :b 200})]
    (jsonl/read-str json :key-fn keyword)))
=> ({:a 100 :b 200})

(do
  (load-module :jsonl)
  (let [json (jsonl/write-str [{:a 100 :b 200} {:a 100 :b 200}])]
    (jsonl/read-str json :key-fn keyword)))
=> ({:a 100 :b 200} {:a 100 :b 200})

(do
  (load-module :jsonl)
  (try-with [sw (io/string-writer)]

```

```
(println sw (jsonl/write-str {:a 100 :b 200}))
(println sw (jsonl/write-str {:a 101 :b 201}))
(println sw (jsonl/write-str {:a 102 :b 202}))
(flush sw)
(let [json @sw]
  (jsonl/read-str json :key-fn keyword)))
=> ({:a 100 :b 200} {:a 101 :b 201} {:a 102 :b 202})
```

SEE ALSO

[jsonl/write-str](#)

Writes the value 'val' to a JSON lines string.

top

jsonl/slurp

(jsonl/slurp in & options)

Slurps a list of JSON line strings from the input 'in' and returns it as a list of Venice data types.

'in' may be a:

- string
- bytebuf
- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.nio.file.Path`
- `java.io.InputStream`
- `java.io.Reader`

Note: The caller is responsible for closing the in stream/reader!

Options:

:key-fn fn	Single argument function called on JSON property names; return value will replace the property names in the output. Default is 'identity', use 'keyword' to get keyword properties.
:value-fn fn	Function to transform values in JSON objects in the output. For each JSON property, value-fn is called with two arguments: the property name (transformed by key-fn) and the value. The return value of value-fn will replace the value in the output. The default value-fn returns the value unchanged.
:decimal b	If true use BigDecimal for decimal numbers instead of Double. Default is false.
:filter-fn fn	Single argument function called on every read value from a JSON line. If it returns true the value will be kept otherwise it will be skipped. The filter is applied after the 'key-fn' and the 'value-fn' have been applied to the line data value.
:encoding e	e.g :encoding :utf-8, defaults to :utf-8

`jsonl/slurp` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

```
(do
  (load-module :jsonl)
  (let [file (io/temp-file "data-" ".jsonl")]
    (io/delete-file-on-exit file)
    (try-with [wr (io/buffered-writer file)]
      (jsonl/spit wr [{:a 100 :b 200} {:a 101 :b 201} {:a 102 :b 202}]))
    (flush wr))
    (try-with [rd (io/buffered-reader file)]
      (jsonl/slurp rd :key-fn keyword))))
=> ({:a 100 :b 200} {:a 101 :b 201} {:a 102 :b 202})
```

```
;; slurp JSON Lines applying mapping functions and a filter on the lines
(do
```

```
(load-module :jsonl)
(let [file (io/temp-file "data-" ".jsonl")
      now (time/local-date-time)]
  (io/delete-file-on-exit file)
  (try-with [wr (io/buffered-writer file)]
    (jsonl/spit wr [{:a 100 :b (time/plus now :days 1) :c 10.12M}
                   {:a 101 :b (time/plus now :days 2) :c 20.12M}
                   {:a 100 :b (time/plus now :days 3) :c 30.12M}]))
  (flush wr))
(try-with [rd (io/buffered-reader file)]
  (jsonl/slurp rd :key-fn keyword
               :value-fn (fn [k v]
                           (case k
                             :b (time/local-date-time-parse v :iso)
                             :c (decimal v)
                             v))
               :filter-fn #(= 100 (:a %)))))
=> ({:a 100 :b 2024-08-28T22:14:17.339 :c 10.12M} {:a 100 :b 2024-08-30T22:14:17.339 :c 30.12M})
```

SEE ALSO

[jsonl/read-str](#)

Reads a JSON line string 's' and returns it as a Venice data type.

[jsonl/lazy-seq-slurper](#)

Returns a lazy sequence of the parsed JSON line strings from the input 'in'.

[top](#)

jsonl/spit

(jsonl/spit out val & options)

Spits the JSON Lines converted value 'val' to the output 'out'.

The 'out' may be a:

- `java.io.File`, e.g: `(io/file "/temp/foo.json")`
- `java.nio.Path`
- `java.io.OutputStream`
- `java.io.Writer`

Note: The caller is responsible for closing the out stream/writer!

Any reasonable Venice value like string, integer, long, double, decimal, boolean, list, vector, set, or map can be passed. Sequences like list or vector are converted to multiple JSON lines, one line for each value in the sequence. All other types are converted to a single JSON line.

Options:

:decimal-as-double b If true emit a decimal as double else as string. Defaults to false.

:append true/false e.g.: `:append true`, defaults to false

:encoding e e.g: `encoding :utf-8`, defaults to `:utf-8`

`jsonl/spit` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

```
(do
  (load-module :jsonl)
  (let [file (io/temp-file "data-" ".jsonl")]
    (io/delete-file-on-exit file)
    (try-with [wr (io/buffered-writer file)]
      (jsonl/spit wr [{:a 100 :b 200} {:a 101 :b 201} {:a 102 :b 202}]))
```



```

    (flush wr))
;; print the json lines data
(println (io/slurp file :encoding :utf-8)))
{"a":100,"b":200}
{"a":101,"b":201}
{"a":102,"b":202}
=> nil

;; spit a list of json lines (linefeeds are added implicitly )
(do
  (load-module :jsonl)
  (let [file (io/temp-file "data-" ".jsonl")]
    (io/delete-file-on-exit file)
    (try-with [wr (io/buffered-writer file)]
      (jsonl/spit wr [{"a" 100, "b" 200}
                     {"a" 101, "b" 201}
                     {"a" 102, "b" 202}]))
    (flush wr))
;; print the json lines data
(println (io/slurp file :encoding :utf-8)))
{"a":100,"b":200}
{"a":101,"b":201}
{"a":102,"b":202}
=> nil

;; spit a list of json lines line by line (linefeeds must be added explicitly)
(do
  (load-module :jsonl)
  (let [file (io/temp-file "data-" ".jsonl")]
    (io/delete-file-on-exit file)
    (try-with [wr (io/buffered-writer file)]
      (jsonl/spit wr {"a" 100, "b" 200})
      (println wr)
      (jsonl/spit wr {"a" 101, "b" 201})
      (println wr)
      (jsonl/spit wr {"a" 102, "b" 202})
      (flush wr))
    ;; print the json lines data
    (println (io/slurp file :encoding :utf-8)))
{"a":100,"b":200}
{"a":101,"b":201}
{"a":102,"b":202}
=> nil

```

SEE ALSO

[jsonl/write-str](#)

Writes the value 'val' to a JSON lines string.

[jsonl/slurp](#)

Slurps a list of JSON line strings from the input 'in' and returns it as a list of Venice data types.

[top](#)

jsonl/spitln

```
(jsonl/spitln out val & options)
```

Spits the JSON Lines converted value 'val' to the output 'out' and adds a new line after the last emitted line.

This function is useful when lines are spitted to a stream/writer line by line.

The 'out' may be a:

- `java.io.File`, e.g.: `(io/file "/temp/foo.json")`
- `java.nio.Path`
- `java.io.OutputStream`
- `java.io.Writer`

Note: The caller is responsible for closing the out stream/writer!

Any reasonable Venice value like string, integer, long, double, decimal, boolean, list, vector, set, or map can be passed. Sequences like list or vector are converted to multiple JSON lines, one line for each value in the sequence. All other types are converted to a single JSON line.

Options:

:decimal-as-double b If true emit a decimal as double else as string. Defaults to false.

:append true/false e.g.: `:append true`, defaults to false

:encoding e e.g. `:encoding utf-8`, defaults to `:utf-8`

`jsonl/spitln` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

```
;; spit a list of json lines line by line
(do
  (load-module :jsonl)
  (let [file (io/temp-file "data-" ".jsonl")]
    (io/delete-file-on-exit file)
    (try-with [wr (io/buffered-writer file)]
      (jsonl/spitln wr {"a" 100, "b" 200})
      (jsonl/spitln wr {"a" 101, "b" 201})
      (jsonl/spit wr {"a" 102, "b" 202})      ;; last line no LF
      (flush wr))
    ;; print the json lines from the written file
    (println (io/slurp file :encoding :utf-8))))
{"a":100,"b":200}
{"a":101,"b":201}
{"a":102,"b":202}
=> nil
```

SEE ALSO

[jsonl/write-str](#)

Writes the value 'val' to a JSON lines string.

[jsonl/slurp](#)

Slurps a list of JSON line strings from the input 'in' and returns it as a list of Venice data types.

[top](#)

jsonl/write-str

`(jsonl/write-str val & options)`

Writes the value 'val' to a JSON lines string.

Any reasonable Venice value like string, integer, long, double, decimal, boolean, list, vector, set, or map can be passed. Sequences like list or vector are converted to multiple JSON lines, one line for each value in the sequence. All other types are converted to a single JSON line.

Options:

:decimal-as-double b If true emit a decimal as double else as string. Defaults to false

```
(do
  (load-module :jsonl)
```

```
(println (jsonl/write-str {:a 100 :b 200})))
{"a":100,"b":200}
=> nil

(do
  (load-module :jsonl)
  (println (jsonl/write-str [{:a 100 :b 200}
                             {:a 101 :b 201}
                             {:a 102 :b 202}])))
{"a":100,"b":200}
{"a":101,"b":201}
{"a":102,"b":202}
=> nil
```

SEE ALSO

[jsonl/spit](#)

Spits the JSON Lines converted value 'val' to the output 'out'.

[jsonl/read-str](#)

Reads a JSON line string 's' and returns it as a Venice data type.

[top](#)

jtokkit/count-tokens

```
(count-tokens encoding text)
```

Encodes the given text into a list of token ids and returns the number of tokens.

```
(do
  (load-module :jtokkit ['jtokkit :as 'jt])
  (-> (jt/encoding :GPT_3_5_TURBO)
      (jt/count-tokens "hello world")))
```

SEE ALSO

[jtokkit/encoding](#)

Returns the encoding with the given encoding or model type returns nil

[jtokkit/encoding-types](#)

Returns the defined encoding types. Actually from the enum type :com.knuddels.jtokkit.api.EncodingType.

[jtokkit/model-types](#)

Returns the defined model types. Actually from the enum type :com.knuddels.jtokkit.api.ModelType.

[jtokkit/encode](#)

Encodes the given text into a list of token ids.

[top](#)

jtokkit/encode

```
(encode encoding text)
```

Encodes the given text into a list of token ids.

```
(do
  (load-module :jtokkit ['jtokkit :as 'jt])
  (-> (jt/encoding :GPT_3_5_TURBO)
    (jt/encode "hello world")))
```

SEE ALSO

[jtokkit/encoding](#)

Returns the encoding with the given encoding or model type returns nil

[jtokkit/encoding-types](#)

Returns the defined encoding types. Actually from the enum type :com.knuddels.jtokkit.api.EncodingType.

[jtokkit/model-types](#)

Returns the defined model types. Actually from the enum type :com.knuddels.jtokkit.api.ModelType.

[jtokkit/count-tokens](#)

Encodes the given text into a list of token ids and returns the number of tokens.

[top](#)

jtokkit/encoding

(encoding type)

Returns the encoding with the given encoding or model type returns `nil`

```
(do
  (load-module :jtokkit ['jtokkit :as 'jt])
  ;; for a list of encoding types see `(jtokkit/encoding-types)`
  (jt/encoding :CL100K_BASE))
```

```
(do
  (load-module :jtokkit ['jtokkit :as 'jt])
  ;; for a list of model types see `(jtokkit/model-types)`
  (jt/encoding :GPT_3_5_TURBO))
```

SEE ALSO

[jtokkit/encode](#)

Encodes the given text into a list of token ids.

[jtokkit/encoding-types](#)

Returns the defined encoding types. Actually from the enum type :com.knuddels.jtokkit.api.EncodingType.

[jtokkit/model-types](#)

Returns the defined model types. Actually from the enum type :com.knuddels.jtokkit.api.ModelType.

[jtokkit/count-tokens](#)

Encodes the given text into a list of token ids and returns the number of tokens.

[top](#)

jtokkit/encoding-types

(encoding-types)

Returns the defined encoding types. Actually from the enum type :com.knuddels.jtokkit.api.EncodingType.

```
(do
  (load-module :jtokkit ['jtokkit :as 'jt])
  (jt/encoding-types))
```

SEE ALSO

[jtokkit/encode](#)

Encodes the given text into a list of token ids.

[jtokkit/model-types](#)

Returns the defined model types. Actually from the enum type :com.knuddels.jtokkit.api.ModelType.

[top](#)

jtokkit/model-types

```
(model-types)
```

Returns the defined model types. Actually from the enum type :com.knuddels.jtokkit.api.ModelType.

```
(do
  (load-module :jtokkit ['jtokkit :as 'jt])
  (jt/model-types))
```

SEE ALSO

[jtokkit/encode](#)

Encodes the given text into a list of token ids.

[jtokkit/encoding-types](#)

Returns the defined encoding types. Actually from the enum type :com.knuddels.jtokkit.api.EncodingType.

[top](#)

just

```
(just x)
```

Creates a wrapped x, that is dereferenceable

```
(just 10)
=> (just 10)

(just "10")
=> (just "10")

(deref (just 10))
=> 10
```

[top](#)

just?

```
(just? x)
```

Returns true if x is of type just

```
(just? (just 1))  
=> true
```

top

juxt

```
(juxt f)  
(juxt f g)  
(juxt f g h)  
(juxt f g h & fs)
```

Takes a set of functions and returns a fn that is the juxtaposition of those fns. The returned fn takes a variable number of args, and returns a vector containing the result of applying each fn to the args (left-to-right).

```
((juxt a b c) x) => [(a x) (b x) (c x)]
```

```
((juxt first last) '(1 2 3 4))  
=> [1 4]
```

```
(do  
  (defn index-by [coll key-fn]  
    (into {} (map (juxt key-fn identity) coll)))  
  
  (index-by [{:id 1 :name "foo"}  
             {:id 2 :name "bar"}  
             {:id 3 :name "baz"}]  
            :id))  
=> {1 {:name "foo" :id 1} 2 {:name "bar" :id 2} 3 {:name "baz" :id 3}}
```

top

keep

```
(keep f coll)
```

Returns a sequence of the non-nil results of `(f item)`. Note, this means false return values will be included. `f` must be free of side-effects. Returns a transducer when no collection is provided.

```
(keep even? (range 1 4))  
=> (false true false)
```

```
(keep (fn [x] (if (odd? x) x)) (range 4))  
=> (1 3)
```

```
(keep #{3 5 7} '(1 3 5 7 9))  
=> (3 5 7)
```

top

key

```
(key e)
```

Returns the key of the map entry.

```
(key (find {:a 1 :b 2} :b))  
=> :b
```

```
(key (first (entries {:a 1 :b 2 :c 3})))  
=> :a
```

SEE ALSO

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[entries](#)

Returns a collection of the map's entries.

[val](#)

Returns the val of the map entry.

[keys](#)

Returns a collection of the map's keys.

[top](#)

keys

```
(keys map)
```

Returns a collection of the map's keys.

Please note that the functions 'keys' and 'vals' applied to the same map are not guaranteed not return the keys and vals in the same order!

To achieve this, keys and vals can be calculated based on the map's entry list:

```
(let [e (entries {:a 1 :b 2 :c 3})]  
  (println (map key e))  
  (println (map val e)))
```

```
(keys {:a 1 :b 2 :c 3})  
=> (:a :b :c)
```

SEE ALSO

[vals](#)

Returns a collection of the map's values.

[entries](#)

Returns a collection of the map's entries.

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[top](#)

keyword

```
(keyword name)
(keyword ns name)
```

Returns a keyword from the given name

```
(keyword "a")
=> :a
```

```
(keyword :a)
=> :a
```

```
(keyword :foo/a)
=> :foo/a
```

```
(keyword "foo" "a")
=> :foo/a
```

```
(keyword (. :java.time.Month :JANUARY)) ;; java enum to keyword
=> :JANUARY
```

```
(name :foo/a)
=> "a"
```

```
(namespace :foo/a)
=> "foo"
```

SEE ALSO

[name](#)

Returns the name string of a string, symbol, keyword, or function. If applied to a string it returns the string itself.

[namespace](#)

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

[top](#)

keyword?

```
(keyword? x)
```

Returns true if x is a keyword

```
(keyword? (keyword "a"))
=> true
```

```
(keyword? :a)
=> true
```

```
(keyword? nil)
=> false
```

```
(keyword? 'a)
=> false
```


kira/escape-html

```
(kira/escape-html val)
(kira/escape-html val f)
```

Returns a HTML escaped string. If the passed data is not of type string it will be converted first to a string using the 'str' function.

An optional function f transforms the value before being converted to a string and HTML escaped.

```
(do
  (ns test)
  (load-module :kira)

  (println (kira/eval "<div><%= (kira/escape-html formula) %></div>"
    { :formula "x > 100" })))

  (defn format [t] (time/format t "yyyy-MM-dd"))
  (println (kira/eval "<div><%= (kira/escape-html date test/format) %></div>"
    { :date (time/local-date 2000 8 1) }))))

<div>x &gt; 100</div>
<div>2000-08-01</div>
=> nil
```

SEE ALSO

[kira/escape-xml](#)

Returns an XML escaped string. If the passed data is not of type string it will be converted first to a string using the 'str' function.

kira/escape-xml

```
(kira/escape-xml val)
(kira/escape-xml val f)
```

Returns an XML escaped string. If the passed data is not of type string it will be converted first to a string using the 'str' function.

An optional function f transforms the value before being converted to a string and XML escaped.

```
(do
  (ns test)
  (load-module :kira)

  (println (kira/eval "<formula><%= (kira/escape-xml formula) %></formula>"
    { :formula "x > 100" })))

  (defn format [t] (time/format t "yyyy-MM-dd"))
  (println (kira/eval "<date><%= (kira/escape-xml date test/format) %></date>"
    { :date (time/local-date 2000 8 1) }))))

<formula>x &gt; 100</formula>
<date>2000-08-01</date>
=> nil
```

SEE ALSO

[kira/escape-html](#)

Returns a HTML escaped string. If the passed data is not of type string it will be converted first to a string using the 'str' function.

[top](#)

kira/eval

```
(kira/eval source)
(kira/eval source bindings)
(kira/eval source delimiters bindings)
```

Evaluate a template using the supplied bindings. The template source may be a string, or an I/O source such as a File, Reader or InputStream.

```
(do
  (ns test)
  (load-module :kira)

  (println (kira/eval "Hello <%= name %>" { :name "Alice" })))
  (println (kira/eval "1 + 2 = <%= (+ 1 2) %>"))
  (println (kira/eval "2 + 3 = <%= (print (+ 2 3)) %>"))
  (println (kira/eval "$#{=x}$ + ${=y}$ = ${= (+ x y) }$"
    ["${" "}"]
    {:x 4 :y 5})))

  (println (kira/eval "margin: <%= (if large 100 10) %>"
    { :large false })))
  (println (kira/eval "fruits: <%= (doseq [f fruits] %><%= f %> <%= ) %>"
    { :fruits '("apple" "peach") })))
  (println (kira/eval "fruits: <%= (doseq [f fruits] %><%= f %> <%= ) %>"
    { :fruits '("apple" "peach") })))

  (println (kira/eval "when: <%= (when large %>is large<%= ) %>"
    { :large true })))
  (println (kira/eval "if: <%= (if large (do %>100<%= ) (do %>1<%= )) %>"
    { :large true })))

  (println (kira/eval "<div><%= (kira/escape-html formula) %></div>"
    { :formula "12 < 15" })))

Hello Alice
1 + 2 = 3
2 + 3 = 5
4 + 5 = 9
margin: 10
fruits: apple peach
fruits: apple peach
when: is large
if: 100
<div>12 &lt; 15</div>
=> nil
```

SEE ALSO

[kira/fn](#)

Compile a template into a function that takes the supplied arguments. The template source may be a string, or an I/O source such as ...

[kira/escape-xml](#)

Returns an XML escaped string. If the passed data is not of type string it will be converted first to a string using the 'str' function.

[kira/escape-html](#)

Returns a HTML escaped string. If the passed data is not of type string it will be converted first to a string using the 'str' function.

kira/fn

```
(kira/fn args source)
(kira/fn args source delimiters)
```

Compile a template into a function that takes the supplied arguments. The template source may be a string, or an I/O source such as a File, Reader or InputStream.

```
(do
  (load-module :kira)

  (def hello (kira/fn [name] "Hello <%= name %>"))
  (println (hello "Alice")))
  (println (hello "Bob"))))
Hello Alice
Hello Bob
=> nil
```

SEE ALSO

[kira/eval](#)

Evaluate a template using the supplied bindings. The template source may be a string, or an I/O source such as a File, Reader or InputStream.

[kira/escape-xml](#)

Returns an XML escaped string. If the passed data is not of type string it will be converted first to a string using the 'str' function.

[kira/escape-html](#)

Returns a HTML escaped string. If the passed data is not of type string it will be converted first to a string using the 'str' function.

last

```
(last coll)
```

Returns the last element of coll.

```
(last nil)
=> nil
```

```
(last [])
=> nil
```

```
(last [1 2 3])
=> 3
```

```
(last '())
=> nil
```

```
(last '(1 2 3))
=> 3
```

```
(last "abc")
=> #\c
```

lazy-seq

```
(lazy-seq)
(lazy-seq f)
(lazy-seq seed f)
(lazy-seq head tail-lazy-seq)
```

Creates a new lazy sequence.

```
(lazy-seq)
```

empty lazy sequence

```
(lazy-seq f)
```

(theoretically) infinitely lazy sequence using a repeatedly invoked supplier function for each next value. The supplier function `f` is a no arg function. The sequence ends if the supplier function returns `nil`.

```
(lazy-seq seed f)
```

(theoretically) infinitely lazy sequence with a seed value and a supplier function to calculate the next value based on the previous. `f` is a single arg function. The sequence ends if the supplier function returns `nil`.

```
(lazy-seq head tail-lazy-seq)
```

Constructs a lazy sequence of a head element and a lazy sequence tail supplier.

```
; empty lazy sequence
```

```
(->> (lazy-seq)
      (doall))
```

```
=> ()
```

```
; lazy sequence with a supplier function producing random longs
```

```
(->> (lazy-seq rand-long)
      (take 4)
      (doall))
```

```
=> (1265497861596398311 3289801833227890895 1748726195181567411 5691426709478694436)
```

```
; lazy sequence with a constant value
```

```
(->> (lazy-seq (constantly 5))
      (take 4)
      (doall))
```

```
=> (5 5 5 5)
```

```
; lazy sequence with a seed value and a supplier function
```

```
; producing of all positive numbers (1, 2, 3, 4, ...)
```

```
(->> (lazy-seq 1 inc)
      (take 10)
      (doall))
```

```
=> (1 2 3 4 5 6 7 8 9 10)
```

```
; producing of all positive even numbers (2, 4, 6, ...)
```

```
(->> (lazy-seq 2 #(+ % 2))
      (take 10)
      (doall))
```

```
=> (2 4 6 8 10 12 14 16 18 20)
```

```
; lazy sequence as value producing function
```

```
(interleave [:a :b :c] (lazy-seq 1 inc))
```

```
=> (:a 1 :b 2 :c 3)
```

```

; lazy sequence with a mapping
(->> (lazy-seq 1 (fn [x] (do (println "realized" x)
                             (inc x)))))

    (take 10)
    (map #(* 10 %))
    (take 2)
    (doall))
realized 1
=> (10 20)

; finite lazy sequence from a vector
(->> (lazy-seq [1 2 3 4])
    (doall))
=> (1 2 3 4)

; finite lazy sequence with a supplier function that
; returns nil to terminate the sequence
(do
  (def counter (atom 5))
  (defn generate []
    (swap! counter dec)
    (if (pos? @counter) @counter nil))
  (doall (lazy-seq generate)))
=> (4 3 2 1)

; lazy sequence from a head element and a tail lazy
; sequence
(->> (cons -1 (lazy-seq 0 #(+ % 1)))
    (take 5)
    (doall))
=> (-1 0 1 2 3)

; lazy sequence from a head element and a tail lazy
; sequence
(->> (lazy-seq -1 (lazy-seq 0 #(+ % 1)))
    (take 5)
    (doall))
=> (-1 0 1 2 3)

; lazy sequence show its power to generate the Fibonacci sequence
(do
  (def fib (map first (lazy-seq [0N 1N] (fn [[a b]] [b (+ a b)]))))
  (doall (take 10 fib)))
=> (0N 1N 1N 2N 3N 5N 8N 13N 21N 34N)

```

SEE ALSO

[doall](#)

When lazy sequences are produced doall can be used to force any effects and realize the lazy sequence. Returns the realized items in a list!

[lazy-seq?](#)

Returns true if obj is a lazyseq

[cons](#)

Returns a new collection where x is the first element and coll is the rest.

[cycle](#)

Returns a lazy (infinite!) sequence of repetitions of the items in coll.

[repeat](#)

Returns a lazy sequence of x values or a collection with the value x repeated n times.

lazy-seq?

```
(lazy-seq? obj)
```

Returns true if obj is a lazyseq

```
(lazy-seq? (lazy-seq rand-long))  
=> true
```

SEE ALSO

[lazy-seq](#)

Creates a new lazy sequence.

let

```
(let [bindings*] exprs*)
```

Evaluates the expressions and binds the values to symbols in the new local context.

```
(let [x 1] x)  
=> 1
```

```
(let [x 1  
      y 2]  
  (+ x y))  
=> 3
```

```
;; Destructured list  
(let [[x y] '(1 2)]  
  (printf "x: %d, y: %d\n" x y))  
x: 1, y: 2  
=> nil
```

```
;; Destructured map  
(let [{:keys [width height title]  
       :or {width 640 height 500}  
       :as styles}  
      {:width 1000 :title "Title"}]  
  (println "width: " width)  
  (println "height: " height)  
  (println "title: " title)  
  (println "styles: " styles))  
width: 1000  
height: 500  
title: Title  
styles: {:width 1000 :title Title}  
=> nil
```

SEE ALSO

[letfn](#)

Takes a vector of function specs and a body, and generates a set of bindings of functions to their names. All of the names are available ...

[if-let](#)

bindings is a vector with 2 elements: binding-form test.

[when-let](#)

bindings is a vector with 2 elements: binding-form test.

[binding](#)

Evaluates the expressions and binds the values to dynamic (thread-local) symbols

[top](#)

letfn

```
(letfn [fnspec*] exprs*)
```

Takes a vector of function specs and a body, and generates a set of bindings of functions to their names. All of the names are available in all of the definitions of the functions, as well as the body.

fnspec ==> (fname [params*] exprs) or (fname ([params*] exprs)+)

```
(letfn [(foo [] "abc")] (foo))
```

is equivalent to

```
(let [foo (fn [] "abc")] (foo))
```

```
(letfn [(foo [] "abc")
        (bar [] (str (foo) "def"))]
  (bar))
=> "abcdef"
```

SEE ALSO

[let](#)

Evaluates the expressions and binds the values to symbols in the new local context.

[top](#)

license

```
(license)
```

Returns the Venice license text.

```
(println (license))
```

[top](#)

license-all

```
(license-all)
```

Returns the Venice license text with all 3rd party licenses.

```
(println (license-all))
```

[top](#)

list

```
(list & items)
```

Creates a new list containing the items.

```
(list)
```

```
=> ()
```

```
(list 1 2 3)
```

```
=> (1 2 3)
```

```
(list 1 2 3 [:a :b])
```

```
=> (1 2 3 [:a :b])
```

[top](#)

list*

```
(list* args)
```

```
(list* a args)
```

```
(list* a b args)
```

```
(list* a b c args)
```

```
(list* a b c d & more)
```

Creates a new list containing the items prepended to the rest, the last of which will be treated as a collection.

```
(list* 1 '(2 3))
```

```
=> (1 2 3)
```

```
(list* 1 2 3 [4])
```

```
=> (1 2 3 4)
```

```
(list* 1 2 3 '(4 5))
```

```
=> (1 2 3 4 5)
```

```
(list* '(1 2) 3 [4])
```

```
=> ((1 2) 3 4)
```

```
(list* nil)
```

```
=> nil
```

```
(list* nil [2 3])
```

```
=> (nil 2 3)
```

```
(list* 1 2 nil)
```

```
=> (1 2)
```

SEE ALSO

[cons](#)

Returns a new collection where x is the first element and coll is the rest.

[conj](#)

Returns a new collection with the x, xs 'added'. (conj nil item) returns (item) and (conj item) returns item.

[concat](#)

Returns a list of the concatenation of the elements in the supplied collections.

[vector*](#)

Creates a new vector containing the items prepended to the rest, the last of which will be treated as a collection.

[top](#)

list-comp

```
(list-comp seq-exprs body-expr)
```

List comprehension. Takes a vector of one or more binding-form or collection-expr pairs, each followed by zero or more modifiers, and yields a collection of evaluations of expr.

Supported modifiers are: `:when` predicate

List comprehensions are used when multiple lists have to be processed down to a single list and some filtering has to be applied.

```
(list-comp [x (range 10)] x)
```

```
=> (0 1 2 3 4 5 6 7 8 9)
```

```
(list-comp [x (range 5)] (* x 2))
```

```
=> (0 2 4 6 8)
```

```
(list-comp [x (range 10) :when (odd? x)] x)
```

```
=> (1 3 5 7 9)
```

```
(list-comp [x (range 10) :when (odd? x)] (* x 2))
```

```
=> (2 6 10 14 18)
```

```
(list-comp [x (seq "abc") y [0 1 2]] [x y])
```

```
=> ([#\a 0] [#\a 1] [#\a 2] [#\b 0] [#\b 1] [#\b 2] [#\c 0] [#\c 1] [#\c 2])
```

SEE ALSO

[mapcat](#)

Returns the result of applying concat to the result of applying map to fn and colls. Thus function fn should return a collection.

[doseq](#)

Repeatedly executes body (presumably for side-effects) with bindings and filtering as provided by list-comp. Does not retain the head ...

[dotimes](#)

Repeatedly executes body with name bound to integers from 0 through n-1.

[top](#)

list?

```
(list? obj)
```

Returns true if obj is a list

```
(list? (list 1 2))
=> true
```

```
(list? '(1 2))
=> true
```

[top](#)

load-classpath-file

```
(load-classpath-file f)
(load-classpath-file f force)
(load-classpath-file f nsalias)
(load-classpath-file f force nsalias)
```

Sequentially read and evaluate the set of forms contained in the classpath file. The function is restricted to classpath files with the extension '.venice'.

Returns a tuple with the file's name and the keyword `:loaded` if the file has been successfully loaded or `:already-loaded` if the file has been already loaded. Throws an exception on any loading error.

With 'force' set to `false` (the default) the file is only loaded once and interpreted once. Subsequent load attempts will be skipped. With 'force' set to `true` it is always loaded and interpreted.

Loaded files are cached by Venice and subsequent loads are just skipped. To enforce a reload call the file load with the force flag set to true:

```
(load-classpath-file "com/github/jlangch/venice/test.venice" true)
```

An optional namespace alias can be passed: `(load-classpath-file "com/github/jlangch/venice/test.venice" ['test :as 't])`

`load-classpath-file` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

```
(do
  (load-classpath-file "com/github/jlangch/venice/test-support.venice")
  (test-support/test-fn "hello"))
=> "test: hello"
```

```
(do
  (load-classpath-file "com/github/jlangch/venice/test-support.venice")
  (test-support/test-fn "hello")
  ; reload the classpath file
  (ns-remove 'test-support)
  (load-classpath-file "com/github/jlangch/venice/test-support.venice" true)
  (test-support/test-fn "hello"))
=> "test: hello"
```

;; namespace aliases

```
(do
  (load-classpath-file "com/github/jlangch/venice/test-support.venice" ['test-support :as 't])
  (t/test-fn "hello"))
=> "test: hello"
```

SEE ALSO

[load-file](#)

Sequentially read and evaluate the set of forms contained in the file.

[load-string](#)

Sequentially read and evaluate the set of forms contained in the string.

[load-module](#)

Loads a Venice predefined extension module.

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

[top](#)

load-file

```
(load-file f)
(load-file f force)
(load-file f nsalias)
(load-file f force nsalias)
```

Sequentially read and evaluate the set of forms contained in the file.

If the file is found on one of the defined load paths it is read and the forms it contains are evaluated. If the file is not found an exception is raised.

Returns a tuple with the file's name and the keyword `:loaded` if the file has been successfully loaded or `:already-loaded` if the file has been already loaded. Throws an exception on any loading error.

With 'force' set to `false` (the default) the file is only loaded once and interpreted once. Subsequent load attempts will be skipped. With 'force' set to `true` it is always loaded and interpreted.

The function is restricted to load files with the extension '.venice'. If the file extension is missing '.venice' will be implicitly added.

An optional namespace alias can be passed: `(load-file "coffee.venice" ['coffee :as 'c])`

`load-file` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

```
;; With load-paths: [/users/foo/scripts]
;;      -> loads: /users/foo/scripts/coffee.venice
(load-file "coffee")

;; With load-paths: [/users/foo/scripts]
;;      -> loads: /users/foo/scripts/coffee.venice
(load-file "coffee.venice")

;; With load-paths: [/users/foo/scripts]
;;      -> loads: /users/foo/scripts/beverages/coffee.venice
(load-file "beverages/coffee")

;; With load-paths: [/users/foo/resources.zip]
;;      -> loads: /users/foo/resources.zip!beverages/coffee.venice
(load-file "beverages/coffee")
```

SEE ALSO

[load-classpath-file](#)

Sequentially read and evaluate the set of forms contained in the classpath file. The function is restricted to classpath files with ...

[load-string](#)

Sequentially read and evaluate the set of forms contained in the string.

[load-module](#)

Loads a Venice predefined extension module.

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

[top](#)

load-module

```
(load-module m)
(load-module m force)
(load-module m nsalias)
(load-module m force nsalias)
```

Loads a Venice predefined extension module.

Returns a tuple with the module's name and the keyword `:loaded` if the module has been successfully loaded or `:already-loaded` if the module has been already loaded. Throws an exception on any loading error.

With 'force' set to `false` (the default) the module is only loaded once and interpreted once. Subsequent load attempts will be skipped. With 'force' set to `true` it is always loaded and interpreted.

Loaded modules are cached by Venice and subsequent loads are just skipped. To enforce a reload call the module load with the force flag set to true: `(load-module :hexdump true)`

An optional namespace alias can be passed: `(load-module :hexdump ['hexdump :as 'h])`

`load-module` supports load paths. See the `loadpath/paths` doc for a description of the *load path* feature.

```
(load-module :trace)

;; loading the :trace modul and define a ns alias 't for namespace
;; 'trace used in the module
(load-module :trace ['trace :as 't])

;; reloading a module
(do
  (load-module :trace)
  ; reload the module
  (ns-remove 'trace)
  (load-module :trace true))

;; namespace aliases
(do
  (load-module :hexdump ['hexdump :as 'h])
  (h/dump (range 32 64)))

;; dynamically load a module
(let [mname (keyword "hexdump")]
  (load-module mname))
```

SEE ALSO

[load-file](#)

Sequentially read and evaluate the set of forms contained in the file.

[load-classpath-file](#)

Sequentially read and evaluate the set of forms contained in the classpath file. The function is restricted to classpath files with ...

[load-string](#)

Sequentially read and evaluate the set of forms contained in the string.

[loaded-modules](#)

Returns the names of the loaded modules.

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

[doc](#)

Prints documentation for a var or special form given x as its name. Prints the definition of custom types.

load-string

```
(load-string s)
```

Sequentially read and evaluate the set of forms contained in the string.

```
(do
  (load-string "(def x 1)")
  (+ x 2))
=> 3
```

SEE ALSO

[load-file](#)

Sequentially read and evaluate the set of forms contained in the file.

[load-classpath-file](#)

Sequentially read and evaluate the set of forms contained in the classpath file. The function is restricted to classpath files with ...

[loaded-modules](#)

Returns the names of the loaded modules.

loaded-modules

```
(loaded-modules)
```

Returns the names of the loaded modules.

SEE ALSO

[load-module](#)

Loads a Venice predefined extension module.

loadpath/normalize

```
(loadpath/normalize f)
```

Normalize a relative file regarding the load paths.

With the load paths: `["/Users/foo/img.png", "/Users/foo/resources"]`

- `(loadpath/normalize "img.png") -> "/Users/foo/img.png"`
- `(loadpath/normalize "test.json") -> "/Users/foo/resources/test.json"`
- `(loadpath/normalize "/tmp/data.json") -> "/tmp/data.json"`

SEE ALSO

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

[loadpath/unrestricted?](#)

Returns true if the load paths are unrestricted.

[top](#)

loadpath/paths

(loadpath/paths)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the application level. They are passed as part of the sandbox to the Venice evaluator.

The functions that support load paths try sequentially every load path to access files. If a load path is a ZIP file, files can be read from within that ZIP file.

Example:

```
/Users/foo/demo
|
+--- resources.zip
|
+--- /data
    |
    +--- config.json
    |
    +--- /scripts
        |
        +--- script1.venice
```

With a load path configuration of `["/Users/foo/demo/resources.zip", "/Users/foo/demo/data"]`

- `(io/slurp "config.json")` -> slurps `/Users/foo/demo/data/config.json`
- `(io/slurp "scripts/script1.venice")` -> slurps `/Users/foo/demo/data/scripts/script1.venice`
- `(io/slurp "img1.png")` -> slurps `/Users/foo/demo/resources.ziplimg1.png`

I/O functions with support for load paths:

- `load-file`
- `io/slurp`
- `io/slurp-lines`
- `io/spit`
- `io/file-in-stream`
- `io/file-out-stream`
- `io/delete-file`

To enforce a Venice script to read/write files on the load paths only:

- Define a custom sandbox
- Disable all I/O functions
- Enable the I/O functions that support load paths

SEE ALSO

[loadpath/unrestricted?](#)

Returns true if the load paths are unrestricted.

[loadpath/normalize](#)

Normalize a relative file regarding the load paths.

[load-file](#)

Sequentially read and evaluate the set of forms contained in the file.

[top](#)

loadpath/unrestricted?

(loadpath/unrestricted?)

Returns true if the load paths are unrestricted.

SEE ALSO

[loadpath/paths](#)

Returns the list of the defined load paths. A load path is either a file, a ZIP file, or a directory. Load paths are defined at the ...

[loadpath/normalize](#)

Normalize a relative file regarding the load paths.

[top](#)

lock

(lock)

Creates a new lock object.

The lock object implements the Java `AutoClosable` interface thus it can be used with try-with-resources.

```
(let [l (lock)]
  (acquire l)
  ;; do something
  (release l))
=> nil
```

```
(let [l (lock)]
  (try-with [l (acquire l)]
    ;; do something
  ))
=> nil
```

SEE ALSO

[acquire](#)

Acquires a lock, blocking until the lock is available.

[try-acquire](#)

Acquires a lock within the given timeout time. Without a timeout returns immediately if the lock is not available.

[release](#)

Releases a lock.

[locked?](#)

Returns true if the lock is in use else false.

[lock?](#)

Returns true if o is a lock object else false.

lock?

```
(lock? o)
```

Returns `true` if `o` is a lock object else `false` .

```
(let [l (lock)]  
  (lock? l))  
=> true
```

SEE ALSO

[acquire](#)

Acquires a lock, blocking until the lock is available.

[try-acquire](#)

Acquires a lock within the given timeout time. Without a timeout returns immediately if the lock is not available.

[release](#)

Releases a lock.

[locked?](#)

Returns true if the lock is in use else false.

locked?

```
(locked? lock)
```

Returns `true` if the lock is in use else `false` .

```
(let [l (lock)]  
  (acquire l)  
  (locked? l))  
=> true
```

SEE ALSO

[lock](#)

Creates a new lock object.

[acquire](#)

Acquires a lock, blocking until the lock is available.

[try-acquire](#)

Acquires a lock within the given timeout time. Without a timeout returns immediately if the lock is not available.

[release](#)

Releases a lock.

locking


```
(locking x & exprs)
```

Executes 'exprs' in an implicit do, while holding the monitor of 'x'. Will release the monitor of 'x' in all circumstances. Locking operates like the synchronized keyword in Java.

```
(do
  (def x 1)
  (locking x
    (println 100)
    (println 200)))
100
200
=> nil

;; Locks are reentrant
(do
  (def x 1)
  (locking x
    (locking x
      (println "in"))
    (println "out")))
in
out
=> nil

(do
  (defn log [msg] (locking log (println msg)))
  (log "message"))
message
=> nil
```

[top](#)

log

```
(log x)
```

Returns the natural logarithm (base e) of a value

```
(log 10)
=> 2.302585092994046
```

```
(log 10.23)
=> 2.325324579963535
```

```
(log 10.23M)
=> 2.325324579963535
```

SEE ALSO

[log10](#)

Returns the base 10 logarithm of a value

[log2](#)

Returns the base 2 logarithm of a value

log10

(log10 x)

Returns the base 10 logarithm of a value

```
(log10 10)
```

```
=> 1.0
```

```
(log10 10.23)
```

```
=> 1.0098756337121602
```

```
(log10 10.23M)
```

```
=> 1.0098756337121602
```

```
;; the number of digits
```

```
(long (+ (floor (log10 235)) 1))
```

```
=> 3
```

SEE ALSO

[log](#)

Returns the natural logarithm (base e) of a value

[log2](#)

Returns the base 2 logarithm of a value

log2

(log2 x)

Returns the base 2 logarithm of a value

```
(log2 8)
```

```
=> 3.0
```

```
(log2 10.23)
```

```
=> 3.354734239970604
```

```
(log2 10.23M)
```

```
=> 3.354734239970604
```

SEE ALSO

[log](#)

Returns the natural logarithm (base e) of a value

[log10](#)

Returns the base 10 logarithm of a value

logo

(logo)

Returns the Venice logo, a map with the keys `:name`, `:mimetype`, and `:data`

(logo)

```
(let [l (logo)]
  (io/spit (io/file (:name l)) (:data l)))
```

[top](#)

long

(long x)

Converts to long

```
(long 1)
=> 1
```

```
(long nil)
=> 0
```

```
(long false)
=> 0
```

```
(long true)
=> 1
```

```
(long 1.2F)
=> 1
```

```
(long 1.2)
=> 1
```

```
(long 1.2M)
=> 1
```

```
(long "1")
=> 1
```

```
(long (char "A"))
=> 65
```

[top](#)

long-array

(long-array coll)

```
(long-array len)
(long-array len init-val)
```

Returns an array of Java primitive longs containing the contents of coll or returns an array with the given length and optional init value.

To create an array of :java.lang.Long use:

```
(make-array :java.lang.Long 3)
```

```
(long-array '(1 2 3))
=> [1, 2, 3]
```

```
(long-array '(1I 2 3.2 3.56M))
=> [1, 2, 3, 3]
```

```
(long-array 10)
=> [0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
```

```
(long-array 10 42)
=> [42, 42, 42, 42, 42, 42, 42, 42, 42, 42]
```

SEE ALSO

[java-long-list](#)

Converts a Venice list/vector to a Java Long list

[top](#)

long?

```
(long? n)
```

Returns true if n is a long

```
(long? 4)
=> true
```

```
(long? 4I)
=> false
```

```
(long? 3.1)
=> false
```

```
(long? true)
=> false
```

```
(long? nil)
=> false
```

```
(long? {})
=> false
```

[top](#)

loop

```
(loop [bindings*] exprs*)
```

Evaluates the exprs and binds the bindings. Creates a recursion point with the bindings.

```
;; tail recursion
(loop [x 10]
  (when (> x 1)
    (println x)
    (recur (- x 2)))))
10
8
6
4
2
=> nil

;; tail recursion
(do
  (defn sum [n]
    (loop [cnt n acc 0]
      (if (zero? cnt)
        acc
        (recur (dec cnt) (+ acc cnt))))))
  (sum 10000))
=> 50005000
```

SEE ALSO

[recur](#)

Evaluates the exprs and rebinds the bindings of the recursion point to the values of the exprs. The recur expression must be at the ...

[top](#)

macro?

```
(macro? x)
```

Returns true if x is a macro

```
(macro? and)
=> true
```

[top](#)

macroexpand

```
(macroexpand form)
```

If form represents a macro form, returns its expansion, else returns form.

To recursively expand all macros in a form use `(macroexpand-all form)`.

```
(macroexpand '(> c (+ 3) (* 2)))
=> (* (+ c 3) 2)
```

SEE ALSO

[defmacro](#)

Macro definition

[macroexpand-all](#)

Recursively expands all macros in the form.

[top](#)

macroexpand-all

(macroexpand-all form)

Recursively expands all macros in the form.

```
(macroexpand-all '(and true true))
=> (let [cond__29039__auto true] (if cond__29039__auto true cond__29039__auto))

(macroexpand-all '(and true (or true false) true))
=> (let [cond__29067__auto true] (if cond__29067__auto (let [cond__29067__auto (let [cond__29068__auto true]
(if cond__29068__auto cond__29068__auto false))] (if cond__29067__auto true cond__29067__auto))
cond__29067__auto))

(macroexpand-all '(let [n 5] (cond (< n 0) -1 (> n 0) 1 :else 0)))
=> (let [n 5] (if (< n 0) -1 (if (> n 0) 1 (if :else 0 nil))))
```

SEE ALSO

[macroexpand](#)

If form represents a macro form, returns its expansion, else returns form.

[defmacro](#)

Macro definition

[top](#)

macroexpand-on-load?

(macroexpand-on-load?)

Returns true if `macroexpand-on-load` feature is enabled else false.

The activation of `macroexpand-on-load` (upfront macro expansion) results in 3x to 15x better performance. Upfront macro expansion can be activated through the `!macroexpand` command in the REPL.

```
(macroexpand-on-load?)
=> false
```

[top](#)

make-array

(make-array type len)

```
(make-array type dim &more-dims)
```

Returns an array of the given type and length

```
(str (make-array :long 5))  
=> "[0, 0, 0, 0, 0]"
```

```
(str (make-array :java.lang.Long 5))  
=> "[nil, nil, nil, nil, nil]"
```

```
(str (make-array :long 2 3))  
=> "[[0 0 0], [0 0 0]]"
```

```
(aset (make-array :java.lang.Long 5) 3 9999)  
=> [nil, nil, nil, 9999, nil]
```

top

map

```
(map f coll colls*)
```

Applies `f` to the set of first items of each `coll`, followed by applying `f` to the set of second items in each `coll`, until any one of the `colls` is exhausted. Any remaining items in other `colls` are ignored.

Returns a transducer when no collection is provided.

Note: if Java collections are used the mapper converts all mapped items back to Java data types to keep Java compatibility as much as possible!

To avoid this just convert the Java collection to a Venice collection. E.g.: `(into [] ...)`.

```
(map inc [1 2 3 4])  
=> (2 3 4 5)
```

```
(map + [1 2 3 4] [10 20 30 40])  
=> (11 22 33 44)
```

```
(map list '(1 2 3 4) '(10 20 30 40))  
=> ((1 10) (2 20) (3 30) (4 40))
```

```
(map vector (lazy-seq 1 inc) [10 20 30 40])  
=> ([1 10] [2 20] [3 30] [4 40])
```

```
(map (fn [[k v]] [k v]) {:a 1 :b 2})  
=> ([:a 1] [:b 2])
```

```
(map (fn [e] [(key e) (inc (val e))]) {:a 1 :b 2})  
=> ([:a 2] [:b 3])
```

```
(map inc #{1 2 3})  
=> (2 3 4)
```

```
;; Venice enforces Java types when using java collections instead  
;; of Venice collections!
```

```
;; -> The returned element type is a 'java.util.ArrayList'
```

```
;; and not a 'core/vector'
```

```
(->> (doto (. :java.util.ArrayList :new) (. :add 1) (. :add 2))  
      (map (fn [x] [(inc x)])) ;; map to a 'core/vector'  
      (first))
```

```
(type))
=> :java.util.ArrayList

;; Same example with a Venice collection!
;; -> The returned element type is a 'core/vector'
(->> [1 2]
      (map (fn [x] [(inc x)])) ;; map to a 'core/vector'
      (first)
      (type))
=> :core/vector
```

SEE ALSO

[filter](#)

Returns a collection of the items in coll for which (predicate item) returns logical true.

[reduce](#)

f should be a function of 2 arguments. If val is not supplied, returns the result of applying f to the first 2 items in coll, then ...

[map-indexed](#)

Returns a collection of applying f to 0 and the first item of coll, followed by applying f to 1 and the second item of coll, etc. until ...

[top](#)

map-entry

```
(map-entry key val)
```

Creates a new map entry

```
(map-entry :a 1)
=> [:a 1]

(key (map-entry :a 1))
=> :a

(val (map-entry :a 1))
=> 1

(entries {:a 1 :b 2 :c 3})
=> ([:a 1] [:b 2] [:c 3])
```

SEE ALSO

[map-entry?](#)

Returns true if m is a map entry

[entries](#)

Returns a collection of the map's entries.

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[key](#)

Returns the key of the map entry.

[val](#)

Returns the val of the map entry.

[top](#)

map-entry?

```
(map-entry? m)
```

Returns true if m is a map entry

```
(map-entry? (map-entry :a 1))  
=> true
```

```
(map-entry? (first (entries {:a 1 :b 2})))  
=> true
```

SEE ALSO

[map-entry](#)

Creates a new map entry

[entries](#)

Returns a collection of the map's entries.

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[top](#)

map-indexed

```
(map-indexed f coll)
```

Returns a collection of applying f to 0 and the first item of coll, followed by applying f to 1 and the second item of coll, etc. until coll is exhausted. Returns a stateful transducer when no collection is provided.

```
(map-indexed (fn [idx val] [idx val]) [:a :b :c])  
=> ([0 :a] [1 :b] [2 :c])
```

```
(map-indexed vector [:a :b :c])  
=> ([0 :a] [1 :b] [2 :c])
```

```
;; start at index 1 instead of zero  
(map-indexed #(vector (inc %1) %2) [:a :b :c])  
=> ([1 :a] [2 :b] [3 :c])
```

```
(map-indexed vector "abcdef")  
=> ([0 #\a] [1 #\b] [2 #\c] [3 #\d] [4 #\e] [5 #\f])
```

```
(map-indexed hash-map [:a :b :c])  
=> ({0 :a} {1 :b} {2 :c})
```

SEE ALSO

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[top](#)

map-invert

```
(map-invert m)
```

Returns the map with the vals mapped to the keys.

```
(map-invert {:a 1 :b 2 :c 3})  
=> {1 :a 2 :b 3 :c}
```

[top](#)

map-keys

```
(map-keys f m)
```

Applies function f to the keys of the map m.

```
(map-keys name {:a 1 :b 2 :c 3})  
=> {"a" 1 "b" 2 "c" 3}
```

SEE ALSO

[map-vals](#)

Applies function f to the values of the map m.

[map-invert](#)

Returns the map with the vals mapped to the keys.

[top](#)

map-vals

```
(map-vals f m)
```

Applies function f to the values of the map m.

```
(map-vals inc {:a 1 :b 2 :c 3})  
=> {:a 2 :b 3 :c 4}  
  
(map-vals :len {:a {:col 1 :len 10} :b {:col 2 :len 20} :c {:col 3 :len 30}})  
=> {:a 10 :b 20 :c 30}
```

SEE ALSO

[map-keys](#)

Applies function f to the keys of the map m.

[map-invert](#)

Returns the map with the vals mapped to the keys.

[top](#)

map?

```
(map? obj)
```

Returns true if obj is a map

```
(map? {:a 1 :b 2})  
=> true
```

[top](#)

mapcat

```
(mapcat fn & colls)
```

Returns the result of applying concat to the result of applying map to fn and colls. Thus function fn should return a collection.

```
(mapcat identity [[1 2 3] [4 5 6] [7 8 9]])  
=> (1 2 3 4 5 6 7 8 9)
```

```
(mapcat identity [[1 2 [3 4]] [5 6 [7 8]]])  
=> (1 2 [3 4] 5 6 [7 8])
```

```
(mapcat reverse [[3 2 1] [6 5 4] [9 8 7]])  
=> (1 2 3 4 5 6 7 8 9)
```

```
(mapcat list [:a :b :c] [1 2 3])  
=> (:a 1 :b 2 :c 3)
```

```
(mapcat #(remove even? %) [[1 2] [2 2] [2 3]])  
=> (1 3)
```

```
(mapcat #(repeat 2 %) [1 2])  
=> (1 1 2 2)
```

```
(mapcat (juxt inc dec) [1 2 3 4])  
=> (2 0 3 1 4 2 5 3)
```

```
;; Turn a frequency map back into a coll.  
(mapcat (fn [[x n]] (repeat n x)) {:a 2 :b 1 :c 3})  
=> (:a :a :b :c :c :c)
```

SEE ALSO

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[flatten](#)

Takes any nested combination of collections (lists, vectors, etc.) and returns their contents as a single, flat sequence. (flatten ...

[top](#)

mapv

```
(mapv f coll colls*)
```

Returns a vector consisting of the result of applying `f` to the set of first items of each `coll`, followed by applying `f` to the set of second items in each `coll`, until any one of the `colls` is exhausted. Any remaining items in other `colls` are ignored.

```
(mapv inc [1 2 3 4])  
=> [2 3 4 5]
```

```
(mapv + [1 2 3 4] [10 20 30 40])  
=> [11 22 33 44]
```

```
(mapv vector [1 2 3 4] [10 20 30 40])  
=> [[1 10] [2 20] [3 30] [4 40]]
```

SEE ALSO

[docoll](#)

Applies `f` to the items of the collection presumably for side effects. Returns `nil`.

[top](#)

match?

```
(match? s regex)
```

Returns `true` if the string `s` matches the regular expression `regex`.

The argument '`regex`' may be a string representing a regular expression or a `java.util.regex.Pattern`.

See the functions in the '`regex`' namespace if more than a simple regex match is required! E.g. `regex/matches?` performs much better on matching many strings against the same pattern:

```
(let [m (regex/matcher #"[0-9]+" "")]  
    (filter #(regex/matches? m %) ["100" "1a1" "200"])))
```

```
(match? "1234" "[0-9]+")  
=> true
```

```
(match? "1234ss" "[0-9]+")  
=> false
```

```
(match? "1234" #"[0-9]+")  
=> true
```

SEE ALSO

[not-match?](#)

Returns `true` if the string `s` does not match the regular expression `regex`.

[regex/matches?](#)

Attempts to match the entire region against the pattern. Returns `true` if the patterns matches the string else `false`.

[regex/matches-not?](#)

Attempts to match the entire region against the pattern. Returns `false` if the patterns matches the string else `true`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/matches](#)

Returns the matches, if any, for the matcher with the pattern of a string, using `java.util.regex.Matcher.matches()`.

[regex/find](#)

Returns the next regex match or nil if there is no further match. Returns nil if there is no match.

[regex/find-all](#)

Returns all regex matches as list or an empty list if there are no matches.

[top](#)

math/acos

```
(math/acos x)
```

Returns the arc cosine of a value; the returned angle is in the range `0.0` through `pi`

```
(math/acos 0.5)  
=> 1.0471975511965979
```

SEE ALSO

[math/cos](#)

Returns the trigonometric cosine of an angle given in radians

[math/asin](#)

Returns the arc sine of a value; the returned angle is in the range `-pi/2` through `pi/2`

[math/atan](#)

Returns the arc tangent of a value; the returned angle is in the range `-pi/2` through `pi/2`.

[top](#)

math/asin

```
(math/asin x)
```

Returns the arc sine of a value; the returned angle is in the range `-pi/2` through `pi/2`

```
(math/asin 0.8660254037844386)  
=> 1.0471975511965976
```

SEE ALSO

[math/sin](#)

Returns the trigonometric sine of an angle given in radians

[math/acos](#)

Returns the arc cosine of a value; the returned angle is in the range `0.0` through `pi`

[math/atan](#)

Returns the arc tangent of a value; the returned angle is in the range `-pi/2` through `pi/2`.

[top](#)

math/atan

```
(math/atan x)
```

Returns the arc tangent of a value; the returned angle is in the range `-pi/2` through `pi/2` .

```
(math/atan 1.7320508075688767)
=> 1.0471975511965976
```

SEE ALSO

[math/tan](#)

Returns the trigonometric tangent of an angle given in radians

[math/asin](#)

Returns the arc sine of a value; the returned angle is in the range `-pi/2` through `pi/2`

[math/acos](#)

Returns the arc cosine of a value; the returned angle is in the range `0.0` through `pi`

[top](#)

math/cos

```
(math/cos x)
```

Returns the trigonometric cosine of an angle given in radians

```
(math/cos (/ math/PI 3.0))
=> 0.5000000000000001
```

SEE ALSO

[math/sin](#)

Returns the trigonometric sine of an angle given in radians

[math/tan](#)

Returns the trigonometric tangent of an angle given in radians

[top](#)

math/mean

```
(math/mean x)
(math/mean x y)
(math/mean x y & more)
```

Returns the mean value of the values

```
(math/mean 10 20 30)
=> 20.0
```

```
(math/mean 1.4 3.6)
=> 2.5
```

```
(math/mean 2.8M 6.4M)
=> 4.6000000000000000M
```

SEE ALSO

[math/median](#)

Returns the median of the values

[math/standard-deviation](#)

Returns the standard deviation of the values for data sample type :population or :sample.

[math/quantile](#)

Returns the quantile [0.0 .. 1.0] of the values

[math/quartiles](#)

Returns the quartiles (1st, 2nd, and 3rd) of the values

[top](#)

math/median

```
(math/median coll)
```

Returns the median of the values

```
(math/median '(3 1 2))
=> 2.0
```

```
(math/median '(3 2 1 4))
=> 2.5
```

```
(math/median '(3.6 1.4 4.8))
=> 3.6
```

```
(math/median '(3.6M 1.4M 4.8M))
=> 3.6M
```

SEE ALSO

[math/mean](#)

Returns the mean value of the values

[math/standard-deviation](#)

Returns the standard deviation of the values for data sample type :population or :sample.

[math/quantile](#)

Returns the quantile [0.0 .. 1.0] of the values

[math/quartiles](#)

Returns the quartiles (1st, 2nd, and 3rd) of the values

[top](#)

math/quantile

```
(math/quantile q coll)
```

Returns the quantile [0.0 .. 1.0] of the values

```
(math/quantile 0.5 '(3, 7, 8, 5, 12, 14, 21, 13, 18))  
=> 12.0
```

```
(math/quantile 0.5 '(3, 7, 8, 5, 12, 14, 21, 15, 18, 14))  
=> 13.0
```

SEE ALSO

[math/mean](#)

Returns the mean value of the values

[math/median](#)

Returns the median of the values

[math/standard-deviation](#)

Returns the standard deviation of the values for data sample type :population or :sample.

[math/quartiles](#)

Returns the quartiles (1st, 2nd, and 3rd) of the values

[top](#)

math/quartiles

```
(math/quartiles coll)
```

Returns the quartiles (1st, 2nd, and 3rd) of the values

```
(math/quartiles '(3, 7, 8, 5, 12, 14, 21, 13, 18))  
=> (6.0 12.0 16.0)
```

```
(math/quartiles '(3, 7, 8, 5, 12, 14, 21, 15, 18, 14))  
=> (7.0 13.0 15.0)
```

SEE ALSO

[math/mean](#)

Returns the mean value of the values

[math/median](#)

Returns the median of the values

[math/standard-deviation](#)

Returns the standard deviation of the values for data sample type :population or :sample.

[math/quantile](#)

Returns the quantile [0.0 .. 1.0] of the values

[top](#)

math/sin

```
(math/sin x)
```

Returns the trigonometric sine of an angle given in radians


```
(math/sin (/ math/PI 3.0))  
=> 0.8660254037844386
```

SEE ALSO

[math/cos](#)

Returns the trigonometric cosine of an angle given in radians

[math/tan](#)

Returns the trigonometric tangent of an angle given in radians

[top](#)

math/softmax

```
(math/softmax coll)
```

Softmax algorithm

```
(math/softmax [3.2 1.3 0.2 0.8])  
=> [0.7751495482986049 0.1159380476300716 0.03859242355646149 0.07031998051486205]
```

[top](#)

math/standard-deviation

```
(math/standard-deviation type coll)
```

Returns the standard deviation of the values for data sample type `:population` or `:sample`.

```
(math/standard-deviation :sample '(10 8 30 22 15))  
=> 9.055385138137417
```

```
(math/standard-deviation :population '(10 8 30 22 15))  
=> 8.099382692526634
```

```
(math/standard-deviation :sample '(1.4 3.6 7.8 9.0 2.2))  
=> 3.40587727318528
```

```
(math/standard-deviation :sample '(2.8M 6.4M 2.0M 4.4M))  
=> 1.942506971244462
```

SEE ALSO

[math/mean](#)

Returns the mean value of the values

[math/median](#)

Returns the median of the values

[math/quantile](#)

Returns the quantile [0.0 .. 1.0] of the values

[math/quartiles](#)

Returns the quartiles (1st, 2nd, and 3rd) of the values

math/tan

```
(math/tan x)
```

Returns the trigonometric tangent of an angle given in radians

```
(math/tan (/ math/PI 3.0))  
=> 1.7320508075688767
```

SEE ALSO

[math/sin](#)

Returns the trigonometric sine of an angle given in radians

[math/cos](#)

Returns the trigonometric cosine of an angle given in radians

math/to-degrees

```
(math/to-degrees x)
```

Converts an angle measured in radians to an approximately equivalent angle measured in degrees. The conversion from radians to degrees is generally inexact; users should not expect (cos (to-radians 90.0)) to exactly equal 0.0

```
(math/to-degrees 3)  
=> 171.88733853924697
```

```
(math/to-degrees 3.1415926)  
=> 179.99999692953102
```

```
(math/to-degrees 3.1415926M)  
=> 179.99999692953102
```

SEE ALSO

[math/to-radians](#)

Converts an angle measured in degrees to an approximately equivalent angle measured in radians. The conversion from degrees to radians is generally inexact.

math/to-radians

```
(math/to-radians x)
```

Converts an angle measured in degrees to an approximately equivalent angle measured in radians. The conversion from degrees to radians is generally inexact.

```
(math/to-radians 90)  
=> 1.5707963267948966
```

```
(math/to-radians 90.0)
=> 1.5707963267948966
```

```
(math/to-radians 90.0M)
=> 1.5707963267948966
```

SEE ALSO

[math/to-degrees](#)

Converts an angle measured in radians to an approximately equivalent angle measured in degrees. The conversion from radians to degrees ...

[top](#)

matrix/add-column-at-end

```
(matrix/add-column-at-end m c)
```

Add a column to a matrix after the last column.

```
(do
  (load-module :matrix)

  ;; | 1 2 3 | + | 4 8 | => | 1 2 3 4 |
  ;; | 5 6 7 |   |      |   | 5 6 7 8 |

  (matrix/add-column-at-end [[1 2 3] [5 6 7]] [4 8]))
=> [[1 2 3 4] [5 6 7 8]]
```

[top](#)

matrix/add-column-at-start

```
(matrix/add-column-at-start m c)
```

Add a column to a matrix before the first column.

```
(do
  (load-module :matrix)

  ;; | 2 3 4 | + | 1 5 | => | 1 2 3 4 |
  ;; | 6 7 8 |   |      |   | 5 6 7 8 |

  (matrix/add-column-at-start [[2 3 4] [6 7 8]] [1 5]))
=> [[1 2 3 4] [5 6 7 8]]
```

[top](#)

matrix/add-row-at-end

```
(matrix/add-row-at-end m r)
```

Add a row to a matrix after the last row.

```
(do
  (load-module :matrix)

  ;; | 1 2 3 | + | 7 8 9 | => | 1 2 3 |
  ;; | 4 5 6 |           | 4 5 6 |
  ;; | 7 8 9 |           | 7 8 9 |

  (matrix/add-row-at-end [[1 2 3] [4 5 6]] [7 8 9]))
=> [[1 2 3] [4 5 6] [7 8 9]]
```

[top](#)

matrix/add-row-at-start

```
(matrix/add-row-at-start m r)
```

Add a row to a matrix before the first row.

```
(do
  (load-module :matrix)

  ;; | 4 5 6 | + | 1 2 3 | => | 1 2 3 |
  ;; | 7 8 9 |           | 4 5 6 |
  ;; | 7 8 9 |           | 7 8 9 |

  (matrix/add-row-at-start [[4 5 6] [7 8 9]] [1 2 3]))
=> [[1 2 3] [4 5 6] [7 8 9]]
```

[top](#)

matrix/assoc-element

```
(matrix/assoc-element m row col val)
```

Replaces an element in the matrix

```
(do
  (load-module :matrix)
  (matrix/assoc-element [[1 2 3] [4 5 6]] 1 2 9))
=> [[1 2 3] [4 5 9]]
```

[top](#)

matrix/column

```
(matrix/column m n)
```

Returns the matrix column n

```
(do
  (load-module :matrix)
  (matrix/column [[1 2 3] [4 5 6]] 1))
=> [2 5]
```

[top](#)

matrix/columns

```
(matrix/columns m)
```

Returns the number of columns in the matrix

```
(do
  (load-module :matrix)
  (matrix/columns [[1 2 3]
                   [4 5 6]]))
=> 3
```

[top](#)

matrix/element

```
(matrix/element m row col)
```

Returns the matrix element at the row and column

```
(do
  (load-module :matrix)
  (matrix/element [[1 2 3] [4 5 6]] 1 2))
=> 6
```

[top](#)

matrix/empty?

```
(matrix/empty? m)
```

Returns true if the matrix is empty else false

```
(do
  (load-module :matrix)
  (matrix/empty? []))
=> true
```

[top](#)

matrix/format

```
(matrix/format m)
(matrix/format m fmt)
```

Formats a matrix.

```
(println (matrix/format [[1 2] [3 4] [5 6]]))
```

```
| 1 2 |  
| 3 4 |  
| 5 6 |
```

```
(do  
  (load-module :matrix)  
  (println (matrix/format [[1 2] [3 14] [10 6]]))  
  (println)  
  (println (matrix/format [[1.8 2.0] [3.0 4.8] [5.1 6.8]]))  
  (println)  
  (println (matrix/format [[1.845 2.009] [3.054 4.889] [5.132 6.878]]  
                          (fn [x] (str/format "%.2f" x)))))  
  
| 1 2 |  
| 3 14 |  
| 10 6 |  
  
| 1.8 2.0 |  
| 3.0 4.8 |  
| 5.1 6.8 |  
  
| 1.85 2.01 |  
| 3.05 4.89 |  
| 5.13 6.88 |  
=> nil
```

[top](#)

matrix/remove-column

```
(matrix/remove-column m n)
```

Remove a column from a matrix.

```
(do  
  (load-module :matrix)  
  (matrix/remove-column [[2 3 4] [6 7 8]] 1))  
=> [[2 4] [6 8]]
```

[top](#)

matrix/remove-row

```
(matrix/remove-row m n)
```

Remove a row from a matrix.

```
(do  
  (load-module :matrix)  
  (matrix/remove-row [[1 2] [3 4] [5 6]] 1))  
=> [[1 2] [5 6]]
```

[top](#)

matrix/row

(matrix/row m n)

Returns the matrix row n

```
(do
  (load-module :matrix)
  (matrix/row [[1 2 3] [4 5 6]] 1))
=> [4 5 6]
```

[top](#)

matrix/rows

(matrix/rows m)

Returns the number of rows in the matrix

```
(do
  (load-module :matrix)
  (matrix/rows [[1 2 3]
                [4 5 6]]))
=> 2
```

[top](#)

matrix/transpose

(matrix/transpose m)

Transposes a matrix. A matrix is a vector of vectors [[1 2] [3 4]]

```
(do
  (load-module :matrix)

  ;; | 1 2 3 |    => | 1 4 |
  ;; | 4 5 6 |      | 2 5 |
  ;;               | 3 6 |
  (matrix/transpose [[1 2 3]
                    [4 5 6]]))
=> [[1 4] [2 5] [3 6]]
```

[top](#)

matrix/validate

(matrix/validate m)

Validates a matrix. A matrix is a vector of vectors [[1 2] [3 4]]

Returns the matrix if valid else throws an exception.

- A matrix must be an empty vector or a vector of vectors!
- All rows must have the same number of columns

```
(do
  (load-module :matrix)
  (matrix/validate [[1 2 3]
                    [4 5 6]]))
=> [[1 2 3] [4 5 6]]
```

[top](#)

matrix/vector2d

(matrix/vector2d m)

Converts a 2D sequential collection into a 2D vector

```
(do
  (load-module :matrix)
  (matrix/vector2d (list (list 1 2 3) (list 4 5 6))))
=> [[1 2 3] [4 5 6]]
```

[top](#)

maven/artifact-filename

(maven/artifact-filename artifact file-suffix)

Returns the artifact file name

"org.knowm.xchart:xchart:3.8.6" -> "xchart-3.8.6.jar"

```
(do
  (load-module :maven)
  (maven/artifact-filename "org.knowm.xchart:xchart:3.8.6" ".jar"))

(do
  (load-module :maven)
  (maven/artifact-filename "org.knowm.xchart:xchart:3.8.6" "-sources.jar"))
```

SEE ALSO

[maven/parse-artifact](#)

Parses a Maven artifact

[maven/artifact-uri](#)

Returns the artifact URI

[maven/download](#)

Downloads an artifact in the format 'group-id:artifact-id:version' from a Maven repository. Can download any combination of the jar, ...

[maven/get](#)

Downloads artifact in the format 'group-id:artifact-id:version' from a Maven repository. The artifact type 'type' is one of {jar, ...

maven/artifact-uri

```
(maven/artifact-uri artifact file-suffix)
(maven/artifact-uri artifact file-suffix repo)
```

Returns the artifact URI

"org.knowm.xchart:xchart:3.8.6" -> "https://repo1.maven.org/maven2/org/knowm/xchart/xchart-3.8.6.jar"

```
(do
  (load-module :maven)
  (maven/artifact-uri "org.knowm.xchart:xchart:3.8.6" ".jar"))

(do
  (load-module :maven)
  (maven/artifact-uri "org.knowm.xchart:xchart:3.8.6" "-sources.jar"))

(do
  (load-module :maven)
  (maven/artifact-uri "org.knowm.xchart:xchart:3.8.6" ".pom"))

(do
  (load-module :maven)
  (maven/artifact-uri "org.knowm.xchart:xchart:3.8.6"
    ".jar"
    "https://repo1.maven.org/maven2"))
```

SEE ALSO

[maven/parse-artifact](#)

Parses a Maven artifact

[maven/artifact-filename](#)

Returns the artifact file name

[maven/download](#)

Downloads an artifact in the format 'group-id:artifact-id:version' from a Maven repository. Can download any combination of the jar, ...

[maven/get](#)

Downloads artifact in the format 'group-id:artifact-id:version' from a Maven repository. The artifact type 'type' is one of {jar, ...

maven/dependencies

```
(maven/dependencies artifacts & options)
```

Returns the dependency tree of an artifact

Relies on the environment variable `MAVEN_HOME` to access Maven.

Options:

:scope s	A scope. :compile, :provided, :runtime, :test. Defaults to :compile
:verbose v	if true invokes for verbose output else standard output. Defaults to false
:excludes e	A list of excluded dependencies
:format f	An output format. :raw, :tree, or :list. Defaults to :tree

`:print p` If true prints the data else returns the data. Defaults to true.
`:print-pom p` If true print the generated pom for debugging purposes. Defaults to false.
`:managed-dependencies d` An optional list of managed dependencies (artifacts). See example 2.

The scope is one of:

- `:compile` - build, test and run
- `:provided` - build and test
- `:runtime` - test and run
- `:test` - compile and test

Excludes dependencies with the group ids (except for `:test` scope):

- `org.junit.*`
- `org.opentest4j`
- `org.apiguardian`
- `junit`

Example 1:

```
(maven/dependencies [ "org.knowm.xchart:xchart:3.8.6" ])  
  
org.knowm.xchart:xchart:jar:3.8.6:compile  
+- de.erichseifert.vectorgraphics2d:VectorGraphics2D:jar:0.13:compile  
+- de.rototor.pdfbox:graphics2d:jar:3.0.0:compile  
| \- org.apache.pdfbox:pdfbox:jar:3.0.0:compile  
|   +- org.apache.pdfbox:pdfbox-io:jar:3.0.0:compile  
|   +- org.apache.pdfbox:fontbox:jar:3.0.0:compile  
|   \- commons-logging:commons-logging:jar:1.2:compile  
\- com.madgag:animated-gif-lib:jar:1.4:compile
```

Example 2:

lock down a transitive dependency to a specific version using Maven managed dependencies

```
(maven/dependencies ["org.knowm.xchart:xchart:3.8.6"]  
                   :managed-dependencies ["org.apache.pdfbox:pdfbox:2.0.27"])  
  
org.knowm.xchart:xchart:jar:3.8.6::compile  
+- de.erichseifert.vectorgraphics2d:VectorGraphics2D:jar:0.13:runtime  
+- de.rototor.pdfbox:graphics2d:jar:3.0.0:runtime  
| \- org.apache.pdfbox:pdfbox:jar:2.0.27:runtime  
|   +- org.apache.pdfbox:fontbox:jar:2.0.27:runtime  
|   \- commons-logging:commons-logging:jar:1.2:runtime  
\- com.madgag:animated-gif-lib:jar:1.4:runtime
```

```
(do  
  (load-module :maven)  
  (maven/dependencies [ "org.knowm.xchart:xchart:3.8.6" ]))  
  
(do  
  (load-module :maven)  
  (maven/dependencies [ "org.knowm.xchart:xchart:3.8.6" ]  
                      :scope :compile  
                      :verbose true))  
  
(do  
  (load-module :maven)  
  (maven/dependencies [ "org.knowm.xchart:xchart:3.8.6" ]  
                      :scope :runtime  
                      :format :list))
```

maven/download

(maven/download artifact options*)

Downloads an artifact in the format 'group-id:artifact-id:version' from a Maven repository. Can download any combination of the jar, sources, or pom artifacts to a directory.

Accepts a sequence of artifacts as well.

Options:

:jar {true,false}	download the jar, defaults to true
:sources {true,false}	download the sources, defaults to false
:pom {true,false}	download the pom, defaults to false
:dir path	download dir, defaults to "."
:repo maven-repo	a maven repo, defaults to "https://repo1.maven.org/maven2"
:silent {true,false}	if silent is true does not show a progress bar, defaults to true
:force {true,false}	if force is true download the artifact even if it exist already on the download dir, else skip the download if it exists. Defaults to true.

```
(do
  (load-module :maven)
  (maven/download "org.knowm.xchart:xchart:3.8.6"))

(do
  (load-module :maven)
  (maven/download "org.knowm.xchart:xchart:3.8.6"
    :sources true
    :pom true))

(do
  (load-module :maven)
  (maven/download "org.knowm.xchart:xchart:3.8.6"
    :dir "."
    :jar false
    :sources true))

(do
  (load-module :maven)
  (maven/download "org.knowm.xchart:xchart:3.8.6"
    :dir "."
    :sources true))

(do
  (load-module :maven)
  (maven/download "org.knowm.xchart:xchart:3.8.6"
    :dir "."
    :sources true
    :repo "https://repo1.maven.org/maven2"))

(do
  (load-module :maven)
  (maven/download "org.knowm.xchart:xchart:3.8.6"
    :dir "."
    :silent false))

(do
  (load-module :maven)
  ;; download all langchain4j artifacts
```

```
(maven/download (maven/dependencies
  [ "dev.langchain4j:langchain4j:0.28.0" ]
  :format :list
  :scope :runtime
  :print false)
:dir "."
:silent false))
```

SEE ALSO

[maven/get](#)

Downloads artifact in the format 'group-id:artifact-id:version' from a Maven repository. The artifact type 'type' is one of {jar, ...

[maven/parse-artifact](#)

Parses a Maven artifact

top

maven/get

```
(maven/get artifact type options*)
```

Downloads artifact in the format 'group-id:artifact-id:version' from a Maven repository. The artifact type 'type' is one of {jar, :sources, :pom}.

Returns the artifact as byte buffer.

Options:

:repo maven-repo a maven repo, defaults to "https://repo1.maven.org/maven2"
:silent {true,false} if silent is true does not show a progress bar, defaults to true

```
(do
  (load-module :maven)
  (maven/get "org.knowm.xchart:xchart:3.8.6" :jar))

(do
  (load-module :maven)
  (maven/get "org.knowm.xchart:xchart:3.8.6" :jar :silent false))

(do
  (load-module :maven)
  (maven/get "org.knowm.xchart:xchart:3.8.6" :sources))

(do
  (load-module :maven)
  (maven/get "org.knowm.xchart:xchart:3.8.6"
    :jar
    :repo "https://repo1.maven.org/maven2"))
```

SEE ALSO

[maven/download](#)

Downloads an artifact in the format 'group-id:artifact-id:version' from a Maven repository. Can download any combination of the jar, ...

[maven/parse-artifact](#)

Parses a Maven artifact

top

maven/home-dir

```
(maven/home-dir)
```

Returns the Apache Maven home directory or nil if Maven is not installed.

If a REPL is active checks first for local Apache Maven installation in the REPL, if none is available checks the environment variable 'MAVEN_HOME'.

If a REPL is not active checks the environment variable 'MAVEN_HOME'.

```
(do
  (load-module :maven)
  (maven/home-dir))
```

SEE ALSO

[maven/mvn](#)

Runs a Maven command

[maven/version](#)

Runs the Maven version command and prints the commands output.

[top](#)

maven/install

```
(maven/install)
(maven/install version)
```

Installs Apache Maven to {repl-home-dir}/tools/apache-maven-x.y.z

Installation is possible from within a REPL only!

```
(do
  (load-module :maven)
  (maven/install)) ;; installs default version 3.9.6

(do
  (load-module :maven)
  (maven/install "3.9.5"))
```

SEE ALSO

[maven/home-dir](#)

Returns the Apache Maven home directory or nil if Maven is not installed.

[maven/uninstall](#)

Uninstalls Apache Maven from {repl-home-dir}/tools

[top](#)

maven/mvn

```
(maven/mvn proj-dir & args)
```

Runs a Maven command

Relies on the environment variable `MAVEN_HOME` to access Maven.

```
(do
  (load-module :maven)
  (->> (maven/mvn "/Users/foo/projects/my-project" "compile")
    (println)))

(do
  (load-module :maven)
  (->> (maven/mvn "/Users/foo/projects/my-project" "-X" "package")
    (println)))
```

SEE ALSO

[maven/version](#)

Runs the Maven version command and prints the commands output.

[maven/home-dir](#)

Returns the Apache Maven home directory or nil if Maven is not installed.

[top](#)

maven/parse-artifact

(maven/parse-artifact artifact)

Parses a Maven artifact

Form 1: "org.knowm.xchart:xchart:3.8.6"

```
{ :group-id      "org.knowm.xchart"
  :artifact-id   "xchart"
  :version       "3.8.6" }
```

Form 2: "org.knowm.xchart:jar:xchart:3.8.6"

```
{ :group-id      "org.knowm.xchart"
  :artifact-id   "xchart"
  :version       "3.8.6"
  :type          :jar }
```

Form 3: "org.knowm.xchart:jar:xchart:3.8.6:compile"

```
{ :group-id      "org.knowm.xchart"
  :artifact-id   "xchart"
  :version       "3.8.6"
  :type          :jar
  :scope         :compile }
```

```
(do
  (load-module :maven)
  (maven/parse-artifact "org.knowm.xchart:xchart:3.8.6"))
```

SEE ALSO

[maven/artifact-filename](#)

Returns the artifact file name

[maven/artifact-uri](#)

Returns the artifact URI

[maven/download](#)

Downloads an artifact in the format 'group-id:artifact-id:version' from a Maven repository. Can download any combination of the jar, ...

[maven/get](#)

Downloads artifact in the format 'group-id:artifact-id:version' from a Maven repository. The artifact type 'type' is one of {jar, ...

[top](#)

maven/uninstall

(maven/uninstall)

Uninstalls Apache Maven from {repl-home-dir}/tools

Uninstallation is possible from within a REPL only!

```
(do
  (load-module :maven)
  (maven/uninstall))
```

SEE ALSO

[maven/home-dir](#)

Returns the Apache Maven home directory or nil if Maven is not installed.

[maven/install](#)

Installs Apache Maven to {repl-home-dir}/tools/apache-maven-x.y.z

[top](#)

maven/version

(maven/version)

Runs the Maven version command and prints the commands output.

Relies on the environment variable `MAVEN_HOME` to access Maven.

```
(do
  (load-module :maven)
  (maven/version))
```

SEE ALSO

[maven/mvn](#)

Runs a Maven command

[maven/home-dir](#)

Returns the Apache Maven home directory or nil if Maven is not installed.

[top](#)

max

```
(max x)
(max x y)
(max x y & more)
```

Returns the greatest of the values

```
(max 1)  
=> 1
```

```
(max 1 2)  
=> 2
```

```
(max 4 3 2 1)  
=> 4
```

```
(max 1I 2I)  
=> 2I
```

```
(max 1.0)  
=> 1.0
```

```
(max 1.0 2.0)  
=> 2.0
```

```
(max 4.0 3.0 2.0 1.0)  
=> 4.0
```

```
(max 1.0M)  
=> 1.0M
```

```
(max 1.0M 2.0M)  
=> 2.0M
```

```
(max 4.0M 3.0M 2.0M 1.0M)  
=> 4.0M
```

```
(max 1.0M 2)  
=> 2
```

SEE ALSO

[min](#)

Returns the smallest of the values

[clamp](#)

Restricts a given value between a lower and upper bound. In this way, it acts like a combination of the min and max functions.

[top](#)

memoize

```
(memoize f)
```

Returns a memoized version of a referentially transparent function.

Note:

Use memoization for expensive calculations. If used with fast calculations it has the opposite effect and can slow it down actually!

```
(do  
  (def fibonacci
```



```

(memoize
  (fn [n]
    (cond
      (<= n 0) 0
      (< n 2) 1
      :else (+ (fibonacci (- n 1)) (fibonacci (- n 2)))))))

(time (fibonacci 25))
Elapsed time: 831.00µs
=> 75025

(do
  (defn test [a b]
    (println (str "calculating a=" a ", b=" b))
    (+ a b))

  (def test-memo (memoize test))

  (test-memo 1 1)
  (test-memo 1 2)
  (test-memo 1 1)
  (test-memo 1 2)
  (test-memo 1 1))
calculating a=1, b=1
calculating a=1, b=2
=> 2

```

SEE ALSO

[delay](#)

Takes a body of expressions and yields a Delay object that will invoke the body only the first time it is forced (with force or deref ...

[top](#)

merge

```
(merge & maps)
```

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from the latter (left-to-right) will be the mapping in the result.

```

(merge {:a 1 :b 2 :c 3} {:b 9 :d 4})
=> {:a 1 :b 9 :c 3 :d 4}

```

```

(merge {:a 1} nil)
=> {:a 1}

```

```

(merge nil {:a 1})
=> {:a 1}

```

```

(merge nil nil)
=> nil

```

SEE ALSO

[merge-with](#)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping(s) from ...

[merge-deep](#)

Recursively merges maps.

[into](#)

Returns a new coll consisting of to coll with all of the items of from coll conjoined.

[concat](#)

Returns a list of the concatenation of the elements in the supplied collections.

[top](#)

merge-deep

```
(merge-deep values)
```

```
(merge-deep strategy & values)
```

Recursively merges maps.

If the first parameter is a keyword it defines the strategy to use when merging non-map collections. Options are:

1. *:replace*, the default, the last value is used
2. *:into*, if the value in every map is a collection they are concatenated using `into`. Thus the type of (first) value is maintained.

```
(merge-deep {:a {:c 2}} {:a {:b 1}})
```

```
=> {:a {:b 1 :c 2}}
```

```
(merge-deep :replace {:a [1]} {:a [2]})
```

```
=> {:a [2]}
```

```
(merge-deep :into {:a [1]} {:a [2]})
```

```
=> {:a [1 2]}
```

```
(merge-deep {:a 1} nil)
```

```
=> nil
```

SEE ALSO

[merge](#)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from ...

[merge-with](#)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping(s) from ...

[top](#)

merge-with

```
(merge-with f & maps)
```

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping(s) from the latter (left-to-right) will be combined with the mapping in the result by calling (f val-in-result val-in-latter).

```
(merge-with + {:a 1 :b 2} {:a 9 :b 98 :c 0})
```

```
=> {:a 10 :b 100 :c 0}
```

```
(merge-with into {:a [1] :b [2]} {:b [3 4] :c [5 6]})
```

```
=> {:a [1] :b [2 3 4] :c [5 6]}
```

SEE ALSO

[merge](#)

Returns a map that consists of the rest of the maps conj-ed onto the first. If a key occurs in more than one map, the mapping from ...

[merge-deep](#)

Recursively merges maps.

[top](#)

meta

`(meta obj)`

Returns the metadata of obj, returns nil if there is no metadata.

```
(meta (vary-meta [1 2] assoc :foo 3))
=> {:foo 3 :line 56 :column 28 :file "example"}
```

SEE ALSO

[vary-meta](#)

Returns a copy of the object obj, with (apply f (meta obj) args) as its metadata.

[with-meta](#)

Returns a copy of the object obj, with a map m as its metadata.

[var-val-meta](#)

Returns the var's value meta data.

[var-sym-meta](#)

Returns the var's symbol meta data.

[top](#)

mimetypes/probe-content-type

`(probe-content-type f)`

Probes the content type of a file.

The function uses a built-in "mime.types" data file to lookup the file's mimetype based on the file extension.

f must be a string or a java.io.File.

Returns `nil` if a mapping is not defined.

```
(do
  (load-module :mimetypes)
  (mimetypes/probe-content-type "foo.png"))
=> "image/png"
```

[top](#)

min

```
(min x)
(min x y)
(min x y & more)
```

Returns the smallest of the values

```
(min 1)
=> 1
```

```
(min 1 2)
=> 1
```

```
(min 4 3 2 1)
=> 1
```

```
(min 1I 2I)
=> 1I
```

```
(min 1.0)
=> 1.0
```

```
(min 1.0 2.0)
=> 1.0
```

```
(min 4.0 3.0 2.0 1.0)
=> 1.0
```

```
(min 1.0M)
=> 1.0M
```

```
(min 1.0M 2.0M)
=> 1.0M
```

```
(min 4.0M 3.0M 2.0M 1.0M)
=> 1.0M
```

```
(min 1.0M 2)
=> 1.0M
```

SEE ALSO

[max](#)

Returns the greatest of the values

[clamp](#)

Restricts a given value between a lower and upper bound. In this way, it acts like a combination of the min and max functions.

[top](#)

mod

```
(mod n d)
```

Modulus of n and d.

```
(mod 10 4)
=> 2
```

```
(mod -1 5)
=> 4
```

```
(mod 10I 4I)
=> 2I
```

SEE ALSO

[mod-floor](#)

floor a number towards 0 to the nearest multiple of a number

[top](#)

mod-floor

```
(mod-floor n m)
```

floor a number towards 0 to the nearest multiple of a number

```
(mod-floor 9 3)
=> 9
```

```
(mod-floor 10 3)
=> 9
```

```
(mod-floor 11 3)
=> 9
```

```
(mod-floor -11 3)
=> -9
```

SEE ALSO

[mod](#)

Modulus of n and d.

[top](#)

module-name

```
(module-name class)
```

Returns the Java module name of a class.

```
(module-name (class :java.util.ArrayList))
```

SEE ALSO

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[class-name](#)

Returns the Java class name of a class.

modules

(modules)

Lists the available Venice modules

SEE ALSO

[doc](#)

Prints documentation for a var or special form given x as its name. Prints the definition of custom types.

[ns-list](#)

Without arg lists the loaded namespaces, else lists all the symbols in the specified namespace ns.

multipart/http-content-type-header

(http-content-type-header)

Returns the HTTP content type header value for *multipart/form-data* HTTP requests.

The `multipart/render` function uses this boundary.

E.g: Content-Type: multipart/form-data; boundary=1234567890N

```
(do
  (load-module :multipart ['multipart :as 'm])

  (m/http-content-type-header))
```

SEE ALSO

[multipart/render](#)

Renders a map of named parts as multipart/form-data format.

[multipart/parse](#)

Parses a multipart bytebuf.

multipart/parse

(parse buffer boundary)

Parses a multipart bytebuf.

```
(do
  (load-module :multipart ['multipart :as 'm])
  (load-module :hexdump ['hexdump :as 'h])

  (defn render []
    (m/render { "Part-1" "xxxxxxxxxxx"

```

```

        "Part-4" { :filename "data.xml"
                  :mimetype "application/xml"
                  :charset  "utf-8"
                  :data     "<user><name>foo</name></user>" })})

(let [mp (render)]
  (m/parse mp (m/boundary)))

;; Returns a list of part maps:
;; ( { :name "Part-1"
;;     :filename nil
;;     :mimetype nil
;;     :charset nil
;;     :data [120 ... 120] ;; shortened for brevity
;;     :data-len 11 }
;;   { :name "Part-4"
;;     :filename "data.xml"
;;     :mimetype "application/xml"
;;     :charset "utf-8"
;;     :data [60 ... 62] ;; shortened for brevity
;;     :data-len 29 })

```

SEE ALSO

[multipart/render](#)

Renders a map of named parts as multipart/form-data format.

[multipart/http-content-type-header](#)

Returns the HTTP content type header value for multipart/form-data HTTP requests.

top

multipart/render

```
(render parts)
```

Renders a map of named parts as *multipart/form-data* format.

The part name must be a string and the part data may be of type:

- string
- string ("file:/user/foo/image.png" to reference a file)
- map (describing a part as :name, :mimetype, :data (string or bytebuf), and an optional charset) elements)
- io/file
- all other part data types are converted with `(str data)` to a string

Returns a bytebuf with all the rendered parts.

```

POST / HTTP/1.1
HOST: host.example.com
Connection: Keep-Alive
Content-Type: multipart/form-data; boundary=12345

--12345
Content-Disposition: form-data; name="notes"
Content-Type: text/plain; charset=utf-8

Lorem ipsum ...
--12345
Content-Disposition: form-data; name="foo"; filename="foo.json"
Content-Type: application/json; charset=utf-8

```

```
content of foo.json
--12345
Content-Disposition: form-data; name="image"; filename="picture.png"
Content-Type: image/png

content of picture.png
--12345--
```

See [multipart/form-data](#)

```
(do
  (load-module :multipart ['multipart :as 'm])

  (->> (m/render { "Part-1" "xxxxxxxxxxx"
                   "Part-2" "yyyyyyyyyyy"})
    (bytebuf-to-string)
    (println)))

(do
  (load-module :multipart ['multipart :as 'm])

  (m/render { "Part-1" "xxxxxxxxxxx"
              "Part-2" "file:/user/foo/image.png"
              "Part-3" (io/file "/user/foo/image.png")
              "Part-4" { :filename "data.xml"
                         :mimetype "application/xml"
                         :charset  "utf-8"
                         :data      "<user><name>foo</name></user>" }}))
```

SEE ALSO

[multipart/parse](#)

Parses a multipart bytebuf.

[multipart/http-content-type-header](#)

Returns the HTTP content type header value for multipart/form-data HTTP requests.

[top](#)

mutable-list

```
(mutable-list & items)
```

Creates a new mutable list containing the items.

The list is backed by `java.util.ArrayList` and is not thread-safe.

```
(mutable-list)
=> ()

(mutable-list 1 2 3)
=> (1 2 3)

(mutable-list 1 2 3 [:a :b])
=> (1 2 3 [:a :b])
```

[top](#)

mutable-list?

```
(mutable-list? obj)
```

Returns true if obj is a mutable list

```
(mutable-list? (mutable-list 1 2))  
=> true
```

[top](#)

mutable-map

```
(mutable-map & keyvals)  
(mutable-map map)
```

Creates a new mutable threadsafe map containing the items.

```
(mutable-map :a 1 :b 2)  
=> {:a 1 :b 2}
```

```
(mutable-map {:a 1 :b 2})  
=> {:a 1 :b 2}
```

[top](#)

mutable-map?

```
(mutable-map? obj)
```

Returns true if obj is a mutable map

```
(mutable-map? (mutable-map :a 1 :b 2))  
=> true
```

[top](#)

mutable-set

```
(mutable-set & items)
```

Creates a new mutable set containing the items.

```
(mutable-set)  
=> #{} 
```

```
(mutable-set nil)  
=> #{nil}
```

```
(mutable-set 1)
=> #{1}

(mutable-set 1 2 3)
=> #{1 2 3}

(mutable-set [1 2] 3)
=> #{3 [1 2]}
```

[top](#)

mutable-set?

```
(mutable-set? obj)
```

Returns true if obj is a mutable-set

```
(mutable-set? (mutable-set 1))
=> true
```

[top](#)

mutable-vector

```
(mutable-vector & items)
```

Creates a new mutable threadsafe vector containing the items.

```
(mutable-vector)
=> []

(mutable-vector 1 2 3)
=> [1 2 3]

(mutable-vector 1 2 3 [:a :b])
=> [1 2 3 [:a :b]]
```

[top](#)

mutable-vector?

```
(mutable-vector? obj)
```

Returns true if obj is a mutable vector

```
(mutable-vector? (mutable-vector 1 2))
=> true
```

[top](#)

name

```
(name x)
```

Returns the name string of a string, symbol, keyword, or function. If applied to a string it returns the string itself.

```
(name 'foo) ;; symbol  
=> "foo"
```

```
(name 'user/foo) ;; symbol  
=> "foo"
```

```
(name (symbol "user/foo")) ;; symbol  
=> "foo"
```

```
(name :foo) ;; keyword  
=> "foo"
```

```
(name :user/foo) ;; keyword  
=> "foo"
```

```
(name +) ;; function  
=> "+"
```

```
(name str/digit?) ;; function  
=> "digit?"
```

```
(name "ab/text") ;; string  
=> "ab/text"
```

```
(name (. :java.time.Month :JANUARY)) ;; java enum  
=> "JANUARY"
```

SEE ALSO

[qualified-name](#)

Returns the qualified name String of a string, symbol, keyword, or function

[namespace](#)

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

[fn-name](#)

Returns the qualified name of a function or macro

[top](#)

namespace

```
(namespace x)
```

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

Throws an exception if x does not support namespaces like `(namespace 2)`.

```
(namespace 'user/foo) ;; symbol  
=> "user"
```

```
(namespace (symbol "user/foo")) ;; symbol
=> "user"
```

```
(namespace :user/foo) ;; keyword
=> "user"
```

```
(namespace str/digit?) ;; function
=> "str"
```

```
(namespace *ns*) ;; symbol
=> "user"
```

SEE ALSO

[name](#)

Returns the name string of a string, symbol, keyword, or function. If applied to a string it returns the string itself.

[fn-name](#)

Returns the qualified name of a function or macro

[ns](#)

Opens a namespace.

[*ns*](#)

The current namespace

[var-ns](#)

Returns the namespace of the var's symbol.

[top](#)

nan?

```
(nan? x)
```

Returns true if x is a NaN else false. x must be a double!

```
(nan? 0.0)
=> false
```

```
(nan? (/ 0.0 0))
=> true
```

```
(nan? (sqrt -1))
=> true
```

```
(pr (sqrt -1))
:NaN
=> nil
```

SEE ALSO

[infinite?](#)

Returns true if x is infinite else false. x must be a double!

[double](#)

Converts to double

nano-time

(nano-time)

Returns the current value of the running Java Virtual Machine's high-resolution time source, in nanoseconds.

(nano-time)

```
=> 359288744093500
```

```
(let [t (nano-time)
      _ (sleep 100)
      e (nano-time)]
  (format-nano-time (- e t) :precision 2))
=> "100.32ms"
```

SEE ALSO

[current-time-millis](#)

Returns the current time in milliseconds.

[format-nano-time](#)

Formats a time given in nanoseconds as long or double.

neg?

(neg? x)

Returns true if x smaller than zero else false

(neg? -3)

```
=> true
```

(neg? 3)

```
=> false
```

(neg? -3I)

```
=> true
```

(neg? -3.2F)

```
=> true
```

(neg? -3.2)

```
=> true
```

(neg? -3.2M)

```
=> true
```

SEE ALSO

[zero?](#)

Returns true if x zero else false

[pos?](#)

Returns true if x greater than zero else false

[negate](#)

Negates x

[top](#)

negate

(negate x)

Negates x

```
(negate 10)  
=> -10
```

```
(negate 10I)  
=> -10I
```

```
(negate 1.23)  
=> -1.23
```

```
(negate 1.23M)  
=> -1.23M
```

SEE ALSO

[abs](#)

Returns the absolute value of the number

[sgn](#)

sgn function for a number.

[top](#)

newline

(newline)
(newline os)

Without arg writes a platform-specific newline to the output channel that is the current value of `*out*`. With arg writes a newline to the passed stream that must be a subclass of either `:java.io.PrintStream` or `:java.io.Writer`.

Returns `nil`.

```
(newline)  
=> nil
```

```
(newline *out*)  
=> nil
```

```
(newline *err*)  
=> nil
```

SEE ALSO

[print](#)

Prints the values xs to the stream that is the current value of *out* or to the passed stream os that must be a subclass of either ...

[println](#)

Prints the values xs to the stream that is the current value of *out* or to the passed output stream os if given followed by a (newline).

[printf](#)

Without output stream prints formatted output as per format to the stream that is the current value of *out*. With a stream prints ...

[top](#)

nfirst

```
(nfirst coll n)
```

Returns a collection of the first n items

```
(nfirst nil 2)
```

```
=> ()
```

```
(nfirst [] 2)
```

```
=> []
```

```
(nfirst [1] 2)
```

```
=> [1]
```

```
(nfirst [1 2 3] 2)
```

```
=> [1 2]
```

```
(nfirst '() 2)
```

```
=> ()
```

```
(nfirst '(1) 2)
```

```
=> (1)
```

```
(nfirst '(1 2 3) 2)
```

```
=> (1 2)
```

```
(nfirst "abcdef" 2)
```

```
=> (#\a #\b)
```

```
(nfirst (lazy-seq 1 #(+ % 1)) 4)
```

```
=> (...)
```

SEE ALSO

[str/nfirst](#)

Returns a string of the n first characters of s.

[top](#)

nil?

```
(nil? x)
```

Returns true if x is nil, false otherwise

```
(nil? nil)  
=> true
```

```
(nil? 0)  
=> false
```

```
(nil? false)  
=> false
```

SEE ALSO

[some?](#)

Returns true if x is not nil, false otherwise

[top](#)

nlast

```
(nlast coll n)
```

Returns a collection of the last n items

```
(nlast nil 2)  
=> ()
```

```
(nlast [] 2)  
=> []
```

```
(nlast [1] 2)  
=> [1]
```

```
(nlast [1 2 3] 2)  
=> [2 3]
```

```
(nlast '() 2)  
=> ()
```

```
(nlast '(1) 2)  
=> (1)
```

```
(nlast '(1 2 3) 2)  
=> (2 3)
```

```
(nlast "abcdef" 2)  
=> (#\e #\f)
```

SEE ALSO

[str/nlast](#)

Returns a string of the n last characters of s.

[top](#)

not

```
(not x)
```

Returns true if x is logical false, false otherwise.

```
(not true)
=> false
```

```
(not (== 1 2))
=> true
```

SEE ALSO

[and](#)

Ands the predicate forms

[or](#)

Ors the predicate forms

[top](#)

not-any?

```
(not-any? pred coll)
```

Returns false if the predicate is true for at least one collection item, true otherwise

```
(not-any? number? nil)
=> true
```

```
(not-any? number? [])
=> true
```

```
(not-any? number? [1 :a :b])
=> false
```

```
(not-any? number? [1 2 3])
=> false
```

```
(not-any? #(>= % 10) [1 5 10])
=> false
```

SEE ALSO

[any?](#)

Returns true if the predicate is true for at least one collection item, false otherwise.

[every?](#)

Returns true if coll is a collection and the predicate is true for all collection items, false otherwise.

[not-every?](#)

Returns true if coll is a collection and the predicate is not true for all collection items, false otherwise.

[top](#)

not-contains?

```
(not-contains? coll key)
```

Returns true if key is not present in the given collection, otherwise returns false.

```
(not-contains? #{:a :b} :c)
=> true
```

```
(not-contains? {:a 1 :b 2} :c)
=> true
```

```
(not-contains? [10 11 12] 1)
=> false
```

```
(not-contains? [10 11 12] 5)
=> true
```

```
(not-contains? "abc" 1)
=> false
```

```
(not-contains? "abc" 5)
=> true
```

SEE ALSO

[contains?](#)

Returns true if key is present in the given collection, otherwise returns false.

[top](#)

not-empty?

```
(not-empty? x)
```

Returns true if x is not empty. Accepts strings, collections and bytebufs.

```
(not-empty? {:a 1})
=> true
```

```
(not-empty? [1 2])
=> true
```

```
(not-empty? '(1 2))
=> true
```

```
(not-empty? "abc")
=> true
```

```
(not-empty? nil)
=> false
```

```
(not-empty? "")
=> false
```

SEE ALSO

[empty?](#)

Returns true if x is empty. Accepts strings, collections and bytebufs.

[top](#)

not-every?

```
(not-every? pred coll)
```

Returns true if coll is a collection and the predicate is not true for all collection items, false otherwise.

```
(not-every? number? nil)
=> false
```

```
(not-every? number? [])
=> true
```

```
(not-every? number? [1 2 3 4])
=> false
```

```
(not-every? number? [1 2 3 :a])
=> true
```

```
(not-every? #(>= % 10) [10 11 12])
=> false
```

SEE ALSO

[every?](#)

Returns true if coll is a collection and the predicate is true for all collection items, false otherwise.

[any?](#)

Returns true if the predicate is true for at least one collection item, false otherwise.

[not-any?](#)

Returns false if the predicate is true for at least one collection item, true otherwise

[top](#)

not-match?

```
(not-match? s regex)
```

Returns true if the string s does not match the regular expression regex.

The argument 'regex' may be a string representing a regular expression or a `:java.util.regex.Pattern`.

See the functions in the 'regex' namespace if more than a simple regex match is required! E.g. `regex/matches-not?` performs much better on matching many strings against the same pattern:

```
(let [m (regex/matcher #"[0-9]+" "")]
  (filter #(regex/matches-not? m %) ["100" "1a1" "200"])))
```

```
(not-match? "S1000" "[0-9]+")
=> true

(not-match? "S1000" #"[0-9]+")
=> true

(not-match? "1000" "[0-9]+")
=> false
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/matches-not?](#)

Attempts to match the entire region against the pattern. Returns false if the patterns matches the string else true.

[regex/matches?](#)

Attempts to match the entire region against the pattern. Returns true if the patterns matches the string else false.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/matches](#)

Returns the matches, if any, for the matcher with the pattern of a string, using `java.util.regex.Matcher.matches()`.

[regex/find](#)

Returns the next regex match or nil if there is no further match. Returns nil if there is no match.

[regex/find-all](#)

Returns all regex matches as list or an empty list if there are no matches.

[top](#)

not=

```
(not= x)
(not= x y)
(not= x y & more)
```

Same as `(not (= x y))`

```
(not= "abc" "abc")
=> false
```

```
(not= 0 0)
=> false
```

```
(not= 0 1)
=> true
```

```
(not= 0 0.0)
=> true
```

```
(not= 0 0.0M)
=> true
```

```
(not= "0" 0)
=> true

(not= 4)
=> false

(not= 1 2 3)
=> true
```

SEE ALSO

[=](#)

Returns true if both operands have equivalent type and value

[==](#)

Returns true if both operands have equivalent value.

[top](#)

ns

```
(ns sym)
```

Opens a namespace.

```
(do
  (ns xxx)
  (def foo 1)
  (ns yyy)
  (def foo 5)
  (println xxx/foo foo yyy/foo))
1 5 5
=> nil
```

SEE ALSO

[*ns*](#)

The current namespace

[ns?](#)

Returns true if n is an existing namespace that has been defined with (ns n) else false.

[ns-unmap](#)

Removes the mappings for the symbol from the namespace.

[ns-remove](#)

Removes the mappings for all symbols from the namespace.

[ns-list](#)

Without arg lists the loaded namespaces, else lists all the symbols in the specified namespace ns.

[ns-alias](#)

Add an alias in the current namespace to another namespace. Arguments are two symbols: the alias to be used, and the symbolic name ...

[ns-meta](#)

Returns the meta data of the namespace n or nil if n is not an existing namespace

[namespace](#)

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

[var-ns](#)

Returns the namespace of the var's symbol.

ns-alias

```
(ns-alias alias namespace-sym)
```

Add an alias in the current namespace to another namespace. Arguments are two symbols: the alias to be used, and the symbolic name of the target namespace.

```
(ns-alias 'p 'parsatron)
=> nil
```

```
(do
  (load-module :hexdump)
  (ns-alias 'h 'hexdump)
  (h/dump [0 1 2 3]))
00000000: 0001 0203          ....
=> nil
```

SEE ALSO

[ns-unalias](#)

Removes a namespace alias in the current namespace.

[ns-aliases](#)

Returns a map of the aliases defined in the current namespace.

[*ns*](#)

The current namespace

[ns](#)

Opens a namespace.

ns-aliases

```
(ns-aliases)
```

Returns a map of the aliases defined in the current namespace.

```
(ns-aliases)
=> {}
```

```
(do
  (ns-alias 'h 'hexdump)
  (ns-alias 'p 'parsatron)
  (ns-aliases))
=> {h hexdump p parsatron}
```

SEE ALSO

[ns-alias](#)

Add an alias in the current namespace to another namespace. Arguments are two symbols: the alias to be used, and the symbolic name ...

[ns-unalias](#)

Removes a namespace alias in the current namespace.

ns

The current namespace

ns

Opens a namespace.

top

ns-list

(ns-list)

(ns-list ns)

Without arg lists the loaded namespaces, else lists all the symbols in the specified namespace ns.

```
(ns-list 'regex)
```

```
=> (regex/count regex/find regex/find+ regex/find-all regex/find-all+ regex/find? regex/group regex/groups regex/matcher regex/matches regex/matches-not? regex/matches? regex/pattern regex/reset)
```

```
(ns-list)
```

```
=> ("ansi" "app" "ascii-table" "benchmark" "cargo" "cargo-arangodb" "cargo-postgresql" "cargo-qdrant" "chinook-postgresql" "cidr" "component" "config" "crypt" "csv" "dag" "dec" "docker" "excel" "fonts" "geoip" "gradle" "gradlew" "grep" "hexdump" "http-client-j8" "images" "inet" "installer" "io" "java" "jdbc-core" "jdbc-postgresql" "json" "jsonl" "jtokkit" "kira" "loadpath" "math" "matrix" "maven" "mimetypes" "multipart" "openai" "parsifal" "pdf" "qrref" "regex" "ring" "ring-multipart" "ring-mw" "ring-session" "ring-util" "sandbox" "semver" "server-side-events" "sh" "shell" "str" "test" "time" "timing" "tomcat" "trace" "xchart" "xml" "zipvault")
```

```
;; dynamically list all public symbols of a module
```

```
(let [module-name$ (keyword "hexdump")
      ns-name$ (symbol "hexdump")]
  (load-module module-name$)
  (->> (ns-list ns-name$)
    (filter #(not (:private (meta %) false)))
    (sort)))
```

```
=> (hexdump/ascii hexdump/ascii-lines hexdump/byte hexdump/byte-offsets hexdump/dump hexdump/hex-ascii-lines hexdump/hex-lines)
```

SEE ALSO

ns

Opens a namespace.

ns

The current namespace

ns-unmap

Removes the mappings for the symbol from the namespace.

ns-remove

Removes the mappings for all symbols from the namespace.

namespace

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

var-ns

Returns the namespace of the var's symbol.

top

ns-meta

```
(ns-meta n)
```

Returns the meta data of the namespace `n` or `nil` if `n` is not an existing namespace

```
(do
  (ns foo)
  (ns-meta foo))
=> {}

(do
  (ns foo)
  (ns-meta 'foo))
=> {}

(do
  (ns foo)
  (def n 'foo)
  (ns-meta (var-get n)))
=> {}
```

SEE ALSO

[alter-ns-meta!](#)

Alters the metadata for a namespace. `f` must be free of side-effects.

[reset-ns-meta!](#)

Resets the metadata for a namespace

[ns](#)

Opens a namespace.

[top](#)

ns-remove

```
(ns-remove ns)
```

Removes the mappings for all symbols from the namespace.

```
(do
  (ns foo)
  (def x 1)
  (ns bar)
  (def y 1)
  (ns-remove 'foo)
  (println "ns foo:" (ns-list 'foo))
  (println "ns bar:" (ns-list 'bar)))
ns foo: ()
ns bar: (bar/y)
=> nil
```

SEE ALSO

[ns](#)

Opens a namespace.

[ns-unmap](#)

Removes the mappings for the symbol from the namespace.

[ns-list](#)

Without arg lists the loaded namespaces, else lists all the symbols in the specified namespace ns.

[namespace](#)

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

[var-ns](#)

Returns the namespace of the var's symbol.

[top](#)

ns-unalias

```
(ns-unalias alias)
```

Removes a namespace alias in the current namespace.

```
(do
  (ns-alias 'h 'hexdump)
  (ns-unalias 'h))
=> nil
```

SEE ALSO

[ns-alias](#)

Add an alias in the current namespace to another namespace. Arguments are two symbols: the alias to be used, and the symbolic name ...

[ns-aliases](#)

Returns a map of the aliases defined in the current namespace.

[*ns*](#)

The current namespace

[ns](#)

Opens a namespace.

[top](#)

ns-unmap

```
(ns-unmap ns sym)
```

Removes the mappings for the symbol from the namespace.

```
(do
  (ns foo)
  (def x 1)
  (ns-unmap 'foo 'x)
  (ns-unmap *ns* 'x))
=> nil
```

SEE ALSO

[ns](#)

Opens a namespace.

`*ns*`

The current namespace

`ns-remove`

Removes the mappings for all symbols from the namespace.

`ns-list`

Without arg lists the loaded namespaces, else lists all the symbols in the specified namespace ns.

`namespace`

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

`var-ns`

Returns the namespace of the var's symbol.

[top](#)

ns?

```
(ns? n)
```

Returns true if n is an existing namespace that has been defined with `(ns n)` else false.

```
(do
  (ns foo)
  (ns? foo))
=> true
```

SEE ALSO

`ns`

Opens a namespace.

[top](#)

nth

```
(nth coll idx)
(nth coll idx defaultVal)
```

Returns the nth element of coll.

Throws an exception if the index does not exist and there is no default value passed else returns the default value.

```
(nth nil 1)
=> nil
```

```
(nth [1 2 3] 1)
=> 2
```

```
(nth '(1 2 3) 1)
=> 2
```

```
(nth "abc" 2)
=> #\c
```

```
(nth nil 1 9)
=> nil

(nth [1 2 3] 6 9)
=> 9

(nth '(1 2 3) 6 9)
=> 9

(nth "abc" 6 9)
=> 9
```

[top](#)

number?

```
(number? n)
```

Returns true if n is a number (int, long, double, or decimal)

```
(number? 4I)
=> true
```

```
(number? 4)
=> true
```

```
(number? 4.0M)
=> true
```

```
(number? 4.0)
=> true
```

```
(number? true)
=> false
```

```
(number? "a")
=> false
```

[top](#)

object-array

```
(object-array coll)
(object-array len)
(object-array len init-val)
```

Returns an array of Java Objects containing the contents of coll or returns an array with the given length and optional init value

```
(object-array '(1 2 3 4 5))
=> [1, 2, 3, 4, 5]
```

```
(object-array '(1 2.0 3.45M "4" true))
=> [1, 2.0, 3.45, 4, true]

(object-array 10)
=> [nil, nil, nil, nil, nil, nil, nil, nil, nil, nil]

(object-array 10 42)
=> [42, 42, 42, 42, 42, 42, 42, 42, 42, 42]
```

[top](#)

odd?

```
(odd? n)
```

Returns true if n is odd, throws an exception if n is not an integer

```
(odd? 3)
=> true
```

```
(odd? 4)
=> false
```

```
(odd? 4I)
=> false
```

SEE ALSO

[even?](#)

Returns true if n is even, throws an exception if n is not an integer

[top](#)

offer!

```
(offer! queue v)
(offer! queue timeout v)
```

Offers an item to a queue with an optional timeout in milliseconds. If a timeout is given waits up to the specified wait time if necessary for space to become available. For an indefinite timeout pass the timeout value :indefinite. If no timeout is given returns immediately false if the queue does not have any more capacity. Returns true if the element was added to this queue, else false.

```
(let [q (queue)]
  (offer! q 1)
  (offer! q 1000 2)
  (offer! q :indefinite 3)
  (offer! q 3)
  (poll! q)
  q)
=> (2 3 3)
```

SEE ALSO

[queue](#)

Creates a new mutable threadsafe bounded or unbounded queue.

[put!](#)

Puts an item to a queue. The operation is synchronous, it waits indefinitely until the value can be placed on the queue. Returns always nil.

[take!](#)

Retrieves and removes the head value of the queue, waiting if necessary until a value becomes available.

[poll!](#)

Polls an item from a queue with an optional timeout in milliseconds. For an indefinite timeout pass the timeout value :indefinite.

[peek](#)

For a list, same as first, for a vector, same as last, for a stack the top element (or nil if the stack is empty), for a queue the ...

[empty?](#)

Returns true if x is empty. Accepts strings, collections and bytebufs.

[count](#)

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

[top](#)

openai/assert-response-http-ok

```
(assert-response-http-ok response)
```

Throws an exception if the response HTTP status is not HTTP_OK.

The exception holds the response details.

[top](#)

openai/assistant-create

```
(assistant-create name model & options)
```

Create an assistant with a model and instructions.

Parameter «name»

The name of the assistant. The maximum length is 256 characters.

Parameter «model»

ID of the model to use. E.g.: `:gpt-4o`

Parameter «options»

:description	The description of the assistant. The maximum length is 512 characters.
:instructions	The system instructions that the assistant uses. The maximum length is 256,000 characters.
:tools	A list of tool enabled on the assistant. There can be a maximum of 128 tools per assistant. Tools can be of types "code_interpreter", "file_search", or "function".
:tool-resources	A set of resources that are used by the assistant's tools. The resources are specific to the type of tool. For example, the code_interpreter tool requires a list of file IDs, while the file_search tool requires a list of vector store IDs.
:assistant-opts	A map of additional assistant options like "metadata", "temperature", "top_p", "response_format". See: OpenAI Request Options
:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "assistants=v2"}

:uri	An OpenAI assistants URI. E.g.: "https://api.openai.com/v1/assistants". Defaults to "https://api.openai.com/v1/assistants"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/assistant-create
                  "Math Tutor"
                  :gpt-4o
                  :instructions (str "You are a personal math tutor. When asked "
                                     "a question, write and run Python code to "
                                     "answer the question.")
                  :tools [ { "type" "code_interpreter" } ]
                  :headers { "OpenAI-Beta" "assistants=v2" })]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/assistant-create](#)

Create an assistant with a model and instructions.

[openai/assistant-list](#)

Returns a list of assistants.

[openai/assistant-retrieve](#)

Retrieves an assistant.

[openai/assistant-delete](#)

Delete an assistant.

[top](#)

openai/assistant-delete

```
(assistant-delete assistant-id & options)
```

Delete an assistant.

Parameter «assistant-id»

The ID of the assistant to delete.

Parameter «options»

:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "assistants=v2"}
:uri	An OpenAI assistants URL. E.g.: "https://api.openai.com/v1/assistants/{assistant-id}". Defaults to "https://api.openai.com/v1/assistants/{assistant-id}"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/assistant-delete "asst_abc123"
                                          :headers { "OpenAI-Beta" "assistants=v2" })]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/assistant-create](#)

Create an assistant with a model and instructions.

[openai/assistant-list](#)

Returns a list of assistants.

[openai/assistant-retrieve](#)

Retrieves an assistant.

[openai/assistant-delete](#)

Delete an assistant.

[top](#)

openai/assistant-list

(assistant-list & options)

Returns a list of assistants.

Parameter «options»

:limit	A limit on the number of objects to be returned. Limit can range between 1 and 100, and the default is 20.
:order	Sort order by the created_at timestamp of the objects. "asc" for ascending order and "desc" for descending order.
:after	A cursor for use in pagination. after is an object ID that defines your place in the list. For instance, if you make a list request and receive 100 objects, ending with obj_foo, your subsequent call can include after=obj_foo in order to fetch the next page of the list.
:before	A cursor for use in pagination. before is an object ID that defines your place in the list. For instance, if you make a list

request and receive 100 objects, ending with `obj_foo`, your subsequent call can include `before=obj_foo` in order to fetch the previous page of the list.

<code>:openai-api-key</code>	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
<code>:headers</code>	Additional headers. E.g.: {"OpenAI-Beta" "assistants=v2"}
<code>:uri</code>	An OpenAI assistants URL. E.g.: "https://api.openai.com/v1/assistants". Defaults to "https://api.openai.com/v1/assistants"
<code>:debug</code>	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

<code>:status</code>	The HTTP status (a long)
<code>:mimetype</code>	The content type's mimetype
<code>:headers</code>	A map of headers. key: header name, value: list of header values
<code>:data</code>	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/assistant-list :limit 10
                                       :order "asc"
                                       :headers { "OpenAI-Beta" "assistants=v2" })]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/assistant-create](#)

Create an assistant with a model and instructions.

[openai/assistant-list](#)

Returns a list of assistants.

[openai/assistant-retrieve](#)

Retrieves an assistant.

[openai/assistant-delete](#)

Delete an assistant.

[top](#)

openai/assistant-modify

```
(assistant-modify assistant-id & options)
```

Modifies an assistant.

Parameter «name»

The name of the assistant. The maximum length is 256 characters.

Parameter «model»

ID of the model to use. E.g.: `:gpt-4o`

Parameter «options»

:name	The name of the assistant. The maximum length is 256 characters.
:model	The ID of the model to use. E.g.: <code>:gpt-4o</code>
:description	The description of the assistant. The maximum length is 512 characters.
:instructions	The system instructions that the assistant uses. The maximum length is 256,000 characters.
:tools	A list of tool enabled on the assistant. There can be a maximum of 128 tools per assistant. Tools can be of types "code_interpreter", "file_search", or "function".
:tool-resources	A set of resources that are used by the assistant's tools. The resources are specific to the type of tool. For example, the code_interpreter tool requires a list of file IDs, while the file_search tool requires a list of vector store IDs.
:assistant-opts	A map of additional assistant options like "metadata", "temperature", "top_p", "response_format". See: OpenAI Request Options
:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "assistants=v2"}
:uri	An OpenAI assistants URI. E.g.: "https://api.openai.com/v1/assistants". Defaults to "https://api.openai.com/v1/assistants"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/assistant-create
                  :instructions (str "You are an HR bot, and you have access to "
                                   "files to answer employee questions about "
                                   "company policies. Always response with info "
                                   "from either of the files.")
                  :tools [ { "type" "file_search" } ]
                  :headers { "OpenAI-Beta" "assistants=v2" })]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/assistant-create](#)

Create an assistant with a model and instructions.

[openai/assistant-list](#)

Returns a list of assistants.

[openai/assistant-retrieve](#)

Retrieves an assistant.

[openai/assistant-delete](#)

Delete an assistant.

openai/assistant-retrieve

(assistant-retrieve assistant-id & options)

Retrieves an assistant.

Parameter «assistant-id»

The ID of the assistant to retrieve.

Parameter «options»

:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "assistants=v2"}
:uri	An OpenAI assistants URL. E.g.: "https://api.openai.com/v1/assistants/{assistant-id}". Defaults to "https://api.openai.com/v1/assistants/{assistant-id}"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/assistant-retrieve "asst_abc123"
                                           :headers { "OpenAI-Beta" "assistants=v2" })]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/assistant-create](#)

Create an assistant with a model and instructions.

[openai/assistant-list](#)

Returns a list of assistants.

[openai/assistant-retrieve](#)

Retrieves an assistant.

[openai/assistant-delete](#)

Delete an assistant.

openai/audio-file-ext

(audio-file-ext mimetype)

Returns the file extension for an audio mimetype.

Examples:

mimetype	file extension
audio/aac	"aac"
audio/flac	"flac"
audio/mpeg	"mp3"
audio/mp4	"mp4"
audio/mpega	"mpega"
audio/opus	"opus"
audio/ogg	"ogg"
audio/pcm	"pcm"
audio/wav	"wav"
audio/webm	"webm"
else	"binary"

[top](#)

openai/audio-speech-generate

(audio-speech-generate text voice response-format & options)

Generates audio from the input text.

Parameter «text»

"The quick brown fox jumped over the lazy dog."

Parameter «voice»

The voice to use when generating the audio.

- `:alloy`
- `:echo`
- `:fable`
- `:onyx`
- `:nova`
- `:shimmer`

Parameter «response-format»

The format in which the generated images are returned

- `:mp3` (mimetype: audio/mpeg)
- `:opus` (mimetype: audio/opus)
- `:aac` (mimetype: audio/aac)
- `:flac` (mimetype: audio/flac)

- `:wav` (mimetype: audio/wav)
- `:pcm` (mimetype: audio/pcm)

Parameter request «options»

<code>:model</code>	An OpenAI model. E.g.: "tts-1". Defaults to "tts-1". The model can also be passed as a keyword. E.g.: <code>:tts-1</code> , <code>:tts-1-hd</code> , ...
<code>:openai-api-key</code>	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
<code>:audio-opts</code>	An optional map of OpenAI audio options. Map keys can be keywords or strings. E.g. <code>{ :speed 1.0 }</code> . See: OpenAI Request Options
<code>:openai-api-key</code>	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
<code>:headers</code>	Additional headers. E.g.: {"OpenAI-Beta" "audio=v2"}
<code>:uri</code>	An OpenAI audio speech URI. E.g.: "https://api.openai.com/v1/audio/speech". Defaults to "https://api.openai.com/v1/audio/speech"
<code>:debug</code>	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

<code>:status</code>	The HTTP status (a long)
<code>:mimetype</code>	The content type's mimetype
<code>:headers</code>	A map of headers. key: header name, value: list of header values
<code>:data</code>	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Audio API](#)

```
(do
  (load-module :openai)

  (let [text      "The quick brown fox jumped over the lazy dog."
        response (openai/audio-speech-generate text
                                                :alloy
                                                :mp3
                                                :model :tts-1
                                                :audio-opts { :speed 1.0 })])

  (openai/assert-response-http-ok response)
  (let [audio      (:data response)
        size       (/ (count audio) 1024.0)
        file-ext   (openai/audio-file-ext (:mimetype response))
        file       (str "./audio." file-ext)]
    (printf "Saving audio (%.1fKB) to: %s\n" size file)
    (io/spit file audio)))
```

SEE ALSO

[openai/audio-speech-transcribe](#)

Transcribes audio into the input language.

[openai/audio-speech-translate](#)

Translates audio into English.

[openai/audio-file-ext](#)

Returns the file extension for an audio mimetype.

openai/audio-speech-transcribe

(audio-speech-transcribe data audio-type response-format & options)

Transcribes audio into the input language.

Parameter «data»

The audio data (a byte buffer)

Parameter «audio-type»

The audio type

- `:flac` (mimetype: audio/flac)
- `:mp3` (mimetype: audio/mpeg)
- `:mp4` (mimetype: audio/mp4)
- `:m4a` (mimetype: audio/m4a)
- `:mpega` (mimetype: audio/mpega)
- `:ogg` (mimetype: audio/ogg)
- `:wav` (mimetype: audio/wav)
- `:webm` (mimetype: audio/webm)

Parameter «response-format»

The format in which the transcribed text is returned

- `:json`
- `:text`
- `:srt`
- `:verbose_json`
- `:vtt`

Parameter «options»

<code>:model</code>	An OpenAI model. E.g.: "whisper-1". Defaults to "whisper-1". The model can also be passed as a keyword. E.g.: <code>:whisper-1</code> ,...
<code>:audio-opts</code>	An optional map of OpenAI audio options. Map keys can be keywords or strings. E.g. <code>{ :language "en", :temperature 0, :timestamp_granularities "word" }</code> . See: OpenAI Request Options
<code>:openai-api-key</code>	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
<code>:headers</code>	Additional headers. E.g.: <code>{"OpenAI-Beta" "audio=v2"}</code>
<code>:uri</code>	An OpenAI audio speech URL. E.g.: "https://api.openai.com/v1/audio/transcriptions". Defaults to "https://api.openai.com/v1/audio/transcriptions"
<code>:debug</code>	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

<code>:status</code>	The HTTP status (a long)
<code>:mimetype</code>	The content type's mimetype
<code>:headers</code>	A map of headers. key: header name, value: list of header values

:data If the response HTTP status is HTTP_OK the data fields contains the chat completion message.
 If the response HTTP status is not HTTP_OK the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Audio API](#)

```
(do
  (load-module :openai)

  (defn generate-mp3-audio [text]
    (let [response (openai/audio-speech-generate text
                                                  :alloy
                                                  :mp3
                                                  :model :tts-1)]

      (openai/assert-response-http-ok response)
      (:data response)))

  (let [text      "The quick brown fox jumped over the lazy dog."
        audio-data (generate-mp3-audio text)
        response   (openai/audio-speech-transcribe audio-data
                                                    :mp3
                                                    :json)]

    (openai/assert-response-http-ok response)
    (println (:text (:data response)))))

(do
  (load-module :openai)

  (defn generate-mp3-audio [text]
    (let [response (openai/audio-speech-generate text
                                                  :alloy
                                                  :mp3
                                                  :model :tts-1)]

      (openai/assert-response-http-ok response)
      (:data response)))

  (let [text      "The quick brown fox jumped over the lazy dog."
        audio-data (generate-mp3-audio text)
        audio-opts { :language "en"      ;; ISO-639-1
                     :temperature 0
                     :timestamp_granularities "word" }
        response   (openai/audio-speech-transcribe audio-data
                                                    :mp3
                                                    :verbose_json
                                                    :audio-opts audio-opts)]

    (openai/assert-response-http-ok response)
    (prn (:data response)))))
```

SEE ALSO

[openai/audio-speech-generate](#)

Generates audio from the input text.

[openai/audio-speech-translate](#)

Translates audio into English.

[openai/audio-file-ext](#)

Returns the file extension for an audio mimetype.

openai/audio-speech-translate

(audio-speech-translate data audio-type response-format & options)

Translates audio into English.

Parameter «data»

The audio data (a byte buffer)

Parameter «audio-type»

The audio type

- `:flac` (mimetype: audio/flac)
- `:mp3` (mimetype: audio/mpeg)
- `:mp4` (mimetype: audio/mp4)
- `:m4a` (mimetype: audio/m4a)
- `:mpega` (mimetype: audio/mpega)
- `:ogg` (mimetype: audio/ogg)
- `:wav` (mimetype: audio/wav)
- `:webm` (mimetype: audio/webm)

Parameter «response-format»

The format in which the transcribed text is returned

- `:json`
- `:text`
- `:srt`
- `:verbose_json`
- `:vtt`

Parameter «options»

<code>:model</code>	An OpenAI model. E.g.: "whisper-1". Defaults to "whisper-1". The model can also be passed as a keyword. E.g.: <code>:whisper-1</code> ,...
<code>:audio-opts</code>	An optional map of OpenAI audio options. Map keys can be keywords or strings. E.g. <code>{ :temperature 0, :prompt "....." }</code> . See: OpenAI Request Options
<code>:openai-api-key</code>	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
<code>:headers</code>	Additional headers. E.g.: <code>{"OpenAI-Beta" "audio=v2"}</code>
<code>:uri</code>	An OpenAI audio speech URI. E.g.: "https://api.openai.com/v1/audio/translations". Defaults to "https://api.openai.com/v1/audio/translations"
<code>:debug</code>	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

<code>:status</code>	The HTTP status (a long)
<code>:mimetype</code>	The content type's mimetype
<code>:headers</code>	A map of headers. key: header name, value: list of header values
<code>:data</code>	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message.

If the response HTTP status is not `HTTP_OK` the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Audio API](#)

```
(do
  (load-module :openai)

  (defn generate-mp3-audio [text]
    (let [response (openai/audio-speech-generate text
                                                :alloy
                                                :mp3
                                                :model :tts-1)]

      (openai/assert-response-http-ok response)
      (:data response)))

  (let [text      "Der schnelle braune Fuchs sprang über den faulen Hund."
        audio-data (generate-mp3-audio text)
        response   (openai/audio-speech-translate audio-data
                                                    :mp3
                                                    :json)]

    (openai/assert-response-http-ok response)
    (println (:text (:data response)))))
```

SEE ALSO

[openai/audio-speech-generate](#)

Generates audio from the input text.

[openai/audio-speech-transcribe](#)

Transcribes audio into the input language.

[openai/audio-file-ext](#)

Returns the file extension for an audio mimetype.

[top](#)

openai/chat-completion

(chat-completion prompt & options)

Runs a chat completion.

To run the request asynchronously just wrap it in a `future` and deref it, when the result is required.

Parameter «prompt»

A prompt is either a simple string like:

```
"Who won the world series in 2020?"
```

or a list of prompt messages:

```
[ {"role": "system", "content": "You are a helpful assistant."},
  {"role": "user", "content": "Who won the world series in 2020?"},
  {"role": "assistant", "content": "The Los Angeles Dodgers won the World Series in 2020."},
  {"role": "user", "content": "Where was it played?" } ]
```

Using prompt roles:

system Allows to specify the way the model answers questions.
Classic example: "You are a helpful assistant."

user Equivalent to the queries made by the user.

assistant Assistant roles are the model's responses, based on the user messages.

Parameter request «options»

:model An OpenAI model. E.g.: "gpt-4o". Defaults to "gpt-4o".
The model can also be passed as a keyword. E.g.: `:gpt-4o`, `:gpt-4-turbo`, ...

:tools a list of tools. e.g.: function definitions (see OpenAI api for details)

:tool-choice a tool choice. e.g.: function definitions (see OpenAI api for details)
This forces the model to use a specific function:
`{:type "function", :function {:name "get_n_day_weather_forecast"}}`

:chat-opts An optional map of OpenAI chat request options Map keys can be keywords or strings.
E.g. `{:temperature 0.2}`.
See: [OpenAI Request Options](#)

:openai-api-key An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".

:headers Additional headers. E.g.: {"OpenAI-Beta" "chats=v2"}

:uri An OpenAI chat completion URL. E.g.: "https://api.openai.com/v1/chat/completions".
Defaults to "https://api.openai.com/v1/chat/completions"

:debug An optional debug flag (true/false). Defaults to false.
In debug mode prints the HTTP request and response data

Tools options (a Venice map) for passing a function definition:

```
[
  { :type "function"
    :function {
      :name "get_current_weather"
      :description "Get the current weather"
      :parameters {
        :type "object"
        :properties {
          :location {
            :type "string"
            :description "The city and state, e.g. San Francisco, CA"
          }
          :format {
            :type "string"
            :enum ["celsius", "fahrenheit"]
            :description "The temperature unit to use. Infer this from the users location."
          }
        }
        :required ["location", "format"]
      }
    }
  }
]
```

Return value

Returns a map with the response data:*

:status The HTTP status (a long)

:mimetype The content type's mimetype

:headers A map of headers. key: header name, value: list of header values

:message The final chat completion message if the OpenAI server returned the HTTP status `HTTP_OK`, else `nil`

:data If the response HTTP status is `HTTP_OK` the data fields contains the chat completion message.
If the response HTTP status is not `HTTP_OK` the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Chat Completions API](#)
- [OpenAI API Reference](#)
- [OpenAI API Messages](#)
- [OpenAI API Functions](#)
- [OpenAI API Functions Cookbook](#)
- [OpenAI API Examples](#)
- [OpenAI API Examples Prompts](#)

```
;; print the full OpenAI response message
(do
  (load-module :openai)

  (let [prompt (str "Count to 10, with a comma between each number and "
                    "no newlines.
E.g., 1, 2, 3, ...")
        response (openai/chat-completion prompt
                                          :model :gpt-4o)]

    (println "Status: " (:status response))
    (println "Mimetype:" (:mimetype response))
    (if (= (:status response) 200)
        (println "Message:" (openai/pretty-print-json (:data response)))
        (println "Error:" (:data response)))))

;; print only the OpenAI response message content
(do
  (load-module :openai)

  (let [prompt ""
        Count to 10, with a comma between each number and no newlines.
        E.g., 1, 2, 3, ...
        ""
        response (openai/chat-completion prompt
                                          :model :gpt-4o)]

    (openai/assert-response-http-ok response)
    (println "Message:" (-> (:data response)
                           (openai/chat-extract-response-message-content)
                           (pr-str)))))

;; Dealing with prompt options
(do
  (load-module :openai)

  (let [prompt [ { :role "system"
                  :content (str "You will be provided with statements, and your "
                                "task is to convert them to standard English.") }
                { :role "user"
                  :content "She no went to the market." } ]
        response (openai/chat-completion prompt
                                          :model :gpt-4o
                                          :chat-opts { :temperature 0.7
                                                      :max_tokens 64
                                                      :top_p 1 } )]

    (openai/assert-response-http-ok response)
    (println "Message:" (-> (:data response)
                           (openai/chat-extract-response-message-content)
                           (openai/pretty-print-json)))))
```

SEE ALSO

[openai/chat-completion-streaming](#)

Runs a chat completion in streaming mode.

[openai/chat-extract-response-message-content](#)

Returns the message content of an OpenAI chat JSON response.

[openai/pretty-print-json](#)

Returns a pretty printed Venice JSON data value.

[top](#)

openai/chat-completion-streaming

(chat-completion-streaming prompt handler & options)

Runs a chat completion in streaming mode.

Processes OpenAI server side events (SSE) and calls for every event the handler 'handler'.

Parameter «prompt»

A prompt is either a simple string like:

```
"Who won the world series in 2020?"
```

or a list of prompt messages:

```
[ {"role": "system", "content": "You are a helpful assistant."},
  {"role": "user", "content": "Who won the world series in 2020?"},
  {"role": "assistant", "content": "The Los Angeles Dodgers won the World Series in 2020."},
  {"role": "user", "content": "Where was it played?" } ]
```

Parameter «handler»

The event handler is a three argument function:

```
(defn handler [delta accumulated status] ...)
```

Handler arguments:

<i>delta</i>	the delta message sent with the event
<i>accumulated</i>	the accumulated message
<i>type</i>	the notification type: <ul style="list-style-type: none"><code>:opened</code> - streaming started<code>:data</code> - streamed event<code>:done</code> - streaming done by the server

Parameter request «options»

<code>:model</code>	An OpenAI model. E.g.: "gpt-4o". Defaults to "gpt-4o". The model can also be passed as a keyword. E.g.: <code>:gpt-4o</code> , <code>:gpt-4-turbo</code> , ...
<code>:sync</code>	if <i>true</i> runs the request synchronously and waits until the full message response is available. if <i>false</i> runs the request asynchronously and returns immediately with the response <code>:data</code> field holding a <code>future</code> that can be deref'd (with an optional timeout) to get the full message. Defaults to <i>true</i>
<code>:chat-opts</code>	An optional map of OpenAI chat request options Map keys can be keywords or strings. E.g. <code>{ :temperature 0.2 }</code> . E.g. <code>{ :stream_options { :include_usage true } }</code> . See: OpenAI Request Options
<code>:openai-api-key</code>	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
<code>:headers</code>	Additional headers. E.g.: <code>{"OpenAI-Beta" "chats=v2"}</code>
<code>:uri</code>	An OpenAI chat completion URI. E.g.: "https://api.openai.com/v1/chat/completions". Defaults to "https://api.openai.com/v1/chat/completions"
<code>:debug</code>	An optional debug flag (true/false). Defaults to false.

In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:message	The final chat completion message if the OpenAI server returned the HTTP status <code>HTTP_OK</code> , else <code>nil</code>
:data	If the response HTTP status is <code>HTTP_OK</code> the data field contains the chat completion message and token usage: {:message "1234" :usage nil} If the response HTTP status is not <code>HTTP_OK</code> the data field contains an error message formatted as plain or JSON string.

Note: The streaming mode does not support functions!

See:

- [OpenAI Chat Completions API](#)
- [OpenAI API Reference](#)
- [OpenAI API Messages](#)
- [OpenAI API Examples](#)
- [OpenAI API Examples Prompts](#)

```
;; synchronous
;; prints the arriving events asynchronously, the response is only
;; returned when the final message is available or the request is bad
(do
  (load-module :openai)

  (let [prompt (str "Count to 10, with a comma between each number and "
                    "no newlines.
E.g., 1, 2, 3, ...")
        handler (fn [delta accumulated status]
                   (case status
                     :opened (println "Started...")
                     :data (println "Delta:" (pr-str delta))
                     :done (println "Completed.")))
        response (openai/chat-completion-streaming
                   prompt
                   handler
                   :model :gpt-4o
                   :sync true
                   :chat-opts { :temperature 0.1
                               :stream_options { :include_usage true } })]
    (openai/assert-response-http-ok response)
    (let [data (:data response)]
      (println "Usage: " (pr-str (:usage data)))
      (println "Message:" (pr-str (:message data))))))

;; asynchronous
;; prints the arriving events asynchronously, returns the response
;; immediately with the data `(:data response)` as a future that can
;; be deref'd to get the final message.
(do
  (load-module :openai)

  (let [prompt (str "Count to 10, with a comma between each number and "
                    "no newlines.
E.g., 1, 2, 3, ...")
        handler (fn [delta accumulated status]
```

```

        (case status
          :opened (println "Started...")
          :data   (println "Delta:" (pr-str delta))
          :done   (println "Completed."))
  response (openai/chat-completion-streaming
    prompt
    handler
    :model :gpt-4o
    :sync false
    :chat-opts { :temperature 0.1
                  :stream_options { :include_usage true } } ])
  (openai/assert-response-http-ok response)
  (let [data @(:data response)]
    (println "Usage:  " (pr-str (:usage data)))
    (println "Message:" (pr-str (:message data))))))

```

SEE ALSO

[openai/chat-completion](#)

Runs a chat completion.

[openai/chat-process-streaming-events](#)

Processes OpenAI server side events (SSE) and calls for every event the passed handler function.

[top](#)

openai/chat-extract-function-name

```

(chat-extract-function-name response)
(chat-extract-function-name response choice-idx tools-calls-idx)

```

Returns the function name of an OpenAI chat JSON response.

SEE ALSO

[openai/chat-extract-response-message](#)

Returns the message of an OpenAI chat JSON response.

[openai/chat-extract-response-message-role](#)

Returns the message role of an OpenAI chat JSON response.

[openai/chat-extract-response-message-content](#)

Returns the message content of an OpenAI chat JSON response.

[openai/chat-extract-response-tool-calls-id](#)

Returns the message "tool_calls" id of an OpenAI chat JSON response.

[top](#)

openai/chat-extract-response-message

```

(chat-extract-response-message response)
(chat-extract-response-message response choice-idx)

```

Returns the message of an OpenAI chat JSON response.

SEE ALSO

[openai/chat-extract-response-message](#)

Returns the message of an OpenAI chat JSON response.

[openai/chat-extract-response-message-role](#)

Returns the message role of an OpenAI chat JSON response.

[openai/chat-extract-response-message-content](#)

Returns the message content of an OpenAI chat JSON response.

[openai/chat-extract-response-tool-calls-id](#)

Returns the message "tool_calls" id of an OpenAI chat JSON response.

[openai/chat-extract-function-name](#)

Returns the function name of an OpenAI chat JSON response.

[top](#)

openai/chat-extract-response-message-content

```
(chat-extract-response-message-content response)
(chat-extract-response-message-content response choice-idx)
```

Returns the message content of an OpenAI chat JSON response.

SEE ALSO

[openai/chat-extract-response-message](#)

Returns the message of an OpenAI chat JSON response.

[openai/chat-extract-response-message-role](#)

Returns the message role of an OpenAI chat JSON response.

[openai/chat-extract-response-tool-calls-id](#)

Returns the message "tool_calls" id of an OpenAI chat JSON response.

[openai/chat-extract-function-name](#)

Returns the function name of an OpenAI chat JSON response.

[top](#)

openai/chat-extract-response-message-role

```
(chat-extract-response-message-role response)
(chat-extract-response-message-role response choice-idx)
```

Returns the message role of an OpenAI chat JSON response.

SEE ALSO

[openai/chat-extract-response-message](#)

Returns the message of an OpenAI chat JSON response.

[openai/chat-extract-response-message-content](#)

Returns the message content of an OpenAI chat JSON response.

[openai/chat-extract-response-tool-calls-id](#)

Returns the message "tool_calls" id of an OpenAI chat JSON response.

[openai/chat-extract-function-name](#)

Returns the function name of an OpenAI chat JSON response.

openai/chat-extract-response-tool-calls-id

```
(chat-extract-response-tool-calls-id response)
(chat-extract-response-tool-calls-id response choice-idx)
```

Returns the message "tool_calls" id of an OpenAI chat JSON response.

SEE ALSO

[openai/chat-extract-response-message](#)

Returns the message of an OpenAI chat JSON response.

[openai/chat-extract-response-message-role](#)

Returns the message role of an OpenAI chat JSON response.

[openai/chat-extract-response-message-content](#)

Returns the message content of an OpenAI chat JSON response.

[openai/chat-extract-function-name](#)

Returns the function name of an OpenAI chat JSON response.

openai/chat-finish-reason

```
(chat-finish-reason response)
(chat-finish-reason response choice-idx)
```

Returns the finish reason text from an OpenAI JSON response.

The text depends may be "stop" or "tool_calls". The first signals that the response contains an answer from the model to the passed question. With the ladder the models signals to the caller that functions must be executed to get specific data to answer the question.

SEE ALSO

[openai/chat-finish-reason-stop?](#)

Returns true if the OpenAI JSON response provides an answer to the prompt.

[openai/chat-finish-reason-tool-calls?](#)

Returns true if the OpenAI JSON response contains tool calls (functions) that it wants the client to run

[openai/exec-fn](#)

Execute all functions from an OpenAI JSON response.

openai/chat-finish-reason-stop?

```
(chat-finish-reason-stop? response)
(chat-finish-reason-stop? response choice-idx)
```

Returns true if the OpenAI JSON response provides an answer to the prompt.

SEE ALSO

[openai/chat-finish-reason](#)

Returns the finish reason text from an OpenAI JSON response.

[openai/chat-finish-reason-tool-calls?](#)

Returns true if the OpenAI JSON response contains tool calls (functions) that it wants the client to run

[openai/exec-fn](#)

Execute all functions from an OpenAI JSON response.

top

openai/chat-finish-reason-tool-calls?

```
(chat-finish-reason-tool-calls? response)
(chat-finish-reason-tool-calls? response choice-idx)
```

Returns true if the OpenAI JSON response contains tool calls (functions) that it wants the client to run

SEE ALSO

[openai/chat-finish-reason](#)

Returns the finish reason text from an OpenAI JSON response.

[openai/chat-finish-reason-stop?](#)

Returns true if the OpenAI JSON response provides an answer to the prompt.

[openai/exec-fn](#)

Execute all functions from an OpenAI JSON response.

top

openai/chat-process-streaming-events

```
(chat-process-streaming-events response handler & options)
```

Processes OpenAI server side events (SSE) and calls for every event the passed handler function.

Returns a `future`. This gives the caller the choice to synchronously or asynchronously process the events from the OpenAI server.

Note: The response from the server must be of the mimetype "text/event-stream" otherwise the processor throws an exception!

The event handler is a three argument function:

```
(defn handler [delta accumulated status] ...)
```

<i>delta</i>	the delta message sent with the event
<i>accumulated</i>	the accumulated message
<i>type</i>	the notification type: <ul style="list-style-type: none"><code>:opened</code> - streaming started<code>:data</code> - streamed event<code>:done</code> - streaming done by the server

Parameter «options»

<code>:debug</code>	An optional debug flag (true/false). Defaults to false. In debug mode prints the streaming response data
---------------------	---


```

(do
  (load-module :openai)
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [api-key (system-env "OPENAI_API_KEY")
        content (str "Count to 10, with a comma between each number "
                      "and no newlines.
E.g., 1, 2, 3, ...")
        body { :model :gpt-4o
                :messages [ { :role "user"
                              :content content } ]
                :stream true }
        response (hc/send :post
                          "https://api.openai.com/v1/chat/completions"
                          :headers { "Content-Type" "application/json"
                                     "Authorization" (str "Bearer " api-key)}
                          :body (json/write-str body)
                          :debug false)]
    (println "Status:" (:http-status response))
    (if (= "text/event-stream" (:content-type-mimetype response))
        (let [data @(openai/chat-process-streaming-events
                      response
                      (fn [delta accumulated status]
                        (case status
                          :opened (println "Started...")
                          :data (println "Delta:" (pr-str delta))
                          :done (println "Completed.")))]
              (println "Message:" (pr-str (message data))))
            (println (hc/slurp-response response :json-parse-mode :pretty-print))))))

```

SEE ALSO

[http-client-j8/slurp-response](#)

Slurps the response data from the response' input stream.

top

openai/embedding-create

(embedding-create input & options)

Creates an embedding vector representing the input text.

Parameter «input»

The input text to embed

Parameter «options»

:model	An OpenAI model. E.g.: "text-embedding-ada-002". Defaults to "text-embedding-ada-002". The model can also be passed as a keyword. E.g.: :text-embedding-ada-002, :text-embedding-3-small, :text-embedding-3-large
:embed-opts	An optional map of OpenAI embedding request options Map keys can be keywords or strings. E.g. { :encoding_format :float } . E.g. { :dimensions 1536 } . See: OpenAI Request Options
:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "assistants=v2"}
:uri	An OpenAI assistants URI. E.g.: "https://api.openai.com/v1/embeddings".

Defaults to "https://api.openai.com/v1/embeddings"

:debug An optional debug flag (true/false). Defaults to false.
In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status The HTTP status (a long)

:mimetype The content type's mimetype

:headers A map of headers. key: header name, value: list of header values

:data If the response HTTP status is `HTTP_OK` the data fields contains the chat completion message.
If the response HTTP status is not `HTTP_OK` the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/embedding-create
                  "Happy Christmas ..."
                  :embed-opts { :model "text-embedding-ada-002"
                                :encoding_format :float} )])
    (openai/assert-response-http-ok response)
    (let [data (:data response)
          embed-vec (:embedding (first (:data data)))]
      (prn data))))
```

[top](#)

openai/exec-fn

(exec-fn response fn-map)

Execute all functions from an OpenAI JSON response.

`fn-map` is map of named functions:

```
{ "get_current_weather"      get-current-weather
  "get_n_day_weather_forecast" get-n-day-weather-forecast }
```

Returns a list of function results, one for each function called.

OK result { :ok value }. E.g: { :ok "15°C" }

ERROR result { :err exception }.

SEE ALSO

[openai/chat-finish-reason](#)

Returns the finish reason text from an OpenAI JSON response.

[openai/chat-finish-reason-stop?](#)

Returns true if the OpenAI JSON response provides an answer to the prompt.

[openai/chat-finish-reason-tool-calls?](#)

Returns true if the OpenAI JSON response contains tool calls (functions) that it wants the client to run

[top](#)

openai/file-delete

(file-delete file-id & options)

Delete a file.

Parameter «file-id»

The ID of the file to use for this request.

Parameter «options»

:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "files=v2"}
:uri	An OpenAI files URI. E.g.: "https://api.openai.com/v1/files/{file-id}". Defaults to "https://api.openai.com/v1/files/{file-id}"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Files API](#)

```
(do
  (load-module :openai)

  (let [response (openai/file-delete "file-u01oro03MMRFwRAypupJX0p0")]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/file-upload](#)

Upload a file that can be used across various endpoints. Individual files can be up to 512 MB, and the size of all files uploaded by ...

[openai/file-list](#)

Returns a list of files that belong to the user's organization.

[openai/file-retrieve](#)

Returns information about a specific file.

[openai/file-retrieve-content](#)

Returns the contents of the specified file.

[top](#)

openai/file-list

(file-list purpose & options)

Returns a list of files that belong to the user's organization.

Parameter «purpose»

The optional purpose is one of `nil`, "assistants", "vision", "batch", "fine-tune"

Parameter «options»

:openai-api-key An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".

:headers Additional headers. E.g.: {"OpenAI-Beta" "files=v2"}

:uri An OpenAI files URI. E.g.: "https://api.openai.com/v1/files?purpose={purpose}".
Defaults to "https://api.openai.com/v1/files?purpose={purpose}"

:debug An optional debug flag (true/false). Defaults to false.
In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status The HTTP status (a long)

:mimetype The content type's mimetype

:headers A map of headers. key: header name, value: list of header values

:data If the response HTTP status is `HTTP_OK` the data fields contains the chat completion message.
If the response HTTP status is not `HTTP_OK` the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Files API](#)

```
(do
  (load-module :openai)

  (let [response (openai/file-list nil)]
    (openai/assert-response-http-ok response)
    (prn (:data response))))

(do
  (load-module :openai)

  (let [response (openai/file-list "assistants")]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/file-upload](#)

Upload a file that can be used across various endpoints. Individual files can be up to 512 MB, and the size of all files uploaded by ...

[openai/file-retrieve](#)

Returns information about a specific file.

[openai/file-delete](#)

Delete a file.

[openai/file-retrieve-content](#)

Returns the contents of the specified file.

openai/file-retrieve

(file-retrieve file-id & options)

Returns information about a specific file.

Parameter «file-id»

The ID of the file to use for this request.

Parameter «options»

:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "files=v2"}
:uri	An OpenAI files URI. E.g.: "https://api.openai.com/v1/files/{file-id}". Defaults to "https://api.openai.com/v1/files/{file-id}"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Files API](#)

```
(do
  (load-module :openai)

  (let [response (openai/file-retrieve "file-uo1oro03MMRFwRAypupJX0p0")]
    (openai/assert-response-http-ok response)
    (prn (:data response)))))
```

SEE ALSO

[openai/file-upload](#)

Upload a file that can be used across various endpoints. Individual files can be up to 512 MB, and the size of all files uploaded by ...

[openai/file-list](#)

Returns a list of files that belong to the user's organization.

[openai/file-delete](#)

Delete a file.

[openai/file-retrieve-content](#)

Returns the contents of the specified file.

[top](#)

openai/file-retrieve-content

(file-retrieve-content file-id & options)

Returns the contents of the specified file.

Parameter «file-id»

The ID of the file to use for this request.

Parameter «options»

:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "files=v2"}
:uri	An OpenAI files URI. E.g.: "https://api.openai.com/v1/files/{file-id}/content". Defaults to "https://api.openai.com/v1/files/{file-id}/content"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Files API](#)

```
(do
  (load-module :openai)

  (let [response (openai/file-retrieve-content "file-uo1oro03MMRFwRAypupJX0p0")]
    (openai/assert-response-http-ok response)
    (let [data      (:data response)
          file      "./example.pdf"]
      (io/spit file data)
      (prn "Saved to:" file)))))
```

SEE ALSO

[openai/file-upload](#)

Upload a file that can be used across various endpoints. Individual files can be up to 512 MB, and the size of all files uploaded by ...

[openai/file-list](#)

Returns a list of files that belong to the user's organization.

[openai/file-retrieve](#)

Returns information about a specific file.

[openai/file-delete](#)

Delete a file.

[top](#)

openai/file-upload

(file-upload file-data file-name file-mimetype purpose & options)

Upload a file that can be used across various endpoints. Individual files can be up to 512 MB, and the size of all files uploaded by one organization can be up to 100 GB.

Parameters file

«file-data» The file data, a `bytebuf` «file-name» The file name. E.g.: "product-into-pdf" «file-mimetype» The file mimetype. E.g.: "application/pdf"

Parameter «purpose»

Purpose is one of "assistants", "vision", "batch", "fine-tune"

Parameter «options»

:openai-api-key An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers Additional headers. E.g.: {"OpenAI-Beta" "files=v2"}
:uri An OpenAI files URI. E.g.: "https://api.openai.com/v1/files".
Defaults to "https://api.openai.com/v1/files"
:debug An optional debug flag (true/false). Defaults to false.
In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status The HTTP status (a long)
:mimetype The content type's mimetype
:headers A map of headers. key: header name, value: list of header values
:data If the response HTTP status is `HTTP_OK` the data fields contains the chat completion message.
If the response HTTP status is not `HTTP_OK` the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Files API](#)

```
(do
  (load-module :openai)

  (let [file      "https://raw.githubusercontent.com/jlangch/venice/master/doc/pdfs/fonts-example.pdf"
        response (openai/file-upload (io/download file :binary true)
                                      "example.pdf"
                                      "application/pdf"
                                      "assistants")]

    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/file-list](#)

Returns a list of files that belong to the user's organization.

[openai/file-retrieve](#)

Returns information about a specific file.

[openai/file-delete](#)

Delete a file.

[openai/file-retrieve-content](#)

Returns the contents of the specified file.


```

                                :image-opts {:quality "hd"}}]
(openai/assert-response-http-ok response)
(println "Response:" (openai/pretty-print-json (:data response))))

;; :b64_json => print the full OpenAI response message
(do
  (load-module :openai)

  (let [prompt    "A portrait of a dog in a library, Sigma 85mm f/1.4"
        response (openai/image-create prompt
                                       :b64_json
                                       :model :dall-e-3
                                       :image-opts {:quality "hd"})]
    (openai/assert-response-http-ok response)
    (println "Response:" (openai/pretty-print-json (:data response)))))

;; :url => save the image
(do
  (load-module :openai)
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [prompt    "A portrait of a dog in a library, Sigma 85mm f/1.4"
        response (openai/image-create prompt
                                       :url
                                       :model :dall-e-3
                                       :image-opts {:quality "hd"})]
    (openai/assert-response-http-ok response)
    (let [data      (:data (:data response))
          img-data  (first data) ;; 1st image data
          url       (:url img-data)
          _         (println "Downloading image...")
          img       (openai/image-download url "image-1")
          file      (str "." (:name img))]
      (io/spit file (:data img))
      (println "Saved image to:" file))))

;; :b64_json => save the image
(do
  (load-module :openai)
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (let [prompt    "A portrait of a dog in a library, Sigma 85mm f/1.4"
        response (openai/image-create prompt
                                       :b64_json
                                       :model :dall-e-3
                                       :image-opts {:quality "hd"})]
    (openai/assert-response-http-ok response)
    (let [data      (:data (:data response))
          img-data  (first data) ;; 1st image data
          img       (->> (get img-data :b64_json)
                        (str/decode-base64))
          file      "./image-2.png"]
      (io/spit file img)
      (println "Saved image to:" file))))

```

SEE ALSO

[openai/image-variants](#)

Create image variants.

[openai/image-edits](#)

Edits an image.

[openai/pretty-print-json](#)

Returns a pretty printed Venice JSON data value.

[openai/image-download](#)

Downloads an image from the given url.

[top](#)

openai/image-download

(image-download url basename)

Downloads an image from the given url.

Returns a map with the image data.

E.g.: basename = image-1

```
{ :name      image-1.png
  :mimetype  "image/png"
  :data      <bytebuf> }
```

[top](#)

openai/image-edits

(image-edits image mask prompt response-format & options)

Edits an image.

Parameter «image»

The image to edit.

Parameter «mask»

The mask image.

Parameter «prompt»

A text description of the desired image.

Parameter «response-format»

The format in which the generated images are returned

- `:url`
- `:b64_json`

Note: URLs are only valid for 60 minutes after the image has been generated.

Parameter request «options»

:model An OpenAI model. E.g.: "dall-e-2". Defaults to "dall-e-2".
 The model can also be passed as a keyword. E.g.: `:dall-e-2` , `:dall-e-3` , ...

:image-opts An optional map of OpenAI image request options Map keys can be keywords or strings.
 E.g. { `:size` "1024x1024", `:n` 1 } .
 See: [OpenAI Request Options](#)

:openai-api-key An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".

:headers	Additional headers. E.g.: {"OpenAI-Beta" "images=v2"}
:uri	An OpenAI chat completion URI. E.g.: "https://api.openai.com/v1/images/edits". Defaults to "https://api.openai.com/v1/images/edits"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Image Guide](#)
- [OpenAI Image API](#)

```
(do
  (load-module :openai)
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])
  (load-module :images)

  (defn create-image [prompt img-file]
    (println "Requesting image...")
    (let [response (openai/image-create prompt
                                         :b64_json
                                         :model :dall-e-3
                                         :image-opts {:size "1024x1024", :quality "hd"})]
      (openai/assert-response-http-ok response)
      (let [data (:data (:data response))
            img-data (first data) ;; 1st image data
            img (->> (get img-data :b64_json)
                     (str/decode-base64))]
        (io/spit img-file img)
        (println "Saved image to:" img-file))))

  (defn create-image-mask [img-file mask-file]
    (println "Creating mask...")
    (let [img (->> (images/load (io/file img-file))
                  (images/convert-to-rgba))
          [w h] (images/dimension img)
          g2d (images/g2d img)]
      (. g2d :setComposite (. :java.awt.AlphaComposite :Clear))
      (images/fg-color g2d images/white)
      (images/fill-circle g2d (/ w 2) (/ h 2) (/ w 4))
      (images/dispose g2d)
      (images/save img :png (io/file mask-file))
      (println "Saved mask to:" mask-file)))

  (defn create-image-edit [prompt img-file mask-file result-file]
    (println "Requesting image edit...")
    (let [response (openai/image-edits (io/slurp img-file :binary true)
                                       (io/slurp mask-file :binary true)
                                       prompt
                                       :b64_json
                                       :model :dall-e-2
                                       :image-opts {:size "1024x1024", :n 1})]
      (openai/assert-response-http-ok response))
```

```

    (let [data      (:data (:data response))
          img-data  (first data) ;; 1st image data
          img       (->> (get img-data :b64_json)
                        (str/decode-base64))]

      (io/spit result-file img)
      (println "Saved edited image to:" result-file)))

;; create the initial image
(create-image "A sunlit indoor lounge area with a large pool at the center of the image"
              "./image-edit-source.png")

;; derive an image with a mask at the center for placing the flamingo
(create-image-mask "./image-edit-source.png"
                  "./image-edit-mask.png")

;; place the flamingo in the mask area at the center
(create-image-edit "A sunlit indoor lounge area with a pool containing a flamingo"
                  "./image-edit-source.png"
                  "./image-edit-mask.png"
                  "./image-edit-result.png"))

```

SEE ALSO

[openai/image-create](#)

Create images.

[openai/image-variants](#)

Create image variants.

[openai/pretty-print-json](#)

Returns a pretty printed Venice JSON data value.

[openai/image-download](#)

Downloads an image from the given url.

top

openai/image-variants

```
(image-variants image response-format & options)
```

Create image variants.

It only supports "dall-e-2". The quality of the variants is poor. Looks like OpenAI is giving it up.

Parameter «image»

The image to create variants from.

Parameter «response-format»

The format in which the generated images are returned

- `:url`
- `:b64_json`

Note: URLs are only valid for 60 minutes after the image has been generated.

Parameter request «options»

:model An OpenAI model. E.g.: "dall-e-2". Defaults to "dall-e-2".
 The model can also be passed as a keyword. E.g.: `:dall-e-2` , `:dall-e-3` , ...

:image-opts	An optional map of OpenAI image request options Map keys can be keywords or strings. E.g. { :size "1024x1024", :n 1 } . See: OpenAI Request Options
:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "images=v2"}
:uri	An OpenAI chat completion URL. E.g.: "https://api.openai.com/v1/images/variants". Defaults to "https://api.openai.com/v1/images/variants"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Image Guide](#)
- [OpenAI Image API](#)

```
(do
  (load-module :openai)
  (load-module :http-client-j8 ['http-client-j8 :as 'hc])

  (defn create-image [img-file]
    (println "Requesting image...")
    (let [prompt "A portrait of a dog in a library, Sigma 85mm f/1.4"
          response (openai/image-create prompt :b64_json
                                         :model :dall-e-3
                                         :image-opts {:size "1024x1024", :quality "hd"})]
      (openai/assert-response-http-ok response)
      (let [data (:data (:data response))
            img-data (first data) ;; 1st image data
            img (->> (get img-data :b64_json)
                     (str/decode-base64))]
        (io/spit img-file img)
        (println "Saved image to:" img-file))))

  (defn create-image-variant [img-file img-variant-file]
    (println "Requesting image variant...")
    (let [img (io/slurp img-file :binary true)
          response (openai/image-variants img
                                         :b64_json
                                         :model :dall-e-3
                                         :image-opts {:size "1024x1024", :n 1})]
      (openai/assert-response-http-ok response)
      (let [data (:data (:data response))
            img-data (first data) ;; 1st image data
            img (->> (get img-data :b64_json)
                     (str/decode-base64))]
        (io/spit img-variant-file img)
        (println "Saved variant to:" img-variant-file))))

  (create-image "./image-variant-1.png") ;; create an image
  (create-image-variant "./image-variant-1.png"
                        "./image-variant-2.png") ;; create a variant of the image
```

SEE ALSO

[openai/image-create](#)

Create images.

[openai/image-edits](#)

Edits an image.

[openai/pretty-print-json](#)

Returns a pretty printed Venice JSON data value.

[openai/image-download](#)

Downloads an image from the given url.

[top](#)

openai/model-delete

(model-delete model & options)

Deletes a model instance.

Parameter «model»

The ID of the model to use for this request

Parameter «options»

:openai-api-key An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".

:headers Additional headers. E.g.: {"OpenAI-Beta" "models=v2"}

:uri An OpenAI models URI. E.g.: "https://api.openai.com/v1/models/{model}".
Defaults to "https://api.openai.com/v1/models/{model}"

:debug An optional debug flag (true/false). Defaults to false.
In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status The HTTP status (a long)

:mimetype The content type's mimetype

:headers A map of headers. key: header name, value: list of header values

:data If the response HTTP status is `HTTP_OK` the data fields contains the chat completion message.
If the response HTTP status is not `HTTP_OK` the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/model-delete "xyz")]
    (openai/assert-response-http-ok response)
    (prn (:data response)))))
```

SEE ALSO

[openai/model-list](#)

Returns a list of the currently available models, and provides basic information about each one such as the owner and availability.

[openai/model-retrieve](#)

Retrieves a model instance, providing basic information about the model such as the owner and permissioning.

[top](#)

openai/model-list

(model-list & options)

Returns a list of the currently available models, and provides basic information about each one such as the owner and availability.

Parameter «options»

:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "models=v2"}
:uri	An OpenAI models URL. E.g.: "https://api.openai.com/v1/models". Defaults to "https://api.openai.com/v1/models"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/model-list)]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/model-retrieve](#)

Retrieves a model instance, providing basic information about the model such as the owner and permissioning.

[openai/model-delete](#)

Deletes a model instance.

[top](#)

openai/model-retrieve

(model-retrieve model & options)

Retrieves a model instance, providing basic information about the model such as the owner and permissioning.

Parameter «model»

The ID of the model to use for this request

Parameter «options»

:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "models=v2"}
:uri	An OpenAI models URI. E.g.: "https://api.openai.com/v1/models/{model}". Defaults to "https://api.openai.com/v1/models/{model}"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/model-retrieve "gpt-4o")]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/model-list](#)

Returns a list of the currently available models, and provides basic information about each one such as the owner and availability.

[openai/model-delete](#)

Deletes a model instance.

[top](#)

openai/pretty-print-json

```
(pretty-print-json data)
```

Returns a pretty printed Venice JSON data value.

SEE ALSO

[openai/chat-extract-response-message-content](#)

Returns the message content of an OpenAI chat JSON response.

[top](#)

openai/thread-create

(thread-create & options)

Create a thread that assistants can interact with.

Parameter «options»

:messages	A list of messages
:tool-resources	A set of resources that are made available to the assistant's tools in this thread. The resources are specific to the type of tool. For example, the <code>code_interpreter</code> tool requires a list of file IDs, while the <code>file_search</code> tool requires a list of vector store IDs.
:metadata	Set of 16 key-value pairs that can be attached to an object. This can be useful for storing additional information about the object in a structured format. Keys can be a maximum of 64 characters long and values can be a maximum of 512 characters long.
:openai-api-key	An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers	Additional headers. E.g.: {"OpenAI-Beta" "assistants=v2"}
:uri	An OpenAI assistants URI. E.g.: "https://api.openai.com/v1/threads". Defaults to "https://api.openai.com/v1/threads"
:debug	An optional debug flag (true/false). Defaults to false. In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status	The HTTP status (a long)
:mimetype	The content type's mimetype
:headers	A map of headers. key: header name, value: list of header values
:data	If the response HTTP status is <code>HTTP_OK</code> the data fields contains the chat completion message. If the response HTTP status is not <code>HTTP_OK</code> the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/thread-create
                  :headers { "OpenAI-Beta" "assistants=v2" })]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/thread-create](#)

Create a thread that assistants can interact with.

[openai/thread-retrieve](#)

Retrieves a thread.

[top](#)

openai/thread-retrieve

(thread-retrieve thread-id & options)

Retrieves a thread.

Parameter thread-id»

The ID of the thread to retrieve.

Parameter «options»

:openai-api-key An optional OpenAI API Key. As default the key is read from the environment variable "OPENAI_API_KEY".
:headers Additional headers. E.g.: {"OpenAI-Beta" "assistants=v2"}
:uri An OpenAI assistants URL. E.g.: "https://api.openai.com/v1/threads/{thread-id}".
 Defaults to "https://api.openai.com/v1/threads/{thread-id}"
:debug An optional debug flag (true/false). Defaults to false.
 In debug mode prints the HTTP request and response data

Return value

Returns a map with the response data:

:status The HTTP status (a long)
:mimetype The content type's mimetype
:headers A map of headers. key: header name, value: list of header values
:data If the response HTTP status is HTTP_OK the data fields contains the chat completion message.
 If the response HTTP status is not HTTP_OK the data fields contains an error message formatted as plain or JSON string.

See:

- [OpenAI Models API](#)

```
(do
  (load-module :openai)

  (let [response (openai/thread-retrieve "thread_abc123"
                                         :headers { "OpenAI-Beta" "assistants=v2" })]
    (openai/assert-response-http-ok response)
    (prn (:data response))))
```

SEE ALSO

[openai/thread-create](#)

Create a thread that assistants can interact with.

[openai/thread-retrieve](#)

Retrieves a thread.

[top](#)

or

```
(or x)
(or x & next)
```

Ors the predicate forms

```
(or true false)
=> true
```

```
(or false false)
=> false
```

```
(or nil 100)
=> 100
```

```
(or)
=> false
```

SEE ALSO

[and](#)

Ands the predicate forms

[not](#)

Returns true if x is logical false, false otherwise.

[top](#)

or-timeout

```
(or-timeout p time time-unit)
```

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

```
(-> (promise (fn [] (sleep 100) "The quick brown fox")))
  (or-timeout 500 :milliseconds)
  (then-apply str/upper-case)
  (deref))
=> "THE QUICK BROWN FOX"
```

```
(-> (promise (fn [] (sleep 300) "The quick brown fox")))
  (or-timeout 200 :milliseconds)
  (then-apply str/upper-case)
  (deref))
=> TimeoutException: java.util.concurrent.TimeoutException
```

```
(-> (promise (fn [] (sleep 300) "The quick brown fox")))
  (then-apply str/upper-case)
  (or-timeout 200 :milliseconds)
  (deref))
=> TimeoutException: java.util.concurrent.TimeoutException
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and set, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two ...

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[then-combine](#)

Applies a function `f` to the result of the previous stage of promise `p` and the result of another promise `p-other`

[then-compose](#)

Composes the result of two promises. f receives the result of the first promise p and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise p with the same result or exception at this stage, that executes the action f. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

ordered-map

```
(ordered-map & keyvals)
(ordered-map map)
```

Creates a new ordered map containing the items.

```
(ordered-map :a 1 :b 2)
=> {:a 1 :b 2}
```

```
(ordered-map (hash-map :a 1 :b 2))
=> {:a 1 :b 2}
```

[top](#)

ordered-map?

```
(ordered-map? obj)
```

Returns true if obj is an ordered map

```
(ordered-map? (ordered-map :a 1 :b 2))
=> true
```

[top](#)

os-arch

```
(os-arch)
```

Returns the OS architecture. E.g: "x86_64"

```
(os-arch)
=> "aarch64"
```

SEE ALSO

[os-type](#)

Returns the OS type. Type is one of :windows, :mac-osx, :linux, :unix, or :unknown

[os-type?](#)

Returns true if the OS id of the type otherwise false. Type is one of :windows, :mac-osx, :linux, or :unix

[os-name](#)

Returns the OS name. E.g.: "Mac OS X"

[os-version](#)

Returns the OS version

[top](#)

os-name

(os-name)

Returns the OS name. E.g.: "Mac OS X"

([os-name](#))

```
=> "Mac OS X"
```

SEE ALSO

[os-type](#)

Returns the OS type. Type is one of :windows, :mac-osx, :linux, :unix, or :unknown

[os-type?](#)

Returns true if the OS id of the type otherwise false. Type is one of :windows, :mac-osx, :linux, or :unix

[os-arch](#)

Returns the OS architecture. E.g: "x86_64"

[os-version](#)

Returns the OS version

[top](#)

os-type

(os-type)

Returns the OS type. Type is one of `:windows`, `:mac-osx`, `:linux`, `:unix`, or `:unknown`

([os-type](#))

```
=> :mac-osx
```

SEE ALSO

[os-type?](#)

Returns true if the OS id of the type otherwise false. Type is one of :windows, :mac-osx, :linux, or :unix

[os-arch](#)

Returns the OS architecture. E.g: "x86_64"

[os-name](#)

Returns the OS name. E.g.: "Mac OS X"

os-version

Returns the OS version

top

os-type?

```
(os-type? type)
```

Returns true if the OS id of the type otherwise false. Type is one of `:windows`, `:mac-osx`, `:linux`, or `:unix`

```
(os-type? :mac-osx)
```

```
=> true
```

```
(os-type? :windows)
```

```
=> false
```

SEE ALSO

[os-type](#)

Returns the OS type. Type is one of `:windows`, `:mac-osx`, `:linux`, `:unix`, or `:unknown`

[os-arch](#)

Returns the OS architecture. E.g: "x86_64"

[os-name](#)

Returns the OS name. E.g.: "Mac OS X"

[os-version](#)

Returns the OS version

top

os-version

```
(os-version)
```

Returns the OS version

```
(os-version)
```

```
=> "14.6.1"
```

SEE ALSO

[os-type](#)

Returns the OS type. Type is one of `:windows`, `:mac-osx`, `:linux`, `:unix`, or `:unknown`

[os-type?](#)

Returns true if the OS id of the type otherwise false. Type is one of `:windows`, `:mac-osx`, `:linux`, or `:unix`

[os-arch](#)

Returns the OS architecture. E.g: "x86_64"

[os-name](#)

Returns the OS name. E.g.: "Mac OS X"

top

parsifal/>>

```
(>> p)
(>> p q)
(>> p q & ps)
```

Returns a new parser that parses a list of parsers. Returns the value of the last parser if all parsers succeed, else the parser fails.

Note: *Parsifal* is not implementing backtracking by default, and instead relies on the programmer to implement backtracking using constructs like `lookahead` and `attempt`.

The parser `>>` does not rewind the input state if any of the sub parsers fails. `>>*` is the backtracking version of `>>` that wraps the parsers within a call to `attempt`. See the backtracking example below.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/>> (p/char #\lparen) (p/digit) (p/char #\rparen)) "(1)")
  ; => #\

  ; Using bindings
  (p/run (p/let->> [l (p/char #\lparen)
                    d (p/digit)
                    r (p/char #\rparen)]
              (p/always (str l d r)))
          "(1)")
  ; => "(1)"
)

; Backtracking demo
(do
  (load-module :parsifal ['parsifal :as 'p])

  ; No backtracking with `>>` parser
  (p/run (p/either (p/>> (p/letter) (p/digit))
                (p/letter))
          "abc")
  ; => ParseError: Unexpected token 'b' at line: 1 column: 2

  ; Backtracking with `>>*` parser
  (p/run (p/either (p/>>* (p/letter) (p/digit))
                (p/letter))
          "abc")
  ; => #\a
)
```

[top](#)

parsifal/SourcePosition

Defines a protocol to add line and column information for custom tokens.

Definition:

```
(defprotocol SourcePosition
  (line [p])
  (column [p]))
```

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (deftype :Token [type :keyword, val :string, line :long, column :long]
    Object
    (toString [this] (str/format "[%s %s (%d,%d)]"
                                   (pr-str (:type this))
                                   (pr-str (:val this))
                                   (:line this)
                                   (:column this)))

    p/SourcePosition
    (line [this] (:line this))
    (column [this] (:column this)))

  (p/defparser lbracket []
    (p/let->> [[l c] (p/pos)
               t      (p/char #\[)]]
      (p/always (Token. :lbracket (str t) l c))))

  (p/run (lbracket) "[1,2,3]")
  ; => [:lbracket "[" (1,1)]
)
```

SEE ALSO

[defprotocol](#)

Defines a new protocol with the supplied function specs.

[deftype](#)

Defines a new custom record type for the name with the fields.

[top](#)

parsifal/always

```
(always x)
```

A parser that always succeeds with the value given and consumes no input.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/defparser integer []
    (p/let->> [t (p/many1 (p/digit))]
      (p/always (long (apply str t)))))

  (p/run (integer) "400")
  ; => 400
)

(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/defparser optional [p default-value]
    (p/either (p/attempt p)
      (p/always default-value)))

  (p/run (optional (p/char #\X) #\?) "X400")
  ; => #\X
)
```



```
(p/run (optional (p/char #\X) #\?) "400")
; => #\?
)
```

[top](#)

parsifal/any

(any)

Consume any single item from the head of the input. This parser will fail to consume if the input is empty.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/any) "Cats")
  ; => #\C

  (p/run (p/any) [#\C #\a #\t #\s])
  ; => #\C
)
```

[top](#)

parsifal/any-char

(any-char)

Consume any character.

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/any-char) "Cats")
  ; => #\C

  (p/run (p/any-char) [#\C #\a #\t #\s])
  ; => #\C
)
```

[top](#)

parsifal/any-char-of

(any-char-of s)

Consume any of the characters given in the string. E.g.: (any-char-of "{[}") .

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])
```

```
(p/run (p/any-char-of "XYZ") "Hello, world!")
; => #\H
)
```

[top](#)

parsifal/attempt

(attempt p)

A parser that will attempt to parse `p`, and upon failure never consume any input.

Note: *Parsifal* is not implementing backtracking by default, and instead relies on the programmer to implement backtracking using constructs like `lookahead` and `attempt`.

The parsers `>>` and `let->>` do not rewind the input state if any of the sub parsers fails. To add backtracking parsers can be wrapped with `attempt!`

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/defparser optional [p default-value]
    (p/either (p/attempt p)
              (p/always default-value)))

  (p/run (optional (p/char #\X) #\?) "400")
  ; => #\?
)

(do
  (load-module :parsifal ['parsifal :as 'p])

  ; Backtracking

  ; No implicit backtracking with `>>` parser!
  (p/run (p/either (p/>> (p/letter) (p/digit))
                  (p/letter))
          "abc")
  ; => ParseError: Unexpected token 'b' at line: 1 column: 2

  ; Explicit backtracking with `>>` parser using `attempt!`
  (p/run (p/either (p/attempt (p/>> (p/letter) (p/digit)))
                  (p/letter))
          "abc")
  ; => #\a
)
```

[top](#)

parsifal/between

(between open close p)

Returns a new parser that parses `open`, `p`, and `close` returning the value of `p` and discarding the values of `open` and `close`. Does not consume any input on failure.

```
(do
  (load-module :parsifal ['parsifal :as 'p])
  (p/run (p/between (p/char #\lparen)
                    (p/char #\rparen)
                    (p/many1 (p/digit))))
  "(123)")
; => [#\1 #\2 #\3]
)
```

[top](#)

parsifal/char

(char)

Consume the given character.

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/char #\H) "Hello")
  ; => #\H

  (p/run (p/char #\H) [#\H #\e #\l #\l #\o])
  ; => #\H
)
```

[top](#)

parsifal/choice

(choice & p)

Returns a new parser that tries each given parsers in turn, returning the value of the first one that succeeds.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/choice (p/many1 (p/digit)) (p/many1 (p/letter))) "Hello")
  ; => [#\H #\e #\l #\l #\o]

  (p/run (p/choice (p/many1 (p/digit)) (p/many1 (p/letter))) "42")
  ; => [#\4 #\2]
)
```

[top](#)

parsifal/defparser

(defparser name args & body)

The `defparser` macro defines `_functions_` that create parsers.

Note: *Parsifal* is not implementing backtracking by default, and instead relies on the programmer to implement backtracking using constructs like `lookahead` and `attempt`.

The parsers created by this macro do not rewind the input state if one of the sub parsers fails. To allow backtracking `attempt` can be used!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/defparser sample []
    (p/string "Hello")
    (p/always 42))

  (p/run (sample) "Hello, world!")
  ; => 42
)

(do
  (load-module :parsifal ['parsifal :as 'p])

  ; Backtracking

  (p/defparser letter-and-digit []
    (p/letter)
    (p/digit))

  ; No implicit backtracking!
  (p/run (p/either (letter-and-digit) (p/letter)) "abc")
  ; => ParseError: Unexpected token 'b' at line: 1 column: 2

  ; Explicit backtracking with `attempt`!
  (p/run (p/either (p/attempt (letter-and-digit)) (p/letter)) "abc")
  ; => #\a
)
```

[top](#)

parsifal/digit

(digit)

Consume a digit [0-9] character.

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/digit) "123")
  ; => #\1

  (p/run (p/any-char) [#\1 #\2 #\3])
  ; => #\1
)
```

[top](#)

parsifal/either

```
(either p q)
```

Returns a new parser that tries `p`, upon success, returning its value, and upon failure (if no input was consumed) tries to parse `q`

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/either (p/many1 (p/digit)) (p/many1 (p/letter))) "Hello")
  ; => [#\H #\e #\l #\l #\o]

  (p/run (p/either (p/many1 (p/digit)) (p/many1 (p/letter))) "42")
  ; => [#\4 #\2]
)
```

[top](#)

parsifal/eof

```
(eof)
(eof err-msg)
```

A parser to detect the end of input. If there is nothing more to consume from the underlying input, this parser succeeds with a `nil` value, otherwise it fails.

A custom error message can be provided for the case the parser fails.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/eof) "")
  ; => nil

  (p/run (p/eof) "a")
  ; => ParseError: Expected end of input at line: 1 column: 1
)
```

[top](#)

parsifal/hexdigit

```
(hexdigit)
```

Consume a hex digit [0-9a-fA-F] character.

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/hexdigit) "A00")
  ; => #\A

  (p/run (p/hexdigit) [#\A #\0 #\0])
  ; => #\A
)
```

parsifal/let->>

```
(let->> [[& bindings_] & body])
```

Binds parser results to names for further processing input.

Note: *Parsifal* is not implementing backtracking by default, and instead relies on the programmer to implement backtracking using constructs like `lookahead` and `attempt`.

The parser `let->>` does not rewind the input state if one of the sub parsers fails. `let->>*` is the backtracking version of `let->>` that wraps the parsers within a call to `attempt`. See the backtracking example below.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/defparser float []
    (p/let->> [i (p/many1 (p/digit))
              d (p/char #\.)
              f (p/many1 (p/digit))]]
    (p/always (apply str (flatten (list i d f))))))

  (p/run (float) "10.56")
  ; => "10.56"
)

(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/defparser int []
    (p/let->> [i (p/many1 (p/digit))]]
    (let [n (long (apply str i))]
      (if (even? n)
          (p/always (str n " is even"))
          (p/always (str n " is odd"))))))

  (p/run (int) "500")
  ; => "500 is even"
)

; Backtracking demo
(do
  (load-module :parsifal ['parsifal :as 'p])

  ; No backtracking with `let->>` parser!
  (p/run (p/either (p/let->> [c (p/letter)
                           d (p/digit)]
                        (p/always (list c d)))
            (p/letter))
        "abc")
  ; => ParseError: Unexpected token 'b' at line: 1 column: 2

  ; Backtracking with `let->>*` parser
  (p/run (p/either (p/let->>* [c (p/letter)
                             d (p/digit)]
                      (p/always (list c d)))
            (p/letter))
        "abc")
  ; => #\a
)
```

parsifal/letter

(letter)

Consume a letter character defined by Java `Character.isLetter(ch)` .

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/letter) "Cats")
  ; => #\C

  (p/run (p/letter) [#\C #\a #\t #\s])
  ; => #\C
)
```

parsifal/letter-or-digit

(letter-or-digit)

Consume a letter or digit character defined by Java `Character.isLetterOrDigit(ch)` .

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/letter-or-digit) "Cats")
  ; => #\C

  (p/run (p/letter-or-digit) "5Cats")
  ; => #\5

  (p/run (p/letter-or-digit) [#\C #\a #\t #\s])
  ; => #\C
)
```

parsifal/lineno

(lineno)

A parser that returns the current line number. It consumes no input.

```
(do
  (load-module :parsifal ['parsifal :as 'p])
```

```
(p/defparser integer []
  (p/let->> [l (p/lineno)
             t (p/many1 (p/digit))])
  (p/always [:int (apply str t) l])))

(p/run (integer) "400")
; => [:int "400" 1]
)
```

top

parsifal/lookahead

```
(lookahead p)
```

A parser that upon success consumes no input, but returns what was parsed.

Note: *Parsifal* is not implementing backtracking by default, and instead relies on the programmer to implement backtracking using constructs like `lookahead` and `attempt`.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/defparser block-string-tok []
    (p/between (p/times 3 (p/char #\quote))
               (p/times 3 (p/char #\quote))
               (p/many (p/let->> [cs (p/lookahead (p/times 3 (p/any-char)))]
                                (if (= cs [#\quote #\quote #\quote])
                                    (p/never)
                                    (p/any-char)))))))

  (p/defparser block-string []
    (p/let->> [s (block-string-tok)]
              (p/always (apply str s)))))

  (p/run (block-string) "\"\"\"A \"string\" with quotes!\"\"\"")
  ; => "A \"string\" with quotes!"
)
```

top

parsifal/many

```
(many p)
```

Returns a new parser that will parse zero or more items that match the given parser `p`. The matched items are concatenated into a sequence.

Note: A `ParseError` will be thrown if this combinator is applied to a parser that accepts the empty string, as that would cause the parser to loop forever.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/many (p/digit)) "1234-0000")
  ; => [#\1 #\2 #\3 #\4]
```



```
(p/run (p/many (p/digit)) "ABC-12345")
; => []
)
```

[top](#)

parsifal/many1

```
(many1 p)
```

Returns a new parser that will parse one or more items that match the given parser `p`. The matched items are concatenated into a sequence.

Note: A `ParseError` will be thrown if this combinator is applied to a parser that accepts the empty string, as that would cause the parser to loop forever.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/many1 (p/digit)) "1234-0000")
  ; => [#\1 #\2 #\3 #\4]

  (p/run (p/many1 (p/digit)) "ABC-12345")
  ; => ParseError: Unexpected token 'A' at line: 1 column: 1
)
```

[top](#)

parsifal/never

```
(never)
(never err-msg)
(never err-msg line column)
```

A parser that always fails, consuming no input.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  ;; parse a string with a single integer
  (p/defparser single-integer []
    (p/let->> [i (p/many1 (p/digit))
               t (p/either (p/eof) (p/any))])
    (if (nil? t)
        (p/always (apply str i))
        (p/never (str "Unexpected token '" t "'")))))

  (p/run (single-integer) "400")
  ; => "400"

  (p/run (single-integer) "400-")
  ; => ParseError: Unexpected token '-' at line: 1 column: 5
)
```

[top](#)

parsifal/none-char-of

(none-char-of s)

Consume all but of the characters given in the string. E.g.: (none-char-of "({}") .

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/none-char-of "()[]{}") "Hello, world!")
  ; => #\H
)
```

[top](#)

parsifal/not-char

(not-char)

Consume all but the given character

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/not-char #\x) "Cats")
  ; => #\C

  (p/run (p/not-char #\x) [#\C #\a #\t #\s])
  ; => #\C
)
```

[top](#)

parsifal/pos

(pos)

A parser that returns the current line/column number as tuple of [line col] . It consumes no input.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/defparser integer []
    (p/let->> [[l c] (p/pos)
               t      (p/many1 (p/digit))]]
    (p/always [:int (apply str t) (list l c)])))

  (p/run (integer) "400")
  ; => [:int "400" (1,1)]
)
```

parsifal/run

```
(run p input)
```

Run a parser `p` over some input. The input can be a string or a seq of tokens, if the parser produces an error, its message is wrapped in a `ParseError` and thrown, and if the parser succeeds, its value is returned.

Parsifal is port of Nate Young's Clojure Parsatron [parser combinators](#) project.

Parsifal is not implementing backtracking by default, and instead relies on the programmer to implement backtracking using constructs like `lookahead` and `attempt`.

A simple parser example:

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/char #\H) "Hello")
  ; => #\H

  (p/run (p/char #\H) [#\H #\e #\l #\l #\o])
  ; => #\H
)
```

parsifal/string

```
(string s)
```

Consume the given string and returns a string. Does not consume any input upon failure.

Note: Works with char items only!

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/string "Hello") "Hello, world!")
  ; => "Hello"

  (p/run (p/string "Hello") (seq "Hello, world!"))
  ; => "Hello"
)

(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/either (p/string "Hello") (p/letter)) "Hello, world!")
  ; => "Hello"

  (p/run (p/either (p/string "Hello") (p/letter)) "Hello, world!")
  ; => #\H
)
```

parsifal/times

(times n p)

Returns a new parser that consumes exactly `n` times what the parser `p` matches. The matched items are concatenated into a sequence. Does not consume any input if not all of the repetitions match.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/times 5 (p/letter)) "Hello, world!")
  ; => [#\H #\e #\l #\l #\o]

  ;; Note: `p/times` is different from parsing letters explicitly
  (p/run (p/>> (p/letter)
               (p/letter)
               (p/letter)
               (p/letter)
               (p/letter))
          "Hello, world!")
  ; => [#\o]
)
```

[top](#)

parsifal/token

(token)

Consume a single item from the head of the input if `(consume? item)` predicate is not `nil`. This parser will fail to consume if either the `consume?` test returns `false` or if the input is empty.

```
(do
  (load-module :parsifal ['parsifal :as 'p])

  (p/run (p/token #(< % 5)) [3 5 7])
  ; => 3

  (p/run (p/token str/upper-case) "Hello")
  ; => #\H
)
```

[top](#)

partial

(partial f args*)

Takes a function `f` and fewer than the normal arguments to `f`, and returns a fn that takes a variable number of additional args. When called, the returned function calls `f` with `args` + additional args.

```
((partial * 2) 3)
=> 6
```

```
(map (partial * 2) [1 2 3 4])
=> (2 4 6 8)

(map (partial reduce +) [[1 2 3 4] [5 6 7 8]])
=> (10 26)

(do
  (def hundred-times (partial * 100))
  (hundred-times 5))
=> 500
```

[top](#)

partition

```
(partition n coll)
(partition n step coll)
(partition n step padcoll coll)
```

Returns a collection of lists of *n* items each, at offsets *step* apart. If *step* is not supplied, defaults to *n*, i.e. the partitions do not overlap. If a *padcoll* collection is supplied, use its elements as necessary to complete last partition upto *n* items. In case there are not enough padding elements, return a partition with less than *n* items. *padcoll* may be a lazy sequence

```
(partition 3 [0 1 2 3 4 5 6])
=> ([0 1 2] [3 4 5])

(partition 3 3 (repeat 99) [0 1 2 3 4 5 6])
=> ([0 1 2] [3 4 5] [6 99 99])

(partition 3 3 [] [0 1 2 3 4 5 6])
=> ([0 1 2] [3 4 5] [6])

(partition 2 3 [0 1 2 3 4 5 6])
=> ([0 1] [3 4])

(partition 3 1 [0 1 2 3 4 5 6])
=> ([0 1 2] [1 2 3] [2 3 4] [3 4 5] [4 5 6])

(partition 3 6 ["a"] (range 20))
=> (([0 1 2] (6 7 8) (12 13 14) (18 19 "a"))

(partition 4 6 ["a" "b" "c" "d"] (range 20))
=> (([0 1 2 3] (6 7 8 9) (12 13 14 15) (18 19 "a" "b"))
```

SEE ALSO

[partition-all](#)

Returns a collection of lists of *n* items each, at offsets *step* apart. If *step* is not supplied, defaults to *n*, i.e. the partitions do ...

[partition-by](#)

Applies *f* to each value in *coll*, splitting it each time *f* returns a new value.

[top](#)

partition-all

```
(partition-all n coll)
(partition-all n step coll)
```

Returns a collection of lists of *n* items each, at offsets *step* apart. If *step* is not supplied, defaults to *n*, i.e. the partitions do not overlap. May include partitions with fewer than *n* items at the end.

```
(partition-all 3 [0 1 2 3 4 5 6])
=> ([0 1 2] [3 4 5] [6])

(partition-all 2 3 [0 1 2 3 4 5 6])
=> ([0 1] [3 4] [6])

(partition-all 3 1 [0 1 2 3 4 5 6])
=> ([0 1 2] [1 2 3] [2 3 4] [3 4 5] [4 5 6] [5 6])

(partition-all 3 6 ["a"])
=> (["a"])

(partition-all 2 2 ["a" "b" "c" "d"])
=> (["a" "b"] ["c" "d"])
```

SEE ALSO

[partition](#)

Returns a collection of lists of *n* items each, at offsets *step* apart. If *step* is not supplied, defaults to *n*, i.e. the partitions do ...

[partition-by](#)

Applies *f* to each value in *coll*, splitting it each time *f* returns a new value.

[top](#)

partition-by

```
(partition-by f coll)
```

Applies *f* to each value in *coll*, splitting it each time *f* returns a new value.

```
(partition-by even? [1 2 4 3 5 6])
=> ((1) (2 4) (3 5) (6))

(partition-by identity (seq "ABBA"))
=> ((#\A) (#\B #\B) (#\A))

(partition-by identity [1 1 1 1 2 2 3])
=> ((1 1 1 1) (2 2) (3))
```

SEE ALSO

[partition](#)

Returns a collection of lists of *n* items each, at offsets *step* apart. If *step* is not supplied, defaults to *n*, i.e. the partitions do ...

[partition-all](#)

Returns a collection of lists of *n* items each, at offsets *step* apart. If *step* is not supplied, defaults to *n*, i.e. the partitions do ...

[top](#)

pcalls

```
(pcalls & fns)
```

Executes the no-arg *fns* in parallel, returning a sequence of their values in the same order the functions are passed. In contrast, side effects of *fns* (if any) are coming in random order!

`pcalls` is implemented using Venice futures and processes `(+ 2 (cpus))` functions in parallel.

```
(pcalls #(+ 1 2) #(+ 2 3) #(+ 3 4))  
=> (3 5 7)
```

SEE ALSO

[pmap](#)

Like map, except f is applied in parallel. Only useful for computationally intensive functions where the time of f dominates the coordination ...

[preduce](#)

Reduces a collection using a parallel reduce-combine strategy. The collection is partitioned into groups of approximately n items, ...

[cpus](#)

Returns the number of available processors or number of hyperthreads if the CPU supports hyperthreads.

[top](#)

pdf/available?

```
(pdf/available?)
```

Checks if the 3rd party libraries required for generating PDFs are available.

```
(pdf/available?)
```

[top](#)

pdf/check-required-libs

```
(pdf/check-required-libs)
```

Checks if the 3rd party libraries required for generating PDFs are available. Throws an exception if not.

```
(pdf/check-required-libs)
```

[top](#)

pdf/copy

```
(pdf/copy pdf & page-nr)
```

Copies pages from a PDF to a new PDF. The PDF is passed as bytebuf. Returns the new PDF as a bytebuf.

```
; copy the first and second page
(pdf/copy pdf :1 :2)

; copy the last and second last page
(pdf/copy pdf :-1 :-2)

; copy the pages 1, 2, 6-10, and 12
(pdf/copy pdf :1 :2 :6-10 :12)
```

SEE ALSO

[pdf/merge](#)

Merge multiple PDFs into a single PDF. The PDFs are passed as bytearray. Returns the new PDF as a bytearray.

[pdf/pages](#)

Returns the number of pages of a PDF. The PDF is passed as bytearray.

[pdf/watermark](#)

Adds a watermark text to the pages of a PDF. The passed PDF pdf is a bytearray. Returns the new PDF as a bytearray.

[top](#)

pdf/merge

```
(pdf/merge pdfs)
```

Merge multiple PDFs into a single PDF. The PDFs are passed as bytearray. Returns the new PDF as a bytearray.

```
(pdf/merge pdf1 pdf2)
```

```
(pdf/merge pdf1 pdf2 pdf3)
```

SEE ALSO

[pdf/copy](#)

Copies pages from a PDF to a new PDF. The PDF is passed as bytearray. Returns the new PDF as a bytearray.

[pdf/pages](#)

Returns the number of pages of a PDF. The PDF is passed as bytearray.

[pdf/watermark](#)

Adds a watermark text to the pages of a PDF. The passed PDF pdf is a bytearray. Returns the new PDF as a bytearray.

[top](#)

pdf/page-count

```
(pdf/page-count pdf)
```

Returns the number of pages in a PDF.

SEE ALSO

[pdf/render](#)

Renders a PDF.

[pdf/to-text](#)

Extracts the text from a PDF.

[top](#)

pdf/page-to-image

```
(pdf/page-to-image pdf page-nr)
(pdf/page-to-image pdf page-nr dpi)
```

Converts a page from the PDF to an image buffer.

The passed PDF `pdf` is a `bytebuf`. Returns the image buffer as a `java.awt.image.BufferedImage` that can be further processed or saved with the `:images` module.

SEE ALSO

[pdf/render](#)

Renders a PDF.

[pdf/to-text](#)

Extracts the text from a PDF.

[top](#)

pdf/pages

```
(pdf/pages pdf)
```

Returns the number of pages of a PDF. The PDF is passed as `bytebuf`.

```
(->> (str/lorem-ipsum :paragraphs 30)
      (pdf/text-to-pdf)
      (pdf/pages))
=> 3
```

SEE ALSO

[pdf/merge](#)

Merge multiple PDFs into a single PDF. The PDFs are passed as `bytebuf`. Returns the new PDF as a `bytebuf`.

[pdf/copy](#)

Copies pages from a PDF to a new PDF. The PDF is passed as `bytebuf`. Returns the new PDF as a `bytebuf`.

[pdf/watermark](#)

Adds a watermark text to the pages of a PDF. The passed PDF `pdf` is a `bytebuf`. Returns the new PDF as a `bytebuf`.

[top](#)

pdf/render

```
(pdf/render xhtml & options)
```

Renders a PDF.

Options:

`:base-url url` a base url for resources . E.g.: "classpath:/"
`:resources resmap` a resource map for dynamic resources

```
(pdf/render xhtml :base-url "classpath:/")
```

```
(pdf/render xhtml  
  :base-url "classpath:/"  
  :resources {"/chart_1.png" (chart-create :2018)  
             "/chart_2.png" (chart-create :2019) })
```

SEE ALSO

[pdf/text-to-pdf](#)

Creates a PDF from simple text. The tool process line-feeds '\n' and form-feeds. To start a new page just insert a form-feed marker ...

top

pdf/text-to-pdf

```
(pdf/text-to-pdf text & options)
```

Creates a PDF from simple text. The tool process line-feeds '\n' and form-feeds. To start a new page just insert a form-feed marker "<form-feed>".

Options:

`:font-size n` font size in pt (double), defaults to 9.0
`:font-weight n` font weight (0...1000) (long), defaults to 200
`:font-monospace b` if true use monospaced font, defaults to false

```
(->> (pdf/text-to-pdf "Lorem Ipsum...")  
  (io/spit "text.pdf"))
```

SEE ALSO

[pdf/render](#)

Renders a PDF.

[pdf/to-text](#)

Extracts the text from a PDF.

top

pdf/to-text

```
(pdf/to-text pdf)
```

Extracts the text from a PDF.

pdf may be a:

- string file path, e.g: "/temp/foo.pdf"
- `bytebuffer`
- `java.io.File` , e.g: `(io/file "/temp/foo.pdf")`
- `java.io.InputStream`

```
(-> (pdf/text-to-pdf "Lorem Ipsum...")
    (pdf/to-text)
    (println))
```

SEE ALSO

[pdf/text-to-pdf](#)

Creates a PDF from simple text. The tool process line-feeds '\n' and form-feeds. To start a new page just insert a form-feed marker ...

[pdf/render](#)

Renders a PDF.

[top](#)

pdf/watermark

```
(pdf/watermark pdf options-map)
(pdf/watermark pdf & options)
```

Adds a watermark text to the pages of a PDF. The passed PDF pdf is a bytebuf. Returns the new PDF as a bytebuf.

Options:

:text s	watermark text (string), defaults to "WATERMARK"
:font-size n	font size in pt (double), defaults to 24.0
:font-char-spacing n	font character spacing (double), defaults to 0.0
:color s	font color (HTML color string), defaults to #000000
:opacity n	opacity 0.0 ... 1.0 (double), defaults to 0.4
:outline-color s	font outline color (HTML color string), defaults to #000000
:outline-opacity n	outline opacity 0.0 ... 1.0 (double), defaults to 0.8
:outline-width n	outline width 0.0 ... 10.0 (double), defaults to 0.5
:angle n	angle 0.0 ... 360.0 (double), defaults to 45.0
:over-content b	print text over the content (boolean), defaults to true
:skip-top-pages n	the number of top pages to skip (long), defaults to 0
:skip-bottom-pages n	the number of bottom pages to skip (long), defaults to 0

```
(pdf/watermark pdf :text "CONFIDENTIAL" :font-size 64 :font-char-spacing 10.0)
```

```
(let [watermark { :text "CONFIDENTIAL"
                  :font-size 64
                  :font-char-spacing 10.0 } ]
    (pdf/watermark pdf watermark))
```

SEE ALSO

[pdf/merge](#)

Merge multiple PDFs into a single PDF. The PDFs are passed as bytebuf. Returns the new PDF as a bytebuf.

[pdf/copy](#)

Copies pages from a PDF to a new PDF. The PDF is passed as bytebuf. Returns the new PDF as a bytebuf.

[pdf/pages](#)

Returns the number of pages of a PDF. The PDF is passed as bytebuf.

[top](#)

peek

```
(peek coll)
```

For a list, same as first, for a vector, same as last, for a stack the top element (or nil if the stack is empty), for a queue the head element (or nil if the queue is empty).

```
(peek '(1 2 3 4))  
=> 1
```

```
(peek [1 2 3 4])  
=> 4
```

```
(let [s (conj! (stack) 1 2 3 4)]  
      (peek s))  
=> 4
```

```
(let [q (conj! (queue) 1 2 3 4)]  
      (peek q))  
=> 1
```

[top](#)

perf

```
(perf expr warmup-iterations test-iterations)
```

Performance test with the given expression.

Runs the test in 3 phases:

1. Runs the expr in a warmup phase to allow the HotSpot compiler to do optimizations.
2. Runs the garbage collector.
3. Runs the expression under profiling. Returns nil.

After a test run metrics data can be obtained with (prof :data-formatted)

```
(do  
  (perf (+ 120 200) 12000 1000)  
  (println (prof :data-formatted)))
```

SEE ALSO

[time](#)

Evaluates expr and prints the time it took. Returns the value of expr.

[prof](#)

Controls the code profiling. See the companion functions/macros 'dorun' and 'perf'. The perf macro is built on prof and dorun and provides ...

[top](#)

pid

```
(pid)
```

Returns the PID of this process.

```
(pid)
=> "49578"
```

[top](#)

pmap

```
(pmap f coll)
(pmap f coll & colls)
```

Like `map`, except `f` is applied in parallel. Only useful for computationally intensive functions where the time of `f` dominates the coordination overhead.

The result collection is sorted in the same way as for `map`, i.e. it preserves the items' order in the `coll` (or `colls`) parameter(s) of `pmap`. In other words: calculation is done parallel, but the result is delivered in the order the input came (in `coll/colls`). In contrast, side effects of `f` (if any) are coming in random order!

`pmap` is implemented using Venice futures and processes `(+ 2 (cpus))` items in parallel.

```
;; With `pmap`, the total elapsed time is just over 2 seconds:
```

```
(do
  (defn long-running-job [n]
    (sleep 2000) ; wait for 2 seconds
    (+ n 10))
  (time (pmap long-running-job (range 4))))
```

Elapsed time: 2.01s

```
=> (10 11 12 13)
```

```
;; With `map`, the total elapsed time is roughly 4 * 2 seconds:
```

```
(do
  (defn long-running-job [n]
    (sleep 2000) ; wait for 2 seconds
    (+ n 10))
  (time (map long-running-job (range 4))))
```

Elapsed time: 8.02s

```
=> (10 11 12 13)
```

SEE ALSO

[pcalls](#)

Executes the no-arg fns in parallel, returning a sequence of their values in the same order the functions are passed. In contrast, ...

[preduce](#)

Reduces a collection using a parallel reduce-combine strategy. The collection is partitioned into groups of approximately `n` items, ...

[map](#)

Applies `f` to the set of first items of each `coll`, followed by applying `f` to the set of second items in each `coll`, until any one of the ...

[cpus](#)

Returns the number of available processors or number of hyperthreads if the CPU supports hyperthreads.

[top](#)

poll!

```
(poll! queue)
(poll! queue timeout)
```

Polls an item from a queue with an optional timeout in milliseconds. For an indefinite timeout pass the timeout value `:indefinite`. If no timeout is given returns the item if one is available else returns `nil`. With a timeout returns the item if one is available within the given timeout else returns `nil`.

```
(let [q (conj! (queue) 1 2 3 4)]
  (poll! q)
  (poll! q 1000)
  q)
=> (3 4)
```

SEE ALSO

[queue](#)

Creates a new mutable threadsafe bounded or unbounded queue.

[put!](#)

Puts an item to a queue. The operation is synchronous, it waits indefinitely until the value can be placed on the queue. Returns always `nil`.

[take!](#)

Retrieves and removes the head value of the queue, waiting if necessary until a value becomes available.

[offer!](#)

Offers an item to a queue with an optional timeout in milliseconds. If a timeout is given waits up to the specified wait time if necessary ...

[peek](#)

For a list, same as `first`, for a vector, same as `last`, for a stack the top element (or `nil` if the stack is empty), for a queue the ...

[empty?](#)

Returns true if `x` is empty. Accepts strings, collections and `bytebufs`.

[count](#)

Returns the number of items in the collection. (`count nil`) returns 0. Also works on strings, and Java Collections

top

pop

```
(pop coll)
```

For a list, returns a new list without the first item, for a vector, returns a new vector without the last item.

```
(pop '(1 2 3 4))
=> (2 3 4)
```

```
(pop [1 2 3 4])
=> [1 2 3]
```

top

pop!

```
(pop! stack)
```

Pops an item from a stack.

```
(let [s (stack)]
  (push! s 1)
  (push! s 2)
  (push! s 3)
  (pop! s))
=> 3
```

SEE ALSO

[stack](#)

Creates a new mutable threadsafe stack.

[peek](#)

For a list, same as first, for a vector, same as last, for a stack the top element (or nil if the stack is empty), for a queue the ...

[push!](#)

Pushes an item to a stack.

[empty?](#)

Returns true if x is empty. Accepts strings, collections and bytebufs.

[count](#)

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

[top](#)

pos?

```
(pos? x)
```

Returns true if x greater than zero else false

```
(pos? 3)
=> true
```

```
(pos? -3)
=> false
```

```
(pos? 3I)
=> true
```

```
(pos? 3.2F)
=> true
```

```
(pos? 3.2)
=> true
```

```
(pos? 3.2M)
=> true
```

SEE ALSO

[zero?](#)

Returns true if x zero else false

[neg?](#)

Returns true if x smaller than zero else false

[top](#)

postwalk

```
(postwalk f form)
```

Performs a depth-first, post-order traversal of form. Calls f on each sub-form, uses f's return value in place of the original.

```
(postwalk (fn [x] (println "Walked:" (pr-str x)) x)
          '(1 2 {:a 1 :b 2}))
```

```
Walked: 1
Walked: 2
Walked: :a
Walked: 1
Walked: [:a 1]
Walked: :b
Walked: 2
Walked: [:b 2]
Walked: {:a 1 :b 2}
Walked: (1 2 {:a 1 :b 2})
=> (1 2 {:a 1 :b 2})
```

SEE ALSO

[prewalk](#)

Performs a depth-last, pre-order traversal of form. Calls f on each sub-form, uses f's return value in place of the original.

[top](#)

postwalk-replace

```
(postwalk-replace smap form)
```

Recursively transforms form by replacing keys in smap with their values. Like `replace` but works on any data structure. Does replacement at the leaves of the tree first.

`postwalk-replace` is the equivalent of *Common Lisp's* `sublis` function.

```
(postwalk-replace {:a 1 :b 2} [:a :b])
=> [1 2]
```

```
(postwalk-replace {:a 1 :b 2} [:a :b :c])
=> [1 2 :c]
```

```
(postwalk-replace {:a 1 :b 2} [:a :b [:a :b] :c])
=> [1 2 [1 2] :c]
```

```
(postwalk-replace {'x 1 'y 2} '(+ x y))
=> (+ 1 2)
```

SEE ALSO

[prewalk-replace](#)

Recursively transforms form by replacing keys in smap with their values. Like `replace` but works on any data structure. Does replacement ...

[postwalk](#)

Performs a depth-first, post-order traversal of form. Calls f on each sub-form, uses f's return value in place of the original.

pow

```
(pow x y)
```

Returns the value of x raised to the power of y

```
(pow 10 2)
=> 100.0
```

```
(pow 10.23 2)
=> 104.6529
```

```
(pow 10.23 2.5)
=> 334.7257199023319
```

pr

```
(pr & xs)
(pr os & xs)
```

Prints the values `xs` to the output stream that is the current value of `*out*` or to the passed output stream `os` if given. The passed stream must be a subclass of either `:java.io.PrintStream` or `:java.io.Writer`.

Prints the values, separated by spaces if there is more than one. `pr` and `prn` print in a way that objects can be read by the reader.

Returns `nil`.

```
(pr "hello")
"hello"
=> nil
```

```
(pr {:foo "hello" :bar 34.5})
{:foo "hello" :bar 34.5}
=> nil
```

```
(pr ['a :b "\n" #\space "c"])
[a :b "\n" #\space "c"]
=> nil
```

```
(pr *out* [10 20 30])
[10 20 30]
=> nil
```

```
(pr *err* [10 20 30])
[10 20 30]
=> nil
```

SEE ALSO

prn

Prints the values `xs` to the output stream that is the current value of `*out*` or to the passed stream `os` if given followed by a (newline).

[newline](#)

Without arg writes a platform-specific newline to the output channel that is the current value of *out*. With arg writes a newline ...

[pr-str](#)

With no args, returns the empty string. With one arg x, returns x.toString(). With more than one arg, returns the concatenation of ...

[top](#)

pr-str

```
(pr-str & xs)
```

With no args, returns the empty string. With one arg x, returns x.toString(). With more than one arg, returns the concatenation of the str values of the args with delimiter ' '.

```
(pr-str)  
=> ""
```

```
(pr-str 1 2 3)  
=> "1 2 3"
```

```
(pr-str 1I)  
=> "1I"
```

```
(pr-str 3.1415927M)  
=> "3.1415927M"
```

```
(pr-str +)  
=> "+"
```

```
(pr-str [1 2 3])  
=> "[1 2 3]"
```

```
(pr-str "total " 100)  
=> "\"total \" 100"
```

```
(pr-str #\h #\i)  
=> "#\\h #\\i"
```

SEE ALSO

[str](#)

With no args, returns the empty string. With one arg x, returns x.toString(). (str nil) returns the empty string. With more than one ...

[top](#)

reduce

```
(reduce n combine-fn combine-seed reduce-fn reduce-seed coll)  
(reduce n reduce-fn reduce-seed coll)
```

Reduces a collection using a parallel reduce-combine strategy. The collection is partitioned into groups of approximately n items, each of which is reduced with reduce-fn (with reduce-seed as its seed value) in parallel. The results of these reductions are then reduced with the combine-fn (with combine-seed as its seed value). Without an explicit combine-fn the reduce-fn and its seed reduce-seed will be used as combine-fn and combine-seed.

```
(preduce 3 + 0 + 0 [1 2 3 4 5])  
=> 15
```

```
(preduce 3 (fn [acc x] (+ acc x)) 0 (fn [acc x] (+ acc x)) 0 [1 2 3 4 5])  
=> 15
```

```
(preduce 3 + 0 [1 2 3 4 5])  
=> 15
```

```
(preduce 3 (fn [acc x] (+ acc x)) 0 [1 2 3 4 5])  
=> 15
```

SEE ALSO

[reduce](#)

f should be a function of 2 arguments. If val is not supplied, returns the result of applying f to the first 2 items in coll, then ...

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[filter](#)

Returns a collection of the items in coll for which (predicate item) returns logical true.

[pmap](#)

Like map, except f is applied in parallel. Only useful for computationally intensive functions where the time of f dominates the coordination ...

[pcalls](#)

Executes the no-arg fns in parallel, returning a sequence of their values in the same order the functions are passed. In contrast, ...

[top](#)

prewalk

```
(prewalk f form)
```

Performs a depth-last, pre-order traversal of form. Calls f on each sub-form, uses f's return value in place of the original.

```
(prewalk (fn [x] (println "Walked:" (pr-str x)) x)  
  '(1 2 {:a 1 :b 2}))  
Walked: (1 2 {:a 1 :b 2})  
Walked: 1  
Walked: 2  
Walked: {:a 1 :b 2}  
Walked: [:a 1]  
Walked: :a  
Walked: 1  
Walked: [:b 2]  
Walked: :b  
Walked: 2  
=> (1 2 {:a 1 :b 2})
```

SEE ALSO

[postwalk](#)

Performs a depth-first, post-order traversal of form. Calls f on each sub-form, uses f's return value in place of the original.

[top](#)

prewalk-replace

```
(prewalk-replace smap form)
```

Recursively transforms form by replacing keys in smap with their values. Like `replace` but works on any data structure. Does replacement at the root of the tree first.

```
(prewalk-replace {:a 1 :b 2} [:a :b])  
=> [1 2]
```

```
(prewalk-replace {:a 1 :b 2} [:a :b :c])  
=> [1 2 :c]
```

```
(prewalk-replace {:a 1 :b 2} [:a :b [:a :b] :c])  
=> [1 2 [1 2] :c]
```

```
(prewalk-replace {'x 1 'y 2} '(+ x y))  
=> (+ 1 2)
```

SEE ALSO

[postwalk-replace](#)

Recursively transforms form by replacing keys in smap with their values. Like `replace` but works on any data structure. Does replacement ...

[prewalk](#)

Performs a depth-last, pre-order traversal of form. Calls `f` on each sub-form, uses `f`'s return value in place of the original.

[top](#)

print

```
(print & xs)  
(print os & xs)
```

Prints the values `xs` to the stream that is the current value of `*out*` or to the passed stream `os` that must be a subclass of either `:java.io.PrintStream` or `:java.io.Writer`.

Prints the values, separated by spaces if there is more than one. `print` and `println` print in a human readable form.

If the printed data needs to be read back by a Venice reader use the functions `pr` and `prn` instead.

Returns `nil`.

```
(print [10 20 30])  
[10 20 30]  
=> nil
```

```
(print *out* [10 20 30])  
[10 20 30]  
=> nil
```

```
(print *err* [10 20 30])  
[10 20 30]  
=> nil
```

SEE ALSO

[println](#)

Prints the values xs to the stream that is the current value of `*out*` or to the passed output stream os if given followed by a (newline).

[printf](#)

Without output stream prints formatted output as per format to the stream that is the current value of `*out*`. With a stream prints ...

[newline](#)

Without arg writes a platform-specific newline to the output channel that is the current value of `*out*`. With arg writes a newline ...

[top](#)

printf

```
(printf fmt & args)
(printf os fmt & args)
```

Without output stream prints formatted output as per format to the stream that is the current value of `*out*` . With a stream prints to that stream that must be a subclass of either `:java.io.PrintStream` or `:java.io.Writer` .

Prints like `print` and `println` in a human readable form.

Returns `nil` .

See: [Java Formatter](#)

```
(printf "%s: %d" "abc" 100)
abc: 100
=> nil
```

```
(printf "line 1: %s\nline 2: %s\n" "123" "456")
line 1: 123
line 2: 456
=> nil
```

```
(printf "%d%" 42)
42%
=> nil
```

```
(printf *out* "%s: %d" "abc" 100)
abc: 100
=> nil
```

```
(printf *err* "%s: %d" "abc" 100)
abc: 100
=> nil
```

SEE ALSO

[print](#)

Prints the values xs to the stream that is the current value of `*out*` or to the passed stream os that must be a subclass of either ...

[println](#)

Prints the values xs to the stream that is the current value of `*out*` or to the passed output stream os if given followed by a (newline).

[newline](#)

Without arg writes a platform-specific newline to the output channel that is the current value of `*out*`. With arg writes a newline ...

[top](#)

println

```
(println & xs)
(println os & xs)
```

Prints the values `xs` to the stream that is the current value of `*out*` or to the passed output stream `os` if given followed by a `(newline)` . The passed stream must be a subclass of either `:java.io.PrintStream` or `:java.io.Writer` .

Prints the values, separated by spaces if there is more than one. `print` and `println` print in a human readable form.

If the printed data needs to be read back by a Venice reader use the functions `pr` and `prn` instead.

Returns `nil` .

```
(println 200)
200
=> nil

(println [10 20 30])
[10 20 30]
=> nil

(println *out* 200)
200
=> nil

(println *err* 200)
200
=> nil
```

SEE ALSO

[print](#)

Prints the values `xs` to the stream that is the current value of `*out*` or to the passed stream `os` that must be a subclass of either ...

[printf](#)

Without output stream prints formatted output as per format to the stream that is the current value of `*out*`. With a stream prints ...

[newline](#)

Without `arg` writes a platform-specific newline to the output channel that is the current value of `*out*`. With `arg` writes a newline ...

[top](#)

prn

```
(prn & xs)
(prn os & xs)
```

Prints the values `xs` to the output stream that is the current value of `*out*` or to the passed stream `os` if given followed by a `(newline)` . The passed stream must be a subclass of either `:java.io.PrintStream` or `:java.io.Writer` .

Prints the values, separated by spaces if there is more than one. `pr` and `prn` print in a way that objects can be read by the reader.

Returns `nil` .

```
(prn "hello")
"hello"
=> nil
```

```
(prn {:foo "hello" :bar 34.5})
{:foo "hello" :bar 34.5}
=> nil
```

```
(prn ['a :b "\n" #\space "c"])
[a :b "\n" #\space "c"]
=> nil
```

```
(prn *out* [10 20 30])
[10 20 30]
=> nil
```

```
(prn *err* [10 20 30])
[10 20 30]
=> nil
```

SEE ALSO

[pr](#)

Prints the values xs to the output stream that is the current value of *out* or to the passed output stream os if given. The passed ...

[newline](#)

Without arg writes a platform-specific newline to the output channel that is the current value of *out*. With arg writes a newline ...

[pr-str](#)

With no args, returns the empty string. With one arg x, returns x.toString(). With more than one arg, returns the concatenation of ...

[top](#)

prof

(prof opts)

Controls the code profiling. See the companion functions/macros 'dorun' and 'perf'. The perf macro is built on prof and dorun and provides all for simple Venice profiling.

The profiler reports a function's elapsed time as "time with children"!

Profiling recursive functions:

Because the profiler reports "time with children" and accumulates the elapsed time across all recursive calls the resulting time for a particular recursive function is higher than the effective time.

```
(do
  (prof :on)    ; turn profiler on
  (prof :off)   ; turn profiler off
  (prof :status) ; returns the profiler on/off status
  (prof :clear) ; clear profiler data captured so far
  (prof :data)  ; returns the profiler data as map
  (prof :data-formatted) ; returns the profiler data as formatted text
  (prof :data-formatted "Metrics") ; returns the profiler data as formatted text with a title
  nil)
=> nil
```

SEE ALSO

[perf](#)

Performance test with the given expression.

[time](#)

Evaluates expr and prints the time it took. Returns the value of expr.

promise

```
(promise)
(promise fn)
```

Returns a promise object that can be read with `deref`, and set, once only, with `deliver`. Calls to `deref` prior to delivery will block, unless the variant of `deref` with timeout is used. All subsequent derefs will return the same delivered value without blocking.

Promises are implemented on top of Java's `CompletableFuture`.

```
(do
  (def p (promise))
  (deliver p 10)
  (deliver p 20) ; no effect
  @p)
=> 10

;; deliver the promise from a future
(do
  (def p (promise))
  (defn task1 [] (sleep 500) (deliver p 10))
  (defn task2 [] (sleep 800) (deliver p 20))
  (future task1)
  (future task2)
  @p)
=> 10

;; deliver the promise from a task's return value
(do
  (defn task [] (sleep 300) 10)
  (def p (promise task))
  @p)
=> 10

(let [p (promise #(do (sleep 300) 10))]
  @p)
=> 10
```

SEE ALSO

[deliver](#)

Delivers the supplied value to the promise, releasing any pending derefs. A subsequent call to deliver on a promise will have no effect.

[promise?](#)

Returns true if f is a Promise otherwise false

[realized?](#)

Returns true if a value has been produced for a promise, delay, or future.

[deref](#)

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will ...

[done?](#)

Returns true if the future or promise is done otherwise false

[cancel](#)

Cancels a future or a promise

[cancelled?](#)

Returns true if the future or promise is cancelled otherwise false

[all-of](#)

Returns a new promise that is completed when all of the given promises complete. If any of the given promises complete exceptionally, ...

[any-of](#)

Returns a new promise that is completed when any of the given promises complete, with the same result. Otherwise, if it completed exceptionally, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function f with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function f with the two ...

[then-apply](#)

Applies a function f on the result of the previous stage of the promise p.

[then-combine](#)

Applies a function f to the result of the previous stage of promise p and the result of another promise p-other

[then-compose](#)

Composes the result of two promises. f receives the result of the first promise p and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise p with the same result or exception at this stage, that executes the action f. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a TimeoutException if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[timeout-after](#)

Returns a promise that timeouts after the specified time. The promise throws a TimeoutException.

[top](#)

promise?

```
(promise? p)
```

Returns true if f is a Promise otherwise false

```
(promise? (promise))  
=> true
```

[top](#)

proxify

```
(proxify interface method-map)
```

Proxifies a Java interface to be passed as a Callback object to Java functions. The interface's methods are implemented by Venice functions.

The dynamic invocation handler takes care that the methods are called in the context of a Venice sandbox even if the Java method that invokes the callback methods is running in another thread.

Supports default method implementations in the proxied Java interface. These Java interface methods can be either overridden by a Venice function or just be omitted. In the latter case the return value of methods default implementation will be handed back.

In case a Java `FunctionalInterface` is required the proxy wrappers from the `:java` module are often simpler to use:

- `java/as-runnable`
- `java/as-callable`
- `java/as-predicate`
- `java/as-function`
- `java/as-consumer`
- `java/as-supplier`
- `java/as-bipredicate`
- `java/as-bifunction`
- `java/as-biconsumer`
- `java/as-binaryoperator`

```
(do
  (import :java.io.File :java.io FilenameFilter)

  (def file-filter
    (fn [dir name] (str/ends-with? name ".xxx")))

  (let [dir (io/tmp-dir)]
    ;; create a dynamic proxy for the interface FilenameFilter
    ;; and implement its function 'accept' by 'file-filter'
    (. dir :list (proxify :FilenameFilter {:accept file-filter}))))
=> []
```

;; Instead of explicit proxies, functional interface wrappers are
;; often simpler to use

```
(do
  (load-module :java)
  (import :java.util.stream.Collectors)

  (-> (. [1 2 3 4] :stream)
    (. :filter (java/as-predicate #(> % 2)))
    (. :map (java/as-function #(* % 10)))
    (. :collect (. :Collectors :toList)))
=> (30 40)
```

SEE ALSO

[java/as-runnable](#)

Wraps the function `f` in a `java.lang.Runnable` (<https://docs.oracle.com/javase/8/docs/api/java/lang/Runnable.html>)

[java/as-callable](#)

Wraps the function `f` in a `java.util.concurrent.Callable` (<https://docs.oracle.com/javase/8/docs/api/java/util/concurrent/Callable.html>)

[java/as-predicate](#)

Wraps the function `f` in a `java.util.function.Predicate` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Predicate.html>)

[java/as-function](#)

Wraps the function `f` in a `java.util.function.Function` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Function.html>)

[java/as-consumer](#)

Wraps the function `f` in a `java.util.function.Consumer` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Consumer.html>)

[java/as-supplier](#)

Wraps the function `f` in a `java.util.function.Supplier` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/Supplier.html>)

[java/as-bipredicate](#)

Wraps the function `f` in a `java.util.function.BiPredicate` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiPredicate.html>)

[java/as-bifunction](#)

Wraps the function `f` in a `java.util.function.BiFunction` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiFunction.html>)

[java/as-biconsumer](#)

Wraps the function `f` in a `java.util.function.BiConsumer` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BiConsumer.html>)

[java/as-binaryoperator](#)

Wraps the function `f` in a `java.util.function.BinaryOperator` (<https://docs.oracle.com/javase/8/docs/api/java/util/function/BinaryOperator.html>)

[top](#)

push!

```
(push! stack v)
```

Pushes an item to a stack.

```
(let [s (stack)]
  (push! s 1)
  (push! s 2)
  (push! s 3)
  (pop! s))
=> 3
```

SEE ALSO

[stack](#)

Creates a new mutable threadsafe stack.

[peek](#)

For a list, same as `first`, for a vector, same as `last`, for a stack the top element (or `nil` if the stack is empty), for a queue the ...

[pop!](#)

Pops an item from a stack.

[empty?](#)

Returns true if `x` is empty. Accepts strings, collections and bytebufs.

[count](#)

Returns the number of items in the collection. (`count nil`) returns 0. Also works on strings, and Java Collections

[top](#)

put!

```
(put! queue val)
(put! queue val delay)
```

Puts an item to a queue. The operation is synchronous, it waits indefinitely until the value can be placed on the queue. Returns always `nil`.

queue: `(put! queue val)`

Puts the value `'val'` to the tail of the queue.

delay-queue: `(put! queue val delay)`

Puts the value `'val'` with a delay of `'delay'` milliseconds to a delay-queue

```
(let [q (queue)]
  (put! q 1)
  (poll! q)
  q)
=> ()
```

```
(let [q (delay-queue)]
  (put! q 1 100)
  (take! q))
=> 1
```

SEE ALSO

queue

Creates a new mutable threadsafe bounded or unbounded queue.

take!

Retrieves and removes the head value of the queue, waiting if necessary until a value becomes available.

offer!

Offers an item to a queue with an optional timeout in milliseconds. If a timeout is given waits up to the specified wait time if necessary ...

poll!

Polls an item from a queue with an optional timeout in milliseconds. For an indefinite timeout pass the timeout value `:indefinite`.

peek

For a list, same as first, for a vector, same as last, for a stack the top element (or nil if the stack is empty), for a queue the ...

empty?

Returns true if x is empty. Accepts strings, collections and bytebufs.

count

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

top

qrref/format

```
(format s)
```

Format a QR reference.

```
(do
  (load-module :qrref ['qrref :as 'qr])
  (qr/format "0000000000000000000000001234011"))
=> "00 00000 00000 00000 00012 34011"
```

```
(do
  (load-module :qrref ['qrref :as 'qr])
  (qr/format (qr/qr-ref 1 :bill "1234")))
=> "00 00000 00000 00000 00012 34011"
```

SEE ALSO

qrref/qr-ref

Creates a QR reference according to the Swiss payment standards.

qrref/parse

Parse a QR reference. The reference may be formatted.

[top](#)

qrref/parse

(parse ref)

Parse a QR reference. The reference may be formatted.

```
(do
  (load-module :qrref ['qrref :as 'qr])
  (qr/parse (qr/qr-ref 1 :bill "1234")))
=> {:bill-typ :bill :bill-nr "1234" :version 1}
```

```
(do
  (load-module :qrref ['qrref :as 'qr])
  (qr/parse "0000000000000000000000001234011"))
=> {:bill-typ :bill :bill-nr "1234" :version 1}
```

```
(do
  (load-module :qrref ['qrref :as 'qr])
  (qr/parse "00 00000 00000 00000 00012 34011"))
=> {:bill-typ :bill :bill-nr "1234" :version 1}
```

SEE ALSO

[qrref/qr-ref](#)

Creates a QR reference according to the Swiss payment standards.

[qrref/format](#)

Format a QR reference.

[top](#)

qrref/qr-ref

(qr-ref version bill-type bill-nr)

Creates a QR reference according to the Swiss payment standards.

- *version*, an integer [1..9]
- *bill-type*, one of {:bill, :reminder-1, :reminder-2, :reminder-3}
- *bill-nr*, a string with up to 24 digits '0'..'9'

[Swiss Payment Standards / de](#)

[Swiss Payment Standards / en](#)

```
(do
  (load-module :qrref ['qrref :as 'qr])
  (qr/qr-ref 1 :bill "1234"))
=> "0000000000000000000000001234011"
```

SEE ALSO

[qrref/parse](#)

Parse a QR reference. The reference may be formatted.

[qrref/format](#)

Format a QR reference.

qualified-name

```
(qualified-name x)
```

Returns the qualified name String of a string, symbol, keyword, or function

```
(qualified-name :user/x)  
=> "user/x"
```

```
(qualified-name 'x)  
=> "x"
```

```
(qualified-name "x")  
=> "x"
```

```
(qualified-name str/digit?)  
=> "str/digit?"
```

SEE ALSO

[name](#)

Returns the name string of a string, symbol, keyword, or function. If applied to a string it returns the string itself.

[namespace](#)

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

[fn-name](#)

Returns the qualified name of a function or macro

qualified-symbol?

```
(qualified-symbol? x)
```

Returns true if x is a qualified symbol

```
(qualified-symbol? 'foo/a)  
=> true
```

```
(qualified-symbol? (symbol "foo/a"))  
=> true
```

```
(qualified-symbol? 'a)  
=> false
```

```
(qualified-symbol? nil)  
=> false
```

```
(qualified-symbol? :a)  
=> false
```

quasiquote

(quasiquote form)

Quasi quotes also called syntax quotes (a backquote) suppress evaluation of the form that follows it and all the nested forms.

unquote:

It is possible to unquote part of the form that is quoted with `~`. Unquoting allows you to evaluate parts of the syntax quoted expression.

unquote-splicing:

Unquote evaluates to a collection of values and inserts the collection into the quoted form. But sometimes you want to unquote a list and insert its elements (not the list) inside the quoted form. This is where `~@` (unquote-splicing) comes to rescue.

```
(quasiquote (16 17 (inc 17)))
```

```
=> (16 17 (inc 17))
```

```
`(16 17 (inc 17))
```

```
=> (16 17 (inc 17))
```

```
`(16 17 ~(inc 17))
```

```
=> (16 17 18)
```

```
`(16 17 ~(map inc [16 17]))
```

```
=> (16 17 (17 18))
```

```
`(16 17 ~@(map inc [16 17]))
```

```
=> (16 17 17 18)
```

```
`(1 2 ~@#{1 2 3})
```

```
=> (1 2 1 2 3)
```

```
`(1 2 ~@{:a 1 :b 2 :c 3})
```

```
=> (1 2 [:a 1] [:b 2] [:c 3])
```

SEE ALSO

[quote](#)

There are two equivalent ways to quote a form either with `quote` or with `'`. They prevent the quoted form from being evaluated.

[top](#)

queue

(queue)

(queue capacity)

Creates a new mutable threadsafe bounded or unbounded queue.

The queue can be turned into a synchronous queue when using the functions `put!` and `take!`. `put!` waits until the value be added and `take!` waits until a value is available from queue thus synchronizing the producer and consumer.

```
; unbounded queue
(let [q (queue)]
  (offer! q 1)
  (offer! q 2)
  (offer! q 3))
```

```

    (poll! q)
    q)
=> (2 3)

; bounded queue
(let [q (queue 10)]
  (offer! q 1000 1)
  (offer! q 1000 2)
  (offer! q 1000 3)
  (poll! q 1000)
  q)
=> (2 3)

; synchronous unbounded queue
(let [q (queue)]
  (put! q 1)
  (put! q 2)
  (put! q 3)
  (take! q)
  q)
=> (2 3)

; synchronous bounded queue
(let [q (queue 10)]
  (put! q 1)
  (put! q 2)
  (put! q 3)
  (take! q)
  q)
=> (2 3)

```

SEE ALSO

[peek](#)

For a list, same as first, for a vector, same as last, for a stack the top element (or nil if the stack is empty), for a queue the ...

[put!](#)

Puts an item to a queue. The operation is synchronous, it waits indefinitely until the value can be placed on the queue. Returns always nil.

[take!](#)

Retrieves and removes the head value of the queue, waiting if necessary until a value becomes available.

[offer!](#)

Offers an item to a queue with an optional timeout in milliseconds. If a timeout is given waits up to the specified wait time if necessary ...

[poll!](#)

Polls an item from a queue with an optional timeout in milliseconds. For an indefinite timeout pass the timeout value :indefinite.

[empty](#)

Returns an empty collection of the same category as coll, or nil if coll is nil. If the collection is mutable clears the collection ...

[empty?](#)

Returns true if x is empty. Accepts strings, collections and bytebufs.

[count](#)

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

[queue?](#)

Returns true if coll is a queue

[reduce](#)

f should be a function of 2 arguments. If val is not supplied, returns the result of applying f to the first 2 items in coll, then ...

[transduce](#)

Reduce with a transformation of a reduction function f (xf). If init is not supplied, (f) will be called to produce it. f should be ...

[docoll](#)

Applies f to the items of the collection presumably for side effects. Returns nil.

[into!](#)

Adds all of the items of 'from' conjoined to the mutable 'to' collection

[conj!](#)

Returns a new mutable collection with the x, xs 'added'. (conj! nil item) returns (item) and (conj! item) returns item.

[top](#)

queue?

```
(queue? coll)
```

Returns true if coll is a queue

```
(queue? (queue))  
=> true
```

[top](#)

quote

```
(quote form)
```

There are two equivalent ways to quote a form either with `quote` or with `'`. They prevent the quoted form from being evaluated.

Regular quotes work recursively with any kind of forms and types: strings, maps, lists, vectors...

```
(quote (1 2 3))  
=> (1 2 3)
```

```
(quote (+ 1 2))  
=> (+ 1 2)
```

```
'(1 2 3)  
=> (1 2 3)
```

```
'(+ 1 2)  
=> (+ 1 2)
```

```
'(a (b (c d (+ 1 2))))  
=> (a (b (c d (+ 1 2))))
```

SEE ALSO

[quasiquote](#)

Quasi quotes also called syntax quotes (a backquote) suppress evaluation of the form that follows it and all the nested forms.

[top](#)

rand-bigint

```
(rand-bigint bits)
```

Constructs a randomly generated BigInteger, uniformly distributed over the range 0 to ($2^N - 1$), inclusive.

```
(rand-bigint 256)
=> 78156862880359979824617891666426515127621577834792452630171885520353777843054N
```

SEE ALSO

[rand-long](#)

Without argument returns a random long between 0 and MAX_LONG. With argument max returns a random long between 0 and max exclusive.

[rand-double](#)

Without argument returns a double between 0.0 and 1.0. With argument max returns a random double between 0.0 and max.

[rand-gaussian](#)

Without argument returns a Gaussian distributed double value with mean 0.0 and standard deviation 1.0. With argument mean and stddev ...

[bytebuf-allocate-random](#)

Allocates a new bytebuf. The values will be all preset with randombytes

[top](#)

rand-double

```
(rand-double)
(rand-double max)
```

Without argument returns a double between 0.0 and 1.0. With argument max returns a random double between 0.0 and max.

This function is based on a cryptographically strong random number generator (RNG).

```
(rand-double)
=> 0.49727862197780814
```

```
(rand-double 100.0)
=> 22.755188022625607
```

SEE ALSO

[rand-long](#)

Without argument returns a random long between 0 and MAX_LONG. With argument max returns a random long between 0 and max exclusive.

[rand-bigint](#)

Constructs a randomly generated BigInteger, uniformly distributed over the range 0 to ($2^N - 1$), inclusive.

[rand-gaussian](#)

Without argument returns a Gaussian distributed double value with mean 0.0 and standard deviation 1.0. With argument mean and stddev ...

[bytebuf-allocate-random](#)

Allocates a new bytebuf. The values will be all preset with randombytes

[top](#)

rand-gaussian

```
(rand-gaussian)
(rand-gaussian mean stddev)
```

Without argument returns a Gaussian distributed double value with mean 0.0 and standard deviation 1.0. With argument mean and stddev returns a Gaussian distributed double value with the given mean and standard deviation.

This function is based on a cryptographically strong random number generator (RNG)

```
(rand-gaussian)
=> -1.9710135384941827
```

```
(rand-gaussian 0.0 5.0)
=> -0.8925411527290966
```

SEE ALSO

[rand-long](#)

Without argument returns a random long between 0 and MAX_LONG. With argument max returns a random long between 0 and max exclusive.

[rand-double](#)

Without argument returns a double between 0.0 and 1.0. With argument max returns a random double between 0.0 and max.

[rand-bigint](#)

Constructs a randomly generated BigInteger, uniformly distributed over the range 0 to (2^N - 1), inclusive.

[bytebuf-allocate-random](#)

Allocates a new bytebuf. The values will be all preset with randombytes

top

rand-long

```
(rand-long)
(rand-long max)
```

Without argument returns a random long between 0 and MAX_LONG. With argument max returns a random long between 0 and max exclusive.

This function is based on a cryptographically strong random number generator (RNG).

```
(rand-long)
=> 7510776493651038133
```

```
(rand-long 100)
=> 52
```

SEE ALSO

[rand-double](#)

Without argument returns a double between 0.0 and 1.0. With argument max returns a random double between 0.0 and max.

[rand-bigint](#)

Constructs a randomly generated BigInteger, uniformly distributed over the range 0 to (2^N - 1), inclusive.

[rand-gaussian](#)

Without argument returns a Gaussian distributed double value with mean 0.0 and standard deviation 1.0. With argument mean and stddev ...

[bytebuf-allocate-random](#)

Allocates a new bytebuf. The values will be all preset with randombytes

top

range

```
(range)
(range end)
(range start end)
(range start end step)
```

Returns a collection of numbers from start (inclusive) to end (exclusive), by step, where start defaults to 0 and step defaults to 1. When start is equal to end, returns empty list. Without args returns a lazy sequence generating numbers starting with 0 and incrementing by 1.

```
(range 10)
=> (0 1 2 3 4 5 6 7 8 9)
```

```
(range 10 20)
=> (10 11 12 13 14 15 16 17 18 19)
```

```
(range 10 20 3)
=> (10 13 16 19)
```

```
(range (int 10) (int 20))
=> (10I 11I 12I 13I 14I 15I 16I 17I 18I 19I)
```

```
(range (int 10) (int 20) (int 3))
=> (10I 13I 16I 19I)
```

```
(range 10 15 0.5)
=> (10 10.5 11.0 11.5 12.0 12.5 13.0 13.5 14.0 14.5)
```

```
(range 1.1M 2.2M 0.1M)
=> (1.1M 1.2M 1.3M 1.4M 1.5M 1.6M 1.7M 1.8M 1.9M 2.0M 2.1M)
```

```
(range 100N 200N 10N)
=> (100N 110N 120N 130N 140N 150N 160N 170N 180N 190N)
```

```
;; capital letters
(map char (range (int #\A) (inc (int #\Z))))
=> (#\A #\B #\C #\D #\E #\F #\G #\H #\I #\J #\K #\L #\M #\N #\O #\P #\Q #\R #\S #\T #\U #\V #\W #\X #\Y #\Z)
```

[top](#)

read-char

```
(read-char)
(read-char is)
```

Without arg reads the next char from the stream that is the current value of `*in*`. With arg reads the next char from the passed stream that must be a subclass of `:java.io.Reader`.

Returns `nil` if the end of the stream is reached.

```
(try-with [rd (io/buffered-reader "1234")]
  (println (read-char rd))
  (println (read-char rd)))
1
2
=> nil
```

SEE ALSO

read-line

Without arg reads the next line from the stream that is the current value of `*in*`. With arg reads the next line from the passed stream ...

top

read-line

```
(read-line)
(read-line is)
```

Without arg reads the next line from the stream that is the current value of `*in*`. With arg reads the next line from the passed stream that must be a subclass of `:java.io.BufferedReader`.

Returns `nil` if the end of the stream is reached.

```
(try-with [rd (io/buffered-reader "1\n2\n3\n4")])
  (println (read-line rd))
  (println (read-line rd)))
1
2
=> nil
```

SEE ALSO

[read-char](#)

Without arg reads the next char from the stream that is the current value of `*in*`. With arg reads the next char from the passed stream ...

top

read-string

```
(read-string s)
(read-string s origin)
```

Reads Venice source from a string and transforms its content into a Venice data structure, following the rules of the Venice syntax.

```
(do
  (eval (read-string "(def x 100)" "test")))
x)
=> 100
```

SEE ALSO

[eval](#)

Evaluates the form data structure (not text!) and returns the result.

top

realized?

```
(realized? x)
```

Returns true if a value has been produced for a promise, delay, or future.

```

(do
  (def task (fn [] 100))
  (let [f (future task)]
    (println (realized? f))
    (println @f)
    (println (realized? f))))
false
100
true
=> nil

(do
  (def p (promise))
  (println (realized? p))
  (deliver p 123)
  (println @p)
  (println (realized? p)))
false
123
true
=> nil

(do
  (def x (delay 100))
  (println (realized? x))
  (println @x)
  (println (realized? x)))
false
100
true
=> nil

```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[delay](#)

Takes a body of expressions and yields a Delay object that will invoke the body only the first time it is forced (with force or deref ...

[promise](#)

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, ...

[top](#)

recur

```
(recur expr*)
```

Evaluates the exprs and rebinds the bindings of the recursion point to the values of the exprs. The recur expression must be at the tail position. The tail position is a position which an expression would return a value from.

```

;; tail recursion
(loop [x 10]
  (when (> x 1)
    (println x)
    (recur (- x 2)))))
10
8
6

```

```

4
2
=> nil

;; tail recursion
(do
  (defn sum [n]
    (loop [cnt n acc 0]
      (if (zero? cnt)
          acc
          (recur (dec cnt) (+ acc cnt))))))
  (sum 10000))
=> 50005000

```

SEE ALSO

[loop](#)

Evaluates the exprs and binds the bindings. Creates a recursion point with the bindings.

[top](#)

reduce

```

(reduce f coll)
(reduce f val coll)

```

`f` should be a function of 2 arguments. If `val` is not supplied, returns the result of applying `f` to the first 2 items in `coll`, then applying `f` to that result and the 3rd item, etc. If `coll` contains no items, `f` must accept no arguments as well, and `reduce` returns the result of calling `f` with no arguments. If `coll` has only 1 item, it is returned and `f` is not called. If `val` is supplied, returns the result of applying `f` to `val` and the first item in `coll`, then applying `f` to that result and the 2nd item, etc. If `coll` contains no items, returns `val` and `f` is not called.

`reduce` can work with queues as collection, given that the end of the queue is marked by adding a `nil` element. Otherwise the reducer does not know when to stop reading elements from the queue.

```

(reduce + [1 2 3 4 5 6 7])
=> 28

(reduce + 10 [1 2 3 4 5 6 7])
=> 38

(reduce (fn [x y] (+ x y 10)) [1 2 3 4 5 6 7])
=> 88

(reduce (fn [x y] (+ x y 10)) 10 [1 2 3 4 5 6 7])
=> 108

((reduce comp [(partial + 1) (partial * 2) (partial + 3)]) 100)
=> 207

(reduce (fn [m [k v]] (assoc m k v)) {} [[:a 1] [:b 2] [:c 3]])
=> {:a 1 :b 2 :c 3}

(reduce (fn [m [k v]] (assoc m v k)) {} [:b 2 :a 1 :c 3])
=> {1 :a 2 :b 3 :c}

(reduce (fn [m c] (assoc m (first c) c)) {} [[:a 1] [:b 2] [:c 3]])
=> {:a [:a 1] :b [:b 2] :c [:c 3]}

```

```
;; sliding window (width 3) average
(->> (partition 3 1 (repeatedly 10 #(rand-long 30)))
      (map (fn [window] (/ (reduce + window) (count window)))))
=> (21 13 11 6 13 11 12 12)
```

```
;; reduce all elements of a queue.
;; calls (take! queue) to get the elements of the queue.
;; note: use nil to mark the end of the queue otherwise
;;       reduce will block forever!
(let [q (conj! (queue) 1 2 3 4 5 6 7 nil)]
  (reduce + q))
=> 28
```

```
;; reduce data supplied by a finit lazy seq
(do
  (def counter (atom 5))
  (defn generate []
    (swap! counter dec)
    (if (pos? @counter) @counter nil))
  (reduce + 100 (lazy-seq generate)))
=> 110
```

SEE ALSO

[reduce-kv](#)

Reduces an associative collection. f should be a function of 3 arguments. Returns the result of applying f to init, the first key and ...

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[filter](#)

Returns a collection of the items in coll for which (predicate item) returns logical true.

top

reduce-kv

```
(reduce-kv f init coll)
```

Reduces an associative collection. f should be a function of 3 arguments. Returns the result of applying f to init, the first key and the first value in coll, then applying f to that result and the 2nd key and value, etc. If coll contains no entries, returns init and f is not called. Note that reduce-kv is supported on vectors, where the keys will be the ordinals.

```
(reduce-kv (fn [m k v] (assoc m v k))
  {}
  {:a 1 :b 2 :c 3})
=> {1 :a 2 :b 3 :c}
```

```
(reduce-kv (fn [m k v] (assoc m k (:col v)))
  {}
  {:a {:col :red :len 10}
   :b {:col :green :len 20}
   :c {:col :blue :len 30}})
=> {:a :red :b :green :c :blue}
```

SEE ALSO

[reduce](#)

f should be a function of 2 arguments. If val is not supplied, returns the result of applying f to the first 2 items in coll, then ...

[map](#)

Applies `f` to the set of first items of each coll, followed by applying `f` to the set of second items in each coll, until any one of the ...

[filter](#)

Returns a collection of the items in coll for which (predicate item) returns logical true.

[top](#)

reduced

`(reduced x)`

Wraps `x` in a way such that a reduce will terminate with the value `x`.

[top](#)

reduced?

`(reduced? x)`

Returns true if `x` is the result of a call to `reduced`.

[top](#)

regex/count

`(regex/count matcher)`

Returns the matcher's group count.

```
(let [m (regex/matcher #"([0-9]+)(.*)" "100abc")]
      (regex/count m))
=> 2
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

regex/find

`(regex/find matcher)`
`(regex/find pattern s)`

Returns the next regex match or nil if there is no further match. Returns `nil` if there is no match.

To get the positional data for the matched group use `(regex/find+ matcher)`.

```
(regex/find #"[0-9]+" "672-345-456-3212")
=> "672"

(let [m (regex/matcher #"[0-9]+" "672-345-456-3212")]
  (println (regex/find m))
  (println (regex/find m))
  (println (regex/find m))
  (println (regex/find m))
  (println (regex/find m)))
672
345
456
3212
nil
=> nil
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/find-all](#)

Returns all regex matches as list or an empty list if there are no matches.

[regex/find+](#)

Returns the next regex match and returns the group with its positional data. Returns nil if there is no match.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

regex/find+

```
(regex/find+ matcher)
(regex/find+ pattern s)
```

Returns the next regex match and returns the group with its positional data. Returns `nil` if there is no match.

```
(regex/find+ #"[0-9]+" "672-345-456-3212")
=> {:start 0 :end 3 :group "672"}

(let [m (regex/matcher #"[0-9]+" "672-345-456-3212")]
  (println (regex/find+ m))
  (println (regex/find+ m))
  (println (regex/find+ m))
  (println (regex/find+ m))
  (println (regex/find+ m)))

{:start 0 :end 3 :group 672}
{:start 4 :end 7 :group 345}
{:start 8 :end 11 :group 456}
{:start 12 :end 16 :group 3212}
```

```
nil
=> nil
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/find-all+](#)

Returns the all regex matches and returns the groups with its positional data. Returns an empty list if there are no matches.

[regex/find](#)

Returns the next regex match or nil if there is no further match. Returns nil if there is no match.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

regex/find-all

```
(regex/find-all matcher)
(regex/find-all pattern s)
```

Returns all regex matches as list or an empty list if there are no matches.

To get the positional data for the matched groups use 'regex/find-all+'.

```
(regex/find-all #"d+" "672-345-456-3212")
=> ("672" "345" "456" "3212")

(->> (regex/matcher #"d+" "672-345-456-3212")
      (regex/find-all))
=> ("672" "345" "456" "3212")

(->> (regex/matcher "([^\"]\\S*|\".+?\\\")\\s*" "1 2 \"3 4\" 5")
      (regex/find-all))
=> ("1 " "2 " "\"3 4\" " "5")
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/find](#)

Returns the next regex match or nil if there is no further match. Returns nil if there is no match.

[regex/find-all+](#)

Returns the all regex matches and returns the groups with its positional data. Returns an empty list if there are no matches.

[regex/groups](#)

Attempts to match the entire region against the pattern and returns all matched groups. The entire regions is the first item in the ...

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

regex/find-all+

```
(regex/find-all+ matcher)
(regex/find-all+ pattern s)
```

Returns the all regex matches and returns the groups with its positional data. Returns an empty list if there are no matches.

```
(regex/find-all+ #"[0-9]+" "672-345-456-3212")
=> ({:start 0 :end 3 :group "672"} {:start 4 :end 7 :group "345"} {:start 8 :end 11 :group "456"} {:start 12 :
end 16 :group "3212"})
```

```
(let [m (regex/matcher #"[0-9]+" "672-345-456-3212")]
  (regex/find-all+ m))
```

```
=> ({:start 0 :end 3 :group "672"} {:start 4 :end 7 :group "345"} {:start 8 :end 11 :group "456"} {:start 12 :
end 16 :group "3212"})
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/find+](#)

Returns the next regex match and returns the group with its positional data. Returns nil if there is no match.

[regex/find-all](#)

Returns all regex matches as list or an empty list if there are no matches.

[regex/groups](#)

Attempts to match the entire region against the pattern and returns all matched groups. The entire regions is the first item in the ...

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

regex/find?

```
(regex/find? matcher)
```

Attempts to find the next subsequence that matches the pattern. If the match succeeds then more information can be obtained via the `regex/group` function

```
(let [m (regex/matcher #"[0-9]+" "100")]
  (regex/find? m))
=> true
```

```
(let [m (regex/matcher #"[0-9]+" "xxx: 100")]
  (regex/find? m))
=> true
```

```
(let [m (regex/matcher #"[0-9]+" "xxx: 100 200")]
  (when (regex/find? m)
```

```

    (println (regex/group m 0)))
  (when (regex/find? m)
    (println (regex/group m 0)))
  (when (regex/find? m)
    (println (regex/group m 0))))
100
200
=> nil

```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/group](#)

Returns the input subsequence captured by the given group during the previous match operation.

[regex/matches?](#)

Attempts to match the entire region against the pattern. Returns true if the patterns matches the string else false.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

regex/group

```
(regex/group matcher group)
```

Returns the input subsequence captured by the given group during the previous match operation.

Note: Do not forget to call the `regex/matches?` function!

```

(let [m (regex/matcher #"(\d+)(.*)" "100abc")]
  (if (regex/matches? m)
    [(regex/group m 1) (regex/group m 2)]
    []))
=> ["100" "abc"]

(do
  (ns-alias 'r 'regex)
  (defn swap [s]
    (let [m (r/matcher #"(\d+)([^\d]*) (\d+)" s)]
      (if (r/matches? m)
        (str (r/group m 3) (r/group m 2) (r/group m 1))
        s)))
  (swap "100::200"))
=> "200::100"

```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/groups](#)

Attempts to match the entire region against the pattern and returns all matched groups. The entire regions is the first item in the ...

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/matches?](#)

Attempts to match the entire region against the pattern. Returns true if the patterns matches the string else false.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

regex/groups

`(regex/groups matcher)`

Attempts to match the entire region against the pattern and returns all matched groups. The entire region is the first item in the returned group list. Returns an empty list if the entire region does not match the pattern.

```
(let [m (regex/matcher #"(\d+)(.*)" "100abc")]
  (regex/groups m))
=> ("100abc" "100" "abc")

(let [m (regex/matcher #"(\d+)([a-z]+)" "100abc:")]
  (regex/groups m))
=> ()
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/group](#)

Returns the input subsequence captured by the given group during the previous match operation.

[regex/find-all](#)

Returns all regex matches as list or an empty list if there are no matches.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/matches?](#)

Attempts to match the entire region against the pattern. Returns true if the patterns matches the string else false.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

regex/matcher

`(regex/matcher pattern str)`

Returns an instance of `java.util.regex.Matcher`.

The pattern can be either a string or a pattern created by `(regex/pattern s)`.

Matchers are mutable and are not safe for use by multiple concurrent threads!

JavaDoc: [Pattern](#)

```
(regex/matcher #"[0-9]+" "100")
=> java.util.regex.Matcher[pattern=[0-9]+ region=0,3 lastmatch=]

(regex/matcher (regex/pattern "[0-9]+") "100")
=> java.util.regex.Matcher[pattern=[0-9]+ region=0,3 lastmatch=]
```

```
(regex/matcher "[0-9]+" "100")
=> java.util.regex.Matcher[pattern=[0-9]+ region=0,3 lastmatch=]
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[regex/matches?](#)

Attempts to match the entire region against the pattern. Returns true if the patterns matches the string else false.

[regex/find?](#)

Attempts to find the next subsequence that matches the pattern. If the match succeeds then more information can be obtained via the ...

[regex/reset](#)

Resets the matcher with a new string

[regex/matches](#)

Returns the matches, if any, for the matcher with the pattern of a string, using `java.util.regex.Matcher.matches()`.

[regex/find](#)

Returns the next regex match or nil if there is no further match. Returns nil if there is no match.

[regex/find-all](#)

Returns all regex matches as list or an empty list if there are no matches.

[top](#)

[regex/matches](#)

```
(regex/matches pattern str)
```

Returns the matches, if any, for the matcher with the pattern of a string, using `java.util.regex.Matcher.matches()` .

If the matcher's pattern matches the entire region sequence returns a list with the entire region sequence and the matched groups otherwise returns an empty list.

Returns matching info as meta data on the region and the groups.

Region meta data:

```
:start      start pos of the overall group
:end        end pos of the overall group
:group-count the number of matched elements groups
```

Group meta data:

```
:start  start pos of the element group
:end    end pos of the element group
```

JavaDoc: [Pattern](#)

```
;; Entire region sequence matched
(regex/matches "hello, (.*)" "hello, world")
=> ("hello, world" "world")
```

```
;; Entire region sequence not matched
(regex/matches "HEllo, (.*)" "hello, world")
=> ()
```

```
;; Matching multiple groups
(regex/matches "([0-9]+)-([0-9]+)-([0-9]+)-([0-9]+)" "672-345-456-212")
=> ("672-345-456-212" "672" "345" "456" "212")

;; Matching multiple groups
(let [p (regex/pattern "([0-9]+)-([0-9]+)")]
  (regex/matches p "672-345"))
=> ("672-345" "672" "345")

;; Access matcher's region meta info
(let [pattern "([0-9]+)-([0-9]+)-([0-9]+)-([0-9]+)"
      matches (regex/matches pattern "672-345-456-212")]
  (println "meta info:" (pr-str (meta matches)))
  (println "matches: " (pr-str matches)))
meta info: {:group-count 4 :start 0 :end 15}
matches:   ("672-345-456-212" "672" "345" "456" "212")
=> nil

;; Access matcher's region meta info and the meta info of each group
(let [pattern "([0-9]+)-([0-9]+)-([0-9]+)-([0-9]+)"
      matches (regex/matches pattern "672-345-456-212")]
  (println "region info: " (pr-str (meta matches)))
  (println "group count: " (count matches) "(region included)"))
  (println "group matches: " (pr-str (nth matches 0)) (meta (nth matches 0)))
  (println " " (pr-str (nth matches 1)) (meta (nth matches 1)))
  (println " " (pr-str (nth matches 2)) (meta (nth matches 2)))
  (println " " (pr-str (nth matches 3)) (meta (nth matches 3)))
  (println " " (pr-str (nth matches 4)) (meta (nth matches 4))))
region info:   {:group-count 4 :start 0 :end 15}
group count:   5 (region included)
group matches: "672-345-456-212" {:start 0 :end 15}
               "672" {:start 0 :end 3}
               "345" {:start 4 :end 7}
               "456" {:start 8 :end 11}
               "212" {:start 12 :end 15}
=> nil
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

top

regex/matches-not?

```
(regex/matches-not? matcher)
(regex/matches-not? matcher str)
```

Attempts to match the entire region against the pattern. Returns false if the patterns matches the string else true.

```
(let [m (regex/matcher #"[0-9]+" "10A")]
  (regex/matches-not? m))
=> true
```



```
(let [m (regex/matcher #"[0-9]+" "value: 10A")]
  (regex/matches-not? m))
=> true

(let [m (regex/matcher #"[0-9]+" "")]
  (filter #(regex/matches-not? m %) ["100" "10A" "200"]))
=> ("10A")
```

SEE ALSO

[match?](#)

Returns true if the string *s* matches the regular expression *regex*.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/matches](#)

Returns the matches, if any, for the matcher with the pattern of a string, using `java.util.regex.Matcher.matches()`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

regex/matches?

```
(regex/matches? matcher)
(regex/matches? matcher str)
```

Attempts to match the entire region against the pattern. Returns true if the patterns matches the string else false.

```
(let [m (regex/matcher #"[0-9]+" "100")]
  (regex/matches? m))
=> true

(let [m (regex/matcher #"[0-9]+" "value: 100")]
  (regex/matches? m))
=> false

(let [m (regex/matcher #"[0-9]+" "")]
  (filter #(regex/matches? m %) ["100" "1a1" "200"]))
=> ("100" "200")
```

SEE ALSO

[match?](#)

Returns true if the string *s* matches the regular expression *regex*.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/matches](#)

Returns the matches, if any, for the matcher with the pattern of a string, using `java.util.regex.Matcher.matches()`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

regex/pattern

```
(regex/pattern s)
```

Returns an instance of `java.util.regex.Pattern`.

Patterns are immutable and are safe for use by multiple concurrent threads!

Alternatively regex pattern literals can be used to define a pattern: `#"[0-9+]"`

```
"\\d" ;; regex string to match one digit
```

Notice that you have to escape the backslash to get a literal backslash in the string. However, regex pattern literals are smart. They don't need to double escape:

```
#"\\d" ;; regex pattern literal to match one digit
```

JavaDoc: [Pattern](#)

```
(regex/pattern "[0-9]+")
```

```
=> [0-9]+
```

```
(regex/pattern "\\d+")
```

```
=> \d+
```

```
#"[0-9]+"
```

```
=> [0-9]+
```

```
#"\\d+"
```

```
=> \d+
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/matches](#)

Returns the matches, if any, for the matcher with the pattern of a string, using `java.util.regex.Matcher.matches()`.

[regex/find](#)

Returns the next regex match or nil if there is no further match. Returns nil if there is no match.

[regex/find-all](#)

Returns all regex matches as list or an empty list if there are no matches.

[top](#)

regex/reset

```
(regex/reset matcher str)
```

Resets the matcher with a new string

```
(do
  (let [m (regex/matcher #"[0-9]+" "100")]
    (println (regex/find m))
    (let [m (regex/reset m "200")]
```

```
(println (regex/find m))))))
100
200
=> nil
```

SEE ALSO

[match?](#)

Returns true if the string `s` matches the regular expression `regex`.

[regex/matcher](#)

Returns an instance of `java.util.regex.Matcher`.

[regex/pattern](#)

Returns an instance of `java.util.regex.Pattern`.

[top](#)

release

```
(release lock)
```

Releases a lock.

```
(let [l (lock)]
  (acquire l)
  ;; do something
  (release l))
=> nil
```

SEE ALSO

[lock](#)

Creates a new lock object.

[acquire](#)

Acquires a lock, blocking until the lock is available.

[try-acquire](#)

Acquires a lock within the given timeout time. Without a timeout returns immediately if the lock is not available.

[locked?](#)

Returns true if the lock is in use else false.

[top](#)

remove

```
(remove predicate coll)
```

Returns a collection of the items in `coll` for which `(predicate item)` returns logical false.
Returns a transducer when no collection is provided.

```
(remove nil? [1 nil nil 4 5 6])
=> (1 4 5 6)
```

```
(remove even? [1 2 3 4 5 6 7])
=> (1 3 5 7)
```

```
(remove #{3 5} '(1 3 5 7 9))  
=> (1 7 9)
```

```
(remove #(= 3 %) '(1 2 3 4 5 6))  
=> (1 2 4 5 6)
```

[top](#)

remove-formal-type

```
(remove-formal-type object)
```

Removes the *formal type* from a Java object.

This is identical to casting an object back to its real type without knowing its real type.

```
(do  
  (let [p0 (. :java.awt.Point :new 0 0)  
        p1 (cast :java.lang.Object p0)  
        p2 (remove-formal-type p1)]  
    (println "p0 ->" (formal-type p0))  
    (println "p1 ->" (formal-type p1))  
    (println "p2 ->" (formal-type p2))))  
p0 -> :java.awt.Point  
p1 -> :java.lang.Object  
p2 -> :java.awt.Point  
=> nil
```

SEE ALSO

[formal-type](#)

Returns the formal type of a Java object.

[cast](#)

Casts a Java object to a specific type

[class](#)

Returns the Java class for the given name. Throws an exception if the class is not found.

[top](#)

remove-tap

```
(remove-tap f)
```

Remove f from the tap set.

```
(do  
  (add-tap prn)  
  (remove-tap prn))  
=> nil
```

SEE ALSO

[add-tap](#)

adds f, a fn of one argument, to the tap set. This function will be called with anything sent via tap>.

[tap>](#)

Sends x to any taps. Will not block. Returns true if there was room in the queue, false if not (x is dropped).

[top](#)

remove-watch

```
(remove-watch ref key)
```

Removes a watch function from an agent/atom reference.

```
(do
  (def x (agent 10))
  (defn watcher [key ref old new]
    (println "watcher: " key))
  (add-watch x :test watcher)
  (remove-watch x :test))
=> nil
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[top](#)

repeat

```
(repeat x)
(repeat n x)
```

Returns a lazy sequence of x values or a collection with the value x repeated n times.

```
(repeat 3 "hello")
=> ("hello" "hello" "hello")

(repeat 5 [1 2])
=> ([1 2] [1 2] [1 2] [1 2] [1 2])

(repeat ":")
=> (...)

(interleave [:a :b :c] (repeat 100))
=> (:a 100 :b 100 :c 100)
```

SEE ALSO

[repeatedly](#)

Takes a function of no args, presumably with side effects, and returns a collection of n calls to it

[dotimes](#)

Repeatedly executes body with name bound to integers from 0 through n-1.

[constantly](#)

Returns a function that takes any number of arguments and returns always the value x.

repeatedly

```
(repeatedly n fn)
```

Takes a function of no args, presumably with side effects, and returns a collection of n calls to it

```
(repeatedly 5 #(rand-long 11))
=> (10 10 7 9 7)
```

```
;; compare with repeat, which only calls the 'rand-long'
;; function once, repeating the value five times.
(repeat 5 (rand-long 11))
=> (10 10 10 10 10)
```

SEE ALSO

[repeat](#)

Returns a lazy sequence of x values or a collection with the value x repeated n times.

[dotimes](#)

Repeatedly executes body with name bound to integers from 0 through n-1.

[constantly](#)

Returns a function that takes any number of arguments and returns always the value x.

repl/add-env

```
(repl/add-env name value)
```

Add (or replace) an env var to the REPL's local env file.

The REPL env file ('repl.env' on Unix or 'repl.env.bat' on Windows) is 'sourced' at REPL start time to make the contained vars available as system env vars!

DO NO FORGET to restart the REPL after adding an env var!

Note: This function is only available when called from within a REPL!

Example

1. Add env var:

```
(repl/add-env "DEMO" "100")
```

2. Restart the REPL:

```
venice> !restart
```

3. Test:

```
(system-env "DEMO")
```

```
(repl/add-env "DEMO" "100")
```

SEE ALSO

[system-env](#)

Returns the system env variable with the given name. Returns the default-val if the variable does not exist or it's value is nil.

[repl?](#)

Returns true if running within a REPL.

[repl/home-dir](#)

Returns the REPL home directory.

[repl/get-env](#)

Returns the value of a REPL local env var.

[repl/cat-env](#)

Returns the content of the REPL's local env file.

[repl/remove-env](#)

Remove an env var to the REPL's local env file.

[top](#)

repl/cat-env

```
(repl/cat-env)
```

Returns the content of the REPL's local env file.

The REPL env file ('repl.env' on Unix or 'repl.env.bat' on Windows) is 'sourced' at REPL start time to make the contained vars available as system env vars!

Note: This function is only available when called from within a REPL!

```
(println (repl/cat-env))
```

SEE ALSO

[system-env](#)

Returns the system env variable with the given name. Returns the default-val if the variable does not exist or it's value is nil.

[repl?](#)

Returns true if running within a REPL.

[repl/home-dir](#)

Returns the REPL home directory.

[repl/get-env](#)

Returns the value of a REPL local env var.

[repl/add-env](#)

Add (or replace) an env var to the REPL's local env file.

[repl/remove-env](#)

Remove an env var to the REPL's local env file.

[top](#)

repl/color-theme

```
(repl/color-theme)
```

Returns REPL's color theme (:light, :dark, :none)

```
(repl/color-theme)
```

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/color-theme!](#)

Set the REPL's color theme (:light, :dark)

[repl/prompt!](#)

Sets the REPL prompt string

[repl/handler!](#)

Sets the REPL command handler

[repl/info](#)

Returns information on the REPL.

[top](#)

repl/color-theme!

```
(repl/color-theme! theme)
```

Set the REPL's color theme (:light, :dark)

```
(repl/color-theme!)
```

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/color-theme](#)

Returns REPL's color theme (:light, :dark, :none)

[repl/prompt!](#)

Sets the REPL prompt string

[repl/handler!](#)

Sets the REPL command handler

[repl/info](#)

Returns information on the REPL.

[top](#)

repl/get-env

```
(repl/get-env name)
```

Returns the value of a REPL local env var.

The REPL env file ('repl.env' on Unix or 'repl.env.bat' on Windows) is 'sourced' at REPL start time to make the contained vars available as system env vars!

Note: This function is only available when called from within a REPL!

```
(repl/get-env "DEMO")
```

SEE ALSO

[system-env](#)

Returns the system env variable with the given name. Returns the default-val if the variable does not exist or it's value is nil.

[repl?](#)

Returns true if running within a REPL.

[repl/home-dir](#)

Returns the REPL home directory.

[repl/cat-env](#)

Returns the content of the REPL's local env file.

[repl/add-env](#)

Add (or replace) an env var to the REPL's local env file.

[repl/remove-env](#)

Remove an env var to the REPL's local env file.

[top](#)

repl/handler!

```
(repl/handler! f)
```

Sets the REPL command handler

```
(do
  (defn handle-command [cmd]
    ;; run the command 'cmd'
    (println "Demo:" cmd))

  (repl/handler! handle-command))
```

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/prompt!](#)

Sets the REPL prompt string

[repl/color-theme](#)

Returns REPL's color theme (:light, :dark, :none)

[repl/info](#)

Returns information on the REPL.

[top](#)

repl/home-dir

```
(repl/home-dir)
```

Returns the REPL home directory.

Note: This function is only available when called from within a REPL!

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/libs-dir](#)

Returns the REPL libs directory

[top](#)

repl/info

(repl/info)

Returns information on the REPL.

Note: This function is only available when called from within a REPL!

E.g.:

```
{ :term-name "JLine terminal"
  :term-type "xterm-256color"
  :term-cols 80
  :term-rows 24
  :term-colors 256
  :term-class :org.repackage.org.jline.terminal.impl.PosixSysTerminal
  :color-mode :light }
```

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/term-rows](#)

Returns number of rows in the REPL terminal.

[repl/term-cols](#)

Returns number of columns in the REPL terminal.

[top](#)

repl/libs-dir

(repl/libs-dir)

Returns the REPL libs directory

Note: This function is only available when called from within a REPL!

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/home-dir](#)

Returns the REPL home directory.

[top](#)

repl/prompt!

```
(repl/prompt! s)
```

Sets the REPL prompt string

```
(repl/prompt! "venice> ")
```

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/handler!](#)

Sets the REPL command handler

[repl/color-theme](#)

Returns REPL's color theme (:light, :dark, :none)

[repl/info](#)

Returns information on the REPL.

[top](#)

repl/remove-env

```
(repl/remove-env name)
```

Remove an env var to the REPL's local env file.

The REPL env file ('repl.env' on Unix or 'repl.env.bat' on Windows) is 'sourced' at REPL start time to make the contained vars available as system env vars!

To take a removed env var into effect a whole new REPL has to be started! A simple restart does not work!

Note: This function is only available when called from within a REPL!

```
(repl/remove-env "DEMO")
```

SEE ALSO

[system-env](#)

Returns the system env variable with the given name. Returns the default-val if the variable does not exist or it's value is nil.

[repl?](#)

Returns true if running within a REPL.

[repl/home-dir](#)

Returns the REPL home directory.

[repl/get-env](#)

Returns the value of a REPL local env var.

[repl/cat-env](#)

Returns the content of the REPL's local env file.

[repl/add-env](#)

Add (or replace) an env var to the REPL's local env file.

[top](#)

repl/term-cols

(`repl/term-cols`)

Returns number of columns in the REPL terminal.

Note: This function is only available when called from within a REPL!

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/term-rows](#)

Returns number of rows in the REPL terminal.

[repl/info](#)

Returns information on the REPL.

[top](#)

repl/term-rows

(`repl/term-rows`)

Returns number of rows in the REPL terminal.

Note: This function is only available when called from within a REPL!

SEE ALSO

[repl?](#)

Returns true if running within a REPL.

[repl/term-cols](#)

Returns number of columns in the REPL terminal.

[repl/info](#)

Returns information on the REPL.

[top](#)

repl?

(`repl?`)

Returns true if running within a REPL.

([repl?](#))

[top](#)

replace

(`replace smap coll`)

Given a map of replacement pairs and a collection, returns a collection with any elements that are a key in smap replaced with the corresponding value in smap.

```
(replace {2 :two, 4 :four} [4 2 3 4 5 6 2])  
=> [:four :two 3 :four 5 6 :two]
```

```
(replace {2 :two, 4 :four} #{1 2 3 4 5})  
=> #{1 3 5 :four :two}
```

```
(replace [{:a 10} [:c 30]] {:a 10 :b 20})  
=> {:b 20 :c 30}
```

[top](#)

reset!

```
(reset! box newval)
```

Sets the value of an atom or a volatile to newval without regard for the current value. Returns newval.

```
(do  
  (def counter (atom 0))  
  (reset! counter 99)  
  @counter)  
=> 99
```

```
(do  
  (def counter (atom 0))  
  (reset! counter 99))  
=> 99
```

```
(do  
  (def counter (volatile 0))  
  (reset! counter 99)  
  @counter)  
=> 99
```

SEE ALSO

[atom](#)

Creates an atom with the initial value x.

[volatile](#)

Creates a volatile with the initial value x

[top](#)

reset-ns-meta!

```
(reset-ns-meta! n datamap)
```

Resets the metadata for a namespace

```
(do  
  (ns foo)
```

```
(reset-ns-meta! foo {}))
=> {}

(do
  (ns foo)
  (def n 'foo)
  (reset-ns-meta! (var-get n) {}))
(pr-str (ns-meta (var-get n)))
=> "{}"
```

SEE ALSO

[ns-meta](#)

Returns the meta data of the namespace n or nil if n is not an existing namespace

[alter-ns-meta!](#)

Alters the metadata for a namespace. f must be free of side-effects.

[ns](#)

Opens a namespace.

[top](#)

resolve

```
(resolve symbol)
```

Resolves a symbol.

```
(resolve '+)
=> +
```

```
(resolve 'y)
=> nil
```

```
(resolve (symbol "+"))
=> +
```

```
((resolve (symbol "core" "+")) 1 2)
=> 3
```

```
((-> "first" symbol resolve) [1 2 3])
=> 1
```

SEE ALSO

[symbol](#)

Returns a symbol from the given name

[top](#)

rest

```
(rest coll)
```

Returns a possibly empty collection of the items after the first.

```
(rest nil)
=> nil

(rest [])
=> []

(rest [1])
=> []

(rest [1 2 3])
=> [2 3]

(rest '())
=> ()

(rest '(1))
=> ()

(rest '(1 2 3))
=> (2 3)

(rest "1234")
=> (#\2 #\3 #\4)
```

SEE ALSO

[str/rest](#)

Returns a possibly empty string of the characters after the first.

[top](#)

restart-agent

```
(restart-agent agent state)
```

When an agent is failed, changes the agent state to new-state and then un-fails the agent so that sends are allowed again.

```
(do
  (def x (agent 100))
  (restart-agent x 200)
  (deref x))
=> 200
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[top](#)

reverse

```
(reverse coll)
```

Returns a collection of the items in coll in reverse order.
Returns a stateful transducer when no collection is provided.

```
(reverse [1 2 3 4 5 6])  
=> [6 5 4 3 2 1]  
  
(reverse "abcdef")  
=> (#\f #\e #\d #\c #\b #\a)
```

SEE ALSO

[str/reverse](#)

Reverses a string

[top](#)

rf-any?

```
(rf-any? pred)
```

Returns a reducing function for a transducer that returns true if the predicate is true for at least one the items, false otherwise.

```
(transduce (filter number?) (rf-any? pos?) [true -1 1 2 false])  
=> true
```

SEE ALSO

[rf-first](#)

Returns a reducing function for a transducer that returns the first item.

[rf-last](#)

Returns a reducing function for a transducer that returns the last item.

[rf-every?](#)

Returns a reducing function for a transducer that returns true if the predicate is true for all the items, false otherwise.

[top](#)

rf-every?

```
(rf-every? pred)
```

Returns a reducing function for a transducer that returns true if the predicate is true for all the items, false otherwise.

```
(transduce (filter number?) (rf-every? pos?) [1 2 3])  
=> true
```

SEE ALSO

[rf-first](#)

Returns a reducing function for a transducer that returns the first item.

[rf-last](#)

Returns a reducing function for a transducer that returns the last item.

[rf-any?](#)

Returns a reducing function for a transducer that returns true if the predicate is true for at least one the items, false otherwise.

rf-first

```
(rf-first)
```

Returns a reducing function for a transducer that returns the first item.

```
(transduce (filter number?) rf-first [false 1 2])  
=> 1
```

```
(transduce identity rf-first [nil 1 2])  
=> nil
```

SEE ALSO

[rf-last](#)

Returns a reducing function for a transducer that returns the last item.

[rf-any?](#)

Returns a reducing function for a transducer that returns true if the predicate is true for at least one the items, false otherwise.

[rf-every?](#)

Returns a reducing function for a transducer that returns true if the predicate is true for all the items, false otherwise.

rf-last

```
(rf-last)
```

Returns a reducing function for a transducer that returns the last item.

```
(transduce (filter number?) rf-last [false 1 2])  
=> 2
```

```
(transduce identity rf-last [1 2 1.2])  
=> 1.2
```

SEE ALSO

[rf-first](#)

Returns a reducing function for a transducer that returns the first item.

[rf-any?](#)

Returns a reducing function for a transducer that returns true if the predicate is true for at least one the items, false otherwise.

[rf-every?](#)

Returns a reducing function for a transducer that returns true if the predicate is true for all the items, false otherwise.

ring-multipart/multipart-request?

```
(ring-multipart/multipart-request? req)
```

Returns true if the request is a multipart request 'multipart/form-data'

SEE ALSO

[ring-multipart/parts](#)

Returns a list of parts of a multipart HTTP request.

[ring-multipart/parts-delete-all](#)

Safely deletes for all parts the underlying storage for the file items, including deleting any associated temporary disk files.

[top](#)

ring-multipart/parts

```
(ring-multipart/parts req)
```

Returns a list of parts of a multipart HTTP request.

A part is map with the fields:

:name	The name of the part
:file-name	The file-name of the part or <i>nil</i> if not available
:size	The size of the file
:content-type	The content type of the part
:headers	A map of part's headers. key: header name, value: list of header values. The header names are mapped to lower case. Use <code>(first ("xxxx" :headers))</code> to get a single value header
:in-stream	The content part as input stream
:delete-fn	A function that deletes the underlying storage for a file item, including deleting any associated temporary disk file.

The part list is empty if the request is not a multipart request.

SEE ALSO

[ring-multipart/multipart-request?](#)

Returns true if the request is a multipart request 'multipart/form-data'

[ring-multipart/parts-delete-all](#)

Safely deletes for all parts the underlying storage for the file items, including deleting any associated temporary disk files.

[top](#)

ring-multipart/parts-delete-all

```
(ring-multipart/parts-delete-all req)
```

Safely deletes for all parts the underlying storage for the file items, including deleting any associated temporary disk files.

Calls the *delete-fn* on every part data map.

SEE ALSO

[ring-multipart/multipart-request?](#)

Returns true if the request is a multipart request 'multipart/form-data'

[ring-multipart/parts](#)

Returns a list of parts of a multipart HTTP request.

[top](#)

ring-mw/mw-debug

(ring-mw/mw-debug handler option)

Turns handler debug flag on the request on/off and then calls the handler with the modified request.

SEE ALSO

[ring-mw/mw-identity](#)

Identity, does effectively just delegate to the handler

[ring-mw/mw-print-uri](#)

Prints the URI from the request and then calls the handler

[ring-mw/mw-request-counter](#)

Increments the number requests, stores it in the attribute 'request-counter' in the session, and then calls the handler.

[ring-mw/mw-add-session](#)

Adds the session to the request. If a new session is created the given timeout is set as the MaxInactiveInterval. If a timeout is not ...

[ring-mw/mw-dump-request](#)

Dumps the request and then calls the handler.

[ring-mw/mw-dump-response](#)

Calls the handler and the dumps the handler's response.

[top](#)

ring-mw/mw-dump-request

(ring-mw/mw-dump-request handler)

Dumps the request and then calls the handler.

SEE ALSO

[ring-mw/mw-identity](#)

Identity, does effectively just delegate to the handler

[ring-mw/mw-debug](#)

Turns handler debug flag on the request on/off and then calls the handler with the modified request.

[ring-mw/mw-print-uri](#)

Prints the URI from the request and then calls the handler

[ring-mw/mw-request-counter](#)

Increments the number requests, stores it in the attribute 'request-counter' in the session, and then calls the handler.

[ring-mw/mw-add-session](#)

Adds the session to the request. If a new session is created the given timeout is set as the MaxInactiveInterval. If a timeout is not ...

[ring-mw/mw-dump-response](#)

Calls the handler and the dumps the handler's response.

ring-mw/mw-dump-response

(ring-mw/mw-dump-response handler)

Calls the handler and then dumps the handler's response.

SEE ALSO

[ring-mw/mw-identity](#)

Identity, does effectively just delegate to the handler

[ring-mw/mw-debug](#)

Turns handler debug flag on the request on/off and then calls the handler with the modified request.

[ring-mw/mw-print-uri](#)

Prints the URI from the request and then calls the handler

[ring-mw/mw-request-counter](#)

Increments the number requests, stores it in the attribute 'request-counter' in the session, and then calls the handler.

[ring-mw/mw-add-session](#)

Adds the session to the request. If a new session is created the given timeout is set as the MaxInactiveInterval. If a timeout is not ...

[ring-mw/mw-dump-request](#)

Dumps the request and then calls the handler.

[ring-mw/mw-dump-response](#)

Calls the handler and then dumps the handler's response.

ring-mw/mw-identity

(ring-mw/mw-identity handler)

Identity, does effectively just delegate to the handler

SEE ALSO

[ring-mw/mw-debug](#)

Turns handler debug flag on the request on/off and then calls the handler with the modified request.

[ring-mw/mw-print-uri](#)

Prints the URI from the request and then calls the handler

[ring-mw/mw-request-counter](#)

Increments the number requests, stores it in the attribute 'request-counter' in the session, and then calls the handler.

[ring-mw/mw-add-session](#)

Adds the session to the request. If a new session is created the given timeout is set as the MaxInactiveInterval. If a timeout is not ...

[ring-mw/mw-dump-request](#)

Dumps the request and then calls the handler.

[ring-mw/mw-dump-response](#)

Calls the handler and then dumps the handler's response.

ring-mw/mw-print-uri

(ring-mw/mw-print-uri handler)

Prints the URI from the request and then calls the handler

SEE ALSO

[ring-mw/mw-identity](#)

Identity, does effectively just delegate to the handler

[ring-mw/mw-debug](#)

Turns handler debug flag on the request on/off and then calls the handler with the modified request.

[ring-mw/mw-request-counter](#)

Increments the number requests, stores it in the attribute 'request-counter' in the session, and then calls the handler.

[ring-mw/mw-add-session](#)

Adds the session to the request. If a new session is created the given timeout is set as the MaxInactiveInterval. If a timeout is not ...

[ring-mw/mw-dump-request](#)

Dumps the request and then calls the handler.

[ring-mw/mw-dump-response](#)

Calls the handler and the dumps the handler's response.

[top](#)

ring-mw/mw-request-counter

(ring-mw/mw-request-counter handler)

Increments the number requests, stores it in the attribute 'request-counter' in the session, and then calls the handler.

SEE ALSO

[ring-mw/mw-identity](#)

Identity, does effectively just delegate to the handler

[ring-mw/mw-debug](#)

Turns handler debug flag on the request on/off and then calls the handler with the modified request.

[ring-mw/mw-print-uri](#)

Prints the URI from the request and then calls the handler

[ring-mw/mw-add-session](#)

Adds the session to the request. If a new session is created the given timeout is set as the MaxInactiveInterval. If a timeout is not ...

[ring-mw/mw-dump-request](#)

Dumps the request and then calls the handler.

[ring-mw/mw-dump-response](#)

Calls the handler and the dumps the handler's response.

[top](#)

ring-session/session-clear

(ring-session/session-clear req)

Removes all attributes from the session

SEE ALSO

[ring-session/session-invalidate](#)

Invalidate the session

[ring-session/session-id](#)

Get the session ID

[ring-session/session-set-value](#)

Sets a value on the session

[ring-session/session-get-value](#)

Get a value from the session

[ring-session/session-remove-value](#)

Remove a value from the session

[ring-session/session-last-access-time](#)

Returns the time (milliseconds since epoch) when this session was last accessed.

[ring-session/session-creation-time](#)

Returns the time (milliseconds since epoch) when this session was created.

[top](#)

ring-session/session-creation-time

(ring-session/session-creation-time req)

Returns the time (milliseconds since epoch) when this session was created.

SEE ALSO

[ring-session/session-invalidate](#)

Invalidate the session

[ring-session/session-clear](#)

Removes all attributes from the session

[ring-session/session-id](#)

Get the session ID

[ring-session/session-set-value](#)

Sets a value on the session

[ring-session/session-get-value](#)

Get a value from the session

[ring-session/session-remove-value](#)

Remove a value from the session

[ring-session/session-last-access-time](#)

Returns the time (milliseconds since epoch) when this session was last accessed.

[top](#)

ring-session/session-get-value

```
(ring-session/session-get-value req name)
```

Get a value from the session

SEE ALSO

[ring-session/session-invalidate](#)

Invalidate the session

[ring-session/session-clear](#)

Removes all attributes from the session

[ring-session/session-id](#)

Get the session ID

[ring-session/session-set-value](#)

Sets a value on the session

[ring-session/session-remove-value](#)

Remove a value from the session

[ring-session/session-last-access-time](#)

Returns the time (milliseconds since epoch) when this session was last accessed.

[ring-session/session-creation-time](#)

Returns the time (milliseconds since epoch) when this session was created.

[top](#)

ring-session/session-id

```
(ring-session/session-id req)
```

Get the session ID

SEE ALSO

[ring-session/session-invalidate](#)

Invalidate the session

[ring-session/session-clear](#)

Removes all attributes from the session

[ring-session/session-set-value](#)

Sets a value on the session

[ring-session/session-get-value](#)

Get a value from the session

[ring-session/session-remove-value](#)

Remove a value from the session

[ring-session/session-last-access-time](#)

Returns the time (milliseconds since epoch) when this session was last accessed.

[ring-session/session-creation-time](#)

Returns the time (milliseconds since epoch) when this session was created.

[top](#)

ring-session/session-invalidate

```
(ring-session/session-invalidate req)
```

Invalidate the session

SEE ALSO

[ring-session/session-clear](#)

Removes all attributes from the session

[ring-session/session-id](#)

Get the session ID

[ring-session/session-set-value](#)

Sets a value on the session

[ring-session/session-get-value](#)

Get a value from the session

[ring-session/session-remove-value](#)

Remove a value from the session

[ring-session/session-last-access-time](#)

Returns the time (milliseconds since epoch) when this session was last accessed.

[ring-session/session-creation-time](#)

Returns the time (milliseconds since epoch) when this session was created.

[top](#)

ring-session/session-remove-value

```
(ring-session/session-remove-value req name)
```

Remove a value from the session

SEE ALSO

[ring-session/session-invalidate](#)

Invalidate the session

[ring-session/session-clear](#)

Removes all attributes from the session

[ring-session/session-id](#)

Get the session ID

[ring-session/session-set-value](#)

Sets a value on the session

[ring-session/session-get-value](#)

Get a value from the session

[ring-session/session-last-access-time](#)

Returns the time (milliseconds since epoch) when this session was last accessed.

[ring-session/session-creation-time](#)

Returns the time (milliseconds since epoch) when this session was created.

ring-util/debug?

```
(ring-util/debug? req)
```

Returns true if debugging is turned on else false

ring-util/get-request-header

```
(ring-util/get-request-header req name)
```

Returns the first value of the specified case independent request header name.

If the request did not include a header of the specified name, this method returns `nil`. If there are multiple headers with the same name, this method returns the first header in the request.

ring-util/get-request-header-accept-mimetypes

```
(ring-util/get-request-header-accept-mimetypes req)
```

Returns all 'Accept' header mime-types of the request as a set. Strips off the ratings

ring-util/get-request-long-parameter

```
(ring-util/get-request-long-parameter request name)  
(ring-util/get-request-long-parameter request name value)
```

Returns the first parameter a the multi value request parameter with the name 'name'. Accepts an optional default value.

Converts the parameter value to long. Returns the default value if the parameter is not of type long.

Returns `nil` if the parameter does not exist and a default value is not passed.

ring-util/get-request-parameter

```
(ring-util/get-request-parameter req name)
```

Returns the first value of the specified case independent request parameter name.

If the request did not include a parameter of the specified name, this method returns `nil`. If there are multiple headers with the same name, this method returns the first parameter in the request.

[top](#)

ring-util/get-request-parameters

```
(ring-util/get-request-parameters req name)
```

Returns all values of the specified case independent request parameter name as a list.

[top](#)

ring-util/html-request?

```
(ring-util/html-request? req)
```

Returns true if the request has content type 'text/html'

[top](#)

ring-util/json-request?

```
(ring-util/json-request? req)
```

Returns true if the request has content type 'application/json'

[top](#)

ring-util/not-found-response

```
(ring-util/not-found-response)  
(ring-util/not-found-response msg)
```

Create a HTTP Not-Found 404 response with content-type text/html.

[top](#)

ring-util/parse-charset

```
(ring-util/parse-charset header)
```

Parses the charset from a header value

E.g.: Returns `utf-8` for a content tye header like: `Content-Type: text/html; charset=utf-8`

ring-util/redirect

```
(ring-util/redirect request url)
```

Redirect to the given URL.

ring/create-servlet

```
(ring/create-servlet handler)
```

Create a ring servlet.

SEE ALSO

[ring/match-routes](#)

Compile the routes and return a function that calls the handler matching the URI.

ring/match-routes

```
(ring/match-routes routes)
```

Compile the routes and return a function that calls the handler matching the URI.

A route is defined by a HTTP verb, a URI filter and a handle function. If multiple routes match the route with the longest URI filter will be chosen.

```
(def routes [
  [:get    "/"**"                hello-world-handler]
  [:get    "/test/**"           test-handler]
  [:get    "/static/images/*.png" image-handler]

  [:get    "/employees"         get-all-employees]
  [:get    "/employees/:id"      get-employee]
  [:post   "/employees"         create-employee]
  [:put    "/employees/:id"      update-employee]
  [:delete "/employees/:id"      delete-employee] ])
```

Routing URI pattern filters:

- `"/**"`
- `"/app/**"`
- `"/static/images/chart.png"`
- `"/static/images/*.png"`
- `"/static/**/*.png"`

A routing handler is single argument function that receives the request and returns a response.

Handler request:

`:server-port` The server port. E.g.: 8080

:server-name	The server name. E.g.: localhost
:remote-addr	The remote address. E.g.: "0:0:0:0:0:0:1"
:uri	The request URI. E.g.: "/employees"
:query-string	The query string
:scheme	The scheme { :http, :https }
:request-method	The lower case request method. { :get, :post, :put, :delete, :head, :options, :trace }
:protocol	The protocol. E.g. "HTTP/1.1"
:headers	A map of part's headers. Key: header name, value: list of header values. The header names are mapped to lower case. Use <code>(first ("xxxx" :headers))</code> to get a single value header
:parameters	A name/value map of the request parameters
:cookies	A map of the cookies. Key: cookie name, value: the Java servlet cookie object
:content-type	The content type (may be nil)
:content-length	The content length
:character-encoding	The character encoding
:ssl-client-cert	The client certificate, if available
:parts	A list of parts, empty for non multipart requests
:body	The content part as input stream

Handler response:

```
{ :status 400
  :headers { "Content-Type" "text/plain" }
  :body "Not a json request!" }
```

The `:body` element of a handler response may be a:

- string
- bytebuf
- `:java.io.InputStream`
- `:java.io.File`

Rigging up a Ring WEB App and starting Tomcat:

```
(tc/run-tomcat
 (ring/create-servlet (-> (ring/match-routes routes)
                          ; >--+
                          ;   |
                          (ring-mw/mw-dump-request)      ; ^  |
                          (ring-mw/mw-request-counter)   ; |  |
                          (ring-mw/mw-add-session 3600)  ; |  |
                          (ring-mw/mw-print-uri)         ; |  |
                          (ring-mw/mw-debug :on)))        ; +--+
 {:await? false}))
```

SEE ALSO

[ring/create-servlet](#)

Create a ring servlet.

top

run!

```
(run! f coll)
```

Runs the supplied function, for purposes of side effects, on successive items in the collection. Returns `nil`

```
(run! prn [1 2 3 4])
1
2
3
4
=> nil
```

SEE ALSO

[docoll](#)

Applies f to the items of the collection presumably for side effects. Returns nil.

[mapv](#)

Returns a vector consisting of the result of applying f to the set of first items of each coll, followed by applying f to the set of ...

[top](#)

sandbox/functions

```
(sandbox/functions group)
```

Lists the sandboxed functions defined by a sandbox function group.

Groups:

- `:io`
- `:print`
- `:concurrency`
- `:java-interop`
- `:system`
- `:special-forms`
- `:unsafe`

```
(sandbox/functions :print)
```

SEE ALSO

[sandboxed?](#)

Returns true if there is a sandbox other than `:AcceptAllInterceptor` otherwise false.

[top](#)

sandbox/type

```
(sandbox/type)
```

Returns the sandbox type.

Venice sandbox types:

- `:AcceptAllInterceptor` - accepts all (no restrictions)
- `:RejectAllInterceptor` - safe sandbox, rejects access to all I/O functions, system properties, environment vars, extension modules, dynamic code loading, multi-threaded functions (futures, agents, ...), and Java calls
- `:SandboxInterceptor` - customized sandbox

```
(sandbox/type)
=> :AcceptAllInterceptor
```

SEE ALSO

[sandboxed?](#)

Returns true if there is a sandbox other than `:AcceptAllInterceptor` otherwise false.

[top](#)

sandboxed?

```
(sandboxed?)
```

Returns true if there is a sandbox other than `:AcceptAllInterceptor` otherwise false.

```
(sandboxed?)
=> false
```

SEE ALSO

[sandbox/type](#)

Returns the sandbox type.

[top](#)

schedule-at-fixed-rate

```
(schedule-at-fixed-rate fn initial-delay period time-unit)
```

Creates and executes a periodic action that becomes enabled first after the given initial delay, and subsequently with the given period. Returns a future. `(future? f)`, `(cancel f)`, and `(done? f)` will work on the returned future. Time unit is one of `:milliseconds`, `:seconds`, `:minutes`, `:hours`, or `:days`.

```
(schedule-at-fixed-rate #(println "test") 1 2 :seconds)

(let [s (schedule-at-fixed-rate #(println "test") 1 2 :seconds)]
  (sleep 16 :seconds)
  (cancel s))
```

SEE ALSO

[schedule-delay](#)

Creates and executes a one-shot action that becomes enabled after the given delay.

[top](#)

schedule-delay

```
(schedule-delay fn delay time-unit)
```

Creates and executes a one-shot action that becomes enabled after the given delay.

Returns a future. `(deref f)`, `(future? f)`, `(cancel f)`, and `(done? f)` will work on the returned future.

Time unit is one of `:milliseconds`, `:seconds`, `:minutes`, `:hours`, or `:days`.

```
(schedule-delay (fn [] (println "test")) 1 :seconds)
```

```
(deref (schedule-delay (fn [] 100) 2 :seconds))
```

SEE ALSO

[schedule-at-fixed-rate](#)

Creates and executes a periodic action that becomes enabled first after the given initial delay, and subsequently with the given period.

[top](#)

second

```
(second coll)
```

Returns the second element of coll.

```
(second nil)
=> nil
```

```
(second [])
=> nil
```

```
(second [1 2 3])
=> 2
```

```
(second '())
=> nil
```

```
(second '(1 2 3))
=> 2
```

[top](#)

select-keys

```
(select-keys map keyseq)
```

Returns a map containing only those entries in map whose key is in keys

```
(select-keys {:a 1 :b 2} [:a])
=> {:a 1}
```

```
(select-keys {:a 1 :b 2} [:a :c])
=> {:a 1}
```

```
(select-keys {:a 1 :b 2 :c 3} [:a :c])
=> {:a 1 :c 3}
```

SEE ALSO

[keys](#)

Returns a collection of the map's keys.

[entries](#)

Returns a collection of the map's entries.

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[top](#)

semver/cmp

```
(semver/cmp a b)
```

Compares versions a and b, returning -1 if a is older than b, 0 if they're the same version, and 1 if a is newer than b.

```
(semver/cmp "1.2.3" "1.5.4")  
=> -1
```

```
(semver/cmp (semver/version "1.2.3") (semver/version "1.5.4"))  
=> -1
```

SEE ALSO

[semver/equal?](#)

Is version a the same as version b?

[semver/newer?](#)

Is version a newer than version b?

[semver/older?](#)

Is version a older than version b?

[top](#)

semver/equal?

```
(semver/equal? a b)
```

Is version a the same as version b?

```
(semver/newer? "1.2.3" "1.2.3")  
=> false
```

```
(semver/newer? (semver/version "1.2.3") (semver/version "1.2.3"))  
=> false
```

SEE ALSO

[semver/newer?](#)

Is version a newer than version b?

[semver/older?](#)

Is version a older than version b?

[semver/cmp](#)

Compares versions a and b, returning -1 if a is older than b, 0 if they're the same version, and 1 if a is newer than b.

[top](#)

semver/newer?

```
(semver/newer? a b)
```

Is version a newer than version b?

```
(semver/newer? "1.5.4" "1.2.3")  
=> true
```

```
(semver/newer? (semver/version "1.5.4") (semver/version "1.2.3"))  
=> true
```

SEE ALSO

[semver/older?](#)

Is version a older than version b?

[semver/equal?](#)

Is version a the same as version b?

[semver/cmp](#)

Compares versions a and b, returning -1 if a is older than b, 0 if they're the same version, and 1 if a is newer than b.

[top](#)

semver/older?

```
(semver/older? a b)
```

Is version a older than version b?

```
(semver/newer? "1.2.3" "1.5.4")  
=> false
```

```
(semver/newer? (semver/version "1.2.3") (semver/version "1.5.4"))  
=> false
```

SEE ALSO

[semver/newer?](#)

Is version a newer than version b?

[semver/equal?](#)

Is version a the same as version b?

[semver/cmp](#)

Compares versions a and b, returning -1 if a is older than b, 0 if they're the same version, and 1 if a is newer than b.

[top](#)

semver/parse

```
(semver/parse s)
```

Parses string 's' into a semantic version map.

Semantic versioning format:

standard

```
version:      1.0.0
pre-release:   1.0.0-beta
meta data:     1.0.0-beta+001
```

with revision

```
version:      1.0.0.0
pre-release:   1.0.0.0-beta
meta data:     1.0.0.0-beta+001
```

```
E.g.: { :major 1, :minor 3, :patch 5 }
      { :major 1, :minor 3, :patch 5 :pre-release "beta" }
      { :major 1, :minor 3, :patch 5 :pre-release "beta" }
      { :major 1, :minor 3, :patch 5 :pre-release "beta" :meta "001" }
```

```
(semver/parse "1.2.3")
```

```
=> { :patch 3 :meta-data nil :minor 2 :major 1 :revision nil :pre-release nil }
```

```
(semver/parse "1.2.3-beta")
```

```
=> { :patch 3 :meta-data nil :minor 2 :major 1 :revision nil :pre-release "beta" }
```

```
(semver/parse "1.2.3-beta+001")
```

```
=> { :patch 3 :meta-data "001" :minor 2 :major 1 :revision nil :pre-release "beta" }
```

SEE ALSO

[semver/version](#)

If 'o' is a valid version map, returns the map. Otherwise, it'll attempt to parse 'o' and return a version map.

[semver/valid-format?](#)

Checks the string 's' for semantic versioning formatting

[top](#)

semver/valid-format?

```
(semver/valid-format? s)
```

Checks the string 's' for semantic versioning formatting

```
(semver/valid-format? "1.2.3")
```

```
=> true
```

SEE ALSO

[semver/parse](#)

Parses string 's' into a semantic version map.

[semver/valid?](#)

Checks if the supplied version map is valid regarding semantic versioning or not.

semver/valid?

```
(semver/valid? v)
```

Checks if the supplied version map is valid regarding semantic versioning or not.

```
(semver/valid? (semver/parse "1.2.3"))  
=> true
```

SEE ALSO

[semver/parse](#)

Parses string 's' into a semantic version map.

[semver/valid?](#)

Checks if the supplied version map is valid regarding semantic versioning or not.

semver/version

```
(semver/version o)
```

If 'o' is a valid version map, returns the map. Otherwise, it'll attempt to parse 'o' and return a version map.

```
(semver/version "1.2.3")  
=> {:patch 3 :meta-data nil :minor 2 :major 1 :revision nil :pre-release nil}
```

SEE ALSO

[semver/parse](#)

Parses string 's' into a semantic version map.

send

```
(send agent action-fn args)
```

Dispatch an action to an agent. Returns the agent immediately.

The state of the agent will be set to the value of:

```
(apply action-fn state-of-agent args)
```

```
(do  
  (def x (agent 100))  
  (send x + 5)  
  (send x (partial + 7))  
  (sleep 100)  
  (deref x))  
=> 112
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[send-off](#)

Dispatch a potentially blocking action to an agent. Returns the agent immediately.

[top](#)

send-off

```
(send-off agent fn args)
```

Dispatch a potentially blocking action to an agent. Returns the agent immediately.

The state of the agent will be set to the value of:

```
(apply action-fn state-of-agent args)
```

```
(do
  (def x (agent 100))
  (send-off x + 5)
  (send-off x (partial + 7))
  (sleep 100)
  (deref x))
=> 112
```

SEE ALSO

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[send](#)

Dispatch an action to an agent. Returns the agent immediately.

[top](#)

seq

```
(seq coll)
```

Returns a sequence on the collection.

If the collection is empty, returns nil! `(seq nil)` returns nil.

seq also works on strings and converts Java streams to lists.

```
(seq nil)
=> nil
```

```
(seq [])
=> nil
```

```
(seq [1 2 3])
=> (1 2 3)
```

```
(seq '(1 2 3))
=> (1 2 3)

(seq {:a 1 :b 2})
=> ([:a 1] [:b 2])

(seq "abcd")
=> (#\a #\b #\c #\d)

(flatten (seq {:a 1 :b 2}))
=> (:a 1 :b 2)
```

[top](#)

sequential?

```
(sequential? coll)
```

Returns true if coll is a sequential collection

```
(sequential? '(1))
=> true

(sequential? [1])
=> true

(sequential? {:a 1})
=> false

(sequential? nil)
=> false

(sequential? "abc")
=> false
```

[top](#)

server-side-events/parse

```
(parse s)
```

Parses a server side event in string representation to a map.

```
(do
  (load-module :server-side-events ['server-side-events :as 'sse])
  (-> (sse/render { :id "100"
                   :event "scores"
                   :data ["100" "200"] } )
      (sse/parse)))
=> {:data ["100" "200"] :event "scores" :id "100"}
```

SEE ALSO

[server-side-events/render](#)

Renders a server side event to a string.

[top](#)

server-side-events/read-event

```
(read-event rd)
```

Read a single event from a `:java.io.BufferedReader`.

Returns the event or `nil` if the underlying stream has been closed.

```
(do
  (load-module :server-side-events ['server-side-events :as 'sse])

  (defn sample-events []
    (str (sse/render { :id "100" :event "scores" :data ["100"] } )
         (sse/render { :id "101" :event "scores" :data ["101"] } )
         (sse/render { :id "102" :event "scores" :data ["102"] } )))

  (try-with [is (io/string-in-stream (sample-events))
              rd (io/wrap-is-with-buffered-reader is :utf-8)]
    (sse/read-event rd)))
=> {:data ["100"] :event "scores" :id "100"}
```

SEE ALSO

[server-side-events/read-events](#)

Reads multiple events from a `:java.io.BufferedReader`.

[top](#)

server-side-events/read-events

```
(read-events rd limit)
```

Reads multiple events from a `:java.io.BufferedReader`.

Returns a list of events. Stops reading events if the limit is reached or the underlying stream has been closed.

```
(do
  (load-module :server-side-events ['server-side-events :as 'sse])

  (defn sample-events []
    (str (sse/render { :id "100" :event "scores" :data ["100"] } )
         (sse/render { :id "101" :event "scores" :data ["101"] } )
         (sse/render { :id "102" :event "scores" :data ["102"] } )
         (sse/render { :id "103" :event "scores" :data ["103"] } )))

  (try-with [is (io/string-in-stream (sample-events))
              rd (io/wrap-is-with-buffered-reader is :utf-8)]
    (sse/read-events rd 3)))
=> [{:data ["100"] :event "scores" :id "100"} {:data ["101"] :event "scores" :id "101"} {:data ["102"] :event "scores" :id "102"}]
```

SEE ALSO

[server-side-events/read-event](#)

Read a single event from a `:java.io.BufferedReader`.

[top](#)

server-side-events/render

`(render event)`

Renders a server side event to a string.

Returns the event as string or `nil` if the event is `nil` or all its fields are empty or `nil`,

Note: SSE is restricted to transporting UTF-8 messages.

The event is a map. E.g. :

```
{ :id      "1"
  :event   "score"
  :data    [ "GOAL Liverpool 1 - 1 Arsenal"
             "GOAL Manchester United 3 - 3 Manchester City" ] }
```

with the text representation

```
id: 1\n
event: score\n
data: GOAL Liverpool 1 - 1 Arsenal\n
data: GOAL Manchester United 3 - 3 Manchester City\n\n
```

The event fields `:id`, `:event`, and `:data` must not contain newline, carriage return, backspace, or formfeed characters!

A HTTP request to initiate SSE streaming looks like:

```
GET /api/v1/live-scores
Accept: text/event-stream
Cache-Control: no-cache
Connection: keep-alive
```

```
(do
  (load-module :server-side-events ['server-side-events :as 'sse])
  (sse/render { :id "100"
                :event "scores"
                :data ["100" "200"] } ))
=> "id: 100\r\nevent: scores\r\ndata: 100\r\ndata: 200\r\n\r\n"
```

SEE ALSO

[server-side-events/parse](#)

Parses a server side event in string representation to a map.

[top](#)

service

`(service name method & args)`

Calls a service with the specified name from the Venice's service registry.

Venice's service registry is used with application scripting scenarios where multiple external services must be made available to Venice. E.g.: the service registry can be used to register an application's *Spring Framework* services and make them discoverable by a Venice script.

Example:

```

Venice venice = new Venice();

venice.getServiceRegistry()
    .register("Calculator", new Calculator())
    .registerServiceDiscovery(new TestServiceDiscovery());

long r = (Long)venice.eval("(service :Calculator :multiply 10 20)");
venice.eval("(service :Logger :log (version))");

```

while `Calculator` and `TestServiceDiscovery` are defined as:

```

public static class TestServiceDiscovery implements IServiceDiscovery {
    @Override public Object lookup(final String name) {
        if (name == null) {
            throw new IllegalArgumentException("A service name must not be null");
        }
        else if (name.equals("Logger")) {
            return logger;
        }
        else {
            throw new VncException("Service " + name + " is not registered");
        }
    }
    private final Logger logger = new Logger();
}

public class Calculator {
    public long multiply(long v1, long v2) {
        return v1 * v2;
    }
}

public static class Logger {
    public void log(String message) {
        System.out.println(message);
    }
}

```

```
(service :UserService :find "Smith" "John")
```

SEE ALSO

[service?](#)

Returns true if the named service exists otherwise false

top

service?

```
(service? name)
```

Returns true if the named service exists otherwise false

```
(service? :UserService
```

SEE ALSO

[service](#)

Calls a service with the specified name from the Venice's service registry.

set

```
(set & items)
```

Creates a new set containing the items.

```
(set)
=> #[]
```

```
(set nil)
=> #{nil}
```

```
(set 1)
=> #{1}
```

```
(set 1 2 3)
=> #{1 2 3}
```

```
(set [1 2] 3)
=> #{[1 2] 3}
```

set!

```
(set! var-symbol expr)
```

Sets a global or thread-local variable to the value of the expression.

```
(do
  (def x 10)
  (set! x 20)
  x)
=> 20
```

```
(do
  (def-dynamic x 100)
  (set! x 200)
  x)
=> 200
```

```
(do
  (def-dynamic x 100)
  (without-str
    (print x)
    (binding [x 200]
      (print (str "- " x))
      (set! x (inc x))
      (print (str "- " x)))
    (print (str "- " x))))
=> "100-200-201-100"
```

SEE ALSO

def

Creates a global variable.

def-dynamic

Creates a dynamic variable that starts off as a global variable and can be bound with 'binding' to a new value on the local thread.

[top](#)

set-error-handler!

```
(set-error-handler! agent handler-fn)
```

Sets the error-handler of an agent to `handler-fn`. If an action being run by the agent throws an exception `handler-fn` will be called with two arguments: the agent and the exception.

```
(do
  (def x (agent 100))
  (defn err-handler-fn [ag ex]
    (println "error occurred: "
              (:message ex)
              " and we still have value"
              @ag))
  (set-error-handler! x err-handler-fn)
  (send x (fn [n] (/ n 0))))
=> (agent :value 100)
```

SEE ALSO

agent

Creates and returns an agent with an initial value of state and zero or more options.

agent-error-mode

Returns the agent's error mode

agent-error

Returns the exception thrown during an asynchronous action of the agent if the agent is failed. Returns nil if the agent is not failed.

[top](#)

set?

```
(set? obj)
```

Returns true if obj is a set

```
(set? (set 1))
=> true
```

[top](#)

sgn

```
(sgn x)
```

sgn function for a number.

```
-1 if x < 0
 0 if x = 0
 1 if x > 0
```

```
(sgn -10)
=> -1
```

```
(sgn 0)
=> 0
```

```
(sgn 10)
=> 1
```

```
(sgn -10I)
=> -1
```

```
(sgn -10.1)
=> -1
```

```
(sgn -10.12M)
=> -1
```

SEE ALSO

[abs](#)

Returns the absolute value of the number

[negate](#)

Negates x

top

sh

```
(sh & args)
```

Launches a new sub-process.

Options:

:in	may be given followed by input source as InputStream, Reader, File, ByteBuf, or String, to be fed to the sub-process's stdin.
:in-enc	option may be given followed by a String, used as a character encoding name (for example "UTF-8" or "ISO-8859-1") to convert the input string specified by the :in option to the sub-process's stdin. Defaults to "UTF-8". If the :in option provides a byte array, then the bytes are passed unencoded, and this option is ignored.
:out-enc	option may be given followed by :bytes or a String. If a String is given, it will be used as a character encoding name (for example "UTF-8" or "ISO-8859-1") to convert the sub-process's stdout to a String which is returned. If :bytes is given, the sub-process's stdout will be stored in a Bytebuf and returned. Defaults to UTF-8.
:out-fn	a function with a single string argument that receives line by line from the process' stdout. If passed the :out value in the return map will be empty.
:err-fn	a function with a single string argument that receives line by line from the process' stderr. If passed the :err value in the return map will be empty.
:env	override the process env with a map.
:dir	override the process dir with a String or java.io.File.
:throw-ex	If true throw an exception if the exit code is not equal to zero, if false returns the exit code. Defaults to false. It's recommended to use <pre>(with-sh-throw (sh "ls" "-l"))</pre> instead.

:timeout A timeout in milliseconds

You can bind :env, :dir for multiple operations using `with-sh-env` or `with-sh-dir`. `with-sh-throw` is binds *:throw-ex* as *true*.

sh returns a map of

```
:exit => sub-process's exit code
:out  => sub-process's stdout (as Bytebuf or String)
:err  => sub-process's stderr (String via platform default encoding)
```

E.g.:

```
(sh "uname" "-r")
=> {:err "" :out "20.5.0\n" :exit 0}
```

```
(println (sh "ls" "-l"))

(println (sh "ls" "-l" "/tmp"))

(println (sh "sed" "s/[aeiou]/oo/g" :in "hello there\n"))

(println (sh "cat" :in "x\u25bax\n"))

(println (sh "echo" "x\u25bax"))

(println (sh "/bin/sh" "-c" "ls -l"))

(sh "ls" "-l" :out-fn println)

(sh "ls" "-l" :out-fn println :err-fn println)

;; background process
(println (sh "/bin/sh" "-c" "sleep 30 >/dev/null 2>&1 &"))

(println (sh "/bin/sh" "-c" "nohup sleep 30 >/dev/null 2>&1 &"))

;; asynchronously slurping stdout and stderr
(sh "/bin/sh"
  "-c" "for i in {1..5}; do sleep 1; echo \"Hello $i\"; done"
  :out-fn println
  :err-fn println)

;; asynchronously slurping stdout and stderr with a timeout
(sh "/bin/sh"
  "-c" "for i in {1..5}; do sleep 1; echo \"Hello $i\"; done"
  :out-fn println
  :err-fn println
  :timeout 2500)

;; reads 4 single-byte chars
(println (sh "echo" "x\u25bax" :out-enc "ISO-8859-1"))

;; reads binary file into bytes[]
(println (sh "cat" "birds.jpg" :out-enc :bytes))

;; working directory
(println (with-sh-dir "/tmp" (sh "ls" "-l") (sh "pwd")))

(println (sh "pwd" :dir "/tmp"))
```

```
;; throw an exception if the shell's subprocess exit code is not equal to 0
(println (with-sh-throw (sh "ls" "-l")))

(println (sh "ls" "-l" :throw-ex true))

;; windows
(println (sh "cmd" "/c dir 1>&2"))
```

SEE ALSO

[with-sh-throw](#)

Shell commands executed within a with-sh-throw context throw an exception if the spawned shell process returns an exit code other than 0.

[with-sh-dir](#)

Sets the directory for use with sh, see sh for details.

[with-sh-env](#)

Sets the environment for use with sh.

[top](#)

sh/open

```
(sh/open f)
```

Opens a *file* or an *URL* with the associated platform specific application.

Uses the OS commands:

- *MacOS*: `/usr/bin/open f`
- *Windows*: `cmd /C start f`
- *Linux*: `/usr/bin/xdg-open f`

Note: `sh/open` can only be run from a REPL!

```
(sh/open "sample.pdf")
```

```
(sh/open "https://github.com/jlangch/venice")
```

[top](#)

sh/pwd

```
(sh/pwd)
```

Returns the current working directory.

Note:

You can't change the current working directory of the Java VM but if you were to launch another process using (sh & args) you can specify the working directory for the new spawned process.

```
(sh/pwd)
```

SEE ALSO

[sh](#)

Launches a new sub-process.

shell/alive?

```
(alive? pid)
(alive? process-handle)
```

Returns true if the process represented by a PID or a process handle is alive otherwise false.

Requires Java 9+.

```
(shell/alive? 4556)
```

SEE ALSO

[shell/pid](#)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for ...

[shell/processes](#)

Returns a snapshot of all processes visible to the current process. Returns a list of :java.lang.ProcessHandle for the processes.

shell/descendant-processes

```
(descendant-processes pid)
(descendant-processes process-handle)
```

Returns the descendants (:java.lang.ProcessHandle) of a process represented by a PID or a process handle.

Requires Java 9+.

```
(shell/descendant-processes 4556)
```

```
(->> (shell/current-process)
      (shell/descendant-processes)
      (map shell/process-info))
```

SEE ALSO

[shell/process-info](#)

Returns the process info for a process represented by a PID or a process handle.

[shell/pid](#)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for ...

shell/diff

```
(diff file1 file2)
```

Compare two files and print the differences.

```
(diff "/tmp/x.txt" "/tmp/y.txt")
```

[top](#)

shell/kill

```
(kill pid)
(kill process-handle)
```

Requests the process to be killed. Returns true if the process is killed and false if the process stays alive. Returns nil if the process does not exist. Accepts a PID or a process handle (:java.lang.ProcessHandle).

Requires Java 9+.

```
(shell/kill 4556)
```

SEE ALSO

[shell/pid](#)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for ...

[shell/kill-forcibly](#)

Requests the process to be killed forcibly. Returns true if the process is killed and false if the process stays alive. Returns nil ...

[shell/processes](#)

Returns a snapshot of all processes visible to the current process. Returns a list of :java.lang.ProcessHandle for the processes.

[top](#)

shell/kill-forcibly

```
(kill-forcibly pid)
(kill-forcibly process-handle)
```

Requests the process to be killed forcibly. Returns true if the process is killed and false if the process stays alive. Returns nil if the process does not exist. Accepts a PID or a process handle (:java.lang.ProcessHandle).

Requires Java 9+.

```
(shell/kill-forcibly 4556)
```

SEE ALSO

[shell/pid](#)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for ...

[shell/kill](#)

Requests the process to be killed. Returns true if the process is killed and false if the process stays alive. Returns nil if the process ...

[shell/processes](#)

Returns a snapshot of all processes visible to the current process. Returns a list of :java.lang.ProcessHandle for the processes.

[top](#)

shell/open

(open url)

Opens a file or an url with the associated platform specific application.

([shell/open](#) "img.png")

([shell/open](#) "https://www.heise.de/")

SEE ALSO

[shell/open-macos-app](#)

Opens a Mac OSX app.

[top](#)

shell/open-macos-app

(open-macos-app name & args)

Opens a Mac OSX app.

([shell/open-macos-app](#) "Calendar")

([shell/open-macos-app](#) "Maps")

([shell/open-macos-app](#) "TextEdit" "example.txt")

SEE ALSO

[shell/open](#)

Opens a file or an url with the associated platform specific application.

[top](#)

shell/parent-process

(parent-process pid)

(parent-process process-handle)

Returns the parent (`java.lang.ProcessHandle`) of a process represented by a PID or a process handle.

Requires Java 9+.

([shell/parent-process](#) 4556)

(->> ([shell/current-process](#))

([shell/parent-process](#))

([shell/process-info](#)))

SEE ALSO

[shell/process-info](#)

Returns the process info for a process represented by a PID or a process handle.

[shell/pid](#)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for ...

[shell/processes](#)

Returns a snapshot of all processes visible to the current process. Returns a list of :java.lang.ProcessHandle for the processes.

[top](#)

shell/pid

(pid)
(pid process-handle)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for the process represented by the handle.

Requires Java 9+.

([shell/pid](#))

SEE ALSO

[shell/process-handle](#)

Returns the process handle (:java.lang.ProcessHandle) for a PID or nil if there is no process.

[shell/process-info](#)

Returns the process info for a process represented by a PID or a process handle.

[shell/alive?](#)

Returns true if the process represented by a PID or a process handle is alive otherwise false.

[shell/kill](#)

Requests the process to be killed. Returns true if the process is killed and false if the process stays alive. Returns nil if the process ...

[shell/processes](#)

Returns a snapshot of all processes visible to the current process. Returns a list of :java.lang.ProcessHandle for the processes.

[top](#)

shell/process-handle

(process-handle pid)

Returns the process handle (:java.lang.ProcessHandle) for a PID or nil if there is no process.

Requires Java 9+.

([shell/process-handle](#) 4556)

SEE ALSO

[shell/pid](#)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for ...

[shell/alive?](#)

Returns true if the process represented by a PID or a process handle is alive otherwise false.

[shell/process-info](#)

Returns the process info for a process represented by a PID or a process handle.

[shell/kill](#)

Requests the process to be killed. Returns true if the process is killed and false if the process stays alive. Returns nil if the process ...

top

shell/process-handle?

```
(process-handle? p)
```

Returns true if p is a process handle (:java.lang.ProcessHandle).

Requires Java 9+.

top

shell/process-info

```
(process-info pid)
(process-info process-handle)
```

Returns the process info for a process represented by a PID or a process handle.

The process info is a map with the keys:

:pid	the PID
:alive	true if the process is alive else false
:arguments	the list of strings of the arguments of the process
:command	the executable pathname of the process
:command-line	the command line of the process
:start-time	the start time of the process
:total-cpu-millis	the total cputime accumulated of the process
:user	the user of the process.

Requires Java 9+.

```
(shell/process-info 4556)
```

```
;; find the PID of the ArangoDB process
;; like: pgrep -lf ArangoDB3 | cut -d ' ' -f 1
(->> (shell/processes)
      (map shell/process-info)
      (filter #(str/contains? (:command-line %) "ArangoDB3"))
      (map :pid))
```

SEE ALSO

[shell/pid](#)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for ...

[shell/process-handle](#)

Returns the process handle (:java.lang.ProcessHandle) for a PID or nil if there is no process.

top

shell/processes

(processes)

Returns a snapshot of all processes visible to the current process. Returns a list of `java.lang.ProcessHandle` for the processes.

Requires Java 9+.

([shell/processes](#))

```
;; find the PID of the ArangoDB process
;; like: pgrep -lf ArangoDB3 | cut -d ' ' -f 1
(->> (shell/processes)
      (map shell/process-info)
      (filter #(str/contains? (:command-line %) "ArangoDB3"))
      (map :pid))
```

SEE ALSO

[shell/processes-info](#)

Returns a snapshot of all processes visible to the current process. Returns a list of process infos for the processes.

top

shell/processes-info

(processes-info)

Returns a snapshot of all processes visible to the current process. Returns a list of process infos for the processes.

The process info is a map with the keys:

:pid	the PID
:alive	true if the process is alive else false
:arguments	the list of strings of the arguments of the process
:command	the executable pathname of the process
:command-line	the command line of the process
:start-time	the start time of the process
:total-cpu-millis	the total cputime accumulated of the process
:user	the user of the process.

Requires Java 9+.

([shell/processes-info](#))

```
;; find the PID of the ArangoDB process
;; like: pgrep -lf ArangoDB3 | cut -d ' ' -f 1
(->> (shell/processes-info)
      (filter #(str/contains? (:command-line %) "ArangoDB3"))
      (map :pid))
```

SEE ALSO

[shell/processes](#)

Returns a snapshot of all processes visible to the current process. Returns a list of `java.lang.ProcessHandle` for the processes.

top

shell/wait-for-process-exit

```
(wait-for-process-exit pid timeout)
(wait-for-process-exit process-handle timeout)
```

Waits until the process with the pid exits. Waits max timeout seconds. Returns nil if the process exits before reaching the timeout, else the pid is returned. Accepts a PID or a process handle (:java.lang.ProcessHandle).

Requires Java 9+.

```
(shell/wait-for-process-exit 12345 20)
```

SEE ALSO

[shell/pid](#)

Without argument returns the PID (type long) of this process. With a process-handle (:java.lang.ProcessHandle) returns the PID for ...

[shell/kill](#)

Requests the process to be killed. Returns true if the process is killed and false if the process stays alive. Returns nil if the process ...

[shell/processes](#)

Returns a snapshot of all processes visible to the current process. Returns a list of :java.lang.ProcessHandle for the processes.

[top](#)

shuffle

```
(shuffle coll)
```

Returns a collection of the items in coll in random order.

```
(shuffle '(1 2 3 4 5 6))
=> (2 6 3 1 5 4)
```

```
(shuffle [1 2 3 4 5 6])
=> [3 4 1 5 2 6]
```

```
(shuffle "abcdef")
=> (#\f #\e #\b #\a #\c #\d)
```

[top](#)

shutdown-agents

```
(shutdown-agents)
```

Initiates a shutdown of the thread pools that back the agent system. Running actions will complete, but no new actions will be accepted

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (shutdown-agents))
```

SEE ALSO

agent

Creates and returns an agent with an initial value of state and zero or more options.

top

shutdown-agents?

(shutdown-agents?)

Returns true if the thread-pool that backs the agents is shut down

```
(do
  (def x1 (agent 100))
  (def x2 (agent 100))
  (shutdown-agents)
  (sleep 300)
  (shutdown-agents?))
```

SEE ALSO

agent

Creates and returns an agent with an initial value of state and zero or more options.

top

shutdown-hook

(shutdown-hook f)

Registers the function f as a JVM shutdown hook.

Shutdown hooks can be tested in a REPL:

- start a REPL
- run (shutdown-hook (fn [] (println "SHUTDOWN") (sleep 3000)))
- exit the REPL with !exit

The sandbox is active within the shutdown hook:

- start a REPL
- run !sandbox customized
- run !sandbox add-rule blacklist:venice:func:+
- run (shutdown-hook (fn [] (try (+ 1 2) (catch :SecurityException ex (println ex) (sleep 3000)))))
- exit the REPL with !exit

```
(shutdown-hook (fn [] (println "shutdown")))
```

top

sleep

(sleep n)

```
(sleep n time-unit)
```

Sleep for the time n. The default time unit is milliseconds.

Time unit is one of :milliseconds, :seconds, :minutes, :hours, or :days or their abbreviations :msec, :ms, :sec, :s, :min, :hr, :h, :d.

```
(sleep 30)
```

```
=> nil
```

```
(sleep 30 :milliseconds)
```

```
=> nil
```

```
(sleep 30 :msec)
```

```
=> nil
```

```
(sleep 5 :seconds)
```

```
=> nil
```

```
(sleep 5 :sec)
```

```
=> nil
```

[top](#)

some

```
(some pred coll)
```

Returns the first logical true value of (pred x) for any x in coll, else nil.

Stops processing the collection if the first value is found that meets the predicate.

```
(some even? '(1 2 3 4))
```

```
=> true
```

```
(some even? '(1 3 5 7))
```

```
=> nil
```

```
(some #{5} [1 2 3 4 5])
```

```
=> 5
```

```
(some #(<= 5 %) [1 2 3 4 5])
```

```
=> true
```

```
(some #(if (even? %) %) [1 2 3 4])
```

```
=> 2
```

[top](#)

some->

```
(some-> expr & forms)
```

When expr is not nil, threads it into the first form (via `->`), and when that result is not nil, through the next etc.

```
(some-> {:y 3 :x 5}
      :y
      (- 2))
=> 1
```

```
(some-> {:y 3 :x 5}
      :z
      (- 2))
=> nil
```

SEE ALSO

[some->>](#)

When expr is not nil, threads it into the first form (via ->), and when that result is not nil, through the next etc.

[top](#)

some->>

```
(some->> expr & forms)
```

When expr is not nil, threads it into the first form (via ->>), and when that result is not nil, through the next etc.

```
(some->> {:y 3 :x 5}
      :y
      (- 2))
=> -1
```

```
(some->> {:y 3 :x 5}
      :z
      (- 2))
=> nil
```

SEE ALSO

[some->](#)

When expr is not nil, threads it into the first form (via ->), and when that result is not nil, through the next etc.

[top](#)

some?

```
(some? x)
```

Returns true if x is not nil, false otherwise

```
(some? nil)
=> false
```

```
(some? 0)
=> true
```

```
(some? 4.0)
=> true
```

```
(some? false)
=> true
```

```
(some? [])
=> true
```

```
(some? {})
=> true
```

SEE ALSO

[nil?](#)

Returns true if x is nil, false otherwise

[top](#)

sort

```
(sort coll)
(sort comparefn coll)
```

Returns a sorted list of the items in coll. If no compare function comparefn is supplied, uses the natural compare. The compare function takes two arguments and returns -1, 0, or 1

```
(sort [3 2 5 4 1 6])
=> [1 2 3 4 5 6]
```

```
(sort compare [3 2 5 4 1 6])
=> [1 2 3 4 5 6]
```

```
; reversed
(sort (comp - compare) [3 2 5 4 1 6])
=> [6 5 4 3 2 1]
```

```
(sort {:c 3 :a 1 :b 2})
=> ([:a 1] [:b 2] [:c 3])
```

SEE ALSO

[sort-by](#)

Returns a sorted sequence of the items in coll, where the sort order is determined by comparing (keyfn item). If no comparator is supplied, ...

[top](#)

sort-by

```
(sort-by keyfn coll)
(sort-by keyfn compfn coll)
```

Returns a sorted sequence of the items in coll, where the sort order is determined by comparing (keyfn item). If no comparator is supplied, uses compare.

To sort by multiple values use `juxt`, see the examples below.


```

(sort-by :id [{:id 2 :name "Smith"} {:id 1 :name "Jones"} ])
=> [{:name "Jones" :id 1} {:name "Smith" :id 2}]

(sort-by count ["aaa" "bb" "c"])
=> ["c" "bb" "aaa"]

; reversed
(sort-by count (comp - compare) ["aaa" "bb" "c"])
=> ["aaa" "bb" "c"]

(sort-by first [[1 2] [3 4] [2 3]])
=> [[1 2] [2 3] [3 4]]

; sort tuples by first value, and where first value is equal,
; sort by second value
(sort-by (juxt first second) [[3 2] [1 3] [3 1] [1 2]])
=> [[1 2] [1 3] [3 1] [3 2]]

; reversed
(sort-by first (comp - compare) [[1 2] [3 4] [2 3]])
=> [[3 4] [2 3] [1 2]]

(sort-by :rank [{:rank 2} {:rank 3} {:rank 1}])
=> [{:rank 1} {:rank 2} {:rank 3}]

; reversed
(sort-by :rank (comp - compare) [{:rank 2} {:rank 3} {:rank 1}])
=> [{:rank 3} {:rank 2} {:rank 1}]

; sort entries in a map by value
(sort-by val {:foo 7, :bar 3, :baz 5})
=> ([:bar 3] [:baz 5] [:foo 7])

; sort by :foo, and where :foo is equal, sort by :bar
(do
  (def x [ {:foo 2 :bar 11}
            {:foo 1 :bar 99}
            {:foo 2 :bar 55}
            {:foo 1 :bar 77} ])
    (sort-by (juxt :foo :bar) x))
=> [{:foo 1 :bar 77} {:foo 1 :bar 99} {:foo 2 :bar 11} {:foo 2 :bar 55}]

; sort by a given key order
(do
  (def x [ {:foo 2 :bar 11}
            {:foo 1 :bar 99}
            {:foo 2 :bar 55}
            {:foo 1 :bar 77} ])
    (def order [55 77 99 11])
    (sort-by #((into {}) (map-indexed (fn [i e] [e i]) order)) (:bar %))
      x))
=> [{:foo 2 :bar 55} {:foo 1 :bar 77} {:foo 1 :bar 99} {:foo 2 :bar 11}]

```

SEE ALSO

[sort](#)

Returns a sorted list of the items in coll. If no compare function comparefn is supplied, uses the natural compare. The compare function ...

sorted

```
(sorted cmp coll)
```

Returns a sorted collection using the compare function `cmp`. The compare function takes two arguments and returns -1, 0, or 1. Returns a stateful transducer when no collection is provided.

```
(sorted compare [4 2 1 5 6 3])  
=> [1 2 3 4 5 6]
```

```
(sorted (comp (partial * -1) compare) [4 2 1 5 6 3])  
=> [6 5 4 3 2 1]
```

[top](#)

sorted-map

```
(sorted-map & keyvals)  
(sorted-map map)
```

Creates a new sorted map containing the items.

```
(sorted-map :a 1 :b 2)  
=> {:a 1 :b 2}
```

```
(sorted-map (hash-map :a 1 :b 2))  
=> {:a 1 :b 2}
```

[top](#)

sorted-map?

```
(sorted-map? obj)
```

Returns true if `obj` is a sorted map

```
(sorted-map? (sorted-map :a 1 :b 2))  
=> true
```

[top](#)

sorted-set

```
(sorted-set & items)
```

Creates a new sorted-set containing the items.

```
(sorted-set)  
=> #{} 
```

```
(sorted-set nil)
=> #{nil}

(sorted-set 1)
=> #{1}

(sorted-set 6 2 4)
=> #{2 4 6}

(str (sorted-set [2 3] [1 2]))
=> "#[[1 2] [2 3]]"
```

[top](#)

sorted-set?

```
(sorted-set? obj)
```

Returns true if obj is a sorted-set

```
(sorted-set? (sorted-set 1))
=> true
```

[top](#)

split-at

```
(split-at n coll)
```

Returns a vector of [(take n coll) (drop n coll)]

```
(split-at 2 [1 2 3 4 5])
=> [(1 2) (3 4 5)]
```

```
(split-at 3 [1 2])
=> [(1 2) ()]
```

[top](#)

split-with

```
(split-with pred coll)
```

Splits the collection at the first false/nil predicate result in a vector with two lists

```
(split-with odd? [1 3 5 6 7 9])
=> [(1 3 5) (6 7 9)]
```

```
(split-with odd? [1 3 5])
=> [(1 3 5) ()]
```

```
(split-with odd? [2 4 6])  
=> [()] (2 4 6)]
```

[top](#)

sqrt

(sqrt x)

Square root of x

```
(sqrt 10)  
=> 3.1622776601683795
```

```
(sqrt 10I)  
=> 3.1622776601683795
```

```
(sqrt 10.23)  
=> 3.1984371183438953
```

```
(sqrt 10.23M)  
=> 3.198437118343895324557024650857783854007720947265625M
```

```
(sqrt 10N)  
=> 3.162277660168379522787063251598738133907318115234375M
```

SEE ALSO

[square](#)
Square of x

[top](#)

square

(square x)

Square of x

```
(square 10)  
=> 100
```

```
(square 10I)  
=> 100I
```

```
(square 10.23)  
=> 104.6529
```

```
(square 10.23M)  
=> 104.6529M
```

SEE ALSO

[sqrt](#)

stack

(stack)

Creates a new mutable threadsafe stack.

```
(let [s (stack)]
  (push! s 1)
  (push! s 2)
  (push! s 3))
=> (3 2 1)
```

SEE ALSO

[peek](#)

For a list, same as first, for a vector, same as last, for a stack the top element (or nil if the stack is empty), for a queue the ...

[pop!](#)

Pops an item from a stack.

[push!](#)

Pushes an item to a stack.

[empty](#)

Returns an empty collection of the same category as coll, or nil if coll is nil. If the collection is mutable clears the collection ...

[empty?](#)

Returns true if x is empty. Accepts strings, collections and bytebufs.

[count](#)

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

[into!](#)

Adds all of the items of 'from' conjoined to the mutable 'to' collection

[conj!](#)

Returns a new mutable collection with the x, xs 'added'. (conj! nil item) returns (item) and (conj! item) returns item.

[stack?](#)

Returns true if coll is a stack

stack?

(stack? coll)

Returns true if coll is a stack

```
(stack? (stack))
=> true
```

stacktrace

(stacktrace ex)

Returns the stacktrace of a java exception

```
(println (stacktrace (. :VncException :new (str "test"))))
```

[top](#)

str

(str & xs)

With no args, returns the empty string. With one arg x, returns x.toString(). (str nil) returns the empty string. With more than one arg, returns the concatenation of the str values of the args.

```
(str)  
=> ""
```

```
(str 1 2 3)  
=> "123"
```

```
(str 1I)  
=> "1"
```

```
(str 3.1415927M)  
=> "3.1415927"
```

```
(str +)  
=> "+"
```

```
(str [1 2 3])  
=> "[1 2 3]"
```

```
(str "total " 100)  
=> "total 100"
```

```
(str #\h #\i)  
=> "hi"
```

SEE ALSO

[pr-str](#)

With no args, returns the empty string. With one arg x, returns x.toString(). With more than one arg, returns the concatenation of ...

[top](#)

str/align

(str/align width align overflow text)

Aligns a text within a string of width characters.

align: :left, :center, :right

overflow: :newline :clip-left, :clip-right, :ellipsis-left, :ellipsis-right

```
(str/align 6 :left :clip-right "abc")  
=> "abc   "
```

```
(str/align 6 :center :clip-right "abc")  
=> "  abc  "
```

```
(str/align 6 :right :clip-right "abc")  
=> "    abc"
```

```
(str/align 6 :left :clip-left "abcdefgh")  
=> "cdefgh"
```

```
(str/align 6 :left :ellipsis-left "abcdefgh")  
=> "...defgh"
```

```
(str/align 6 :left :ellipsis-right "abcdefgh")  
=> "abcde..."
```

SEE ALSO

[str/trim-to-nil](#)

Trims leading and trailing whitespaces from s. Returns nil if the resulting string is empty

[str/trim-left](#)

Trims leading whitespaces from s.

[str/trim-right](#)

Trims trailing whitespaces from s.

[top](#)

str/blank?

```
(str/blank? s)
```

True if s is nil, empty, or contains only whitespace.

```
(str/blank? nil)  
=> true
```

```
(str/blank? "")  
=> true
```

```
(str/blank? " ")  
=> true
```

```
(str/blank? "abc")  
=> false
```

SEE ALSO

[str/not-blank?](#)

True if s contains at least one non whitespace char.

`empty?`

Returns true if x is empty. Accepts strings, collections and bytebufs.

`not-empty?`

Returns true if x is not empty. Accepts strings, collections and bytebufs.

`nil?`

Returns true if x is nil, false otherwise

[top](#)

`str/butlast`

```
(str/butlast s)
```

Returns a possibly empty string of the characters without the last.

```
(str/butlast "abcdef")  
=> "abcde"
```

[top](#)

`str/butnlast`

```
(str/butnlast s n)
```

Returns a possibly empty string of the characters without the n last characters.

```
(str/butnlast "abcdef" 3)  
=> "abc"
```

[top](#)

`str/bytebuf-to-hex`

```
(str/bytebuf-to-hex data)  
(str/bytebuf-to-hex data :upper)
```

Converts byte data to a hex string using the hexadecimal digits: `0123456789abcdef` .
If the `:upper` options is passed the hex digits `0123456789ABCDEF` are used.

```
(str/bytebuf-to-hex (bytebuf [0 1 2 3 4 5 6]))  
=> "00010203040506"
```

```
(str/bytebuf-to-hex (bytebuf [202 254]) :upper)  
=> "CAFE"
```

[top](#)

`str/char?`


```
(str/char? s)
```

Returns true if s is a char or a single char string.

```
(str/char? "x")  
=> true
```

```
(str/char? #\x)  
=> true
```

[top](#)

str/chars

```
(str/chars s)
```

Converts a string to a char list.

```
(str/chars "abcdef")  
=> (#\a #\b #\c #\d #\e #\f)
```

```
(str/join (str/chars "abcdef"))  
=> "abcdef"
```

[top](#)

str/contains?

```
(str/contains? s substr)
```

True if s contains with substr.

```
(str/contains? "abc" "ab")  
=> true
```

```
(str/contains? "abc" #\b)  
=> true
```

[top](#)

str/cr-lf

```
(str/cr-lf s mode)
```

Convert a text to use LF or CR-LF.

```
(str/cr-lf "line1  
line2  
line3" :cr-lf)
```

```
(str/cr-lf "line1
line2
line3" :lf)
```

[top](#)

str/decode-base64

```
(str/decode-base64 s)
```

Base64 decode.

```
(str/decode-base64 (str/encode-base64 (bytebuf [0 1 2 3 4 5 6])))
=> [0 1 2 3 4 5 6]
```

[top](#)

str/decode-url

```
(str/decode-url s)
```

URL decode.

```
(str/decode-url "The+string+%C3%BC%40foo-bar")
=> "The string ü@foo-bar"
```

[top](#)

str/digit?

```
(str/digit? s)
```

True if s is a char and the char is a digit.

Defined by Java Character.isDigit(ch).

```
(str/digit? #\8)
=> true
```

```
(str/digit? "8")
=> false
```

SEE ALSO

[str/letter?](#)

True if s is a char and the char is a letter.

[str/hexdigit?](#)

True if s is a char and the char is a hex digit.

[top](#)

str/double-quote

```
(str/double-quote str)
```

Double quotes a string.

```
(str/double-quote "abc")  
=> "\"abc\""
```

```
(str/double-quote "")  
=> "\"\""
```

[top](#)

str/double-quoted?

```
(str/double-quoted? str)
```

Returns true if the string is double quoted.

```
(str/double-quoted? "\"abc\"")  
=> true
```

[top](#)

str/double-unquote

```
(str/double-unquote str)
```

Unquotes a double quoted string.

```
(str/double-unquote "\"abc\"")  
=> "abc"
```

```
(str/double-unquote "\"\"")  
=> ""
```

```
(str/double-unquote nil)  
=> nil
```

[top](#)

str/encode-base64

```
(str/encode-base64 data)
```

Base64 encode.

```
(str/encode-base64 (bytebuf [0 1 2 3 4 5 6]))
=> "AAECAwQFBg=="
```

[top](#)

str/encode-url

```
(str/encode-url s)
```

URL encode.

```
(str/encode-url "The string ü@foo-bar")
=> "The+string+%C3%BC%40foo-bar"
```

[top](#)

str/ends-with?

```
(str/ends-with? s substr)
```

True if s ends with substr.

```
(str/ends-with? "abc" "bc")
=> true
```

[top](#)

str/equals-ignore-case?

```
(str/equals-ignore-case? s1 s2)
```

Compares two strings ignoring case. True if both are equal.

```
(str/equals-ignore-case? "abc" "abC")
=> true
```

[top](#)

str/escape-html

```
(str/escape-html s)
```

HTML escape. Escapes `&`, `<`, `>`, `"`, `'`, and the non blocking space `U+00A0`

```
(str/escape-html "1 2 3 & < > \" ' \u00A0")
=> "1 2 3 &amp; &lt; &gt; &quot; &apos; "
```

[top](#)

str/escape-xml

```
(str/escape-xml s)
```

XML escape. Escapes `&`, `<`, `>`, `"`, `'`

```
(str/escape-xml "1 2 3 & < > \" '\")
=> "1 2 3 &amp; &lt; &gt; &quot; &apos;"
```

[top](#)

str/expand

```
(str/expand s len fill mode*)
```

Expands a string to the max length `len`. Fills up with the `fillstring` if the string needs to be expanded. The fill string is added to the start or end of the string depending on the mode `:start`, `:end`. The mode defaults to `:end`

```
(str/expand "abcdefghij" 8 ".")
=> "abcdefghij"

(str/expand "abcdefghij" 20 ".")
=> "abcdefghij....."

(str/expand "abcdefghij" 20 "." :start)
=> ".....abcdefghij"

(str/expand "abcdefghij" 20 "." :end)
=> "abcdefghij....."

(str/expand "abcdefghij" 30 "1234" :start)
=> "123412341234123412341234abcdefghij"

(str/expand "abcdefghij" 30 "1234" :end)
=> "abcdefghij12341234123412341234"
```

[top](#)

str/format

```
(str/format format args*)
(str/format locale format args*)
```

Returns a formatted string using the specified format string and arguments.
Venice uses the Java format syntax.

JavaDoc: [Format Syntax](#)

```
(str/format "value: %.4f" 1.45)
=> "value: 1.4500"
```

```
(str/format (. :java.util.Locale :new "de" "DE") "value: %.4f" 1.45)
=> "value: 1,4500"

(str/format (. :java.util.Locale :GERMANY) "value: %.4f" 1.45)
=> "value: 1,4500"

(str/format (. :java.util.Locale :new "de" "CH") "value: %,d" 2345000)
=> "value: 2'345'000"

(str/format [ "de" ] "value: %,2f" 100000.45)
=> "value: 100.000,45"

(str/format [ "de" "DE" ] "value: %,2f" 100000.45)
=> "value: 100.000,45"

(str/format [ "de" "CH" ] "value: %,2f" 100000.45)
=> "value: 100'000.45"

(str/format [ "en" "US" ] "value: %,2f" 100000.45)
=> "value: 100,000.45"

(str/format [ "de" "DE" ] "value: %,d" 2345000)
=> "value: 2.345.000"
```

[top](#)

str/format-bytebuf

(str/format-bytebuf data delimiter & options)

Formats a bytearray.

Options

:prefix0x prefix with 0x

```
(str/format-bytebuf (bytebuf [0 34 67 -30 -1]) nil)
=> "002243E2FF"

(str/format-bytebuf (bytebuf [0 34 67 -30 -1]) "")
=> "002243E2FF"

(str/format-bytebuf (bytebuf [0 34 67 -30 -1]) ", ")
=> "00, 22, 43, E2, FF"

(str/format-bytebuf (bytebuf [0 34 67 -30 -1]) ", " :prefix0x)
=> "0x00, 0x22, 0x43, 0xE2, 0xFF"
```

[top](#)

str/hex-to-bytebuf

(str/hex-to-bytebuf hex)

Converts a hex string to a bytebuf

```
(str/hex-to-bytebuf "005E4AFF")  
=> [0 94 74 255]
```

```
(str/hex-to-bytebuf "005e4aff")  
=> [0 94 74 255]
```

[top](#)

str/hexdigit?

```
(str/hexdigit? s)
```

True if s is a char and the char is a hex digit.

```
(str/hexdigit? #\8)  
=> true
```

```
(str/hexdigit? #\a)  
=> true
```

```
(str/hexdigit? #\A)  
=> true
```

```
(str/hexdigit? #\Y)  
=> false
```

[top](#)

str/index-of

```
(str/index-of s value)  
(str/index-of s value from-index)
```

Return index of value (string or char) in s, optionally searching forward from from-index. Return nil if value not found.

```
(str/index-of "abcdefabc" "ab")  
=> 0
```

SEE ALSO

[str/index-of-char](#)

Return index of the first char of chars (string or sequence of chars) in s, optionally searching forward from from-index. Return nil ...

[str/index-of-not-char](#)

Return index of the first char not of chars (string or sequence of chars) in s, optionally searching forward from from-index. Return ...

[str/last-index-of](#)

Return last index of value (string or char) in s, optionally searching backward from from-index. Return nil if value not found.

[top](#)

str/index-of-char

```
(str/index-of-char s chars)
(str/index-of-char s chars from-index)
```

Return index of the first char of chars (string or sequence of chars) in s, optionally searching forward from from-index. Return nil if value not found.

```
(str/index-of-char "-+-123+-123" "012")
=> 3
```

```
(str/index-of-char "-+-123+-123" [#\0 #\1 #\2])
=> 3
```

```
(str/index-of-char "-+-123+-123" "012" 7)
=> 9
```

SEE ALSO

[str/index-of-not-char](#)

Return index of the first char not of chars (string or sequence of chars) in s, optionally searching forward from from-index. Return ...

[str/index-of](#)

Return index of value (string or char) in s, optionally searching forward from from-index. Return nil if value not found.

[str/last-index-of](#)

Return last index of value (string or char) in s, optionally searching backward from from-index. Return nil if value not found.

[top](#)

str/index-of-not-char

```
(str/index-of-not-char s chars)
(str/index-of-not-char s chars from-index)
```

Return index of the first char not of chars (string or sequence of chars) in s, optionally searching forward from from-index. Return nil if value not found.

```
(str/index-of-not-char "-+-123+-123" "-+")
=> 3
```

```
(str/index-of-not-char "-+-123+-123" [#\ - #\+])
=> 3
```

```
(str/index-of-not-char "-+-123+-123" "-+" 7)
=> 9
```

SEE ALSO

[str/index-of-char](#)

Return index of the first char of chars (string or sequence of chars) in s, optionally searching forward from from-index. Return nil ...

[str/index-of](#)

Return index of value (string or char) in s, optionally searching forward from from-index. Return nil if value not found.

[str/last-index-of](#)

Return last index of value (string or char) in s, optionally searching backward from from-index. Return nil if value not found.

str/join

```
(str/join coll)
(str/join separator coll)
```

Joins all elements in coll separated by an optional separator.

```
(str/join [1 2 3])
=> "123"

(str/join "-" [1 2 3])
=> "1-2-3"

(str/join "-" [(char "a") 1 "xyz" 2.56M])
=> "a-1-xyz-2.56"

(str/join #\- [1 2 3])
=> "1-2-3"
```

str/last-index-of

```
(str/last-index-of s value)
(str/last-index-of s value from-index)
```

Return last index of value (string or char) in s, optionally searching backward from from-index. Return nil if value not found.

```
(str/last-index-of "abcdefabc" "ab")
=> 6

(str/last-index-of "abcdefabc" "de" 6)
=> 3
```

SEE ALSO

[str/index-of](#)

Return index of value (string or char) in s, optionally searching forward from from-index. Return nil if value not found.

[str/index-of-char](#)

Return index of the first char of chars (string or sequence of chars) in s, optionally searching forward from from-index. Return nil ...

[str/index-of-not-char](#)

Return index of the first char not of chars (string or sequence of chars) in s, optionally searching forward from from-index. Return ...

str/letter?

```
(str/letter? s)
```

True if *s* is a char and the char is a letter.

Defined by Java `Character.isLetter(ch)`.

```
(str/letter? #\x)
=> true
```

[top](#)

str/levenshtein

```
(str/levenshtein s1 s2)
```

Returns the *Levenshtein* distance of two strings.

The *Damerau-Levenshtein* algorithm is an extension to the *Levenshtein* algorithm which solves the edit distance problem between a source string and a target string with the following operations:

- Character Insertion
- Character Deletion
- Character Replacement
- Adjacent Character Swap

Note that the adjacent character swap operation is an edit that may be applied when two adjacent characters in the source string match two adjacent characters in the target string, but in reverse order, rather than a general allowance for adjacent character swaps.

This implementation allows the client to specify the costs of the various edit operations with the restriction that the cost of two swap operations must not be less than the cost of a delete operation followed by an insert operation. This restriction is required to preclude two swaps involving the same character being required for optimality which, in turn, enables a fast dynamic programming solution.

The cost of the *Damerau-Levenshtein* algorithm is $O(n*m)$ where *n* is the length of the source string and *m* is the length of the target string. This implementation consumes $O(n*m)$ space.

```
(str/levenshtein "Tier" "Tor")
=> 2
```

```
(str/levenshtein "Tier" "tor")
=> 3
```

[top](#)

str/linefeed?

```
(str/linefeed? s)
```

True if *s* is a char and the char is a linefeed.

```
(str/linefeed? #\newline)
=> true
```

```
(str/linefeed? (first "
"))
=> true
```

[top](#)

str/lorem-ipsum

```
(str/lorem-ipsum & options)
```

Creates an arbitrary length Lorem Ipsum text.

Options:

:chars n returns n characters (limited to 1000000)

:paragraphs n returns n paragraphs (limited to 100)

```
(str/lorem-ipsum :chars 250)
```

```
=> "Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent ac iaculis turpis. Duis dictum id sem et
consectetur. Nullam lobortis, libero non consequat aliquet, lectus diam fringilla velit, finibus eleifend ipsum
urna at lacus. Phasellus sit am"
```

```
(str/lorem-ipsum :paragraphs 1)
```

```
=> "Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent ac iaculis turpis. Duis dictum id sem et
consectetur. Nullam lobortis, libero non consequat aliquet, lectus diam fringilla velit, finibus eleifend ipsum
urna at lacus. Phasellus sit amet nisl fringilla, cursus est in, mollis lacus. Proin dignissim rhoncus dolor.
Cras tellus odio, elementum sed erat sit amet, euismod tincidunt nisl. In hac habitasse platea dictumst. Duis
aliquam sollicitudin tempor. Sed gravida tincidunt felis at fringilla. Morbi tempor enim at commodo vulputate.
Aenean et ultrices lorem, placerat pretium augue. In hac habitasse platea dictumst. Cras fringilla ligula quis
interdum hendrerit. Etiam at massa tempor, facilisis lacus placerat, congue erat."
```

[top](#)

str/lower-case

```
(str/lower-case s)
```

```
(str/lower-case locale s)
```

Converts s to lowercase.

Since case mappings are not always 1:1 character mappings when a locale is given, the resulting string may be a different length than the original!

```
(str/lower-case "aBcDeF")
```

```
=> "abcdef"
```

```
(str/lower-case #\A)
```

```
=> #\a
```

```
(str/lower-case (. :java.util.Locale :new "de" "DE") "aBcDeF")
```

```
=> "abcdef"
```

```
(str/lower-case (. :java.util.Locale :GERMANY) "aBcDeF")
```

```
=> "abcdef"
```

```
(str/lower-case (. :java.util.Locale :new "de" "CH") "aBcDeF")
```

```
=> "abcdef"
```

```
(str/lower-case [ "de"] "aBcDeF")
```

```
=> "abcdef"
```

```
(str/lower-case [ "de" "DE"] "aBcDeF")  
=> "abcdef"
```

```
(str/lower-case [ "de" "DE"] "aBcDeF")  
=> "abcdef"
```

SEE ALSO

[str/upper-case](#)

Converts s to uppercase.

[top](#)

str/lower-case?

```
(str/lower-case? s)
```

True if s is a char and the char is a lower case char.

Defined by Java Character.isLowerCase(ch).

```
(str/lower-case? #\x)  
=> true
```

```
(str/lower-case? #\X)  
=> false
```

```
(str/lower-case? #\8)  
=> false
```

[top](#)

str/nfirst

```
(str/nfirst s n)
```

Returns a string of the n first characters of s.

```
(str/nfirst "abcdef" 2)  
=> "ab"
```

```
(str/nfirst "abcdef" 10)  
=> "abcdef"
```

```
(str/nfirst "abcdef" 0)  
=> ""
```

[top](#)

str/nlast

```
(str/nlast s n)
```

Returns a string of the *n* last characters of *s*.

```
(str/nlast "abcdef" 2)
=> "ef"
```

```
(str/nlast "abcdef" 10)
=> "abcdef"
```

```
(str/nlast "abcdef" 0)
=> ""
```

[top](#)

str/normalize-utf

```
(str/normalize-utf text form)
```

Normalizes an UTF string.

On MacOS umlauts like ä are just encoded as 'a' plus the combining dieresis character. Therefore an 'ä' (\u00FC) and an 'ä' (a + \u0308) from a MacOS filename are different!

This function normalizes UTF strings to simplify processing.

The *form* argument is one of:

- :NFD Canonical decomposition
- :NFC Canonical decomposition, followed by canonical composition
- :NFKD Compatibility decomposition
- :NFKC Compatibility decomposition, followed by canonical composition

```
(load-module :hexdump ['hexdump :as 'h])
```

```
;; Even though printed the same these two strings are NOT equal
;; 1: "ü"           prints to "ü"
;; 2: "u\u0308"     prints to "ü"
```

«If it looks like a duck and quacks like a duck, then it probably is a duck» is definitely **WRONG** here!

```
;; ü represented as u with combining dieresis char: \u0308
(println "u\u0308")
;; => u      (actually prints as ü on a terminal)
```

```
;; ü: \u00FC
(println "\u00FC")
;; => ü
```

```
;; u with combining dieresis character
(h/dump (bytebuf-from-string "u\u0308"))
;; 00000000: 75cc 88                                u..
```

```
;; ü
(h/dump (bytebuf-from-string "ü"))
;; 00000000: c3bc                                ..
```

```
;; ü: \u00FC
(h/dump (bytebuf-from-string "\u00FC"))
;; 00000000: c3bc                                ..
```

```
;; u with combined diaeresis character normalized to get a standard ü
(h/dump (bytebuf-from-string (str/normalize-utf "u\u0308" :NFC)))
;; 00000000: c3bc ..

;; the reverse (decomposition)
(h/dump (bytebuf-from-string (str/normalize-utf "\u00FC" :NFD)))
;; 00000000: 75cc 88 u..
```

SEE ALSO

[io/file-normalize-utf](#)

Normalizes the UTF string of a file path.

[top](#)

str/not-blank?

```
(str/not-blank? s)
```

True if s contains at least one non whitespace char.

```
(str/not-blank? "abc")
=> true
```

```
(str/not-blank? " a ")
=> true
```

```
(str/not-blank? nil)
=> false
```

```
(str/not-blank? "")
=> false
```

```
(str/not-blank? " ")
=> false
```

SEE ALSO

[str/blank?](#)

True if s is nil, empty, or contains only whitespace.

[empty?](#)

Returns true if x is empty. Accepts strings, collections and bytebufs.

[not-empty?](#)

Returns true if x is not empty. Accepts strings, collections and bytebufs.

[nil?](#)

Returns true if x is nil, false otherwise

[top](#)

str/nrest

```
(str/nrest s n)
```

Returns a possibly empty string of the characters after the n first characters.

```
(str/nrest "abcdef" 3)
=> "def"
```

[top](#)

str/pos

```
(str/pos s pos)
```

Returns the 0 based row/column position within a string based on absolute character position. Returns a map with the keys 'row' and 'col'.

Note: CR & LF count together as one each regarding the absolute position.

```
(str/pos "abcdefghij" 4)
=> {:col 4 :row 0}
```

```
(str/pos "ab
cdefghij" 6)
=> {:col 3 :row 1}
```

[top](#)

str/quote

```
(str/quote str q)
(str/quote str start end)
```

Quotes a string.

```
(str/quote "abc" "-")
=> "-abc-"
```

```
(str/quote "abc" "<" ">")
=> "<abc>"
```

[top](#)

str/quoted?

```
(str/quoted? str q)
(str/quoted? str start end)
```

Returns true if the string is quoted.

```
(str/quoted? "-abc-" "-")
=> true
```

```
(str/quoted? "<abc>" "<" ">")
=> true
```

str/repeat

```
(str/repeat s n)
(str/repeat s n sep)
```

Repeats s n times with an optional separator.

```
(str/repeat "abc" 0)
=> ""
```

```
(str/repeat "abc" 3)
=> "abcbcbcb"
```

```
(str/repeat "abc" 3 "-")
=> "abc-abc-abc"
```

```
(str/repeat #\* 0)
=> ""
```

```
(str/repeat #\* 3)
=> "***"
```

```
(str/repeat #\* 3 #\-)
=> "*-*-*"
```

str/replace-all

```
(str/replace-all s search replacement)
```

Replaces the all occurrences of search in s. The search arg may be a string or a regex pattern

```
(str/replace-all "abcdefabc" "ab" "__")
=> "__cdef__c"
```

```
(str/replace-all "a0b01c012d" (regex/pattern "[0-9]+") "_")
=> "a_b_c_d"
```

```
(str/replace-all "a0b01c012d" #"[0-9]+" "_")
=> "a_b_c_d"
```

SEE ALSO

[str/replace-first](#)

Replaces the first occurrence of search in s. The search arg may be a string or a regex pattern. If the search arg is of type string ...

[str/replace-last](#)

Replaces the last occurrence of search in s.

str/replace-first

```
(str/replace-first s search replacement & options)
```

Replaces the first occurrence of search in s. The search arg may be a string or a regex pattern. If the search arg is of type string the options :ignore-case and :nfirst are supported.

Options:

:ignore-case b if true ignores case, defaults to false

:nfirst n e.g :nfirst 2, defaults to 1

```
(str/replace-first "ab-cd-ef-ab-cd" "ab" "XYZ")
```

```
=> "XYZ-cd-ef-ab-cd"
```

```
(str/replace-first "AB-CD-EF-AB-CD" "ab" "XYZ" :ignore-case true)
```

```
=> "XYZ-CD-EF-AB-CD"
```

```
(str/replace-first "ab-ab-cd-ab-ef-ab-cd" "ab" "XYZ" :nfirst 3)
```

```
=> "XYZ-XYZ-cd-XYZ-ef-ab-cd"
```

```
(str/replace-first "a0b01c012d" (regex/pattern "[0-9]+") "_")
```

```
=> "a_b01c012d"
```

```
(str/replace-first "a0b01c012d" #"[0-9]+" "_")
```

```
=> "a_b01c012d"
```

SEE ALSO

[str/replace-last](#)

Replaces the last occurrence of search in s.

[str/replace-all](#)

Replaces the all occurrences of search in s. The search arg may be a string or a regex pattern

[top](#)

str/replace-last

```
(str/replace-last s search replacement & options)
```

Replaces the last occurrence of search in s.

Options:

:ignore-case b if true ignores case, defaults to false

```
(str/replace-last "abcdefabc" "ab" "XYZ")
```

```
=> "abcdeXYZc"
```

```
(str/replace-last "foo.JPG" ".jpg" ".png" :ignore-case true)
```

```
=> "foo.png"
```

SEE ALSO

[str/replace-first](#)

Replaces the first occurrence of search in s. The search arg may be a string or a regex pattern. If the search arg is of type string ...

str/replace-all

Replaces the all occurrences of search in s. The search arg may be a string or a regex pattern

[top](#)

str/rest

```
(str/rest s)
```

Returns a possibly empty string of the characters after the first.

```
(str/rest "abcdef")  
=> "bcdef"
```

[top](#)

str/reverse

```
(str/reverse s)
```

Reverses a string

```
(str/reverse "abcdef")  
=> "fedcba"
```

[top](#)

str/split

```
(str/split s regex)  
(str/split s regex limit)
```

Splits string on a regular expression. Optional argument limit is the maximum number of splits. Returns a list of the splits.

```
(str/split "abc,def,ghi" ",")  
=> ("abc" "def" "ghi")
```

```
(str/split "James Peter Robert" " " 2)  
=> ("James" "Peter Robert")
```

```
(str/split "abc , def , ghi" " *, *")  
=> ("abc" "def" "ghi")
```

```
(str/split "abc,def,ghi" "((?<=,)|(?=,))")  
=> ("abc" ", " "def" ", " "ghi")
```

```
(str/split "q1w2e3r4t5y6u7i8o9p0" #"\d+")  
=> ("q" "w" "e" "r" "t" "y" "u" "i" "o" "p")
```

```
(str/split "q1w2e3r4t5y6u7i8o9p0" #"\d+" 5)  
=> ("q" "w" "e" "r" "t5y6u7i8o9p0")
```

```
(str/split "1234567890" #"(<=&\\G.{4})")  
=> ("1234" "5678" "90")
```

```
(str/split "1234567890" #"(<=(.{4})+$)")  
=> ("12" "3456" "7890")
```

```
(str/split " q1w2 " #"")  
=> (" " "q" "1" "w" "2" " " )
```

```
(str/split nil ",")  
=> ()
```

SEE ALSO

[str/split-lines](#)

Splits s into lines.

[top](#)

str/split-at

```
(str/split-at s pos)
```

Splits string at the given position. Returns a list of the splits.

```
(str/split-at nil 1)  
=> (" " " ")
```

```
(str/split-at "" 1)  
=> (" " " ")
```

```
(str/split-at "abc" 0)  
=> (" " "abc")
```

```
(str/split-at "abc" 1)  
=> ("a" "bc")
```

```
(str/split-at "abc" 2)  
=> ("ab" "c")
```

```
(str/split-at "abc" 3)  
=> ("abc" " ")
```

SEE ALSO

[str/split-lines](#)

Splits s into lines.

[top](#)

str/split-columns

```
(str/split-columns s cols)
```

Splits a string into columns. The columns are given by their start positions.

```
(str/split-columns "1abc 2d 3gh" [0 6 12])  
=> ("1abc" "2d" "3gh")
```

SEE ALSO

[str/split](#)

Splits string on a regular expression. Optional argument limit is the maximum number of splits. Returns a list of the splits.

[top](#)

str/split-lines

```
(str/split-lines s)
```

Splits s into lines.

```
(str/split-lines "line1  
line2  
line3")  
=> ("line1" "line2" "line3")
```

SEE ALSO

[str/split](#)

Splits string on a regular expression. Optional argument limit is the maximum number of splits. Returns a list of the splits.

[io/slurp-lines](#)

Read all lines from f.

[top](#)

str/starts-with?

```
(str/starts-with? s substr)
```

True if s starts with substr.

```
(str/starts-with? "abc" "ab")  
=> true
```

[top](#)

str/strip-end

```
(str/strip-end s substr)
```

Removes a substr only if it is at the end of a s, otherwise returns s.

```
(str/strip-end "abcdef" "def")  
=> "abc"
```

```
(str/strip-end "abcdef" "abc")  
=> "abcdef"
```

[top](#)

str/strip-indent

```
(str/strip-indent s)
```

Strip the indent of a multi-line string. The first line's leading whitespaces define the indent.

```
(str/strip-indent "  line1  
    line2  
    line3")  
=> "line1\n  line2\n  line3"
```

[top](#)

str/strip-margin

```
(str/strip-margin s)
```

Strips leading whitespaces upto and including the margin '|' from each line in a multi-line string.

```
(str/strip-margin "line1  
|  line2  
|  line3")  
=> "line1\n  line2\n  line3"
```

[top](#)

str/strip-start

```
(str/strip-start s substr)
```

Removes a substr only if it is at the beginning of a s, otherwise returns s.

```
(str/strip-start "abcdef" "abc")  
=> "def"
```

```
(str/strip-start "abcdef" "def")  
=> "abcdef"
```

[top](#)

str/subs

```
(str/subs s start)  
(str/subs s start end)
```

Returns the substring of s beginning at start inclusive, and ending at end (defaults to length of string), exclusive.

```
(str/subs "abcdef" 2)  
=> "cdef"
```

```
(str/subs "abcdef" 2 5)  
=> "cde"
```

[top](#)

str/trim

```
(str/trim s)
```

Trims leading and trailing whitespaces from s.

```
(str/trim " abc ")  
=> "abc"
```

SEE ALSO

[str/trim-to-empty](#)

Trims leading and trailing whitespaces from s. Returns an empty string if s is nil.

[str/trim-to-nil](#)

Trims leading and trailing whitespaces from s. Returns nil if the resulting string is empty

[str/trim-left](#)

Trims leading whitespaces from s.

[str/trim-right](#)

Trims trailing whitespaces from s.

[top](#)

str/trim-left

```
(str/trim-left s)
```

Trims leading whitespaces from s.

```
(str/trim-left " abc ")  
=> "abc "
```

SEE ALSO

[str/trim-right](#)

Trims trailing whitespaces from s.

[str/trim](#)

Trims leading and trailing whitespaces from s.

[str/trim-to-nil](#)

Trims leading and trailing whitespaces from s. Returns nil if the resulting string is empty

[top](#)

str/trim-right

```
(str/trim-right s)
```

Trims trailing whitespaces from s.

```
(str/trim-right " abc ")  
=> " abc"
```

SEE ALSO

[str/trim-left](#)

Trims leading whitespaces from s.

[str/trim](#)

Trims leading and trailing whitespaces from s.

[str/trim-to-nil](#)

Trims leading and trailing whitespaces from s. Returns nil if the resulting string is empty

[top](#)

str/trim-to-empty

```
(str/trim-to-empty s)
```

Trims leading and trailing whitespaces from s. Returns an empty string if s is nil.

```
(str/trim-to-empty "")  
=> ""
```

```
(str/trim-to-empty "   ")  
=> ""
```

```
(str/trim-to-empty nil)  
=> ""
```

```
(str/trim-to-empty " abc ")  
=> "abc"
```

SEE ALSO

[str/trim](#)

Trims leading and trailing whitespaces from s.

[str/trim-left](#)

Trims leading whitespaces from s.

[str/trim-right](#)

Trims trailing whitespaces from s.

[top](#)

str/trim-to-nil

```
(str/trim-to-nil s)
```

Trims leading and trailing whitespaces from s. Returns nil if the resulting string is empty

```
(str/trim-to-nil "")  
=> nil
```

```
(str/trim-to-nil "   ")  
=> nil
```

```
(str/trim-to-nil nil)  
=> nil
```

```
(str/trim-to-nil " abc  ")  
=> "abc"
```

SEE ALSO

[str/trim-to-empty](#)

Trims leading and trailing whitespaces from s. Returns an empty string if s is nil.

[str/trim](#)

Trims leading and trailing whitespaces from s.

[str/trim-left](#)

Trims leading whitespaces from s.

[str/trim-right](#)

Trims trailing whitespaces from s.

[top](#)

str/truncate

```
(str/truncate s maxlen marker mode*)
```

Truncates a string to the max length maxlen and adds the marker if the string needs to be truncated. The marker is added to the start, middle, or end of the string depending on the mode :start, :middle, :end. The mode defaults to :end

```
(str/truncate "abcdefghij" 20 "...")  
=> "abcdefghij"
```

```
(str/truncate "abcdefghij" 9 "...")  
=> "abcdef..."
```

```
(str/truncate "abcdefghij" 4 "...")  
=> "a..."
```

```
(str/truncate "abcdefghij" 7 "...":start)  
=> "...ghij"
```

```
(str/truncate "abcdefghij" 7 "...":middle)  
=> "ab...ij"
```

```
(str/truncate "abcdefghij" 7 "...":end)  
=> "abcd..."
```


str/upper-case

```
(str/upper-case s)
(str/upper-case locale s)
```

Converts s to uppercase.

Since case mappings are not always 1:1 character mappings when a locale is given, the resulting string may be a different length than the original!

```
(str/upper-case "aBcDeF")
=> "ABCDEF"

(str/upper-case #\a)
=> #\A

(str/upper-case (. :java.util.Locale :new "de" "DE") "aBcDeF")
=> "ABCDEF"

(str/upper-case (. :java.util.Locale :GERMANY) "aBcDeF")
=> "ABCDEF"

(str/upper-case (. :java.util.Locale :new "de" "CH") "aBcDeF")
=> "ABCDEF"

(str/upper-case [ "de" ] "aBcDeF")
=> "ABCDEF"

(str/upper-case [ "de" "DE" ] "aBcDeF")
=> "ABCDEF"

(str/upper-case [ "de" "DE" ] "aBcDeF")
=> "ABCDEF"
```

SEE ALSO

[str/lower-case](#)

Converts s to lowercase.

str/upper-case?

```
(str/upper-case? s)
```

True if s is a char and the char is an upper case char.

Defined by Java Character.isUpperCase(ch).

```
(str/upper-case? #\x)
=> false

(str/upper-case? #\X)
=> true
```

```
(str/upper-case? #\8)
=> false
```

[top](#)

str/valid-email-addr?

```
(str/valid-email-addr? e)
```

Returns true if e is a valid email address according to RFC5322, else returns false

```
(str/valid-email-addr? "user@domain.com")
=> true

(str/valid-email-addr? "user@domain.co.in")
=> true

(str/valid-email-addr? "user.name@domain.com")
=> true

(str/valid-email-addr? "user_name@domain.com")
=> true

(str/valid-email-addr? "username@yahoo.corporate.in")
=> true
```

[top](#)

str/whitespace?

```
(str/whitespace? s)
```

True if s is char and the char is a whitespace.

Defined by Java Character.isWhitespace(ch).

```
(str/whitespace? #\space)
=> true
```

[top](#)

str/wrap

```
(str/wrap text & options)
```

Wraps ascii text to lines with a length of maxlen characters .

Options:

```
:maxlen n      the max len of line (default 80)
:line-wrap     controls the line wrap
{:}
```

```
anywhere,  
:break-  
word}
```

```
(-> (str/lorem-ipsum :paragraphs 1)  
    (str/wrap :maxlen 80 :line-wrap :break-word))  
=> "Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent ac iaculis\nturpis. Duis dictum id sem et  
consectetur. Nullam lobortis, libero non consequat\naliquet, lectus diam fringilla velit, finibus eleifend  
ipsum urna at lacus.\nPhasellus sit amet nisl fringilla, cursus est in, mollis lacus. Proin dignissim\nrhoncus  
dolor. Cras tellus odio, elementum sed erat sit amet, euismod tincidunt\nnisl. In hac habitasse platea  
dictumst. Duis aliquam sollicitudin tempor. Sed\ngravida tincidunt felis at fringilla. Morbi tempor enim at  
commodo vulputate.\nAenean et ultrices lorem, placerat pretium augue. In hac habitasse platea\ndictumst. Cras  
fringilla ligula quis interdum hendrerit. Etiam at massa tempor,\nfacilisis lacus placerat, congue erat."
```

top

string-array

```
(string-array coll)  
(string-array len)  
(string-array len init-val)
```

Returns an array of Java strings containing the contents of coll or returns an array with the given length and optional init value

```
(string-array '("1" "2" "3"))  
=> [1, 2, 3]
```

```
(string-array 10)  
=> [nil, nil, nil, nil, nil, nil, nil, nil, nil, nil]
```

```
(string-array 10 "42")  
=> [42, 42, 42, 42, 42, 42, 42, 42, 42, 42]
```

SEE ALSO

[java-string-list](#)

Converts a Venice list/vector to a Java String list

top

string?

```
(string? x)
```

Returns true if x is a string

```
(string? "abc")  
=> true
```

```
(string? 1)  
=> false
```

```
(string? nil)  
=> false
```

sublist

```
(sublist l start) (sublist l start end)
```

Returns a list of the items in list from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count list).

`sublist` accepts a lazy-seq if both start and end is given.

```
(sublist '(1 2 3 4 5 6) 2)
=> (3 4 5 6)
```

```
(sublist '(1 2 3 4 5 6) 2 3)
=> (3)
```

```
(doall (sublist (lazy-seq 1 inc) 3 7))
=> (4 5 6 7)
```

SEE ALSO

[subvec](#)

Returns a vector of the items in vector from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count vector)

subset?

```
(subset? set1 set2)
```

Return true if set1 is a subset of set2

```
(subset? #{2 3} #{1 2 3 4})
=> true
```

```
(subset? #{2 5} #{1 2 3 4})
=> false
```

SEE ALSO

[set](#)

Creates a new set containing the items.

[superset?](#)

Return true if set1 is a superset of set2

[union](#)

Return a set that is the union of the input sets

[difference](#)

Return a set that is the first set without elements of the remaining sets

[intersection](#)

Return a set that is the intersection of the input sets

subvec

(subvec v start) (subvec v start end)

Returns a vector of the items in vector from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count vector)

```
(subvec [1 2 3 4 5 6] 2)
=> [3 4 5 6]
```

```
(subvec [1 2 3 4 5 6] 2 3)
=> [3]
```

SEE ALSO

[sublist](#)

Returns a list of the items in list from start (inclusive) to end (exclusive). If end is not supplied, defaults to (count list).

[top](#)

supers

(supers class)

Returns the immediate and indirect superclasses and interfaces of class, if any.

```
(supers :java.util.ArrayList)
=> (:java.util.AbstractList :java.util.AbstractCollection :java.util.List :java.util.Collection :java.lang.
Iterable)
```

[top](#)

superset?

(superset? set1 set2)

Return true if set1 is a superset of set2

```
(superset? #{1 2 3 4} #{2 3} )
=> true
```

```
(superset? #{1 2 3 4} #{2 5})
=> false
```

SEE ALSO

[set](#)

Creates a new set containing the items.

[subset?](#)

Return true if set1 is a subset of set2

[union](#)

Return a set that is the union of the input sets

[difference](#)

Return a set that is the first set without elements of the remaining sets

[intersection](#)

Return a set that is the intersection of the input sets

[top](#)

supertype

```
(supertype x)
```

Returns the super type of x.

```
(supertype 5)
```

```
=> :core/number
```

```
(supertype [1 2])
```

```
=> :core/sequence
```

```
(supertype (. :java.math.BigInteger :valueOf 100))
```

```
=> :java.lang.Number
```

SEE ALSO

[type](#)

Returns the type of x.

[supertypes](#)

Returns the super types of x.

[instance-of?](#)

Returns true if x is an instance of the given type

[top](#)

supertypes

```
(supertypes x)
```

Returns the super types of x.

```
(supertypes 5)
```

```
=> (:core/number :core/val)
```

```
(supertypes [1 2])
```

```
=> (:core/sequence :core/collection :core/val)
```

```
(supertypes (. :java.math.BigInteger :valueOf 100))
```

```
=> (:java.lang.Number :java.lang.Object)
```

SEE ALSO

[type](#)

Returns the type of x.

[supertype](#)

Returns the super type of x.

[instance-of?](#)

Returns true if x is an instance of the given type

[top](#)

swap!

```
(swap! box f & args)
```

Atomically swaps the value of an atom or a volatile to be: `(apply f current-value-of-box args)` . Note that f may be called multiple times, and thus should be free of side effects. Returns the value that was swapped in.

```
(do
  (def counter (atom 0))
  (swap! counter inc))
=> 1

(do
  (def counter (atom 0))
  (swap! counter inc)
  (swap! counter + 1)
  (swap! counter #(inc %))
  (swap! counter (fn [x] (inc x))))
@counter
=> 4

(do
  (def fruits (atom ()))
  (swap! fruits conj :apple)
  (swap! fruits conj :mango)
  @fruits)
=> (:apple :mango)

(do
  (def counter (volatile 0))
  (swap! counter (partial + 6))
  @counter)
=> 6
```

SEE ALSO

[swap-vals!](#)

Atomically swaps the value of an atom to be: `(apply f current-value-of-atom args)`. Note that f may be called multiple times, and thus ...

[reset!](#)

Sets the value of an atom or a volatile to newval without regard for the current value. Returns newval.

[compare-and-set!](#)

Atomically sets the value of atom to newval if and only if the current value of the atom is identical to oldval. Returns true if set ...

[atom](#)

Creates an atom with the initial value x.

[volatile](#)

Creates a volatile with the initial value x

[top](#)

swap-vals!

```
(swap-vals! atom f & args)
```

Atomically swaps the value of an atom to be: `(apply f current-value-of-atom args)`. Note that `f` may be called multiple times, and thus should be free of side effects. Returns `[old new]`, the value of the atom before and after the swap.

```
(do
  (def queue (atom '(1 2 3)))
  (swap-vals! queue pop))
=> [(1 2 3) (2 3)]
```

SEE ALSO

[swap!](#)

Atomically swaps the value of an atom or a volatile to be: `(apply f current-value-of-box args)`. Note that `f` may be called multiple ...

[reset!](#)

Sets the value of an atom or a volatile to `newval` without regard for the current value. Returns `newval`.

[compare-and-set!](#)

Atomically sets the value of `atom` to `newval` if and only if the current value of the atom is identical to `oldval`. Returns true if set ...

[atom](#)

Creates an atom with the initial value `x`.

[volatile](#)

Creates a volatile with the initial value `x`

[top](#)

symbol

```
(symbol name)
(symbol ns name)
```

Returns a symbol from the given name

```
(symbol "a")
=> a
```

```
(symbol "foo" "a")
=> foo/a
```

```
(symbol *ns* "a")
=> user/a
```

```
(symbol 'a)
=> a
```

```
((resolve (symbol "core" "+")) 1 2)
=> 3
```

```
(name str/reverse)
=> "reverse"
```



```
(namespace str/reverse)
=> "str"
```

SEE ALSO

[resolve](#)

Resolves a symbol.

[name](#)

Returns the name string of a string, symbol, keyword, or function. If applied to a string it returns the string itself.

[namespace](#)

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

[top](#)

symbol?

```
(symbol? x)
```

Returns true if x is a symbol

```
(symbol? 'a)
=> true
```

```
(symbol? (symbol "a"))
=> true
```

```
(symbol? nil)
=> false
```

```
(symbol? :a)
=> false
```

[top](#)

system-env

```
(system-env)
(system-env name)
(system-env name default-val)
```

Returns the system env variable with the given name. Returns the default-val if the variable does not exist or it's value is nil.

Without arguments returns all system env variables authorized by the configured sandbox.

```
(system-env :SHELL)
=> "/bin/zsh"
```

```
(system-env :FOO "test")
=> "test"
```

```
(system-env "SHELL")
=> "/bin/zsh"
```

SEE ALSO

[system-prop](#)

Returns the system property with the given name. Returns the default-val if the property does not exist or it's value is nil.

[top](#)

system-exit-code

```
(system-exit-code code)
```

Defines the exit code that is used if the Java VM exits. Defaults to 0.

Note:

The exit code is only used when the Venice launcher has been used to run a script file, a command line script, a Venice app archive, or the REPL.

```
(system-exit-code 0)
```

[top](#)

system-prop

```
(system-prop)
(system-prop name)
(system-prop name default-val)
```

Returns the system property with the given name. Returns the default-val if the property does not exist or it's value is nil.

Without arguments returns all system properties authorized by the configured sandbox.

```
(system-prop :os.name)
=> "Mac OS X"

(system-prop :foo.org "abc")
=> "abc"

(system-prop "os.name")
=> "Mac OS X"
```

SEE ALSO

[system-env](#)

Returns the system env variable with the given name. Returns the default-val if the variable does not exist or it's value is nil.

[top](#)

tail-pos

```
(tail-pos)
(tail-pos name)
```

Throws a `NotInTailPositionException` if the `expr` is not in tail position otherwise returns nil.

Definition:

The tail position is a position which an expression would return a value from. There are no more forms evaluated after the form in the tail position is evaluated.

```
;; in tail position
(do 1 (tail-pos))
=> nil
```

```
;; not in tail position
(do (tail-pos) 1)
=> NotInTailPositionException: Not in tail position
```

[top](#)

take

```
(take n coll)
```

Returns a collection of the first n items in coll, or all items if there are fewer than n.

Returns a stateful transducer when no collection is provided. Returns a lazy sequence if coll is a lazy sequence.

```
(take 3 [1 2 3 4 5])
=> [1 2 3]
```

```
(take 10 [1 2 3 4 5])
=> [1 2 3 4 5]
```

```
(doall (take 4 (repeat 3)))
=> (3 3 3 3)
```

```
(doall (take 10 (cycle (range 0 3))))
=> (0 1 2 0 1 2 0 1 2 0)
```

[top](#)

take!

```
(take! queue)
```

Retrieves and removes the head value of the queue, waiting if necessary until a value becomes available.

```
(let [q (queue)]
  (put! q 1)
  (take! q)
  q)
=> ()
```

SEE ALSO

[queue](#)

Creates a new mutable threadsafe bounded or unbounded queue.

[put!](#)

Puts an item to a queue. The operation is synchronous, it waits indefinitely until the value can be placed on the queue. Returns always nil.

offer!

Offers an item to a queue with an optional timeout in milliseconds. If a timeout is given waits up to the specified wait time if necessary ...

poll!

Polls an item from a queue with an optional timeout in milliseconds. For an indefinite timeout pass the timeout value :indefinite.

peek

For a list, same as first, for a vector, same as last, for a stack the top element (or nil if the stack is empty), for a queue the ...

empty?

Returns true if x is empty. Accepts strings, collections and bytebufs.

count

Returns the number of items in the collection. (count nil) returns 0. Also works on strings, and Java Collections

top

take-last

```
(take-last n coll)
```

Return a sequence of the last n items in coll.

Returns a stateful transducer when no collection is provided.

```
(take-last 3 [1 2 3 4 5])  
=> [3 4 5]
```

```
(take-last 10 [1 2 3 4 5])  
=> [1 2 3 4 5]
```

top

take-while

```
(take-while predicate coll)
```

Returns a list of successive items from coll while (predicate item) returns logical true.

Returns a transducer when no collection is provided.

```
(take-while neg? [-2 -1 0 1 2 3])  
=> [-2 -1]
```

top

tap>

```
(tap> x)
```

Sends x to any taps. Will not block. Returns true if there was room in the queue, false if not (x is dropped).

```
(do  
  (add-tap prn)  
  (tap> {:foo "hello" :bar 34.5}))  
=> true
```

SEE ALSO

[add-tap](#)

adds `f`, a fn of one argument, to the tap set. This function will be called with anything sent via `tap>`.

[remove-tap](#)

Remove `f` from the tap set.

[clear-taps](#)

Removes all tap sets.

[top](#)

test/deftest

```
(deftest name & body)
```

Defines a test function with no arguments.

All assertion macros are available for test assertions within the test function body:

- `assert`
- `assert-false`
- `assert-eq`
- `assert-ne`
- `assert-throws`
- `assert-does-not-throw`
- `assert-throws-with-msg`

It's recommended to use dedicated test namespaces for the tests and to group tests by namespaces.

Note: Actually, the test body goes in the `:test` metadata on the var, and the real function (the value of the var) calls `test-var` on itself.

```
(do
  (load-module :test)

  (ns foo-test)

  (test/deftest add-test []
    (assert-eq 0 (+ 0 0))
    (assert-eq 3 (+ 1 2)))

  (test/deftest mul-test []
    (assert-eq 6 (* 2 3)))

  (ns bar)
  (test/run-tests 'foo-test))
```

Testing namespace 'foo-test

PASS foo-test/add-test

PASS foo-test/mul-test

Ran 2 tests with 3 assertions

0 failures, 0 errors.

=> {:assert 3 :error 0 :pass 2 :test 2 :type :summary :fail 0}

;; Explicit setup/teardown

```
(do
  (ns foo-test)
```

```
(load-module :test)

(test/deftest sum-test []
  (let [f (io/temp-file "test-", ".txt")]
    (try
      (io/spit f "1234" :append true)
      (assert-eq "1234" (io/slurp f :binary false))
      (finally
        (io/delete-file f))))))

(test/run-tests *ns*)

Testing namespace 'foo-test

PASS foo-test/sum-test

Ran 1 tests with 1 assertions
0 failures, 0 errors.
=> {:assert 1 :error 0 :pass 1 :test 1 :type :summary :fail 0}
```

SEE ALSO

[test/run-tests](#)

Runs all tests in the given namespaces; prints results. The tests are run grouped the namespace.

[test/run-test-var](#)

Runs a single test; prints results. Returns a map summarizing the test results.

[test/use-fixtures](#)

Wrap test runs in a fixture function to perform setup and teardown. Fixtures are always bound to a namespace, hence tests from different ...

[test/successful?](#)

Returns true if the given test summary indicates all tests were successful, false otherwise.

[assert](#)

Evaluates expr and throws an :AssertionException exception if it does not evaluate to logical true.

[assert-false](#)

Evaluates expr and throws an :AssertionException exception if it does not evaluate to logical false.

[assert-eq](#)

Assert that expected and actual are equal. Throws an :AssertionException exception if they are not equal.

[assert-ne](#)

Assert that unexpected and actual are not equal. Throws an :AssertionException exception if they are equal.

[assert-throws](#)

Evaluates expr and throws an :AssertionException exception if it does not throw the expected exception of type ex-type.

[assert-does-not-throw](#)

Evaluates expr and throws an :AssertionException exception if it does throw any kind of exception.

[top](#)

test/run-test-var

```
(run-test-var v)
```

Runs a single test; prints results. Returns a map summarizing the test results.

```
(do
  (ns foo-test)
  (load-module :test))
```

```
(test/deftest plus-test []  
  (assert-eq 3 (+ 1 2)))  
  
(test/run-test-var plus-test))
```

Testing namespace 'foo-test

PASS foo-test/plus-test

Ran 1 tests with 1 assertions

0 failures, 0 errors.

=> {:assert 1 :error 0 :pass 1 :test 1 :type :summary :fail 0}

SEE ALSO

[test/deftest](#)

Defines a test function with no arguments.

[test/run-tests](#)

Runs all tests in the given namespaces; prints results. The tests are run grouped the namespace.

[test/use-fixtures](#)

Wrap test runs in a fixture function to perform setup and teardown. Fixtures are always bound to a namespace, hence tests from different ...

[top](#)

test/run-tests

(run-tests & namespaces)

Runs all tests in the given namespaces; prints results. The tests are run grouped the namespace.

Returns a map summarizing test results.

```
(do  
  (load-module :test)  
  
  (ns foo-test)  
  (test/deftest add-test []  
    (assert-eq 3 (+ 1 2)))  
  (test/deftest sub-test []  
    (assert-eq 1 (- 2 1)))  
  
  (ns bar-test)  
  (test/deftest mul-test []  
    (assert-eq 2 (* 1 2)))  
  
  (test/run-tests 'foo-test 'bar-test))
```

Testing namespace 'foo-test

PASS foo-test/add-test

PASS foo-test/sub-test

Testing namespace 'bar-test

PASS bar-test/mul-test

Ran 3 tests with 3 assertions

0 failures, 0 errors.

=> {:assert 3 :error 0 :pass 3 :test 3 :type :summary :fail 0}

SEE ALSO

[test/deftest](#)

Defines a test function with no arguments.

[test/run-test-var](#)

Runs a single test; prints results. Returns a map summarizing the test results.

[test/use-fixtures](#)

Wrap test runs in a fixture function to perform setup and teardown. Fixtures are always bound to a namespace, hence tests from different ...

[top](#)

test/successful?

```
(successful? summary)
```

Returns true if the given test summary indicates all tests were successful, false otherwise.

```
(do
  (ns foo-test)
  (load-module :test)

  (test/deftest plus-test []
    (assert-eq 3 (+ 1 2)))

  (let [summary (test/run-tests 'foo-test)]
    (test/successful? summary)))
```

Testing namespace 'foo-test

PASS foo-test/plus-test

Ran 1 tests with 1 assertions

0 failures, 0 errors.

=> true

SEE ALSO

[test/deftest](#)

Defines a test function with no arguments.

[test/run-tests](#)

Runs all tests in the given namespaces; prints results. The tests are run grouped the namespace.

[test/run-test-var](#)

Runs a single test; prints results. Returns a map summarizing the test results.

[test/use-fixtures](#)

Wrap test runs in a fixture function to perform setup and teardown. Fixtures are always bound to a namespace, hence tests from different ...

[top](#)

test/use-fixtures

```
(use-fixtures ns fixture-type & fixture-fns)
```


Wrap test runs in a fixture function to perform setup and teardown. Fixtures are always bound to a namespace, hence tests from different namespaces have different fixtures.

A fixture of type `:each` is called before and after each test in the fixture's namespace.

A fixture of type `:once` is called before the first and after the last test in the fixture's namespace serving as an initial setup and final teardown.

To pass a value from a fixture to the tests dynamic vars can be used. See the 3rd example below.

```
;; Fixtures :each
;; Adds logic for a setup and teardown method that will be called
;; before and after each test
(do
  (load-module :test)

  (defn each-time-setup []
    (println "FIXTURE each time setup"))

  (defn each-time-teardown []
    (println "FIXTURE each time teardown"))

  (defn each-fixture [f]
    (each-time-setup)
    (try
      (f)
      (finally (each-time-teardown))))

  ;; register as an each-time callback
  (test/use-fixtures *ns* :each each-fixture)

  (test/deftest add-test []
    (assert-eq 3 (+ 1 2)))

  (test/deftest sub-test []
    (assert-eq 3 (- 4 1)))

  (test/run-tests *ns*))
```

Testing namespace 'user

```
FIXTURE each time setup
PASS user/add-test
FIXTURE each time teardown
FIXTURE each time setup
PASS user/sub-test
FIXTURE each time teardown
```

```
Ran 2 tests with 2 assertions
0 failures, 0 errors.
=> {:assert 2 :error 0 :pass 2 :test 2 :type :summary :fail 0}
```

```
;; Fixtures :once
;; Adds logic for a setup and teardown method that will be called
;; before the first and after the last test as an initial setup
;; and final teardown
(do
  (load-module :test)

  (defn one-time-setup []
    (println "FIXTURE one time setup"))

  (defn one-time-teardown []
    (println "FIXTURE one time teardown"))

  (defn one-fixture [f]
```

```

(one-time-setup)
(try
  (f)
  (finally (one-time-teardown))))

;; register as a one-time callback
(test/use-fixtures *ns* :once one-fixture)

(test/deftest add-test []
  (assert-eq 3 (+ 1 2)))

(test/deftest sub-test []
  (assert-eq 3 (- 4 1)))

(test/run-tests *ns*)

Testing namespace 'user

FIXTURE one time setup
PASS user/add-test
PASS user/sub-test
FIXTURE one time teardown

Ran 2 tests with 2 assertions
0 failures, 0 errors.
=> {:assert 2 :error 0 :pass 2 :test 2 :type :summary :fail 0}

```

;; Passing a value from a setup fixture to the tests

```

(do
  (load-module :test)

  (def-dynamic *state* 0)

  (defn one-time-setup []
    (println "FIXTURE one-time setup")
    100)

  (defn one-time-teardown []
    (println "FIXTURE one-time teardown"))

  (defn one-fixture [f]
    (binding [*state* (one-time-setup)]
      (try
        (f)
        (finally (one-time-teardown))))))

;; register as a one-time callback
(test/use-fixtures *ns* :once one-fixture)

(test/deftest add-test []
  (println "state user/add-test:" *state*)
  (assert-eq 3 (+ 1 2)))

(test/deftest sub-test []
  (println "state user/sub-test:" *state*)
  (assert-eq 3 (- 4 1)))

(test/run-tests *ns*)

```

Testing namespace 'user

```

FIXTURE one-time setup
state user/add-test: 100
PASS user/add-test

```

```
state user/sub-test: 100
PASS user/sub-test
FIXTURE one-time teardown

Ran 2 tests with 2 assertions
0 failures, 0 errors.
=> {:assert 2 :error 0 :pass 2 :test 2 :type :summary :fail 0}
```

SEE ALSO

[test/deftest](#)

Defines a test function with no arguments.

[test/run-tests](#)

Runs all tests in the given namespaces; prints results. The tests are run grouped the namespace.

[test/run-test-var](#)

Runs a single test; prints results. Returns a map summarizing the test results.

[top](#)

then-accept

```
(then-accept p f)
```

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

```
(-> (promise (fn [] "the quick brown fox"))
    (then-accept (fn [v] (println (pr-str v)))))
(deref))
"the quick brown fox"
=> nil

(let [result (promise)
      p      (promise)]
  (thread #(deliver p 5))
  (then-accept p (fn [v] (deliver result (+ v 2)))))
[@p @result]))
=> [5 7]
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two ...

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[then-combine](#)

Applies a function `f` to the result of the previous stage of promise `p` and the result of another promise `p-other`

[then-compose](#)

Composes the result of two promises. `f` receives the result of the first promise `p` and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise `p` with the same result or exception at this stage, that executes the action `f`. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completeness normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

then-accept-both

```
(then-accept-both p p-other f)
```

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two results as arguments.

```
(-> (promise (fn [] (sleep 200) "The quick brown fox"))
    (then-accept-both (promise (fn [] (sleep 100) "jumps over the lazy dog"))
                      (fn [u v] (println (pr-str (str u " " v))))))
    (deref))
"The quick brown fox jumps over the lazy dog"
=> nil
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and set, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[then-combine](#)

Applies a function `f` to the result of the previous stage of promise `p` and the result of another promise `p-other`

[then-compose](#)

Composes the result of two promises. `f` receives the result of the first promise `p` and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise `p` with the same result or exception at this stage, that executes the action `f`. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completess normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

then-apply

```
(then-apply p f)
```

Applies a function f on the result of the previous stage of the promise p.

```
(> (promise (fn [] "the quick brown fox"))
    (then-apply str/upper-case)
    (then-apply #(str % " jumps over the lazy dog"))
    (deref))
=> "THE QUICK BROWN FOX jumps over the lazy dog"
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function f with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function f with the two ...

[then-combine](#)

Applies a function f to the result of the previous stage of promise p and the result of another promise p-other

[then-compose](#)

Composes the result of two promises. f receives the result of the first promise p and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise p with the same result or exception at this stage, that executes the action f. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a TimeoutException if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

then-combine

```
(then-combine p p-other f)
```

Applies a function f to the result of the previous stage of promise p and the result of another promise p-other

```
(> (promise (fn [] "The Quick Brown Fox"))
    (then-apply str/upper-case)
    (then-combine (> (promise (fn [] "Jumps Over The Lazy Dog"))
                    (then-apply str/lower-case))
                  #(str %1 " " %2))
    (deref))
=> "THE QUICK BROWN FOX jumps over the lazy dog"
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two ...

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[then-compose](#)

Composes the result of two promises. `f` receives the result of the first promise `p` and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise `p` with the same result or exception at this stage, that executes the action `f`. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

then-compose

```
(then-compose p f)
```

Composes the result of two promises. `f` receives the result of the first promise `p` and returns a new promise that composes that value with this promise.

```
(-> (promise (fn [] "The Quick Brown Fox"))
    (then-apply str/upper-case)
    (then-compose (fn [x] (-> (promise (fn [] "Jumps Over The Lazy Dog"))
                              (then-apply str/lower-case)
                              (then-apply #(str x " " %1)))))
    (deref))
=> "THE QUICK BROWN FOX jumps over the lazy dog"
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two ...

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[then-combine](#)

Applies a function `f` to the result of the previous stage of promise `p` and the result of another promise `p-other`

[when-complete](#)

Returns the promise `p` with the same result or exception at this stage, that executes the action `f`. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

third

```
(third coll)
```

Returns the third element of coll.

```
(third nil)
=> nil
```

```
(third [])
=> nil
```

```
(third [1 2 3])
=> 3
```

```
(third '())
=> nil
```

```
(third '(1 2 3))
=> 3
```

[top](#)

thread

```
(thread f)
(thread f name)
(thread f name type)
```

Executes the function `f` in another thread, returning immediately to the calling thread. Returns a `promise` which will receive the result of calling the function `f` when completed. Optionally a name can be assigned to the spawned thread.

The thread can be given a name by passing the *name* argument. By default the thread name is set to "venice-thread". For each thread spawned on a name the thread's name will be suffixed with an incrementing index starting from 1.

The thread type (*daemon* or *user*) can be controlled by the *type* argument that must be one of `{:daemon, :user}`. By default a daemon thread is spawned.

Note: Each call to `thread` creates a new expensive system thread. Consider to use futures or promises that use an *ExecutorService* to deal efficiently with threads.

```
@(thread #(do (sleep 100) 1))
=> 1
```

```
@(thread #(do (sleep 100) (thread-name)))
=> "venice-thread-3"

@(thread #(do (sleep 100) (thread-name)) "job")
=> "job-1"

@(thread #(do (sleep 100) (thread-name)) "job" :daemon)
=> "job-2"

;; consumer / producer
(do
  (defn produce [q]
    (doseq [x (range 4)] (put! q x) (sleep 100))
    (put! q nil))
  (defn consume [q]
    (transduce (map println) (constantly nil) q))
  (let [q (queue 10)]
    (thread #(produce q))
    @(thread #(consume q))))
0
1
2
3
=> nil
```

SEE ALSO

[future](#)

Takes a function without arguments and yields a future object that will invoke the function in another thread, and will cache the result ...

[promise](#)

Returns a promise object that can be read with deref, and set, once only, with deliver. Calls to deref prior to delivery will block, ...

[agent](#)

Creates and returns an agent with an initial value of state and zero or more options.

[top](#)

thread-daemon?

```
(thread-daemon?)
```

Returns true if this Thread is a daemon thread else false.

```
(thread-daemon?)
=> false
```

SEE ALSO

[thread-name](#)

Returns this thread's name.

[top](#)

thread-id

```
(thread-id)
```


Returns the identifier of this Thread. The thread ID is a positive number generated when this thread was created. The thread ID is unique and remains unchanged during its lifetime. When a thread is terminated, this thread ID may be reused.

```
(thread-id)  
=> 1
```

SEE ALSO

[thread-name](#)
Returns this thread's name.

[top](#)

thread-interrupted

```
(thread-interrupted)
```

Tests whether the current thread has been interrupted. The interrupted status of the thread is cleared by this method. In other words, if this method were to be called twice in succession, the second call would return false (unless the current thread were interrupted again, after the first call had cleared its interrupted status and before the second call had examined it).

Returns true if the current thread has been interrupted else false.

```
(thread-interrupted)  
=> false
```

SEE ALSO

[thread-interrupted?](#)
Tests whether this thread has been interrupted. The interrupted status of the thread is unaffected by this method. Returns true if ...

[top](#)

thread-interrupted?

```
(thread-interrupted?)
```

Tests whether this thread has been interrupted. The interrupted status of the thread is unaffected by this method. Returns true if the current thread has been interrupted else false.

```
(thread-interrupted?)  
=> false
```

SEE ALSO

[thread-interrupted](#)
Tests whether the current thread has been interrupted. The interrupted status of the thread is cleared by this method. In other words, ...

[top](#)

thread-local

```
(thread-local)
```

Creates a new thread-local accessor

```
(do
  (assoc! (thread-local) :a 1)
  (get (thread-local) :a))
=> 1

(do
  (assoc! (thread-local) :a 1)
  (get (thread-local) :b 999))
=> 999

(do
  (thread-local :a 1 :b 2)
  (get (thread-local) :a))
=> 1

(do
  (thread-local { :a 1 :b 2 })
  (get (thread-local) :a))
=> 1

(do
  (thread-local-clear)
  (assoc! (thread-local) :a 1 :b 2)
  (dissoc! (thread-local) :a)
  (get (thread-local) :a 999))
=> 999
```

SEE ALSO

[thread-local-clear](#)

Removes all thread local vars

[thread-local-map](#)

Returns a snapshot of the thread local vars as a map.

[assoc!](#)

Associates key/vals with a mutable map, returns the map

[dissoc!](#)

Dissociates keys from a mutable map, returns the map

[get](#)

Returns the value mapped to key, not-found or nil if key not present.

[top](#)

thread-local-clear

```
(thread-local-clear)
```

Removes all thread local vars

```
(thread-local-clear)
=> thread-local-clear
```

SEE ALSO

[thread-local](#)

Creates a new thread-local accessor

[dissoc!](#)

Dissociates keys from a mutable map, returns the map

[top](#)

thread-local-map

```
(thread-local-map)
```

Returns a snapshot of the thread local vars as a map.

Note:

The returned map is a copy of the current thread local vars. Thus modifying this map is not modifying the thread local vars! Use `assoc!` and `dissoc!` for that purpose!

```
(do
  (thread-local-clear)
  (thread-local :a 1 :b 2)
  (thread-local-map))
=> {:a 1 :b 2 :*assertions* (0)}
```

SEE ALSO

[thread-local](#)

Creates a new thread-local accessor

[get](#)

Returns the value mapped to key, not-found or nil if key not present.

[assoc!](#)

Associates key/vals with a mutable map, returns the map

[dissoc!](#)

Dissociates keys from a mutable map, returns the map

[top](#)

thread-local?

```
(thread-local? x)
```

Returns true if x is a thread-local, otherwise false

```
(do
  (def x (thread-local))
  (thread-local? x))
=> true
```

SEE ALSO

[thread-local](#)

Creates a new thread-local accessor

[top](#)

thread-name

```
(thread-name)
```

Returns this thread's name.

```
(thread-name)
=> "main"
```

SEE ALSO

[thread-id](#)

Returns the identifier of this Thread. The thread ID is a positive number generated when this thread was created. The thread ID is ...

[top](#)

throw

```
(throw)
(throw val)
(throw ex)
```

Throws an exception.

```
(throw)
```

Throws a :ValueException with `nil` as its value.

```
(throw val)
```

With *va* as a Venice value throws a :ValueException with *va* as its value.
E.g: `(throw [1 2 3])`

```
(throw ex)
```

With a *ex* as an exception type throws the exception.
E.g: `(throw (ex :VncException "invalid data"))`

```
(try
  (+ 100 200)
  (catch :Exception e
    "caught ~(ex-message e)"))
=> 300
```

```
(try
  (+ 100 200)
  (throw)
  (catch :ValueException e
    "caught ~(pr-str (ex-value e))"))
=> "caught nil"
```

```
(try
  (+ 100 200)
  (throw 100)
  (catch :ValueException e
    "caught ~(ex-value e)"))
=> "caught 100"
```

;; The finally block is just for side effects, like
;; closing resources. It never returns a value!

```

(try
  (+ 100 200)
  (throw [100 {:a 3}])
  (catch :ValueException e
    "caught ~(ex-value e)")
  (finally (println "#finally")
    :finally))
#finally
=> "caught [100 {:a 3}]"

(try
  (throw (ex :RuntimeException "#test"))
  (catch :RuntimeException e
    "caught ~(ex-message e)")
=> "caught #test"

;; Venice wraps thrown checked exceptions with a RuntimeException!
(do
  (import :java.io.IOException)
  (try
    (throw (ex :IOException "#test"))
    (catch :RuntimeException e
      "caught ~(ex-message (ex-cause e))")))
=> "caught #test"

```

SEE ALSO

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of `:java.lang.Exception`

[try](#)

Exception handling: try - catch - finally

[try-with](#)

try-with-resources allows the declaration of resources to be used in a try block with the assurance that the resources will be closed ...

[top](#)

time

```
(time expr)
```

Evaluates `expr` and prints the time it took. Returns the value of `expr`.

```

(time (+ 100 200))
Elapsed time: 3.83µs
=> 300

```

SEE ALSO

[dorun](#)

Runs the `expr` count times in the most effective way. It's main purpose is supporting benchmark tests. Returns the expression result ...

[top](#)

time/after?

```
(time/after? date1 date2)
(time/after? date1 date2 & more)
```

Returns true if all dates are ordered from the latest to the earliest (same semantics as [>](#))

```
(time/after? (time/local-date 2019 1 1)
             (time/local-date 2018 1 1))
=> true

(time/after? (time/local-date-time "2019-01-01T10:00:00.000")
             (time/local-date-time "2018-01-01T10:00:00.000"))
=> true

(time/after? (time/zoned-date-time "2019-01-01T10:00:00.000+01:00")
             (time/zoned-date-time "2018-01-01T10:00:00.000+01:00"))
=> true
```

SEE ALSO

[time/before?](#)

Returns true if all dates are ordered from the earliest to the latest (same semantics as [<](#))

[time/not-after?](#)

Returns true if date1 is not-after date2 else false (same semantics as [<=](#))

[time/not-before?](#)

Returns true if date1 is not-before date2 else false (same semantics as [>=](#))

[top](#)

time/before?

```
(time/before? date1 date2)
(time/before? date1 date2 & more)
```

Returns true if all dates are ordered from the earliest to the latest (same semantics as [<](#))

```
(time/before? (time/local-date 2018 1 1)
              (time/local-date 2019 1 1))
=> true

(time/before? (time/local-date-time "2018-01-01T10:00:00.000")
              (time/local-date-time "2019-01-01T10:00:00.000"))
=> true

(time/before? (time/zoned-date-time "2018-01-01T10:00:00.000+01:00")
              (time/zoned-date-time "2019-01-01T10:00:00.000+01:00"))
=> true
```

SEE ALSO

[time/after?](#)

Returns true if all dates are ordered from the latest to the earliest (same semantics as [>](#))

[time/not-after?](#)

Returns true if date1 is not-after date2 else false (same semantics as [<=](#))

[time/not-before?](#)

Returns true if date1 is not-before date2 else false (same semantics as [>=](#))

time/date

```
(time/date)
(time/date x)
```

Creates a new date of type 'java.util.Date'. x can be a long representing milliseconds since the epoch, a 'java.time.LocalDate', a 'java.time.LocalDateTime', or a 'java.time.ZonedDateTime'

```
(time/date)
=> Tue Aug 27 22:14:04 CEST 2024
```

time/date?

```
(time/date? date)
```

Returns true if date is a 'java.util.Date' else false

```
(time/date? (time/date))
=> true
```

time/day-of-month

```
(time/day-of-month date)
```

Returns the day of the month (1..31)

```
(time/day-of-month (time/local-date))
=> 27
```

```
(time/day-of-month (time/local-date-time))
=> 27
```

```
(time/day-of-month (time/zoned-date-time))
=> 27
```

SEE ALSO

[time/year](#)

Returns the year of the date

[time/month](#)

Returns the month of the date 1..12

[time/day-of-year](#)

Returns the day of the year (1..366)

[time/first-day-of-month](#)

Returns the first day of a month as a local-date.

[time/last-day-of-month](#)

Returns the last day of a month as a local-date.

[time/day-of-week](#)

Returns the day of the week (:MONDAY ... :SUNDAY)

[top](#)

time/day-of-week

([time/day-of-week](#) date)

Returns the day of the week (:MONDAY ... :SUNDAY)

([time/day-of-week](#) ([time/local-date](#)))

=> :TUESDAY

([time/day-of-week](#) ([time/local-date-time](#)))

=> :TUESDAY

([time/day-of-week](#) ([time/zoned-date-time](#)))

=> :TUESDAY

SEE ALSO

[time/year](#)

Returns the year of the date

[time/month](#)

Returns the month of the date 1..12

[time/day-of-year](#)

Returns the day of the year (1..366)

[time/day-of-month](#)

Returns the day of the month (1..31)

[time/first-day-of-month](#)

Returns the first day of a month as a local-date.

[time/last-day-of-month](#)

Returns the last day of a month as a local-date.

[top](#)

time/day-of-year

([time/day-of-year](#) date)

Returns the day of the year (1..366)

([time/day-of-year](#) ([time/local-date](#)))

=> 240

([time/day-of-year](#) ([time/local-date-time](#)))

=> 240


```
(time/day-of-year (time/zoned-date-time))  
=> 240
```

SEE ALSO

[time/year](#)

Returns the year of the date

[time/month](#)

Returns the month of the date 1..12

[time/day-of-month](#)

Returns the day of the month (1..31)

[time/first-day-of-month](#)

Returns the first day of a month as a local-date.

[time/last-day-of-month](#)

Returns the last day of a month as a local-date.

[time/day-of-week](#)

Returns the day of the week (:MONDAY ... :SUNDAY)

[top](#)

time/earliest

```
(time/earliest coll)
```

Returns the earliest date from a collection of dates. All dates must be of equal type. The coll may be empty or nil.

```
(time/earliest [(time/local-date 2018 8 4) (time/local-date 2018 8 3)])  
=> 2018-08-03
```

[top](#)

time/first-day-of-month

```
(time/first-day-of-month date)
```

Returns the first day of a month as a local-date.

```
(time/first-day-of-month (time/local-date))  
=> 2024-08-01
```

```
(time/first-day-of-month (time/local-date-time))  
=> 2024-08-01
```

```
(time/first-day-of-month (time/zoned-date-time))  
=> 2024-08-01
```

SEE ALSO

[time/year](#)

Returns the year of the date

[time/month](#)

Returns the month of the date 1..12

[time/day-of-year](#)

Returns the day of the year (1..366)

[time/day-of-month](#)

Returns the day of the month (1..31)

[time/last-day-of-month](#)

Returns the last day of a month as a local-date.

[time/day-of-week](#)

Returns the day of the week (:MONDAY ... :SUNDAY)

[top](#)

time/format

```
(time/format date format)
(time/format date format locale)
(time/format date formatter)
(time/format date formatter locale)
```

Formats a date with a format.

To format a large number of dates a pre instantiated formatter delivers best performance:

```
(let [fmt (time/formatter "yyyy-MM-dd'T'HH:mm:ss")]
  (dotimes [n 100] (time/format (time/local-date-time) fmt)))
```

```
(time/format (time/local-date) "dd-MM-yyyy")
=> "27-08-2024"
```

```
(time/format (time/local-date) (time/formatter "dd-MM-yyyy"))
=> "27-08-2024"
```

```
(time/format (time/local-date) :iso)
=> "2024-08-27"
```

```
(time/format (time/local-date-time) "yyyy-MM-dd'T'HH:mm:ss")
=> "2024-08-27T22:14:07"
```

```
(time/format (time/local-date-time) (time/formatter "yyyy-MM-dd'T'HH:mm:ss"))
=> "2024-08-27T22:14:07"
```

```
(time/format (time/local-date-time) :iso)
=> "2024-08-27T22:14:07.879"
```

```
(time/format (time/zoned-date-time) "yyyy-MM-dd'T'HH:mm:ss.SSSz")
=> "2024-08-27T22:14:07.906CEST"
```

```
(time/format (time/zoned-date-time) :iso)
=> "2024-08-27T22:14:07.933+02:00"
```

```
(time/format (time/zoned-date-time) (time/formatter "yyyy-MM-dd'T'HH:mm:ss.SSSz"))
=> "2024-08-27T22:14:07.960CEST"
```

SEE ALSO

[time/formatter](#)

Creates a formatter

top

time/formatter

```
(time/formatter format)
(time/formatter format locale)
```

Creates a formatter

```
(time/formatter "dd-MM-yyyy")

(time/formatter "dd-MM-yyyy" :en_EN)

(time/formatter "dd-MM-yyyy" "en_EN")

(time/formatter "yyyy-MM-dd'T'HH:mm:ss.SSSz")

(time/formatter :ISO_OFFSET_DATE_TIME)
```

SEE ALSO

[time/format](#)

Formats a date with a format.

top

time/hour

```
(time/hour date)
```

Returns the hour of the date 0..23

```
(time/hour (time/local-date))
=> 0

(time/hour (time/local-date-time))
=> 22

(time/hour (time/zoned-date-time))
=> 22
```

SEE ALSO

[time/minute](#)

Returns the minute of the date 0..59

[time/second](#)

Returns the second of the date 0..59

[time/milli](#)

Returns the millis of the date 0..999

top

time/last-day-of-month

```
(time/last-day-of-month date)
```

Returns the last day of a month as a local-date.

```
(time/last-day-of-month (time/local-date))  
=> 2024-08-31
```

```
(time/last-day-of-month (time/local-date-time))  
=> 2024-08-31
```

```
(time/last-day-of-month (time/zoned-date-time))  
=> 2024-08-31
```

SEE ALSO

[time/year](#)

Returns the year of the date

[time/month](#)

Returns the month of the date 1..12

[time/day-of-year](#)

Returns the day of the year (1..366)

[time/day-of-month](#)

Returns the day of the month (1..31)

[time/first-day-of-month](#)

Returns the first day of a month as a local-date.

[time/day-of-week](#)

Returns the day of the week (:MONDAY ... :SUNDAY)

[top](#)

time/latest

```
(time/latest coll)
```

Returns the latest date from a collection of dates. All dates must be of equal type. The coll may be empty or nil.

```
(time/latest [(time/local-date 2018 8 1) (time/local-date 2018 8 3)])  
=> 2018-08-03
```

[top](#)

time/leap-year?

```
(time/leap-year? date)
```

Checks if the year is a leap year.

```
(time/leap-year? 2000)
=> true

(time/leap-year? (time/local-date 2000 1 1))
=> true

(time/leap-year? (time/local-date-time))
=> true

(time/leap-year? (time/zoned-date-time))
=> true
```

SEE ALSO

[time/length-of-year](#)

Returns the length of the year represented by this date.

[time/length-of-month](#)

Returns the length of the month represented by this date.

[top](#)

time/length-of-month

```
(time/length-of-month date)
```

Returns the length of the month represented by this date.

This returns the length of the month in days. For example, a date in January would return 31.

```
(time/length-of-month (time/local-date 2000 2 1))
=> 29

(time/length-of-month (time/local-date 2001 2 1))
=> 28

(time/length-of-month (time/local-date-time))
=> 31

(time/length-of-month (time/zoned-date-time))
=> 31
```

SEE ALSO

[time/length-of-year](#)

Returns the length of the year represented by this date.

[time/leap-year?](#)

Checks if the year is a leap year.

[top](#)

time/length-of-year

```
(time/length-of-year date)
```

Returns the length of the year represented by this date.

This returns the length of the year in days, either 365 or 366.

```
(time/length-of-year (time/local-date 2000 1 1))  
=> 366
```

```
(time/length-of-year (time/local-date 2001 1 1))  
=> 365
```

```
(time/length-of-year (time/local-date-time))  
=> 366
```

```
(time/length-of-year (time/zoned-date-time))  
=> 366
```

SEE ALSO

[time/length-of-month](#)

Returns the length of the month represented by this date.

[time/leap-year?](#)

Checks if the year is a leap year.

[top](#)

time/local-date

```
(time/local-date)  
(time/local-date year month day)  
(time/local-date date)
```

Creates a new local-date. A local-date is represented by 'java.time.LocalDate'

```
(time/local-date)  
=> 2024-08-27
```

```
(time/local-date 2018 8 1)  
=> 2018-08-01
```

```
(time/local-date "2018-08-01")  
=> 2018-08-01
```

```
(time/local-date (time/local-date-time 2018 8 1 14 20 10))  
=> 2018-08-01
```

```
(time/local-date 1375315200000)  
=> 2013-08-01
```

```
(time/local-date (. :java.util.Date :new))  
=> 2024-08-27
```

SEE ALSO

[time/local-date-time](#)

Creates a new local-date-time. A local-date-time is represented by 'java.time.LocalDateTime'

[time/zoned-date-time](#)

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

[top](#)

time/local-date-parse

```
(time/local-date-parse str format
(time/local-date-parse str format locale
```

Parses a local-date.

To parse a large number of dates a pre instantiated formatter delivers best performance:

```
(let [fmt (time/formatter "yyyy-MM-dd")]
(dotimes [n 100] (time/local-date-parse "2018-12-01" fmt)))
```

```
(time/local-date-parse "2018-12-01" "yyyy-MM-dd")
=> 2018-12-01
```

```
(time/local-date-parse "2018-Dec-01" "yyyy-MMM-dd" :ENGLISH)
=> 2018-12-01
```

```
(time/local-date-parse "2018-12-01" :iso)
=> 2018-12-01
```

[top](#)

time/local-date-time

```
(time/local-date-time)
(time/local-date-time year month day)
(time/local-date-time year month day hour minute second)
(time/local-date-time year month day hour minute second millis)
(time/local-date-time date)
```

Creates a new local-date-time. A local-date-time is represented by 'java.time.LocalDateTime'

```
(time/local-date-time)
=> 2024-08-27T22:14:05.147
```

```
(time/local-date-time 2018 8 1)
=> 2018-08-01T00:00
```

```
(time/local-date-time 2018 8 1 14 20 10)
=> 2018-08-01T14:20:10
```

```
(time/local-date-time 2018 8 1 14 20 10 200)
=> 2018-08-01T14:20:10.200
```

```
(time/local-date-time "2018-08-01T14:20:10.200")
=> 2018-08-01T14:20:10.200
```

```
(time/local-date-time (time/local-date 2018 8 1))
=> 2018-08-01T00:00
```

```
(time/local-date-time 1375315200000)
=> 2013-08-01T02:00
```

```
(time/local-date-time (. :java.util.Date :new))
=> 2024-08-27T22:14:05.338
```

SEE ALSO

[time/local-date](#)

Creates a new local-date. A local-date is represented by 'java.time.LocalDate'

[time/zoned-date-time](#)

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

[top](#)

time/local-date-time-parse

```
(time/local-date-time-parse str format
(time/local-date-time-parse str format locale
```

Parses a local-date-time.

To parse a large number of dates a pre instantiated formatter delivers best performance:

```
(let [fmt (time/formatter "yyyy-MM-dd HH:mm:ss")]
(dotimes [n 100] (time/local-date-time-parse "2018-12-01 14:20:01" fmt)))
```

```
(time/local-date-time-parse "2018-08-01 14:20" "yyyy-MM-dd HH:mm")
=> 2018-08-01T14:20
```

```
(time/local-date-time-parse "2018-08-01 14:20:01.231" "yyyy-MM-dd HH:mm:ss.SSS")
=> 2018-08-01T14:20:01.231
```

```
(time/local-date-time-parse "2018-08-01T14:20:01.231" :iso)
=> 2018-08-01T14:20:01.231
```

[top](#)

time/local-date-time?

```
(time/local-date-time? date)
```

Returns true if date is a local-date-time ('java.time.LocalDateTime') else false

```
(time/local-date-time? (time/local-date-time))
=> true
```

[top](#)

time/local-date?

```
(time/local-date? date)
```


Returns true if date is a locale date ('java.time.LocalDate') else false

```
(time/local-date? (time/local-date))  
=> true
```

[top](#)

time/milli

(time/milli date)

Returns the millis of the date 0..999

```
(time/milli (time/local-date))  
=> 0
```

```
(time/milli (time/local-date-time))  
=> 74
```

```
(time/milli (time/zoned-date-time))  
=> 100
```

SEE ALSO

[time/hour](#)

Returns the hour of the date 0..23

[time/minute](#)

Returns the minute of the date 0..59

[time/second](#)

Returns the second of the date 0..59

[top](#)

time/minus

(time/minus date unit n)
(time/minus date temporal)

Subtracts the n units from the date. Units: {years :months :weeks :days :hours :minutes :seconds :milliseconds}

In the two argument version subtracts a java.time.Temporal (Period, Duration) from the date.

```
(time/minus (time/local-date) :days 2)  
=> 2024-08-25
```

```
(time/minus (time/local-date-time) :days 2)  
=> 2024-08-25T22:14:08.834
```

```
(time/minus (time/zoned-date-time) :days 2)  
=> 2024-08-25T22:14:08.860+02:00[Europe/Zurich]
```

```
(time/minus (time/local-date) (. :java.time.Period :ofDays 2))  
=> 2024-08-25
```

```
(time/minus (time/local-date-time) (. :java.time.Period :ofDays 2))  
=> 2024-08-25T22:14:08.914
```

```
(time/minus (time/zoned-date-time) (. :java.time.Period :ofDays 2))  
=> 2024-08-25T22:14:08.941+02:00[Europe/Zurich]
```

SEE ALSO

[time/plus](#)

Adds the n units to the date. Units: {years :months :weeks :days :hours :minutes :seconds :milliseconds}

[top](#)

time/minute

```
(time/minute date)
```

Returns the minute of the date 0..59

```
(time/minute (time/local-date))  
=> 0
```

```
(time/minute (time/local-date-time))  
=> 14
```

```
(time/minute (time/zoned-date-time))  
=> 14
```

SEE ALSO

[time/hour](#)

Returns the hour of the date 0..23

[time/second](#)

Returns the second of the date 0..59

[time/milli](#)

Returns the millis of the date 0..999

[top](#)

time/month

```
(time/month date)
```

Returns the month of the date 1..12

```
(time/month (time/local-date))  
=> 8
```

```
(time/month (time/local-date-time))  
=> 8
```

```
(time/month (time/zoned-date-time))  
=> 8
```

SEE ALSO

[time/year](#)

Returns the year of the date

[time/day-of-year](#)

Returns the day of the year (1..366)

[time/day-of-month](#)

Returns the day of the month (1..31)

[time/first-day-of-month](#)

Returns the first day of a month as a local-date.

[time/last-day-of-month](#)

Returns the last day of a month as a local-date.

[time/day-of-week](#)

Returns the day of the week (:MONDAY ... :SUNDAY)

[top](#)

time/not-after?

```
(time/not-after? date1 date2)
```

Returns true if date1 is not-after date2 else false (same semantics as `<=`)

```
(time/not-after? (time/local-date 2018 1 1)
                 (time/local-date 2019 1 1))
=> true
```

```
(time/not-after? (time/local-date-time "2018-01-01T10:00:00.000")
                 (time/local-date-time "2019-01-01T10:00:00.000"))
=> true
```

```
(time/not-after? (time/zoned-date-time "2018-01-01T10:00:00.000+01:00")
                 (time/zoned-date-time "2019-01-01T10:00:00.000+01:00"))
=> true
```

SEE ALSO

[time/after?](#)

Returns true if all dates are ordered from the latest to the earliest (same semantics as `>`)

[time/before?](#)

Returns true if all dates are ordered from the earliest to the latest (same semantics as `<`)

[time/not-before?](#)

Returns true if date1 is not-before date2 else false (same semantics as `>=`)

[top](#)

time/not-before?

```
(time/not-before? date1 date2)
```

Returns true if date1 is not-before date2 else false (same semantics as `>=`)

```
(time/not-before? (time/local-date 2019 1 1)
                  (time/local-date 2019 1 1))
=> true

(time/not-before? (time/local-date-time "2019-01-01T10:00:00.000")
                  (time/local-date-time "2018-01-01T10:00:00.000"))
=> true

(time/not-before? (time/zoned-date-time "2019-01-01T10:00:00.000+01:00")
                  (time/zoned-date-time "2018-01-01T10:00:00.000+01:00"))
=> true
```

SEE ALSO

[time/after?](#)

Returns true if all dates are ordered from the latest to the earliest (same semantics as >)

[time/before?](#)

Returns true if all dates are ordered from the earliest to the latest (same semantics as <)

[time/not-after?](#)

Returns true if date1 is not-after date2 else false (same semantics as <=)

[top](#)

time/period

```
(time/period from to unit)
```

Returns the period interval of two dates in the specified unit.

Units: {years :months :weeks :days :hours :minutes :seconds :milliseconds}

```
(time/period (time/local-date) (time/plus (time/local-date) :days 3) :days)
=> 3
```

```
(time/period (time/local-date-time) (time/plus (time/local-date-time) :days 3) :days)
=> 3
```

```
(time/period (time/zoned-date-time) (time/plus (time/zoned-date-time) :days 3) :days)
=> 3
```

SEE ALSO

[time/local-date](#)

Creates a new local-date. A local-date is represented by 'java.time.LocalDate'

[time/local-date-time](#)

Creates a new local-date-time. A local-date-time is represented by 'java.time.LocalDateTime'

[time/zoned-date-time](#)

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

[top](#)

time/plus

```
(time/plus date unit n)
```

(time/minus plus temporal)

Adds the n units to the date. Units: {years :months :weeks :days :hours :minutes :seconds :milliseconds}

In the two argument version add a :java.time.Temporal (Period, Duration) to the date.

```
(time/plus (time/local-date) :days 2)
```

```
=> 2024-08-29
```

```
(time/plus (time/local-date-time) :days 2)
```

```
=> 2024-08-29T22:14:08.671
```

```
(time/plus (time/zoned-date-time) :days 2)
```

```
=> 2024-08-29T22:14:08.699+02:00[Europe/Zurich]
```

```
(time/plus (time/local-date) (. :java.time.Period :ofDays 2))
```

```
=> 2024-08-29
```

```
(time/plus (time/local-date-time) (. :java.time.Period :ofDays 2))
```

```
=> 2024-08-29T22:14:08.753
```

```
(time/plus (time/zoned-date-time) (. :java.time.Period :ofDays 2))
```

```
=> 2024-08-29T22:14:08.780+02:00[Europe/Zurich]
```

SEE ALSO

[time/minus](#)

Subtracts the n units from the date. Units: {years :months :weeks :days :hours :minutes :seconds :milliseconds}

[top](#)

time/second

(time/second date)

Returns the second of the date 0..59

```
(time/second (time/local-date))
```

```
=> 0
```

```
(time/second (time/local-date-time))
```

```
=> 6
```

```
(time/second (time/zoned-date-time))
```

```
=> 7
```

SEE ALSO

[time/hour](#)

Returns the hour of the date 0..23

[time/minute](#)

Returns the minute of the date 0..59

[time/milli](#)

Returns the millis of the date 0..999

[top](#)

time/to-millis

```
(time/to-millis date)
```

Converts the passed date to milliseconds since epoch

```
(time/to-millis (time/date))
```

```
=> 1724789649152
```

```
(time/to-millis (time/local-date))
```

```
=> 1724709600000
```

```
(time/to-millis (time/local-date-time))
```

```
=> 1724789649206
```

```
(time/to-millis (time/zoned-date-time))
```

```
=> 1724789649233
```

[top](#)

time/unix-timestamp

```
(time/unix-timestamp)
```

```
(time/unix-timestamp year month day)
```

```
(time/unix-timestamp year month day hour minute second)
```

```
(time/unix-timestamp year month day hour minute second millis)
```

```
(time/unix-timestamp date)
```

Returns a unix timestamp. Seconds since Jan 01 1970 (UTC).

See: [Unix Timestamp](#)

```
(time/unix-timestamp)
```

```
=> 1724796846
```

```
(time/unix-timestamp 2018 8 1)
```

```
=> 1533081600
```

```
(time/unix-timestamp 2018 8 1 14 20 10)
```

```
=> 1533133210
```

```
(time/unix-timestamp 2018 8 1 14 20 10 200)
```

```
=> 1533133210
```

```
(time/unix-timestamp "2018-08-01T14:20:10.200")
```

```
=> 2018-08-01T14:20:10.200
```

```
(time/unix-timestamp (time/local-date-time))
```

```
=> 1724796846
```

```
(time/unix-timestamp (time/local-date 2018 8 1))
```

```
=> 1533081600
```

```
(time/unix-timestamp (. :java.util.Date :new))  
=> 1724796846
```

SEE ALSO

[time/unix-timestamp-to-local-date-time](#)

Converts a unix timestamp (seconds since Jan 01 1970 (UTC)) to a java :LocalDateTime.

[time/local-date-time](#)

Creates a new local-date-time. A local-date-time is represented by 'java.time.LocalDateTime'

[time/local-date](#)

Creates a new local-date. A local-date is represented by 'java.time.LocalDate'

[time/zoned-date-time](#)

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

[top](#)

time/unix-timestamp-to-local-date-time

```
(time/unix-timestamp-to-local-date-time seconds-since-epoch)
```

Converts a unix timestamp (seconds since Jan 01 1970 (UTC)) to a java :LocalDateTime.

See: [Unix Timestamp](#)

```
(time/unix-timestamp-to-local-date-time (time/unix-timestamp))  
=> 2024-08-27T22:14:06
```

SEE ALSO

[time/unix-timestamp](#)

Returns a unix timestamp. Seconds since Jan 01 1970 (UTC).

[top](#)

time/with-time

```
(time/with-time date hour minute second)  
(time/with-time date hour minute second millis)
```

Sets the time of a date. Returns a new date

```
(time/with-time (time/local-date) 22 00 15 333)  
=> 2024-08-27T22:00:15.333
```

```
(time/with-time (time/local-date-time) 22 00 15 333)  
=> 2024-08-27T22:00:15.333
```

```
(time/with-time (time/zoned-date-time) 22 00 15 333)  
=> 2024-08-27T22:00:15.333+02:00[Europe/Zurich]
```

SEE ALSO

[time/local-date](#)

Creates a new local-date. A local-date is represented by 'java.time.LocalDate'

[time/local-date-time](#)

Creates a new local-date-time. A local-date-time is represented by 'java.time.LocalDateTime'

[time/zoned-date-time](#)

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

[top](#)

time/within?

(time/within? date start end)

Returns true if the date is after or equal to the start and is before or equal to the end. All three dates must be of the same type. The start and end date may each be nil meaning start is -infinity and end is +infinity. (same semantics as `start <= date <= end`)

```
(time/within? (time/local-date 2018 8 15)
              (time/local-date 2018 8 10)
              (time/local-date 2018 8 20))
=> true

(time/within? (time/local-date 2018 8 25)
              (time/local-date 2018 8 10)
              (time/local-date 2018 8 20))
=> false

(time/within? (time/local-date 2018 8 20)
              (time/local-date 2018 8 10)
              nil)
=> true

(time/within? (time/local-date-time "2019-01-01T10:00:00.000")
              (time/local-date-time "2010-01-01T10:00:00.000")
              (time/local-date-time "2020-01-01T10:00:00.000"))
=> true

(time/within? (time/zoned-date-time "2010-01-01T10:00:00.000+01:00")
              (time/zoned-date-time "2019-01-01T10:00:00.000+01:00")
              (time/zoned-date-time "2020-01-01T10:00:00.000+01:00"))
=> false
```

[top](#)

time/year

(time/year date)

Returns the year of the date

```
(time/year (time/local-date))
=> 2024

(time/year (time/local-date-time))
=> 2024
```



```
(time/year (time/zoned-date-time))  
=> 2024
```

SEE ALSO

[time/month](#)

Returns the month of the date 1..12

[time/day-of-year](#)

Returns the day of the year (1..366)

[time/day-of-month](#)

Returns the day of the month (1..31)

[time/first-day-of-month](#)

Returns the first day of a month as a local-date.

[time/last-day-of-month](#)

Returns the last day of a month as a local-date.

[time/day-of-week](#)

Returns the day of the week (:MONDAY ... :SUNDAY)

[top](#)

time/zone

```
(time/zone date)
```

Returns the zone of the date

```
(time/zone (time/zoned-date-time))  
=> "Europe/Zurich"
```

[top](#)

time/zone-ids

```
(time/zone-ids)
```

Returns all available zone ids with time offset

```
(nfirst (seq (time/zone-ids)) 10)  
=> ("Africa/Abidjan" "+00:00") ("Africa/Accra" "+00:00") ("Africa/Addis_Ababa" "+03:00") ("Africa/Algiers"  
"+01:00") ("Africa/Asmara" "+03:00") ("Africa/Asmera" "+03:00") ("Africa/Bamako" "+00:00") ("Africa/Bangui"  
"+01:00") ("Africa/Banjul" "+00:00") ("Africa/Bissau" "+00:00"))
```

[top](#)

time/zone-offset

```
(time/zone-offset date)
```

Returns the zone-offset of the date in minutes

```
(time/zone-offset (time/zoned-date-time))  
=> 120
```

SEE ALSO

[time/zoned-date-time](#)

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

[top](#)

time/zoned-date-time

```
(time/zoned-date-time)  
(time/zoned-date-time year month day)  
(time/zoned-date-time year month day hour minute second)  
(time/zoned-date-time year month day hour minute second millis)  
(time/zoned-date-time date)  
(time/zoned-date-time zone-id)  
(time/zoned-date-time zone-id year month day)  
(time/zoned-date-time zone-id year month day hour minute second)  
(time/zoned-date-time zone-id year month day hour minute second millis)  
(time/zoned-date-time zone-id date)
```

Creates a new zoned-date-time. A zoned-date-time is represented by 'java.time.ZonedDateTime'

```
(time/zoned-date-time)  
=> 2024-08-27T22:14:05.473+02:00[Europe/Zurich]  
  
(time/zoned-date-time 2018 8 1)  
=> 2018-08-01T00:00+02:00[Europe/Zurich]  
  
(time/zoned-date-time 2018 8 1 14 20 10)  
=> 2018-08-01T14:20:10+02:00[Europe/Zurich]  
  
(time/zoned-date-time 2018 8 1 14 20 10 200)  
=> 2018-08-01T14:20:10.200+02:00[Europe/Zurich]  
  
(time/zoned-date-time "2018-08-01T14:20:10.200+01:00")  
=> 2018-08-01T14:20:10.200+01:00  
  
(time/zoned-date-time (time/local-date 2018 8 1))  
=> 2018-08-01T00:00+02:00[Europe/Zurich]  
  
(time/zoned-date-time (time/local-date-time 2018 8 1 14 20 10))  
=> 2018-08-01T14:20:10+02:00[Europe/Zurich]  
  
(time/zoned-date-time 1375315200000)  
=> 2013-08-01T02:00+02:00[Europe/Zurich]  
  
(time/zoned-date-time (. :java.util.Date :new))  
=> 2024-08-27T22:14:05.702+02:00[Europe/Zurich]  
  
(time/zoned-date-time "UTC")  
=> 2024-08-27T20:14:05.729Z[UTC]  
  
(time/zoned-date-time "UTC" 2018 8 1)  
=> 2018-08-01T00:00Z[UTC]
```

```

(time/zoned-date-time "UTC" 2018 8 1 14 20 10)
=> 2018-08-01T14:20:10Z[UTC]

(time/zoned-date-time "UTC" 2018 8 1 14 20 10 200)
=> 2018-08-01T14:20:10.200Z[UTC]

(time/zoned-date-time "UTC" "2018-08-01T14:20:10.200+01:00")
=> 2018-08-01T14:20:10.200Z[UTC]

(time/zoned-date-time "UTC" (time/local-date 2018 8 1))
=> 2018-08-01T00:00Z[UTC]

(time/zoned-date-time "UTC" (time/local-date-time 2018 8 1 14 20 10))
=> 2018-08-01T14:20:10Z[UTC]

(time/zoned-date-time "UTC" 1375315200000)
=> 2013-08-01T00:00Z[UTC]

(time/zoned-date-time "UTC" (. :java.util.Date :new))
=> 2024-08-27T20:14:05.961Z[UTC]

```

SEE ALSO

[time/local-date](#)

Creates a new local-date. A local-date is represented by 'java.time.LocalDate'

[time/local-date-time](#)

Creates a new local-date-time. A local-date-time is represented by 'java.time.LocalDateTime'

[top](#)

time/zoned-date-time-parse

```

(time/zoned-date-time-parse str format
(time/zoned-date-time-parse str format locale

```

Parses a zoned-date-time.

To parse a large number of dates a pre instantiated formatter delivers best performance:

```

(let [fmt (time/formatter "yyyy-MM-dd'T'HH:mm:ssz")]
  (dotimes [n 100] (time/zoned-date-time-parse "2018-12-01T14:20:01+01:00" fmt)))

```

```

(time/zoned-date-time-parse "2018-08-01T14:20:01+01:00" "yyyy-MM-dd'T'HH:mm:ssz")
=> 2018-08-01T14:20:01+01:00

```

```

(time/zoned-date-time-parse "2018-08-01T14:20:01.000+01:00" "yyyy-MM-dd'T'HH:mm:ss.SSSz")
=> 2018-08-01T14:20:01+01:00

```

```

(time/zoned-date-time-parse "2018-08-01T14:20:01.000+01:00" :iso)
=> 2018-08-01T14:20:01+01:00

```

```

(time/zoned-date-time-parse "2018-08-01 14:20:01.000 +01:00" "yyyy-MM-dd' 'HH:mm:ss.SSS' 'z")
=> 2018-08-01T14:20:01+01:00

```

[top](#)

time/zoned-date-time?

```
(time/zoned-date-time? date)
```

Returns true if date is a zoned-date-time ('java.time.ZonedDateTime') else false

```
(time/zoned-date-time? (time/zoned-date-time))  
=> true
```

[top](#)

timeout-after

```
(timeout-after p time time-unit)
```

Returns a promise that timeouts after the specified time. The promise throws a `TimeoutException`.

```
(-> (promise (fn [] (sleep 100) "The quick brown fox"))  
    (accept-either (timeout-after 500 :milliseconds)  
                  (fn [v] (println (pr-str v)))))  
  
    (deref))  
"The quick brown fox"  
=> nil  
  
(-> (promise (fn [] (sleep 1000) "The quick brown fox"))  
    (accept-either (timeout-after 500 :milliseconds)  
                  (fn [v] (println (pr-str v)))))  
  
    (deref))  
=> TimeoutException: java.util.concurrent.TimeoutException  
  
(-> (promise (fn [] (sleep 1000) "The quick brown fox"))  
    (accept-either (timeout-after 500 :milliseconds)  
                  (fn [v] (println (pr-str v)))))  
  
    (deref 2000 :timeout))  
=> :timeout  
  
(-> (promise (fn [] (sleep 200) "The quick brown fox"))  
    (apply-to-either (timeout-after 100 :milliseconds)  
                    identity)  
  
    (deref))  
=> TimeoutException: java.util.concurrent.TimeoutException
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and set, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two ...

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[then-combine](#)

Applies a function `f` to the result of the previous stage of promise `p` and the result of another promise `p-other`

[then-compose](#)

Composes the result of two promises. `f` receives the result of the first promise `p` and returns a new promise that composes that value ...

[when-complete](#)

Returns the promise `p` with the same result or exception at this stage, that executes the action `f`. Passes the current stage's result ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

timing/elapsed

```
(timing/elapsed f)
```

Runs a function `f` and returns the elapsed time in milliseconds.

```
(timing/elapsed #(sleep 500))  
=> 505
```

SEE ALSO

[timing/run](#)

Runs a function `f` with printing the elapsed time. Returns the value that `f` has produced.

[top](#)

timing/run

```
(timing/run f)  
(timing/run f start-msg)
```

Runs a function `f` with printing the elapsed time. Returns the value that `f` has produced.

```
(timing/run #(sleep 500))  
Elapsed: 505ms  
=> nil
```

```
(timing/run #(sleep 500) "Sleeping...")  
Sleeping...  
Elapsed: 505ms  
=> nil
```

SEE ALSO

[timing/elapsed](#)

Runs a function `f` and returns the elapsed time in milliseconds.

tomcat/create-servlet

(create-servlet handler-map)

Creates a servlet from a HTTP method handler map

```
;; minimal servlet
(tomcat/create-servlet
 { :doGet (fn [req res servlet] (tomcat/send-ok res "Hello World")) })

;; servlet with lifecycle and all HTTP methods
(tomcat/create-servlet
 { :init (fn [config] nil)
   :destroy (fn [servlet] nil)
   :doGet (fn [req res servlet] (tomcat/send-ok res "Hello World"))
   :doHead (fn [req res servlet] (tomcat/send-not-implemented res "HTTP Method HEAD"))
   :doPost (fn [req res servlet] (tomcat/send-not-implemented res "HTTP Method POST"))
   :doPut (fn [req res servlet] (tomcat/send-not-implemented res "HTTP Method PUT"))
   :delete (fn [req res servlet] (tomcat/send-not-implemented res "HTTP Method DELETE"))
   :getLastModified (fn [req] -1) })
```

tomcat/destroy

(destroy server)

Destroys a Tomcat server after having stopped it.

```
(do
 (load-module :tomcat ['tomcat :as 'tc])
 (let [server (tc/start (tc/hello-world-servlet)
                       {:await? false, :base-dir ".", :port 8080})]
  (tc/state server)
  (sleep 20_000)
  (tc/stop server)
  (tc/destroy server)))
```

SEE ALSO

[tomcat/start](#)

Start a Tomcat to serve given servlet with supplied options:

[tomcat/state](#)

Returns the state of a Tomcat server.

[tomcat/stop](#)

Stops a Tomcat server.

[tomcat/shutdown](#)

Shutdown a Tomcat server.

tomcat/hello-world-servlet

'Hello World' demo servlet

[top](#)

tomcat/shutdown

(shutdown server)

Shutdown a Tomcat server.

Shutdown effectively calls

- (stop server)
- (destroy server)

on the server

```
(do
  (load-module :tomcat ['tomcat :as 'tc])
  (let [server (tc/start (tc/hello-world-servlet)
                        {:await? false, :base-dir ".", :port 8080})]
    (tc/state server)
    (sleep 20_000)
    (tc/shutdown server)))
```

SEE ALSO

[tomcat/start](#)

Start a Tomcat to serve given servlet with supplied options:

[tomcat/state](#)

Returns the state of a Tomcat server.

[tomcat/stop](#)

Stops a Tomcat server.

[tomcat/destroy](#)

Destroys a Tomcat server after having stopped it.

[top](#)

tomcat/start

(start servlet options)
(start servlet context-path context-doc-base options)

Start a Tomcat to serve given servlet with supplied options:

Server options:

:base-dir	the server's base directory (default: ".")
:await?	block the thread until server get shutdown command (default: true)
:http?	create http connector (default: true)

:port	the port to listen on http connector (default: 8080)
:https?	create https connector (default: false)
:https-port	the port to listen on https connector (default: 8443)
:keystore	path to keystore file include server certificate
:key-pass	password of keystore file
:tls-hostname	hostname to listen for https connector (default: _default_)
:tls-protocol	list of SSL/TLS protocol to support for https connector (default: TLS)
:tls-ciphers	list of SSL/TLS ciphers to support for https connector
:executor?	use executor (default: true)
:executor-name	name of executor (default: tc-executor)
:max-threads	max number of threads in executor (default: 200)
:min-spare-threads	minimum number of spare threads in executor (default: 25)
:max-idle-time	max milliseconds before an idle thread shutdown (default: 60000)

| :max-post-size | max post size for file uploads. Tomcat defaults to 2MB. A value of -1 specifies a indefinite upload size

Servlet options:

:name	the servlet's name (default: "venice-servlet")
:mapping	the servlet's mapping path (default: "/*") single or multiple mappings are possible for a servlet: - single: "/employees" - multiple: ["/employees" "/employees/*"]
:async-support	if true add async support for servlet (default: false)
:load-on-startup	the load-on-startup order value, a negative value means load on first call. (default: -1)
:file-upload	if true configure as file-upload servlet (default: false)
:location	file-upload location (default: "")
:max-file-size	file-upload max file size in bytes (default: -1)
:max-request-size	file-upload max request size in bytes (default: -1)
:file-size-threshold	file-upload max file threshold in bytes (default: 0l)

```
;; Example 1:
;; start Tomcat with
;;   - a servlet
;;   - server options
(tomcat/start (tomcat/hello-world-servlet)
  {:await? false, :base-dir ".", :port 8080})
```

```
;; Example 2:
;; start Tomcat with
;;   - a servlet
;;   - web app context-path
;;   - web app context-doc-base
;;   - server options
(tomcat/start (tomcat/hello-world-servlet)
  ""
  "."
  {:await? false, :base-dir ".", :port 8080})
```

```
;; Example 3:
;; start Tomcat with
;;   - a single servlet with servlet options
;;   - web app context-path
;;   - web app context-doc-base
;;   - server options
(tomcat/start [ [ (tomcat/hello-world-servlet)
```



```

        { :name "hello-servlet" :mapping "/"* } ] ]
    ""
    "."
    { :await? false, :base-dir ".", :port 8080 } })

;; Example 4:
;; start Tomcat with
;; - a single fileupload servlet with servlet options
;; - web app context-path
;; - web app context-doc-base
;; - server options
(tomcat/start [ [ (upload-servlet)
                  { :name      "upload-servlet"
                    :mapping   "/upload"
                    :file-upload true
                    :location   "/tmp"
                    :max-file-size 10485760
                    :max-request-size 10485760
                    :file-size-threshold -1 } ] ]
    ""
    "."
    { :await? false, :base-dir ".", :port 8080 } })

```

SEE ALSO

[tomcat/state](#)

Returns the state of a Tomcat server.

[tomcat/stop](#)

Stops a Tomcat server.

[tomcat/destroy](#)

Destroys a Tomcat server after having stopped it.

[tomcat/shutdown](#)

Shutdown a Tomcat server.

[top](#)

tomcat/state

(state server)

Returns the state of a Tomcat server.

A Tomcat server state is of:

- `:NEW`
- `:INITIALIZING`
- `:INITIALIZED`
- `:STARTING_PREP`
- `:STARTING`
- `:STARTED`
- `:STOPPING_PREP`
- `:STOPPING`
- `:STOPPED`
- `:DESTROYING`
- `:DESTROYED`
- `:FAILED`

```
(do
  (load-module :tomcat ['tomcat :as 'tc])
  (let [server (tc/start (tc/hello-world-servlet)
                        {:await? false, :base-dir ".", :port 8080})]
    (tc/state server)
    (sleep 20_000)
    (tc/shutown server)))
```

SEE ALSO

[tomcat/start](#)

Start a Tomcat to serve given servlet with supplied options:

[tomcat/stop](#)

Stops a Tomcat server.

[tomcat/destroy](#)

Destroys a Tomcat server after having stopped it.

[tomcat/shutdown](#)

Shutdown a Tomcat server.

[top](#)

tomcat/stop

```
(stop server)
```

Stops a Tomcat server.

Note: Do not forget to call `destroy` on the server after having stopped it.

```
(do
  (load-module :tomcat ['tomcat :as 'tc])
  (let [server (tc/start (tc/hello-world-servlet)
                        {:await? false, :base-dir ".", :port 8080})]
    (tc/state server)
    (sleep 20_000)
    (tc/stop server)
    (tc/destroy server)))
```

SEE ALSO

[tomcat/start](#)

Start a Tomcat to serve given servlet with supplied options:

[tomcat/state](#)

Returns the state of a Tomcat server.

[tomcat/destroy](#)

Destroys a Tomcat server after having stopped it.

[tomcat/shutdown](#)

Shutdown a Tomcat server.

[top](#)

total-memory

```
(total-memory)
```

Returns the total amount of memory available to the Java VM.

```
(total-memory)
=> "2306.0MB"
```

SEE ALSO

[used-memory](#)

Returns the currently used memory by the Java VM.

[top](#)

trace/tee

```
(tee x)
```

Allows to branch off values passed to `tee` to a printer.

The form is equivalent to:

```
(tee-> x #(println "trace:" %))
```

```
(tee->> x #(println "trace:" %))
```

when used with the threading macros `->` and `->>`

```
(do
  (load-module :trace ['trace :as 't])
```

```
  (-> 5
    (+ 3)
    t/tee
    (/ 2)
    t/tee
    (- 1)))
```

```
trace: 8
```

```
trace: 4
```

```
=> 3
```

SEE ALSO

[trace/tee->](#)

Allows to branch off values passed through the forms of a `->` macro

[trace/tee->>](#)

Allows to branch off values passed through the form of a `->>` macro

[top](#)

trace/tee->

```
(tee-> x f!)
```

Allows to branch off values passed through the forms of a `->` macro

```
(do
  (load-module :trace ['trace :as 't])
```

```
(-> 5
  (+ 3)
  (t/tee-> #(println "trace:" %))
  (/ 2)
  (t/tee-> #(println "trace:" %))
  (- 1)))
trace: 8
trace: 4
=> 3
```

SEE ALSO

[trace/tee->>](#)

Allows to branch off values passed through the form of a `->>` macro

[trace/tee](#)

Allows to branch off values passed to tee to a printer.

[top](#)

trace/tee->>

```
(tee->> f! x)
```

Allows to branch off values passed through the form of a `->>` macro

```
(do
  (load-module :trace ['trace :as 't])

  (->> 5
    (+ 3)
    (t/tee->> #(println "trace:" %))
    (/ 32)
    (t/tee->> #(println "trace:" %))
    (- 1)))
trace: 8
trace: 4
=> -3
```

SEE ALSO

[trace/tee->](#)

Allows to branch off values passed through the forms of a `->` macro

[trace/tee](#)

Allows to branch off values passed to tee to a printer.

[top](#)

trace/trace

```
(trace val)
(trace name val)
```

Sends name (optional) and value to the tracer function, then returns value. May be wrapped around any expression without affecting the result.

```
(trace/trace (+ 1 2))  
TRACE: 3  
=> 3
```

```
(trace/trace "add" (+ 1 2))  
TRACE add: 3  
=> 3
```

```
(* 4 (trace/trace (+ 1 2)))  
TRACE: 3  
=> 12
```

SEE ALSO

[trace/trace-var](#)

Traces the var

[trace/trace-str-limit](#)

Manages the trace string limit for the current thread. Without argument returns the current limit. With argument sets the trace string ...

[top](#)

trace/trace-str-limit

```
(trace-str-limit)  
(trace-str-limit n)
```

Manages the trace string limit for the current thread. Without argument returns the current limit. With argument sets the trace string length limit to n. The limit defaults to 80.

```
(trace/trace-str-limit 120)  
=> 120
```

SEE ALSO

[trace/trace-var](#)

Traces the var

[trace/trace](#)

Sends name (optional) and value to the tracer function, then returns value. May be wrapped around any expression without affecting the result.

[top](#)

trace/trace-var

```
(trace-var v)
```

Traces the var

```
(do  
  (load-module :trace ['trace :as 't])  
  
  (t/trace-var +)  
  
  (+ 1 2))
```

```
TRACE t96316: (core/+ 1 2)
TRACE t96316: | => 3
=> 3

(do
  (load-module :trace ['trace :as 't])

  (defn foo [x] (+ x 2))
  (defn zoo [x] (foo x))
  (defn bar [x] (zoo x))

  (t/trace-var +)
  (t/trace-var foo)
  (t/trace-var bar)

  (bar 5))
TRACE t96345: (user/bar 5)
TRACE t96346: | (user/foo 5)
TRACE t96347: | | (core/+ 5 2)
TRACE t96347: | | | => 7
TRACE t96346: | | => 7
TRACE t96345: | => 7
=> 7

(do
  (load-module :trace ['trace :as 't])

  (defn foo [x] (/ x 0)) ;; division by zero!
  (defn bar [x] (foo x))

  (t/trace-var /)
  (t/trace-var foo)
  (t/trace-var bar)

  (bar 5))
TRACE t96376: (user/bar 5)
TRACE t96377: | (user/foo 5)
TRACE t96378: | | (core// 5 0)
TRACE t96378: | | | => com.github.jlangch.venice.VncException: / by zero
TRACE t96377: | | => com.github.jlangch.venice.VncException: / by zero
TRACE t96376: | => com.github.jlangch.venice.VncException: / by zero
=> VncException: / by zero
```

SEE ALSO

[trace/untrace-var](#)

Untraces the var

[trace/traced?](#)

Returns true if the given var is currently traced, false otherwise

[trace/traceable?](#)

Returns true if the given var can be traced, false otherwise

[trace/trace](#)

Sends name (optional) and value to the tracer function, then returns value. May be wrapped around any expression without affecting the result.

[trace/trace-str-limit](#)

Manages the trace string limit for the current thread. Without argument returns the current limit. With argument sets the trace string ...

[top](#)

trace/traceable?

```
(traceable? v)
```

Returns true if the given var can be traced, false otherwise

```
(trace/traceable? +)  
=> true
```

SEE ALSO

[trace/trace-var](#)

Traces the var

[trace/traced?](#)

Returns true if the given var is currently traced, false otherwise

[top](#)

trace/traced?

```
(traced? v)
```

Returns true if the given var is currently traced, false otherwise

```
(trace/traced? +)  
=> false
```

SEE ALSO

[trace/trace-var](#)

Traces the var

[trace/untrace-var](#)

Untraces the var

[trace/traceable?](#)

Returns true if the given var can be traced, false otherwise

[trace/trace](#)

Sends name (optional) and value to the tracer function, then returns value. May be wrapped around any expression without affecting the result.

[top](#)

trace/untrace-var

```
(untrace-var v)
```

Untraces the var

```
(trace/untrace-var +)  
=> nil
```

SEE ALSO

[trace/trace-var](#)

Traces the var

trace/traced?

Returns true if the given var is currently traced, false otherwise

top

trampoline

```
(trampoline f)
(trampoline f & args)
```

trampoline can be used to convert algorithms requiring mutual recursion without stack consumption. Calls f with supplied args, if any. If f returns a fn, calls that fn with no arguments, and continues to repeat, until the return value is not a fn, then returns that non-fn value.

Note that if you want to return a fn as a final value, you must wrap it in some data structure and unpack it after trampoline returns.

```
(do
  (defn factorial
    ([n] #(factorial n 1N))
    ([n acc] (if (< n 2)
               acc
               #(factorial (dec n) (* acc n)))))

  (trampoline (factorial 20)))
=> 2432902008176640000N
```

top

transduce

```
(transduce xform f coll)
(transduce xform f init coll)
```

Reduce with a transformation of a reduction function f (xf). If init is not supplied, (f) will be called to produce it. f should be a reducing step function that accepts both 1 and 2 arguments. Returns the result of applying (the transformed) xf to init and the first item in coll, then applying xf to that result and the 2nd item, etc. If coll contains no items, returns init and f is not called.

transduce can work with queues as collection, given that the end of the queue is marked by adding a nil element. Otherwise the transducer does not know when to stop reading elements from the queue.

Transformations		Reductions	Control
-----		-----	-----
map	map-indexed	rf-first	halt-when
filter	flatten	rf-last	
drop	drop-while	rf-any?	
drop-last	remove	rf-every?	
take	take-while		
take-last	keep	conj	
dedupe	distinct	+, *	
sorted	reverse	max, min	

```
(transduce identity + [1 2 3 4])
=> 10
```

```
(transduce (map #(+ % 3)) + [1 2 3 4])
=> 22
```



```

(transduce identity max [1 2 3])
=> 3

(transduce identity rf-last [1 2 3])
=> 3

(transduce identity (rf-every? pos?) [1 2 3])
=> true

(transduce (map inc) conj [1 2 3])
=> [2 3 4]

;; transduce all elements of a queue.
;; calls (take! queue) to get the elements of the queue.
;; note: use nil to mark the end of the queue otherwise
;;       transduce will block forever!
(let [q (conj! (queue) 1 2 3 nil)]
  (transduce (map inc) conj q))
=> [2 3 4]

;; reduce data supplied by a finit lazy seq
(do
  (def counter (atom 5))
  (defn generate []
    (swap! counter dec)
    (if (pos? @counter) @counter nil))
  (transduce (map inc) conj (lazy-seq generate)))
=> [5 4 3 2]

(do
  (def xform (comp (drop 2) (take 3)))
  (transduce xform conj [1 2 3 4 5 6]))
=> [3 4 5]

(do
  (def xform (comp
    (map #(* % 10))
    (map #(+ % 1))
    (sorted compare)
    (drop 3)
    (take 2)
    (reverse)))
  (transduce xform conj [1 2 3 4 5 6]))
=> [51 41]

```

top

true?

```
(true? x)
```

Returns true if x is true, false otherwise

```
(true? true)
=> true
```

```
(true? false)
=> false

(true? nil)
=> false

(true? 0)
=> false

(true? (== 1 1))
=> true
```

SEE ALSO

[false?](#)

Returns true if x is false, false otherwise

[not](#)

Returns true if x is logical false, false otherwise.

[top](#)

try

```
(try expr*)
(try expr* (catch selector ex-sym expr*)*)
(try expr* (catch selector ex-sym expr*)* (finally expr*))
```

Exception handling: try - catch - finally

`(try)` without any expression returns `nil`.

The exception types

- `:java.lang.Exception`
- `:java.lang.RuntimeException`
- `:com.github.jlangch.venice.VncException`
- `:com.github.jlangch.venice.ValueException`

are imported implicitly so its alias `:Exception`, `:RuntimeException`, `:VncException`, and `:ValueException` can be used as selector without an import of the class.

Selectors

- a class: (e.g., `:RuntimeException`, `:java.text.ParseException`), matches any instance of that class
- a key-values vector: (e.g., `[key val & kvs]`), matches any instance of `:ValueException` where the exception's value meets the expression
(and `(= (get ex-value key) val) ...`)
- a predicate: (a function of one argument like `map?`, `set?`), matches any instance of `:ValueException` where the predicate applied to the exception's value returns true

Notes:

The finally block is just for side effects, like closing resources. It never returns a value!

All exceptions in Venice are *unchecked*. If *checked* exceptions are thrown in Venice they are immediately wrapped in a `:RuntimeException` before being thrown! If Venice catches a *checked* exception from a Java interop call it wraps it in a `:RuntimeException` before handling it by the catch block selectors.

Venice follows the Java rules when propagating exceptions:

1. exception from finally block

2. exception from catch block
3. exception from body block

```
(try
  (throw "test")
  (catch :ValueException e
    "caught ~(ex-value e)"))
=> "caught test"

(try
  (throw 100)
  (catch :Exception e -100))
=> -100

(try
  (throw 100)
  (catch :ValueException e (ex-value e))
  (finally (println "...finally")))
...finally
=> 100

(try
  (throw (ex :RuntimeException "message"))
  (catch :RuntimeException e (ex-message e)))
=> "message"

;; exception type selector:
(try
  (throw [1 2 3])
  (catch :ValueException e (ex-value e))
  (catch :RuntimeException e "runtime ex")
  (finally (println "...finally")))
...finally
=> [1 2 3]

;; key-value selector:
(try
  (throw {:a 100, :b 200})
  (catch [:a 100] e
    (println "ValueException, value: ~(ex-value e)"))
  (catch [:a 100, :b 200] e
    (println "ValueException, value: ~(ex-value e)")))
ValueException, value: {:a 100 :b 200}
=> nil

;; key-value selector (exception cause):
(try
  (throw (ex :java.io.IOException "failure"))
  (catch [:cause-type :java.io.IOException] e
    (println "IOException, msg: ~(ex-message (ex-cause e))"))
  (catch :RuntimeException e
    (println "RuntimeException, msg: ~(ex-message e)")))
IOException, msg: failure
=> nil

;; predicate selector:
(try
  (throw {:a 100, :b 200})
  (catch long? e
    (println "ValueException, value: ~(ex-value e)"))
  (catch map? e
```

```

    (println "ValueException, value: ~(ex-value e)")
    (catch #(and (map? %) (= 100 (:a %))) e
      (println "ValueException, value: ~(ex-value e))))
ValueException, value: {:a 100 :b 200}
=> nil

;; predicate selector with custom types:
(do
  (deftype :my-exception1 [message :string, position :long])
  (deftype :my-exception2 [message :string])

  (try
    (throw (my-exception1. "error" 100))
    (catch my-exception1? e
      (println (:value e)))
    (catch my-exception2? e
      (println (:value e)))))
{:custom-type* :user/my-exception1 :message error :position 100}
=> nil

```

SEE ALSO

[try-with](#)

try-with-resources allows the declaration of resources to be used in a try block with the assurance that the resources will be closed ...

[throw](#)

Throws an exception.

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of :java.lang.Exception

[top](#)

try-acquire

```

(try-acquire lock)
(try-acquired lock timeout time-unit)

```

Acquires a lock within the given timeout time. Without a timeout returns immediately if the lock is not available.

Returns `true` if the lock could be acquired within the given time else `false` .

```

(let [l (lock)]
  (when (try-acquire l)
    ;; do something
    (release l)))
=> nil

(let [l (lock)]
  (when (try-acquire l 3 :seconds)
    ;; do something
    (release l)))
=> nil

```

SEE ALSO

[lock](#)

Creates a new lock object.

[acquire](#)

Acquires a lock, blocking until the lock is available.

[release](#)

Releases a lock.

[locked?](#)

Returns true if the lock is in use else false.

[top](#)

try-with

```
(try-with [bindings*] expr*)
(try-with [bindings*] expr* (catch selector ex-sym expr*)*)
(try-with [bindings*] expr* (catch selector ex-sym expr*)* (finally expr))
```

try-with-resources allows the declaration of resources to be used in a try block with the assurance that the resources will be closed after execution of that block. The resources declared must implement the `Closeable` or `AutoCloseable` interface.

Venice follows the Java rules when propagating exceptions:

1. exception from finally block
2. exception from catch block
3. exception from body block
4. exception from resource auto-close

```
(do
  (let [file (io/temp-file "test-", ".txt")]
    (io/spit file "123456789" :append true)
    (try-with [is (io/file-in-stream file)]
      (io/slurp-stream is :binary false))))
=> "123456789"
```

SEE ALSO

[try](#)

Exception handling: try - catch - finally

[throw](#)

Throws an exception.

[ex](#)

Creates an exception of type class with optional args. The class must be a subclass of `:java.lang.Exception`

[top](#)

type

```
(type x)
```

Returns the type of x.

```
(type 5)
=> :core/long
```

```
(type [1 2])
=> :core/vector
```

```
(type (. :java.math.BigInteger :valueOf 100))  
=> :java.math.BigInteger
```

SEE ALSO

[supertype](#)

Returns the super type of x.

[supertypes](#)

Returns the super types of x.

[instance-of?](#)

Returns true if x is an instance of the given type

[top](#)

union

```
(union s1)  
(union s1 s2)  
(union s1 s2 & sets)
```

Return a set that is the union of the input sets

```
(union (set 1 2 3))  
=> #{1 2 3}
```

```
(union (set 1 2) (set 2 3))  
=> #{1 2 3}
```

```
(union (set 1 2 3) (set 1 2) (set 1 4) (set 3))  
=> #{1 2 3 4}
```

SEE ALSO

[difference](#)

Return a set that is the first set without elements of the remaining sets

[intersection](#)

Return a set that is the intersection of the input sets

[cons](#)

Returns a new collection where x is the first element and coll is the rest.

[conj](#)

Returns a new collection with the x, xs 'added'. (conj nil item) returns (item) and (conj item) returns item.

[disj](#)

Returns a new set with the x, xs removed.

[top](#)

update

```
(update m k f)  
(update m k f & fargs)
```

Updates a value in an associative structure, where `k` is a key and `f` is a function that will take the old value and any supplied fargs and return the new value. Returns a new structure.

If the key does not exist, `nil` is passed as the old value. The optional fargs are passed to the function `f` as `(f old-value (f old-value arg1 arg2 ...) ...)`.

```
(update [] 0 (fn [x] 5))  
=> [5]
```

```
(update [0 1 2] 0 (fn [x] 5))  
=> [5 1 2]
```

```
(update [0 1 2] 1 (fn [x] (+ x 3)))  
=> [0 4 2]
```

```
(update {} :a (fn [x] 5))  
=> {:a 5}
```

```
(update {:a 0} :b (fn [x] 5))  
=> {:a 0 :b 5}
```

```
(update {:a 0 :b 1} :a (fn [x] (+ x 5)))  
=> {:a 5 :b 1}
```

```
(update [0 1 2] 1 + 3)  
=> [0 4 2]
```

```
(update {:a 0 :b 1} :b * 4)  
=> {:a 0 :b 4}
```

SEE ALSO

[assoc](#)

When applied to a map, returns a new map of the same type, that contains the mapping of key(s) to val(s). When applied to a vector, ...

[dissoc](#)

Returns a new coll of the same type, that does not contain a mapping for key(s)

[top](#)

update!

```
(update! m k f & fargs)
```

Updates a value in a mutable associative structure, where `k` is a key and `f` is a function that will take the old value and any supplied fargs and return the new value. Returns a new structure.

If the key does not exist, `nil` is passed as the old value. The optional fargs are passed to the function `f` as `(f old-value arg1 arg2 ...)`.

```
(update! (mutable-vector) 0 (fn [x] 5))  
=> [5]
```

```
(update! (mutable-vector 0 1 2) 0 (fn [x] 5))  
=> [5 1 2]
```

```
(update! (mutable-vector 0 1 2) 0 (fn [x] (+ x 1)))  
=> [1 1 2]
```

```
(update! (mutable-map) :a (fn [x] 5))
=> {:a 5}

(update! (mutable-map :a 0) :b (fn [x] 5))
=> {:a 0 :b 5}

(update! (mutable-map :a 0 :b 1) :a (fn [x] 5))
=> {:a 5 :b 1}

(update! (mutable-vector 0 1 2) 0 + 4)
=> [4 1 2]

(update! (mutable-map :a 0 :b 1) :b * 4)
=> {:a 0 :b 4}
```

SEE ALSO

[assoc!](#)

Associates key/vals with a mutable map, returns the map

[dissoc!](#)

Dissociates keys from a mutable map, returns the map

[top](#)

update-in

```
(update-in [m ks f & fargs])
```

Updates' a value in a nested associative structure, where ks is a sequence of keys and f is a function that will take the old value and any supplied fargs and return the new value, and returns a new nested structure.

If any levels do not exist, hash-maps will be created.

```
(do
  (def users [ {:name "James" :age 26}
                {:name "John" :age 43} ])
  (update-in users [1 :age] inc))
=> [{:name "James" :age 26} {:name "John" :age 44}]

(update-in {:a 12} [:a] * 4)
=> {:a 48}

(update-in {:a 12} [:a] + 3 4)
=> {:a 19}
```

[top](#)

used-memory

```
(used-memory)
```

Returns the currently used memory by the Java VM.


```
(used-memory)
=> "297.9MB"
```

SEE ALSO

[total-memory](#)

Returns the total amount of memory available to the Java VM.

top

user-name

```
(user-name)
```

Returns the logged-in's user name.

```
(user-name)
=> "juerg"
```

SEE ALSO

[io/user-home-dir](#)

Returns the user's home dir as a java.io.File.

top

uuid

```
(uuid)
```

Generates a UUID.

```
(uuid)
=> "7be302d6-bbd9-43e0-a107-071ef06d1bd8"
```

top

val

```
(val e)
```

Returns the val of the map entry.

```
(val (find {:a 1 :b 2} :b))
=> 2
```

```
(val (first (entries {:a 1 :b 2 :c 3})))
=> 1
```

SEE ALSO

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[entries](#)

Returns a collection of the map's entries.

[key](#)

Returns the key of the map entry.

[vals](#)

Returns a collection of the map's values.

[top](#)

vals

```
(vals map)
```

Returns a collection of the map's values.

Please note that the functions 'keys' and 'vals' applied to the same map are not guaranteed not return the keys and vals in the same order!

To achieve this, keys and vals can be calculated based on the map's entry list:

```
(let [e (entries {:a 1 :b 2 :c 3})]  
  (println (map key e))  
  (println (map val e)))
```

```
(vals {:a 1 :b 2 :c 3})  
=> (1 2 3)
```

SEE ALSO

[keys](#)

Returns a collection of the map's keys.

[entries](#)

Returns a collection of the map's entries.

[map](#)

Applies f to the set of first items of each coll, followed by applying f to the set of second items in each coll, until any one of the ...

[top](#)

var-get

```
(var-get v)
```

Returns a var's value.

The var must exist (bound with a value) otherwise nil is returned.

```
(var-get +)  
=> +
```

```
(var-get '+)  
=> +
```

```
(var-get (symbol "+"))  
=> +
```

```
((var-get +) 1 2)
=> 3
```

```
(do
  (def x 10)
  (var-get 'x))
=> 10
```

SEE ALSO

[var-sym](#)

Returns the var's symbol.

[var-name](#)

Returns the unqualified name of the var's symbol.

[var-ns](#)

Returns the namespace of the var's symbol.

[var-val-meta](#)

Returns the var's value meta data.

[var-local?](#)

Returns true if the var is local else false

[var-global?](#)

Returns true if the var is global else false

[var-thread-local?](#)

Returns true if the var is thread-local else false

[top](#)

var-global?

```
(var-global? v)
```

Returns true if the var is global else false

```
(var-global? +)
=> true
```

```
(var-global? '+)
=> true
```

```
(var-global? (symbol "+"))
=> true
```

```
(do
  (def x 10)
  (var-global? x))
=> true
```

```
(let [x 10]
  (var-global? x))
=> false
```

SEE ALSO

[var-get](#)

Returns a var's value.

[var-name](#)

Returns the unqualified name of the var's symbol.

[var-ns](#)

Returns the namespace of the var's symbol.

[var-local?](#)

Returns true if the var is local else false

[var-thread-local?](#)

Returns true if the var is thread-local else false

[bound?](#)

Returns true if the symbol is bound to a value else false

[top](#)

var-local?

```
(var-local? v)
```

Returns true if the var is local else false

```
(var-local? +)
```

```
=> true
```

```
(var-local? '+)
```

```
=> true
```

```
(var-local? (symbol "+"))
```

```
=> true
```

```
(let [x 10]  
  (var-local? x))
```

```
=> true
```

```
(do  
  (def x 10)  
  (var-local? x))
```

```
=> false
```

SEE ALSO

[var-get](#)

Returns a var's value.

[var-name](#)

Returns the unqualified name of the var's symbol.

[var-ns](#)

Returns the namespace of the var's symbol.

[var-global?](#)

Returns true if the var is global else false

[var-thread-local?](#)

Returns true if the var is thread-local else false

[bound?](#)

Returns true if the symbol is bound to a value else false

var-name

```
(var-name v)
```

Returns the unqualified name of the var's symbol.

The var must exist (bound with a value) otherwise nil is returned.

```
(var-name +)  
=> "+"
```

```
(var-name '+)  
=> "+"
```

```
(var-name (symbol "+"))  
=> "+"
```

```
;; aliased function  
(do  
  (ns foo)  
  (def add +)  
  (var-name add))  
=> "add"
```

```
(do  
  (def x 10)  
  (var-name x))  
=> "x"
```

```
(let [x 10]  
  (var-name x))  
=> "x"
```

```
;; compare with name  
(do  
  (ns foo)  
  (def add +)  
  (name add))  
=> "+"
```

```
;; compare aliased function with name  
(do  
  (ns foo)  
  (def add +)  
  (name add))  
=> "+"
```

SEE ALSO

[name](#)

Returns the name string of a string, symbol, keyword, or function. If applied to a string it returns the string itself.

[var-get](#)

Returns a var's value.

[var-sym](#)

Returns the var's symbol.

`var-ns`

Returns the namespace of the var's symbol.

`var-sym-meta`

Returns the var's symbol meta data.

`var-local?`

Returns true if the var is local else false

`var-global?`

Returns true if the var is global else false

`var-thread-local?`

Returns true if the var is thread-local else false

[top](#)

`var-ns`

```
(var-ns v)
```

Returns the namespace of the var's symbol.

The var must exist (bound with a value) otherwise nil is returned.

```
(var-ns +)
```

```
=> "core"
```

```
(var-ns '+)
```

```
=> "core"
```

```
(var-ns (symbol "+"))
```

```
=> "core"
```

```
;; aliased function
```

```
(do
```

```
  (ns foo)
```

```
  (def add +)
```

```
  (var-ns add))
```

```
=> "foo"
```

```
(do
```

```
  (def x 10)
```

```
  (var-ns x))
```

```
=> "user"
```

```
(let [x 10]
```

```
  (var-ns x))
```

```
=> nil
```

```
;; compare with namespace
```

```
(do
```

```
  (ns foo)
```

```
  (def add +)
```

```
  (namespace add))
```

```
=> nil
```

```
;; compare aliased function with namespace
```

```
(do
```

```
  (ns foo)
```

```
(def add +)
(namespace add)
=> nil
```

SEE ALSO

[namespace](#)

Returns the namespace string of a symbol, keyword, or function. If x is a registered namespace returns x.

[var-get](#)

Returns a var's value.

[var-name](#)

Returns the unqualified name of the var's symbol.

[var-local?](#)

Returns true if the var is local else false

[var-global?](#)

Returns true if the var is global else false

[var-thread-local?](#)

Returns true if the var is thread-local else false

[top](#)

var-sym

```
(var-sym v)
```

Returns the var's symbol.

The var must exist (bound with a value) otherwise nil is returned.

```
(var-sym +)
=> core/+
```

```
(var-sym '+)
=> core/+
```

```
(var-sym (symbol "+"))
=> core/+
```

```
(do
  (ns test)
  (defn x [] nil)
  (var-sym x))
=> test/x
```

```
(let [x 100] (var-sym x))
=> x
```

```
(binding [x 100] (var-sym x))
=> x
```

```
(do
  (defn foo [x] (var-sym x))
  (foo nil))
=> x
```

SEE ALSO

[var-get](#)

Returns a var's value.

[var-name](#)

Returns the unqualified name of the var's symbol.

[var-ns](#)

Returns the namespace of the var's symbol.

[var-sym-meta](#)

Returns the var's symbol meta data.

[var-local?](#)

Returns true if the var is local else false

[var-global?](#)

Returns true if the var is global else false

[var-thread-local?](#)

Returns true if the var is thread-local else false

[top](#)

var-sym-meta

```
(var-sym-meta v)
```

Returns the var's symbol meta data.

The var must exist (bound with a value) otherwise nil is returned.

```
(do
  (def ^{:foo 3} x 100)
  (:foo (var-sym-meta 'x)))
=> 3

(do
  (let [^{:foo 3} x 100]
    (:foo (var-sym-meta 'x))))
=> 3

(do
  (defn bar [^{:foo 3} x]
    (:foo (var-sym-meta 'x)))
  (bar 100))
=> 3
```

SEE ALSO

[var-val-meta](#)

Returns the var's value meta data.

[var-get](#)

Returns a var's value.

[var-sym](#)

Returns the var's symbol.

[var-name](#)

Returns the unqualified name of the var's symbol.

[bound?](#)

Returns true if the symbol is bound to a value else false

[top](#)

var-thread-local?

```
(var-thread-local? v)
```

Returns true if the var is thread-local else false

```
(binding [x 100]
  (var-thread-local? x))
=> true
```

SEE ALSO

[var-get](#)

Returns a var's value.

[var-name](#)

Returns the unqualified name of the var's symbol.

[var-ns](#)

Returns the namespace of the var's symbol.

[var-local?](#)

Returns true if the var is local else false

[var-global?](#)

Returns true if the var is global else false

[bound?](#)

Returns true if the symbol is bound to a value else false

[top](#)

var-val-meta

```
(var-val-meta v)
```

Returns the var's value meta data.

The var must exist (bound with a value) otherwise nil is returned.

```
(do
  (def x ^{:foo 4} 100)
  (:foo (var-val-meta 'x)))
=> 4
```

```
(do
  (def x (vary-meta 100 assoc :foo 4))
  (:foo (var-val-meta 'x)))
=> 4
```

```
(do
  (let [x ^{:foo 4} 100]
    (:foo (var-val-meta 'x))))
=> 4

(do
  (defn bar [x]
    (:foo (var-val-meta 'x)))
  (bar (vary-meta 100 assoc :foo 4)))
=> 4
```

SEE ALSO

[var-sym-meta](#)

Returns the var's symbol meta data.

[var-get](#)

Returns a var's value.

[var-sym](#)

Returns the var's symbol.

[var-name](#)

Returns the unqualified name of the var's symbol.

[bound?](#)

Returns true if the symbol is bound to a value else false

[top](#)

vary-meta

```
(vary-meta obj f & args)
```

Returns a copy of the object obj, with (apply f (meta obj) args) as its metadata.

```
(meta (vary-meta [1 2] assoc :foo 3))
=> {:foo 3 :line 56 :column 28 :file "example"}
```

SEE ALSO

[meta](#)

Returns the metadata of obj, returns nil if there is no metadata.

[with-meta](#)

Returns a copy of the object obj, with a map m as its metadata.

[var-val-meta](#)

Returns the var's value meta data.

[var-sym-meta](#)

Returns the var's symbol meta data.

[top](#)

vector

```
(vector & items)
```

Creates a new vector containing the items.

```
(vector)
=> []

(vector 1 2 3)
=> [1 2 3]

(vector 1 2 3 [:a :b])
=> [1 2 3 [:a :b]]

(vector "abc")
=> ["abc"]
```

[top](#)

vector*

```
(vector* args)
(vector* a args)
(vector* a b args)
(vector* a b c args)
(vector* a b c d & more)
```

Creates a new vector containing the items prepended to the rest, the last of which will be treated as a collection.

```
(vector* 1 [2 3])
=> [1 2 3]

(vector* 1 2 3 [4])
=> [1 2 3 4]

(vector* 1 2 3 '(4 5))
=> [1 2 3 4 5]

(vector* '[1 2] 3 [4])
=> [[1 2] 3 4]

(vector* nil)
=> nil

(vector* nil [2 3])
=> [nil 2 3]

(vector* 1 2 nil)
=> (1 2)
```

SEE ALSO

[cons](#)

Returns a new collection where x is the first element and coll is the rest.

[conj](#)

Returns a new collection with the x, xs 'added'. (conj nil item) returns (item) and (conj item) returns item.

[concat](#)

Returns a list of the concatenation of the elements in the supplied collections.

list*

Creates a new list containing the items prepended to the rest, the last of which will be treated as a collection.

[top](#)

vector?

(vector? obj)

Returns true if obj is a vector

```
(vector? (vector 1 2))  
=> true
```

```
(vector? [1 2])  
=> true
```

[top](#)

version

(version)

Returns the Venice version.

```
(version)  
=> "0.0.0"
```

[top](#)

volatile

(volatile x)

Creates a volatile with the initial value x

```
(do  
  (def counter (volatile 0))  
  (swap! counter inc)  
  (deref counter))  
=> 1
```

```
(do  
  (def counter (volatile 0))  
  (reset! counter 9)  
  @counter)  
=> 9
```

SEE ALSO

[deref](#)

Dereferences an atom, a future or a promise object. When applied to an atom, returns its current state. When applied to a future, will ...

[reset!](#)

Sets the value of an atom or a volatile to newval without regard for the current value. Returns newval.

[swap!](#)

Atomically swaps the value of an atom or a volatile to be: (apply f current-value-of-box args). Note that f may be called multiple ...

[top](#)

volatile?

```
(volatile? x)
```

Returns true if x is a volatile, otherwise false

```
(do
  (def counter (volatile 0))
  (volatile? counter))
=> true
```

[top](#)

when

```
(when test & body)
```

Evaluates test. If logical true, evaluates body in an implicit do.

```
(when (== 1 1) true)
=> true
```

SEE ALSO

[when-not](#)

Evaluates test. If logical false, evaluates body in an implicit do.

[when-let](#)

bindings is a vector with 2 elements: binding-form test.

[if](#)

Evaluates test. If logical true, evaluates and returns then expression, otherwise else expression, if supplied, else nil.

[if-not](#)

Evaluates test. If logical false, evaluates and returns then expression, otherwise else expression, if supplied, else nil.

[if-let](#)

bindings is a vector with 2 elements: binding-form test.

[top](#)

when-complete

```
(when-complete p f)
```

Returns the promise p with the same result or exception at this stage, that executes the action f. Passes the current stage's result value as first and a possible exception as second argument to the function. The asynchronous function f is called presumably for handling side effects.

```
(-> (promise (fn [] "The Quick Brown Fox"))
    (then-apply str/upper-case)
    (when-complete (fn [v,e] (println (pr-str {:value v :ex e}))))
    (then-apply str/lower-case)
    (deref))
{:value "THE QUICK BROWN FOX" :ex nil}
=> "the quick brown fox"
```

SEE ALSO

[promise](#)

Returns a promise object that can be read with `deref`, and `set`, once only, with `deliver`. Calls to `deref` prior to delivery will block, ...

[then-accept](#)

Returns a new promise that, when this promise completes normally, is executing the function `f` with this stage's result as the argument.

[then-accept-both](#)

Returns a new promise that, when either this or the other given promise completes normally, is executing the function `f` with the two ...

[then-apply](#)

Applies a function `f` on the result of the previous stage of the promise `p`.

[then-combine](#)

Applies a function `f` to the result of the previous stage of promise `p` and the result of another promise `p-other`

[then-compose](#)

Composes the result of two promises. `f` receives the result of the first promise `p` and returns a new promise that composes that value ...

[accept-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[apply-to-either](#)

Returns a new promise that, when either this or the other given promise completes normally, is executed with the corresponding result ...

[or-timeout](#)

Exceptionally completes the promise with a `TimeoutException` if not otherwise completed before the given timeout.

[complete-on-timeout](#)

Completes the promise with the given value if not otherwise completed before the given timeout.

[top](#)

when-let

```
(when-let bindings & body)
```

`bindings` is a vector with 2 elements: binding-form test.

If test is true, evaluates the body expressions with binding-form bound to the value of test, if not, yields nil

```
(when-let [value (* 100 2)]
  (str "The expression is true. value=" value))
=> "The expression is true. value=200"
```

SEE ALSO

[if-let](#)

`bindings` is a vector with 2 elements: binding-form test.

[let](#)

Evaluates the expressions and binds the values to symbols in the new local context.

when-not

```
(when-not test & body)
```

Evaluates test. If logical false, evaluates body in an implicit do.

```
(when-not (== 1 2) true)
=> true
```

SEE ALSO

[when](#)

Evaluates test. If logical true, evaluates body in an implicit do.

[when-let](#)

bindings is a vector with 2 elements: binding-form test.

[if](#)

Evaluates test. If logical true, evaluates and returns then expression, otherwise else expression, if supplied, else nil.

[if-not](#)

Evaluates test. If logical false, evaluates and returns then expression, otherwise else expression, if supplied, else nil.

[if-let](#)

bindings is a vector with 2 elements: binding-form test.

while

```
(while test & body)
```

Repeatedly executes body while test expression is true. Presumes some side-effect will cause test to become false/nil. Returns nil.

```
(do
  (def a (atom 5))
  (while (pos? @a)
    (println @a)
    (swap! a dec)))
5
4
3
2
1
=> nil
```

with-err-str

```
(with-err-str & forms)
```

Evaluates exprs in a context in which `*err*` is bound to a capturing output stream. Returns the string created by any nested printing calls. `with-err-str` can be nested.

```
(with-err-str (println *err* "a string"))  
=> "a string\n"
```

SEE ALSO

[with-out-str](#)

Evaluates exprs in a context in which `*out*` is bound to a capturing output stream. Returns the string created by any nested printing ...

[top](#)

with-meta

```
(with-meta obj m)
```

Returns a copy of the object `obj`, with a map `m` as its metadata.

```
(meta (with-meta [1 2] {:foo 3}))  
=> {:foo 3}
```

SEE ALSO

[meta](#)

Returns the metadata of `obj`, returns nil if there is no metadata.

[vary-meta](#)

Returns a copy of the object `obj`, with `(apply f (meta obj) args)` as its metadata.

[var-val-meta](#)

Returns the var's value meta data.

[var-sym-meta](#)

Returns the var's symbol meta data.

[top](#)

with-out-str

```
(with-out-str & forms)
```

Evaluates exprs in a context in which `*out*` is bound to a capturing output stream. Returns the string created by any nested printing calls. `with-out-str` can be nested.

```
(with-out-str (println "a string"))  
=> "a string\n"
```

SEE ALSO

[with-err-str](#)

Evaluates exprs in a context in which `*err*` is bound to a capturing output stream. Returns the string created by any nested printing ...

[top](#)

with-sh-dir

```
(with-sh-dir dir & forms)
```

Sets the directory for use with sh, see sh for details.

```
(with-sh-dir "/tmp" (sh "ls" "-l"))
```

SEE ALSO

[sh](#)

Launches a new sub-process.

[with-sh-env](#)

Sets the environment for use with sh.

[with-sh-throw](#)

Shell commands executed within a with-sh-throw context throw an exception if the spawned shell process returns an exit code other than 0.

[top](#)

with-sh-env

```
(with-sh-env env & forms)
```

Sets the environment for use with `sh`.

```
(with-sh-env {"NAME" "foo"} (sh "ls" "-l"))
```

SEE ALSO

[sh](#)

Launches a new sub-process.

[with-sh-dir](#)

Sets the directory for use with sh, see sh for details.

[with-sh-throw](#)

Shell commands executed within a with-sh-throw context throw an exception if the spawned shell process returns an exit code other than 0.

[top](#)

with-sh-throw

```
(with-sh-throw forms)
```

Shell commands executed within a `with-sh-throw` context throw an exception if the spawned shell process returns an exit code other than 0.

For use with `sh`, see sh for details. `with-sh-throw` can be nested.

```
(with-sh-throw (sh "ls" "-l"))
```

SEE ALSO

[sh](#)

Launches a new sub-process.

[with-sh-env](#)

Sets the environment for use with sh.

[with-sh-dir](#)

Sets the directory for use with sh, see sh for details.

[top](#)

xml/children

(xml/children nodes)

Returns the children of the XML nodes collection

```
(do
  (load-module :xml)
  (xml/children
    (list (xml/parse-str "<a><b>B</b></a>"))))
=> ({:content ["B"] :tag "b"})
```

[top](#)

xml/parse

(xml/parse s)
(xml/parse s handler)

Parses and loads the XML from the source s with the parser XMLHandler handler. The source may be an InputSource or an InputStream.

Returns a tree of XML element maps with the keys :tag, :attrs, and :content.

[top](#)

xml/parse-str

(xml/parse-str s)
(xml/parse-str s handler)

Parses an XML from the string s. Returns a tree of XML element maps with the keys :tag, :attrs, and :content.

```
(do
  (load-module :xml)
  (xml/parse-str "<a><b>B</b></a>"))
=> {:content [{:content ["B"] :tag "b"}] :tag "a"}
```

[top](#)

xml/path->

```
(xml/path-> path nodes)
```

Applies the path to a node or a collection of nodes

```
(do
  (load-module :xml)
  (let [nodes (xml/parse-str "<a><b><c>C</c></b></a>")
        path [(xml/tag= "b")
              (xml/tag= "c")
              xml/text
              first]]
    (xml/path-> path nodes)))
=> "C"
```

[top](#)

xml/text

```
(xml/text nodes)
```

Returns a list of text contents of the XML nodes collection

```
(do
  (load-module :xml)
  (let [nodes (xml/parse-str "<a><b>B</b></a>")
        path [(xml/tag= "b")
              xml/text]]
    (xml/path-> path nodes)))
=> ("B")
```

[top](#)

zero?

```
(zero? x)
```

Returns true if x zero else false

```
(zero? 0)
=> true
```

```
(zero? 2)
=> false
```

```
(zero? 0I)
=> true
```

```
(zero? 0.0F)
=> true
```

```
(zero? 0.0)
=> true
```

```
(zero? 0.0M)
=> true
```

SEE ALSO

[neg?](#)

Returns true if x smaller than zero else false

[pos?](#)

Returns true if x greater than zero else false

[top](#)

zipmap

```
(zipmap keys vals)
```

Returns a map with the keys mapped to the corresponding vals.

To create a list of tuples from two or more lists use

```
(map list '(1 2 3) '(4 5 6)) .
```

```
(zipmap [:a :b :c :d :e] [1 2 3 4 5])
=> {:a 1 :b 2 :c 3 :d 4 :e 5}
```

```
(zipmap [:a :b :c] [1 2 3 4 5])
=> {:a 1 :b 2 :c 3}
```

[top](#)

zipvault/add-files

```
(zipvault/add-files zip passphrase & files)
```

Adds a list of files to the zip.

```
(do
  (load-module :zipvault)

  (let [zip (io/file "vault.zip")
        tmp-1 (io/file (io/tmp-dir) "a1.txt")
        tmp-2 (io/file (io/tmp-dir) "a2.txt")]
    (io/spit tmp-1 "1234")
    (io/spit tmp-2 "2345")
    (io/delete-file-on-exit tmp-1)
    (io/delete-file-on-exit tmp-2)

    (zipvault/zip zip "pwd" "a.txt" "A")
    (zipvault/add-files zip "pwd" tmp-1 tmp-2)))
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[zipvault/add-folder](#)

Adds a folder to the zip file.

[zipvault/add-stream](#)

Creates a new entry in the zip file and adds the content of the input stream to the zip file.

[zipvault/remove-files](#)

Removes all files from the zip file that match the names in the input list.

[top](#)

zipvault/add-folder

```
(zipvault/add-folder zip passphrase folder)
(zipvault/add-folder zip passphrase folder include-root-folder)
(zipvault/add-folder zip passphrase folder include-root-folder exclude-fn)
```

Adds a folder to the zip file.

If 'include-root-folder' (default true) is true the root folder name will be added to the entry name as folder.

The 'exclude-fn' filters the files in the folder that are to be excluded from the zip. 'exclude-fn' is a single argument function that receives a file and returns true if the files is to be excluded otherwise it returns false.

```
(do
  (load-module :zipvault)

  (let [zip      (io/file "vault.zip")
        tmp-folder (io/file (io/tmp-dir) "ziptest")
        tmp-1     (io/file tmp-folder "a1.txt")
        tmp-2     (io/file tmp-folder "a2.txt")]
    (io/mkdir tmp-folder)
    (io/spit tmp-1 "1234")
    (io/spit tmp-2 "2345")
    (io/delete-file-on-exit tmp-folder)

    (zipvault/zip zip "pwd" "a.txt" "A")
    (zipvault/add-folder zip "pwd" tmp-folder)))

(do
  (load-module :zipvault)

  (defn exclude-fn [file] (io/file-ext? file "log"))

  (let [zip      (io/file "vault.zip")
        tmp-folder (io/file (io/tmp-dir) "ziptest")
        tmp-1     (io/file tmp-folder "a.txt")
        tmp-2     (io/file tmp-folder "b.txt")
        tmp-3     (io/file tmp-folder "c.log")]
    (io/mkdir tmp-folder)
    (io/spit tmp-1 "12")
    (io/spit tmp-2 "23")
    (io/spit tmp-3 "34")
    (io/delete-file-on-exit tmp-folder)

    (zipvault/zip zip "pwd")
    (zipvault/add-folder zip "pwd" tmp-folder true exclude-fn)))
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[zipvault/add-files](#)

Adds a list of files to the zip.

[zipvault/add-stream](#)

Creates a new entry in the zip file and adds the content of the input stream to the zip file.

[zipvault/remove-files](#)

Removes all files from the zip file that match the names in the input list.

[top](#)

zipvault/add-stream

```
(zipvault/add-stream zip passphrase name is)
```

Creates a new entry in the zip file and adds the content of the input stream to the zip file.

```
(do
  (load-module :zipvault)

  (let [zip (io/file "vault.zip")
        is  (io/string-in-stream "abc")]
    (zipvault/zip zip "pwd" "a.txt" "A")
    (zipvault/add-stream zip "pwd" "a.txt" is)))
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[zipvault/add-files](#)

Adds a list of files to the zip.

[zipvault/add-folder](#)

Adds a folder to the zip file.

[zipvault/remove-files](#)

Removes all files from the zip file that match the names in the input list.

[top](#)

zipvault/encrypted?

```
(zipvault/encrypted? zip)
```

Extracts a specific file from the zip file to the destination path.

```
(do
  (load-module :zipvault)

  (zipvault/zip (io/file "vault.zip") "pwd" "a.txt" "abc")
  (zipvault/encrypted? (io/file "vault.zip")))
```

[top](#)

zipvault/entropy

```
(zipvault/entropy passphrase)
```

Returns the passphrase's entropy in bits.

The password entropy using the formula: $E = \log_2(RL)$

- **E** stands for password entropy, measured in bits
- **Log₂** is a mathematical formula that converts the total number of possible character combinations to bits
- **R** stands for the range of characters
- **L** stands for the number of characters in a password

The entropy is calculated based on 26 lower and upper case letters, 10 digits, and 24 symbols like `^+*%&/()=?'`^:_.-$!#~;`

Note: The function just calculates the entropy. A strong passphrase does not rely on the entropy solely. Avoid passphrases containing words from the dictionary ("admin_passw0rd"), dates (birthdate, ...), repetitions ("aaaaa"), or sequences ("123456")!

```
(do
  (load-module :zipvault)
  (zipvault/entropy "uibsd6b38hs7b_La'sdgk898wbver"))
=> 186.36167788636087
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[top](#)

zipvault/extract-all

```
(zipvault/extract-all zip destpath)
(zipvault/extract-all zip passphrase destpath)
```

Extracts all files from the zip file to the destination path.

```
(do
  (load-module :zipvault)

  (zipvault/zip (io/file "vault.zip")
    "pwd"
    "a.txt" "abc"
    "b.txt" "def")

  (zipvault/extract-all (io/file "vault.zip")
    "pwd"
    "."))
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[zipvault/extract-file](#)

Extracts a specific file or folder from the zip file to the destination path.

[zipvault/extract-file-data](#)

Extracts a specific file from the zip file and returns it as binary data. in may be a file or an input stream.

[top](#)

zipvault/extract-file

```
(zipvault/extract-file zip password filename destpath)
```

Extracts a specific file or folder from the zip file to the destination path.

```
(do
  (load-module :zipvault)

  (zipvault/zip (io/file "vault.zip")
    "pwd"
    "a.txt" "abc"
    "b.txt" "def")

  ;; extract a file
  (zipvault/extract-file (io/file "vault.zip")
    "pwd"
    "a.txt"
    "."))

(do
  (load-module :zipvault)

  (zipvault/zip (io/file "vault.zip")
    "pwd"
    "words/one.txt" "one"
    "words/two.txt" "two"
    "logs/001.log" "xxx")

  ;; extract a folder
  (zipvault/extract-file (io/file "vault.zip")
    "pwd"
    "words/"
    "."))
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[zipvault/extract-all](#)

Extracts all files from the zip file to the destination path.

[zipvault/extract-file-data](#)

Extracts a specific file from the zip file and returns it as binary data. in may be a file or an input stream.

[top](#)

zipvault/extract-file-data

```
(zipvault/extract-file-data in passphrase filename)
```

Extracts a specific file from the zip file and returns it as binary data. in may be a file or an input stream.

Returns `nil` if the file does not exist.


```
(do
  (load-module :zipvault)

  (zipvault/zip (io/file "vault.zip")
    "pwd"
    "a.txt" "abc"
    "b.txt" "def")

  (zipvault/extract-file-data (io/file "vault.zip")
    "pwd"
    "a.txt"))
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[zipvault/extract-file](#)

Extracts a specific file or folder from the zip file to the destination path.

[zipvault/extract-all](#)

Extracts all files from the zip file to the destination path.

[top](#)

zipvault/remove-files

```
(zipvault/remove-files zip passphrase & files)
```

Removes all files from the zip file that match the names in the input list.

If any of the file is a directory, all the files and directories under this directory will be removed as well.

```
(do
  (load-module :zipvault)

  (let [zip (io/file "vault.zip")]
    (zipvault/zip zip "pwd" "a.txt" "A" "b.txt" "B")
    (zipvault/remove-files zip "pwd" "a.txt")))
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[zipvault/add-files](#)

Adds a list of files to the zip.

[zipvault/add-folder](#)

Adds a folder to the zip file.

[zipvault/add-stream](#)

Creates a new entry in the zip file and adds the content of the input stream to the zip file.

[top](#)

zipvault/valid-zip-file?

```
(zipvault/valid-zip-file? zip)
```

Returns true if the zip is a valid zip file else false.

```
(do
  (load-module :zipvault)

  (zipvault/zip (io/file "vault.zip") "pwd" "a.txt" "abc")
  (zipvault/valid-zip-file? (io/file "vault.zip")))
```

[top](#)

zipvault/zip

(zipvault/zip out passphrase & entries)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

An entry is given by a name and data. The entry data may be nil, a bytebuf, a string, a file, an input stream, or a producer function. An entry name with a trailing '/' creates a directory.

Entry value types:

nil	an empty file is written to the zip entry
bytebuf	the bytes are written to the zip entry
string	the string is written to the zip entry
file	the content of the file is written to the zip entry
input stream	the slurped input stream data is written to the zip entry
function	a producer function with a single output stream argument. All data written to the stream is written to the zip entry. The stream can be flushed but must not be closed!

Passphrases:

The AES-256 algorithm requires a 256-bit key as input. One should use a passphrase with at least 128 bits of entropy (that's roughly a 20-character passphrase of random upper/lower/digits/symbols). Less is dropping below general limits of safety, and more than 256 bits won't accomplish anything.

See function: `zipvault/entropy`

```
(do
  (load-module :zipvault)
  (zipvault/zip (io/file "vault.zip") "pwd")) ; empty zip

(do
  (load-module :zipvault)
  (zipvault/zip (io/file "vault.zip") "pwd" "a.txt" "abc"))

(do
  (load-module :zipvault)
  (zipvault/zip (io/file-out-stream "vault.zip")
    "pwd"
    "a.txt"      "abc"
    "b.txt"      (bytebuf [100 101 102])))

(do
  (load-module :zipvault)

  (let [file (io/file (io/tmp-dir) "c.txt")]
    (io/spit file "1234")
    (io/delete-file-on-exit c-tmp)

    ;; create "vault.zip"
```

```

;;      |— a.txt
;;      |— b.txt
;;      |— c.txt
;;      |— d.txt
;;      |— e.txt
;;      |— empty.txt
;;      |— xx
;;      |— g.txt
(zipvault/zip
  (io/file "vault.zip")
  "pwd"
  "a.txt"      "abc"
  "b.txt"      (bytebuf "def")
  file         file ; equivalent: (io/file-basename file) file
  "d.txt"      (io/string-in-stream "ghi")
  "e.txt"      (fn [os]
                (let [wr (io/wrap-os-with-buffered-writer os)]
                  (println wr "200")
                  (flush wr))))
  "empty.txt"  nil
  "xx/g.txt"   "jkl"))

```

SEE ALSO

[zipvault/zip-folder](#)

Creates an AES-256 encrypted and password protected zip from the folder.

[zipvault/entries](#)

Returns a list of the entry names in the zip.

[zipvault/add-files](#)

Adds a list of files to the zip.

[zipvault/add-folder](#)

Adds a folder to the zip file.

[zipvault/add-stream](#)

Creates a new entry in the zip file and adds the content of the input stream to the zip file.

[zipvault/remove-files](#)

Removes all files from the zip file that match the names in the input list.

[zipvault/extract-file](#)

Extracts a specific file or folder from the zip file to the destination path.

[zipvault/extract-all](#)

Extracts all files from the zip file to the destination path.

[zipvault/extract-file-data](#)

Extracts a specific file from the zip file and returns it as binary data. in may be a file or an input stream.

[zipvault/entropy](#)

Returns the passphrase's entropy in bits.

[top](#)

zipvault/zip-folder

```

(zipvault/zip-folder out passphrase folder)
(zipvault/zip-folder out passphrase folder include-root-folder)
(zipvault/zip-folder out passphrase folder include-root-folder exclude-fn)

```

Creates an AES-256 encrypted and password protected zip from the folder.

If 'include-root-folder' (default true) is true the root folder name will be added to the entry name as folder.

The 'exclude-fn' filters the files in the folder that are to be excluded from the zip. 'exclude-fn' is a single argument function that receives a file and returns true if the files is to be excluded otherwise it returns false.

```
(do
  (load-module :zipvault)

  (let [zip      (io/file "vault.zip")
        tmp-folder (io/file (io/tmp-dir) "ziptest")
        tmp-1      (io/file tmp-folder "a1.txt")
        tmp-2      (io/file tmp-folder "a2.txt")]
    (io/mkdir tmp-folder)
    (io/spit tmp-1 "1234")
    (io/spit tmp-2 "2345")
    (io/delete-file-on-exit tmp-folder)

    (zipvault/zip-folder zip "pwd" tmp-folder)))

(do
  (load-module :zipvault)

  (defn exclude-fn [file] (io/file-ext? file "log"))

  (let [zip      (io/file "vault.zip")
        tmp-folder (io/file (io/tmp-dir) "ziptest")
        tmp-1      (io/file tmp-folder "a.txt")
        tmp-2      (io/file tmp-folder "b.txt")
        tmp-3      (io/file tmp-folder "c.log")]
    (io/mkdir tmp-folder)
    (io/spit tmp-1 "12")
    (io/spit tmp-2 "23")
    (io/spit tmp-3 "34")
    (io/delete-file-on-exit tmp-folder)

    (zipvault/zip -folder zip "pwd" tmp-folder true exclude-fn)))
```

SEE ALSO

[zipvault/zip](#)

Creates an AES-256 encrypted and password protected zip form the entries and writes it to out. out may be a file or an output stream.

[zipvault/add-folder](#)

Adds a folder to the zip file.

[top](#)



Creates a hash map.

```
{:a 10 :b 20}
=> {:a 10 :b 20}
```