ICON
AGILITY SERVICES

Test-Driven Development Foundations v1.2

Jeff Langr

jeff@langrsoft.com
@JLangr

What's a Unit Test Look Like?

```
describe('something', () => {
  it('demonstrates some behavior', () => {
    // Arrange


    // Act


    // Assert
  })
})
```

The AAA mnemonic is courtesy of Bill Wake.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

A Sample Unit Test

```
describe('an auto', () =>
  const auto = new Auto()

  it('idles engine when started', () => {
    auto.depressBrake()

    auto.pressStartButton()

    expect(auto.RPM()).toBeWithinRange(950, 1100)
  })
})
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

What's an Assertion Look Like?

```
expect(someCondition).toBe(true)
expect(idleSpeed).toBe(1000)
expect(alphabetizedName).toEqual('Schmoo, Kelly Loo')
expect(someArray).toEqual(['O','T','F','F','F','S'])
expect(alphabetizedName).toMatch(/^S.*,/)
expect(idleSpeed).not.toEqual(42)
expect(alphabetizedName).not.toEqual("Smelt"))))
expect(someVariable).toBeUndefined
expect(someArray).toHaveLength(3)
expect(someArray).toContain(42)
expect(someArray).toContainEqual({ name: 'Amit' })
```

See https://jest-bot.github.io/jest/docs/expect.html

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Simple Outcomes

Flesh out the tests in ./src/misc/basics.test.js

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Test-Driven Development

An incremental design technique

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: (Test)-Code-Refactor

TDD Paint by Numbers

See ./src/misc/name-normalizer.test.js

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Core TDD Themes

- Test-drive behavior
- Small increments
- Stick to the cycle
  - Always see red
  - Always refactor
- Specification by example

It's just code!

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"BinaryCode," courtesy https://www.flickr.com/photos/132889348@N07/
License: https://creativecommons.org/licenses/by-sa/2.0/

Stepping Back: Writing Tests

Area Calculator

Given an object with height & width, test-drive a function that calculates its area.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Kata," courtesy https://www.flickr.com/photos/superwebdeveloper/
License: https://creativecommons.org/licenses/by/2.0/

ZOMBIES!

- Zero
- One
- Many
- Boundaries
- Interface definition
- Exceptional behavior
- Simple Solutions & Scenarios

http://blog.wingman-sw.com/archives/677

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Test Lists

- ~~Z: Empty rectangle~~
- O: 1 x 1
- M: Larger sizes
- B: Maximum integer size
- E: Negative input

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Your Test Is the First Client

You are the designer of the interface!

The SUT

"System Under Test"

- How does the client want to interact with the system?
- What sequence of events gets you into the right state?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Structuring the Test

Arrange	Create an object storing H & W
Act	Pass it to the area function & store the return
Assert	Compare against the return value

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Assert-First

Consider working from the outcome:

```
expect(areaOfEmptyRectangle)
  .is.equal.to(0)
```

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Assert-First: Backing Up

```
const areaOfEmptyRectangle =
  area(emptyRectangle)

expect(areaOfEmptyRectangle)
  .is.equal.to(0)
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Assert-First: Backing Up

```
const emptyRectangle =
  { height: 0, width: 0 }

const areaOfEmptyRectangle =
  area(emptyRectangle)

expect(areaOfEmptyRectangle)
  .is.equal.to(0)
```

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Weather Machine

The weather module is an OO class.

It accepts and stores new cities.

It can return the temperature for any one city (by interfacing with an external REST service).

It can return the average temperature for all cities.

Create a test list.

Write the average temperature test, assertion first.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Kata," courtesy https://www.flickr.com/photos/superwebdeveloper/
License: https://creativecommons.org/licenses/by/2.0/

Exercise: Stock Portfolio Class

In-memory only

- is it empty or not?
- what is the count of unique symbols?
- given a symbol and # of shares, make a purchase
- how many shares exist for a given symbol?
- given a symbol and # of shares, sell the shares
- throw a RangeError when selling too many shares

"Tokyo Stock Exchange," courtesy https://www.flickr.com/photos/31029865@N06/
License: https://creativecommons.org/licenses/by/2.0/

*** Remember! ***

Red: Ensure test fails

Green: Implement no more code than necessary

Refactor: Clarify and eliminate all duplication

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

A Functional Implementation

Store portfolio info in a state object:

```
{
  holdings:
  {
    IBM: 20,
    BAYN: 10
  }
}
```

Pass state to each function, return updated state:

```
const portfolio = { holdings: [] }
const newPortfolio = purchase(portfolio, 'BAYN', 42)
```

Ensure your function creates no side-effects!

- I.e., portfolio should not change

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

TAD** and TDD: What's the Difference?

"Test-After Development"

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Small Increments

vs.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Test-After Development (TAD)

- Some refactoring accommodated
- Coverage: ~70%
- Design not usually impacted
- Some defect reduction
- Separate task?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Test-Driven Development (TDD)

- Continual refactoring
- Coverage for all intended features
- Incremental design shaping
- Significant defect reduction
- Minimized debugging
- Integral part of coding process
- Clarify / document needs / choices
- Continual forward progress
- Consistent pacing
- Continual feedback / learning
- Sustainable

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Unit Testing: Insufficient!

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Eye image: Frank Boston, https://www.flickr.com/photos/fixersphotos/4019797096/
License: https://creativecommons.org/licenses/by/2.0/

A Re-leveled Pyramid

Regression Feedback

Manual Exploratory (Tester)

hours/days

many minutes/hours

UI

up to a couple dozen

Acceptance

minutes/hours

up to a few hundred

"Integration"

minutes

a few dozen

Unit ("Fast")

< 10 seconds

thousands

Automated

Count

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Eye image: Frank Boston, https://www.flickr.com/photos/fixersphotos/4019797096/
License: https://creativecommons.org/licenses/by/2.0/

Katas

http://codekata.com

Other sites:

https://exercism.io

http://cyber-dojo.org

https://sites.google.com/site/tddproblems/

https://www.codewars.com

https://github.com/jlangr/name-normalizer

https://github.com/emilybache

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Kata," courtesy https://www.flickr.com/photos/superwebdeveloper/
License: https://creativecommons.org/licenses/by/2.0/

Roman Numeral Converter

Given a positive integer
from 1 up to 4000,
answer its Roman equivalent

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Kata," courtesy https://www.flickr.com/photos/superwebdeveloper/
License: https://creativecommons.org/licenses/by/2.0/

Feedback Q's

:-)	What have I learned of value?
%-I	What am I unclear about regarding the discussion / exercises?
?:-/	What, if anything, did I find disturbing / disconcerting?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Documentation

Tests as Documents

what we're describing

```
describe('an unstarted auto', () => {
  let auto
  beforeEach(() => { auto = new Au
```

the generalized behavior it supports

```
  it('idles engine when started', () => {
    auto.depressBrake()

    auto.pressStartButton()

    expect(auto.RPM()).
      toBeWithinRange(950, 1100)
  })
})
```

an example of that behavior

Seek to first understand through the tests.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Behavior-Driven Structuring

```
describe('given some context', () => {
  describe('when some event occurs', () => {
    it('then can be verified', () => {


    })
  })
})
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

BDD Structuring Example

```
describe('given a checked-out material', () => {
  let dueDate

  beforeEach(() => {
   dueDate = borrow(AgileJava, PatronId)
  })

  describe('when returned late', () => {
    let daysLate
    beforeEach(() => {
      daysLate = returnMaterial(AgileJava)
    })

    it('is marked as available', () => {})
    it('generates a late fine', () => {})
    it('notifies patrons with hold', () => {})
  })
})
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Iterative Naming

- Re-consider name continually

```
it('does something', …

it('verifies engine start', …

it('verifies engine start idle speed', …

it('has low idle on engine start', …
```

- Review often and holistically!

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Sustainable Tests

- Single behavior tests
- AAA
- Correlate result with context
- Test abstraction

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Test Smells

Find and fix test smells.

Paraphrase cleaned tests
to your pair.

Further instructions: ./src/pos/routes/checkout.test.js

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"skunk_dog," courtesy https://www.flickr.com/photos/istolethetv/
License: https://creativecommons.org/licenses/by/2.0/

Continual Design

ICON
AGILITY SERVICES

Langr
Software Solutions
SOFTWARE TRAINING/CONSULTING
TDD
AGILE

Software Development

- Activities:
  - Analysis, design, coding, testing, review, documentation, planning, deployment, ...

- Agile:
  - All activities all the time

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

TDD: Continual ...

- Testing
- Coding
- Design
- Documentation

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Continual Design

- Always retain an optimal design
- Entropy is unavoidable

Never skimp on the refactoring step!

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Refactoring

Same "externally recognized" behavior

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

For (almost) Every Transform...

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Code Smells

- Comments
- Duplicate Code
- Feature Envy
- Large Class
- Long Method
- Long Parameter List
- Primitive Obsession
- Shotgun Surgery
- Speculative Generality
- Switch Statements
- . . . and many more

"a complete code smells reference:"
https://github.com/lee-dohm/code-smells

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

The Nature of the Smell

Aroma?

Stench?

"beagle smelling roses," courtesy Grangernite, https://www.flickr.com/photos/ldoty/2573672102
https://creativecommons.org/licenses/by/2.0/

adapted from "Yum, that smells good!", courtesy Tankboy,
https://www.flickr.com/photos/tankboy/284958387; https://creativecommons.org/licenses/by-sa/2.0/

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Refactoring Opportunities

small cleanup

verify

small cleanup

verify

...

One thing at a time!

Break things once in a while.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Refactoring: Extract Function

```
const uglyFunction = () => {
   // stuff a
   ...
   // stuff b
   ...
   // some smaller behavior
   doSomething()
   doSomethingElse()
   // ...
   // stuff c
   // ...
}
```

```
const lessUglyFunction = () => {
   // stuff a   ...
   // stuff b
   ...
   someSmallerBehavior()
   // ...
   // stuff c
   // ...
}

const someSmallerBehavior = () => {
   doSomething()
   doSomethingElse()
}
```

Why?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Single-Line Extract?

```
catch(err) {
  const { sev, system, module, msg } = err
  const errMsg = `${new Date()}: ${system}-${module} ${sev} ${trunc(msg, 80)}`
  log(errMsg)
  throw new Error(errMsg, err)
}
```

```
  catch(err) {
    const { sev, system, module, msg } = err
    const errMsg = formatErrorMessage(sev, system, module, msg)
    log(errMsg)
    throw new Error(errMsg, err)
  }

const formatErrorMessage = (sev, system, module, msg) =>
  `${new Date()}: ${system}-${module} ${sev} ${trunc(msg, 80)}`
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Extract Function

- In ./src/pos/routes/checkout.js
  - Do a single-line function extract on `postCheckoutTotal`
  - Otherwise focus on renaming and eliminating lies

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Refactoring-Inhibiting Temp

```
checkout.items.forEach(item => {
  let price = item.price;
  const isExempt = item.exempt;
  if (!isExempt && discount > 0) {
    const discountAmount = discount * price;
    const discountedPrice = price * (1.0 - discount);

    // add into total
    totalOfDiscountedItems += discountedPrice;

    let text = item.description;
    // format percent
    const amount = parseFloat(Math.round(price * 100) / 100).toFixed(2)
    const amountWidth = amount.length;

    let textWidth = LineWidth - amountWidth;
    messages.push(pad(text, textWidth) + amount);

    total += discountedPrice;

    // discount line
    const discountFormatted = '-' + parseFloat(Math.round(discountAmount * 100) / 100).toFixed(2)
    textWidth = LineWidth - discountFormatted.length;
    text = `   ${discount * 100}% mbr disc`;
    messages.push(`${pad(text, textWidth)}${discountFormatted}`);

    totalSaved += discountAmount;
  }
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Refactoring: Replace Temp With Query

```
const discountAmount = discount * price;
// . . .

// discount line
const discountFormatted = '-' + parseFloat(Math.round(discountAmount * 100) / 100).toFixed(2)
textWidth = LineWidth - discountFormatted.length;
text = `   ${discount * 100}% mbr disc`;
messages.push(`${pad(text, textWidth)}${discountFormatted}`);

totalSaved += discountAmount;
```

```
  // discount line
  const discountFormatted =
    '-' + parseFloat(Math.round(discountAmount(discount, price) * 100) / 100).toFixed(2)
  textWidth = LineWidth - discountFormatted.length;
  text = `   ${discount * 100}% mbr disc`;
  messages.push(`${pad(text, textWidth)}${discountFormatted}`);

  totalSaved += discountAmount(discount, price);
  // …
});

const discountAmount = (discount, price) => discount * price;
// . . . . . . . .
```

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Replace Temp With Query

Steps:

- Make temp const
- Extract Function on the rhs
- Replace temp references with the query
- Remove temp

Why?

Concerns?

Can we go the other way?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Replace Temp with Query

- In ./src/pos/routes/checkout.js
  - Apply Replace Temp with Query in `postCheckoutTotal` as appropriate
  - Extract as many additional functions as you can

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Code Smell: Feature Envy

```
class WrongPlace {
   client() {
      const x = enviousFunction()
      ...
   }

   enviousFunction() {
      const there = new GreenerGrass()
      const result = there.doStuff(this.someValue)
      there.doMoreStuff(result)
      return there.answer()
   }
}
```

Why is this a problem?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Refactoring: Move Function

```
class WrongPlace {
   client() {
      const x = new GreenerGrass().homebodyMethod(this.someValue)
      ...
   }
}

class GreenerGrass {
   homebodyMethod(someValue) {
      var result = doStuff(someValue)
      doMoreStuff(result)
      return answer()
   }
   ...
}
```

What must you also do when you move a function?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Move Function

- In ./src/pos/routes/checkout.js
- Move at least 2 envious functions to better (or new!) homes
- Ensure you've added documentation (i.e tests)!

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Macro Refactorings

Might need to backtrack!

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Stepping Stones," courtesy https://www.flickr.com/photos/jmalonzo/
License: https://creativecommons.org/licenses/by-sa/2.0/

Smell: Switch Statements

```
switch (movie.code) {
  case 'regular':
    thisAmount = 2
    if (r.days > 2) {
      thisAmount += (r.days - 2) * 1.5
    }
    break
  case 'new':
    thisAmount = r.days * 3
    break
  case 'childrens':
    thisAmount = 1.5
    if (r.days > 3) {
      thisAmount += (r.days - 3) * 1.5
    }
    break
}
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Some of the Transforms (OO)

- Self-encapsulate field
- Replace Conditional With Polymorphism
  - Extract Function, Move Function
  - Replace Type Code with Subclasses
    - Push Down Method / Field

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

A Refactored Result (OO)

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Planning: Up-Front Design

- Not just once!
  - Planning: project, release, iteration, day, task, test
  - Any estimation
- Minimal: sketches & conversations
  - Not detailed specs

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"UML Diagram," courtesy https://www.flickr.com/photos/acehoward/
License: https://creativecommons.org/licenses/by/2.0/

Premature Generalization

- Need might never materialize
- Details might change
- Interim complexity $

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"crystal," courtesy https://www.flickr.com/photos/bb_matt/
License: https://creativecommons.org/licenses/by/2.0/

Refactoring Guidelines

Never skip!

Single-goal

Run all tests

It's your responsibility

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Design Drivers / Guidelines

- Code smells
- SOLID
- Design patterns
- GRASP
- Simple design
- DRY
- ...

It's all good!

Does everything point to the same place?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

41 Build Superior Systems with Simple Design

- All tests must pass
- No code is duplicated
- Code is self-explanatory
- No superfluous parts exist

Kent Beck's (ordered) rules for emergent design

Exercise: Simple Design Rules

- In ./src/pos/routes/checkout.js
  - Stamp out duplication!
  - Strive for rapid readability
  - Have you gone too far?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Test Doubles

Testing Challenge: Portfolio

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Using a Test Double

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Portfolio Code

Test-Driving from portfolio.test.js:

```
import * as StockLookupService from './stock-lookup-service'

describe('portfolio value with stub', () => {
  it('is symbol price for single-share purchase', () => {
    portfolio = purchase(portfolio, 'IBM', 1)
    expect(value(portfolio)).to.equal(42) // how to make this work?
  })
})
```

Some notion of an implementation in portfolio.js:

```
import { symbolLookup } from './stock-lookup-service'
export const value =
  portfolio => symbolLookup(Object.keys(portfolio.holdings)[0])
```

The troublesome dependency in stock-lookup-service.js:

```
export let symbolLookup = _symbol => { /* prod code */ }
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

ES6: Function Override

(using **`import * as`**)

portfolio.test.js

```
import * as StockLookupService from './stock-lookup-service'

describe('portfolio value with stub', () => {
  it('is symbol price for single-share purchase', () => {
    StockLookupService.symbolLookupStub(_ => 42)
    portfolio = purchase(portfolio, 'IBM', 1)
    expect(value(portfolio)).to.equal(42)
  })
})
```

stock-lookup-service.js

```
export let symbolLookup = _symbol => { /* prod code */ }
export const symbolLookupStub = stub => symbolLookup = stub
```

portfolio.js

```
import { symbolLookup } from './stock-lookup-service'
export const value =
  portfolio => symbolLookup(Object.keys(portfolio.holdings)[0])
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Function Override

using `import * as`

Test Double Injection Techniques

Functional

Function argument

import * Function Override

exports injection

OO

Constructor / setter

Prototype

Method override

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Prototype Injection

```
PortfolioObj.prototype.value = function() {
  if (this.size() === 0) return 0
  return this.lookupPrice('BAYN')
    .then(function({_symbol, price
      return price
    })
}

PortfolioObj.prototype.lookupPrice
  return ax.get(`http://localhost
    .then(function(response) {
      return { symbol: symbol, pr
    })
}
```

```
let realLookupPrice

beforeEach(() => {
  realLookupPrice = PortfolioObj.prototype.lookupPrice
  PortfolioObj.prototype.lookupPrice =
    function() {
      return Promise.resolve(
        { symbol: Monsanto, price: MonsantoValue })
    }
})

afterEach(() => {
  PortfolioObj.prototype.lookupPrice = realLookupPrice
})

it('...', async () => {
  portfolio.purchase(Monsanto, 1)
  const result = await portfolio.value()
  expect(result).to.equal(MonsantoValue)
})
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Prototype Injection

Flesh out the portfolio value function, using TDD, starting with `./src/misc/portfolio-obj.test.js` and `./src/misc/portfolio/portfolio-obj.js`

Start simple! Add in small increments!

You should end up with at least three tests, perhaps four.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Test Double Terms

Stub: dumb emulation

Spy: captures values to verify

Mock: self-verifies

Fake: whole collaborator emulation

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Mock Tools

JsMock

JSmockito

td
test double

Jack

History suggests more & changes coming!

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest

https://jestjs.io

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest: A Simple Stub

https://jestjs.io

What if the cities are ordered differently?

```
const temperatureServerStub = jest.fn()
temperatureServerStub.mockReturnValueOnce(96)
temperatureServerStub.mockReturnValueOnce(88)

const result = averageTemp(['Miami', 'St. Louis'], temperatureServerStub)

expect(result).toEqual(92)
```

```
export const currentTemperature = _city => {
  throw Error('server down')
}

export const averageTemp = (cities, currentTemperature) => {
  return cities
    .map(city => currentTemperature(city))
    .reduce((sum, temp) => sum + temp, 0) / cities.length
}
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Mocks Are Trackers

https://jestjs.io/docs/en/mock-function-api.html

`mockFn.mock.calls`: list of arguments for all calls to `mockFn`

`mockFn.mock.results`: list of results for all calls to `mockFn`

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

jest-when

https://github.com/timkindberg/jest-when

```
import { when } from 'jest-when'
// ...
const temperatureServerStub = jest.fn()
when(temperatureServerStub).calledWith('Miami').mockReturnValueOnce(96)
when(temperatureServerStub).calledWith('St. Louis').mockReturnValueOnce(88)

const result = averageTemp(['Miami', 'St. Louis'], temperatureServerStub)

expect(result).toEqual(92)
```

npm install --save-dev jest-when

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

jest.fn() shorthand

```
jest.fn(() => doSomething())
```

is equivalent to:

```
jest.fn().mockImplementation(() => doSomething())
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Jest Stubs

Test-drive the `value()` function for your Portfolio solution, using Jest for stubs.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest: Exceptions

```
it('answers 0 when price retrieval throws', () => {
  const portfolio = {}
  purchase(portfolio, "BAYN", 1)

  const priceRetrieveStub =
    jest.fn(() => { throw new Error() })
  const result = value(portfolio, priceRetrieveStub)

  expect(result).toEqual(0)
})
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exercise: Jest Exceptions

When calculating the portfolio value,
use zero dollars for the current stock price
if the symbol lookup throws an error.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Verifying a "Tell" (aka Spying)

How to test-drive?

```
const sell = (portfolio, symbol, shares, auditor) {
  portfolio[symbol] -= shares
  auditor('sell made')
}
```

```
const portfolio = {}
purchase(portfolio, "BAYN", 10)
const auditorSpy = jest.fn()

sell(portfolio, "BAYN", 3, auditorSpy)

expect(auditorSpy).toHaveBeenCalled()
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest: Was It Called?

```
expect(mock).toHaveBeenCalled()

expect(mock).toHaveBeenCalledTimes(2)

expect(mock).toHaveBeenCalledWith(arg1, arg2, ...)

expect(mock).toHaveBeenCalledWith(1, arg1, arg2, ...)
expect(mock).toHaveBeenCalledWith(2, arg1, arg2, ...)

expect(mock).toHaveReturned() // i.e. did not throw error
expect(mock).toHaveReturnedWith('some value')

expect(mock).toHaveLastReturnedWith('...')
...
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest Spying: Verifying Arguments

```
expect(auditorStub)
  .toHaveBeenCalledWith('sold shares of BAYN', 3)
```

```
const sell = (portfolio, symbol, shares, auditor) => {
  portfolio[symbol] -= shares
  auditor(`sold shares of ${symbol}`, shares)
}
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest Argument Matching

How to verify the date?

```
auditor(`sold shares of ${symbol}`, shares, Date.now())
```

Use `expect.any(constructor)`:

```
expect(auditorStub)
  .toHaveBeenCalledWith(
    'sold shares of BAYN',
    3,
    expect.any(Number))
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Spy Exercise

Verify that the portfolio sends an appropriate audit message on all buy & sell transactions.

The audit function should take on a description,
the current timestamp,
and the number of shares involved.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest: Replace a Module Function

```
import * as TemperatureServer from './temperature-server'

TemperatureServer.currentTemperature = jest.fn()

it('calculates average temperature', () => {
  TemperatureServer.currentTemperature.mockReturnValueOnce(83)
  TemperatureServer.currentTemperature.mockReturnValueOnce(52)

  const result = averageTemperature(['Miami', 'St. Louis'])

  expect(result).toEqual(67)
})
```

Not as common as mocking a module (next!)

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Mocking a Module

```
import { currentTemperature} from './temperature-server'

jest.mock('./temperature-server.js')

it('calculates average temperature', () => {
  currentTemperature.mockReturnValueOnce(82)
  currentTemperature.mockReturnValueOnce(52)

  const result = averageTemperature(['Miami', 'St. Louis'])

  expect(result).toEqual(67)
})
```

All exports in a module are initialized to jest.fn()

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest: Is That All?

No.

- Manual mocks
- Alternate ways to create an ES6 class mock
- Partial module mocks ("bypassing module mocks")
- Fake timers (`setTimeout`, `setInterval`, etc.)

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Schools of Mock

Classic ("Detroit")

- algorithmic approach
- verification of state
- tests drive code from specific to general

London

- roles, responsibilities, and interactions
- "Fake it until you make it"
- drive incrementally from the outside in

Read Martin Fowler's "Mocks Aren't Stubs"

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Classic School: When to Mock

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

When Not to Mock?

Can you inject the data or a generator instead?

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

The Pragmatic Mocker

- Writes integration tests where mocks are used
- Watches coupling between tests & implementation
- Seeks to mock only direct collaborators
- Avoids mocking what they don't own
- Avoids fakes (and if necessary, test-drives 'em!)
- Isolates, minimizes the use of test doubles
  - But prefers testability

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Jester," courtesy https://www.flickr.com/photos/mrpolyonymous/
License: https://creativecommons.org/licenses/by/2.0/

Wrap-Up Exercise

- Support voids on checkout

Work outside in:

- Stub collaborators until ready to build them out

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"barcode_scan3_code128.png," courtesy https://www.flickr.com/photos/mdornseif/
License: https://creativecommons.org/licenses/by-sa/2.0/

Growing & Sustaining TDD

Next Week

- Create team policies/standards around TDD
- Ensure your build pipeline supports it
- Reviews must include the tests
- Pairing / mobbing helps quite a bit!
- Focus on problem areas first
- Adopt on smaller scale if necessary

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Kickoff," courtesy https://www.flickr.com/photos/edrost88/
License: https://creativecommons.org/licenses/by/2.0/

Growing TDD

- Education / sharing sessions
- Challenges / contests / randoris
- Coach / champion
- "Stop the line" mentality
- Changing metrics for education
- Pair & paraphrase
  - Three+ sets of eyes!
- Mobbing

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Kickoff," courtesy https://www.flickr.com/photos/10209472@N03/
License: https://creativecommons.org/licenses/by-sa/2.0/

Sustaining TDD

Everything under "Growing TDD," plus:

- TDD-specific retrospectives
- Daily stand-down
- Regular reminders as to "why?"
- Revisit standards regularly
- Keep the tests fast
  - Segregate (and fix) slow tests
- Always use tests as an entry point
- Refactor, refactor, refactor
  - Tests too!

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Infinity!" courtesy https://www.flickr.com/photos/thecampbell/
License: https://creativecommons.org/licenses/by/2.0/

Mastering TDD

TDD is a skill.

Practice, practice, practice.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Beautiful and dusty," courtesy https://www.flickr.com/photos/80435089@N08/
License: https://creativecommons.org/licenses/by/2.0/

Miscellaneous Topics

Testing With Promises: ES6

```
const funcReturningPromise = () =>
  new Promise((resolve, _reject) => setTimeout(resolve, 500, 42))
```

Nope:

```
describe('testing promises', () => { // doesn't work!
  const x = funcReturningPromise()
  expect(x).to.equal(41)
})
```

ES6: await

```
describe('testing promises', async () => {
  const x = await funcReturningPromise()
  expect(x).to.equal(41)
})
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Testing With Promises: Old School

```
it('is worth share price for single share purchase', done => {
  portfolio.retrievePrice = () => Promise.resolve({ symbol: IBM, price: 100 });
  portfolio.purchase(IBM, 1);

  portfolio.value()
    .then(result => {
      expect(result).to.equal(IBM);
      done();
    });
});
```

If that doesn't work:

```
it('is worth share price for single share purchase', done => {
  portfolio.retrievePrice = () => Promise.resolve({ symbol: IBM, price: 100 });
  portfolio.purchase(IBM, 1);

  portfolio.value()
    .then(result => { expect(result).to.equal(100); })
    .then(done, done);
});
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Testing Non-Public Behavior?

Or simply relax access.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Rules of Ten

Green & clean in < 10 (minutes)

Delete and repeat if you're late!

... taking smaller steps this time.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Egg Timer," courtesy https://www.flickr.com/photos/engendercdp/ spikeheap/
License: https://creativecommons.org/licenses/by/2.0/

Rules of Ten

Debate stops at 10 (minutes)

"Show me."

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Egg Timer," courtesy https://www.flickr.com/photos/engendercdp/ spikeheap/
License: https://creativecommons.org/licenses/by/2.0/

Rules of Ten

All unit tests run in < 10 (seconds).

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

"Egg Timer," courtesy https://www.flickr.com/photos/engendercdp/ spikeheap/
License: https://creativecommons.org/licenses/by/2.0/

Fixing a Slow Test Run

Warn on tests < n ms

Fail on tests > n ms

Running a subset of tests increases risk.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Uncle Bob's TPP

Transformations have a preferred ordering, which if maintained by ordering of tests, prevents "long outages" in TDD.

The Priority List

(\{\}->nil) no code at all->code that employs nil
(nil->constant)
(constant->constant+) a simple constant to a more complex constant
(constant->scalar) replacing a const. with a variable or an argument
(statement->statements) adding more unconditional statements.
(unconditional->if) splitting the execution path
(scalar->array)
(array->container)
(statement->tail-recursion)
(if->while)
(statement->recursion)
(expression->function) replacing expression w/ a function or algorithm
(variable->assignment) replacing the value of a variable.
(case) adding a case (or else) to an existing switch or if

"As the tests get more specific, the code gets more generic."

http://thecleancoder.blogspot.com/2011/02/fib-t-p-premise.html
https://8thlight.com/blog/uncle-bob/2013/05/27/TheTransformationPriorityPremise.html

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Per and updated by Uncle Bob.

Behavior-Driven Development (BDD)

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest: Method Dependency

https://jestjs.io/docs/en/es6-class-mocks

```
class TemperatureService {
  currentTemperature(_city) {
    throw Error('server *really* down')
  }
}

const averageTemperature = (cities, temperatureService)  => {
  return cities
    .map(city => temperatureService.currentTemperature(city))
    .reduce((sum, temp) => sum + temp, 0) / cities.length
};
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Jest Method Stub

```
class TemperatureService {
  currentTemperature(_city) {
    // ...
  }}
```

```
import TemperatureService from './temperature-class'
import { when } from 'jest-when'

const mockCurrentTemperature = jest.fn()
jest.mock('./temperature-class', () =>
  jest.fn().mockImplementation(() => ({ currentTemperature: mockCurrentTemperature }))
)

    TemperatureService.mockClear() // in beforeEach
    mockCurrentTemperature.mockClear() // in beforeEach

    const temperatureService = new TemperatureService()
    when(mockCurrentTemperature).calledWith('Miami').mockReturnValueOnce(82)
    when(mockCurrentTemperature).calledWith('St. Louis').mockReturnValueOnce(52)

    const result =  averageTemperature(['Miami', 'St. Louis'], temperatureService)

    expect(result).toEqual(67)
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

require() Dependency Challenge

portfolio.js

```
var symbolLookup = require('./stock-lookup-service').symbolLookup

// ... other funcs ...

var value = function(portfolio) {
  var sumValues = function(totalValue, symbol) {
    return totalValue + symbolLookup(symbol) * sharesOf(portfolio, symbol)
  }
  return empty(portfolio) ? 0 :
    Object.keys(portfolio.holdings).reduce(sumValues, 0)
}

module.exports = { /* ... */, value: value }
```

stock-lookup-service.js

```
module.exports = {
  symbolLookup: function(symbol) { /* ... */ }
}
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Exports Injection: Old School

portfolio.js

```
var value = function(symbolLookup, portfolio) {
  var sumValues = function(totalValue, symbol) {
    return totalValue + symbolLookup(symbol) * sharesOf(portfolio, symbol)
  }
  return empty(portfolio)
    ? 0
    : Object.keys(portfolio.holdings).reduce(sumValues, 0)
}

module.exports = function(symbolLookup) {
  return {
    // ... other funcs ...
    value: value.bind(null, symbolLookup)
  }
}
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Injecting Via Exports

portfolio.test.js

```
var stubSymbolLookup = jest.fn()
var Portfolio = require('./portfolio')(stubSymbolLookup)

describe('portfolio value', function() {
  it('is symbol price for single-share purchase', function() {
    stubSymbolLookup.mockReturnValueOnce(IBMPrice)
    var portfolio = createPortfolio()

    portfolio = purchase(portfolio, 'IBM', 1)

    expect(value(portfolio)).toEqual(IBMPrice)
  })
})
```


Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

References / Reading List

"Chat" icon courtesy Gregor Cesnar, Noun Project (Creative Commons)

[Beck2002] Beck, Kent. **Test-Driven Development: By Example**. Addison-Wesley, 2002.

[Feathers2005] Feathers, Michael. **Working Effectively With Legacy Code**. Prentice Hall, 2005.

[Fowler1999] Fowler, Martin. **Refactoring: Improving the Design of Existing Code**. Addison-Wesley, 1999.

[Freeman, 2009]. Freeman, S. and Pryce, N. **Growing Object-Oriented Software, Guided By Tests**. Addison-Wesley, 2009.

[Langr2005] Langr, Jeff. **Agile Java: Crafting Code With Test-Driven Development**. Prentice Hall, 2005.

[Langr2011] Langr, Jeff and Ottinger, Tim. **Agile in a Flash**. Pragmatic Programmers, 2011.

[Langr2013] Langr, Jeff. **Modern C++ Programming With Test-Driven Development**, Pragmatic Programmers, 2013.

[Langr2015] Langr, Jeff, et. al. **Pragmatic Unit Testing in Java 8 with Junit.** Pragmatic Programmers, 2015.

[Martin2002] Martin, Robert C. **Agile Software Development: Principles, Patterns, and Practices**. Prentice Hall, 2002.

[Meszaros2007] Meszaros, Gerard. **xUnit Test Patterns: Refactoring Test Code**. Addison-Wesley, 2007.

Copyright © Langr Software Solutions, Inc. 2019. All rights reserved.

Thank you!

ICON
AGILITY SERVICES

Langr
Software Solutions
SOFTWARE TRAINING/CONSULTING
TDD
AGILE