

---

# Lab 6 Christian Ardito SID: 861140154

# Jesse Layman SID: 861135479

## Table of Contents

task 1 .....	1
task 2 .....	6

Professor: Yingbo Hua, TA: Qiping Zhu, EE110B-023

*Task 1:* Design the impulse response  $h[n]$  of a low pass filter by first determining  $h_0[n]$  the inverse DTFT of  $H_0(f) = \begin{cases} 1 & |f| \leq 0.1 \\ 0 & 0.1 < |f| < 0.5 \end{cases}$  and then computing  $h[n] = h_0[n - n_0]w[n]$  with  $w[n] = \begin{cases} n & 0 \leq n \leq n_0 \\ 2n_0 - n & n_0 \leq n \leq 2n_0 \end{cases}$  and  $n_0 = 20$ . Compute, plot and discuss the amplitude and phase spectra, i.e.,  $|H(f)|$  and  $\angle H(f)$ , of  $h[n]$ . Compare the amplitude and phase spectra of  $h[n]$  with those of  $h_0[n]$ . If you increase or decrease  $n_0$ , what effects do you observe?





## task 1





```
clear all
close all
n0 = 10;
n = 0:2*n0;
h0 = 1/5*sinc((n-n0)/5);
w = [0:(n0-1), n0:-1:0];
%plot(0:length(w)-1,w)
%plot(n,h0)
h = h0.*w;
%plot(0:length(h)-1,abs(h));
figure
subplot(1,2,1)
H = fftshift(fft(h));
plot(0:length(H)-1,abs(H))
title(' |H(f)| ')
subplot(1,2,2)
plot(0:length(H)-1,angle(H))
title('angle(H(f))')
figure
subplot(1,2,1);
plot(n,abs(h0))
title(' |h0| ,n_0=20 ')
subplot(1,2,2);
plot(n,angle(h0))
```





```
title('angle(h0),n_0=20')
h = h0.*w;
figure
subplot(1,2,1);
plot(0:length(h)-1,abs(h));
title('|h(n),n_0=20|')
subplot(1,2,2);
plot(0:length(h)-1,angle(h));
title('angle(h(n)),n_0=20')
n0 = 10;
figure
subplot(1,2,1);
plot(n,abs(h0))
title('|h0|,n_0=10')
subplot(1,2,2);
plot(n,angle(h0))
title('angle(h0),n_0=10')
figure
subplot(1,2,1);
plot(0:length(h)-1,abs(h));
title('|h(n),n_0=10|')
subplot(1,2,2);
plot(0:length(h)-1,angle(h));
title('angle(h(n)),n_0=10')
n0 = 5;
figure
subplot(1,2,1);
plot(n,abs(h0))
title('|h0|,n_0=5')
subplot(1,2,2);
plot(n,angle(h0))
title('angle(h0),n_0=5')
figure
subplot(1,2,1);
plot(0:length(h)-1,abs(h));
title('|h(n),n_0=5|')
subplot(1,2,2);
plot(0:length(h)-1,angle(h));
title('angle(h(n)),n_0=5')


n0 = 20; % reset value for n0

% As n0 decreases the image appears to zoom in. The overall shape
% loses detail as n0 decreases.
```









**Task 2:** Generate a pseudo random signal  $v[n]$  and then filter it by performing  $x[n] = v[n] * h[n]$  where  $h[n]$  is obtained from Task 1. Compute, plot and discuss the following:

- The amplitude DTFT of  $v[n]$ , for  $|f| < 0.5$ ;
- The amplitude DTFT of  $x[n]$ , for  $|f| < 0.5$ ;
- The amplitude DTFT of  $x_{up}[n] = \begin{cases} x[m] & n = 3m \\ 0 & n \neq 3m \end{cases}$ , for  $|f| < 0.5$ ;
- The amplitude DTFT of  $x_{down}[n] = x[3n]$ , for  $|f| < 0.5$ .

## task 2

```
%close all
v = rand(1,41);
x = conv(v,h);
V = fftshift(fft(v));

%plot the DTFT of v[n]
figure
plot(0:length(V)-1,abs(V))
title('|V(f)|')


X = fftshift(fft(x));
%plot the DTFT of x[n]
figure
```



```
plot(0:length(X)-1,abs(X))  
title(' |X(f)| ')
```

```
figure  
x1 = upsample(x,3);  
X = fftshift(fft(x1));  
plot(0:length(X)-1,abs(X))  
title(' |X_u_p(f)| ')
```


```
figure  
x2 = downsample(x,3);  
X = fftshift(fft(x2));  
plot(0:length(X)-1,abs(X))  
title(' |X_d_o_w_n(f)| ')
```

% Down-sampling produced a wider, less detailed signal than up-sampling.









*Published with MATLAB® R2016b*