

net_archives.db — Database Schema

Source: Z:\Claude\net_archives.db

Tables

checkins

```
CREATE TABLE checkins (  
  checkin_id INTEGER PRIMARY KEY AUTOINCREMENT,  
  session_id INTEGER NOT NULL,  
  freq_type TEXT,  
  from_callsign TEXT,  
  to_callsign TEXT,  
  checkin_time TEXT,  
  manual_time INTEGER DEFAULT 0,  
  noise_level TEXT,  
  antenna TEXT,  
  signal_L INTEGER DEFAULT 0,  
  signal_G INTEGER DEFAULT 0,  
  signal_W INTEGER DEFAULT 0,  
  signal_VW INTEGER DEFAULT 0,  
  signal_F INTEGER DEFAULT 0,  
  signal_C INTEGER DEFAULT 0,  
  signal_R INTEGER DEFAULT 0,  
  signal_UR INTEGER DEFAULT 0,  
  signal_D INTEGER DEFAULT 0,  
  signal_WI INTEGER DEFAULT 0,  
  signal_I INTEGER DEFAULT 0,  
  has_traffic INTEGER DEFAULT 0,  
  traffic_destination TEXT,  
  traffic_notes TEXT,  
  propagation TEXT,  
  from_operator TEXT,  
  to_operator TEXT,  
  city TEXT,  
  state TEXT,  
  sector TEXT,  
  distance_miles REAL,  
  bearing_degrees REAL,  
  checkin_order INTEGER,  
  dest_operator TEXT  
)
```

sessions

```
CREATE TABLE sessions (  
  session_id INTEGER PRIMARY KEY AUTOINCREMENT,  
  freq_type TEXT,
```

```
net name TEXT,  
net_date TEXT,  
start time TEXT,  
transceiver TEXT,  
antenna TEXT,  
location TEXT,  
primary freq TEXT,  
alt_freq_1 TEXT,  
alt freq 2 TEXT,  
digital mode TEXT,  
secured_time TEXT,  
propagation TEXT,  
noise level TEXT,  
antenna_1_desc TEXT,  
antenna 2 desc TEXT,  
ncs callsign TEXT,  
show_my_db INTEGER DEFAULT 0,  
manual time INTEGER DEFAULT 0,  
archived at TEXT  
)
```

sqlite_sequence

```
CREATE TABLE sqlite_sequence(name,seq)
```