

Contest Duration: 2025-10-18(Sat) 23:30 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20251018T2130&p1=248>) - 2025-10-19(Sun) 01:10 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20251018T2310&p1=248>) (local time) (100 minutes)

[Back to Home \(/home\)](#)

 [Top \(/contests/abc428\)](#)

 [Tasks \(/contests/abc428/tasks\)](#)

 [Clarifications \(/contests/abc428/clarifications\)](#)  [Results ▾](#)

 [Standings \(/contests/abc428/standings\)](#)

 [Virtual Standings \(/contests/abc428/standings/virtual\)](#)  [Editorial \(/contests/abc428/editorial\)](#)

 [Discuss \(<https://codeforces.com/blog/entry/147512>\)](#) 

F - Pyramid Alignment

[Editorial \(/contests/abc428/tasks/abc428_f/editorial\)](#)

 / 

Time Limit: 2 sec / Memory Limit: 1024 MiB

Score : 525 points

Problem Statement

There are N intervals on a number line, numbered from 1 to N .

The left endpoint of interval i is at coordinate 0, and the right endpoint is at coordinate W_i .
Here, $W_1 < W_2 < \dots < W_N$.

You are given Q queries; process them in the order they are given. Each query is one of the following three types:

- Type 1 (1 v): Let l be the coordinate of the current **left endpoint** of interval v . Translate each of the intervals numbered v or less so that its **left endpoint** is at coordinate l .
- Type 2 (2 v): Let r be the coordinate of the current **right endpoint** of interval v . Translate each of the intervals numbered v or less so that its **right endpoint** is at coordinate r .
- Type 3 (3 x): Output the current number of intervals that contain coordinate $x + \frac{1}{2}$.

Constraints

- $1 \leq N \leq 2 \times 10^5$
- $1 \leq Q \leq 2 \times 10^5$
- $1 \leq W_i \leq 10^9$ ($1 \leq i \leq N$)
- $W_1 < W_2 < \dots < W_N$
- For v given in queries of types 1 and 2, $1 \leq v \leq N$.

2026-01-02 (Fri)
05:31:58 +11:00

- For x given in queries of type 3, $0 \leq x \leq 10^9$.
 - At least one query of type 3 is given.
 - All input values are integers.
-

Input

The input is given from Standard Input in the following format:

```
N  
W1 ... WN  
Q  
query1  
query2  
:  
queryQ
```

query_j represents the j -th query. Each query is given in one of the following formats:

```
1 v
```

```
2 v
```

```
3 x
```

Output

Let q be the number of queries of type 3, output q lines. The j -th line ($1 \leq j \leq q$) should contain the answer to the j -th query of type 3.

Sample Input 1

Copy

```
4  
2 4 6 10  
5  
2 3  
1 2  
3 2  
2 4  
3 1
```

Copy

Sample Output 1

Copy

4
1

Copy

Initially, the intervals in order of their numbers are $[0, 2]$, $[0, 4]$, $[0, 6]$, $[0, 10]$.

- For the 1st query, the coordinate of the **right endpoint** of interval 3 before the operation is 6, so the intervals after the operation are $[4, 6]$, $[2, 6]$, $[0, 6]$, $[0, 10]$ in order of their numbers.
- For the 2nd query, the coordinate of the **left endpoint** of interval 2 before the operation is 2, so the intervals after the operation are $[2, 4]$, $[2, 6]$, $[0, 6]$, $[0, 10]$ in order of their numbers.
- For the 3rd query, the intervals that contain coordinate $2 + \frac{1}{2}$ are intervals 1, 2, 3, 4, which is four intervals, so output 4.
- For the 4th query, the coordinate of the **right endpoint** of interval 4 before the operation is 10, so the intervals after the operation are $[8, 10]$, $[6, 10]$, $[4, 10]$, $[0, 10]$ in order of their numbers.
- For the 5th query, the intervals that contain coordinate $1 + \frac{1}{2}$ is only interval 4, which is one interval, so output 1.

/#telegram)

#url=https%3A%2F%2Fatcoder.jp%2Fcontests%2Fabc428%2Ftasks%2Fabc428_f%3Flang%3Den&title=F%20-

[Rule \(/contests/abc428/rules\)](#) [Glossary \(/contests/abc428/glossary\)](#)

[Terms of service \(/tos\)](#) [Privacy Policy \(/privacy\)](#) [Information Protection Policy \(/personal\)](#) [Company \(/company\)](#)
[FAQ \(/faq\)](#) [Contact \(/contact\)](#)

Copyright Since 2012 ©AtCoder Inc. (<http://atcoder.co.jp>) All rights reserved.