

Contest Duration: 2025-06-14(Sat) 22:00 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20250614T2100&p1=248>) - 2025-06-14(Sat) 23:40 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20250614T2240&p1=248>) (local time) (100 minutes)

[Back to Home \(/home\)](/home)

[🏠 Top \(/contests/abc410\)](/contests/abc410)

[📋 Tasks \(/contests/abc410/tasks\)](/contests/abc410/tasks)

[❓ Clarifications \(/contests/abc410/clarifications\)](/contests/abc410/clarifications)

[📊 Results ▼](#)

[🏆 Standings \(/contests/abc410/standings\)](/contests/abc410/standings)

[🏆 Virtual Standings \(/contests/abc410/standings/virtual\)](/contests/abc410/standings/virtual)

[📖 Editorial \(/contests/abc410/editorial\)](/contests/abc410/editorial)

[💬 Discuss \(https://codeforces.com/blog/entry/143737\)](https://codeforces.com/blog/entry/143737)



C - Rotatable Array

[Editorial \(/contests/abc410/tasks/abc410_c/editorial\)](/contests/abc410/tasks/abc410_c/editorial)



Time Limit: 2 sec / Memory Limit: 1024 MiB

Score : 300 points

Problem Statement

There is an integer sequence A of length N , initially $A_i = i$. Process a total of Q queries of the following types:

- Type 1: Change A_p to x .
- Type 2: Output A_p .
- Type 3: Repeat the operation "move the first element of A to the end" k times.
 - Formally, replace A with $(A_2, A_3, \dots, A_N, A_1)$ k times.

Constraints

- All input values are integers.
- $1 \leq N \leq 10^6$
- $1 \leq Q \leq 3 \times 10^5$
- All queries satisfy the following constraints:
 - $1 \leq p \leq N$
 - $1 \leq x \leq 10^6$
 - $1 \leq k \leq 10^9$

Input

The input is given from Standard Input in the following format:

```
N Q
Query1
Query2
⋮
QueryQ
```

Here, Query_{*i*} represents the *i*-th query.

Type 1 queries are given in the following format:

```
1 p x
```

Type 2 queries are given in the following format:

```
2 p
```

Type 3 queries are given in the following format:

```
3 k
```

Output

For each Type 2 query, output the answer on a line.

Sample Input 1

[Copy](#)

```
5 5
2 3
1 2 1000000
3 4
2 2
2 3
```

[Copy](#)

Sample Output 1

[Copy](#)

```
3
1
1000000
```

[Copy](#)

This input contains 5 queries.

2026-01-02 (Fri)
05:25:24 +11:00

- Initially, $A = (1, 2, 3, 4, 5)$.
- The 1st query is Type 2: output $A_3 = 3$.
- The 2nd query is Type 1: replace A_2 with 1000000.
 - After the query, $A = (1, 1000000, 3, 4, 5)$.
- The 3rd query is Type 3: repeat the operation "move the first element of A to the end" 4 times.
 - After the query, $A = (5, 1, 1000000, 3, 4)$.
- The 4th query is Type 2: output $A_2 = 1$.
- The 5th query is Type 2: output $A_3 = 1000000$.

Sample Input 2

Copy

```
1000000 2
1 1000000 999999
3 1000000000
```

Copy

Sample Output 2

Copy

Copy

The output may be empty.

'#telegram)

re#url=https%3A%2F%2Fatcoder.jp%2Fcontests%2Fabc410%2Ftasks%2Fabc410_c%3Flang%3Den&title=C%

[Rule \(/contests/abc410/rules\)](/contests/abc410/rules) [Glossary \(/contests/abc410/glossary\)](/contests/abc410/glossary)

[Terms of service \(/tos\)](/tos) [Privacy Policy \(/privacy\)](/privacy) [Information Protection Policy \(/personal\)](/personal) [Company \(/company\)](/company)

[FAQ \(/faq\)](/faq) [Contact \(/contact\)](/contact)

Copyright Since 2012 ©AtCoder Inc. (<http://atcoder.co.jp>) All rights reserved.

2026-01-02 (Fri)
05:25:24 +11:00