

V1

Nouns & Noun Phrases → Candidate Classes / Value Objects

- Need → Need (interface / abstract)
- Basic need → BasicNeed (leaf in Composite)
- Bundle → Bundle (composite)
- Child part (bundle member) → BundlePart (value object: needName, count)
- Catalog (collection of all needs/bundles) → Catalog
- Log / Ledger / Entry → Ledger, LogEntry
- Funds (daily value) → represented as LogEntry with type FUND
- Goal (daily value) → LogEntry with type GOAL
- Fulfillment (acquire a need) → LogEntry with type NEED (name+count)
- Repository (persistence) → Repository (CSV I/O)
- Controller / App → ApplicationController
- View / Chart / Summary → View, DTOs: DaySummary, SliceBreakdown
- Money/Date → Money (value object), LocalDate (JDK)
- Synonyms normalized: “log/ledger” → Ledger
- “funds/goal entries” → LogEntry typed
- “need/bundle” → Need with BasicNeed/Bundle

Adjectives & Adverbs → Attributes

- Need “fixed / variable / fees / total” →
 - BasicNeed: name: String, fixed: Money, variable: Money, fees: Money
 - Derived total = fixed + variable + fees
- Bundle “composed of... counts” →
 - Bundle: name: String, parts: List<BundlePart>, computed totals via recursion
- Ledger “daily” / “last known” →
 - Ledger: methods fundOn(date), goalOn(date), lastKnownBefore(date)
- Log rules “duplicates allowed” (do not merge) →
 - Ledger stores entries as-is; aggregation happens in queries
- Catalog “no forward references” →
 - Two-phase build or deferred resolution (resolve() after parsing)

Verbs → Methods (first → refined home)

- “load/save” →
 - Repository.loadNeeds()

- Repository.loadLog()
 - Repository.appendLog()
 - Repository.saveAll()
- “add donation / fulfillment” →
 - ApplicationController.addDonation()
 - ApplicationController.addFulfillment()
- “compute today’s totals” →
 - ApplicationController.computeDaySummary()
- “total/fixed/variable/fees” →
 - Need.total()
 - Need.fixed()
 - Need.variable()
 - Need.fees()
- “resolve need names” →
 - Catalog.get(name)
 - Catalog.resolveAll()

V2

Nouns & Noun Phrases → Candidate Classes / Value Objects

- **Need** → **NeedComponent** (interface / abstract)
- **Basic need** → **BasicNeed** (leaf in Composite)
 - Concrete implementation of **NeedComponent**
- **Bundle** → **Bundle** (composite)
 - Concrete implementation of **NeedComponent**
- **Child part** (bundle member) → **BundlePart** (value object: needName, count)
 - Used by **Bundle** to store components
- **Catalog** (collection of all needs/bundles) → **NeedsRepository**
 - Repository for need data
- **Log / Ledger / Entry** → **LedgerRepository**, **LedgerEntry**
 - Repository for log data
- **Abstraction layer** → **AbstractLedgerEntry** (interface)
 - Ensures all entries share common methods
- **Funds** (daily value) → represented as **LedgerEntry** with type FUND
 - Concrete type of **AbstractLedgerEntry**
- **Goal** (daily value) → **LedgerEntry** with type GOAL
 - Concrete type of **AbstractLedgerEntry**
- **Fulfillment** (acquire a need) → **LedgerEntry** with type NEED (name+count)
 - Concrete type of **AbstractLedgerEntry**
- **Repository** (persistence) → Repository (CSV I/O)
 - **NeedsRepository**, **LedgerRepository**
 - Isolates persistence logic (CSV I/O)
- **CSV File Handler** → CSVManager
 - Isolates low-level CSV read/write details
- **Controller / App** → ApplicationController
 - **NeedsRepository**, **LedgerRepository**
 - Coordinates logic
- **View / Chart / Summary** → View, DTOs: DaySummary, SliceBreakdown
 - **ConsoleView**, **DaySummary** (DTO)
 - Presentation layer
- **Money/Date** → **Money** (value object), **LocalDate** (JDK)
 - Primitive types/value objects
- Synonyms normalized: "log/ledger" → Ledger
- "funds/goal entries" → **LedgerEntry** typed

- “need/bundle” → **NeedComponent** with **BasicNeed/Bundle**

Adjectives & Adverbs → Attributes

- Need “fixed / variable / fees / total” →
 - **BasicNeed**: name: String, fixed: Money, variable: Money, fees: Money
 - Derived total = fixed + variable + fees
- Bundle “composed of... counts” →
 - **Bundle**: name: String, parts: List<BundlePart>, computed totals via recursion
- Ledger “daily” / “last known” →
 - **LedgerEntry**: methods fundOn(date), goalOn(date), lastKnownBefore(date)
- Log rules “duplicates allowed” (do not merge) →
 - Ledger stores entries as-is; aggregation happens in queries
- Catalog “no forward references” →
 - Two-phase build or deferred resolution (resolve() after parsing)

Verbs → Methods (first → refined home)

- “load/save” → (**NeedsRepository**, **LedgerRepository**)
 - Repository.loadNeeds()
 - Repository.loadLog()
 - Repository.appendLog()
 - Repository.saveAll()
- “read/write CSV lines” → (**CSVManager**)
 - CSVManager.readAllLines(filename)
 - CSVManager.appendLine(filename, line)
 - CSVManager.writeAllLines(filename, lines)
- “add donation / fulfillment” → (**LedgerController**)
 - AppController.addDonation()
 - AppController.addFulfillment()
- “compute today’s totals” → (**LedgerController**)
 - AppController.computeDaySummary()
- “total/fixed/variable/fees” → (**NeedComponent**, **BasicNeed**, **Bundle**)
 - Need.getTotalCost()
 - Need.getFixedCost()
 - Need.getVariableCost()

- Need.getFeesCost()
- “resolve need names” → (NeedsRepository)
 - Catalog.getNeed(name)
 - Catalog.resolveAll()
- “display” → (ConsoleView)
 - View.displaySummary()
 - View.displayGoal()
- “convert” → (NeedsRepository)
 - Repository.concertNeedsToNeedsObject()
 - Repository.toCSVLine()
- “get summary/need” → (NeedsRepository, LedgerRepository)
 - Repository.getSummary()
 - Repository.getNeed()