

BEYOND NODAL DAMPING

WHEN STABLE REPLACEMENTS FAIL TOGETHER

Minimal Incompatibility Hypergraphs for Safe SG → IBR Transition Planning

Jorge Luis Mayorga Taborda | Universidad de los Andes, Colombia

1 MOTIVATION & QUESTION

Replacing SG units changes the full portfolio. A stable endpoint can still contain an unstable intermediate coalition.




Which replacement combinations are incompatible, why do they fail, and how can paths avoid them?

$$\mathcal{H}(\theta) = \text{Min}_{\subseteq} \{S : \alpha_{\perp}(S, \theta) \geq 0\}$$

Edges mark minimal unstable coalitions.

2 FLAGSHIP RESULT: IEEE-39



15/15
smaller portfolios stable
all strict subsets

$H_4 = \{30, 33, 35, 37\}$
canonical witness
not the universal blocker

$+0.127 \text{ s}^{-1}$
critical growth rate
canonical portfolio

3/327
order-dependent targets
matched-policy IEEE-39 census

4A FROM DEVICES TO NETWORK RETURN

Network update $T_S(s) = T_0(s) + \sum_{i \in S} E_i \Delta Y_i(s) E_i^T$

Characteristic $\det P_S(s) = h_S(s) \det T_0(s) \det(I + M_{SS}(s))$


Local × collective $\det(I + M_{SS}) = \left[\prod_{i \in S} \det(I + M_{ii}) \right] \det(I + Q_{SS})$

Interactions $\det(I + Q_{SS}) = \sum_{T \subseteq S} \mu_T$

Full-order factorization; no reduced-mode equivalence is claimed.

4B THE COLLECTIVE TERM CLOSES

Boundary scan: $g^* = 0.207681$; $\alpha_{\perp} = 0$; $f = 0.7064 \text{ Hz}$



LOCAL DEVICES


$\sigma_{\min} \approx 0.49$
remain regular

NETWORK RETURN

$\sigma_{\min} \approx 4.4 \times 10^{-8}$
approaches singularity


5 POLICY CHANGES THE MINIMAL BLOCKER

Policy atlas A: four IBR candidates




Q/V gain g (horizontal); AVR gain k (vertical).

Distinct full-spectrum hypergraphs



7 A CANONICAL REPAIR IS NOT UNIVERSAL

Synthetic retuning: $g = 0.03625 \rightarrow 0.25$



9A MODEL CHECKS


100/100
cross-code agreement
same model

56/60
time-domain sign agreement
completed phasor-DAE runs

4 zero-frequency disagreements among 60 completed runs; 30 of 90 runs had solver failures.

6 THE CANONICAL H_4 IS NOT UNIVERSAL

Frozen synthetic envelope (1000 scenario IDs)




8 SAFE PATHS CHECK EVERY PREFIX

Path-constrained planning formulation

$$\max \sum_{i \in S_f} P_i \quad \text{s.t. } S_0 = \emptyset, S_{t+1} = S_t \cup \{i_t\}, \alpha_{\perp}(S_t, \theta) < 0 \quad \forall t$$

Matched-policy IEEE-39 census: 3/327 stable targets depend on order.



The order matters: test stability after each replacement.

9B WHAT “SAFE PATH” MEANS HERE

Each prefix is a **re-equilibrated phasor-DAE** portfolio.
The analysis does not simulate **physical switching**, EMT, current limits or DC-link limits.
Blockers depend on the model and control policy.

TAKEAWAY

SAFE PREFIXES, SAFE TRANSITIONS.

A stable endpoint can still hide an unstable intermediate coalition.
Blockers change with the control policy.
Safety here refers to re-equilibrated phasor-DAE prefixes.

CONTACT

Jorge Luis Mayorga Taborda
jl.mayorga@uniandes.edu.co
Universidad de los Andes
Bogotá, Colombia

REFERENCES

- [1] Kundur, *Power System Stability and Control*, 1994.
- [2] Kundur et al., IEEE Trans. Power Syst. 19:1387–1401, 2004.
- [3] Hatziaargyriou et al., IEEE Trans. Power Syst. 36:3271–3281, 2021.
- [4] Dörfler et al., PNAS 110:2005–2010, 2013.
- [5] Milano, *Power System Modelling and Scripting*, 2010.