

# Running funconstrain tests in package optimx

John C. Nash (profjcnash at gmail.com)

2024-04-08

## Abstract

The **funconstrain** package (<https://github.com/jlmelville/funconstrain>) provides R users with a convenient tool to access the test functions of Moré, Garbow, and Hillstom (1981). This vignette article describes a program to apply these test functions to solvers in the **optimx** package (Nash and Varadhan (2011)).

## Background

Numerical optimization of functions of several, namely **n**, parameters is an important computational task. R (R Development Core Team (2008)) is a major platform for scientific and statistical calculations and has provided tools for numerical optimization and nonlinear least squares since its inception. These have been extended via a number of packages. In particular, the author has been heavily involved in this effort, and in collaboration with others has provided the package **optimx** which wraps a number of solvers to allow their invocation by a common calling syntax. Note that *optimization* in R generally means *function minimization*, possibly with bounds (or box) constraints on the function parameters.

It is extremely helpful to users to have examples and tests of function minimization. In many situations it is extremely easy to insert an error into code, so easy-to-apply tests allow for the discovery of such errors. There are a number of collections of test functions with many overlaps and minor differences. A well-established and well-documented set of such functions are those of (**More1981TU?**). These have been translated into R by James Melville in the R package **funconstrain** (<https://github.com/jlmelville/funconstrain>). While initially these provided the function and its gradient given a set of suitable input parameters, the present author added code to compute the Hessian for each test function. This allows Newton-like solvers to be applied. **funconstrain** also provides suggested initial parameter vectors for each of the 35 test functions. However, where there are multiple input possibilities, just one is provided, for example when the test function has a variable number of parameters.

What is then missing is the link between **funconstrain** and the tools in **optimx**, which this article aims to provide.

## Function fufn()

Most of the test functions in (**More1981TU?**) are sums of squares of nonlinear functions. While **n** is the number of parameters, we may have a different number of functions squared in the summation. Call this **m**. This may be altered to give different variations of a given function, so **m** must be provided.

Many of the solvers in **optimx** are capable of handling bounds constraints on the **n** parameters. That is parameter **i** must satisfy

```
lower[i] <= prm[i] <= upper[i]
```

where **prm** is the parameter vector and **lower** and **upper** are vectors of numbers providing lower and upper bounds. Methods in **optimx** that can handle masks are listed in the character vector **bdmeth** returned by the function **optimx::ctrldefault(n)**. Note that a number of parameters **n** must nominally be provided to **ctrldefault()** but generally **n** can be specified as 2 to get the default settings for ‘optimx’. At time of writing

```
bdmeth <- c("L-BFGS-B", "nlinb", "lbfgsb3c", "Rcgmin", "Rtnmin", "nvm",
"Rvmmmin", "bobyqa", "nmkb", "hjk", "hjn", "snewtonm", "ncg",
"slsqp", "tnewt", "nlm", "snewtm", "spg")
```

If the upper and lower bound for a parameter are equal, we can say the parameter is **fixed** or **masked**. This may seem to be a silly option, since it essentially reduces the dimensionality of the problem. However, there are many situations where we have evidence that a parameter takes a particular (fixed) value, but know that we may wish to allow optimization over that parameter in later investigations. Masks allow us to avoid having to rewrite the function, gradient and Hessian code. However, only a few optimization solvers handle masks. The function `optimx::ctrldefault()` returns a value `maskmeth` with a list of solvers that do handle the situation where lower and upper bounds coincide. At the time of writing this is specified as

```
maskmeth <- c("Rcgmin", "nvm", "hjn", "ncg", "snewtonm", "nlinb", "L-BFGS-B")
```

With the above in mind, the function `fufn()` was written to access the test functions of `funconstrain`.

### The fufn.R code

```
fufn <- function(n=NULL, fnum=NULL){
  # return list with tfn=function, tgr=gradient given fn number and n
  if (is.null(fnum)) stop("ffn needs a function number fnum")
  if ((fnum < 1) || (fnum > 35)) stop("fnum must be in [1, 35]")
  # cat("entering ffn, fnum=", fnum, "\n")
  # select function
  funnam <- c("rosen", "freud_roth", "powell_bs", "brown_bs", "beale",
    "jenn_samp", "helical", "bard", "gauss", "meyer", "gulf",
    "box_3d", "powell_s", "wood", "kow_osb", "brown_den",
    "osborne_1", "biggs_exp6", "osborne_2", "watson", "ex_rosen",
    "ex_powell", "penalty_1", "penalty_2", "var_dim", "trigon",
    "brown_al", "disc_bv", "disc_ie", "broyden_tri", "broyden_band",
    "linfun_fr", "linfun_r1", "linfun_r1z", "chebyquad")
  # print(str(funnam))
  fname <- funnam[as.integer(fnum)]
  # cat("fname:", fname, "\n")
  while (fnum %in% 1:35) {
    ameth <- optimx::ctrldefault(2)$bdmeth # Choose only bounded methods
    ameth <- ameth[ameth != "lbfgsb3c"] ## ?? Temporarily remove lbfgsb3c
    ameth <- c(ameth, "L-BFGS-B")
    # ?? may want to test allmeth to check that inappropriate methods are captured
    # cat("in while, fnum=", fnum); tmp <- readline("cont.")
    mm <- 0 # in case m value needed
    if (fnum == 1) {
      n <- 2 # fixed
      mm <- 2
      tt <- rosen()
      if (is.function(tt$x0)) {
        xx0 <- tt$x0(n)
      }
      else xx0 <- tt$x0
      lo <- rep((min(xx0)-0.1), n)
      up <- rep((max(xx0)+0.1), n)
      break }

    if (fnum == 2) {
      n <- 2 # fixed
```

```

mm <- 2
tt <- freud_roth()
if (is.function(tt$x0)) {
  xx0<-tt$x0(n)
}
else xx0 <- tt$x0
lo <- rep((min(xx0)-0.1), n)
up <- rep((max(xx0)+0.1), n)
break }

if (fnum == 3) {
  n <- 2 # fixed
  mm <- 2
  tt <- powell_bs()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 4) {
  n <- 2 # fixed
  mm <- 3
  tt <- brown_bs()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
## BAD -- reset 20240323
#   lo <- rep((min(xx0)-0.1), n)
#   up <- rep((max(xx0)+0.1), n)
  lo <- -1e20
  up <- -lo
  break }

if (fnum == 5) {
  n <- 2 # fixed
  mm <- 3
  tt <- beale()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 6) {
  n <- 2 # fixed
  mm <- 10
  tt <- jenn_samp()

```

```

if (is.function(tt$x0)) {
  xx0<-tt$x0(n)
}
else xx0 <- tt$x0
lo <- rep((min(xx0)-0.1), n)
up <- rep((max(xx0)+0.1), n)
break }

if (fnum == 7) {
  n <- 3 # fixed
  tt <- helical()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 8) {
  n <- 3 # fixed
  mm <- 15
  tt <- bard()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 9) {
  n <- 3 # fixed
  mm <- 15
  tt <- gauss()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 10) {
  n <- 3 # fixed
  m <- 16 # ?? how to return
  tt <- meyer()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)

```

```

break }

if (fnum == 11) {
  n <- 3
  mm <- 99
  tt <- gulf()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 12) {
  n <- 3
  mm <- 20
  tt <- box_3d()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 13) {
  n <- 4
  tt <- powell_s()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 14) {
  n <- 4
  tt <- wood()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 15) {
  mm <- 11
  n <- 4
  tt <- kow_osb()
  if (is.function(tt$x0)) {

```

```

    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 16) {
  mm <- 20
  n <- 4
  tt <- brown_den()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 17) {
  mm <- 33
  n <- 5
  tt <- osborne_1()
  ameth<-ameth[-which(ameth=="L-BFGS-B")] # remove L-BFGS-B from this case
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  lo[4] <- 0
  lo[5] <- 0
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 18) {
  mm <- 20
  n <- 6
  tt <- biggs_exp6()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 19) {
  mm <- 65
  n <- 11
  tt <- osborne_2()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }

```

```

else xx0 <- tt$x0
lo <- rep((min(xx0)-0.1), n)
up <- rep((max(xx0)+0.1), n)
break }

if (fnum == 20) {
  n <- 8
  mm <- 31
  tt <- watson()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 21) {
  n <- 10
  tt <- ex_rosen()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 22) {
  n <- 20
  tt <- ex_powell()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 23) {
  n <- 10
  mm <- n + 1
  tt <- penalty_1()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 24) {
  n <- 10

```

```

mm <- n + 1
tt <- penalty_2()
if (is.function(tt$x0)) {
  xx0<-tt$x0(n)
}
else xx0 <- tt$x0
lo <- rep((min(xx0)-0.1), n)
up <- rep((max(xx0)+0.1), n)
break }

if (fnum == 25) {
  n <- 6
  mm <- n + 2
  tt <- var_dim()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 26) {
  n <- 8
  tt <- trigon()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 27) {
  n <- 8
  mm <- n
  tt <- brown_al()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 28) {
  n <- 6
  mm <- n
  tt <- disc_bv()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0

```



```

lo <- rep((min(xx0)-0.1), n)
up <- rep((max(xx0)+0.1), n)
break }

if (fnum == 29) {
  n <- 8
  mm <- n
  tt <- disc_ie()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 30) {
  n <- 8
  mm <- n
  tt <- broyden_tri()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 31) {
  n <- 8
  mm <- n
  tt <- broyden_band()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 32) {
  mm <- 10
  n <- 8
  tt <- linfun_fr()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 33) {

```

```

mm <- 10
n <- 8
tt <- linfofun_r1()
if (is.function(tt$x0)) {
  xx0<-tt$x0(n)
}
else xx0 <- tt$x0
lo <- rep((min(xx0)-0.1), n)
up <- rep((max(xx0)+0.1), n)
break }

if (fnum == 34) {
  mm <- 10
  n <- 8
  tt <- linfofun_r1z()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }

if (fnum == 35) {
  n <- 8
  m <- n
  tt <- chebyquad()
  if (is.function(tt$x0)) {
    xx0<-tt$x0(n)
  }
  else xx0 <- tt$x0
  lo <- rep((min(xx0)-0.1), n)
  up <- rep((max(xx0)+0.1), n)
  break }
}
# NOTE: bounds are experimental only
mask <- rep(1L, n) # masks set to "free" (not masked)
val <- list(npar = n, ffn=tt$fn, fgr=tt$gr, x0=xx0, lo=lo, up=up,
           mask=mask, fname=fname, ameth=ameth)
# cat("val:"); print(val); tmp<-readline('exit ffn')
val
} # end fufn

```

## References

- Moré, Jorge J., Burton S. Garbow, and Kenneth E. Hillstom. 1981. "Testing Unconstrained Optimization Software." *J-Toms* 7 (1): 17–41.
- Nash, John C, and Ravi Varadhan. 2011. *Optimx: A Replacement and Extension of the optim() Function*. Nash Information Services Inc.; Johns Hopkins University.
- R Development Core Team. 2008. *R: A Language and Environment for Statistical Computing*. Vienna, Austria: R Foundation for Statistical Computing. <http://www.R-project.org>.