Lecture 15: Single-Source Shortest Paths

Jessica Sorrell

October 27, 2026
601.433/633 Introduction to Algorithms
Slides by Mike Dinitz

Announcements

- Mid-semester feedback form on courselore!
- HW7 an oral presentation. Start forming groups.

Prof. Dinitz will be away on Thursday. So:

- No office hours.
- I'll be teaching 1:30pm section.

Introduction

Setup:

- Directed graph $G = (V, E)$
- Length $\ell(x, y)$ on each edge $(x, y) \in E$ (equivalent: $\ell : E \to \mathbb{R}$)
- Length of path P is $\ell(P) = \sum_{(x,y) \in P} \ell(x, y)$
- $d(x, y) = \min_{x \to y \text{ paths } P} \ell(P)$

Introduction

Setup:

- Directed graph $G = (V, E)$
- Length $\ell(x, y)$ on each edge $(x, y) \in E$ (equivalent: $\ell : E \to \mathbb{R}$)
- Length of path P is $\ell(P) = \sum_{(x,y) \in P} \ell(x, y)$
- $d(x, y) = \min_{x \to y \text{ paths } P} \ell(P)$

Today: source $v \in V$, want to compute shortest path from v to every $u \in V$

- $d(u) = d(v, u)$ for all $u \in V$
- Representation: "shortest path tree" out of v.
- Often only care about distances – can reconstruct tree from distances.

Bellman-Ford

Dynamic Programming Approach

Subproblems:

- $OPT(u, i)$: shortest path from v to u that uses at most i hops (edges)
- If no such path, set to "infinitely long" fake path.
- For simplicity, create loop (edge to and from the same node) at every node, length 0

Dynamic Programming Approach

Subproblems:

- $OPT(u, i)$: shortest path from v to u that uses at most i hops (edges)
- If no such path, set to "infinitely long" fake path.
- For simplicity, create loop (edge to and from the same node) at every node, length 0

Theorem (Optimal Substructure)

$$\ell(OPT(u,k)) = \begin{cases} 0 & \text{if } u = v, k = 0 \\ \infty & \text{if } u \neq v, k = 0 \\ & \text{otherwise} \end{cases}$$

Dynamic Programming Approach

Subproblems:

- $OPT(u, i)$: shortest path from v to u that uses at most i hops (edges)
- If no such path, set to "infinitely long" fake path.
- For simplicity, create loop (edge to and from the same node) at every node, length 0

Theorem (Optimal Substructure)

$$\ell(OPT(u,k)) = \begin{cases} 0 & \text{if } u = v, k = 0 \\ \infty & \text{if } u \neq v, k = 0 \\ \min_{w:(w,u)\in E}(\ell(OPT(w,k-1)) + \ell(w,u)) & \text{otherwise} \end{cases}$$

Proof of Optimal Substructure

Induction on k.

$k = 0$: ✓. So let $k \geq 1$.

Proof of Optimal Substructure

Induction on k.

$k = 0$: ✓. So let $k \geq 1$.

$\leq$: Let $x = \arg\min_{w:(w,u)\in E}(\ell(OPT(w, k-1)) + \ell(w, u))$

$\implies$ $OPT(x, k-1) \circ (x, u)$ is a $v \to u$ path with at most k edges, length $\ell(OPT(x, k-1)) + \ell(x, u)$

$\implies$ $\ell(OPT(u, k)) \leq \min_{w:(w,u)\in E}(\ell(OPT(w, k-1)) + \ell(w, u))$

Proof of Optimal Substructure

Induction on k.

$k = 0$: ✓. So let $k \geq 1$.

$\leq$: Let $x = \arg\min_{w:(w,u)\in E}(\ell(OPT(w, k-1)) + \ell(w, u))$

$\implies$ $OPT(x, k-1) \circ (x, u)$ is a $v \to u$ path with at most k edges, length $\ell(OPT(x, k-1)) + \ell(x, u)$

$\implies$ $\ell(OPT(u, k)) \leq \min_{w:(w,u)\in E}(\ell(OPT(w, k-1)) + \ell(w, u))$

$\geq$: Let z be node before u in $OPT(u, k)$, and let P' be the first $k-1$ edges of $OPT(u, k)$. Then

$$\begin{aligned}\ell(OPT(u, k)) &= \ell(P') + \ell(z, u) \geq \ell(OPT(z, k-1)) + \ell(z, u) \\ &\geq \min_{w:(w,u)\in E}(\ell(OPT(w, k-1)) + \ell(w, u))\end{aligned}$$

Bellman-Ford Algorithm

Obvious dynamic program!

$M[u, 0] = \infty$ for all $u \in V, u \neq v$
$M[v, 0] = 0$

for($k = 1$ to $n - 1$) {
    for($u \in V$) {
        $M[u, k] = \min_{w:(w,u)\in E}(M[w, k-1] + \ell(w, u))$
    }
}

Bellman-Ford Algorithm

Obvious dynamic program!

$M[u, 0] = \infty$ for all $u \in V, u \neq v$
$M[v, 0] = 0$

for($k = 1$ to $n - 1$) {
  for($u \in V$) {
    $M[u, k] = \min_{w:(w,u)\in E}(M[w, k-1] + \ell(w, u))$
  }
}

Running Time:

Bellman-Ford Algorithm

Obvious dynamic program!

$M[u, 0] = \infty$ for all $u \in V, u \neq v$
$M[v, 0] = 0$

for($k = 1$ to $n - 1$) {
  for($u \in V$) {
    $M[u, k] = \min_{w:(w,u) \in E}(M[w, k-1] + \ell(w, u))$
  }
}

Running Time:

- Obvious: $O(n^3)$

Bellman-Ford Algorithm

Obvious dynamic program!

$M[u, 0] = \infty$ for all $u \in V, u \neq v$
$M[v, 0] = 0$

for($k = 1$ to $n - 1$) {
  for($u \in V$) {
    $M[u, k] = \min_{w:(w,u)\in E}(M[w, k-1] + \ell(w, u))$
  }
}

Running Time:

- Obvious: $O(n^3)$
- Smarter: $O(mn)$

Bellman-Ford: Correctness

Theorem

After algorithm completes, $M[u,k] = \ell(OPT(u,k))$ *for all* $k \leq n-1$ *and* $u \in V$.

Bellman-Ford: Correctness

Theorem

After algorithm completes, $M[u,k] = \ell(OPT(u,k))$ *for all* $k \leq n-1$ *and* $u \in V$.

Proof.

Induction on k. Obviously true for $k = 0$.

Bellman-Ford: Correctness

Theorem

After algorithm completes, $M[u,k] = \ell(OPT(u,k))$ *for all* $k \leq n-1$ *and* $u \in V$.

Proof.

Induction on k. Obviously true for $k = 0$.

$$
\begin{aligned}
M[u,k] &= \min_{w:(w,u)\in E} (M[w,k-1] + \ell(w,u)) && \text{(algorithm)} \\
&= \min_{w:(w,u)\in E} (\ell(OPT(w,k-1)) + \ell(w,u)) && \text{(induction)} \\
&= \ell(OPT(u,k)) && \text{(optimal substructure)}
\end{aligned}
$$

□

Negative Weights and Cycles

Suppose weights are negative. Does the problem make sense?

Negative Weights and Cycles

Suppose weights are negative. Does the problem make sense?

- Negative-weight cycle: not really!

Negative Weights and Cycles

Suppose weights are negative. Does the problem make sense?

- Negative-weight cycle: not really! Go around cycle forever, make distances arbitrarily negative

Negative Weights and Cycles

Suppose weights are negative. Does the problem make sense?

- Negative-weight cycle: not really! Go around cycle forever, make distances arbitrarily negative
- No negative-weight cycle: everything we did before is fine!

Negative Weights and Cycles

Suppose weights are negative. Does the problem make sense?

- Negative-weight cycle: not really! Go around cycle forever, make distances arbitrarily negative
- No negative-weight cycle: everything we did before is fine!

Detecting negative-weight cycle:

Negative Weights and Cycles

Suppose weights are negative. Does the problem make sense?

- Negative-weight cycle: not really! Go around cycle forever, make distances arbitrarily negative
- No negative-weight cycle: everything we did before is fine!

Detecting negative-weight cycle: One more round of Bellman-Ford!

Recent Progress

Fun fact: Bellman-Ford was best-known algorithm with negative (real) edge weights until very recently!

- Fineman [STOC '24, best paper]: $\tilde{O}(mn^{8/9})$.
- Yufan Huang, Peter Jin, and Kent Quanrud [SODA '25]: $\tilde{O}(mn^{4/5})$.
- $\vdots$
- Isaac M. Hair, George Z. Li, Jason Li, and Junkai Zhang [arXiv July '26]: $O(m^{1+o(1)})$.

Caveat: randomized!

Relaxations

Common primitive in shortest path algorithms

- Reinterpret Bellman-Ford via relaxations
- Use relaxations for Dijkstra's algorithm

Relaxations

Common primitive in shortest path algorithms

- Reinterpret Bellman-Ford via relaxations
- Use relaxations for Dijkstra's algorithm

$\hat{d}(u)$: upper bound on $d(u)$

- Initially: $\hat{d}(v) = 0$, $\hat{d}(u) = \infty$ for all $u \neq v$

Relaxations

Common primitive in shortest path algorithms

- Reinterpret Bellman-Ford via relaxations
- Use relaxations for Dijkstra's algorithm

$\hat{d}(u)$: upper bound on $d(u)$

- Initially: $\hat{d}(v) = 0$, $\hat{d}(u) = \infty$ for all $u \neq v$

Intuition for relax(x, y): can we improve $\hat{d}(y)$ by going through x?

Relaxations

Common primitive in shortest path algorithms

- Reinterpret Bellman-Ford via relaxations
- Use relaxations for Dijkstra's algorithm

$\hat{d}(u)$: upper bound on $d(u)$

- Initially: $\hat{d}(v) = 0$, $\hat{d}(u) = \infty$ for all $u \neq v$

Intuition for relax(x, y): can we improve $\hat{d}(y)$ by going through x?

```
relax(x, y) {
    if(d̂(y) > d̂(x) + ℓ(x, y)) {
        d̂(y) = d̂(x) + ℓ(x, y)
        y.parent = x
    }
}
```

Bellman-Ford as Relaxations

```
for(i = 1 to n − 1) {
    foreach(u ∈ V) {
        foreach(edge (x, u)) {
            relax(x, u)
        }
    }
}
```

Bellman-Ford as Relaxations

```
for(i = 1 to n − 1) {
    foreach(u ∈ V) {
        foreach(edge (x, u)) {
            relax(x, u)
        }
    }
}
```

Not precisely the same: freezing/parallelism

Dijkstra's Algorithm

High Level

Intuition: "greedy starting at v"

- BFS but with edge lengths: use priority queue (heap) instead of queue!

Pros: faster than Bellman-Ford (super fast with appropriate data structures)


Cons: Doesn't work with negative edge weights.

Dijkstra's Algorithm

$T = \varnothing$
$\hat{d}(v) = 0$
$\hat{d}(u) = \infty$ for all $u \neq v$

while(not all nodes in T) {
    let u be node not in T with minimum $\hat{d}(u)$
    Add u to T
    foreach edge (u, x) with $x \notin T$ {
        relax(u,x)
    }
}

Dijkstra Example



Dijkstra Correctness

Theorem

Throughout the algorithm:

1. $\boldsymbol{T}$ *is a shortest-path tree from* $\boldsymbol{v}$ *to the nodes in* $\boldsymbol{T}$*, and*
2. $\hat{\boldsymbol{d}}(\boldsymbol{u}) = \boldsymbol{d}(\boldsymbol{u})$ *for every* $\boldsymbol{u} \in \boldsymbol{T}$*.*

Dijkstra Correctness

Theorem

Throughout the algorithm:

1. T *is a shortest-path tree from* v *to the nodes in* T, *and*
2. $\hat{d}(u) = d(u)$ *for every* $u \in T$.

Proof. Induction on $|T|$ (iterations of algorithm)

Dijkstra Correctness

Theorem

Throughout the algorithm:

1. T *is a shortest-path tree from* v *to the nodes in* T*, and*
2. $\hat{d}(u) = d(u)$ *for every* $u \in T$*.*

Proof. Induction on $|T|$ (iterations of algorithm)

Base Case: After first iteration (when $|T| = 1$), added v to T with $\hat{d}(v) = d(v) = 0$ ✓

Correctness: Inductive Step (Sketch)


Consider iteration when $\boldsymbol{u}$ added to $\boldsymbol{T}$, let $\boldsymbol{w} = \boldsymbol{u.parent}$

$\implies \hat{\boldsymbol{d}}(\boldsymbol{u}) = \hat{\boldsymbol{d}}(\boldsymbol{w}) + \ell(\boldsymbol{w}, \boldsymbol{u}) = \boldsymbol{d}(\boldsymbol{w}) + \ell(\boldsymbol{w}, \boldsymbol{u})$ (induction)

Correctness: Inductive Step (Sketch)

Consider iteration when u added to T, let $w = u.parent$

$\implies \hat{d}(u) = \hat{d}(w) + \ell(w,u) = d(w) + \ell(w,u)$ (induction)




- Assume for contradiction that $\hat{d}(u) > d(u)$.
- Red path P actual shortest path, black path found by Dijkstra.
- w' predecessor of u on P. Can't be in T.
  - If it was, would have $\hat{d}(w') = d(w')$ by induction, would have relaxed (w', u), so would have $w' = u.parent$
- x first node of P outside T, previous node y

Correctness: Inductive Step (Sketch)

Consider iteration when u added to T, let $w = u.parent$

$\implies \hat{d}(u) = \hat{d}(w) + \ell(w,u) = d(w) + \ell(w,u)$ (induction)




- Assume for contradiction that $\hat{d}(u) > d(u)$.
- Red path P actual shortest path, black path found by Dijkstra.
- w' predecessor of u on P. Can't be in T.
  - If it was, would have $\hat{d}(w') = d(w')$ by induction, would have relaxed (w', u), so would have $w' = u.parent$
- x first node of P outside T, previous node y

$$\hat{d}(x) \leq \hat{d}(y) + \ell(y,x) = d(y) + \ell(y,x) \leq \ell(P) = d(u) < \hat{d}(u)$$

Correctness: Inductive Step (Sketch)

Consider iteration when u added to T, let $w = u.parent$

$\implies \hat{d}(u) = \hat{d}(w) + \ell(w,u) = d(w) + \ell(w,u)$ (induction)



- Assume for contradiction that $\hat{d}(u) > d(u)$.
- Red path P actual shortest path, black path found by Dijkstra.
- w' predecessor of u on P. Can't be in T.
  - If it was, would have $\hat{d}(w') = d(w')$ by induction, would have relaxed (w', u), so would have $w' = u.parent$
- x first node of P outside T, previous node y

$$\hat{d}(x) \leq \hat{d}(y) + \ell(y,x) = d(y) + \ell(y,x) \leq \ell(P) = d(u) < \hat{d}(u)$$

Contradiction! Algorithm would have chosen x next, not u.

Running Time

Algorithm needs to:

- Select node with minimum $\hat{d}$ value n times
- Decrease a $\hat{d}$ value at most once per relaxation $\implies \leq m$ times.

Running Time

Algorithm needs to:

- Select node with minimum $\hat{d}$ value n times
- Decrease a $\hat{d}$ value at most once per relaxation $\implies \leq m$ times.

Nothing fancy, keep $\hat{d}(u)$ in the adjacency list (or separate array):
$\implies$ Selecting min $\hat{d}$ value takes $O(n)$ time $\implies O(n^2 + m) = O(n^2)$ total.

Running Time

Algorithm needs to:

- Select node with minimum $\hat{d}$ value n times
- Decrease a $\hat{d}$ value at most once per relaxation $\implies \leq m$ times.

Nothing fancy, keep $\hat{d}(u)$ in the adjacency list (or separate array):
$\implies$ Selecting min $\hat{d}$ value takes $O(n)$ time $\implies O(n^2 + m) = O(n^2)$ total.

Keep $\hat{d}$ values in a heap!

- Insert n times
- Extract-Min n times
- Decrease-Key m times

Running Time

Algorithm needs to:

- Select node with minimum $\hat{d}$ value n times
- Decrease a $\hat{d}$ value at most once per relaxation $\implies \leq m$ times.

Nothing fancy, keep $\hat{d}(u)$ in the adjacency list (or separate array):
$\implies$ Selecting min $\hat{d}$ value takes $O(n)$ time $\implies O(n^2 + m) = O(n^2)$ total.

Keep $\hat{d}$ values in a heap!

- Insert n times
- Extract-Min n times
- Decrease-Key m times

Binary heap: $O(\log n)$ per operation
$\implies O((m + n) \log n)$ running time.

Running Time

Algorithm needs to:

- Select node with minimum $\hat{d}$ value n times
- Decrease a $\hat{d}$ value at most once per relaxation $\implies \leq m$ times.

Nothing fancy, keep $\hat{d}(u)$ in the adjacency list (or separate array):
$\implies$ Selecting min $\hat{d}$ value takes $O(n)$ time $\implies O(n^2 + m) = O(n^2)$ total.

Keep $\hat{d}$ values in a heap!

- Insert n times
- Extract-Min n times
- Decrease-Key m times

Binary heap: $O(\log n)$ per operation
$\implies O((m+n)\log n)$ running time.

Fibonacci Heap:

- Insert, Decrease-Key $O(1)$ amortized
- Extract-Min $O(\log n)$ amortized

$\implies O(m + n\log n)$ running time