

Lecture 9: Disjoint Sets / Union-Find

Jessica Sorrell

September 29, 2026

601.433/633 Introduction to Algorithms

Slides by Mike Dinitz

Introduction

Informal: Universe of elements, want to maintain *disjoint sets*.

Slightly more formally:

- ▶ $\text{Make-Set}(x)$: create a new set containing just x (i.e., $\{x\}$)
- ▶ $\text{Union}(x, y)$: Replace set containing x (S) and set containing y (T) with single set $S \cup T$
- ▶ $\text{Find}(x)$: Return *representative* of set containing x

Introduction

Informal: Universe of elements, want to maintain *disjoint sets*.

Slightly more formally:

- ▶ Make-Set($\mathbf{x}$): create a new set containing just $\mathbf{x}$ (i.e., $\{\mathbf{x}\}$)
- ▶ Union($\mathbf{x}, \mathbf{y}$): Replace set containing $\mathbf{x}$ ($\mathbf{S}$) and set containing $\mathbf{y}$ ($\mathbf{T}$) with single set $\mathbf{S} \cup \mathbf{T}$
- ▶ Find($\mathbf{x}$): Return *representative* of set containing $\mathbf{x}$

Rules: every set has a *unique* representative.

- ▶ If $\mathbf{x}$ and $\mathbf{y}$ are in same set, Find($\mathbf{x}$) = Find($\mathbf{y}$)
- ▶ If $\mathbf{x}$ and $\mathbf{y}$ are in different sets, then Find($\mathbf{x}$) $\neq$ Find($\mathbf{y}$)
- ▶ Make-Set($\mathbf{x}$): cannot be called on the same $\mathbf{x}$ twice

Introduction

Informal: Universe of elements, want to maintain *disjoint sets*.

Slightly more formally:

- ▶ $\text{Make-Set}(x)$: create a new set containing just x (i.e., $\{x\}$)
- ▶ $\text{Union}(x, y)$: Replace set containing x (S) and set containing y (T) with single set $S \cup T$
- ▶ $\text{Find}(x)$: Return *representative* of set containing x

Rules: every set has a *unique* representative.

- ▶ If x and y are in same set, $\text{Find}(x) = \text{Find}(y)$
- ▶ If x and y are in different sets, then $\text{Find}(x) \neq \text{Find}(y)$
- ▶ $\text{Make-Set}(x)$: cannot be called on the same x twice

Note: disjoint (and partition) by construction!

Introduction (II)


Notation and Notes:

- ▶ **m** operations total
- ▶ **n** of which are Make-Sets (so **n** elements)
- ▶ Assume have pointer/access to elements we care about (like last class)

First Approach: Lists

Linked list for each set.


- ▶ Representative of set is head (first element on list)
- ▶ Each element has pointer to head and to next element, so stored as triple: (element, head, next)




First Approach: Lists

Linked list for each set.

- ▶ Representative of set is head (first element on list)
- ▶ Each element has pointer to head and to next element, so stored as triple: (element, head, next)




Make-Set(*x*):




First Approach: Lists

Linked list for each set.

- ▶ Representative of set is head (first element on list)
- ▶ Each element has pointer to head and to next element, so stored as triple: (element, head, next)





Make-Set(x):




Find(x): return $x \rightarrow \text{head}$

Union(x, y)




Union(x, y)




Obvious approach:

- ▶ Walk down **S** to final element **z** (starting from **x**)
- ▶ Set **z** $\rightarrow$ next = **y** $\rightarrow$ head
- ▶ Walk down **T**, set every element's head pointer to **x** $\rightarrow$ head



Union(x, y)





Union(x, y)





Union(x, y)




Running time:




Union(x, y)



Running time: $O(|S| + |T|)$




Union(x, y)



Running time: $O(|S| + |T|)$

- ▶ $|S|$ to walk down S to final element
- ▶ $|T|$ to walk down T resetting head pointers

Union(x, y)



Running time: $O(|S| + |T|)$

- ▶ $|S|$ to walk down S to final element
- ▶ $|T|$ to walk down T resetting head pointers

Since $|S|, |T|$ could be $\Theta(n)$,
can only say $O(n)$ for Unions


Improved Union(x, y)

Observation: don't need to preserve ordering inside the Union!

Improved Union(x, y)

Observation: don't need to preserve ordering inside the Union!


- ▶ Splice T into S right after x



Improved Union(x, y)

Observation: don't need to preserve ordering inside the Union!

- ▶ Splice T into S right after x




Running time:

Improved Union(x, y)

Observation: don't need to preserve ordering inside the Union!

- ▶ Splice T into S right after x




Running time: $O(|T|)$

Improved Union(x, y)

Observation: don't need to preserve ordering inside the Union!

- ▶ Splice T into S right after x



Running time: $O(|T|)$

- ▶ Still can't say anything better than $O(n)$

Even more improved $\text{Union}(x, y)$

Observation: Why splice T into S ? Could also splice S into T .

- ▶ Time $O(|S|)$

Even more improved $\text{Union}(x, y)$

Observation: Why splice T into S ? Could also splice S into T .

- ▶ Time $O(|S|)$

Splice smaller into bigger!

- ▶ Store size of set in head node.
- ▶ Splice smaller into bigger: time $O(\min(|S|, |T|))$
- ▶ *Still* only $O(n)$. But now can make stronger amortized guarantee!

Even more improved Union(x, y)

Observation: Why splice T into S ? Could also splice S into T .

- ▶ Time $O(|S|)$

Splice smaller into bigger!

- ▶ Store size of set in head node.
- ▶ Splice smaller into bigger: time $O(\min(|S|, |T|))$
- ▶ *Still* only $O(n)$. But now can make stronger amortized guarantee!

Theorem

The amortized cost of Find and Union is $O(1)$, and the amortized cost of Make-Set is $O(\log n)$.

Corollary

The total running time is $O(m + n \log n)$.

Amortized Analysis of List Algorithm

Banking/accounting argument: bank for every element

- ▶ When an element is created (via Make-Set), add **$\log n$** tokens to its bank
- ▶ Find does not affect banks
- ▶ When doing Union, take token from bank of each element in smaller set.

Amortized Analysis of List Algorithm

Banking/accounting argument: bank for every element

- ▶ When an element is created (via Make-Set), add **$\log n$** tokens to its bank
- ▶ Find does not affect banks
- ▶ When doing Union, take token from bank of each element in smaller set.

Obvious: initially, total bank is **0** (no elements).

Amortized Analysis of List Algorithm

Banking/accounting argument: bank for every element

- ▶ When an element is created (via Make-Set), add **$\log n$** tokens to its bank
- ▶ Find does not affect banks
- ▶ When doing Union, take token from bank of each element in smaller set.

Obvious: initially, total bank is **0** (no elements).

Lemma

No bank is ever negative.

Amortized Analysis of List Algorithm

Banking/accounting argument: bank for every element

- ▶ When an element is created (via Make-Set), add **$\log n$** tokens to its bank
- ▶ Find does not affect banks
- ▶ When doing Union, take token from bank of each element in smaller set.

Obvious: initially, total bank is **0** (no elements).

Lemma

No bank is ever negative.

Proof.

Fix element **e** . Starts with **$\log n$** tokens. When do we remove a token?

Amortized Analysis of List Algorithm

Banking/accounting argument: bank for every element

- ▶ When an element is created (via Make-Set), add **$\log n$** tokens to its bank
- ▶ Find does not affect banks
- ▶ When doing Union, take token from bank of each element in smaller set.

Obvious: initially, total bank is **0** (no elements).

Lemma

No bank is ever negative.

Proof.

Fix element **e** . Starts with **$\log n$** tokens. When do we remove a token?

- ▶ When in smaller set of a Union.

Amortized Analysis of List Algorithm

Banking/accounting argument: bank for every element

- ▶ When an element is created (via Make-Set), add **$\log n$** tokens to its bank
- ▶ Find does not affect banks
- ▶ When doing Union, take token from bank of each element in smaller set.

Obvious: initially, total bank is **0** (no elements).

Lemma

No bank is ever negative.

Proof.

Fix element **e** . Starts with **$\log n$** tokens. When do we remove a token?

- ▶ When in smaller set of a Union.
- ▶ Size of set containing **e** at least doubles!

Amortized Analysis of List Algorithm

Banking/accounting argument: bank for every element

- ▶ When an element is created (via Make-Set), add **$\log n$** tokens to its bank
- ▶ Find does not affect banks
- ▶ When doing Union, take token from bank of each element in smaller set.

Obvious: initially, total bank is **0** (no elements).

Lemma

No bank is ever negative.

Proof.

Fix element **e** . Starts with **$\log n$** tokens. When do we remove a token?

- ▶ When in smaller set of a Union.
- ▶ Size of set containing **e** at least doubles!
- ▶ Can only happen at most **$\log n$** times.



Amortized Analysis of List Algorithm (cont'd)

Make-Set:

- ▶ True cost: $O(1)$
- ▶ Change in banks: $\log n$

⇒ Amortized cost: $O(1) + O(\log n) = O(\log n)$

Amortized Analysis of List Algorithm (cont'd)

Make-Set:

- ▶ True cost: $O(1)$
- ▶ Change in banks: $\log n$

⇒ Amortized cost: $O(1) + O(\log n) = O(\log n)$

Find:

- ▶ True cost: $O(1)$
- ▶ Change in banks: 0

⇒ Amortized cost: $O(1) + 0 = O(1)$

Amortized Analysis of List Algorithm (cont'd)

Make-Set:

- ▶ True cost: $O(1)$
- ▶ Change in banks: $\log n$

⇒ Amortized cost: $O(1) + O(\log n) = O(\log n)$

Find:

- ▶ True cost: $O(1)$
- ▶ Change in banks: 0

⇒ Amortized cost: $O(1) + 0 = O(1)$

Union:

- ▶ True cost: $\min(|S|, |T|)$
- ▶ Change in banks: $-\min(|S|, |T|)$

⇒ Amortized cost: $\min(|S|, |T|) - \min(|S|, |T|) = 0 = O(1)$.

Even Better

Starting idea: want to make Unions faster, willing to make Finds a little slower.

- ▶ Slow part of Union: updating all head pointers in smaller list.
- ▶ Don't do it!

Even Better

Starting idea: want to make Unions faster, willing to make Finds a little slower.

- ▶ Slow part of Union: updating all head pointers in smaller list.
- ▶ Don't do it!
- ▶ Results in trees rather than lists (can drop next pointer)

Even Better

Starting idea: want to make Unions faster, willing to make Finds a little slower.

- ▶ Slow part of Union: updating all head pointers in smaller list.
- ▶ Don't do it!
- ▶ Results in trees rather than lists (can drop next pointer)

Finds slow: need to walk up tree

Even Better

Starting idea: want to make Unions faster, willing to make Finds a little slower.

- ▶ Slow part of Union: updating all head pointers in smaller list.
- ▶ Don't do it!
- ▶ Results in trees rather than lists (can drop next pointer)

Finds slow: need to walk up tree

- ▶ Use *this* time to “update head” pointers: on Find(x), change pointers of x and all ancestors to point to root
- ▶ *Path Compression*

Even Better

Starting idea: want to make Unions faster, willing to make Finds a little slower.

- ▶ Slow part of Union: updating all head pointers in smaller list.
- ▶ Don't do it!
- ▶ Results in trees rather than lists (can drop next pointer)

Finds slow: need to walk up tree

- ▶ Use *this* time to “update head” pointers: on Find(x), change pointers of x and all ancestors to point to root
- ▶ *Path Compression*

Idea 2: *Union By Rank*

- ▶ Size of set was important for lists, less important for trees.
- ▶ Choose which set to splice into which by *rank* of trees (related to height)

Main Result

Theorem

When using Path Compression and Union By Rank, total time at most $O(m \log^ n)$.*

$\log^*$: iterated $\log_2$.

- ▶ $\log^* n = \#$ times apply $\log_2$ until get to ≤ 1

Main Result

Theorem

When using Path Compression and Union By Rank, total time at most $O(m \log^ n)$.*

$\log^*$: iterated $\log_2$.

- ▶ $\log^* n = \#$ times apply $\log_2$ until get to ≤ 1
- ▶ $\log^*(2^{65536}) = 1 + \log^*(65536) = 2 + \log^*(16) = 3 + \log^*(4) = 4 + \log^*(2) = 5$

Main Result

Theorem

When using Path Compression and Union By Rank, total time at most $O(m \log^ n)$.*

$\log^*$: iterated $\log_2$.

- ▶ $\log^* n = \#$ times apply $\log_2$ until get to ≤ 1
- ▶ $\log^*(2^{65536}) = 1 + \log^*(65536) = 2 + \log^*(16) = 3 + \log^*(4) = 4 + \log^*(2) = 5$
- ▶ Basically $\log^* n$ always ≤ 5 .

Main Result

Theorem

When using Path Compression and Union By Rank, total time at most $O(m \log^ n)$.*

$\log^*$: iterated $\log_2$.

- ▶ $\log^* n = \#$ times apply $\log_2$ until get to ≤ 1
- ▶ $\log^*(2^{65536}) = 1 + \log^*(65536) = 2 + \log^*(16) = 3 + \log^*(4) = 4 + \log^*(2) = 5$
- ▶ Basically $\log^* n$ always ≤ 5 .

Stronger theorem: total time at most $O(m \cdot \alpha(m, n))$.

- ▶ $\alpha(m, n)$: inverse Ackermann function. Grows even slower than $\log^*$.
- ▶ See CLRS for details

Formal Procedures: Make-Set and Find

Make-Set(x): Set $x \rightarrow \textit{rank} = 0$ and $x \rightarrow \textit{parent} = x$

- ▶ Running time: $O(1)$.

Formal Procedures: Make-Set and Find

Make-Set(x): Set $x \rightarrow \textit{rank} = 0$ and $x \rightarrow \textit{parent} = x$

- ▶ Running time: $O(1)$.

Find(x): Walk from x to root, and return root. Set parent pointers of x and all ancestors to root.

- ▶ If $x \rightarrow \textit{parent} = x$ then return x
- ▶ $x \rightarrow \textit{parent} = \textit{Find}(x \rightarrow \textit{parent})$
- ▶ Return $x \rightarrow \textit{parent}$

Formal Procedures: Make-Set and Find

Make-Set(x): Set $x \rightarrow \textit{rank} = 0$ and $x \rightarrow \textit{parent} = x$


- ▶ Running time: $O(1)$.

Find(x): Walk from x to root, and return root. Set parent pointers of x and all ancestors to root.



- ▶ If $x \rightarrow \textit{parent} = x$ then return x
- ▶ $x \rightarrow \textit{parent} = \textit{Find}(x \rightarrow \textit{parent})$
- ▶ Return $x \rightarrow \textit{parent}$

Running time of Find: depth of x (distance to root)

Find example



Find example



Formal Procedure: Union

Link(r_1, r_2): Only applied to root nodes

- ▶ If $r_1 \rightarrow \text{rank} > r_2 \rightarrow \text{rank}$, set $r_2 \rightarrow \text{parent} = r_1$
- ▶ If $r_2 \rightarrow \text{rank} > r_1 \rightarrow \text{rank}$, set $r_1 \rightarrow \text{parent} = r_2$
- ▶ If $r_1 \rightarrow \text{rank} = r_2 \rightarrow \text{rank}$, set $r_2 \rightarrow \text{parent} = r_1$ and increment $r_1 \rightarrow \text{rank}$.

Formal Procedure: Union

Link(r_1, r_2): Only applied to root nodes

- ▶ If $r_1 \rightarrow \text{rank} > r_2 \rightarrow \text{rank}$, set $r_2 \rightarrow \text{parent} = r_1$
- ▶ If $r_2 \rightarrow \text{rank} > r_1 \rightarrow \text{rank}$, set $r_1 \rightarrow \text{parent} = r_2$
- ▶ If $r_1 \rightarrow \text{rank} = r_2 \rightarrow \text{rank}$, set $r_2 \rightarrow \text{parent} = r_1$ and increment $r_1 \rightarrow \text{rank}$.

Running time of Link: $O(1)$

Formal Procedure: Union

Link(r_1, r_2): Only applied to root nodes

- ▶ If $r_1 \rightarrow \text{rank} > r_2 \rightarrow \text{rank}$, set $r_2 \rightarrow \text{parent} = r_1$
- ▶ If $r_2 \rightarrow \text{rank} > r_1 \rightarrow \text{rank}$, set $r_1 \rightarrow \text{parent} = r_2$
- ▶ If $r_1 \rightarrow \text{rank} = r_2 \rightarrow \text{rank}$, set $r_2 \rightarrow \text{parent} = r_1$ and increment $r_1 \rightarrow \text{rank}$.

Running time of Link: $O(1)$

Union(x, y): Link(Find(x), Find(y))

Formal Procedure: Union

Link(r_1, r_2): Only applied to root nodes



- ▶ If $r_1 \rightarrow \text{rank} > r_2 \rightarrow \text{rank}$, set $r_2 \rightarrow \text{parent} = r_1$
- ▶ If $r_2 \rightarrow \text{rank} > r_1 \rightarrow \text{rank}$, set $r_1 \rightarrow \text{parent} = r_2$
- ▶ If $r_1 \rightarrow \text{rank} = r_2 \rightarrow \text{rank}$, set $r_2 \rightarrow \text{parent} = r_1$ and increment $r_1 \rightarrow \text{rank}$.

Running time of Link: $O(1)$



Union(x, y): Link(Find(x), Find(y))

- ▶ Running time: $\text{depth}(x) + \text{depth}(y)$

Union example




Union example




If $z \rightarrow \text{rank} \geq w \rightarrow \text{rank}$



Union example



If $z \rightarrow \text{rank} \geq w \rightarrow \text{rank}$




Union example



If $z \rightarrow \text{rank} \geq w \rightarrow \text{rank}$

If $z \rightarrow \text{rank} = w \rightarrow \text{rank}$,
then $(z \rightarrow \text{rank})++$



Properties of Ranks

1. If x not a root, then $(x \rightarrow \textit{rank}) < (x \rightarrow \textit{parent} \rightarrow \textit{rank})$
2. When doing path compression, if parent of x changes, new parent has rank strictly larger than old parent
3. $x \rightarrow \textit{rank}$ can change only if x a root, and once x is a non-root it never becomes a root again.

Properties of Ranks

1. If x not a root, then $(x \rightarrow \textit{rank}) < (x \rightarrow \textit{parent} \rightarrow \textit{rank})$
2. When doing path compression, if parent of x changes, new parent has rank strictly larger than old parent
3. $x \rightarrow \textit{rank}$ can change only if x a root, and once x is a non-root it never becomes a root again.
4. When x first reaches rank r , there are at least 2^r nodes in tree rooted at x .

Properties of Ranks

1. If x not a root, then $(x \rightarrow \textit{rank}) < (x \rightarrow \textit{parent} \rightarrow \textit{rank})$
2. When doing path compression, if parent of x changes, new parent has rank strictly larger than old parent
3. $x \rightarrow \textit{rank}$ can change only if x a root, and once x is a non-root it never becomes a root again.
4. When x first reaches rank r , there are at least 2^r nodes in tree rooted at x .

Proof of Property 4.

Induction. Base case: $r = 0$.

Properties of Ranks

1. If x not a root, then $(x \rightarrow \textit{rank}) < (x \rightarrow \textit{parent} \rightarrow \textit{rank})$
2. When doing path compression, if parent of x changes, new parent has rank strictly larger than old parent
3. $x \rightarrow \textit{rank}$ can change only if x a root, and once x is a non-root it never becomes a root again.
4. When x first reaches rank r , there are at least 2^r nodes in tree rooted at x .

Proof of Property 4.

Induction. Base case: $r = 0$. ✓

Properties of Ranks

1. If x not a root, then $(x \rightarrow \textit{rank}) < (x \rightarrow \textit{parent} \rightarrow \textit{rank})$
2. When doing path compression, if parent of x changes, new parent has rank strictly larger than old parent
3. $x \rightarrow \textit{rank}$ can change only if x a root, and once x is a non-root it never becomes a root again.
4. When x first reaches rank r , there are at least 2^r nodes in tree rooted at x .

Proof of Property 4.

Induction. Base case: $r = 0$. ✓

Inductive case: Suppose true for $r - 1$.

Properties of Ranks

1. If x not a root, then $(x \rightarrow \text{rank}) < (x \rightarrow \text{parent} \rightarrow \text{rank})$
2. When doing path compression, if parent of x changes, new parent has rank strictly larger than old parent
3. $x \rightarrow \text{rank}$ can change only if x a root, and once x is a non-root it never becomes a root again.
4. When x first reaches rank r , there are at least 2^r nodes in tree rooted at x .

Proof of Property 4.

Induction. Base case: $r = 0$. ✓

Inductive case: Suppose true for $r - 1$.

When x first gets rank r , must be because x had rank $r - 1$ (and was root), unioned with another set with root z of rank $r - 1$.

Properties of Ranks

1. If x not a root, then $(x \rightarrow \text{rank}) < (x \rightarrow \text{parent} \rightarrow \text{rank})$
2. When doing path compression, if parent of x changes, new parent has rank strictly larger than old parent
3. $x \rightarrow \text{rank}$ can change only if x a root, and once x is a non-root it never becomes a root again.
4. When x first reaches rank r , there are at least 2^r nodes in tree rooted at x .

Proof of Property 4.

Induction. Base case: $r = 0$. ✓

Inductive case: Suppose true for $r - 1$.

When x first gets rank r , must be because x had rank $r - 1$ (and was root), unioned with another set with root z of rank $r - 1$.

⇒ By induction, at least 2^{r-1} nodes in each tree

Properties of Ranks

1. If x not a root, then $(x \rightarrow \text{rank}) < (x \rightarrow \text{parent} \rightarrow \text{rank})$
2. When doing path compression, if parent of x changes, new parent has rank strictly larger than old parent
3. $x \rightarrow \text{rank}$ can change only if x a root, and once x is a non-root it never becomes a root again.
4. When x first reaches rank r , there are at least 2^r nodes in tree rooted at x .

Proof of Property 4.

Induction. Base case: $r = 0$. ✓

Inductive case: Suppose true for $r - 1$.

When x first gets rank r , must be because x had rank $r - 1$ (and was root), unioned with another set with root z of rank $r - 1$.

⇒ By induction, at least 2^{r-1} nodes in each tree

⇒ At least $2^{r-1} + 2^{r-1} = 2^r$ nodes in combined tree.



Nodes of rank r

Lemma

There are at most $n/2^r$ nodes of rank at least r .

Proof.

Let x be node of rank at least r . Let S_x be descendants of x when it first got rank r .
 $\implies |S_x| \geq 2^r$ by property 4.

Nodes of rank r

Lemma

There are at most $n/2^r$ nodes of rank at least r .

Proof.

Let x be node of rank at least r . Let S_x be descendants of x when it first got rank r .

$\implies |S_x| \geq 2^r$ by property 4.

Let z be some other node of rank $\geq r$. Without loss of generality, suppose x got rank r before z . Consider some $e \in S_x$. Then e can't be in S_z (already in tree with rank $\geq r$). So $S_x \cap S_z = \emptyset$.

Nodes of rank r

Lemma

There are at most $n/2^r$ nodes of rank at least r .

Proof.

Let x be node of rank at least r . Let S_x be descendants of x when it first got rank r .

$\implies |S_x| \geq 2^r$ by property 4.

Let z be some other node of rank $\geq r$. Without loss of generality, suppose x got rank r before z . Consider some $e \in S_x$. Then e can't be in S_z (already in tree with rank $\geq r$). So $S_x \cap S_z = \emptyset$.

$\implies$ At most $n/2^r$ nodes of rank $\geq r$.



Main Result I

Theorem

When using Path Compression and Union By Rank, total time at most $O(m \log^ n)$.*

Main Result I

Theorem

When using Path Compression and Union By Rank, total time at most $O(m \log^ n)$.*

m operations total. Analyze each type separately:

- ▶ Make-Set: $O(1)$ time each
- ▶ Union: two Find operations, plus $O(1)$ other work.
- ▶ Find($\mathbf{x}$): proportional to depth of $\mathbf{x}$. Count number of parent pointers followed, call this the time.

Main Result I

Theorem

When using Path Compression and Union By Rank, total time at most $O(m \log^ n)$.*

m operations total. Analyze each type separately:

- ▶ Make-Set: $O(1)$ time each
- ▶ Union: two Find operations, plus $O(1)$ other work.
- ▶ Find(x): proportional to depth of x . Count number of parent pointers followed, call this the time.

So at most $2m$ Finds, want to bound total # parent pointers followed.

Main Result I

Theorem

When using Path Compression and Union By Rank, total time at most $O(m \log^ n)$.*

m operations total. Analyze each type separately:

- ▶ Make-Set: $O(1)$ time each
- ▶ Union: two Find operations, plus $O(1)$ other work.
- ▶ Find(x): proportional to depth of x . Count number of parent pointers followed, call this the time.

So at most $2m$ Finds, want to bound total # parent pointers followed.

- ▶ At most one parent pointer to root per Find $\implies$ at most $O(m)$ parent pointers to roots.
- ▶ So only need to worry about parent pointers to non-roots.

Main Result II: Buckets

Put elements in buckets according to rank (only in analysis).

Notation: $2 \uparrow i$ denotes a tower of i 2's

- ▶ $2 \uparrow 1 = 2$, $2 \uparrow 2 = 2^2 = 4$, $2 \uparrow 3 = 2^{2^2} = 2^4 = 16$, $2 \uparrow 4 = 2^{2^{2^2}} = 2^{16} = 65536$
- ▶ $\log^*(2 \uparrow i) = i$

Main Result II: Buckets

Put elements in buckets according to rank (only in analysis).

Notation: $2 \uparrow i$ denotes a tower of i 2's

- ▶ $2 \uparrow 1 = 2$, $2 \uparrow 2 = 2^2 = 4$, $2 \uparrow 3 = 2^{2^2} = 2^4 = 16$, $2 \uparrow 4 = 2^{2^{2^2}} = 2^{16} = 65536$
- ▶ $\log^*(2 \uparrow i) = i$

$B(i)$ (Bucket i): All elements of rank at least $2 \uparrow (i - 1)$, at most $(2 \uparrow i) - 1$

- ▶ Bucket **0**: nodes with rank **0**
- ▶ Bucket **1**: rank at least **1**, at most **1**
- ▶ Bucket **2**: rank at least **2**, at most **3**
- ▶ Bucket **3**: rank at least **4**, at most **15**
- ▶ Bucket **4**: rank at least **16**, at most **65535**

Main Result II: Buckets

Put elements in buckets according to rank (only in analysis).

Notation: $2 \uparrow i$ denotes a tower of i 2's

- ▶ $2 \uparrow 1 = 2$, $2 \uparrow 2 = 2^2 = 4$, $2 \uparrow 3 = 2^{2^2} = 2^4 = 16$, $2 \uparrow 4 = 2^{2^{2^2}} = 2^{16} = 65536$
- ▶ $\log^*(2 \uparrow i) = i$

$B(i)$ (Bucket i): All elements of rank at least $2 \uparrow (i - 1)$, at most $(2 \uparrow i) - 1$

- ▶ Bucket **0**: nodes with rank **0**
- ▶ Bucket **1**: rank at least **1**, at most **1**
- ▶ Bucket **2**: rank at least **2**, at most **3**
- ▶ Bucket **3**: rank at least **4**, at most **15**
- ▶ Bucket **4**: rank at least **16**, at most **65535**
- ▶ At most $\log^* n$ buckets.

Main Result II: Buckets

Put elements in buckets according to rank (only in analysis).

Notation: $2 \uparrow i$ denotes a tower of i 2's

- ▶ $2 \uparrow 1 = 2$, $2 \uparrow 2 = 2^2 = 4$, $2 \uparrow 3 = 2^{2^2} = 2^4 = 16$, $2 \uparrow 4 = 2^{2^{2^2}} = 2^{16} = 65536$
- ▶ $\log^*(2 \uparrow i) = i$

$B(i)$ (Bucket i): All elements of rank at least $2 \uparrow (i - 1)$, at most $(2 \uparrow i) - 1$

- ▶ Bucket **0**: nodes with rank **0**
- ▶ Bucket **1**: rank at least **1**, at most **1**
- ▶ Bucket **2**: rank at least **2**, at most **3**
- ▶ Bucket **3**: rank at least **4**, at most **15**
- ▶ Bucket **4**: rank at least **16**, at most **65535**
- ▶ At most $\log^* n$ buckets.

From Lemma: at most $n/(2^{2 \uparrow (i-1)}) = n/(2 \uparrow i)$ elements in bucket i .

Main Result III

Want to bound total # parent pointers (to non-roots) followed over all $\leq 2m$ Finds.

Main Result III

Want to bound total # parent pointers (to non-roots) followed over all $\leq 2m$ Finds.

Type 1: Parent pointers that cross buckets

- ▶ $\leq \log^* n$ buckets $\implies \leq \log^* n$ per Find $\implies \leq 2m \log^* n = O(m \log^* n)$ total

Main Result III

Want to bound total $\#$ parent pointers (to non-roots) followed over all $\leq 2m$ Finds.

Type 1: Parent pointers that cross buckets

- ▶ $\leq \log^* n$ buckets $\implies \leq \log^* n$ per Find $\implies \leq 2m \log^* n = O(m \log^* n)$ total

Type 2: Parent pointers that do not cross buckets

- ▶ For each x , let $\alpha(x) = \#$ times follow parent pointer from x to parent in same bucket, not root. Want to show $\sum_x \alpha(x) \leq O(m \log^* n)$.
- ▶ Since x not root when following pointers, always has same rank

Main Result III

Want to bound total $\#$ parent pointers (to non-roots) followed over all $\leq 2m$ Finds.

Type 1: Parent pointers that cross buckets

- ▶ $\leq \log^* n$ buckets $\implies \leq \log^* n$ per Find $\implies \leq 2m \log^* n = O(m \log^* n)$ total

Type 2: Parent pointers that do not cross buckets

- ▶ For each x , let $\alpha(x) = \#$ times follow parent pointer from x to parent in same bucket, not root. Want to show $\sum_x \alpha(x) \leq O(m \log^* n)$.
- ▶ Since x not root when following pointers, always has same rank
- ▶ Whenever x 's pointer followed, gets new parent (path compression)
 - $\implies$ rank of parent goes up by at least **1** (properties of rank)
 - $\implies$ happens at most $2 \uparrow i$ times if x in bucket i
 - $\implies \alpha(x) \leq 2 \uparrow i$.

Main Result III

Want to bound total # parent pointers (to non-roots) followed over all $\leq 2m$ Finds.

Type 1: Parent pointers that cross buckets

- ▶ $\leq \log^* n$ buckets $\implies \leq \log^* n$ per Find $\implies \leq 2m \log^* n = O(m \log^* n)$ total

Type 2: Parent pointers that do not cross buckets

- ▶ For each x , let $\alpha(x) = \#$ times follow parent pointer from x to parent in same bucket, not root. Want to show $\sum_x \alpha(x) \leq O(m \log^* n)$.
- ▶ Since x not root when following pointers, always has same rank
- ▶ Whenever x 's pointer followed, gets new parent (path compression)
 - $\implies$ rank of parent goes up by at least 1 (properties of rank)
 - $\implies$ happens at most $2 \uparrow i$ times if x in bucket i
 - $\implies \alpha(x) \leq 2 \uparrow i$.

$$\begin{aligned} \sum_x \alpha(x) &= \sum_{i=1}^{O(\log^* n)} \sum_{x \in B(i)} \alpha(x) \leq \sum_{i=1}^{O(\log^* n)} \sum_{x \in B(i)} (2 \uparrow i) \leq \sum_{i=1}^{O(\log^* n)} \frac{n}{2 \uparrow i} (2 \uparrow i) = O(n \log^* n) \\ &\leq O(m \log^* n) \end{aligned}$$