Lecture 17: Minimum Spanning Trees

Jessica Sorrell

November 3, 2026
601.433/633 Introduction to Algorithms
Slides by Mike Dinitz

Announcements

Oral presentations for HW7!

- Must be groups of 3 unless you talked to us about an exception (rarely granted).
- Sign up by Wed 5pm.
- Same system as for HW2 (Canvas). See Courselore.

Introduction

Definition

A *spanning tree* of an undirected graph $G = (V, E)$ is a set of edges $T \subseteq E$ such that (V, T) is connected and acyclic.

Definition


Minimum Spanning Tree problem (MST):


- Input:
  - Undirected graph $G = (V, E)$
  - Edge weights $w : E \to \mathbb{R}_{\geq 0}$
- Output: Spanning tree minimizing $w(T) = \sum_{e \in T} w(e)$.


Foundational problem in *network design*. Tons of applications.


Today: one "recipe", two different algorithms from recipe. Main idea: greedy.

Examples


4
1
4
9
5
3
9
9
10
2
7
6
4
8
2
18
3
9
9
8
9


A
1
B
C
4
3
4
4
2
5
D
4
E
7
F


A
1
B
C
2
4
5
D
4
E
F


A
1
B
C
4
2
4
5
D
E
F

Generic Algorithm

Generic Greedy

Definition

Suppose that $\boldsymbol{A}$ is subset of *some* MST. If $\boldsymbol{A} \cup \{\boldsymbol{e}\}$ is also a subset of some MST, then $\boldsymbol{e}$ is *safe* for $\boldsymbol{A}$.

Generic Greedy

Definition

Suppose that A is subset of *some* MST. If $A \cup \{e\}$ is also a subset of some MST, then e is *safe* for A.

```
Generic-MST {
    A = ∅
    while(A not a spanning tree) {
        find an edge e safe for A
        A = A ∪ {e}
    }
    return A
}
```

Generic Greedy

Definition

Suppose that A is subset of *some* MST. If $A \cup \{e\}$ is also a subset of some MST, then e is *safe* for A.

Theorem

Generic-MST is correct: it always returns an MST.

```
Generic-MST {
    A = ∅
    while(A not a spanning tree) {
        find an edge e safe for A
        A = A ∪ {e}
    }
    return A
}
```

Generic Greedy

Definition

Suppose that A is subset of *some* MST. If $A \cup \{e\}$ is also a subset of some MST, then e is *safe* for A.

```
Generic-MST {
    A = ∅
    while(A not a spanning tree) {
        find an edge e safe for A
        A = A ∪ {e}
    }
    return A
}
```

Theorem

Generic-MST is correct: it always returns an MST.

Proof.

Induction.

Claim: A always a subset of some MST.
Base case: ✓
Inductive step: ✓ □

Generic Greedy

Definition

Suppose that A is subset of *some* MST. If $A \cup \{e\}$ is also a subset of some MST, then e is *safe* for A.

```
Generic-MST {
    A = ∅
    while(A not a spanning tree) {
        find an edge e safe for A
        A = A ∪ {e}
    }
    return A
}
```

Theorem

Generic-MST is correct: it always returns an MST.

Proof.

Induction.


Claim: A always a subset of some MST.
Base case: ✓
Inductive step: ✓ □

But how to find a safe edge? And which one to add?

Structural Properties

Lemma


Let T *be a spanning tree, let* $u, v \in V$*, and let* P *be the* $u - v$ *path in* T*. If* $\{u, v\} \notin T$*, then* $T' = (T \cup \{\{u, v\}\}) \setminus \{e\}$ *is a spanning tree for all* $e \in P$*.*



Structural Properties

Definition


A *cut* $(S, V \setminus S)$ (or $(S, \bar{S})$ or just S) is a partition of V into two parts. Edge e *crosses* cut $(S, \bar{S})$ if e has one endpoint in S and one endpoint in $\bar{S}$.



Structural Properties

Definition

A *cut* $(S, V \setminus S)$ (or $(S, \bar{S})$ or just S) is a partition of V into two parts. Edge e *crosses* cut $(S, \bar{S})$ if e has one endpoint in S and one endpoint in $\bar{S}$.



Definition


Cut $(S, \bar{S})$ *respects* $A \subseteq E$ if no edge in A crosses $(S, \bar{S})$



Structural Properties

Definition

A *cut* $(S, V \setminus S)$ (or $(S, \bar{S})$ or just S) is a partition of V into two parts. Edge e *crosses* cut $(S, \bar{S})$ if e has one endpoint in S and one endpoint in $\bar{S}$.



Definition

Cut $(S, \bar{S})$ *respects* $A \subseteq E$ if no edge in A crosses $(S, \bar{S})$



Definition

e is a *light edge* for $(S, \bar{S})$ if e crosses $(S, \bar{S})$ and $w(e) = \min_{e' \text{ crossing } (S,\bar{S})} w(e')$

Main Structural Theorem

Theorem

Let $A \subseteq E$ be a subset of some MST T, let $(S, \bar{S})$ be a cut respecting A, and let $e = \{u, v\}$ be a light edge for $(S, \bar{S})$. Then e is safe for A.

Main Structural Theorem

Theorem

Let $A \subseteq E$ be a subset of some MST T, let $(S, \bar{S})$ be a cut respecting A, and let $e = \{u, v\}$ be a light edge for $(S, \bar{S})$. Then e is safe for A.

Need to show there is an MST containing $A \cup \{e\}$.

Main Structural Theorem

Theorem

Let $A \subseteq E$ be a subset of some MST T, let $(S, \bar{S})$ be a cut respecting A, and let $e = \{u, v\}$ be a light edge for $(S, \bar{S})$. Then e is safe for A.

Need to show there is an MST containing $A \cup \{e\}$.
If $e \in T$: ✓

Main Structural Theorem

Theorem

Let $A \subseteq E$ be a subset of some MST T, let $(S, \bar{S})$ be a cut respecting A, and let $e = \{u, v\}$ be a light edge for $(S, \bar{S})$. Then e is safe for A.

Need to show there is an MST containing $A \cup \{e\}$.
If $e \in T$: ✓ Otherwise:

Main Structural Theorem


Theorem

Let $A \subseteq E$ be a subset of some MST T, let $(S, \bar{S})$ be a cut respecting A, and let $e = \{u, v\}$ be a light edge for $(S, \bar{S})$. Then e is safe for A.

Need to show there is an MST containing $A \cup \{e\}$.
If $e \in T$: ✓ Otherwise:

Let $T' = (T \cup \{e\}) \setminus \{\{x, y\}\}$

$\Longrightarrow$ T' a spanning tree by first lemma



Main Structural Theorem

Theorem

Let $A \subseteq E$ be a subset of some MST T, let $(S, \bar{S})$ be a cut respecting A, and let $e = \{u, v\}$ be a light edge for $(S, \bar{S})$. Then e is safe for A.


Need to show there is an MST containing $A \cup \{e\}$.
If $e \in T$: ✓ Otherwise:

Let $T' = (T \cup \{e\}) \setminus \{\{x, y\}\}$

$\Longrightarrow$ T' a spanning tree by first lemma

$\{x, y\} \notin A$, since $(S, \bar{S})$ respects A

$\Longrightarrow$ $A \cup \{e\} \subseteq T'$



Main Structural Theorem

Theorem

Let $A \subseteq E$ be a subset of some MST T, let $(S, \bar{S})$ be a cut respecting A, and let $e = \{u, v\}$ be a light edge for $(S, \bar{S})$. Then e is safe for A.

Need to show there is an MST containing $A \cup \{e\}$.
If $e \in T$: ✓ Otherwise:


Let $T' = (T \cup \{e\}) \setminus \{\{x, y\}\}$

$\Longrightarrow$ T' a spanning tree by first lemma

$\{x, y\} \notin A$, since $(S, \bar{S})$ respects A

$\Longrightarrow$ $A \cup \{e\} \subseteq T'$

$w(T') = w(T) + w(e) - w(\{x, y\}) \leq w(T)$



Main Structural Theorem

Theorem

Let $A \subseteq E$ be a subset of some MST T, let $(S, \bar{S})$ be a cut respecting A, and let $e = \{u, v\}$ be a light edge for $(S, \bar{S})$. Then e is safe for A.

Need to show there is an MST containing $A \cup \{e\}$.
If $e \in T$: ✓ Otherwise:

Let $T' = (T \cup \{e\}) \setminus \{\{x, y\}\}$


$\Longrightarrow$ T' a spanning tree by first lemma

$\{x, y\} \notin A$, since $(S, \bar{S})$ respects A

$\Longrightarrow$ $A \cup \{e\} \subseteq T'$

$w(T') = w(T) + w(e) - w(\{x, y\}) \leq w(T)$

$\Longrightarrow$ T' an MST containing $A \cup \{e\}$



Prim's Algorithm

Prim's Algorithm


Idea: start at arbitrary node u. Greedily grow MST out of u.

$A = \varnothing$
Let u be an arbitrary node, and let $S = \{u\}$
while(A is not a spanning tree) {
    Find an edge $\{x, y\}$ with $x \in S$ and $y \notin S$ that is light for $(S, \bar{S})$
    $A \leftarrow A \cup \{\{x, y\}\}$
    $S \leftarrow S \cup \{y\}$
}
return A

Prim's Algorithm

Idea: start at arbitrary node u. Greedily grow MST out of u.

$A = \varnothing$
Let u be an arbitrary node, and let $S = \{u\}$
while(A is not a spanning tree) {
    Find an edge $\{x, y\}$ with $x \in S$ and $y \notin S$ that is light for $(S, \bar{S})$
    $A \leftarrow A \cup \{\{x, y\}\}$
    $S \leftarrow S \cup \{y\}$
}
return A



Correctness

Theorem

Prim's algorithm returns an MST.

Correctness

Theorem

Prim's algorithm returns an MST.

Proof.

Just Generic-MST!

Correctness

Theorem

Prim's algorithm returns an MST.

Proof.

Just Generic-MST!

- $(S, \bar{S})$ always respects A (induction).
- If edge e added then light for $(S, \bar{S})$
- Hence e safe for A by main structural theorem.

□

Running Time

Trivial analysis:

- Every spanning tree has $n-1$ edges $\implies$ $n-1$ iterations
- In each iteration, look through all edges to find min-weight edge crossing $(S, \bar{S})$ $\implies$ $O(m)$ time
- Total $O(mn)$

Running Time

Trivial analysis:

- Every spanning tree has $n-1$ edges $\implies$ $n-1$ iterations
- In each iteration, look through all edges to find min-weight edge crossing $(S, \bar{S})$ $\implies$ $O(m)$ time
- Total $O(mn)$

Like Dijkstra's algorithm, do better by using a data structure: heap!

Running Time

Trivial analysis:

- Every spanning tree has $n-1$ edges $\implies$ $n-1$ iterations
- In each iteration, look through all edges to find min-weight edge crossing $(S, \bar{S})$ $\implies$ $O(m)$ time
- Total $O(mn)$

Like Dijkstra's algorithm, do better by using a data structure: heap!

- Need to be able to get minimum-weight edge across $(S, \bar{S})$

Running Time

Trivial analysis:

- Every spanning tree has $n-1$ edges $\implies$ $n-1$ iterations
- In each iteration, look through all edges to find min-weight edge crossing $(S, \bar{S})$ $\implies$ $O(m)$ time
- Total $O(mn)$

Like Dijkstra's algorithm, do better by using a data structure: heap!

- Need to be able to get minimum-weight edge across $(S, \bar{S})$

Heap of *vertices* in $\bar{S}$. Key of v is minimum weight of an edge from v to S.

Running Time

Trivial analysis:

- Every spanning tree has $n-1$ edges $\implies$ $n-1$ iterations
- In each iteration, look through all edges to find min-weight edge crossing $(S, \bar{S})$ $\implies$ $O(m)$ time
- Total $O(mn)$

Like Dijkstra's algorithm, do better by using a data structure: heap!

- Need to be able to get minimum-weight edge across $(S, \bar{S})$

Heap of *vertices* in $\bar{S}$. Key of v is minimum weight of an edge from v to S.

- When new vertex y added to S, need to update keys of nodes adjacent to y

Running Time

Trivial analysis:

- Every spanning tree has $n-1$ edges $\implies$ $n-1$ iterations
- In each iteration, look through all edges to find min-weight edge crossing $(S, \bar{S})$ $\implies$ $O(m)$ time
- Total $O(mn)$

Like Dijkstra's algorithm, do better by using a data structure: heap!

- Need to be able to get minimum-weight edge across $(S, \bar{S})$

Heap of *vertices* in $\bar{S}$. Key of v is minimum weight of an edge from v to S.

- When new vertex y added to S, need to update keys of nodes adjacent to y
  - Happens at most m times total

Running Time

Trivial analysis:

- Every spanning tree has $n-1$ edges $\implies$ $n-1$ iterations
- In each iteration, look through all edges to find min-weight edge crossing $(S, \bar{S})$ $\implies$ $O(m)$ time
- Total $O(mn)$

Like Dijkstra's algorithm, do better by using a data structure: heap!

- Need to be able to get minimum-weight edge across $(S, \bar{S})$

Heap of *vertices* in $\bar{S}$. Key of v is minimum weight of an edge from v to S.

- When new vertex y added to S, need to update keys of nodes adjacent to y
  - Happens at most m times total
- n Inserts, n Extract-Mins, m Decrease-Keys

Running Time

Trivial analysis:

- Every spanning tree has $n-1$ edges $\implies$ $n-1$ iterations
- In each iteration, look through all edges to find min-weight edge crossing $(S, \bar{S})$ $\implies$ $O(m)$ time
- Total $O(mn)$

Like Dijkstra's algorithm, do better by using a data structure: heap!

- Need to be able to get minimum-weight edge across $(S, \bar{S})$

Heap of *vertices* in $\bar{S}$. Key of v is minimum weight of an edge from v to S.

- When new vertex y added to S, need to update keys of nodes adjacent to y
  - Happens at most m times total
- n Inserts, n Extract-Mins, m Decrease-Keys
- Like Dijkstra, $O(m \log n)$ using binary heap. $O(m + n \log n)$ with Fibonacci heap (only Extract-Min is logarithmic)

Kruskal's Algorithm

Algorithm

Intuition: can we be *even greedier* than Prim's Algorithm?

Algorithm

Intuition: can we be *even greedier* than Prim's Algorithm?

$\boldsymbol{A} = \varnothing$
Sort edges by weight (small to large)
For each edge $\boldsymbol{e}$ in this order $\{$
    if $\boldsymbol{A} \cup \{\boldsymbol{e}\}$ has no cycles, $\boldsymbol{A} = \boldsymbol{A} \cup \{\boldsymbol{e}\}$
$\}$
return $\boldsymbol{A}$

Correctness

Theorem

Kruskal's algorithm computes an MST.


Want to show just Generic-MST: when $\{u, v\}$ added, it was safe for A.

Correctness

Theorem

Kruskal's algorithm computes an MST.

Want to show just Generic-MST: when $\{u, v\}$ added, it was safe for A.




Correctness

Theorem

Kruskal's algorithm computes an MST.

Want to show just Generic-MST: when $\{u, v\}$ added, it was safe for A.




Consider cut $(C, \bar{C})$. Respects A, and $\{u, v\}$ light for it.

Correctness

Theorem

Kruskal's algorithm computes an MST.

Want to show just Generic-MST: when $\{u, v\}$ added, it was safe for A.



Consider cut $(C, \bar{C})$. Respects A, and $\{u, v\}$ light for it.
Main structural theorem $\implies$ $\{u, v\}$ safe for A

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

- Make-Sets:

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

- Make-Sets: n

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

- Make-Sets: n
- Finds:

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

- Make-Sets: n
- Finds: $2m$

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

- Make-Sets: n
- Finds: $2m$
- Unions:

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

- Make-Sets: n
- Finds: $2m$
- Unions: $n - 1$

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

- Make-Sets: n
- Finds: $2m$
- Unions: $n - 1$

$O(m \log^* n)$ using union-by-rank + path compression
$O(m + n \log n)$ using list data structure

Running Time

Sorting edges: $O(m \log m) = O(m \log n)$
Easy analysis: m iterations, DFS/BFS in each iteration to check if endpoints already connected.

- A a forest so $|A| \leq n - 1$, so DFS/BFS takes $O(n)$ time $\implies$ $O(mn)$ time total.

Can we speed this up with data structures?

Union-Find! Connected components of A are disjoint sets.

- Make-Sets: n
- Finds: $2m$
- Unions: $n - 1$

$O(m \log^* n)$ using union-by-rank + path compression
$O(m + n \log n)$ using list data structure

Sorting dominates! $O(m \log n)$ total.