

Lecture 3: Intro to proofs for algorithms

Michael Dinitz

September 8, 2026
601.433/633 Introduction to Algorithms
(Slides by Jessica Sorrell)

Today

Discuss common proof techniques for algorithms.

- ▶ Inductive arguments (weak, strong)
- ▶ Proof by contradiction
- ▶ Direct proof
- ▶ Loop invariant
- ▶ Proof by contrapositive

We'll demonstrate proof techniques by proving the correctness and running time of sorting algorithms you've seen before.

Quicksort review

Algorithm Quicksort

Input: array $\mathbf{A}$ of length n (assume all elements distinct)

- 1: **if** $n \leq 1$ **then**
 - 2: **return** $\mathbf{A}$
 - 3: **end if**
 - 4: Pick some element $p \in \mathbf{A}$ as the *pivot*
 - 5: Let $\mathbf{L}$ be the elements less than p , let $\mathbf{G}$ be the elements larger than p
 - 6: $\mathbf{L}' \leftarrow \text{Quicksort}(\mathbf{L})$
 - 7: $\mathbf{G}' \leftarrow \text{Quicksort}(\mathbf{G})$
 - 8: **return** $\mathbf{L}' \parallel p \parallel \mathbf{G}'$
-

Strong Induction vs Weak Induction

Strong induction:

- ▶ Prove property holds for a base case.
- ▶ e.g., Quicksort always returns a sorted array for input arrays of size $n \leq 1$.

Strong Induction vs Weak Induction

Strong induction:

- ▶ Prove property holds for a base case.
- ▶ e.g., Quicksort always returns a sorted array for input arrays of size $n \leq 1$.
- ▶ Assume inductive hypothesis, that property holds *for all* $n \leq k$. Then show that property holds for $n = k + 1$.
- ▶ e.g. Assume Quicksort always returns a sorted array for input arrays of size $\leq k$. Show it returns a sorted array for input arrays of size $k + 1$.

Strong Induction vs Weak Induction

Strong induction:

- ▶ Prove property holds for a base case.
- ▶ e.g., Quicksort always returns a sorted array for input arrays of size $n \leq 1$.
- ▶ Assume inductive hypothesis, that property holds *for all* $n \leq k$. Then show that property holds for $n = k + 1$.
- ▶ e.g. Assume Quicksort always returns a sorted array for input arrays of size $\leq k$. Show it returns a sorted array for input arrays of size $k + 1$.

Weak induction:

- ▶ Prove property holds for a base case.

Strong Induction vs Weak Induction

Strong induction:

- ▶ Prove property holds for a base case.
- ▶ e.g., Quicksort always returns a sorted array for input arrays of size $n \leq 1$.
- ▶ Assume inductive hypothesis, that property holds *for all* $n \leq k$. Then show that property holds for $n = k + 1$.
- ▶ e.g. Assume Quicksort always returns a sorted array for input arrays of size $\leq k$. Show it returns a sorted array for input arrays of size $k + 1$.

Weak induction:

- ▶ Prove property holds for a base case.
- ▶ Assume inductive hypothesis, that property holds for $n = k$. Then show that property holds for $n = k + 1$.
- ▶ e.g. Assume Quicksort always returns a sorted array for input arrays of size *exactly* k . Show it returns a sorted array for input arrays of size $k + 1$.

Correctness of Quicksort - (Strong) Inductive Proof

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Correctness of Quicksort - (Strong) Inductive Proof

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Base case: $n \leq 1$.

Correctness of Quicksort - (Strong) Inductive Proof

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Base case: $n \leq 1$. Quicksort($\mathbf{A}$) returns $\mathbf{A}$.

Correctness of Quicksort - (Strong) Inductive Proof

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Base case: $n \leq 1$. Quicksort($\mathbf{A}$) returns $\mathbf{A}$. ✓

Correctness of Quicksort - (Strong) Inductive Proof

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Base case: $n \leq 1$. Quicksort($\mathbf{A}$) returns $\mathbf{A}$. ✓
- ▶ Inductive step: Assume Quicksort($\mathbf{A}$) returns a sorted array for all $\mathbf{A}$ of length $\leq n$. Show it returns a sorted array for all $\mathbf{A}$ of length $n + 1$.

Correctness of Quicksort - (Strong) Inductive Proof

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Base case: $n \leq 1$. Quicksort($\mathbf{A}$) returns $\mathbf{A}$. ✓
- ▶ Inductive step: Assume Quicksort($\mathbf{A}$) returns a sorted array for all $\mathbf{A}$ of length $\leq n$. Show it returns a sorted array for all $\mathbf{A}$ of length $n + 1$.
 - ▶ Pick pivot $p \in \mathbf{A}$. Let $\mathbf{L}$ be the elements less than p , let $\mathbf{G}$ be the elements larger than p .

Correctness of Quicksort - (Strong) Inductive Proof

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Base case: $n \leq 1$. Quicksort($\mathbf{A}$) returns $\mathbf{A}$. ✓
- ▶ Inductive step: Assume Quicksort($\mathbf{A}$) returns a sorted array for all $\mathbf{A}$ of length $\leq n$. Show it returns a sorted array for all $\mathbf{A}$ of length $n + 1$.
 - ▶ Pick pivot $p \in \mathbf{A}$. Let $\mathbf{L}$ be the elements less than p , let $\mathbf{G}$ be the elements larger than p .
 - ▶ $\mathbf{L}$ and $\mathbf{G}$ are of length $\leq n$, so by the inductive hypothesis, Quicksort($\mathbf{L}$) and Quicksort($\mathbf{G}$) return sorted arrays $\mathbf{L}'$ and $\mathbf{G}'$.

Correctness of Quicksort - (Strong) Inductive Proof

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Base case: $n \leq 1$. Quicksort($\mathbf{A}$) returns $\mathbf{A}$. ✓
- ▶ Inductive step: Assume Quicksort($\mathbf{A}$) returns a sorted array for all $\mathbf{A}$ of length $\leq n$. Show it returns a sorted array for all $\mathbf{A}$ of length $n + 1$.
 - ▶ Pick pivot $p \in \mathbf{A}$. Let $\mathbf{L}$ be the elements less than p , let $\mathbf{G}$ be the elements larger than p .
 - ▶ $\mathbf{L}$ and $\mathbf{G}$ are of length $\leq n$, so by the inductive hypothesis, Quicksort($\mathbf{L}$) and Quicksort($\mathbf{G}$) return sorted arrays $\mathbf{L}'$ and $\mathbf{G}'$.
 - ▶ Therefore $\mathbf{L}' \parallel p \parallel \mathbf{G}'$ is sorted.

Why Strong Induction?

- ▶ A weak inductive hypothesis assumes the desired property holds for $n = k$.

Why Strong Induction?

- ▶ A weak inductive hypothesis assumes the desired property holds for $n = k$.
- ▶ A strong inductive hypothesis assumes the desired property holds for all $n \leq k$.

Why Strong Induction?

- ▶ A weak inductive hypothesis assumes the desired property holds for $n = k$.
- ▶ A strong inductive hypothesis assumes the desired property holds for all $n \leq k$.
- ▶ Quicksort recursively calls itself on L and G , which we don't know the size of a priori.
- ▶ In strong induction, we assume that Quicksort is correct for all arrays of size $\leq k$, so it doesn't matter what the exact sizes of L and G are, because we know they are both $\leq k$.

Correctness of Quicksort - Proof by Contradiction

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Correctness of Quicksort - Proof by Contradiction

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Assume there exists at least one array such that Quicksort does not return a sorted array. Let $\mathbf{A}$ be the smallest such array and let n be the size of $\mathbf{A}$.

Correctness of Quicksort - Proof by Contradiction

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Assume there exists at least one array such that Quicksort does not return a sorted array. Let $\mathbf{A}$ be the smallest such array and let n be the size of $\mathbf{A}$.
- ▶ Note $n \geq 2$.

Correctness of Quicksort - Proof by Contradiction

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Assume there exists at least one array such that Quicksort does not return a sorted array. Let $\mathbf{A}$ be the smallest such array and let n be the size of $\mathbf{A}$.
- ▶ Note $n \geq 2$.
- ▶ So Quicksort($\mathbf{A}$) picks a pivot element $p \in \mathbf{A}$, defines $\mathbf{L}$ and $\mathbf{G}$ as the elements less than p and the elements greater than p respectively, and recursively calls Quicksort on $\mathbf{L}$ and $\mathbf{G}$ to get $\mathbf{L}'$ and $\mathbf{G}'$.

Correctness of Quicksort - Proof by Contradiction

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Assume there exists at least one array such that Quicksort does not return a sorted array. Let $\mathbf{A}$ be the smallest such array and let n be the size of $\mathbf{A}$.
- ▶ Note $n \geq 2$.
- ▶ So Quicksort($\mathbf{A}$) picks a pivot element $p \in \mathbf{A}$, defines $\mathbf{L}$ and $\mathbf{G}$ as the elements less than p and the elements greater than p respectively, and recursively calls Quicksort on $\mathbf{L}$ and $\mathbf{G}$ to get $\mathbf{L}'$ and $\mathbf{G}'$.
- ▶ By the assumption that $\mathbf{A}$ is the smallest such array, $\mathbf{L}'$ and $\mathbf{G}'$ are sorted.

Correctness of Quicksort - Proof by Contradiction

Claim: Given an array $\mathbf{A}$ of length n , Quicksort($\mathbf{A}$) returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Assume there exists at least one array such that Quicksort does not return a sorted array. Let $\mathbf{A}$ be the smallest such array and let n be the size of $\mathbf{A}$.
- ▶ Note $n \geq 2$.
- ▶ So Quicksort($\mathbf{A}$) picks a pivot element $p \in \mathbf{A}$, defines $\mathbf{L}$ and $\mathbf{G}$ as the elements less than p and the elements greater than p respectively, and recursively calls Quicksort on $\mathbf{L}$ and $\mathbf{G}$ to get $\mathbf{L}'$ and $\mathbf{G}'$.
- ▶ By the assumption that $\mathbf{A}$ is the smallest such array, $\mathbf{L}'$ and $\mathbf{G}'$ are sorted.
- ▶ Therefore $\mathbf{L}' \parallel p \parallel \mathbf{G}'$ is sorted.
- ▶ Contradiction: Quicksort($\mathbf{A}$) *does* return a sorted array.

Direct Proof

A direct proof argues the conclusion of a claim *directly* from its assumptions.

Direct Proof

A direct proof argues the conclusion of a claim *directly* from its assumptions.

For a statement of the form $\mathbf{A} \Rightarrow \mathbf{B}$, a direct proof shows that $\mathbf{B}$ follows from the logical implications of $\mathbf{A}$.

Quicksort Runtime - Direct Proof

Claim: Quicksort runs in time $O(n^2)$ in the worst case.

Quicksort Runtime - Direct Proof

Claim: Quicksort runs in time $O(n^2)$ in the worst case.

- ▶ Before making its two recursive calls, Quicksort compares every element of its input array to the pivot, taking time $\Theta(n)$.

Quicksort Runtime - Direct Proof

Claim: Quicksort runs in time $O(n^2)$ in the worst case.

- ▶ Before making its two recursive calls, Quicksort compares every element of its input array to the pivot, taking time $\Theta(n)$.
- ▶ The worst case for runtime occurs when the pivot is the smallest or largest element of the array. (slightly informal)

Quicksort Runtime - Direct Proof

Claim: Quicksort runs in time $O(n^2)$ in the worst case.

- ▶ Before making its two recursive calls, Quicksort compares every element of its input array to the pivot, taking time $\Theta(n)$.
- ▶ The worst case for runtime occurs when the pivot is the smallest or largest element of the array. (slightly informal)

$$\begin{aligned}T(n) &= T(|L|) + T(|G|) + \Theta(n) = T(|L|) + T(n - 1 - |L|) + \Theta(n) \\&\leq T(n - 1) + T(0) + \Theta(n) = T(n - 1) + \Theta(n)\end{aligned}$$

Quicksort Runtime - Direct Proof

Claim: Quicksort runs in time $O(n^2)$ in the worst case.

- ▶ Before making its two recursive calls, Quicksort compares every element of its input array to the pivot, taking time $\Theta(n)$.
- ▶ The worst case for runtime occurs when the pivot is the smallest or largest element of the array. (slightly informal)

$$\begin{aligned}T(n) &= T(|L|) + T(|G|) + \Theta(n) = T(|L|) + T(n - 1 - |L|) + \Theta(n) \\&\leq T(n - 1) + T(0) + \Theta(n) = T(n - 1) + \Theta(n)\end{aligned}$$

- ▶ Solve: $T(n) = \Theta(n^2)$.

Insertion Sort Review

Algorithm Insertion Sort

Input: array A of length n

```
1: for  $i \leftarrow 2$  to  $n$  do  
2:    $j \leftarrow i$   
3:   while  $j > 1$  and  $A[j] < A[j - 1]$  do  
4:     Swap  $A[j]$  and  $A[j - 1]$   
5:      $j \leftarrow j - 1$   
6:   end while  
7: end for
```

Proof by Loop Invariant (induction)

Proof by loop invariant is a proof technique that establishes some useful property that is true throughout every loop of an iterative algorithm.

- ▶ Initialization: the property is true at the start of the loop.

Proof by Loop Invariant (induction)

Proof by loop invariant is a proof technique that establishes some useful property that is true throughout every loop of an iterative algorithm.

- ▶ Initialization: the property is true at the start of the loop.
- ▶ Maintenance: if the property is true at the beginning of an iteration, it is true at the beginning of the next iteration.

Proof by Loop Invariant (induction)

Proof by loop invariant is a proof technique that establishes some useful property that is true throughout every loop of an iterative algorithm.

- ▶ Initialization: the property is true at the start of the loop.
- ▶ Maintenance: if the property is true at the beginning of an iteration, it is true at the beginning of the next iteration.
- ▶ Termination: when the loop terminates, the invariant holds and shows that the algorithm is correct.

Proof by Loop Invariant (induction)

Proof by loop invariant is a proof technique that establishes some useful property that is true throughout every loop of an iterative algorithm.

- ▶ Initialization: the property is true at the start of the loop.
- ▶ Maintenance: if the property is true at the beginning of an iteration, it is true at the beginning of the next iteration.
- ▶ Termination: when the loop terminates, the invariant holds and shows that the algorithm is correct.

Just induction on time!

Correctness of Insertion Sort - Proof by Loop Invariant

Claim: Given an array $\mathbf{A}$ of length n , $\text{InsertionSort}(\mathbf{A})$ returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Correctness of Insertion Sort - Proof by Loop Invariant

Claim: Given an array $\mathbf{A}$ of length n , $\text{InsertionSort}(\mathbf{A})$ returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Loop invariant: at the beginning of iteration i (or end of iteration $i - 1$), $\mathbf{A}[1, i - 1]$ contains all elements of the original input array $\mathbf{A}[1, i - 1]$, and is sorted.

Correctness of Insertion Sort - Proof by Loop Invariant

Claim: Given an array $\mathbf{A}$ of length n , $\text{InsertionSort}(\mathbf{A})$ returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Loop invariant: at the beginning of iteration i (or end of iteration $i - 1$), $\mathbf{A}[1, i - 1]$ contains all elements of the original input array $\mathbf{A}[1, i - 1]$, and is sorted.
- ▶ Initialization - At the beginning of the first iteration $i = 2$, $\mathbf{A}[1]$ is sorted.
- ▶ Maintenance - In a single iteration, element $\mathbf{A}[i]$ of the input array is moved to the left until it is no longer smaller than the element to its left; therefore at the beginning of the next iteration, $\mathbf{A}[1, i]$ is sorted and contains exactly the same elements as $\mathbf{A}[1, i]$ from the original input array.

Correctness of Insertion Sort - Proof by Loop Invariant

Claim: Given an array $\mathbf{A}$ of length n , $\text{InsertionSort}(\mathbf{A})$ returns an array with all elements of $\mathbf{A}$ sorted from least to greatest.

Proof:

- ▶ Loop invariant: at the beginning of iteration i (or end of iteration $i - 1$), $\mathbf{A}[1, i - 1]$ contains all elements of the original input array $\mathbf{A}[1, i - 1]$, and is sorted.
- ▶ Initialization - At the beginning of the first iteration $i = 2$, $\mathbf{A}[1]$ is sorted.
- ▶ Maintenance - In a single iteration, element $\mathbf{A}[i]$ of the input array is moved to the left until it is no longer smaller than the element to its left; therefore at the beginning of the next iteration, $\mathbf{A}[1, i]$ is sorted and contains exactly the same elements as $\mathbf{A}[1, i]$ from the original input array.
- ▶ Termination - When the loop terminates, $i = n + 1$ and therefore $\mathbf{A}[1, n]$ is sorted and contains exactly the same elements as $\mathbf{A}[1, n]$ from the original input array. Therefore the original input array has been sorted.

Proof by Contrapositive

Proof by contrapositive is a proof technique for conditional statements. That is, statements of the form “If ***A***, then ***B***.”

Proof by Contrapositive

Proof by contrapositive is a proof technique for conditional statements. That is, statements of the form “If **A**, then **B**.”

It relies on the fact that $\mathbf{A} \Rightarrow \mathbf{B}$ is logically equivalent to $\neg \mathbf{B} \Rightarrow \neg \mathbf{A}$.

Proof by Contrapositive

Proof by contrapositive is a proof technique for conditional statements. That is, statements of the form “If A , then B .”

It relies on the fact that $A \Rightarrow B$ is logically equivalent to $\neg B \Rightarrow \neg A$.

To prove $A \Rightarrow B$ by contrapositive, we show that if the negation of the conclusion is true ($\neg B$), then the negation of the hypothesis is true ($\neg A$).

Correctness of (one iteration of) Insertion Sort - Proof by Contrapositive

Claim: If the inner while loop during the i 'th iteration of the outer loop terminates with counter value j for $j > 1$, then element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

Correctness of (one iteration of) Insertion Sort - Proof by Contrapositive

Claim: If the inner while loop during the i 'th iteration of the outer loop terminates with counter value j for $j > 1$, then element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

- ▶ **A:** The inner while loop terminates with value $j > 1$ in the i 'th iteration of the outer loop.

Correctness of (one iteration of) Insertion Sort - Proof by Contrapositive

Claim: If the inner while loop during the i 'th iteration of the outer loop terminates with counter value j for $j > 1$, then element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

- ▶ **A:** The inner while loop terminates with value $j > 1$ in the i 'th iteration of the outer loop.
- ▶ **B:** Element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

Correctness of (one iteration of) Insertion Sort - Proof by Contrapositive

Claim: If the inner while loop during the i 'th iteration of the outer loop terminates with counter value j for $j > 1$, then element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

- ▶ **A:** The inner while loop terminates with value $j > 1$ in the i 'th iteration of the outer loop.
- ▶ **B:** Element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.
- ▶ Want to prove $A \Rightarrow B$.

Correctness of (one iteration of) Insertion Sort - Proof by Contrapositive

Claim: If the inner while loop during the i 'th iteration of the outer loop terminates with counter value j for $j > 1$, then element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

- ▶ **A:** The inner while loop terminates with value $j > 1$ in the i 'th iteration of the outer loop.
- ▶ **B:** Element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.
- ▶ Want to prove $A \Rightarrow B$.
- ▶ So we will argue that if element $A[i]$ of the original input array is less than $A[j - 1]$, then the inner while loop in the i 'th iteration will not terminate with counter value j for $j > 1$.

Algorithm Insertion Sort

Input: array A of length n

```
1: for  $i \leftarrow 2$  to  $n$  do
2:    $j \leftarrow i$ 
3:   while  $j > 1$  and  $A[j] < A[j - 1]$ 
4:     do
5:       Swap  $A[j]$  and  $A[j - 1]$ 
6:        $j \leftarrow j - 1$ 
7:   end while
8: end for
```

Correctness of (one iteration of) Insertion Sort - Proof by Contrapositive

Claim: If the inner while loop during the i 'th iteration of the outer loop terminates with counter value j for $j > 1$, then element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

Correctness of (one iteration of) Insertion Sort - Proof by Contrapositive

Claim: If the inner while loop during the i 'th iteration of the outer loop terminates with counter value j for $j > 1$, then element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

- ▶ In order for the loop to terminate at counter value $j > 1$, it must hold that $A[j] \geq A[j - 1]$.

Correctness of (one iteration of) Insertion Sort - Proof by Contrapositive

Claim: If the inner while loop during the i 'th iteration of the outer loop terminates with counter value j for $j > 1$, then element $A[i]$ of the original input array is greater than or equal to $A[j - 1]$.

- ▶ In order for the loop to terminate at counter value $j > 1$, it must hold that $A[j] \geq A[j - 1]$.
- ▶ Note that inside the WHILE loop, $A[j] = A[i]$ of the original input array. Therefore, if $A[i] = A[j] < A[j - 1]$, the loop will not terminate with counter value j .

Algorithm Insertion Sort

Input: array A of length n

```
1: for  $i \leftarrow 2$  to  $n$  do
2:    $j \leftarrow i$ 
3:   while  $j > 1$  and  $A[j] < A[j - 1]$ 
     do
4:     Swap  $A[j]$  and  $A[j - 1]$ 
5:      $j \leftarrow j - 1$ 
6:   end while
7: end for
```

Master Theorem from last lecture (time permitting)

Master Theorem

$$T(n) = aT(n/b) + cn^k \qquad T(1) = c$$


a, b, c, k constants with **$a \geq 1$** , **$b > 1$** , **$c > 0$** , and **$k \geq 0$**

Master Theorem

$$T(n) = aT(n/b) + cn^k$$

$$T(1) = c$$

a, b, c, k constants with $a \geq 1$, $b > 1$, $c > 0$, and $k \geq 0$




Master Theorem

$$T(n) = aT(n/b) + cn^k$$

$$T(1) = c$$

a, b, c, k constants with $a \geq 1$, $b > 1$, $c > 0$, and $k \geq 0$




levels: $\log_b n + 1$

Master Theorem

$$T(n) = aT(n/b) + cn^k$$

$$T(1) = c$$

a, b, c, k constants with $a \geq 1$, $b > 1$, $c > 0$, and $k \geq 0$



levels: $\log_b n + 1$

Level i : $a^{i-1}c(n/b^{i-1})^k = cn^k(a/b^k)^{i-1}$

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

- ▶ Case 1: $\alpha = 1$. All levels the same. $T(n) = cn^k \sum_{i=1}^{\log_b n+1} 1 = \Theta(n^k \log n)$

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

- ▶ Case 1: $\alpha = 1$. All levels the same. $T(n) = cn^k \sum_{i=1}^{\log_b n+1} 1 = \Theta(n^k \log n)$
- ▶ Case 2: $\alpha < 1$. Dominated by top level.

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

► Case 1: $\alpha = 1$. All levels the same. $T(n) = cn^k \sum_{i=1}^{\log_b n+1} 1 = \Theta(n^k \log n)$

► Case 2: $\alpha < 1$. Dominated by top level.

$$\implies \sum_{i=1}^{\log_b n+1} \alpha^{i-1} \leq \sum_{i=1}^{\infty} \alpha^{i-1} = \frac{1}{1-\alpha}.$$

$$\implies T(n) = O(n^k)$$

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

► Case 1: $\alpha = 1$. All levels the same. $T(n) = cn^k \sum_{i=1}^{\log_b n+1} 1 = \Theta(n^k \log n)$

► Case 2: $\alpha < 1$. Dominated by top level.

$$\implies \sum_{i=1}^{\log_b n+1} \alpha^{i-1} \leq \sum_{i=1}^{\infty} \alpha^{i-1} = \frac{1}{1-\alpha}.$$

$$\implies T(n) = O(n^k)$$

$$T(n) \geq cn^k \implies T(n) = \Omega(n^k)$$

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

- ▶ Case 1: $\alpha = 1$. All levels the same. $T(n) = cn^k \sum_{i=1}^{\log_b n+1} 1 = \Theta(n^k \log n)$
- ▶ Case 2: $\alpha < 1$. Dominated by top level.

$$\implies \sum_{i=1}^{\log_b n+1} \alpha^{i-1} \leq \sum_{i=1}^{\infty} \alpha^{i-1} = \frac{1}{1-\alpha}.$$

$$\implies T(n) = O(n^k)$$

$$T(n) \geq cn^k \implies T(n) = \Omega(n^k) \implies T(n) = \Theta(n^k)$$

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

► Case 1: $\alpha = 1$. All levels the same. $T(n) = cn^k \sum_{i=1}^{\log_b n+1} 1 = \Theta(n^k \log n)$

► Case 2: $\alpha < 1$. Dominated by top level.

$$\implies \sum_{i=1}^{\log_b n+1} \alpha^{i-1} \leq \sum_{i=1}^{\infty} \alpha^{i-1} = \frac{1}{1-\alpha}.$$

$$\implies T(n) = O(n^k)$$

$$T(n) \geq cn^k \implies T(n) = \Omega(n^k) \implies T(n) = \Theta(n^k)$$

► Case 3: $\alpha > 1$. Dominated by bottom level.

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

► Case 1: $\alpha = 1$. All levels the same. $T(n) = cn^k \sum_{i=1}^{\log_b n+1} 1 = \Theta(n^k \log n)$

► Case 2: $\alpha < 1$. Dominated by top level.

$$\implies \sum_{i=1}^{\log_b n+1} \alpha^{i-1} \leq \sum_{i=1}^{\infty} \alpha^{i-1} = \frac{1}{1-\alpha}.$$

$$\implies T(n) = O(n^k)$$

$$T(n) \geq cn^k \implies T(n) = \Omega(n^k) \implies T(n) = \Theta(n^k)$$

► Case 3: $\alpha > 1$. Dominated by bottom level.

$$\begin{aligned} \implies \sum_{i=1}^{\log_b n+1} \alpha^{i-1} &= \alpha^{\log_b n} \sum_{i=1}^{\log_b n+1} \left(\frac{1}{\alpha}\right)^{i-1} \leq \alpha^{\log_b n} \frac{1}{1-(1/\alpha)} \\ &= O(\alpha^{\log_b n}) \end{aligned}$$

Master Theorem II

Let $\alpha = (a/b^k)$

$$\implies T(n) = cn^k \sum_{i=1}^{\log_b n+1} (a/b^k)^{i-1} = cn^k \sum_{i=1}^{\log_b n+1} \alpha^{i-1}$$

► Case 1: $\alpha = 1$. All levels the same. $T(n) = cn^k \sum_{i=1}^{\log_b n+1} 1 = \Theta(n^k \log n)$

► Case 2: $\alpha < 1$. Dominated by top level.

$$\implies \sum_{i=1}^{\log_b n+1} \alpha^{i-1} \leq \sum_{i=1}^{\infty} \alpha^{i-1} = \frac{1}{1-\alpha}.$$

$$\implies T(n) = O(n^k)$$

$$T(n) \geq cn^k \implies T(n) = \Omega(n^k) \implies T(n) = \Theta(n^k)$$

► Case 3: $\alpha > 1$. Dominated by bottom level.

$$\implies \sum_{i=1}^{\log_b n+1} \alpha^{i-1} = \alpha^{\log_b n} \sum_{i=1}^{\log_b n+1} \left(\frac{1}{\alpha}\right)^{i-1} \leq \alpha^{\log_b n} \frac{1}{1-(1/\alpha)}$$

$$= O(\alpha^{\log_b n})$$

$$\begin{aligned} \implies T(n) &= \Theta(n^k \alpha^{\log_b n}) = \Theta(n^k (a/b^k)^{\log_b n}) = \Theta(a^{\log_b n}) \\ &= \Theta(n^{\log_b a}) \end{aligned}$$

Master Theorem III

Theorem (“Master Theorem”)

The recurrence

$$T(n) = aT(n/b) + cn^k$$

$$T(1) = c$$

where a, b, c , and k are constants with $a \geq 1$, $b > 1$, $c > 0$, and $k \geq 0$, satisfies

$$T(n) = \begin{cases} \Theta(n^k) & \text{if } a < b^k, \\ \Theta(n^k \log n) & \text{if } a = b^k, \\ \Theta(n^{\log_b a}) & \text{if } a > b^k. \end{cases}$$