TORQUE SPECIFICATION

SS081-02

Part tightened		N⋅m	kgf⋅cm	ft-lbf
Brake line union nut		15	155	11
Hydraulic brake booster clevis lock nut		25	260	19
Hydraulic brake booster x Pedal bracket		14	140	10
Bleeder plug		11	110	8
Front disc brake caliper x Steering knuckle		123	1,250	90
Front disc brake caliper x Brake line union nut		15	155	11
Parking brake bellcrank bracket x Backing plate		13	130	9
Rear drum brake wheel cylinder x Backing plate		10	100	7
Reservoir set screw		1.7	18	16 in.·lbf
Union bolt		32	320	23
Oil pressure sensor x Hydraulic brake booster		81	830	60
Accumulator x Booster pump motor		54	550	36
No. 1 hanger set bolt		7.8	80	69 in.·lbf
No. 2 hanger set bolt		7.8	80	69 in.·lbf
Fluid level warning switch connector clamp set bolt		7.8	80	69 in.·lbf
Speed sensor harness x Steering knuckle and upper arm		8.0	82	71 in.·lbf
Speed sensor harness x Side rail		12	122	9
Speed sensor installation bolt	front	8.0	82	71 in.·lbf
	rear	10	100	7

2002 4RUNNER (RM887U)

Author: Date: 167