
## ENGINE INSPECTION

MA004-15

## HINT:

Inspect these items when the engine is cold.

- 1. REPLACE TIMING BELT (See page EM-1 1)
- 2. INSPECT DRIVE BELTS (See page CH-1)
- 3. REPLACE SPARK PLUGS (See page IG-1)



## 4. INSPECT AIR FILTER

(a) Visually check that the air cleaner element is not excessively dirty, damaged or oily.

## HINT:

Oiliness may indicate a stuck PCV valve.

If necessary, replace the air cleaner element.

- (b) Clean the element with compressed air.
  First blow from back side thoroughly, then blow off the front side of the element.
- 5. REPLACE AIR FILTER

Replace the used air cleaner element with a new one.

- 6. REPLACE ENGINE OIL AND OIL FILTER (See page LU-3)
- 7. REPLACE ENGINE COOLANT (See page CO-2)
- 8. REPLACE GASKET IN FUEL TANK CAP (See page EC-6)
- 9. INSPECT FUEL LINES AND CONNECTIONS (See page SF-26)
- 10. INSPECT EXHAUST PIPES AND MOUNTINGS (See page EM-105)
- 11. INSPECT VALVE CLEARANCE (See page EM-4)

2002 4RUNNER (RM887U)

Author: Date: 45