$$\Phi = \{\textsc{Outline},\ \textsc{Draft},\ \textsc{Probe},\ \textsc{Evidence},\ \textsc{Revise},\ \textsc{Compile},\ \textsc{Check}\} \quad \text{the seven phases}$$

$$T = \{\textsc{Close},\ \textsc{Hold}\} \quad \text{the two terminals}$$

$R(\varphi)$ row by row, and the point is that it is **not** uniform:

$$\begin{aligned}
R(\textsc{Outline}) &= \{\textsc{Outline},\ \textsc{Draft},\ \textsc{Hold}\}\\
R(\textsc{Draft}) &= \{\textsc{Draft},\ \textsc{Probe},\ \textsc{Evidence},\ \textsc{Revise},\ \textsc{Check},\ \textsc{Hold}\}\\
R(\textsc{Probe}) &= \{\textsc{Probe},\ \textsc{Evidence},\ \textsc{Revise},\ \textsc{Hold}\}\\
R(\textsc{Evidence}) &= \{\textsc{Evidence},\ \textsc{Revise},\ \textsc{Draft},\ \textsc{Check},\ \textsc{Hold}\}\\
R(\textsc{Revise}) &= \{\textsc{Revise},\ \textsc{Compile},\ \textsc{Evidence},\ \textsc{Draft},\ \textsc{Check},\ \textsc{Hold}\}\\
R(\textsc{Compile}) &= \{\textsc{Compile},\ \textsc{Check},\ \textsc{Revise},\ \textsc{Hold}\}\\
R(\textsc{Check}) &= \{\textsc{Close},\ \textsc{Outline},\ \textsc{Revise},\ \textsc{Probe},\ \textsc{Evidence},\ \textsc{Draft},\ \textsc{Hold}\}
\end{aligned}$$

Three laws follow from the table, and they are why it is worth printing:

$$\begin{aligned}
\textsc{Close} \in R(\varphi) \iff \varphi = \textsc{Check} &\qquad \text{only a judge may close}\\
\textsc{Check} \notin R(\textsc{Check}) &\qquad \text{no version is judged twice untouched}\\
\textsc{Hold} \in R(\varphi) \ \text{ for every } \varphi \in \Phi &\qquad \text{every phase may stop honestly}
\end{aligned}$$