

SM-1000B Semi-auto Component Taping Machine

SAMTRONIK

With pocket detecte function(CCD Check)

Features :

- 1.Track width can work freely in the range of 8mm to 72mm, the screen is easy and convenient for operate and control.
- 2.Fine adjustment head installed in hot-press device, adjustment of sealing position can accurate to $0.1 \pm \text{mm}$, independent PID temperature control accurately and steadily.
- 3.The position of cover tape can make fine adjustment by adjust the tension of the moving cover tape.
- 4.Count by fiber-optical sensitiveand equipped with leakage detection make braiding accurate.
- 5.Moving tape speed can be adjusted continuously and control by pedal, Ccompatible with all ELA-481 standard plastic reels.

Specifications:

Model	SM-1000B
Point	With CCD Check function
Mchine Dimension	1650*460*580mm (L*H*W)
Feeding	suitable with ELA-481 standard wheel and cover tape
Tape width	12mm-72mm (8mm need customized)
Power supply	AC200V50HZ
Pressure	3.0kg/cm2
Temperature control	two heads and independent PID temperature control, temperature range is 20-200°C
Taping speed	3000-7000PCS/hr. According to specific Component
Calculator	count by fiber-optical sensitive
Package type	self adhesive or hot sealing
Weight	50KG