

```
import React, { useState } from "react";
import "./App.css";

function App() {
  const [formData, setFormData] = useState({
    name: "",
    email: "",
    password: "",
  });

  const [errors, setErrors] = useState({});

  const handleChange = (e) => {
    setFormData({
      ...formData,
      [e.target.name]: e.target.value,
    });
  };

  const validate = () => {
    let newErrors = {};

    if (!formData.name.trim()) {
      newErrors.name = "Name is required";
    }

    if (!formData.email.trim()) {
      newErrors.email = "Email is required";
    } else if (
      !/^[A-Z0-9._%+-]+@[A-Z0-9.-]+\.[A-Z]{2,}$/i.test(formData.email)
    ) {

```

```
newErrors.email = "Invalid email address";
}

if (!formData.password.trim()) {
  newErrors.password = "Password is required";
} else if (formData.password.length < 6) {
  newErrors.password = "Password must be at least 6 characters";
}

return newErrors;
};

const handleSubmit = (e) => {
  e.preventDefault();

  const validationErrors = validate();

  if (Object.keys(validationErrors).length === 0) {
    alert("Form Submitted Successfully!");
    console.log(formData);

    setFormData({
      name: "",
      email: "",
      password: "",
    });

    setErrors({});
  } else {
    setErrors(validationErrors);
  }
}
```

```
};
```

```
return (
```

```
<div className="container">
```

```
<div className="form-box">
```

```
<h2>React Form Validation</h2>
```

```
<form onSubmit={handleSubmit}>
```

```
<div className="input-group">
```

```
<label>Name</label>
```

```
<input
```

```
  type="text"
```

```
  name="name"
```

```
  placeholder="Enter your name"
```

```
  value={formData.name}
```

```
  onChange={handleChange}
```

```
{errors.name && <span className="error">{errors.name}</span>}
```

```
</div>
```

```
<div className="input-group">
```

```
<label>Email</label>
```

```
<input
```

```
  type="text"
```

```
  name="email"
```

```
  placeholder="Enter your email"
```

```
  value={formData.email}
```

```
  onChange={handleChange}
```

```
{errors.email && <span className="error">{errors.email}</span>}
```

```
</div>
```

```
<div className="input-group">
  <label>Password</label>
  <input
    type="password"
    name="password"
    placeholder="Enter your password"
    value={formData.password}
    onChange={handleChange}
  />
  {errors.password && (
    <span className="error">{errors.password}</span>
  )}
</div>

<button type="submit">Submit</button>
</form>
</div>
</div>
);
}
```

```
export default App;
```