CloudBees Core Client Master   **admin**   **I log out**

Jenkins ▸ CM-1 ▸ Configure Global Security

🔒 Configure Global Security

☑ Enable security *(Managed by Operations Center security policy)*   ❓

Disable remember me   ☐ *(Managed by Operations Center security policy)*   ❓

Access Control

Security Realm

◯ Delegate to servlet container   ❓

🔘 Jenkins' own user database   ❓

     ☐ Allow users to sign up   ❓

◯ LDAP   ❓

◯ Operations Center Single Sign On

Authorization

◯ Anyone can do anything   ❓

◯ Legacy mode   ❓

🔘 Logged-in users can do anything   ❓

     ☐ Allow anonymous read access   ❓

◯ Role-based matrix authorization strategy   ❓

Markup Formatter

Markup Formatter

Plain text	⬍

(Managed by Operations Center security policy)

Agents

TCP port for JNLP agents   ◯ Fixed : [   ]   ◯ Random   🔘 Disable   ❓

     Agent protocols...

CSRF Protection

☑ Prevent Cross Site Request Forgery exploits *(Managed by Operations Center security policy)*   ❓

CLI

☐ Enable CLI over Remoting   ❓

Plugin Manager

☐ Use browser for metadata download *(Managed by Operations Center security policy)*   ❓

API Token

☐ Generate a legacy API token for each newly created user (Not recommended)   ❓

☐ Allow users to manually create a legacy API token (Not recommended)   ❓

☑ Enable API Token usage statistics   ❓

☑ Enable Agent → Master Access Control *(Managed by Operati*   ❓

Rules can be tweaked <u>here</u>   **Save**   **Apply**

SSH Server

SSHD Port   ◯ Fixed :   ◯ Random ● Disable

☑ Security settings managed by Operations Center

CloudBees Core

Page generated: Feb 9, 2019 8:56:38 PM   CloudBees Core Client Master 2.150.2.3-rolling

SSH Server

SSHD Port   ◯ Fixed :   ◯ Random ● Disable

☑ Security settings managed by Operations Center

Save   Apply