

MCUSDKARTOSRN

MCUXpresso SDK Azure RTOS Release Notes

Rev. 2.13.0 — 30 November 2022

Release notes

1 MCUXpresso SDK Azure RTOS introduction

Azure RTOS is an embedded development suite including a small but powerful operating system that provides reliable, ultra-fast performance for resource-constrained devices. It is easy-to-use and market-proven, deployed on more than 6.2 billion devices worldwide. Azure RTOS supports the most popular 32-bit microcontrollers and embedded development tools. Azure RTOS components include Azure RTOS ThreadX, Azure RTOS ThreadX Modules, Azure RTOS FileX, Azure RTOS GUIX, Azure RTOS NetX Duo, and Azure RTOS USBX. This release includes the above components and corresponding examples. For more information and getting started instructions, see *Getting Started with MCUXpresso SDK for Azure RTOS* (document MCUXSDKAZURERTOSGSUG).

2 Supported development systems

This release supports the boards and examples listed in the following table.

Table 1. Supported boards and examples

Components	Example Name	Boards	Description
ThreadX	i2c_example	evkmimxrt1020, evkmimxrt1040 evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s06, lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	The example shows an application using Azure RTOS ThreadX with the I2C driver.
	spi_b2b_example_master	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064	The example shows how to use the LPSPI driver in the master mode with Azure RTOS.



Table 1. Supported boards and examples...continued

Components	Example Name	Boards	Description
	spi_b2b_example_slave	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064	The example shows how to use the LPSPI driver in the slave mode with Azure RTOS.
	spi_example	evkbimxrt1050, lpcxpresso55s06, lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	The example shows how to use the SPI driver with Azure RTOS.
	threadx_demo	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s06, lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	An example of creating multiple threads.
	uart_example	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s06, lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	The example demonstrates how to use the UART driver in Azure RTOS.
ThreadX Modules	threadx_module_manager	evkmimxrt1060	This example creates a ThreadX Module Manager thread that manages module loading, starting, stopping and unloading.

Table 1. Supported boards and examples...continued

Components	Example Name	Boards	Description
	threadx_module	evkmimxrt1060	This example includes two threads of same priorities, using two message queue to communicate between these two threads and calling the uart interface to print information.
FileX	filex_ram_disk	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s06, lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	This is a small demo of the high-performance FileX FAT file system.
	filex_sdcard	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s28, lpcxpresso55s69	The example shows how to use the SD card middleware with Azure RTOS.
LevelX	filex_levelx_spiflash	lpcxpresso55s06, lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	The example shows how to use FileX and LevelX based on SPI NOR flash.
	filex_levelx_mflash	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170	The example shows how to use FileX and LevelX with the mflash component.

Table 1. Supported boards and examples...continued

Components	Example Name	Boards	Description
GUIX	guix_washing_machine	evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064	A GUI example of a washing machine. Support PXP acceleration.
	guix_washing_machine_hd	evkmimxrt1160, evkmimxrt1170	A high-definition GUI example of a washing machine. Support PXP acceleration.
NetX Duo	azure_iot_embedded_sdk	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s28, lpcxpresso55s69	An example communicating with Azure IoT Hub using Azure IoT SDK.
	azure_iot_embedded_sdk_pnp	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170	An example communicating with Azure IoT Hub using Azure IoT SDK and enabling Azure IoT Plug and Play feature.
	azure_iot_embedded_sdk_adu	evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1170	This example showcases the Azure device update (ADU) feature. It connects to Azure IoT Hub and starts interacting with the service, Device Update for IoT Hubs. When the example is running, it will report the device status, and fetch the device update information. In this example, the device credential is stored in flash securely.

Table 1. Supported boards and examples...continued

Components	Example Name	Boards	Description
	azure_iot_mqtt	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170	An example communicating with Azure IoT Hub using MQTT
	ethernet_over_usb	lpcxpresso55s28, lpcxpresso55s69	An example doing the iperf network test over a HP USB Ethernet adapter.
	netx_duo_iperf	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170	An example doing the iperf network test.
	netx_duo_ping	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170	A network ping example.
	pnp_temperature_controller	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170	An example communicating with Azure IoT Hub using Azure IoT SDK and enabling Azure IoT Plug and Play feature, constantly reporting the device temperature value.
	azure_iot_embedded_sdk_adu_se050	evkmimxrt1060, evkmimxrt1170	This example is similar to azure_iot_embedded_sdk_adu. The difference is using SE050 to store device credential (private key and device certificate) and support device authentication when connecting with Azure IoT hub.

Table 1. Supported boards and examples...continued

Components	Example Name	Boards	Description
USBX	usb_x_device_audio_loopback	lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	This example works as a USB audio device. When connecting it to a PC, it will appear as a USB speaker and a USB microphone device.
	usb_x_device_audio_microphone	evkmimxrt1060, evkmimxrt1040	This example works as a USB Audio Microphone device. It will appear as a USB Audio Microphone when connected to PC.
	usb_x_device_audio_speaker	evkmimxrt1060, evkmimxrt1040	This example works as a USB Audio Speaker device. It will appear as a USB Speaker device when connected to PC.
	usb_x_device_cdc_acm	lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	An example works as a USB CDC ACM device.
	usb_x_device_composite_cdc_acm_cdc_acm	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	This example works as two USB CDC ACM devices.
	usb_x_device_hid_keyboard	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s16, lpcxpresso55s28, lpcxpresso55s69	An example works as a USB HID keyboard device.

Table 1. Supported boards and examples...continued

Components	Example Name	Boards	Description
	usb_device_hid_mouse	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcpresso55s16, lpcpresso55s28, lpcpresso55s69	This example works as a USB HID mouse device.
	usb_device_mass_storage	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcpresso55s28, lpcpresso55s69	USB mass storage device example.
	usb_host_cdc_acm	lpcpresso55s28, lpcpresso55s69	This example works as a USB host. It can communicate with a USB CDC ACM device
	usb_host_hid_keyboard	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcpresso55s28, lpcpresso55s69	An example works as a USB HID keyboard host. When connecting a USB HID keyboard and pressing keys, the serial port will output which key has been pressed.

Table 1. Supported boards and examples...continued

Components	Example Name	Boards	Description
	usbx_host_hid_mouse	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024 evkmimxrt1040 evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s28, lpcxpresso55s69	This example works as a USB HID mouse host. When connecting a USB HID mouse and clicking the mouse buttons, the serial console will output which button has been clicked.
	usbx_host_mass_storage	evkmimxrt1010, evkmimxrt1015, evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170, lpcxpresso55s28, lpcxpresso55s69	USB mass storage host example.
combined examples	combine_usbx_netxduo_filex	evkmimxrt1020, evkmimxrt1024, evkmimxrt1040, evkbimxrt1050, evkmimxrt1060, evkbmimxrt1060, evkmimxrt1064, evkmimxrt1160, evkmimxrt1170	An example combined a ping example and a USB mass storage device example. It uses these components: ThreadX, FileX, USBX, NetX Duo.

3 Known issues

This section lists the know issues.

3.1 NetX Duo iperf example

The NetX Duo iperf example works for Linux but not for Windows 10.

3.2 ThreadX Module example

The ThreadX Module example currently only supports the IAR toolchain.

4 Legal information

4.1 Definitions

Draft — A draft status on a document indicates that the content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included in a draft version of a document and shall have no liability for the consequences of use of such information.

4.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Suitability for use in non-automotive qualified products — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

Translations — A non-English (translated) version of a document, including the legal information in that document, is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Security — Customer understands that all NXP products may be subject to unidentified vulnerabilities or may support established security standards or specifications with known limitations. Customer is responsible for the design and operation of its applications and products throughout their lifecycles to reduce the effect of these vulnerabilities on customer's applications and products. Customer's responsibility also extends to other open and/or proprietary technologies supported by NXP products for use in customer's applications. NXP accepts no liability for any vulnerability. Customer should regularly check security updates from NXP and follow up appropriately. Customer shall select products with security features that best meet rules, regulations, and standards of the intended application and make the ultimate design decisions regarding its products and is solely responsible for compliance with all legal, regulatory, and security related requirements concerning its products, regardless of any information or support that may be provided by NXP.

NXP has a Product Security Incident Response Team (PSIRT) (reachable at PSIRT@nxp.com) that manages the investigation, reporting, and solution release to security vulnerabilities of NXP products.

4.3 Trademarks

Notice: All referenced brands, product names, service names, and trademarks are the property of their respective owners.

NXP — wordmark and logo are trademarks of NXP B.V.

Contents

1 MCUXpresso SDK Azure RTOS

 introduction 1

2 Supported development systems1

3 Known issues8

 3.1 NetX Duo iperf example 8

 3.2 ThreadX Module example 8

4 Legal information9

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.