

# Práctica 7

Alejandro Macías Fonseca

13 de octubre de 2024

**Url del repositorio:** <https://github.com/jmacias1503/practica-7-fundamentos-go>  
**Código fuente:**

```
package main

import (
    "fmt"
    "net/http"
    "os"

    "github.com/gin-gonic/gin"
    "gorm.io/driver/postgres"
    "gorm.io/gorm"
)

type User struct {
    gorm.Model
    Id int
    Name string
    Email string
}

func main() {
    dsn := os.Getenv("DATABASEURL")
    db, err := gorm.Open(postgres.Open(dsn), &gorm.Config{})
    if err != nil {
        panic("Error connecting to DB")
    }
    db.AutoMigrate(&User{})
    router := gin.Default()
    var users []User
    fmt.Println("Running app")
    router.LoadHTMLGlob("templates/*")
    router.GET("/ping", func(c *gin.Context) {
        c.JSON(http.StatusOK, gin.H{
            "message": "pong",
        })
    })
}
```

```

        })
    })
    router.GET("/", func(c *gin.Context) {
        c.HTML(200, "index.html", gin.H{
            "title": "My first Go website with gin",
            "total_users": len(users),
            "users": users,
        })
    })
    router.GET("/api/users", func(c *gin.Context) {
        var users [] User
        db.Find(&users)
        c.JSON(200, users)
    })
    router.POST("/api/users", func(c *gin.Context) {
        var user User
        if c.BindJSON(&user) == nil {
            db.Create(&user)
            c.JSON(201, user)
        } else {
            c.JSON(400, gin.H{
                "error": "Invalid payload",
            })
        }
    })
    router.DELETE("/api/users/:id", func(c *gin.Context) {
        id := c.Param("id")
        var user User
        err := db.First(&user, id).Error
        if err != nil {
            c.JSON(400, gin.H{
                "error": "invalid id",
            })
        }
        db.Delete(&user)
        c.JSON(201, gin.H{"message": "User deleted"})
    })
    router.PUT("/api/users/:id", func(c *gin.Context) {
        id := c.Param("id")
        var user User
        err := db.First(&user, id).Error
        if err != nil {
            c.JSON(404, gin.H{
                "error": "User not found",
            })
        }
    })

```

```

    }
    err = c.BindJSON(&user)
    if err != nil {
        c.JSON(400, gin.H{
            "error": "Invalid payload",
        })
        return
    }
    db.Save(&user)
    c.JSON(201, gin.H{})
})

router.Run(":8000") // listen and serve on 0.0.0.0:8080 (for windows "localhost")
}

```